

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12383146
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Kim; Nan Hee et al.

Diabetic complication monitoring device and diabetic complication management system using same

Abstract

A diabetic complications monitoring apparatus and a diabetic complications monitoring system using the same, includes a support fixture having a liquid crystal color changing sheet that is located on an upper surface of the support fixture and displays a foot heat distribution based on a color, a transparent glass that is located on an upper surface of the liquid crystal color changing sheet and comes into contact with user's feet to support the user's feet, a foot heat distribution measurement unit that includes a camera for imaging the liquid crystal color changing sheet and extracts and outputs a foot heat distribution from an image of the camera, a processor that acquires and outputs whether a disease occurs, or a position and size of occurrence of a disease, based on the foot heat distribution, and a data input/output device that audioizes and visualizes an output result of the processor.

Inventors:	Kim; Nan Hee (Seoul, KR), Kim; Jaeyoung (Seoul, KR), Lee; Da Young (Gwacheon-si, KR), Lee; Ki Sun (Seoul, KR)
Applicant:	KOREA UNIVERSITY RESEARCH AND BUSINESS FOUNDATION (Seoul, KR)
Family ID:	78468126
Assignee:	KOREA UNIVERSITY RESEARCH AND BUSINESS FOUNDATION (Seoul, KR)
Appl. No.:	17/923606
Filed (or PCT Filed):	May 06, 2021
PCT No.:	PCT/KR2021/005639
PCT Pub. No.:	WO2021/225370
PCT Pub. Date:	November 11, 2021

Prior Publication Data

Document Identifier

US 20230181046 A1

Publication Date

Jun. 15, 2023

Foreign Application Priority Data

KR

10-2020-0053761

May. 06, 2020

Publication Classification

Int. Cl.: **A61B5/01** (20060101); **A61B5/00** (20060101); **A61B5/103** (20060101); **G01G19/44** (20060101)

U.S. Cl.:

CPC **A61B5/015** (20130101); **A61B5/0075** (20130101); **A61B5/1036** (20130101); **A61B5/7275** (20130101); **G01G19/44** (20130101); A61B5/7405 (20130101); A61B5/742 (20130101); A61B2562/0247 (20130101)

Field of Classification Search

CPC: A61B (5/015); A61B (5/0075); A61B (5/1036); A61B (5/7275); A61B (5/7405); A61B (5/742); A61B (2562/0247); A61B (5/0077); A61B (5/441); A61B (5/1032); A61B (5/4842); A61B (5/6829); A61B (5/7267); A61B (5/7425); A61B (5/447); A61B (5/746); A61B (5/7465); G01G (19/44); G01G (19/50); G16H (30/40); G16H (50/20); G16H (50/30)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2013/0296708	12/2012	Zuzak et al.	N/A	N/A
2015/0057562	12/2014	Linders et al.	N/A	N/A
2017/0319115	12/2016	Cuccia	N/A	A61B 5/14551
2018/0028079	12/2017	Gurevich et al.	N/A	N/A
2019/0200917	12/2018	Murphy et al.	N/A	N/A
2019/0209076	12/2018	Murphy	N/A	A61B 5/7235
2020/0107732	12/2019	Cuccia et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
6297696	12/2017	JP	N/A
2019-519294	12/2018	JP	N/A
2019-527073	12/2018	JP	N/A
10-2018-0071837	12/2017	KR	N/A
10-1949840	12/2018	KR	N/A

OTHER PUBLICATIONS

PCT/KR2021/005639 english translation Sep. 1, 2021. cited by examiner

International Search Report for PCT/KR2021/005639 mailed Sep. 1, 2021 from Korean Intellectual Property Office. cited by applicant

Primary Examiner: Bockelman; Mark W.

Attorney, Agent or Firm: Revolution IP, PLLC

Background/Summary**TECHNICAL FIELD**

(1) The present invention relates to a diabetic complications monitoring apparatus which may more simply and effectively identify and notify diabetic complications, such as diabetic foot disease, and a diabetic complications management system using the diabetic complications monitoring apparatus.

BACKGROUND

(2) Recently, the number of adult diseases has increased due to the improved living environment, and most of all, the number of patients with adult diseases such as diabetes is gradually increasing.

(3) Chronic disease patients also need to visit a hospital but have to check blood sugar levels regularly and follow up conditions from time to time and take appropriate measures.

(4) When the diabetic foot disease is not treated early, a leg may have to be amputated, and thus, it is important to perform early diagnosis. This is caused by a combination of an atherosclerotic vascular change and a diabetic neuropathy. In other words, when a small wound occurs in the foot, a blood flow is not smooth due to arteriosclerosis, and pain may not be felt due to neuropathy, and thus, the wound worsens to eventually develop into a foot ulcer.

(5) According to the various pathophysiology, the temperature of diabetic foot is low in a place where there is occlusive vascular disorder and is high in a place where there is inflammation due to a small wound. Therefore, this change has to be detected early, and appropriate treatment has to be made, but it is very difficult to be examined for a foot in a diabetes clinic.

(6) A current approach to prevention of the diabetic foot ulcers is patient education, foot skin and toenail care, proper footwear selection, and preventive hygiene.

(7) Therefore, when patients themselves regularly monitor and pre-detect diabetic foot disease, amputation of a leg may be reduced by preventing ulcers and surgical procedures through more active hygiene and therapeutic interventions.

(8) Korean patent application No. 10-2018-0071837 and so on propose a system for measuring the temperature of a user's foot to prevent foot disease of a diabetic patient. However, there is disadvantages in that a thermal imaging system is expensive and a temperature sensor may measure only a narrow area causing not to measure the entire foot. In addition, there is a limitation in that an analysis algorithm using foot heat data of a diabetic patient is not used.

SUMMARY OF INVENTION**Technical Problem**

(9) Therefore, the present invention provides a diabetic complications monitoring apparatus that may more simply and effectively identify and notify diabetic complications such as a diabetic foot disease by measuring and analyzing a foot heat distribution based on images, and a diabetic complications management system including the diabetic complications monitoring apparatus.

(10) In addition, a diabetic complication monitoring apparatus that may predict disease information, such as diabetic complications and blood sugar, by additionally using at least one of a foot pressure distribution, a weight change pattern, a Raman spectrum, and a near-infrared spectrum, and particularly, by using an artificial intelligence network method, and a diabetic complications management system.

Solution to Problem

(11) According to an embodiment of the present invention, in order to solve the technical problem, a diabetic complications monitoring apparatus includes a support fixture having a plate shape, a liquid crystal color changing sheet that is located on an upper surface of the support fixture and displays a foot heat distribution based on a color, a transparent glass that is located on an upper surface of the liquid crystal color changing sheet and comes into contact with user's feet to support the user's feet, a foot heat distribution measurement unit that includes a camera for imaging the liquid crystal color changing sheet and extracts and outputs a foot heat distribution from an image of the camera, a processor that acquires and outputs whether a disease occurs, or a position and size of occurrence of a disease, based on the foot heat distribution, and a data input/output device that audioizes and visualizes an output result of the processor to guide a user or notify a preset external device.

(12) It is characterized in that the diabetic complications monitoring apparatus further includes a foot pressure distribution measurement unit which measures a foot pressure distribution by using a pressure sensor array between the liquid crystal color changing sheet and the support fixture or between the transparent glass and the liquid crystal color changing sheet.

(13) It is characterized in that the diabetic complications monitoring apparatus further includes a light spectrum measurement unit which is attached to a side surface of the transparent glass and measures at least one of a Raman spectrum and a near-infrared spectrum for a user's skin.

(14) It is characterized in that a weight change measurement unit that measures and collects a user's weight by using a weight measurement sensor attached to a lower portion of one of the liquid crystal color changing sheet and the support fixture and acquires and outputs a weight change pattern.

(15) It is characterized in that the processor includes a disease prediction model obtained by previously learning a correlation between the measurement information and disease information and further includes a function of predicting diabetic complications corresponding to at least one of a foot heat distribution, a foot pressure distribution, a weight change pattern, a Raman spectrum, and a near-infrared spectrum through the disease prediction model, the measurement information includes at least one of the foot heat distribution, the foot pressure distribution, the weight change pattern, the Raman spectrum, and the near-infrared spectrum, and the disease information includes at least one of the diabetic complications and blood sugar.

(16) According to another embodiment of the present invention, in order to solve the technical problem, a diabetic complications management system includes a patient monitoring apparatus that measures at least one of a foot heat distribution, a foot pressure distribution, a weight change pattern, a Raman spectrum, and a near-infrared spectrum of each patient and generates and outputs measurement information, a patient information management device that acquires disease information of each patient and maps and stores the measurement information, and disease prediction server that generates a plurality of learning data in which a correlation between measurement information and disease information is defined based on information stored in the patient information management device, trains repetitively a disease prediction model, and acquires the disease information corresponding to new measurement information through the disease prediction model and provides the disease information when the patient monitoring apparatus transmits the new measurement information.

(17) It is characterized in that the patient monitoring apparatus includes a support fixture having a plate shape, a liquid crystal color changing sheet that is located on an upper surface of the support

fixture and displays a foot heat distribution based on a color, a transparent glass that is located on an upper surface of the liquid crystal color changing sheet and comes into contact with user's feet to support the user's feet, a foot heat distribution measurement unit that includes a camera for imaging the liquid crystal color changing sheet and extracts and outputs a foot heat distribution from an image of the camera, a foot pressure distribution measurement unit that measures a foot pressure distribution by using a pressure sensor array between the liquid crystal color changing sheet and the support fixture or between the transparent glass and the liquid crystal color changing sheet, a light spectrum measurement unit that is attached to a side surface of the transparent glass and measures at least one of a Raman spectrum and a near-infrared spectrum for a user's skin, a weight change measurement unit that measures and collects a user's weight by using a weight measurement sensor attached to a lower portion of one of the liquid crystal color changing sheet and the support fixture and acquires and outputs a weight change pattern, and a processor that generates and outputs measurement information including at least one of the foot heat distribution, the foot pressure distribution, the weight change pattern, the Raman spectrum, and the near-infrared spectrum, or receives the disease information to audioize and visualize the disease information and outputs the audioized and visualized disease information.

Advantageous Effects

(18) In the present invention, diabetic complications such as a diabetic foot disease may be identified and notified more simply and effectively by measuring and analyzing a foot heat distribution based on an image obtained by using a liquid crystal color changing sheet and a camera.

(19) In addition, at least one of a foot pressure distribution, a weight change pattern, a Raman spectrum, and a near-infrared spectrum is additionally acquired and used, and particularly, disease information, such as diabetic complications and blood sugar, may be predicted by using an artificial intelligence network method, and thus, more reliable disease diagnosis information may be acquired and provided more quickly and accurately.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIGS. 1 and 2 illustrate a diabetic complications monitoring apparatus according to a first embodiment of the present invention.

(2) FIG. 3 is a diagram illustrating a diabetic complications monitoring apparatus according to a second embodiment of the present invention.

(3) FIG. 4 is a view illustrating a diabetic complications management system using a diabetic complications monitoring apparatus, according to the present invention.

(4) FIG. 5 is a view illustrating an embodiment of a diabetic complications monitoring apparatus according to the present invention.

BEST MODE FOR INVENTION

(5) Hereinafter, the present invention will be described in detail with reference to the accompanying drawings.

(6) However, in describing the present invention, when it is determined that a detailed description of a related well-known function or configuration may unnecessarily obscure the gist of the present invention, the detailed description thereof is omitted. Even in a case in which terms are the same, when the indicated parts are different from each other, the reference numerals do not match each other.

(7) The terms to be described below are set in consideration of functions of the present invention, which may change depending on intentions or customs of medical personnel, such as experimenters or measurers, so definitions thereof should be made based on content throughout the present

specification.

(8) In the present specification, terms such as first and second may be used to describe various components, but the components are not limited by the terms. The terms are used only for the purpose of distinguishing one component from another. For example, the first component may be referred to as the second component, and similarly, the second component may also be referred to as the first component without departing from the scope of the present invention. “and/or” includes a combination of a plurality of related listed items or any one thereof.

(9) The terms used herein are used only to describe specific embodiments and are not intended to limit the present invention. A singular expression includes a plural expression unless stated otherwise.

(10) Unless defined otherwise, all terms, which are used herein and include technical or scientific terms, have the same meaning as commonly understood by those skilled in the art to which the present invention belongs. Terms defined in a commonly used dictionary should be interpreted as having a meaning consistent with the meaning in the context of the related art, and should not be interpreted in an ideal or excessively formal meaning unless explicitly defined in the present application.

(11) Hereinafter, the present invention will be described in detail with reference to the accompanying drawings. In describing the present invention, the same reference numerals are used for the same components in the drawings and redundant descriptions of the same components are omitted to facilitate the overall understanding.

(12) FIGS. 1 and 2 illustrate a diabetic complications monitoring apparatus according to a first embodiment of the present invention, in which (a) of FIG. 1 is a front view, (b) of FIG. 1 is a side view, and (c) of FIG. 1 is an exploded view, and FIG. 2 is a detailed configuration diagram.

(13) Referring to FIGS. 1 and 2, a monitoring apparatus **100** of the present invention includes a support fixture **110** having a plate shape, a liquid crystal color changing sheet **120** that is located on an upper surface of the support fixture **110** and displays a foot heat distribution based on a color, a transparent glass **130** that is located on an upper surface of the liquid crystal color changing sheet **120** and comes into contact with user's feet to support the user's feet, a foot heat distribution measurement unit **140** that includes a camera **141** for imaging the liquid crystal color changing sheet **120** and extracts and outputs a foot heat distribution from an image of the camera **141**, a processor **150** that acquires and outputs whether a disease occurs, or a position and size of occurrence of a disease, based on the foot heat distribution, a data input/output device **160** that audioizes and visualizes an output result of the processor **150** to guide a user or notify a preset external device, and so on.

(14) The liquid crystal color changing sheet **120** is a material having characteristics that a color changes according to the temperature of a contact object and immediately displays a color distribution that matches 1:1 with a foot heat distribution of a user when the user's feet are placed on the liquid crystal color changing sheet **120**.

(15) Accordingly, in the present invention, when a user is on the liquid crystal color changing sheet **120**, the liquid crystal color changing sheet **120** displays a color distribution corresponding to the user's foot heat distribution. In addition, when the user comes down from the liquid crystal color changing sheet **120**, the foot heat distribution is obtained based on an image obtained by imaging the liquid crystal color changing sheet **120** through the camera **141**.

(16) The processor **150** compares the foot heat distribution obtained by the foot heat distribution measurement unit **140** with a preset reference value and analyzes the comparison result, and checks and notifies that diabetic complications occur when a region having an abnormal temperature value is detected. In addition, the processor **150** may identify and notify a position and a size of the diabetic complications based on relative position and size of the region having the abnormal temperature value.

(17) The data input/output device **160** of the present invention may include a small monitor, a small

speaker, a short-range wireless communication module, a control panel, and so on, and audioizes and visualizes output data of the processor **150** through the small monitor and the small speaker to perform a user guide operation, and transmits in real time the output data of the processor **150** to a preset external device through the short-range wireless communication module. The data input/output device **160** acquires various control values manually input by a user through the control panel and transmits the various control values to the processor **150**.

(18) In addition, it is preferable that the camera **141** is implemented integrally with the support fixture **110**, but, when necessary, the communication module may be configured as a communicable and detachable type.

(19) However, when the camera **141** is configured as an integrated support fixture, a protrusion portion **111** may be additionally formed on one side of the support fixture **110**, and the camera **141** may be provided on the protrusion portion **111**. This is to image all of the foot heat distributions displayed on the liquid crystal color changing sheet **120** by allowing an image capturing range of the camera **141** to cover the entire area of the liquid crystal color changing sheet.

(20) FIG. 5 is a view illustrating an embodiment of the diabetic complications monitoring apparatus according to the present invention. As illustrated in FIG. 5, the data input/output device **160** may also be installed on an additional support fixture **112** formed to extend toward an upper portion of the support fixture for the sake of a user when the user checks an output result, and in this case, the protrusion portion **111** may be formed on a lower portion of the additional support fixture **112**.

(21) FIG. 3 is a diagram illustrating a diabetic complications monitoring apparatus according to a second embodiment of the present invention.

(22) Referring to FIG. 3, the monitoring apparatus **100** of the present invention may further include at least one of a foot pressure distribution measurement unit **170**, a light spectrum measurement unit **180**, and a weight change measurement unit **190** in addition to the support fixture **110**, the liquid crystal color changing sheet **120**, the transparent glass **130**, the camera **141**, the processor **150**, and the data input/output device **160**.

(23) The foot pressure distribution measurement unit **170** includes a pressure sensor array between the liquid crystal color changing sheet **120** and the support fixture **110** or between the transparent glass **130** and the liquid crystal color changing sheet **120** to measure a pressure distribution of feet of a user and notifies the user of the measurement result.

(24) The light spectrum measurement unit **180** may include at least one of a Raman spectrum sensor **181** and a near-infrared spectrum sensor **182** attached to a side surface of the transparent glass **130**.

(25) Both the Raman spectrum sensor **181** and the near-infrared spectrum sensor **182** may each be configured with a light source that emits light to a user's skin, and a spectrometer that detects absorbed, scattered, or reflected light of the user's skin to measure light spectrum data, and use the transparent glass **130** as a light transmission path.

(26) In this case, the light source may be configured with a light emitting diode (LED), a laser diode, or so on, and a wavelength and a frequency of the light changes depending on the type of sensor. The spectrometer may be configured with a photo diode, a photo transistor (PTr), a charge-coupled device (CCD), or so on.

(27) The weight change measurement unit **190** includes a weight measurement sensor attached to a lower portion of the liquid crystal color changing sheet **120** or the support fixture **110** to track and monitor a user's weight measured by the weight measurement sensor in a period of time and acquires and outputs a user's weight change pattern.

(28) In this case, the processor **150** of the present invention includes a disease prediction model obtained by previously learning a correlation between measurement information (that is, at least one of a foot heat distribution, a foot pressure distribution, a Raman spectrum, a near-infrared spectrum, and a weight change pattern) and disease information (that is, at least one of diabetic

complications and blood sugar).

(29) In addition, when new measurement information is acquired by a user, diabetic complications corresponding to the newly acquired measurement information through the disease prediction model is predicted, and the prediction result is notified to at least one of the user and an external device.

(30) In this case, the disease prediction model may be built and trained based on a machine learning algorithm, and the machine learning algorithm may include a partial least squares regression, a linear regression, a neural network, a decision tree, a genetic algorithm, genetic programming, k-nearest neighbor, a radial basis function network, a random forest, a support vector machine, deep learning, and so on but is not limited thereto.

(31) As described above, the diabetic complications monitoring apparatus of the present invention acquires and utilizes a foot heat distribution by using a liquid crystal color changing sheet to simply check whether a user has diabetic complications.

(32) In addition, various types of information, such as a foot pressure distribution, a Raman spectrum, a near-infrared spectrum, and a weight change pattern may be additionally used, and thus, occurrence of diabetic complications may be more accurately diagnosed.

(33) FIG. 4 is a view illustrating a diabetic complications management system using a diabetic complications monitoring apparatus, according to the present invention.

(34) Referring to FIG. 4, the diabetic complications management system of the present invention includes a patient information management device **200**, and a disease prediction server **300** in addition to the patient monitoring apparatus **100** described above.

(35) The patient monitoring apparatus **100** measures at least one of a foot heat distribution, a foot pressure distribution, a Raman spectrum, and a near-infrared spectrum of each patient and generates and outputs measurement information.

(36) The patient information management device **200** may be configured with a patient terminal or a medical staff terminal that may be interconnected to the patient monitoring apparatus **100** in a short-range wireless communication manner to acquire disease information of each patient and then map and store the measurement information.

(37) In this case, the disease information may be diabetes-related information, such as diabetic complications information and blood sugar information but is not limited thereto.

(38) The disease prediction server **300** may include a model learning unit, a prediction unit, and so on, and may be interconnected to the patient information management device **200** in a remote wireless communication manner.

(39) The model learning unit generates a plurality of learning data in which a correlation between measurement information and disease information is defined based on information stored and managed by the patient information management device **200**, and then repeatedly trains a disease prediction model through the plurality of learning data.

(40) When the patient monitoring apparatus **100** requests a disease diagnosis while acquiring and transmitting new measurement information, the prediction unit acquires disease information corresponding to the new measurement information through the disease prediction model, and then provides the disease information to the patient monitoring apparatus **100** or a system manager.

(41) The above description is merely illustrative of the technical idea of the present invention, and various modifications and changes may be made without departing from the essential characteristics of the present invention by those skilled in the art to which the present invention belongs. Therefore, the embodiments disclosed in the present invention are not intended to limit the technical idea of the present invention, but to describe, and the scope of the technical idea of the present invention is not limited by the embodiments. The protection scope of the present invention should be interpreted by the following claims, and all technical ideas within the scope equivalent thereto should be construed as being included in the scope of the present invention.

Claims

1. A diabetic complications monitoring apparatus comprising: a support fixture having a plate shape; a liquid crystal color changing sheet that is located on an upper surface of the support fixture and displays a foot heat distribution based on a color; a transparent glass that is located on an upper surface of the liquid crystal color changing sheet and comes into contact with user's feet to support the user's feet; a foot heat distribution measurement unit that includes a camera for imaging the liquid crystal color changing sheet and extracts and outputs a foot heat distribution from an image of the camera; a processor that acquires and outputs whether a disease occurs, or a position and size of occurrence of a disease, based on the foot heat distribution; a data input/output device that audioizes and visualizes an output result of the processor to guide the user or notify a preset external device; and a light spectrum measurement unit disposed to a side surface of the transparent glass and configured to measure at least one of a Raman and a near-infrared spectrum of the user's skin, wherein the light spectrum measurement unit comprises a light source that emits light through the transparent glass as a light transmission path toward the user's skin and a spectrometer that detects light absorbed, scattered, or reflected from the user's skin to obtain spectral data.
2. The diabetic complications monitoring apparatus of claim 1, further comprising a foot pressure distribution measurement unit that measures a foot pressure distribution of the user's feet using a pressure sensor array disposed between the liquid crystal color changing sheet and the support fixture, or between the transparent glass and the liquid crystal color changing sheet.
3. The diabetic complications monitoring apparatus of claim 1, further comprising: a weight change measurement unit that measures the user's weight using a weight measurement sensor attached to a lower portion of one of the liquid crystal color changing sheet and the support fixture and acquires and outputs a weight change pattern of the user.
4. The diabetic complications monitoring apparatus of claim 1, wherein the processor includes a disease prediction model obtained by previously learning a correlation between measurement information and disease information, and is configured to predict diabetic complications corresponding to at least one of a foot heat distribution, a foot pressure distribution, a weight change pattern, a Raman spectrum, and a near-infrared spectrum through the disease prediction model, the measurement information includes at least one of the foot heat distribution, the foot pressure distribution, the weight change pattern, the Raman spectrum, and the near-infrared spectrum, and the disease information includes at least one of the diabetic complications and blood sugar.
5. A diabetic complications monitoring system comprising: a patient monitoring apparatus that measures at least one of a foot heat distribution, a foot pressure distribution, a weight change pattern, a Raman spectrum, and a near-infrared spectrum of each patient and generates and outputs measurement information; a patient information management device that acquires disease information of each patient and maps and stores the measurement information; and a disease prediction server that generates a plurality of learning data in which a correlation between measurement information and disease information is defined based on information stored in the patient information management device, trains repetitively a disease prediction model, and acquires the disease information corresponding to new measurement information through the disease prediction model and provides the disease information when the patient monitoring apparatus transmits the new measurement information, wherein the patient monitoring apparatus includes: a support fixture having a plate shape; a liquid crystal color changing sheet that is located on an upper surface of the support fixture and displays a foot heat distribution based on a color; a transparent glass that is located on an upper surface of the liquid crystal color changing sheet and comes into contact with user's feet to support the user's feet; a foot heat distribution measurement unit that includes for imaging the liquid crystal color changing sheet and extracts and outputs a foot

heat distribution from an image of camera; a foot pressure distribution measurement unit that measure distribution by using a pressure sensor array between the liquid crystal color charging sheet and the support fixture or between the transparent glass and the liquid crystal color changing sheet; a light spectrum vent nit that is attached to a side surface of the transparent glass and measures at least one of a Re man spectrum and a near infrared spectrum for a user's skin; a weight change measurement unit that measures and collects a user's weight by using a weight measurement sensor attached to a lower portion of one of the liquid crystal color changing sheet and the support fixture and acquires and outputs a weight change pattern, and a processor that generates and outputs is measurement information including at least one of the foot heat distribution, the foot pressure distribution, the weight change pattern, the Raman spectrum, and the near-infrared spectrum, receives the disease information to audioize and visualize the disease information and outputs the audioized and visualized disease information, wherein the light spectrum measurement unit is attached to a side surface of the transparent glass and configured to measure at least one of aspect a near-infrared spectrum of the user's skin, wherein the light spectrum measurement unit comprises a light source that emits light through the transparent glass as a light transmission path toward the user's skin and a spectrometer that detects light absorbed, scattered, or reflected from the user's skin to obtain spectral data.
