

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12387069
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Sweeney; Michael F. et al.

Systems and methods for age verification

Abstract

Systems and methods for age verification are disclosed. According to one disclosed embodiment, a system includes: a scanner configured to scan a passive data source on an identification card; and a processor coupled to the scanner, the processor configured to: receive a scanner signal from the scanner; verify an age of a user based on the scanner signal; and transmit verification information to a point of sale device, the point of sale device configured to authorize a sale of age-restricted material based on the verification information. According to another disclosed embodiment, a system includes: a scanner configured to scan a passive data source on an identification card; and a processor coupled to the scanner, the processor configured to: receive a scanner signal from the scanner; verify an age of a user based on the scanner signal; and transmit a verification signal to an age-restricted device.

Inventors: Sweeney; Michael F. (Winston-Salem, NC), Stopyra; Thomas J. (Winston-Salem, NC)

Applicant: Integrated Solutions International, LLC (Winston-Salem, NC)

Family ID: 78512475

Assignee: Integrated Solutions International, LLC (Winston-Salem, NC)

Appl. No.: 18/545695

Filed: December 19, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240311595 A1	Sep. 19, 2024

Related U.S. Application Data

continuation parent-doc US 17225192 20210408 US 11886952 child-doc US 18545695
continuation parent-doc WO PCT/US2019/055337 20191009 PENDING child-doc US 17225192

continuation parent-doc US 15382319 20161216 US 9984266 20180529 child-doc US 16205809
continuation parent-doc US 14487952 20140916 US 9558387 20170131 child-doc US 15382319
continuation-in-part parent-doc US 16205809 20181130 US 10867143 20201215 child-doc US
PCT/US2019/055337
continuation-in-part parent-doc US 15954909 20180417 US 10339351 20190702 child-doc US
PCT/US2019/055337
us-provisional-application US 62815147 20190307
us-provisional-application US 62746675 20181017
us-provisional-application US 61878823 20130917

Publication Classification

Int. Cl.: **G06K7/10** (20060101); **G06K7/14** (20060101); **G06K19/06** (20060101)

U.S. Cl.:

CPC **G06K7/10821** (20130101); **G06K7/1404** (20130101); **G06K7/1408** (20130101);
G06K7/1417 (20130101); **G06K19/06037** (20130101);

Field of Classification Search

CPC: G06K (19/06037); G06K (7/10821); G06K (7/1404); G06K (7/1408); G06K (7/1417);
G06Q (20/206); G06Q (20/401); G06Q (20/4014); G07G (1/0036)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7734779	12/2009	Piccionelli	N/A	N/A
8392975	12/2012	Raghunath	N/A	N/A
8485440	12/2012	Arora et al.	N/A	N/A
8967460	12/2014	Baykal et al.	N/A	N/A
9558387	12/2016	Sweeney et al.	N/A	N/A
9721147	12/2016	Kapczynski	N/A	N/A
9734377	12/2016	Sevier et al.	N/A	N/A
9984266	12/2017	Sweeney et al.	N/A	N/A
10257052	12/2018	Lønborg et al.	N/A	N/A
10339351	12/2018	Sweeney et al.	N/A	N/A
10726226	12/2019	Sweeney et al.	N/A	N/A
10867143	12/2019	Sweeney et al.	N/A	N/A
10867144	12/2019	Sweeney et al.	N/A	N/A
11074603	12/2020	Smith	N/A	G06Q 30/0607
11880438	12/2023	Sweeney et al.	N/A	N/A
11886952	12/2023	Sweeney et al.	N/A	N/A
2003/0037075	12/2002	Hannigan et al.	N/A	N/A
2003/0061172	12/2002	Robinson	N/A	N/A
2003/0132292	12/2002	Gomez et al.	N/A	N/A
2003/0152947	12/2002	Crossman et al.	N/A	N/A

2004/0181749	12/2003	Chellapilla et al.	N/A	N/A
2005/0059339	12/2004	Honda et al.	N/A	N/A
2005/0080649	12/2004	Alvarez et al.	N/A	N/A
2006/0157559	12/2005	Levy et al.	N/A	N/A
2006/0252055	12/2005	Francis et al.	N/A	N/A
2006/0256388	12/2005	Erol et al.	N/A	N/A
2006/0280364	12/2005	Ma et al.	N/A	N/A
2007/0005173	12/2006	Kanitz et al.	N/A	N/A
2007/0047818	12/2006	Hull et al.	N/A	N/A
2007/0138260	12/2006	Keys	235/380	G07F 7/08
2008/0191035	12/2007	Cheon	N/A	N/A
2008/0207296	12/2007	Lutnick et al.	N/A	N/A
2008/0247363	12/2007	Lee et al.	N/A	N/A
2009/0001173	12/2008	Sevier et al.	N/A	N/A
2009/0036405	12/2008	Kennedy	N/A	N/A
2009/0039146	12/2008	Seo	N/A	N/A
2009/0092578	12/2008	Su et al.	N/A	N/A
2009/0108057	12/2008	Mu et al.	N/A	N/A
2009/0307232	12/2008	Hall	N/A	N/A
2010/0251336	12/2009	Allen, Jr.	726/4	G06F 21/32
2012/0166309	12/2011	Hwang et al.	N/A	N/A
2013/0018794	12/2012	Ungerland et al.	N/A	N/A
2013/0112746	12/2012	Krell	235/380	G06Q 20/4014
2014/0039932	12/2013	Walton	N/A	N/A
2014/0136012	12/2013	Tam	N/A	N/A
2014/0136223	12/2013	Phillips	N/A	N/A
2014/0222948	12/2013	Terasawa	N/A	N/A
2014/0246035	12/2013	Minskoff et al.	N/A	N/A
2014/0279526	12/2013	Jackson	N/A	N/A
2014/0279540	12/2013	Jackson	N/A	N/A
2014/0289107	12/2013	Moshal	N/A	N/A
2015/0076225	12/2014	Sweeney et al.	N/A	N/A
2015/0081460	12/2014	Chong et al.	N/A	N/A
2015/0106291	12/2014	Robinson et al.	N/A	N/A
2015/0120529	12/2014	Faaborg	N/A	N/A
2015/0124791	12/2014	Mazandarany et al.	N/A	N/A
2015/0181945	12/2014	Tremblay	N/A	N/A
2015/0245668	12/2014	Memari et al.	N/A	N/A
2016/0021930	12/2015	Minskoff et al.	N/A	N/A
2016/0098581	12/2015	Ascencio et al.	N/A	N/A
2016/0100111	12/2015	Atkinson	N/A	N/A
2016/0143361	12/2015	Juster et al.	N/A	N/A
2016/0342970	12/2015	Horn et al.	N/A	N/A
2016/0380774	12/2015	Lovelock et al.	N/A	N/A
2017/0098108	12/2016	Sweeney et al.	N/A	N/A
2017/0116450	12/2016	Sevier et al.	N/A	N/A
2017/0124587	12/2016	White	N/A	N/A
2017/0295014	12/2016	Baras et al.	N/A	N/A
2018/0018659	12/2017	Bolton	N/A	N/A

2018/0020720	12/2017	Matschek et al.	N/A	N/A
2018/0043114	12/2017	Bowen et al.	N/A	N/A
2018/0068105	12/2017	Shapiro et al.	N/A	N/A
2018/0197263	12/2017	Pearson et al.	N/A	N/A
2018/0263283	12/2017	Popplewell et al.	N/A	N/A
2018/0296777	12/2017	Terry et al.	N/A	N/A
2019/0050921	12/2018	Ryner et al.	N/A	N/A
2019/0095665	12/2018	Sweeney et al.	N/A	N/A
2019/0158938	12/2018	Bowen et al.	N/A	N/A
2019/0167922	12/2018	Cole	N/A	N/A
2019/0258838	12/2018	Sweeney et al.	N/A	N/A
2019/0272359	12/2018	Popplewell et al.	N/A	N/A
2019/0295353	12/2018	Cipriano	N/A	N/A
2020/0000143	12/2019	Anderson et al.	N/A	N/A
2020/0001027	12/2019	Jackson et al.	N/A	N/A
2020/0019920	12/2019	Durkee et al.	N/A	N/A
2020/0140256	12/2019	Setchell et al.	N/A	N/A
2020/0175802	12/2019	Crawford	N/A	G07F 11/007
2021/0174417	12/2020	Kawamoto	N/A	N/A
2021/0209204	12/2020	Flokos	N/A	G06F 21/31
2021/0350374	12/2020	Keen	N/A	N/A
2021/0350446	12/2020	D'Haenens	N/A	G06Q 30/0639
2021/0358285	12/2020	Schorey et al.	N/A	N/A
2021/0390556	12/2020	Bermudez	N/A	G06Q 20/405
2021/0401061	12/2020	Davis et al.	N/A	N/A
2021/0403239	12/2020	Patel et al.	N/A	N/A
2021/0405602	12/2020	Patel et al.	N/A	N/A
2021/0406970	12/2020	Patel	N/A	G06Q 20/322
2022/0071299	12/2021	Patel	N/A	N/A
2022/0256930	12/2021	Thomas et al.	N/A	N/A
2022/0264956	12/2021	Kim et al.	N/A	N/A
2023/0322487	12/2022	Patel	N/A	N/A
2024/0311455	12/2023	Sweeney et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2924503	12/2021	CA	N/A
10334012	12/2004	DE	N/A
1548664	12/2004	EP	N/A
1811472	12/2006	EP	N/A
3047423	12/2015	EP	N/A
2786254	12/2019	ES	N/A
2010031110	12/2009	WO	N/A
2011147433	12/2010	WO	N/A
2015042060	12/2014	WO	N/A
2019162157	12/2018	WO	N/A
2020081316	12/2019	WO	N/A
2020081317	12/2019	WO	N/A
2020176898	12/2019	WO	N/A

OTHER PUBLICATIONS

Advisory Action, dated Jul. 21, 2016, by the USPTO, re U.S. Appl. No. 14/487,952. cited by applicant

Advisory Action, mailed Jun. 2, 2020, by the USPTO, re U.S. Appl. No. 16/205,809. cited by applicant

CA Office Action, mailed Apr. 8, 2022, by the CIPO, re Application No. 3,115,293. cited by applicant

CA Office Action, mailed Mar. 28, 2022, by the CIPO, re Application No. 3,115,275. cited by applicant

EP Exam Report, dated Jan. 19, 2023, by the European Patent Office, in connection with EP Application No. 19797866.2. cited by applicant

EP Exam Report, dated Jan. 19, 2023, by the European Patent Office, in connection with EP Application No. 19797867.9. cited by applicant

Final Office Action, dated Jun. 6, 2023, by the USPTO, re U.S. Appl. No. 17/225,192. cited by applicant

Final Office Action, dated Mar. 13, 2020, by the USPTO, re U.S. Appl. No. 16/205,809. cited by applicant

Final Office Action, dated May 18, 2016, by the USPTO, re U.S. Appl. No. 14/487,952. cited by applicant

Final Office Action, dated Oct. 13, 2015, by the USPTO, re U.S. Appl. No. 14/487,952. cited by applicant

Final Office Action, dated Oct. 18, 2022, by the USPTO, re U.S. Appl. No. 17/225,192. cited by applicant

International Search Report and Written Opinion, dated Dec. 3, 2014, by the ISA/EP, regarding PCT/US2014/055916. cited by applicant

International Search Report, dated Jan. 20, 2020, by the ISA/EP, regarding PCT/US2019/055334. cited by applicant

International Search Report, dated Jan. 20, 2020, by the ISA/EP, regarding PCT/US2019/055337. cited by applicant

Notice of Allowance, dated Dec. 13, 2016, by the USPTO, re U.S. Appl. No. 14/487,952. cited by applicant

Notice of Allowance, dated Feb. 20, 2018, by the USPTO, re U.S. Appl. No. 15/382,319. cited by applicant

Notice of Allowance, dated Mar. 15, 2019, by the USPTO, re U.S. Appl. No. 15/954,909. cited by applicant

Notice of Allowance, dated Mar. 26, 2020, by the USPTO, re U.S. Appl. No. 16/418,285. cited by applicant

Notice of Allowance, dated Sep. 18, 2023, by the USPTO, re U.S. Appl. No. 17/225,192. cited by applicant

Notice of Allowance, dated Sep. 29, 2020, by the USPTO, re U.S. Appl. No. 16/205,809. cited by applicant

Notice of Allowance, dated Sep. 3, 2020, by the USPTO, re U.S. Appl. No. 16/403,785. cited by applicant

Notice of Allowance; mailed Sep. 18, 2023; by the USPTO; re U.S. Appl. No. 17/225,192. cited by applicant

Notice of Allowance; mailed Sep. 20, 2023; by the USPTO; re U.S. Appl. No. 17/467,654. cited by applicant

Office Action, dated Apr. 27, 2023, by the USPTO, regarding U.S. Appl. No. 17/467,654. cited by applicant

Office Action, dated Dec. 13, 2018, by the USPTO, re U.S. Appl. No. 15/954,909. cited by applicant
Office Action, dated Dec. 28, 2016, by the CIPO, re CA App No. 2,924,503. cited by applicant
Office Action, dated Feb. 1, 2023, by the USPTO, re U.S. Appl. No. 17/225,192. cited by applicant
Office Action, dated Jan. 5, 2016, by the USPTO, re U.S. Appl. No. 14/487,952. cited by applicant
Office Action, dated Jul. 13, 2017, by the EPO, re EP App No. 14777999.5. cited by applicant
Office Action, dated Jun. 8, 2022, by the USPTO, re U.S. Appl. No. 17/225,192. cited by applicant
Office Action, dated May 22, 2020, by the USPTO, re U.S. Appl. No. 16/403,785. cited by applicant
Office Action, dated May 29, 2015, by the USPTO, re U.S. Appl. No. 14/487,952. cited by applicant
Office Action, dated Nov. 24, 2017, by the CIPO, re CA App No. 2,924,503. cited by applicant
Office Action, dated Nov. 25, 2019, by the USPTO, re U.S. Appl. No. 16/418,285. cited by applicant
Office Action, dated Oct. 2, 2019, by the USPTO, re U.S. Appl. No. 16/205,809. cited by applicant
Office Action, dated Sep. 12, 2017, by the USPTO, re U.S. Appl. No. 15/382,319. cited by applicant
Written Opinion, dated Jan. 20, 2020, by the ISA/EP, regarding PCT/US2019/055334. cited by applicant
Written Opinion, dated Jan. 20, 2020, by the ISA/EP, regarding PCT/US2019/055337. cited by applicant
Office Action, mailed Nov. 15, 2024, by the USPTO, re U.S. Appl. No. 18/545,320. cited by applicant
Notice of Allowance, dated Apr. 7, 2025, by the USPTO, re U.S. Appl. No. 18/545,320. cited by applicant

Primary Examiner: Le; Thien M

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This Application is a continuation of U.S. application Ser. No. 17/225,192, filed Apr. 8, 2021, entitled “Systems and Methods for Point of Sale Age Verification,” which is a continuation of International Application No. PCT/US2019/055337, filed Oct. 9, 2019, and entitled “Systems and Methods for Point of Sale Age Verification,” which claims priority to Provisional Patent Application No. 62/815,147, filed on Mar. 7, 2019, entitled “Systems and Methods for Point of Sale Age Verification.” International Application No. PCT/US2019/055337 also claims priority to and is a continuation-in-part of application Ser. No. 16/205,809, filed on Nov. 30, 2018, and entitled “Systems and Methods for Age-Restricted Product Registration,” which claims the benefit of Application No. 62/746,675, filed on Oct. 17, 2018, entitled “Systems and Methods for Age-Restricted Product Registration.” International Application No. PCT/US2019/055337 also claims the benefit of, and is a continuation-in-part of, U.S. patent application Ser. No. 15/954,909, filed on Apr. 17, 2018, and entitled “Systems and Methods For Decoding And Using Data On Cards,” which is a continuation of and claims the benefit of U.S. patent application Ser. No. 15/382,319, filed on Dec. 16, 2016, and entitled “Systems and Methods For Decoding And Using Data On Cards,” now U.S. Pat. No. 9,984,266, issued on May 29, 2018, which is a continuation of and claims the benefit of U.S. patent application Ser. No. 14/487,952, filed on Sep. 16, 2014, and entitled “Systems and Methods for Decoding and Using Data on Cards,” now U.S. Pat. No. 9,558,387, issued on Jan. 31, 2017, which

claims priority to U.S. Provisional Application No. 61/878,823, filed on Sep. 17, 2013, and entitled “Systems and Methods for Decoding and Using Data on Cards,” the entirety of all of which is hereby incorporated by reference herein.

BACKGROUND

(1) Age-restricted materials are sold at many points of sale. Many points of sale do not have proper procedures in place for restricting access to users who are too young to consume the age-restricted material. Identification cards, such as government issued identification cards, increasingly include some form of machine-readable data. Often many different entities (e.g., corporations, states, or government organizations) use different encoding for this machine-readable data.

SUMMARY OF EXAMPLE EMBODIMENTS

(2) One illustrative system according to the present disclosure comprises a system for age verification, the system comprising: a scanner configured to scan a passive data source on an identification card; and a processor coupled to the scanner, the processor configured to: receive a scanner signal from the scanner; verify an age of a user based on the scanner signal; and transmit verification information to a point of sale device, the point of sale device configured to authorize a sale of age-restricted material based on the verification information.

(3) According to another embodiment, a method according to the present disclosure comprises: receiving a scanner signal from a scanner configured to scan a passive data source on an identification card; verifying an age of a user based on the scanner signal; and transmitting verification information to a point of sale device, the point of sale device configured to authorize a sale of age-restricted material based on the verification information.

(4) According to yet another embodiment of the present disclosure a non-transitory computer readable medium may comprise program code, which when executed by a processor is configured to cause the processor to: receive a scanner signal from a scanner configured to scan a passive data source on an identification card; verify an age of a user based on the scanner signal; and transmit verification information to a point of sale device, the point of sale device configured to authorize a sale of age-restricted material based on the verification information.

(5) This illustrative embodiment is mentioned not to limit or define the limits of the present subject matter, but to provide an example to aid understanding thereof. Illustrative embodiments are discussed in the Detailed Description, and further description is provided there. Advantages offered by various embodiments may be further understood by examining this specification and/or by practicing one or more embodiments of the claimed subject matter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) A full and enabling disclosure is set forth more particularly in the remainder of the specification. The specification makes reference to the following appended figures.

(2) FIG. 1 shows an illustrative system for point of sale age verification according to one embodiment of the present disclosure;

(3) FIG. 2A shows another illustrative system for point of sale age verification according to one embodiment of the present disclosure;

(4) FIG. 2B shows another illustrative system for point of sale age verification according to one embodiment of the present disclosure;

(5) FIG. 3 shows another illustrative system for point of sale age verification according to one embodiment of the present disclosure;

(6) FIG. 4A shows an illustrative example for a passive data source according to one embodiment of the present disclosure;

(7) FIG. 4B shows another illustrative example for a passive data source according to one

embodiment of the present disclosure;

(8) FIG. 4C shows an illustrative example of an identification card according to one embodiment of the present disclosure;

(9) FIG. 4D shows another illustrative example of an identification card according to one embodiment of the present disclosure;

(10) FIG. 5 shows a flow chart of method steps for implementing a method for point of sale age verification according to one embodiment of the present disclosure; and

(11) FIG. 6 shows a flow chart of method steps for implementing a method for point of sale age verification according to one embodiment of the present disclosure.

(12) FIG. 7 shows an illustrative system for age-restricted product registration according to one embodiment of the present disclosure;

(13) FIG. 8A shows another illustrative system for age-restricted product registration according to one embodiment of the present disclosure;

(14) FIG. 8B shows another illustrative system for age-restricted product registration according to one embodiment of the present disclosure;

(15) FIG. 9 shows another illustrative system for age-restricted product registration according to one embodiment of the present disclosure;

(16) FIG. 10A shows yet another illustrative system for age-restricted product registration according to one embodiment of the present disclosure;

(17) FIG. 10B shows yet another illustrative system for age-restricted product registration according to one embodiment of the present disclosure;

(18) FIG. 10C shows yet another illustrative system for age-restricted product registration according to one embodiment of the present disclosure;

(19) FIG. 10D shows yet another illustrative system for age-restricted product registration according to one embodiment of the present disclosure;

(20) FIG. 11 shows a flow chart of method steps for implementing a method for age-restricted product registration according to one embodiment of the present disclosure; and

(21) FIG. 12 shows a flow chart of method steps for implementing a method for age-restricted product registration according to one embodiment of the present disclosure.

DETAILED DESCRIPTION

(22) Reference will now be made in detail to various and alternative illustrative embodiments and to the accompanying drawings. Each example is provided by way of explanation and not as a limitation. It will be apparent to those skilled in the art that modifications and variations can be made. For instance, features illustrated or described as part of one embodiment may be used in another embodiment to yield a still further embodiment. Thus, it is intended that this disclosure include modifications and variations as come within the scope of the appended claims and their equivalents.

(23) Illustrative Example of a Device for Point of Sale Age Verification

(24) Turning now to FIG. 1, which shows one illustrative embodiment of the present disclosure **100**. As shown in FIG. 1, the system **100** comprises an identification card **102**, and internet enabled device **106**, and a point of sale **118**. The point of sale **118** comprises age-restricted material **116**, such as an electronic cigarette (e-cigarette), which are sometimes referred to as vaping devices. An e-cigarette dispenses a vapor that contains nicotine, and which a user inhales. An e-cigarette is not authorized for use for people under the age of eighteen. In other embodiments, age-restricted material may comprise, e.g., a tobacco product, an electronic cigarette, an alcohol product, a firearm, ammunition, explosives, pornography, gambling, or lottery tickets. Embodiments disclosed herein provide systems and methods for restricting the sale of age-restricted material **116** to unauthorized users (e.g., user's below a designated age such as 18 or 21 years of age).

(25) The illustrative embodiment further comprises an internet enabled device **106** (e.g., a wearable device, smartphone, tablet, portable music device, kiosk, desktop, or laptop). In the embodiment

shown in FIG. 1, the internet enabled device **106** comprises a scanner **108** for reading data from an identification card **102** comprising a passive data source **104**. In some embodiments, the identification card may include, e.g., a State Issued Driver License, State Issued Real ID Compliant Driver License, State issued identification card, Federally issued Passport or Military Identification. In some embodiments, the identification card **102** may comprise an electronic identification card, e.g., an electronic ID stored in an application on a mobile device such as a smartphone. In some embodiments, such an electronic identification may comply with ISO/IEC CD 18013-5. For example, some governments or other entities may issue an electronic identification that the user stores in a mobile wallet application. Thus, in some embodiments, the identification card **102** and the internet enabled device **106** may comprise a single device, e.g., a mobile device comprising an electronic identification card.

(26) In the embodiment shown in FIG. 1, the scanner **108** comprises a digital camera configured to capture images. In the illustrative embodiment, this camera comprises a standard camera found on mobile devices, without any specialized hardware. The illustrative embodiment further comprises a network connection, such as a wired or wireless internet connection. The illustrative embodiment further comprises a network interface **110** (e.g., Bluetooth, Near Field Communication (“NFC”), or RFID) to connect to a similar network interface **114** on the point of sale device **112**.

(27) In the illustrative embodiment, the user accesses an application configured to verify the user's age by capturing an image of the user's identification card **102**. For example, the user captures an image of either the front or back face of a driver's license. For example, the user may load a mobile application that includes a widget to execute an age-verification application. In such an embodiment, this widget may appear as a button, switch, graphical user interface, or other user interface available for use with the mobile application. After the user accesses this functionality, e.g., by interacting with the widget, the internet enabled device **106** may be configured to enter an image capture mode. Alternatively, the user may access a web browser and upload a picture of the identification card **102** via a website accessed through the web browser.

(28) In the image-capture mode, the internet enabled device **106** may access a digital camera coupled to the mobile device and display the output on a display of the internet enabled device **106**. The user may then direct the camera toward the user's identification card **102** (such as a driver's license). Specifically, the user may direct the camera toward passive data source **104**, which may comprise machine-readable data (e.g., a barcode encoded in PDF-417 appearing on the back of the identification card). Examples of PDF-417 are shown in FIGS. 4A and 4B below. When the camera captures an image of the machine-readable data at sufficient resolution to extract the data encoded therein, the application may exit the image capture screen, and return to another screen of the mobile application.

(29) Once the image has been captured, a processor on the internet enabled device **106** may process the image to extract encoded data. In some embodiments, this processing may comprise cropping and compressing the data contained on the image. The internet enabled device **106** may then use a network interface (e.g., a wired or wireless network interface) to transmit the image data to a server.

(30) In some embodiments, the server may comprise algorithms developed to quickly process and determine information associated with the cards. In some embodiments, these algorithms may have been developed utilizing a database of data associated with identification cards. Currently, in the United States, there are more than 1,000 different formats of encoded data associated with identification cards issued by various entities (e.g., corporations, states, government organizations, military, or post office). For example, some states change the encoding used on their drivers licenses every few years. However, those states may leave the older drivers licenses in rotation. Thus, these identification cards may comprise out of date encoding. Further, some states may use multiple different types of encryption. Similarly, multiple states use different encoding and encryption, thus, an algorithm associated with, e.g., Georgia may not be useful for decoding data

associated with another state's identification cards. In some embodiments, the remote database may comprise data associated with a large number of these entities. Algorithms developed based on the data in this database may enable the server to quickly process and parse the data on an identification card. Further, in some other embodiments, data comparison software or string searches may enable the database to be quickly searched to determine information about the received data.

(31) Further, in some embodiments, the server may determine whether the identification card is valid or “fake,” e.g., by comparing extracted data to a database of valid identification cards. Further, the server may track whether the user has recently activated or purchased other age-restricted material or purchased more than a certain amount of age-restricted material (e.g., more than a specified number of e-cigarette devices) in a specified period. In still other embodiments, the server may be configured to compare information associated with the user to a no sell list. If the user is on the no sell list the server may send information to the internet enabled device **106** to prevent the internet enabled device **106** from authorizing purchase of age-restricted material **116**.

(32) Once the data is decoded, the server may use a network connection to transmit the decoded data back to the internet enabled device **106**. This data may include, e.g., the user's date of birth, a first name, a last name, an address, a city, a state, a zip code, an issue date, or an expiration date, and may further include information accessed from a purchase history database, e.g., the last time the user bought age-restricted material **116**, the prior quantities of age-restricted material **116** bought by the user, and/or whether the user has recently activated an age-restricted device. In other embodiments, this information may be a simple authorization code indicating that the user is authorized to complete the transaction. This information is then used to confirm that the user is authorized to purchase age-restricted material **116**. If the user is authorized to purchase the age-restricted material, the Internet enabled device **106** will transmit a verification signal to the point of sale device **112**. The point of sale device **112** is programmed to not authorize sale of the age-restricted material **116** without the authorization signal. In one embodiment transmitting the verification signal may comprise displaying a second passive data source comprising a verification code and configured to be scanned by the point of sale device **112**. In another embodiment transmitting the verification signal may comprise displaying a textual verification code configured to be entered by a user into the point of sale device **112**. In still another embodiment, transmitting the verification signal may comprise transmitting a verification signal to the point of sale device **112** network interfaces **110** and **114**, e.g., via wired or wireless data transmission.

(33) This illustrative embodiment is mentioned not to limit or define the limits of the present subject matter, but to provide an example to aid understanding thereof. Illustrative embodiments are discussed in the Detailed Description, and further description is provided there. Advantages offered by various embodiments may be further understood by examining this specification and/or by practicing one or more embodiments of the claimed subject matter.

(34) Illustrative Systems for Point of Sale Age Verification

(35) FIG. 2A shows an illustrative system **200** for point of sale age verification. Particularly, in this example, system **200** comprises a computing device **201** such as, e.g., a wearable device, smartphone, tablet, portable music device, laptop, desktop, kiosk, or dedicated computer terminal. As shown in FIG. 2A, computing device **201** has one or more processor(s) **202** interfaced with other hardware via bus **206**. A memory **204**, which can comprise any suitable tangible (and non-transitory) computer-readable medium such as RAM, ROM, EEPROM, or the like, embodies program components that configure operation of the computing device. In this example, computing device **201** further includes one or more network interface devices **210**, input/output (I/O) interface components **212**, and additional storage **214**.

(36) Network device **210** can represent one or more of any components that facilitate a network connection. Examples include, but are not limited to, wired interfaces such as Ethernet, USB, IEEE 1394, and/or wireless interfaces such as IEEE 802.11, Bluetooth, Near Field Communication,

RFID, and/or radio interfaces for accessing cellular telephone networks (e.g., transceiver/antenna for accessing a CDMA, GSM, UMTS, or other mobile communications network(s)).

(37) I/O components **212** may be used to facilitate connection to devices such as one or more user interfaces **216** (e.g., keyboards, mice, speakers, microphones, and/or other hardware used to input data or output data) and display **220** (e.g., a display such as a plasma, liquid crystal display (LCD), electronic paper, cathode ray tube (CRT), light emitting diode (LED), or some other type of display known in the art). In some embodiments, user interfaces **216** and display **220** may comprise a single component, e.g., a touch screen display. In some embodiments, I/O components **212** may include speakers configured to play audio signals provided by processor **202**. Storage **214** represents nonvolatile storage such as magnetic, optical, or other storage media.

(38) Scanner **218** comprises a sensor configured to detect a passive data-source, such as data encoded in a multidimensional code. For example, in one embodiment, scanner **218** may comprise an optical sensor such as a digital camera. In such an embodiment, processor **202** may use scanner **218** to take an image of a passive data-source, e.g., a matrix barcode such as a QR code, bar code, or multidimensional bar code encoded in PDF-417. In some embodiments, the digital camera may comprise no specialized hardware capability, for example, in some embodiments, the digital camera may be a standard digital camera found on mobile devices such as smartphones and tablets. Further, in some embodiments, the digital camera may comprise an auto-focus capability that enables the camera to capture an image of the multidimensional code at sufficient resolution to reliably extract the encoded data. In such an embodiment, processor **202** may use software stored in memory **204** (discussed below) to determine data encoded in the multidimensional bar code. In other embodiments, scanner **218** may comprise another component, such as a laser scanner, CCD, reader, video camera reader, or other type of scanner configured to scan a passive data-source such as a multidimensional bar code. In still other embodiments, scanner **218** may comprise a scanner configured to detect data from a magnetic code (e.g., a magnetic strip), an RFID, NFC, a SmartCard, an Integrated Circuit Card (ICC) or some other type of passive data.

(39) Turning to memory **204**, exemplary program components **224** and **226** are depicted to illustrate how a device may be configured to decode data on identification cards. In this example, an image detection module **224** configures processor **202** to monitor the input from scanner **218** to detect an image comprising machine-readable data. For example, module **224** may configure processor **202** to enter an image capture mode in which display **220** shows the output from scanner **218**. Further, in some embodiments, image detection module **224** may be configured to determine the quality of data received from scanner **218**. For example, in one embodiment, this may comprise measuring the resolution and focus of the received image. In some embodiments, image detection module **224** may further comprise software to enable processor **202** to determine that the image is of sufficient quality, and therefore capture the image.

(40) Image-parsing module **226** represents a program component that analyzes image data received from scanner **218**. In one embodiment, image-parsing module **226** may comprise software configured to enable processor **202** to crop and/or compress the captured image for transmission via network **210** to a remote server. In further embodiments, image-parsing module **226** may comprise program components configured to enable processor **202** to perform an image comparison between the captured image and data stored on a local database. In some other embodiments, image-parsing module **226** may comprise algorithms that enable the processor **202** to quickly determine the data encoded in a label, e.g., the name, date of birth, address, driver's license number, height, weight, state, county, race, organ donor status, issue date, expiration date, driver restriction, class of vehicle, passport information, criminal record information, or any other information stored in the encoded data. In some embodiments, some of this information may be withheld, e.g., due to privacy concerns. Thus, in some embodiments, information such as a person's height, weight, race, organ donor status, driver restrictions, or class of vehicle may be withheld.

(41) In other embodiments, program components **224** and **226** may be comprise software

components configured to enable processor **202** to process other types of passive data-sources, e.g., magnetic strips, RFIDs, NFC, SmartCards, or Integrated Circuit Cards (ICC). In still other embodiments, components **224** and **226** may be configured to access and authenticate data associated with electronic identification cards, e.g., cards that comply with ISO/IEC CD 18013-5.

(42) In other embodiments, computing device **201** may comprise additional components, such as motion detectors, accelerometers, or GPS receivers that processor **202** may use to determine other information, such as the movements or orientation of computing device **201**.

(43) Turning now to FIG. 2B, which shows an illustrative system **250** of an age-restricted device **251**, e.g., an e-cigarette device. In some embodiments, the age-restricted material **116** discussed above with regard to FIG. 1, may comprise such an age-restricted device **251**.

(44) As shown in FIG. 2B, the system **250** has one or more processor(s) **252** interfaced with other hardware via bus **256**, age-restricted material **254** (e.g., a nicotine or a cannabinoid such as THC or CBD containing substance, or some controlled medication (e.g., anxiety or depression medication), opioids, or some other controlled substance, which may be configured to be vaporized or otherwise dispensed by age-restricted device **251**), a network interface **260**, and input/output (I/O) interface components **262**.

(45) Network device **260** can represent one or more of any components that facilitate a network connection. Examples include, but are not limited to, wired interfaces such as Ethernet, USB, microUSB, Firewire, IEEE 1394, and/or wireless interfaces such as IEEE 802.11, Bluetooth, Near Field Communication, RFID, and/or radio interfaces for accessing cellular telephone networks (e.g., transceiver/antenna for accessing a CDMA, GSM, UMTS, or other mobile communications network(s)). In some embodiments, network interface **260** is configured to receive an activation signal from computing device **201**, described above with regard to FIG. 2A, transmit this activation signal to processor(s) **252**, which then activate the age-restricted device **251** based on the activation signal.

(46) I/O components **262** may be used to facilitate connection to devices such as one or more user interfaces **266** (e.g., keyboards, mice, speakers, microphones, and/or other hardware used to input data or output data) and display **220** (e.g., a display such as a plasma, liquid crystal display (LCD), electronic paper, cathode ray tube (CRT), light emitting diode (LED), or some other type of display known in the art). In some embodiments, I/O components **262** may include speakers configured to play audio signals provided by processor **262**.

(47) FIG. 3 illustrates another illustrative system for point of sale age verification **300**. As shown in FIG. 3, system **300** comprises a computing device **310**, comprising a processor **311**, memory **312** comprising instructions **313**, and a network interface **314**. In some embodiments, computing device **310**, and its components may operate similarly to the components of computing device **201** described above with regard to FIG. 2A. Thus, in some embodiments, the components of computing device **310** may enable the computing device to scan a passive data-source, process the data, and transmit the processed data via access network **330**.

(48) In some embodiments the access network **330** may be a 3GPP network, a 3GPP2 network, a WiMAX network, 4G LTE, HSPA+, UMTS, a Wi-Fi network (e.g., a network that operates in accordance with an IEEE 802.11 standard), or some other wireless access network. In other embodiments, access network **330** may comprise a wired network such as Ethernet, USB, microUSB, Firewire, IEEE 1394, cable, or telephone networks. In some embodiments, access network **330** may comprise a plurality of different types of wired and/or wireless networks configured to transmit data between computing device **310** and server **320**.

(49) As shown in FIG. 3, the access network **330** is further coupled to a server **320**. Server **320** is configured to receive data sent from computing device **310** via access network **330** using network interface **323**. Network interface **323** may comprise a wired and/or wireless network interface configured to receive data using access network **330**.

(50) Server **320** further comprises a processor **321** coupled to a database **322**. Database **322** may

comprise a database of data associated with identification cards. In some embodiments, the database **322** may comprise data associated with identification cards issued by one or more of corporations, states, and government organizations. Processor **321** may be configured to use data comparison software to compare data received from computing device **310** to data stored in database **322** to determine the type of encoding associated with an image and then quickly decode the data, e.g., by parsing the data to determine the stored information, e.g., the name, date of birth, address, driver's license number, height, weight, state, county, or any other information stored in the encoded data.

(51) In other embodiments, rather than performing a full lookup of database **322**, processor **321** may instead comprise algorithms configured to determine information about a passive data source without having to search database **322**. In some embodiments, these algorithms may have been developed using the data available in database **322**. Further, in some embodiments, these algorithms may enable the processor **321** to quickly determine the jurisdiction that issued a card, e.g., by determining the Issuer Identification Number (“IIN Number”) associated with the card, or the type of encryption used in the card. Once this is determined, processor **321** may access an algorithm associated with that IIN number to quickly determine data associated with the passive data source. In some embodiments, processor **321** may be configured to determine the stored data in 2 seconds or less. Processor **321** may also be configured to determine that a passive data source is associated with a valid identification card, e.g., by confirming that extracted data matches data in a database of valid identification cards.

(52) Further, in some embodiments, processor **321** and database **322** may be configured to adapt to new data types. For example, in some embodiments, the administrators of database **322** may periodically update database **322** with new data associated with new entities (e.g., states, government organizations, or corporations). In other embodiments, processor **321**, may be configured to update database **322** based on new data received from entities as the entities post new information (e.g., as a state releases a new type of identification card).

(53) In other embodiments, processor **321** and database **322** may be configured to analyze received data that is not associated with a known type, and based on patterns of other received data, make a determination about the received data. For example, in one embodiment, processor **321** and database **322** may be configured to compare the encoding to known encoding types and thus determine that the encoded data is associated with North Carolina. The processor **321** and database **322** may be configured to further determine that some component of the encoding or encryption is incorrect, for example, because the person who set up the multidimensional code for the drivers' licenses in a jurisdiction (e.g., a state or county) used the wrong type of encoding. Based on this determination processor **321** may update database **322** with new information about this jurisdiction (e.g., the state or county), to thus enable processor **321** to use database **322** to determine data associated with that jurisdiction in the future. In still other embodiments, computing device **310** and server **320** may comprise additional components, such as additional memory and processing components or network components configured to provide faster or more convenient access via access network **330**.

(54) In some embodiments, the parsed data may be stored on the server **320**. In some embodiments, this information may be used for future processing and authentication. For example, in some embodiments, a user may not be able to purchase more than a certain amount of age-restricted material (e.g., no more than one e-cigarette) within a set time period (e.g., one-day, one-week, one-month) to prevent a user from distributing them. Further, in some embodiments, the server **320** may store the total amount of an age-restricted material purchased by the user. In some embodiments, this information may be used to restrict the user's access to additional amounts of an age-restricted material. For example, one user may not be able to purchase over a certain quantity of the age-restricted material in a set time period. In still other embodiments, the user's age, the total amount of a substance the user has purchased, and the time since the user's last purchase may all be used

together to determine whether the user can purchase more of the age-restricted material. In still other embodiments, the server may be configured to determine whether the user is on a no sell list, and, if so, prevent authorization of a purchase of age-restricted material.

(55) Turning now to FIGS. **4A** and **4B**, FIGS. **4A** and **4B** comprise images **400** and **450** of data encoded on the back of drivers licenses from two different states. As shown in FIGS. **4A** and **4B**, the data is encoded using PDF-417. As discussed above, PDF-417 is a stacked linear barcode format. PDF stands for Portable Data File. The 417 signifies that each pattern in the code consists of 4 bars and spaces, and that each pattern is 17 units long.

(56) In some embodiments, data encoded using PDF-417 may further comprise some type of compression or encryption. These types of encryption and compression are applied irregularly amongst jurisdictions such as Federal and State organizations. The present disclosure comprises a database that takes into account these differences and is usable for all jurisdictions. Further, in some embodiments, additional data may be encoded into the identification card. For example, in Florida some information associated with the driver may be embedded into the driver's license number. Thus, in some embodiments, a database associated with Florida driver's licenses may be useful only if it is designed to store this information.

(57) Turning to FIG. **4C**, FIG. **4C** illustrates an example embodiment of the front face of an identification card **460**. As shown in FIG. **4C**, the identification card is an example similar to many states' driver's licenses and includes a picture as well as written information identifying the holder of the driver's license. FIG. **4D** shows the reverse side **470** of the identification card **460**. As shown in FIG. **4D**, the identification card includes a PDF-417 label (e.g., labels **400** or **450** described above). In some embodiments, this label may comprise all or some part of the data on the front of the identification card. Further, in some embodiments, rather than being on the back of the card, the label may instead be located on the front. For example, some military identification cards (e.g., CAC cards) include a label on the front of the card. Some of these cards further include additional passive data-sources, such as ICC, SmartCards, RFIDs, NFCs, magnetic strips, or QR Codes. In some embodiments, rather than a PDF-417 label, the driver's license may instead comprise one of these other types of passive data-sources. Embodiments of the present disclosure may use similar technology to capture and decode data stored in these additional types of passive data sources. Further, In some embodiments, the identification card may comprise an electronic identification card, e.g., an electronic ID stored in a computer associated with the user, e.g., stored in an application on the user's mobile device. In some embodiments, such an electronic identification may comply with ISO/IEC CD 18013-5.

(58) Illustrative Methods for Point of Sale Age Verification

(59) FIG. **5** is a flowchart showing an illustrative method **500** for point of sale age verification. In some embodiments, the steps in flow chart **500** may be implemented in program code executed by a processor, for example, the processor in a general purpose computer, mobile device, or server. In some embodiments, these steps may be implemented by a group of processors. In some embodiments the steps shown in FIG. **5** may be performed in a different order. Alternatively, in some embodiments, one or more of the steps shown in FIG. **5** may be skipped or additional steps not shown in FIG. **5** may be performed. The steps below are described with reference to components described above with regard to the systems described above with regard to FIGS. **2A**, **2B**, and **3**.

(60) The method **500** is described with regard to image capture of a passive data source (e.g., of an image of a multidimensional bar code). However, the steps below are equally applicable to processing data extracted from other types of passive data sources. For example, these method steps may be applied to capturing data from a magnetic code (e.g., a magnetic strip), an RFID, NFC, a SmartCard, an Integrated Circuit Card (ICC) or some other type of passive data. Further, in some embodiments, the methods described below may be used to extract data appearing as printed text on the front of an identification card. In such an embodiment the processor **202** may be

configured to perform an optical character recognition (OCR) of this text.

(61) The method **500** begins at step **502** when processor **202** receives a scanner signal from scanner **218**. As discussed above, scanner **218** may comprise one of a plurality of devices configured extract data from a passive data source (e.g., a barcode or other information printed on an identification card). In one embodiment, scanner **218** may comprise a camera configured to capture an image of the front or the back of an identification card. In some embodiments, the image may comprise an image of machine-readable data encoded in an identification card (e.g., on the back of the identification card). In some embodiments, the machine-readable data may comprise a multidimensional encoding, such as data encoded using PDF-417. In other embodiments, the image may comprise an image of text printed on the front or the back of the identification card. In still other embodiments the scanner **218** may comprise a scanner configured to scan other types of passive data sources, e.g., a magnetic code (e.g., a magnetic strip), an RFID, NFC, a SmartCard, an Integrated Circuit Card (ICC) or some other type of passive data.

(62) Next processor **202** determines a type of encryption associated with the scanner signal **504**. In some embodiments, determining the type of encryption may comprise determining a type of encoding associated with the scanner signal or determining that the scanner signal is not encoded or encrypted. For example, in some embodiments, determining a type of encryption may comprise determining how data is encoded, e.g., encoded in a matrix barcode such as a QR code, bar code, or multidimensional bar code encoded in PDF-417. Further, in some embodiments, determining a type of encoding may comprise determining a type of scanner, e.g., determining that the scanner signal is received from one or more different types of scanners **218**, e.g., scanners configured to detect information embedded in one or more of an image, a magnetic code (e.g., a magnetic strip), an RFID, NFC, a SmartCard, an Integrated Circuit Card (ICC) or some other type of passive data. In still other embodiments, the type of encryption may be determined by processor **321** on a server connected to computing device **201** via a network connection.

(63) At step **506** the processor **202** extracts known data elements from the scanner signal. For example, the processor may be configured to extract data elements such as e.g., the name, date of birth, address, driver's license number, height, weight, state, county, race, organ donor status, issue date, expiration date, driver restriction, class of vehicle, passport information, criminal record information, or any other information stored based on the scanner signal. The processor **202** may extract this information by comparing the scanner signal to data stored in a local data store. Alternatively, the processor **202** may execute algorithms to extract certain encoded data from the scanner signal. In still other embodiments, known data elements may be determined by processor **321** on a server connected to computing device **201** via a network connection.

(64) Then at step **508** processor **202** transmits data associated with the scanner signal to a server **320**. In some embodiments, processor **202** may compress data prior to transmission, e.g., the processor **202** may perform one or more compression algorithms to reduce network overhead and upload time in transmitting data associated with the scanner signal. Processor **202** may use network **210** to transmit the data. As discussed above, network **210** may comprise any type of wired and/or wireless network available to computing device **201**. In other embodiments, processing the image data may comprise extracting known elements from the image. For example, in some embodiments, the image may comprise non-encrypted PDF-417. In such an embodiment, processor **202** may extract available known data from the image. For example, in some embodiments, the processor **202** may resize the image to 640×480 pixels, transform the image to 24-bit grayscale with a quality of 80%, and convert the image to Base64 string representation.

(65) Processor **321** on server **320** may process the scanner signal to extract data from the scanner signal. Alternatively, in some embodiments, the processing may occur on processor **202** local to computing device **201**. In some embodiments, processing the scanner signal may comprise determining information about the scanner signal, e.g., a type of encoding or encryption type associated with the scanner signal. In some embodiments, processing the data may comprise

comparing the data to a database. In other embodiments, rather than performing a line-by-line comparison to a database, the server may instead use a series of algorithms developed based on previous cards to determine the data. For example, the server may comprise a database **322** of data associated with identification cards. The server may further comprise a series of algorithms configured to determine information about identification cards.

(66) In some embodiments, these algorithms may have been developed using the data stored in database **322**. In some embodiments, these algorithms may enable the server to quickly determine identification data. For example, the server may use algorithms and logic to quickly determine the IIN Number associated with the card. Further, once the IIN number is identified, the server may use low overhead string functions to perform a lookup in a specially formatted string that contains all of the applicable values. In some embodiments, this may comprise using a Supertanker String Lookup technique during the data discovery process. These may comprise low overhead string functions to perform a lookup in a specially formatted string that contains all of the applicable values. For example, enclosing the ID Issue State/Province in dashes “-” and looking for the index of its position in the following string: “-BC-, -MB-, -NF-, -PO-, -SK-, -ON-, -NS-, -NB-, -PE-”. In some embodiments, if the index is greater than zero, then the country of origin is Canada. Another example, putting a dash in front of the IIN and looking for the index of its position in a string like the following would return the corresponding state if valid: “-636033AL, -636059AK, -636026AZ, -636021AR”. In both of the above examples, the resources required to find the position of a string within another are much lower than doing a lookup in a table or other data structure.

(67) Further, in some embodiments, processing the image data comprises determining that there is enough captured data to start the process. In some embodiments, processing may also determine whether the data was extracted from a magnetic stripe (e.g., via swiping a reader rather than a captured image) or a barcode. In some embodiments, processing the data may further comprise replacing any invalid binary characters and standardizing on the Track Sentinels. In some embodiments, processing the data may further comprise checking binary data points to determine if any information is encrypted (e.g., if the data comprises an encrypted driver's license or identification card). In some embodiments, the processing may further comprise replacing any invalid binary characters and determining the type of data (e.g., driver's license, military identification, passport, or some other data type).

(68) Processing the scanner signal enables data associated with the scanner signal to be determined. In some embodiments, determining the data associated with the scanner signal comprise parsing the data to determine the stored information, e.g., the name, date of birth, address, driver's license number, height, weight, state, county, issue date, expiration date, or any other information stored in the encoded data. In some embodiments, this parsing process may comprise identifying and consolidating the field separators and delimiters in the multidimensional code, and identifying the name parts, taking into account the variations based on state/province, and intelligently recognizing which parts of the name are provided.

(69) In some embodiments, the parsed data may be stored on the server **320**. In some embodiments, this information may be used for future processing and authentication. For example, in some embodiments, a user may not be able to purchase more than one device within a set time period (e.g., one-day, one-week, one-month) to prevent a user from purchasing multiple age-restricted devices (e.g., from multiple points of sale) and distributing them (e.g., to underage users). Further, in some embodiments, the server **320** may store the total amount of an age-restricted material purchased by the user. In some embodiments, this information may be used to restrict the user's access to additional amounts of an age-restricted material. For example, one user may not be able to purchase over a certain quantity of the age-restricted material in a set time period. In still other embodiments, the user's age, the total amount of a substance the user has purchased, and the time since the user's last purchase may all be used together to determine whether the user can purchase more of the age-restricted material.

(70) Then at step **508**, server **320** transmits a data signal associated with the data extracted from the scanner signal. In some embodiments, this data signal comprises information associated with the age or identity of the user who scanned the identification card. Further, in some embodiments, this data includes whether the user is authorized to purchase age-restricted material **116**, e.g., the user is over a certain age and had not purchased more than a certain quantity of age-restricted material within a certain time period.

(71) At step **510**, the computing device **201** receives the data signal from the server **320**. Then at step **512**, the computing device **201** transmits a verification signal to a point of sale device **112**. In one embodiment transmitting the verification signal may comprise displaying a second passive data source comprising a verification code and configured to be scanned by the point of sale device **112**. For example, in such an embodiment, the internet enable device **106** may display a machine readable code (e.g., a barcode) configured to be scanned by a scanner on the point of sale device **112**. In some embodiments, such a machine readable code may comprise one or more of: a matrix barcode such as a QR code, bar code, or multidimensional bar code encoded in PDF-417. This machine readable code comprises data indicating that the user associated with the identification card **102** is authorized to purchase age restricted material **116**. In another embodiment transmitting the verification signal may comprise displaying a textual verification code (e.g., an alphanumeric code) configured to be entered by a user into the point of sale device **112**. In still another embodiment, transmitting the verification signal may comprise transmitting a verification signal to the point of sale device **112** network interfaces **110** and **114**, e.g., via wired or wireless data transmission. For example, such a signal may be transmitted via one or more of a Ethernet, USB, microUSB, Firewire, IEEE 1394, and/or wireless interfaces such as IEEE 802.11, Bluetooth, Near Field Communication, RFID, and/or radio interfaces for accessing cellular telephone networks (e.g., transceiver/antenna for accessing a CDMA, GSM, UMTS, or other mobile communications network(s)).

(72) The verification signal is required to allow point of sale device **112** to authorize and complete a sale of the age-restricted material **116** to the user associated with the identification card **102**. Further, in some embodiments, the point of sale device **118** and/or the internet enabled device **106** may transmit data associated with the transaction to a remote database that stores information associated with purchases of age-restricted material **116**. This information may be used in future sales transactions, e.g., to deny sale of an age-restricted device **251** to a user who has recently purchased another age-restricted device, thus preventing a user from purchasing a larger number of age-restricted devices **251** and distributing them.

(73) Turning now to FIG. **6**, which is a flowchart showing an illustrative method **600** for point of sale age verification. In some embodiments, the steps in flow chart **600** may be implemented in program code executed by a processor, for example, the processor in a general purpose computer, mobile device, or server. In some embodiments, these steps may be implemented by a group of processors. In some embodiments the steps shown in FIG. **6** may be performed in a different order. Alternatively, in some embodiments, one or more of the steps may be skipped or additional steps may be performed. The steps below are described with reference to components described above with regard to the systems described above with regard to FIGS. **2A**, **2B**, and **3**.

(74) At step **602** an point of sale device **112** receives an verification signal from internet enabled device **106**. The verification signal was determined based on scanning a passive data source and extracting data from the passive data source as described in the embodiments above.

(75) At step **604** the point of sale device **112** authorizes sales transaction allowing a user associated with identification card **102** to complete the transaction purchasing age-restricted material **116**.

(76) Illustrative Example of a Device for Age-Restricted Product Registration

(77) Turning now to FIG. **7**, which shows one illustrative embodiment of the present disclosure **1100**. As shown in FIG. **7**, the system **1100** comprises an age-restricted device **1112**, such as an electronic cigarette (e-cigarette), which are sometimes referred to as vaping devices. An e-cigarette

dispenses a vapor that contains nicotine, and which a user inhales. An e-cigarette is not authorized for use for people under the age of eighteen. An illustrative embodiment herein provides systems and methods for restricting the use of an e-cigarette by people under the age of eighteen.

(78) The illustrative embodiment further comprises a mobile device **1106** (e.g., a wearable device, smartphone, tablet, portable music device, or laptop). In the embodiment shown in FIG. 7, the mobile device **1106** comprises a scanner **1108** for reading data from an identification card **1102** comprising a passive data source **1104**. In some embodiments, the identification card may include, e.g., a State Issued Driver License, State Issued Real ID Compliant Driver License, State issued identification card, Federally issued Passport or Military Identification. In some embodiments, the identification card **1102** may comprise an electronic identification card, e.g., an electronic ID stored in an application on, e.g., the user's mobile device.

(79) In the embodiment shown in FIG. 7, the scanner **1108** comprises a digital camera configured to capture images. In the illustrative embodiment, this camera comprises a standard camera found on mobile devices, without any specialized hardware. The illustrative embodiment further comprises a network connection, such as a wired or wireless internet connection. The illustrative embodiment further comprises a network interface **1110** (e.g., Bluetooth, Near Field Communication ("NFC"), or RFID) to connect to a similar network interface **1114** on the age-restricted device **1112**.

(80) In the illustrative embodiment the user accesses an application configured to verify the user's age by capturing an image of the user's identification card **1102**. For example, the user captures an image of either the front or back face of a driver's license. For example, the user may load a mobile application that includes a widget to execute an age-verification application. In such an embodiment, this widget may appear as a button, switch, graphical user interface, or other user interface available for use with the mobile application. After the user accesses this functionality, e.g., by interacting with the widget, the mobile device **1106** may be configured to enter an image capture mode.

(81) In the image-capture mode, the mobile device **1106** may access a digital camera coupled to the mobile device and display the output on a display of the mobile device **1106**. The user may then direct the camera toward the user's identification card **1102** (such as a driver's license). Specifically, the user may direct the camera toward passive data source **1104**, which may comprise machine-readable data (e.g., a barcode encoded in PDF-417 appearing on the back of the identification card). Examples of PDF-417 are shown in FIGS. 10A and 10B below. When the camera captures an image of the machine-readable data at sufficient resolution to extract the data encoded therein, the application may exit the image capture screen, and return to another screen of the mobile application.

(82) Once the image has been captured, a processor on the mobile device **1106** may process the image to extract encoded data. In some embodiments, this processing may comprise cropping and compressing the data contained on the image. The mobile device **1106** may then use a network interface (e.g., a wired or wireless network interface) to transmit the image data to a server.

(83) In some embodiments, the server may comprise algorithms developed to quickly process and determine information associated with the cards. In some embodiments, these algorithms may have been developed utilizing a database of data associated with identification cards. Currently, in the United States, there are more than 1,000 different formats of encoded data associated with identification cards issued by various entities (e.g., corporations, states, government organizations, military, or post office). For example, some states change the encoding used on their drivers licenses every few years. However, those states may leave the older drivers licenses in rotation. Thus, these identification cards may comprise out of date encoding. Further, some states may use multiple different types of encryption. Similarly, multiple states use different encoding and encryption, thus, an algorithm associated with, e.g., Georgia may not be useful for decoding data associated with another state's identification cards. In some embodiments, the remote database may

comprise data associated with a large number of these entities. Algorithms developed based on the data in this database may enable the server to quickly process and parse the data on an identification card. Further, in some other embodiments, data comparison software or string searches may enable the database to be quickly searched to determine information about the received data.

(84) Further, in some embodiments, the server may track whether the user has recently activated a different age-restricted device or bought more than a certain number of age-restricted devices. The server may be configured to deny access to a user that has activated another age-restricted device within a certain time period (e.g., one day or one-week), thus ensuring that one user who is of age (e.g., over eighteen or twenty-one) cannot activate multiple age-restricted devices for users that are not of age. In still other embodiments, the server may be configured to compare information associated with the user to a no sell list. If the user is on the no sell list the server may send information to the mobile device **1106** to prevent the mobile device **1106** from activating the age-restricted device **1112**.

(85) Once the data is decoded, the server may use a network connection to transmit the decoded data back to the mobile device **1106**. Once the mobile device receives this data, it will confirm that the user is over an age required to access the age-restricted device. If the user is over the age required to access the age-restricted device, the computing device will transmit an activation signal to the age-restricted device **1112**. Once the age-restricted device receives this activation signal, it will be activated and allow users to access the age-restricted material **1116**. In some embodiments, the age-restricted material **1116** may comprise one or more of e.g., a nicotine or a cannabinoid such as THC or CBD containing substance, or some controlled medication (e.g., anxiety or depression medication), opioids, or some other controlled substance, which may be configured to be vaporized or otherwise dispensed by age-restricted device **1112**.

(86) This illustrative embodiment is mentioned not to limit or define the limits of the present subject matter, but to provide an example to aid understanding thereof. Illustrative embodiments are discussed in the Detailed Description, and further description is provided there. Advantages offered by various embodiments may be further understood by examining this specification and/or by practicing one or more embodiments of the claimed subject matter.

(87) Illustrative Systems for Age-Restricted Product Registration

(88) FIG. **8A** shows an illustrative system **1200** for age-restricted product registration. Particularly, in this example, system **1200** comprises a computing device **1201** such as, e.g., a wearable device, smartphone, tablet, portable music device, laptop, desktop, kiosk, or dedicated computer terminal. As shown in FIG. **8A**, computing device **1201** has one or more processor(s) **1202** interfaced with other hardware via bus **1206**. A memory **1204**, 'which can comprise any suitable tangible (and non-transitory) computer-readable medium such as RAM, ROM, EEPROM, or the like, embodies program components that configure operation of the computing device. In this example, computing device **1201** further includes one or more network interface devices **1210**, input/output (I/O) interface components **1212**, and additional storage **1214**.

(89) Network device **1210** can represent one or more of any components that facilitate a network connection. Examples include, but are not limited to, wired interfaces such as Ethernet, USB, IEEE 1394, and/or wireless interfaces such as IEEE 802.11, Bluetooth, Near Field Communication, RFID, and/or radio interfaces for accessing cellular telephone networks (e.g., transceiver/antenna for accessing a CDMA, GSM, UMTS, or other mobile communications network(s)).

(90) I/O components **1212** may be used to facilitate connection to devices such as one or more user interfaces **1216** (e.g., keyboards, mice, speakers, microphones, and/or other hardware used to input data or output data) and display **1220** (e.g., a display such as a plasma, liquid crystal display (LCD), electronic paper, cathode ray tube (CRT), light emitting diode (LED), or some other type of display known in the art). In some embodiments, user interfaces **1216** and display **1220** may comprise a single component, e.g., a touch screen display. In some embodiments, I/O components

1212 may include speakers configured to play audio signals provided by processor **1202**. Storage **1214** represents nonvolatile storage such as magnetic, optical, or other storage media.

(91) Scanner **1218** comprises a sensor configured to detect a passive data-source, such as data encoded in a multidimensional code. For example, in one embodiment, scanner **1218** may comprise an optical sensor such as a digital camera. In such an embodiment, processor **1202** may use scanner **1218** to take an image of a passive data-source, e.g., a matrix barcode such as a QR code, bar code, or multidimensional bar code encoded in PDF-417. In some embodiments, the digital camera may comprise no specialized hardware capability, for example, in some embodiments, the digital camera may be a standard digital camera found on mobile devices such as smartphones and tablets. Further, in some embodiments, the digital camera may comprise an auto-focus capability that enables the camera to capture an image of the multidimensional code at sufficient resolution to reliably extract the encoded data. In such an embodiment, processor **1202** may use software stored in memory **1204** (discussed below) to determine data encoded in the multidimensional bar code. In other embodiments, scanner **1218** may comprise another component, such as a laser scanner, CCD, reader, video camera reader, or other type of scanner configured to scan a passive data-source such as a multidimensional bar code. In still other embodiments, scanner **1218** may comprise a scanner configured to detect data from a magnetic code (e.g., a magnetic strip), an RFID, NFC, a SmartCard, an Integrated Circuit Card (ICC) or some other type of passive data.

(92) Turning to memory **1204**, exemplary program components **1224** and **1226** are depicted to illustrate how a device may be configured to decode data on identification cards. In this example, an image detection module **1224** configures processor **1202** to monitor the input from scanner **1218** to detect an image comprising machine-readable data. For example, module **1224** may configure processor **1202** to enter an image capture mode in which display **1220** shows the output from scanner **1218**. Further, in some embodiments, image detection module **1224** may be configured to determine the quality of data received from scanner **1218**. For example, in one embodiment, this may comprise measuring the resolution and focus of the received image. In some embodiments, image detection module **1224** may further comprise software to enable processor **1202** to determine that the image is of sufficient quality, and therefore capture the image.

(93) Image-parsing module **1226** represents a program component that analyzes image data received from scanner **1218**. In one embodiment, image-parsing module **1226** may comprise software configured to enable processor **1202** to crop and/or compress the captured image for transmission via network **1210** to a remote server. In further embodiments, image-parsing module **1226** may comprise program components configured to enable processor **1202** to perform an image comparison between the captured image and data stored on a local database. In some other embodiments, image-parsing module **1226** may comprise algorithms that enable the processor **1202** to quickly determine the data encoded in a label, e.g., the name, date of birth, address, driver's license number, height, weight, state, county, race, organ donor status, issue date, expiration date, driver restriction, class of vehicle, passport information, criminal record information, or any other information stored in the encoded data. In some embodiments, some of this information may be withheld, e.g., due to privacy concerns. Thus, in some embodiments, information such as a person's height, weight, race, organ donor status, driver restrictions, or class of vehicle may be withheld.

(94) In other embodiments, program components **1224** and **1226** may be comprise software components configured to enable processor **1202** to process other types of passive data-sources, e.g., magnetic strips, RFIDs, NFC, SmartCards, or Integrated Circuit Cards (ICC).

(95) In other embodiments, computing device **1201** may comprise additional components, such as motion detectors, accelerometers, or GPS receivers that processor **1202** may use to determine other information, such as the movements or orientation of computing device **1201**.

(96) Turning now to FIG. 8B, which shows an illustrative system **1250** for age-restricted product registration. Particularly, in this example, system **1250** comprises an age-restricted device **1251**, e.g., an e-cigarette device. As shown in FIG. 8B, the system **1250** has one or more processor(s)

1252 interfaced with other hardware via bus **1256**, age-restricted material **1254** (e.g., a nicotine or a cannabinoid such as THC or CBD containing substance, or some controlled medication (e.g., anxiety or depression medication), opioids, or some other controlled substance, which may be configured to be vaporized or otherwise dispensed by age-restricted device **1251**), a network interface **1260**, and input/output (I/O) interface components **1262**.

(97) Network device **1260** can represent one or more of any components that facilitate a network connection. Examples include, but are not limited to, wired interfaces such as Ethernet, USB, microUSB, Firewire, IEEE 1394, and/or wireless interfaces such as IEEE 802.11, Bluetooth, Near Field Communication, RFII), and/or radio interfaces for accessing cellular telephone networks (e.g., transceiver/antenna for accessing a CDMA, GSM, UMTS, or other mobile communications network(s)). In some embodiments, network interface **1260** is configured to receive an activation signal from computing device **1201**, described above with regard to FIG. **8A**, transmit this activation signal to processor(s) **1252**, which then activate the age-restricted device **1251** based on the activation signal.

(98) I/O components **1262** may be used to facilitate connection to devices such as one or more user interfaces **1266** (e.g., keyboards, mice, speakers, microphones, and/or other hardware used to input data or output data) and display **1220** (e.g., a display such as a plasma, liquid crystal display (LCD), electronic paper, cathode ray tube (CRT), light emitting diode (LED), or some other type of display known in the art). In some embodiments, I/O components **1262** may include speakers configured to play audio signals provided by processor **1262**.

(99) FIG. **9** illustrates another illustrative system for age-restricted product registration **1300**. As shown in FIG. **9**, system **1300** comprises a computing device **1310**, comprising a processor **1311**, memory **1312** comprising instructions **1313**, and a network interface **1314**. In some embodiments, computing device **1310**, and its components may operate similarly to the components of computing device **1201** described above with regard to FIG. **8A**. Thus, in some embodiments, the components of computing device **1310** may enable the computing device to scan a passive data-source, process the data, and transmit the processed data via access network **1330**.

(100) In some embodiments the access network **1330** may be a 3GPP network, a 3GPP2 network, a WiMAX network, 4G LTE, HSPA+, UMTS, a Wi-Fi network (e.g., a network that operates in accordance with an IEEE 802.11 standard), or some other wireless access network. In other embodiments, access network **1330** may comprise a wired network such as Ethernet, USB, microUSB, Firewire, IEEE 1394, cable, or telephone networks. In some embodiments, access network **1330** may comprise a plurality of different types of wired and/or wireless networks configured to transmit data between computing device **1310** and server **1320**.

(101) As shown in FIG. **9**, the access network **1330** is further coupled to a server **1320**. Server **1320** is configured to receive data sent from computing device **1310** via access network **1330** using network interface **1323**. Network interface **1323** may comprise a wired and/or wireless network interface configured to receive data using access network **1330**.

(102) Server **1320** further comprises a processor **1321** coupled to a database **1322**. Database **1322** may comprise a database of data associated with identification cards. In some embodiments, the database **1322** may comprise data associated with identification cards issued by one or more of corporations, states, and government organizations. Processor **1321** may be configured to use data comparison software to compare data received from computing device **1310** to data stored in database **1322** to determine the type of encoding associated with an image and then quickly decode the data, e.g., by parsing the data to determine the stored information, e.g., the name, date of birth, address, driver's license number, height, weight, state, county, or any other information stored in the encoded data.

(103) In other embodiments, rather than performing a full lookup of database **1322**, processor **1321** may instead comprise algorithms configured to determine information about a passive data source without having to search database **1322**. In some embodiments, these algorithms may have been

developed using the data available in database **1322**. Further, in some embodiments, these algorithms may enable the processor **1321** to quickly determine the jurisdiction that issued a card, e.g., by determining the Issuer Identification Number (“IIN Number”) associated with the card, or the type of encryption used in the card. Once this is determined, processor **1321** may access an algorithm associated with that HN number to quickly determine data associated with the passive data source. In some embodiments, processor **1321** may be configured to determine the stored data in 2 seconds or less.

(104) Further, in some embodiments, processor **1321** and database **1322** may be configured to adapt to new data types. For example, in some embodiments, the administrators of database **1322** may periodically update database **1322** with new data associated with new entities (e.g., states, government organizations, or corporations). In other embodiments, processor **1321**, may be configured to update database **1322** based on new data received from entities as the entities post new information (e.g., as a state releases a new type of identification card).

(105) In other embodiments, processor **1321** and database **1322** may be configured to analyze received data that is not associated with a known type, and based on patterns of other received data, make a determination about the received data. For example, in one embodiment, processor **1321** and database **1322** may be configured to compare the encoding to known encoding types and thus determine that the encoded data is associated with North Carolina. The processor **1321** and database **1322** may be configured to further determine that some component of the encoding or encryption is incorrect, for example, because the person who set up the multidimensional code for the drivers' licenses in a jurisdiction (e.g., a state or county) used the wrong type of encoding. Based on this determination processor **1321** may update database **1322** with new information about this jurisdiction (e.g., the state or county), to thus enable processor **1321** to use database **1322** to determine data associated with that jurisdiction in the future. In still other embodiments, computing device **1310** and server **1320** may comprise additional components, such as additional memory and processing components or network components configured to provide faster or more convenient access via access network **1300**.

(106) In some embodiments, the parsed data may be stored on the server **1320**. In some embodiments, this information may be used for future processing and authentication. For example, in some embodiments, a user may not be able to authenticate more than one device within a set time period (e.g., one-day, one-week, one-month) to prevent a user from authenticating multiple age-restricted devices and distributing them. Further, in some embodiments, the server **1320** may store the total amount of an age-restricted substance purchased by the user in some embodiments, this information may be used to restrict the user's access to additional amounts of an age restricted substance. For example, one user may not be able to purchase over a certain quantity of the age-restricted substance in a set time period. In still other embodiments, the user's age, the total amount of a substance the user has purchased, and the time since the user's last purchased may all be used together to determine whether the user can purchase more of the age-restricted substance. In still other embodiments, the server may be configured to determine whether the user is on a no sell list, and, if so, prevent the user from being able to activate the age-restricted device.

(107) Further, in some embodiments, the user may be able to deactivate an age-restricted device, e.g., if the user loses the age-restricted device. In such an embodiment, users may verify their identity by scanning an ID card as described above and sending data to the server **1320** indicating that an age-restricted device should be deactivated. In such an embodiment, the server **1320** may send a signal to the age-restricted device or to a computing device associated with the age-restricted device to deactivate the age-restricted device so it cannot be operated.

(108) Turning now to FIGS. **10A** and **10B**, FIGS. **10A** and **10B** comprise images **1400** and **1450** of data encoded on the back of drivers licenses from two different states. As shown in FIGS. **10A** and **10B**, the data is encoded using PDF-417. As discussed above, PDF-417 is a stacked linear barcode format. PDF stands for Portable Data File. The 417 signifies that each pattern in the code consists

of 4 bars and spaces, and that each pattern is 17 units long.

(109) In some embodiments, data encoded using PDF-417 may further comprise some type of compression or encryption. These types of encryption and compression are applied irregularly amongst jurisdictions such as Federal and State organizations. The present disclosure comprises a database that takes into account these differences and is usable for all jurisdictions (e.g., using a prior technology a Georgia government body may be able to scan identification cards issued by Georgia but cannot effectively scan cards issued by other states). Further, in some embodiments, additional data may be encoded into the identification card. For example, in Florida some information associated with the driver may be embedded into the driver's license number. Thus, in some embodiments, a database associated with Florida driver's licenses may be useful only if it is designed to store this information.

(110) Turning to FIG. 10C, FIG. 10C illustrates an example embodiment of the front face of an identification card **1460**. As shown in FIG. 10C, the identification card is an example similar to many states' driver's licenses and includes a picture as well as written information identifying the holder of the driver's license. FIG. 10D shows the reverse side **1470** of the identification card **1460**. As shown in FIG. 10D, the identification card includes a PDF-417 label (e.g., labels **1400** or **1450** described above). In some embodiments, this label may comprise all or some part of the data on the front of the identification card. Further, in some embodiments, rather than being on the back of the card, the label may instead be located on the front. For example, some military identification cards (e.g., CAC cards) include a label on the front of the card. Some of these cards further include additional passive data-sources, such as ICC, SmartCards, RFIDs, NFCs, magnetic strips, or QR Codes. In some embodiments, rather than a PDF-417 label, the driver's license may instead comprise one of these other types of passive data-sources. Embodiments of the present disclosure may use similar technology to capture and decode data stored in these additional types of passive data sources. Further, in some embodiments, the identification card may comprise an electronic identification card, e.g., an electronic ID stored in a computer associated with the user, e.g., stored in an application on the user's mobile device.

(111) Illustrative Method for Age-Restricted Product Registration

(112) FIG. 11 is a flowchart showing an illustrative method **1500** for age-restricted product registration. In some embodiments, the steps in flow chart **1500** may be implemented in program code executed by a processor, for example, the processor in a general purpose computer, mobile device, or server in some embodiments, these steps may be implemented by a group of processors. In some embodiments the steps shown in FIG. 11 may be performed in a different order.

Alternatively, in some embodiments, one or more of the steps shown in FIG. 11 may be skipped or additional steps not shown in FIG. 11 may be performed. The steps below are described with reference to components described above with regard to the systems described above with regard to FIGS. 8A, 8B, and 9.

(113) The method **1500** is described with regard to image capture of a passive data source (e.g., of an image of a multidimensional bar code) However, the steps below are equally applicable to processing data extracted from other types of passive data sources. For example, these method steps may be applied to capturing data from a magnetic code (e.g., a magnetic strip), an RFID, NFC, a SmartCard, an Integrated Circuit Card (ICC) or some other type of passive data. Further, in some embodiments, the methods described below may be used to extract data appearing as printed text on the front of an identification card. In such an embodiment the processor **1202** may be configured to perform an optical character recognition (OCR) of this text.

(114) The method **1500** begins at step **1502** when processor **1202** receives a scanner signal from scanner **1218**. As discussed above, scanner **1218** may comprise one of a plurality of devices configured extract data from a passive data source (e.g., a barcode or other information printed on an identification card). In one embodiment, scanner **1218** may comprise a camera configured to capture an image of the front or the back of an identification card. In some embodiments, the image

may comprise an image of machine-readable data encoded in an identification card (e.g., on the back of the identification card). In some embodiments, the machine-readable data may comprise a multidimensional encoding, such as data encoded using PDF-417. In other embodiments, the image may comprise an image of text printed on the front or the back of the identification card. In still other embodiments the scanner **1218** may comprise a scanner configured to scan other types of passive data sources, e.g., a magnetic code (e.g., a magnetic strip), an RFID, NFC, a SmartCard, an Integrated Circuit Card (ICC) or some other type of passive data.

(115) Next processor **1202** determines a type of encryption associated with the scanner signal **1504**. In some embodiments, determining the type of encryption may comprise determining a type of encoding associated with the scanner signal or determining that the scanner signal is not encoded or encrypted. For example, in some embodiments, determining a type of encryption may comprise determining how data is encoded, e.g., encoded in a matrix barcode such as a QR code, bar code, or multidimensional bar code encoded in PDF-417. Further, in some embodiments, determining a type of encoding may comprise determining a type of scanner, e.g., determining that the scanner signal is received from one or more different types of scanners **1218**, e.g., scanners configured to detect information embedded in one or more of an image, a magnetic code (e.g., a magnetic strip), an RFID, NFC, a SmartCard, an Integrated Circuit Card (ICC) or some other type of passive data. In still other embodiments, the type of encryption may be determined by processor **1321** on a server connected to computing device **1201** via a network connection.

(116) At step **1506** the processor **1202** extracts known data elements from the scanner signal. For example, the processor may be configured to extract data elements such as e.g., the name, date of birth, address, driver's license number, height, weight, state, county, race, organ donor status, issue date, expiration date, driver restriction, class of vehicle, passport information, criminal record information, or any other information stored based on the scanner signal. The processor **1202** may extract this information by comparing the scanner signal to data stored in a local data store. Alternatively, the processor **1202** may execute algorithms to extract certain encoded data from the scanner signal. In still other embodiments, known data elements may be determined by processor **1321** on a server connected to computing device **1201** via a network connection.

(117) Then at step **1508** processor **1202** transmits data associated with the scanner signal to a server **1320**. In some embodiments, processor **1202** may compress data prior to transmission, e.g., the processor **1202** may perform one or more compression algorithms to reduce network overhead and upload time in transmitting data associated with the scanner signal. Processor **1202** may use network **1210** to transmit the data. As discussed above, network **1210** may comprise any type of wired and/or wireless network available to computing device **1201**. In other embodiments, processing the image data may comprise extracting known elements from the image. For example, in some embodiments, the image may comprise non-encrypted PDF-417. In such an embodiment, processor **1202** may extract available known data from the image. For example, in some embodiments, the processor **1202** may resize the image to 640×480 pixels, transform the image to 24-bit grayscale with a quality of 80%, and convert the image to Base64 string representation.

(118) Processor **1321** on server **1320** may process the scanner signal to extract data from the scanner signal. Alternatively, in some embodiments, the processing may occur on processor **1202** local to computing device **1201**. In some embodiments, processing the scanner signal may comprise determining information about the scanner signal, e.g., a type of encoding or encryption type associated with the scanner signal. In some embodiments, processing the data may comprise comparing the data to a database. In other embodiments, rather than performing a line-by-line comparison to a database, the server may instead use a series of algorithms developed based on previous cards to determine the data. For example, the server may comprise a database **1322** of data associated with identification cards. The server may further comprise a series of algorithms configured to determine information about identification cards.

(119) In some embodiments, these algorithms may have been developed using the data stored in

database **1322**. In some embodiments, these algorithms may enable the server to quickly determine identification data. For example, the server may use algorithms and logic to quickly determine the IIN Number associated with the card. Further, once the IIN number is identified, the server may use low overhead string functions to perform a lookup in a specially formatted string that contains all of the applicable values. In some embodiments, this may comprise using a Supertanker String Lookup technique during the data discovery process. These may comprise low overhead string functions to perform a lookup in a specially formatted string that contains all of the applicable values. For example, enclosing the ID Issue State/Province in dashes“-” and looking for the index of its position in the following string: “-BC-, -MB-, -NF-, -PO-, -SK-, -ON-’-NS-, -NB-, -PE-”. In some embodiments, if the index is greater than zero, then the country of origin is Canada. Another example, putting a dash in front of the IIN and looking for the index of its position in a string like the following would return the corresponding state if valid: “-636033AL, -636059AK, -636026AZ, -636021AR”. In both of the above examples, the resources required to find the position of a string within another are much lower than doing a lookup in a table or other data structure.

(120) Further, in some embodiments, processing the image data comprises determining that there is enough captured data to start the process. In some embodiments, processing may also determine whether the data was extracted from a magnetic stripe (e.g., via swiping a reader rather than a captured image) or a barcode. In some embodiments, processing the data may further comprise replacing any invalid binary characters and standardizing on the Track Sentinels. In some embodiments, processing the data may further comprise checking binary data points to determine if any information is encrypted (e.g., if the data comprises an encrypted driver's license or identification card). In some embodiments, the processing may further comprise replacing any invalid binary characters and determining the type of data (e.g., driver's license, military identification, passport, or some other data type).

(121) Processing the scanner signal enables data associated with the scanner signal to be determined. In some embodiments, determining the data associated with the scanner signal comprise parsing the data to determine the stored information, e.g., the name, date of birth, address, driver's license number, height, weight, state, county, issue date, expiration date, or any other information stored in the encoded data. In some embodiments, this parsing process may comprise identifying and consolidating the field separators and delimiters in the multidimensional code, and identifying the name parts, taking into account the variations based on state/province, and intelligently recognizing which parts of the name are provided.

(122) In some embodiments, the parsed data may be stored on the server **1320**. In some embodiments, this information may be used for future processing and authentication. For example, in some embodiments, a user may not be able to authenticate more than one device within a set time period (e.g., one-day, one-week, one-month) to prevent a user from authenticating multiple age-restricted devices and distributing them. Further, in some embodiments, the server **1320** may store the total amount of an age-restricted substance purchased by the user. In some embodiments, this information may be used to restrict the user's access to additional amounts of an age restricted substance. For example, one user may not be able to purchase over a certain quantity of the age-restricted substance in a set time period. In still other embodiments, the user's age, the total amount of a substance the user has purchased, and the time since the user's last purchased may all be used together to determine whether the user can purchase more of the age-restricted substance.

(123) Then at step **1508**, server **1320** transmits a data signal associated with the data extracted from the scanner signal. In some embodiments, this data signal comprises information associated with the age or identity of the user who scanned the identification card. Further, in some embodiments, this data includes whether the user is authorized to activate an age-restricted device **1251**, e.g., the user is over a certain age and had not activated an age-restricted device within a certain time period.

(124) At step **1510**, the computing device **1201** receives the data signal from the server **1320**. Then

at step **1512**, the computing device **1201** transmits an activation signal to the age-restricted device **1251**. The activation signal may be transmitted via either a wired or wireless network connection, e.g., via one or more of a Ethernet, USB, microUSB, Firewire, IEEE 1394, and/or wireless interfaces such as IEEE 802.11, Bluetooth, Near Field Communication, RFID, and/or radio interfaces for accessing cellular telephone networks (e.g., transceiver/antenna for accessing a CDMA, GSM, UMTS, or other mobile communications network(s)). The activation signal causes a processor **1252** on the age-restricted device to activate the device and enable a user to access age-restricted material **1254** on the device. For example, if the age-restricted device **1251** is an e-cigarette, the activation signal will enable the user to use thee-cigarette. In some embodiments, the age-restricted device **1251** is required to be activated only once. In other embodiments, the age-restricted device **1251** must be activated each time a user attempts to use the device, or must be activated within a certain set period, e.g., every day, week, month, etc. Turning now to FIG. **12**, which is a flowchart showing an illustrative method **1600** for age-restricted product registration. In some embodiments, the steps in flow chart **1600** may be implemented in program code executed by a processor, for example, the processor in a general purpose computer, mobile device, or server. In some embodiments, these steps may be implemented by a group of processors. In some embodiments the steps shown in FIG. **11** may be performed in a different order. Alternatively, in some embodiments, one or more of the steps may be skipped or additional steps may be performed. The steps below are described with reference to components described above with regard to the systems described above with regard to FIGS. **8A**, **8B**, and **9**.

(125) At step **1602** an age-restricted device **1251** receives a verification signal from computing device **1201**. The verification signal was determined based on scanning a passive data source and extracting data from the passive data source as described in the embodiments above. At step **1604** a processor **1252** activates the age-restricted device based on the verification signal. In some embodiments, the activation signal causes a processor **1252** on the age-restricted device to activate the device and enable a user to access age-restricted material **1254** on the device. For example, if the age-restricted device **1251** is an e-cigarette, the activation signal will enable the user to use the e-cigarette. In some embodiments, the age-restricted device **1251** is required to be activated only once. In other embodiments, the age-restricted device **1251** must be activated each time a user attempts to use the device, or must be activated within a certain set period, e.g., every day, week, month, etc.

(126) In some embodiments, the systems and methods described above may be provided to application developers on a software development kit (SDK) that enables the developer (e.g., the developer of the webpage or IOS, Android, or Windows application) to quickly plug the functionality into their application or 'web page as a module. In other embodiments, an application or web page development company may develop its own image capture software, but may be given access to image processing capability using the database and algorithms described herein. In other embodiments, the database of data associated with identification card data may be sold to application or web page development companies. In other embodiments, only portions of the database may be sold or made available, e.g., only the segment of the database associated with a state, region, or government entity. In other embodiments, algorithms developed to determine identification data associated only a certain region may be made available.

(127) In some embodiments, the systems and methods described above may be provided to application developers on a software development kit (SDK) that enables the developer (e.g., the developer of the webpage or IOS, Android, or Windows application) to quickly plug the functionality into their application or web page as a module. In other embodiments, an application or web page development company may develop its own image capture software, but may be given access to image processing capability using the database and algorithms described herein. In other embodiments, the database of data associated with identification card data may be sold to application or web page development companies. In other embodiments, only portions of the

database may be sold or made available, e.g., only the segment of the database associated with a state, region, or government entity. In other embodiments, algorithms developed to determine identification data associated only a certain region may be made available.

General Considerations

(128) The methods, systems, and devices discussed above are examples. Various configurations may omit, substitute, or add various procedures or components as appropriate. For instance, in alternative configurations, the methods may be performed in an order different from that described, and/or various stages may be added, omitted, and/or combined. Also, features described with respect to certain configurations may be combined in various other configurations. Different aspects and elements of the configurations may be combined in a similar manner. Also, technology evolves and, thus, many of the elements are examples and do not limit the scope of the disclosure or claims.

(129) Specific details are given in the description to provide a thorough understanding of example configurations (including implementations). However, configurations may be practiced without these specific details. For example, well-known circuits, processes, algorithms, structures, and techniques have been shown without unnecessary detail in order to avoid obscuring the configurations. This description provides example configurations only, and does not limit the scope, applicability, or configurations of the claims. Rather, the preceding description of the configurations will provide those skilled in the art with an enabling description for implementing described techniques. Various changes may be made in the function and arrangement of elements without departing from the spirit or scope of the disclosure.

(130) Also, configurations may be described as a process that is depicted as a flow diagram or block diagram. Although each may describe the operations as a sequential process, many of the operations can be performed in parallel or concurrently. In addition, the order of the operations may be rearranged. A process may have additional steps not included in the figure. Furthermore, examples of the methods may be implemented by hardware, software, firmware, middleware, microcode, hardware description languages, or any combination thereof. When implemented in software, firmware, middleware, or microcode, the program code or code segments to perform the necessary tasks may be stored in a non-transitory computer-readable medium such as a storage medium. Processors may perform the described tasks.

(131) Having described several example configurations, various modifications, alternative constructions, and equivalents may be used without departing from the spirit of the disclosure. For example, the above elements may be components of a larger system, wherein other rules may take precedence over or otherwise modify the application of the invention. Also, a number of steps may be undertaken before, during, or after the above elements are considered. Accordingly, the above description does not bound the scope of the claims.

(132) The use of “adapted to” or “configured to” herein is meant as open and inclusive language that does not foreclose devices adapted to or configured to perform additional tasks or steps. Additionally, the use of “based on” is meant to be open and inclusive, in that a process, step, calculation, or other action “based on” one or more recited conditions or values may, in practice, be based on additional conditions or values beyond those recited. Headings, lists, and numbering included herein are for ease of explanation only and are not meant to be limiting.

(133) Embodiments in accordance with aspects of the present subject matter can be implemented in digital electronic circuitry, in computer hardware, firmware, software, or in combinations of the preceding. In one embodiment, a computer may comprise a processor or processors. The processor comprises or has access to a computer-readable medium, such as a random access memory (RAM) coupled to the processor. The processor executes computer-executable program instructions stored in memory, such as executing one or more computer programs including a sensor sampling routine, selection routines, and other routines to perform the methods described above.

(134) Such processors may comprise a microprocessor, a digital signal processor (DSP), an

application-specific integrated circuit (ASIC), field programmable gate arrays (FPGAs), and state machines. Such processors may further comprise programmable electronic devices such as PLCs, programmable interrupt controllers (PICs), programmable logic devices (PLDs), programmable read-only memories (PROMs), electronically programmable read-only memories (EPROMs or EEPROMs), or other similar devices.

(135) Such processors may comprise, or may be in communication with, media, for example tangible computer-readable media, that may store instructions that, when executed by the processor, can cause the processor to perform the steps described herein as carried out, or assisted, by a processor. Embodiments of computer-readable media may comprise, but are not limited to, all electronic, optical, magnetic, or other storage devices capable of providing a processor, such as the processor in a web server, with computer-readable instructions. Other examples of media comprise, but are not limited to, a floppy disk, CD-ROM, magnetic disk, memory chip, ROM, RAM, ASIC, configured processor, all optical media, all magnetic tape or other magnetic media, or any other medium from which a computer processor can read. Also, various other devices may include computer-readable media, such as a router, private or public network, or other transmission device. The processor, and the processing, described may be in one or more structures, and may be dispersed through one or more structures. The processor may comprise code for carrying out one or more of the methods (or parts of methods) described herein.

(136) While the present subject matter has been described in detail with respect to specific embodiments thereof, it will be appreciated that those skilled in the art, upon attaining an understanding of the foregoing may readily produce alterations to, variations of, and equivalents to such embodiments. Accordingly, it should be understood that the present disclosure has been presented for purposes of example rather than limitation, and does not preclude inclusion of such modifications, variations and/or additions to the present subject matter as would be readily apparent to one of ordinary skill in the art.

Claims

1. A system for activating an age-restricted device, the system comprising: a mobile computing device configured to store an electronic identification card; a server in communication with the mobile computing device, the server configured to: receive the electronic identification card from the mobile computing device; verify an age of a user based on the electronic identification card; and transmit a verification signal to an age-restricted device, the verification signal configured to be received by the age-restricted device, the age-restricted device configured to allow use based in part on receipt of the verification signal.
2. The system of claim 1, wherein verifying an age of the user comprises: determining a type of encryption associated with the electronic identification card; and extracting one or more known data elements from the electronic identification card.
3. The system of claim 1, wherein the server is further configured to extract data comprising one or more of: a first name, a last name, an address, a city, a state, a zip code, an issue date, or an expiration date from the electronic identification card.
4. The system of claim 1, wherein the server is further configured to determine whether a user is an authorized user.
5. The system of claim 1, wherein the age-restricted device is in communication with the server via a network connection.
6. The system of claim 1, wherein the mobile computing device comprises a smartphone.
7. The system of claim 1, wherein the electronic identification card is an electronic identification stored in an application on a computing device.
8. The system of claim 1, wherein the electronic identification card complies with the International Organization for Standardization's ISO/IEC CD 18013-5.

9. The system of claim 1, wherein the electronic identification card is an image in a PDF-417 format.
10. The system of claim 1, wherein the age-restricted device comprises an electronic cigarette.
11. The system of claim 1, wherein the age-restricted device comprises a networked computer.
12. A method for activating an age-restricted device, the method comprising: retrieving an electronic identification card from an application stored on a mobile computing device; sending the electronic identification card to a server; verifying, by the server, an age of a user based on the electronic identification card; and transmitting a verification signal to an age-restricted device, the verification signal configured to be received by the age-restricted device, the age-restricted device configured to activate for use based in part on receipt of the verification signal.
13. The method of claim 12, wherein verifying an age of the user comprises: determining a type of encryption associated with the electronic identification card; and extracting one or more known data elements from the electronic identification card.
14. The method of claim 13, wherein extracting one or more known data elements comprises transmitting data associated with the electronic identification card to a server configured to extract a date of birth from the electronic identification card.
15. The method of claim 12, wherein the server is further configured to determine whether a user is an authorized user.
16. The method of claim 12, wherein the age-restricted device comprises an electronic cigarette.
17. A method for allowing use of an age-restricted device, the method comprising: retrieving information from an electronic identification card stored on a mobile computing device; verify an age of a user based on the information retrieved from the electronic identification card; transmitting the verification signal to an age-restricted device, the verification signal configured to be received by the age restricted device, the age restricted device configured to use based in part on receipt of the verification signal; and allowing use of material stored in the age-restricted device based on the verification signal.
18. The method of claim 17, wherein retrieving comprises: determining a type of encryption associated with the electronic identification card; and extracting one or more known data elements from the electronic identification card.
19. The method of claim 18, wherein extracting one or more known data elements comprises: transmitting data associated with the electronic identification card to a server configured to determine a date of birth from the data retrieved from the electronic identification card.
20. The method of claim 17, wherein the retrieving information from an electronic identification card stored on a mobile computing device further comprises retrieving information from an electronic identification card stored on a smartphone.
21. The method of claim 17, wherein the electronic identification card complies with ISO/IEC CD 18013-5.
22. The method of claim 18, wherein the age-restricted device comprises an electronic cigarette.
-