

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414762
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Huang; Yi Hsi et al.

Surgical device

Abstract

A surgical device has a housing having a hook portion at a distal end of the housing, an opening radially penetrating between the hook portion and the housing; a grasping structure comprising a rotating member rotatably positioned within the hook portion, having a notch radially recessed on a periphery of the rotating member, at least a portion of the notch corresponding to at least a portion of the opening; and reciprocating motion of an actuator along the axis for rotating the rotating member such that the open end of the notch is selectively connected to or misaligned with the open end of the opening.

Inventors: Huang; Yi Hsi (Taipei, TW), Tsai; I-Lin (Taipei, TW), Chen; Kuei-Hua (Taichung, TW)

Applicant: ASTRON MEDTECH CORPORATION (Wilmington, DE)

Family ID: 1000008821563

Assignee: ASTRON MEDTECH CORPORATION (Wilmington, DE)

Appl. No.: 18/343513

Filed: June 28, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240050088 A1	Feb. 15, 2024

Related U.S. Application Data

us-provisional-application US 63396681 20220810

Publication Classification

Int. Cl.: A61B17/04 (20060101); A61B8/00 (20060101)

U.S. Cl.:

CPC A61B17/0491 (20130101); A61B8/4209 (20130101);

Field of Classification Search

CPC: A61B (17/0483); A61B (17/0469); A61B (17/06061); A61B (17/0491); A61B (17/0493); A61B (17/0485)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5499991	12/1995	Garman	606/148	A61B 17/0483
2022/0240926	12/2021	Sauer	N/A	A61B 17/0482

Primary Examiner: Nguyen; Tuan V

Attorney, Agent or Firm: Best & Flanagan LLP

Background/Summary

FIELD OF THE INVENTION

(1) The present invention relates to a surgical device.

BACKGROUND OF THE INVENTION

(2) As modern medical technology becomes more advanced, minimally invasive surgery or small wound surgery has gradually become the goal in a surgical operation, which can not only achieve a quick and good wound healing effect, but also help the post-healing scar fade and improve. When a surgeon performs a suture in the body, the small operation space could not allow the surgeon to perform the operation deeper with hands, so the surgeon usually uses a long, thin surgical clamp or hemostatic forceps to facilitate the removal of the suture or the stitch in deep.

(3) However, due to the dense and complex distribution of tissues in the body, and the fact that other surgical instruments will be placed in the body at the same time during surgery, if one is not cautious enough, the surgical clamp or hemostat could easily damage or pull the adjacent tissues and other surgical instruments when clamping the stitch or suture back and forth, causing unnecessary injuries. Therefore, the development of a product that allows the surgeon to easily perform stitching without damaging or pulling adjacent tissues and other surgical instruments is an urgent goal in the related industry.

SUMMARY OF THE INVENTION

(4) In order to develop a product that facilitates a surgeon to perform stitching and avoids damaging or pulling the adjacent tissues and other surgical instruments, the present invention provides a surgical device comprising a housing having a receiving space inside, a hook portion extending downwardly and arcuately at distal end of the housing, an opening radially penetrating between the hook portion and the housing, a circle-like rotation space being formed inside the hook portion together with the opening, and the receiving space, the rotation space and the opening being connected to each other; a grasping structure positioned at a distal end of the housing, comprising a

block-type rotating member having a similar circular shape rotatably placed in the rotation space, a notch radially recessed on a periphery of the rotating member, at least a portion of the notch corresponding to at least a portion of the opening; and an actuator, the reciprocating motion along the axial direction being used to rotate the rotating member so that the open end of the notch is selectively connected to or misaligned with the open end of the opening; and a driver used to drive the actuator in the reciprocating motion, wherein when the open end of the notch is misaligned with the open end of the opening, a connected receiving perforation is formed at the location of the notch and the opening corresponding to each other.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1A is a side view of the preferred embodiment of the present invention;
- (2) FIG. 1B is a partial enlarged view of the preferred embodiment of the present invention;
- (3) FIG. 2A is an exploded view of the preferred embodiment of the present invention;
- (4) FIG. 2B is an enlarged view of the components of the preferred embodiment of the present invention;
- (5) FIG. 3 is a schematic view of the first action of the preferred embodiment of the present invention;
- (6) FIG. 4 is a schematic view of the second action of the preferred embodiment of the present invention;
- (7) FIG. 5 is a schematic view of the use of the preferred embodiment of the present invention; and
- (8) FIG. 6 is a partial enlarged view of the second preferred embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

- (9) Referring to FIGS. 1 and 2, a preferred embodiment of the surgical device **10** provided by the present invention comprises a housing **11** extending in an axial direction with a receiving space formed therein. A hook portion **111** extending downwardly and arcuately at a distal end of the housing **11**, and the entire hook portion **111** is similar to a circular shape and the diameter of which is larger than the diameter of the housing **11** adjacent to the hook portion **111**. An opening **112** radially penetrating between a hook end **1111** of the hook portion **111** and the housing **11**. A circle-like rotation space is formed inside the hook portion **111** together with the opening **112**, and the receiving space, the rotation space, and the opening **112** are connected to each other.
- (10) The housing **11** may consist of two components to be assembled up and down or left and right, but may also be assembled correspondingly with a number of components according to the requirement. In this embodiment, the housing **11** includes a left housing member **114** and a right housing member **115** at the proximal end, which can be assembled with each other, and the hook portion **111** at the distal end includes a hook left housing member **116** and a hook right housing member **117**, which can be assembled with each other. wherein, when the hook left housing member **116** and the hook right housing member **117** are assembled, the diameter of the assembly is gradually reduced toward the distal end, and the proximal end of the assembly of the hook left housing member **116** and the hook right housing member **117** can be interconnected with the distal end of the assembly of the left housing member **114** and the right housing member **115**. This helps the housing **11** to use the smaller outer diameter of the hook portion **111** (the left housing member **114** and the right housing member **115**) to penetrate deeply into the surgical site to achieve a minimally invasive effect.
- (11) The housing **11** can be made to have a suitable appearance according to the practical application as desired, for example, the housing **11** can extend in a straight rod shape along the axis, or it can be in a curved shape with an angle. In this embodiment, the proximal end of the housing **11** extends horizontally toward the distal end, and the housing **11** extends downward at an

angle relative to the horizontal at the middle portion and then returns to the horizontal extension adjacent to the hook portion **111** to form the distal end, wherein the angle is between 10 degrees and 60 degrees. In this way, the housing **11** can be made to conform to the shape of each part.

(12) Further, with reference to FIG. 5, the housing **11** has a curved section **118** extending upwardly and arcuately adjacent to the hook portion **111**, and the hook portion **111** is formed along the curved section **118** extending upwardly, so that the curved section **118** and the hook portion **111** as a whole have a curved upward appearance, and it is noteworthy that because the curved section **118** extends upwardly, a height difference space **h** is formed under the curved section and the housing **11** so that the hook end **1111** can be accommodated therein. This not only helps the hook portion **111** to penetrate deeper into the surgical site and move more smoothly between the two tissues **A1**, **A2**, but also prevents the hook end **1111** from hooking on the side of the tissue **A2** when the hook portion **111** exits between the two tissues **A1**, **A2**.

(13) In the housing **11**, a gripping structure **12** is provided at the distal end and a driver **13** is provided at the proximal end, which is used to drive the gripping structure **12** to change its relative position. The gripping structure **12** includes a rotating member **121** and an actuator **122** arranged from the distal end to the proximal end, wherein the rotating member **121** is a circle-like block and can be placed in the rotation space by rotating in the direction of the axis.

(14) The rotating member **121** is provided with a notch **123** recessed on a periphery in a radial direction, and when the rotating member **121** is positioned in the rotation space, at least a portion of the notch **123** corresponds to at least a portion of the opening **112**. In this embodiment, the closed end of the notch **123** is connected to the closed end of the opening **112**. The rotating member **121** can be rotated relative to the rotation space by the axial displacement of the actuator **122**, so that the open end of the notch **123** can be selectively connected or misaligned with the open end of the opening **112**. When the open end of the notch **123** is misaligned with the open end of the opening **112**, a connected receiving perforation is formed at the location of the notch **123** and the opening **112** corresponding to each other.

(15) Wherein, the manner of which the rotating member **121** is urged by the actuator **122** to rotate is not limited, as long as the rotation of the rotating member **121** can be associated with the axial displacement of the actuator **122** which should be covered within the scope of the present invention.

(16) In this embodiment, the actuator **122** includes a rotating connector **1221** and a driving rod **1222**. The rotating connector **1221** is a circular block and is connected to one end of the driving rod **1222** at any point on its periphery, the rotating member **121** has a rotating notch **124** recessed on the other periphery, and the rotating connector **1221** is rotatable in the rotating notch **124**.

(17) With further reference to FIGS. 3 and 4, in the starting position shown in FIG. 3, the rotating member **121** is disposed in the rotation space, and the open end of the notch **123** is connected to the open end of the opening **112**. The rotating connector **1221** is positioned where the rotation space is connected to the receiving space and near the top of the housing **11**, and the driving rod **1222** extends toward the proximal end corresponding to the rotating connector **1221**.

(18) In a driving position shown in FIG. 4, the driving rod **1222** is displaced toward the proximal end, and at this time, the driving rod **1222** pulls the rotating member **121** through the rotating connector **1221** so that a push-pull force is generated over the rotating member **121** toward the proximal end, so that the rotating member **121** rotates relative to the rotating connector **1221**, causing the misalignment of the open end of the notch **123** and the open end of the opening **112**, forming the receiving perforation. In this way, the rotating member **121** can be urged to rotate by using the actuator **122**, and the movement relationship of the open end of the notch **123** can be selectively connected or misaligned with the open end of the opening **112**.

(19) Wherein, the rotating connector **1221** and the driving rod **1222** may be provided in the form of a one-piece or assembled combination.

(20) Wherein, the rotating member **121** is next to the rotating notch **124**, and a receiving slot is

recessed on the periphery corresponding to the driving rod **1222**. When the driving rod **1222** is displaced toward the distal end and causes the rotating member **121** to rotate relative to the rotating connector **1221**, the driving rod **1222** can be correspondingly displaced into the receiving slot to avoid interfering with the rotation of the rotating member **121**.

(21) The driver **13** is located near the proximal end of the receiving space and is used to push the driving rod **1222** for displacement toward the proximal end by a reciprocating motion so that the rotating member **121** can be moved from the starting position to the driving position.

(22) In this embodiment, the driver **13** comprises an operation member **131** and a restoration member **132** used to restore the operation member **131** from the driving position to the starting position. Adjacent to the proximal end, a handle perforation **113** is pierced through the housing **11** and extends along the axial direction. The distal end of the operation member **131** is connected to the proximal end of the driving rod **1222**, and the operation member **131** is movable at a position in the axial direction corresponding to the handle perforation **113**.

(23) The operation member **131** has a handle structure **133** protruding toward the handle perforation **113** to the outside of the housing **11**, so that the displacement distance of the operation member **131** can be limited by the handle perforation **113** and the handle structure **133**. The restoration member **132** comprises a resisting ring **1321** fixed and sleeved to the proximal end of the driving rod **1222**, a resisting member **1323** protruding from the housing **11** near the distal end of the handle perforation **113**, and a spring **1322** mounted on the outer periphery of the driving rod **1222** and abutted against the resisting ring **1321** and the resisting member **1323** at each end thereof.

(24) The spring **1322** is a compression spring, as in FIG. 3, at the starting position, the spring **1322** has no tension, when the operation member **131** is pulled toward the proximal end to the driving position (as in FIG. 4), the driving rod **1222** is displaced toward the forward end together with the resisting ring **1321**. At this moment, the spring **1322** receives compression to form a tension, and when the operation member **131** is stopped being pulled, the spring **1322** can drive the operation member **131** back to the starting position based on the elastic restoring force.

(25) The present invention further comprises a limiter **14** for holding the surgical device **10** in the driving position. In this embodiment, the limiter **14** comprises a limiting member **141** and a limiting spring **142**. The housing **11** is pierced with a limiting perforation **113** adjacent to the proximal end, and the resisting ring **1321** is recessed with a limiting slot **1324** around the circumference so that the resisting ring **1321** has a smaller outer diameter than the limiting slot **1324**.

(26) The limiting spring **142** is a torsion spring whose two ends are connected to the housing **11** and the middle section of the limiting member **141**, the two ends of the limiting member **141** form a stop portion **1411** and a release portion **1412** respectively, the limiting member **141** can be rotated in the receiving space according to the torsion spring, and at the same time the stop portion **1411** and the release portion **1412** at two ends may be made to move in opposite directions. According to the relative position of the limiting member **141** during the rotation, the stop portion **1411** is selectively fitted concavely and convexly into the limiting slot **1324** and the release portion **1412** is selectively protruded from the limiting perforation **113**.

(27) In the starting position of FIG. 3, the resisting ring **1321** is positioned at the distal end so that the stop portion **1411** is misaligned with the limiting slot **1324**, and at that moment the stop portion **1411** is pressed by the larger outer diameter of the resisting ring **1321**, causing tension in the torsion spring, and the release portion **1412** at the other end remains in the receiving space and the limiting perforation **114**.

(28) When the operation member **131** is pulled and driven to move toward the proximal end so that the limiting slot **1324** corresponds to the stop portion **1411**, then the torsion spring drives the limiting member **141** to rotate based on the elastic restoring force so that the stop portion **1411** is displaced toward the limiting slot **1324** and fitted concavely and convexly, and the release portion **1412** at the other end protrudes from the limiting perforation **114** to the outside of the housing **11**.

The limiter **14** can then fix the surgical device **10** in a suspension state in the driving position.

(29) Then, the release portion **1412** is pressed to rotate the limiting member **141** and cause the stop portion **1411** to release the limiting slot **1324** so that the spring **1322** can drive the operation member **131** back to the starting position based on the elastic restoring force.

(30) Referring further to FIG. **6**, the second embodiment of the present invention differs from the foregoing in that the hook portion **11** is rotatable in the axial direction. In this embodiment, the housing **11** comprises a first housing **15** disposed at the proximal end and a second housing **16** positioned at the distal end corresponding to the hook portion **11** and/or the curved section **118**, wherein the distal inner surface of the first housing **15** is annularly recessed with a limiting slot **151**, and the proximal surface of the second housing **16** has at least one convex rib **161** protruding from the limiting slot **151**, wherein the convex rib may be symmetrically protruded from the surface of the second housing **16** or annularly protruded from the surface of the second housing **16**. When the first housing **15** is assembled with the second housing **16**, the convex rib **161** is rotatably positioned in the limiting slot **151** so that the second housing **16** can be rotated relative to the first housing **15**.

(31) The proximal end of the driving rod **1222** can be rotatably connected to the operation member **131**. In this embodiment, the driving rod **1222** crosses the operation member **131** at any position toward the proximal end, and the surface of the proximal end of the driving rod **1222** is screwed with a nut **1223** so that the proximal end of the driving rod **1222** can be rotated on the operation member **131**, and the operation member **131** can pull the driving rod **1222** toward the proximal end by pushing the nut **1223**.

(32) When the surgical device provided by the present invention is used in a surgical operation, when the open end of the notch **123** is connected to the open end of the opening **112** of the housing **11**, a stitch can be grasped through the connected open end and enter the place where the notch **123** and the opening **112** correspond to each other, and further, when the open end of the notch **123** is misaligned with the open end of the opening **112** of the housing **11**, the stitch can be retained in the receiving perforation without being detached.

Claims

1. A surgical device comprising: a housing extending in the form of a rod in an axial direction with a receiving space formed therein, a hook portion formed at a distal end of the housing, an opening radially penetrating between a hook end of the hook portion and the housing, and a rotation space formed inside the hook portion together with the opening, the receiving space, the rotation space, and the opening being connected to each other; a gripping structure positioned in the housing at the distal end, comprising: a rotating member, rotatably disposed in the rotation space, a notch being radially recessed in one periphery of the rotating member, at least a portion of the notch corresponding to at least a portion of the opening; and an actuator for rotating the rotating member in a reciprocating motion along the axis so that the open end of the notch is selectively connected to or misaligned with the open end of the opening; and a driver for driving the actuator in a reciprocating motion, wherein, when the open end of the notch is misaligned with the open end of the opening, a connected receiving perforation is formed at the location of the notch and the opening corresponding to each other.
2. The surgical device according to claim 1, wherein, the hook portion extends downwardly and arcuately at the distal end of the housing, the rotation space has a circle-like shape, and the rotating member is arranged therein in a circle-like block shape, a diameter of the hook portion is larger than the diameter of the housing adjacent to the hook portion.
3. The surgical device according to claim 1, wherein, the housing has a curved section extending upwardly and arcuately adjacent to the hook portion, and the hook portion is formed along the curved section extending upwardly, and a height difference space is formed under the curved

section and the housing, and the end of the hook portion is accommodated in the height difference space.

4. The surgical device according to claim 3, wherein, the actuator comprises a rotating connector in the form of a circular block and is connected to one end of a driving rod at any point on its periphery; and the rotating member has a rotating notch recessed on the other periphery, the rotating connector is rotatably provided in the rotating notch, and the other end of the driving rod extends towards the proximal end and is driven by the actuator for reciprocating motion, causing the rotating member to rotate relative to the rotating connector.

5. The surgical device according to claim 4, wherein, the rotating member is adjacent to the rotating notch and a receiving slot is recessed on the corresponding periphery of the driving rod, when the driving rod is displaced toward the distal end and cause the rotating member to rotate relative to the rotating connector, the driving rod is entered into the receiving slot.

6. The surgical device according to claim 5, wherein, the housing is provided with a handle perforation extending in the direction of the axis adjacent to the proximal end thereof, and a resisting member is protruded adjacent to the distal end of the handle perforation; the distal end of the operation member is connected to the proximal end of the driving rod, the operation member has a handle structure protruding toward the handle perforation to the outside of the housing, and the reciprocating motion of the operation member is limited by the handle perforation and the handle structure; and the restoration member comprises a resisting ring fixed and sleeved to the proximal end of the driving rod, and a spring mounted on the outer periphery of the driving rod and abutted against the resisting ring and the resisting member at each end thereof, the spring having no tension in the starting position, when the operation member is pulled toward the proximal end and the driving rod is displaced toward the forward end together with the resisting ring to compress the spring.

7. The surgical device according to claim 6, wherein, the housing is pierced with a limiting perforation adjacent to the proximal end; the resisting ring is recessed with a limiting slot around the periphery so that the resisting ring is formed with an outer diameter smaller than the limiting slot; and the limiter comprises a limiting spring whose two ends are connected to the housing and to the middle section of the limiting member, the two ends of the limiting member are a stop portion and a release portion respectively, the limiting member rotating in the receiving space in accordance with the limiting spring, and the stop portion and the release portion being displaced in opposite directions, wherein, in the starting position, the resisting ring being positioned at the distal end so that the stop portion is misaligned with the limiting slot and is pressed by the larger outer diameter of the resisting ring, causing tension in the torsion spring, and the release portion remains in the receiving space and the limiting perforation, when the operation member is moved toward the proximal end so that the limiting slot corresponds to the stop portion, the stop portion is displaced toward the limiting slot, and the release portion protrudes from the limiting perforation to the outside of the housing.

8. The surgical device according to claim 4, the driver is disposed in the housing at the proximal end, comprising: an operation member for pulling the driving rod towards the proximal end so that the rotating member to move from the starting position to a driving position, the open end of the notch being connected to the open end of the opening in the driving position; and a restoration member for restoring the operation member from the driving position to the starting position.

9. The surgical device according to claim 8, comprising a limiter for holding the surgical device in the driving position.

10. The surgical device according to claim 8, wherein, the housing comprises: a first housing disposed at the proximal end having a limiting slot annularly recessed on the distal inner surface; and a second housing positioned at the distal end corresponding to the hook portion, having at least one convex rib protruding from the outer surface of the proximal end, wherein when the first housing is assembled with the second housing, the convex rib is rotatably positioned in the limiting

slot so that the second housing is rotatable relative to the first housing; and the proximal end of the driving rod is rotatably connected with the operation member.

11. The surgical device according to claim 10, wherein, the driving rod crosses the operation member at any position toward the proximal end, and the surface of the proximal end of the driving rod is screwed with a nut, and the operation member pulls the driving rod toward the proximal end by pushing the nut.

12. The surgical device according to claim 1, wherein, the rotating member and the actuator rotate in an axial direction relative to the driver.
