

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414792
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Turano; Bo D. et al.

Microdebrider with stability interface bushing

Abstract

A device for removing tissue or bone includes a housing having an outer tube defining an inner lip. A middle tube is supported within the outer tube and includes an opening having teeth at a distal end thereof and a shoulder defined around an outer surface thereof proximate the opening. An inner tube is disposed within the middle tube and includes an opening having teeth at a distal end thereof in registration with the opening in the middle tube. The inner tube couples to a power source and rotates relative to the middle tube such that the teeth cooperate to cut tissue or bone disposed in a cutting window between the openings. A bushing is disposed atop the middle tube against the shoulder, such that, upon assembly, the bushing seats between the shoulder of the middle tube and the inner lip of the outer tube to provide stability therebetween.

Inventors:	Turano; Bo D. (Jacksonville, FL), Papenfuss; Erik (Naples, FL)
Applicant:	Medtronic Xomed, LLC (Jacksonville, FL)
Family ID:	1000008821526
Assignee:	Medtronic Xomed LLC (Minneapolis, MN)
Appl. No.:	17/900349
Filed:	August 31, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240065718 A1	Feb. 29, 2024

Publication Classification

Int. Cl.: A61B17/32 (20060101); A61B17/00 (20060101)

U.S. Cl.:

CPC **A61B17/32002** (20130101); A61B2017/00367 (20130101); A61B2017/00526 (20130101); A61B2217/005 (20130101)

Field of Classification Search

CPC: A61B (17/24); A61B (17/32002); A61B (17/320783)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4958932	12/1989	Kegelman	600/172	A61B 5/1076
5618293	12/1996	Sample et al.	N/A	N/A
6007556	12/1998	Kablik et al.	N/A	N/A
6645218	12/2002	Cassidy et al.	N/A	N/A
6824552	12/2003	Robison et al.	N/A	N/A
7077845	12/2005	Hacker et al.	N/A	N/A
7244263	12/2006	Robison et al.	N/A	N/A
7674263	12/2009	Ryan	N/A	N/A
7699846	12/2009	Ryan	N/A	N/A
7719437	12/2009	Bertram, III	N/A	N/A
7803170	12/2009	Mitusina	N/A	N/A
7854736	12/2009	Ryan	N/A	N/A
7942880	12/2010	Bertram, III	N/A	N/A
7993360	12/2010	Hacker et al.	N/A	N/A
8052706	12/2010	Mitusina	N/A	N/A
8057500	12/2010	Mitusina	N/A	N/A
8142464	12/2011	Mitusina	N/A	N/A
8366559	12/2012	Papenfuss et al.	N/A	N/A
8808375	12/2013	Bertram, III	N/A	N/A
8852191	12/2013	Bertram, III	N/A	N/A
8870893	12/2013	Makower et al.	N/A	N/A
8944926	12/2014	Kramer et al.	N/A	N/A
9198685	12/2014	Edwards et al.	N/A	N/A
9381032	12/2015	Edwards et al.	N/A	N/A
9474541	12/2015	Zider et al.	N/A	N/A
9486232	12/2015	Heisler et al.	N/A	N/A
9517076	12/2015	Papenfuss	N/A	N/A
9603607	12/2016	Papenfuss	N/A	N/A
9668751	12/2016	Papenfuss	N/A	N/A
9775967	12/2016	Hatta et al.	N/A	N/A
9808867	12/2016	Krause et al.	N/A	N/A
9833249	12/2016	Bertram, III	N/A	N/A
9839441	12/2016	Hayes et al.	N/A	N/A
10179002	12/2018	Wasicek et al.	N/A	N/A
10271830	12/2018	Papenfuss et al.	N/A	N/A
10492800	12/2018	Papenfuss	N/A	N/A
10524820	12/2019	Algawi et al.	N/A	N/A
10743912	12/2019	Papenfuss	N/A	N/A

10779806	12/2019	Kieturakis et al.	N/A	N/A
11020139	12/2020	Curtin et al.	N/A	N/A
11064980	12/2020	Papenfuss et al.	N/A	N/A
11065012	12/2020	Edwards	N/A	N/A
2005/0277970	12/2004	Norman	606/180	A61B 17/32002
2019/0357924	12/2018	Papenfuss	N/A	N/A
2020/0245854	12/2019	Mach	N/A	A61B 1/00167
2021/0282799	12/2020	Curtin	N/A	A61B 17/32002
2022/0015821	12/2021	Norton et al.	N/A	N/A
2022/0133360	12/2021	Papenfuss et al.	N/A	N/A

OTHER PUBLICATIONS

Extended European Search Report EP23193270.8 dated Jan. 15, 2024, 6pp. cited by applicant

Primary Examiner: McGrath; Erin

Attorney, Agent or Firm: Carter, DeLuca & Farrell LLP

Background/Summary

FIELD

(1) The present disclosure is generally directed to devices and systems for cutting and treating tissue, such as bone and soft tissue. The present disclosure may be particularly suitable for sinus applications and nasopharyngeal/laryngeal procedures.

BACKGROUND

(2) Devices and systems in accordance with the present disclosure may be suitable for a variety of procedures including ear, nose and throat (ENT) procedures, head and neck procedures, otology procedures, including otoneurologic procedures. Other surgical procedures suitable for use with the devices described herein include: mastoidectomies; nasopharyngeal and laryngeal procedures such as tonsillectomies, tracheal procedures, adenoidectomies, laryngeal lesion removal, and polypectomies; for sinus procedures such as polypectomies, septoplasties, removals of septal spurs, antrostomies, frontal sinus trephination and irrigation, sinus opening, endoscopic DCR, correction of deviated septum s and trans-sphenoidal procedures; rhinoplasty and removal of fatty tissue in the maxillary and mandibular regions of the face.

(3) Of particular significance is the usefulness of the devices and systems described herein with sinus surgery which is often challenging due to the obvious location of the sinus cavity to sensitive organs such as the eyes and brain. Moreover, the relatively small size of the anatomy of interest to the surgeon and the complexity of the typical procedures places a heavy emphasis on precision. Examples of deriders with mechanical cutting components are described in commonly-owned U.S. Pat. Nos. 5,685,838; 5,957,881; and 6,293,957, the entire contents of each of which being incorporated by reference herein.

(4) The Medtronic Straightshot® Microdebridors, e.g., Medtronic Straightshot® RAD40 or RAD60 Microdebridors, use sharp cutters to cut tissue, and suction to withdraw tissue. While tissue debridement with the Medtronic microdebrider systems is a simple and safe technique, the blade angle of the middle tube and the concentric inner rotating tube of these devices relative to the outer tube may vary from about 12 degrees to about 120 degrees. Depending on the angle, the middle tube and the inner tube may extend several centimeters from the distal end of the outer tube, which in some instance can promote instability especially when the inner tube is rotating at high rpms and

encountering heavy tissue or bone. Moreover, since one of the unique advantages of the Medtronic Straightshot® Microdebridors is the ability to rotate the cooperating inner and middle cutting tubes 360 degrees to excise tissue and bone without rotating the outer tube, the forces associated with cutting tissue or bone in one rotational position may place more stress on the middle tube and outer tube interface than a different rotational position. As such, a need exists to provide a stabilizing interface between the middle and outer tubes for all blade angles that works during all cutting rotational positions.

SUMMARY

(5) Provided in accordance with the present disclosure is a device for removing tissue or bone including a housing having an outer tube extending therefrom having a longitudinal axis defined therealong, the outer tube including a distal end defining an inner lip. A middle tube is operably supported concentrically within the outer tube, the middle tube including an opening having a series of teeth at a distal end thereof and a shoulder defined around an outer peripheral surface thereof.

(6) An inner tube is concentrically disposed within the middle tube and includes an opening having a series of teeth at a distal end thereof in longitudinal registration with the opening in the middle tube. The inner tube is adapted to couple to a power source such that, upon activation thereof, the inner tube rotates relative to the middle tube and the series of teeth of the inner tube cooperate with the series of teeth of middle tube to cut tissue or bone disposed in a cutting window between the openings defined therebetween. A bushing is disposed atop the middle tube in abutting relation against the shoulder, such that, upon assembly, the bushing seats between the shoulder of the middle tube and the inner lip of the outer tube.

(7) In aspects according to the present disclosure, the distal end is rolled and reamed to form the inner lip.

(8) In aspects according to the present disclosure, the inner tube defines a lumen therethrough and extending therealong from the opening, and a portion of the lumen is adapted to connect to a suction source for eliminating cut tissue or bone.

(9) In aspects according to the present disclosure, a channel is defined between the concentric inner and middle tubes along a length thereof for passing a fluid therealong from a fluid source.

(10) In aspects according to the present disclosure, the device further includes a rotating wheel disposed atop the housing. The rotating wheel is configured to permit selective orientation of the cutting window between respective openings between the middle and inner tubes 360° of rotation without repositioning the outer tube.

(11) Provided in accordance with the present disclosure is a system for removing tissue or bone, the system including a housing adapted to be connected to a power source, a fluid source and a suction source. The housing includes an adapter configured to operably connect to a selectively removable blade. The selectively removable blade has a blade angle of about 12° to about 90°, with the blade including: an outer tube extending therefrom including a longitudinal axis defined therealong, the outer tube including a distal end defining an inner; a middle tube operably supported concentrically within the outer tube, the middle tube including an opening having a series of teeth at a distal end thereof and a shoulder defined around an outer peripheral surface thereof; an inner tube concentrically disposed within the middle tube including an opening having a series of teeth at a distal end thereof in longitudinal registration with the opening in the middle tube, the inner tube adapted to couple to a power source such that, upon activation thereof, the inner tube rotates relative to the middle tube and the series of teeth of the inner tube cooperate with the series of teeth of middle tube to cut tissue or bone disposed in a cutting window defined in the openings defined therebetween; and a bushing disposed atop the middle tube in abutting relation against the shoulder, such that, upon assembly, the bushing seats between the shoulder of the middle tube and the inner lip of the outer tube.

(12) In aspects according to the present disclosure, the system is configured to cooperate with a

surgical navigation system.

(13) In aspects according to the present disclosure, the distal end of the outer tube is rolled and reamed to form the inner lip.

(14) In aspects according to the present disclosure, the inner tube defines a lumen therethrough and extending therealong from the opening, a portion of the lumen adapted to connect to the suction source for eliminating cut tissue or bone.

(15) In aspects according to the present disclosure, a channel is defined between the concentric inner and middle tubes along a length thereof for passing a fluid therealong from the fluid source.

(16) In aspects according to the present disclosure, the housing further includes a rotating wheel disposed thereon, the rotating wheel configured to permit selective orientation of the cutting window between respective openings between the middle and inner tubes 360° of rotation without repositioning the outer tube.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In the drawings, where like numerals refer to like components throughout several views:

(2) FIG. 1 is a perspective view of a prior art system for performing one or more ENT surgical procedures;

(3) FIG. 2 is an enlarged, perspective view of a distal end of a blade for use with the system of FIG. 1;

(4) FIG. 3 is an enlarged, perspective view of a distal end of another blade for use with the system of FIG. 1;

(5) FIGS. 4 and 5 are enlarged, perspective views of distal ends of a blade for use with the system of FIG. 1;

(6) FIG. 6 is an enlarged, top view of a distal end of a blade in accordance with the present disclosure;

(7) FIG. 7 is an enlarged, perspective view of the blade shown in FIG. 6 with parts separated; and

(8) FIG. 8 is a side, perspective view of the blade of FIG. 6 shown assembled on a tissue removal system and being used in conjunction with a surgical navigation system.

DETAILED DESCRIPTION

(9) FIG. 1 illustrates a prior art system **10** having a surgical device **100** including a distal end region indicated generally at **120** and a proximal end region indicated generally at **110**. The device **100** includes an outer shaft **130** and an inner shaft **140** coaxially maintained within the outer shaft **130**. A portion of the inner shaft **140** is shown in FIG. 1 at distal end region **120**. Proximal end region **110** includes a button activation cell **200** having a housing **204** and an activation button **202**, the proximal end region further including a hub **175** coupled to inner shaft **140**. The hub **175** is configured to operably couple to a handpiece **177**, which can be manipulated by a user (e.g., a surgeon). The handpiece **177**, in turn, may be coupled to an integrated power console or IPC **179** for driving the device **100** and, specifically, for controlling rotation of inner shaft **140**. The IPC **179** may also include a fluid source (not shown) for providing fluid to device **100**.

(10) Proximal end region **110** also includes a fluid source connector **150**, a power source connector **160** and a suction source connector **170** operably connected to a fluid source **152**, a power source **162**, and a suction source **172**, respectively, of system **10**. While saline is particularly useful with the present disclosure, other fluids are contemplated. Power source **162**, e.g., a generator, is an optional component of system **10** and may be designed for use with bipolar energy. For example, the Transcollation® sealing energy supplied by the Aquamantys® System may be used. Both the fluid source **152** and suction source **172** are also optional components of system **10**. However, use of fluid in conjunction with energy delivery may provide additional tissue benefits.

(11) In use, a fluid (e.g., saline) may be emitted from an opening at the distal end region of the device **100**. Tissue fragments and fluids can be removed from a surgical site through an opening (not shown in FIG. 1) in the distal end region via the suction source **172**, as will be further explained below.

(12) FIG. 2 shows an enlarged perspective view of distal end portion **120** of device **100**. It is important to note that shaft **130** may be selectively engaged with housing **204** such that various cutters **132** at various angles may be utilized for various surgical purposes, e.g., FIGS. 6-8 discussing the Medtronic Straightshot® M4 or M5.

(13) The outer shaft **130** includes an opening **134** at a distal end **135** of the outer shaft **130**. Opening **134** is defined by cutters **132**, which includes cutting teeth **133**. The outer shaft **130** may be rigid or malleable (or combinations thereof) and may be made of a variety of metals and/or polymers or combinations thereof, e.g., stainless steel. A distal portion **148** of inner shaft **140** can be seen through the opening **134** of outer shaft **130**. In FIG. 1, inner shaft **140** is depicted in a position such that an inner shaft cutter **141** (FIG. 3), including cutting teeth **143**, is facing an inner wall (not shown) of outer shaft **130**. Cutter **141** defines an inner shaft opening **154** (FIG. 3). Outer and inner shaft cutters **132** and **141** may move relative to one another in oscillation or rotation (or both) in order to mechanically cut tissue. For example, outer shaft cutter **132** may remain stationary relative to the hub **175** while the inner shaft cutter **141** may rotate about a longitudinal axis A-A defined through the device **100** (FIG. 2), thereby cutting tissue.

(14) Rotation of inner shaft **140** may be achieved via manipulation of hub **175** (FIG. 1) that can orient the inner shaft **140** relative to the outer shaft **130** and may additionally allow for locking of the inner shaft **140** relative to the outer shaft **130** in a desired position, i.e., inner shaft **140** may be locked in position when cutter **141** is facing down and an electrode assembly **142** is facing up. As described above, hub **175** may be connected to handpiece **177**, which may be controlled by an ITC **179**. Alternatively, the hub **175** and/or handpiece **177** may be manipulated manually.

(15) Inner shaft **140** may be selectively rotated to expose electrode assembly **142** including electrodes **142a**, **142b**, through opening **134** of outer shaft **130**, as shown in FIG. 2. As depicted in FIG. 2, inner shaft **140** is positioned such that the inner shaft cutter **141** is facing the interior (not shown) of outer shaft **130** and may be in a downward facing direction and include a downward position. In the downward position, tissue is shielded from the inner shaft cutter **141** during hemostasis (via energy delivery through electrodes **142a**, **142b**), thereby delivering energy to tissue with no attendant risk that the cutting teeth **143** of the inner shaft **140** will diminish the efforts to achieve hemostasis. Device **100** may thus include two modes: a cutting or debridement mode and a sealing or hemostasis mode and the two modes may be mutually exclusive, i.e., hemostasis is achieved via energy delivery to tissue while cutters **132**, **141** are not active or cutting. As described below, energy may be advantageously delivered simultaneously with a fluid such as saline to achieve an optimal tissue effect by delivering controlled RF energy to tissue.

(16) As depicted in FIG. 3, when the inner shaft **140** is oriented such that cutter **141** is in the downward position, rotating inner shaft **140** approximately 180 degrees relative to the outer shaft **130** will expose inner shaft cutter **141** and inner shaft opening **154** through the outer shaft opening **134**. When the inner shaft cutter **141** is positioned as shown in FIG. 3, the inner shaft cutter **141** may be in an upward position. The inner shaft opening **154** is fluidly connected to an inner shaft lumen **156** that extends from the inner shaft distal portion **148** to the proximal end **151** of inner shaft **140** and may be fluidly connected with the suction source **172**. With this configuration, tissue cut via inner and outer shaft cutters **141**, **132** may be aspirated into the inner shaft lumen **156** through the inner shaft opening **154** upon application of suction source **172**, thereby removing tissue from a target site.

(17) With reference between FIGS. 4 and 5, the inner shaft **140** includes a proximal assembly **168** including a proximal assembly shaft component **169** (more clearly seen in FIG. 5) and electrodes **142a** and **142b**. Electrodes **142a** and **142b** may be used to deliver any suitable energy for purposes

of coagulation, hemostasis or sealing of tissue. Electrodes **142a** and **142b** are particularly useful with fluid, such as saline, provided by fluid source **152** (FIG. **1**) which may be emitted near the outer shaft opening **134**. Outer shaft opening **134** is fluidly connected to an outer shaft lumen **136** that extends from outer shaft opening **134** to the proximal end region **110** of device **100** and may be fluidly connected to the fluid source **152** (FIG. **1**). Thus, fluid can be delivered to the opening **134** of outer shaft. **130** and interacts with electrode **142a**, **142b**.

(18) Turning to FIG. **6**, which shows a schematic cross-section of a surgical blade **400** (which is selectively engageable with a portion of device **100** above, e.g., housing **204**) of the present disclosure for use with the surgical system **10** described above and in connection with various ENT procedures, such as transnasal endoscopic bone and tissue removal under navigation or under navigation with devices that utilize irrigation and suction to help maximize visibility during surgery. Similar to the above-described components of device **100**, blade **400** is configured to connect to the one or more surgical bone removal tools, e.g., the Medtronic Straightshot® M4 (or M5) and enables a surgeon to rapidly shave bone or tissue without thermal burn by rotating an inner tube **440** (shown in phantom) relative to a middle tube **430** and drawing debris through an inner lumen **443** defined in the inner tube **440** along a suction path “S” via a suction source **172** (FIG. **1**).

(19) More particularly, inner tube **440** is concentrically disposed within the middle tube **430** and includes an opening **445** at a distal end thereof. Distal cutting teeth **441** (shown in phantom) are disposed around the peripheral edge of the opening **445**. Inner tube **440** is configured to connect to a power source **162** (FIG. **1**) and is selectively activatable to rotate relative to middle tube **430**. Middle tube **430** is concentrically disposed within the outer tube **450** and includes an opening **435** defined at a distal end thereof. Distal cutting teeth **431** are disposed around the peripheral edge of the opening **435** of the middle tube **430**. Openings **445** and **435** are disposed in longitudinal registration relative to one another (i.e., in alignment along the longitudinal axis A-A defined through outer tube **450**) such that, upon rotation of the inner tube **440** relative to the middle tube **430**, tissue or bone disposed in the cutting window defined between the openings **435**, **445** is cut or shaved by the cooperating series of teeth **431**, **441** at a high speed.

(20) In one embodiment, irrigation fluid “F”, e.g., saline, is supplied from a fluid source, e.g., fluid source **152** of FIG. **1**, in a channel defined between the inner diameter of middle tube **430** and the outer diameter of inner tube **440** and to respective openings **435** and **445** thereof, such that upon rotation of the inner tube **440** relative to the middle tube **430**, the cooperating teeth **431**, **441** shave bone or tissue disposed within the openings **435**, **445** while suction from the suction source, e.g., suction source **172** of FIG. **1**, draws debris through the inner lumen **443** along the suction path “S”.

(21) As mentioned above, one of the advantages when using the prior art surgical bone removal tools, e.g., the Medtronic Straightshot® M4 (or M5) (hereinafter microdebrider **700** of FIG. **8**) is the ability to rotate the inner tube relative to the middle tube three-hundred sixty degrees (360°) to excise tissue and bone without rotating the outer tube **450**. This gives a surgeon a wide degree of flexibility when using a navigation system (hereinafter system **600**) in that any number of blades **400** having varying angles alpha “ α ” (FIG. **8**) can be attached to the microdebrider **700** and tissue or bone can be easily excised.

(22) More particularly, and with particular reference to FIG. **8**, microdebrider **700** may be configured to operably engage blade **400** having inner tube **440**, middle tube **430** and outer tube **450** and attach to an irrigation source **750** (FIG. **8**) and a suction source **172** (FIG. **1**) as described above. A rotation wheel **710** is disposed atop the housing **704** and configured to operably communicate with the inner and middle tubes **440**, **430** and is selectively rotatable in direction “R.sub.1” to permit 360° of selective rotation in direction “R.sub.2” of the cutting window between openings **445**, **435** of the inner and middle tubes **440**, **430**, respectively, without requiring reorientation of the microdebrider **700** in situ. In some embodiments, the rotation wheel **710** may be operably coupled to the middle tube **430**.

(23) The combination of the surgeon being able to initially determine the most efficient angle α for the blade **400** at the onset of the surgery (or selectively switch blades **400** as needed during surgery), the ability of the surgeon to rotate the cutting window between the inner and middle tubes **440**, **430** with the rotation wheel **710** without reorientation of the blade **400** in situ, and the use of the navigation system **600**, all enhance the surgeon's ability to perform the overall surgical procedure.

(24) When using navigation system **600** with prior art blades (not shown) configured to operably connect to the Medtronic Straightshot® M4 (or M5) having an angle α greater than forty degrees (40°), the stability of the middle tube and outer tube was unpredictable affecting the reliability of the navigation system **600**. The issue was exacerbated when using prior art blades with greater angles α and at different cutting window rotational positions “R.sub.1” due to the forces on the middle tube **430** and outer tube **450** interface associated with cutting tissue or bone in one rotational position, e.g., “R.sub.1”, versus at different rotational positions, e.g., “R.sub.2”.

(25) Turning briefly back to FIGS. **6** and **7**, which details the presently disclosed blade **400**, a distal end of the outer tube **450** is manufactured (e.g., roiled and reamed) to form an inner lip **451** configured to seat a bushing **500** thereagainst when middle tube **430** is inserted within the outer tube **450**. Although bushing **500** may take on many forms, in one embodiment, bushing **500** takes the form of a washer and includes an inner diameter that is configured to slide atop an outer surface **430a** of middle tube **430** in a tight, friction-fit manner. A shoulder **437** is machined or otherwise formed on the outer surface **430a** of the middle tube **430** and is configured to seat a proximal facing surface **502a** of the bushing **500** thereagainst. When the middle tube **430** is inserted within the outer tube **450**, a distal facing surface **502b** of bushing **500** abuts the inner lip **451** while the proximal facing surface **502b** is maintained by the shoulder **437** of middle tube **430** thereagainst. As can be appreciated, bushing **500** enhances the interface between the outer tube **450** and the middle tube **430**. It is contemplated that bushing **500** enhances the middle tube **430** and outer tube **450** interface such that blades **400** having angles α up to about 90° remain reliable without affecting the stability of navigation system **600**. Moreover, the bushing **500** is configured to maintain the stability of the interface between the outer tube **450** and the middle tube **430** when the rotating wheel **710** is rotated to reorient the cutting window between openings **435**, **445** to position, e.g., “R.sub.2”, wherein the cutting forces associated with thick tissue or bone may be higher than with a different position, e.g., “R.sub.1”.

(26) It is contemplated that bushing **500** may be made from any suitable type of material, such as a polymer, and may be of varying thicknesses, lengths and diameters to enhance the stability between tubes **450**, **430**, blade **400** or microdebrider **700**.

(27) While several aspects of the disclosure have been shown in the drawings, it is not intended that the disclosure be limited thereto, as it is intended that the disclosure be as broad in scope as the art will allow and that the specification be read likewise. Therefore, the above description should not be construed as limiting, but merely as exemplifications of particular configurations. Those skilled in the art will envision other modifications within the scope and spirit of the claims appended hereto.

(28) It will be understood that various modifications may be made to the aspects and features disclosed herein. Therefore, the above description should not be construed as limiting, but merely as exemplifications of various aspects and features. Those skilled in the art will envision other modifications within the scope and spirit of the claims appended hereto.

Claims

1. A device for removing tissue or bone, comprising: a housing having an outer tube extending therefrom including a longitudinal axis defined therealong, the outer tube including a distal end defining an inner lip on an inner periphery thereof; a middle tube operably supported concentrically

within the outer tube, the middle tube including an opening having a series of teeth at a distal end thereof and a shoulder defined around an outer peripheral surface thereof; an inner tube concentrically disposed within the middle tube including an opening having a series of teeth at a distal end thereof in longitudinal registration with the opening in the middle tube, the inner tube adapted to couple to a power source such that, upon activation thereof, the inner tube rotates relative to the middle tube and the series of teeth of the inner tube cooperates with the series of teeth of middle tube to cut tissue or bone disposed in a cutting window between the openings defined therebetween; and a bushing disposed on an outer surface of the middle tube in abutting relation against the shoulder, such that, upon assembly, the bushing seats in axial, abutting retention between the shoulder of the middle tube and the inner lip of the outer tube, the seating of the bushing in axial, abutting retention configured to maintain the stability of an interface between the outer tube and the middle tube when the cutting window between the openings is reoriented.

2. The device for removing tissue or bone according to claim 1, wherein the distal end is rolled and reamed to form the inner lip.

3. The device for removing tissue or bone according to claim 1, wherein the inner tube defines a lumen therethrough and extending therealong from the opening, a portion of the lumen adapted to connect to a suction source for eliminating cut tissue or bone.

4. The device for removing tissue or bone according to claim 1, wherein a channel is defined between the concentric inner and middle tubes along a length thereof for passing a fluid therealong from a fluid source.

5. The device for removing tissue or bone according to claim 1, further comprising a rotating wheel disposed atop the housing, the rotating wheel configured to permit selective 360° of rotation of the cutting window defined between respective openings of the middle and inner tubes without repositioning the outer tube.

6. A system for removing tissue or bone, comprising: a housing adapted to connect to a power source, a fluid source and a suction source, the housing including an adapter configured to operably connect to a selectively removable blade, the selectively removable blade having a blade angle of about 12° to about 90° and including: an outer tube extending therefrom including a longitudinal axis defined therealong, the outer tube including a distal end defining an inner lip on an inner periphery thereof; a middle tube operably supported concentrically within the outer tube, the middle tube including an opening having a series of teeth at a distal end thereof and a shoulder defined around an outer peripheral surface thereof; an inner tube concentrically disposed within the middle tube including an opening having a series of teeth at a distal end thereof in longitudinal registration with the opening in the middle tube, the inner tube adapted to couple to a power source such that, upon activation thereof, the inner tube rotates relative to the middle tube and the series of teeth of the inner tube cooperate with the series of teeth of middle tube to cut tissue or bone disposed in a cutting window defined in the openings defined therebetween; and a bushing disposed atop the middle tube in abutting relation against the shoulder, such that, upon assembly, the bushing seats in axial, abutting retention between the shoulder of the middle tube and the inner lip of the outer tube, the seating of the bushing in axial, abutting retention configured to maintain the stability of an interface between the outer tube and the middle tube when the cutting window between the openings is reoriented.

7. The system for removing tissue or bone according to claim 6, wherein the system is adapted to connect to a navigation system.

8. The system for removing tissue or bone according to claim 6, wherein the distal end of the outer tube is rolled and reamed to form the inner lip.

9. The system for removing tissue or bone according to claim 6, wherein the inner tube defines a lumen therethrough and extending therealong from the opening, a portion of the lumen adapted to connect to the suction source for eliminating cut tissue or bone.

10. The system for removing tissue or bone according to claim 6, wherein a channel is defined

between the concentric inner and middle tubes along a length thereof for passing a fluid therealong from the fluid source.

11. The system for removing tissue or bone according to claim 6, further comprising a rotating wheel disposed atop the housing, the rotating wheel configured to permit selective 360° of rotation of the cutting window defined between respective openings of the middle and inner tubes without repositioning the outer tube.
