

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415289
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Arkwright; Chris

Hand-held pipe edge beveler with vacuum adapter

Abstract

A beveler device is configured for removable attachment to a hand-held power unit and to simultaneously de-burr and bevel the raw cut edge of a PVC pipe. An adapter may be attached to the beveler device and connect a vacuum hose for suction of chips and debris into the interior of the beveler device and out through the vacuum hose during operation.

Inventors:	Arkwright; Chris (Erie, PA)
Applicant:	Arkwright; Chris (Erie, PA)
Family ID:	1000008821527
Assignee:	REED MANUFACTURING COMPANY (Erie, PA)
Appl. No.:	18/373038
Filed:	September 26, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250100172 A1	Mar. 27, 2025

Related U.S. Application Data

continuation-in-part parent-doc US 15487481 20170414 PENDING child-doc US 18373038

Publication Classification

Int. Cl.: B26D3/02 (20060101)

U.S. Cl.:

Field of Classification Search

CPC: B26D (3/02); B23C (1/20); B23Q (11/00); B27C (5/10)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4674548	12/1986	Mills	144/154.5	B23Q 11/0046
7290967	12/2006	Steimel	409/137	B23Q 11/0046
7971611	12/2010	Wells	144/286.5	B27C 5/02
8708624	12/2013	Marusiak	144/136.95	B27G 21/00
D826496	12/2017	Witter	D32/31	N/A
10189134	12/2018	Brigolin	N/A	B23Q 11/0046
10449689	12/2018	Firth	N/A	B25F 5/021
10603754	12/2019	Witter et al.	N/A	B23Q 11/0071
2002/0168241	12/2001	David	409/178	B23Q 9/0042
2002/0182023	12/2001	Lai	409/137	B23Q 5/06
2008/0156396	12/2007	Cooper	144/136.95	B25F 5/02
2010/0089497	12/2009	Keenan	144/252.1	N/A
2013/0051951	12/2012	Friegang	409/137	B27C 5/10
2016/0250731	12/2015	Wong	408/56	B25F 5/026
2017/0197286	12/2016	Sheldon	N/A	A46B 15/0053
2024/0100641	12/2023	Limberg	N/A	B23Q 11/0071
2024/0100732	12/2023	Roloff	N/A	B27C 5/10
2025/0091192	12/2024	Lauer	N/A	B27C 5/10

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102017203278	12/2017	DE	N/A

Primary Examiner: Sanchez; Omar Flores

Attorney, Agent or Firm: Bauer & Joseph

Background/Summary

PRIORITY CLAIM (1) This application is a continuation-in-part of U.S. patent application Ser. No. 15/487,481 filed on Apr. 14, 2017, which is hereby incorporated by reference in its entirety.

FIELD OF THE INVENTION

(1) The present invention is directed to the field of hand tools. More particularly, the present invention is directed to a hand-held beveler attachment device for simultaneously de-burring and beveling the cut edge of a PVC pipe.

BACKGROUND

(2) PVC pipes frequently have to be cut to various lengths and joined together at a worksite. It is frequently desirable to cleanly connect and cement one PVC pipe to an adjacent length of pipe,

elbow, etc. Cutting the end of a PVC pipe will typically leave a rough, burred edge around the periphery of the cut edge. If not removed, the burrs on the cut edge will interfere with a clean connection. The cut edge of a pipe is also sometimes beveled to further facilitate the clean connection to the adjacent length of pipe, elbow, etc. The pipes can be large in diameter or lengthy, making it difficult to handle the pipes so as to apply the cut edge of the pipe to a lathe or table saw for de-burring or making a bevel cut.

BRIEF SUMMARY

(3) It is among the objects of the preferred embodiments of the present invention to provide a hand-held pipe edge beveler attachment that facilitates the simultaneous de-burring and beveling of the cut edge of a PVC pipe of 2" diameter and larger. Another one of the objects of the preferred embodiments is the ability to make various adjustable bevel cuts to the cut edge of the PVC pipe. Another object of the preferred embodiments is to manage the dust, small chips and debris that result when the cut edge of the PVC pipe is de-burred and beveled. It is another object that the preferred embodiments that they are configured to attach to a variety of readily available hand-held power units so that they can be used to simultaneously de-burr and bevel the cut edge of a PVC pipe, even when the pipe is large, lengthy or cannot be moved. While it is conceivable that other power units could effectively be used with the beveler attachment of the preferred embodiments of the present invention, the Bosch 18v cordless die grinder with a 4.0 amp-hour-lithium-ion battery has proven to be a highly effective drive source for this attachment device.

(4) Various other features, advantages, and characteristics of the preferred embodiments will become apparent after a reading of the following detailed description.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The preferred embodiments of the present invention are described in conjunction with the associated drawings in which like features are indicated with like reference numerals and in which
- (2) FIG. 1 is a frontal perspective view of a first preferred embodiment of the beveler attachment connected to a power unit;
- (3) FIG. 2 is an exploded view of the first preferred embodiment of the beveler attachment;
- (4) FIG. 3 is a front view of a partial assembly of the first preferred embodiment of the beveler attachment;
- (5) FIG. 4 is a cross-sectional front view of the fully assembled first preferred embodiment of the beveler attachment;
- (6) FIG. 5 is a frontal perspective view of a vacuum adapter for the beveler attachment;
- (7) FIG. 6 shows an exemplary operation of a second preferred embodiment of the beveler with the vacuum adapter installed and connected to a vacuum hose;
- (8) FIG. 7 is an exploded view of the vacuum adapter; and
- (9) FIG. 8 shows a frontal perspective view of the second preferred embodiment with the vacuum adapter.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

(10) A first embodiment of the cordless hand-held pipe edge beveler attachment of the present invention is depicted in FIGS. 1-2 generally at **20**. The hand-held beveler attachment **20** of the present invention includes router bit **22** which is received in chuck **19** of hand-held power unit **11**. While other power units may be used, it is preferred that power unit **11** comprise a Bosch 18v cordless die grinder. When the Bosch grinder is used, a 4.0 amp-hour-lithium-ion battery and charger **13** is used in conjunction therewith.

(11) As best seen in FIG. 2, adaptor **32** has a lateral saw cut **33** as well as a vertical saw cut (not shown) forming two annular fingers **36** (one shown). Screw **76** is inserted from the back side (as

seen in FIG. 2) threading into hole 35 drawing annular fingers 36 together, thereby clamping adaptor 32 onto collar 15 of hand-held grinder 11. The top of adaptor 32 has three slots 38 (two shown) in the upper rim for reasons to be enumerated shortly.

(12) Adjusting ring 42 which slides over adaptor 32, has elliptical openings 48 which align with slots 38 allowing chips and debris to be centrifugally or gravitationally expelled from the adaptor 20 as they are formed during the beveling process. As best seen in FIGS. 1 and 4, adjusting ring 42 has an elongated slot 45 which allows its axial movement along the primary axis of the grinder 11.

(13) Shroud 52 fits inside the inner periphery of adjusting ring 42 and protruding annular bottom flange 54 is seated on an inwardly directed flange 44 of adjusting ring 42. The shroud is less than a complete circle, but more than 180 degrees of a circle. While seated and fixed in the vertical direction, shroud 52 can freely rotate about the axis of rotation of the router bit 22. A hole 64 in guide plate 62 encircles shroud 52 allowing guide plate 62 to sit atop and be secured to the upper rim of adjusting ring 42 by three (two shown) flat head screws 70.

(14) To mount the beveler attachment 20 to the power unit 11, the router bit 22 is secured in chuck 19 with the distance d1, i.e., the distance the bottom of bit 22 is from the top of the chuck 19, being in the range from 3/16" to 1/4". Adaptor 32 is then secured to the power unit with the distance d2, i.e., the distance the upper rim thereof is below the bottom of bit 22, being 1/2", as shown in FIG. 3. The remaining elements are attached seriatim and adjustment screw 74 inserted through plate washer 72 and threaded into hole 34. When positioning adaptor 32 on the power unit 11, care must be taken to position hole 34 at a 90 degree counterclockwise from on-off switch 17.

(15) In use, the size of the 15 degree bevel can be adjusted from 0" to 5/8" on pipe sizes 2" in diameter and larger. Adjustment is made by loosening adjustment screw 74 and moving the bevel unit to adjust the amount of router bit 22 extending above the adjustment plate 62 to the amount desired.

(16) A second preferred embodiment is depicted in FIGS. 7-8. It is similar to the first preferred embodiment, but includes an additional vacuum adapter, indicated generally at 80 and shown in FIG. 5. The vacuum adapter 80 of the second preferred embodiments includes a vacuum box 81 with a hose connector 82 at the front face thereof. Vacuum box 81 has no rear face. The top surface 83 and bottom surface (not shown) each has a partial circular cut-out from the rear portion thereof as shown in FIG. 5, the arc of the cut-out matching the arc of the circular exterior surface of adjusting ring 42 so that there is an air-tight fit between vacuum box 81 and adjusting ring 42. The vacuum box 81 has a width, from one side surface 84 to the other, that is slightly greater than the width of the three elliptical openings 48 in adjusting ring 42.

(17) The vacuum box is aligned with one of the three elliptical openings 48 by vacuum band element 85. The vacuum band element 85 has a circular ring portion 86 that fits around the part of the circular exterior of the adjusting ring 42 that is not abutted by vacuum box 81 and two flat strap portions 87 connected to the sides of the hose connecting element 81 by screws 88. When the screws 88 are completely tightened, the vacuum box 81 and vacuum band element 85 are secured into place on the exterior of adjusting ring 42. The circular ring portion 86 has three half-circle shaped cutouts 89 located and sized to accommodate the dimensions of the flat washer 72 and adjustment screw 74 as they are moved in elongated slot 45. This arrangement allows the vacuum box 81 to be located immediately adjacent to any one of the elliptical openings 48 in adjusting ring. When the vacuum box 81 is immediately adjacent to one of the elliptical openings 48, the other two elliptical openings 48 are covered up by circular ring portion 86 of vacuum adapter 80.

(18) FIG. 6 shows an exemplary operation of the second preferred embodiment. A vacuum hose 90, is connected to the hose connector 82 of the vacuum adapter 80. A vacuum (not shown) at the other end of vacuum hose 90 provides suction to create an airflow from the router bit 22 through the hole 64 in guide plate, down into the interior of the beveler attachment, out the slot 38 in adapter 32 and the elliptical opening 48 aligned with the hose connecting element 81 (which is preferably substantially hollow), and into vacuum hose 90. The router bit 22 of the beveler attachment is

guided into contact with the cut edge of PVC pipe **100** at a perpendicular angle with the assistance of shroud **52** and guide plate **62**. The airflow conveniently collects the dust, chips and debris creating when de-burring and beveling the cut edge of PVC pipe **100** into the vacuum. The operator is able to keep both hands on the beveler attachment and/or power unit as shown in FIG. **6**.

(19) Various changes, alternatives, and modifications will become apparent to a person of ordinary skill in the art after a reading of the foregoing specification. It is intended that all such changes, alternatives, and modification as fall within the scope of the appended claims be considered part of the present invention.

Claims

1. A beveler device, comprising: an adapter configured to removably attach the beveler device to a hand-held power tool operable to rotate a bit about an axis of rotation, to simultaneously de-burr and bevel a cut edge of a plastic pipe when engaged with said cut edge; an adjustment ring, the adjustment ring configured to fit over and be connected to the adaptor and including a slot, wherein a connection of the adjustment ring to the adaptor through the slot determines the position of the adjustment ring in the direction parallel to the axis of rotation of the bit; a guide plate, the guide plate configured so that the face of the guide plate lies in a plane perpendicular to the axis of rotation, the bit partially protruding from a hole in the center of the guide plate, the amount of said bit protruding from the hole in the center of said guide plate being adjusted by loosening an adjustment screw and manually adjusting the location of said guide plate along the axis of rotation of the bit; and a vacuum attachment, said vacuum attachment being removably attached to said beveler device and connecting a vacuum hose to suck chips and debris through the hole in the center of the guide plate, the interior of said adjustment ring, and out through the vacuum hose.
2. The beveler device of claim 1, further comprising a shroud seated atop an upper rim of said adaptor, fitting within said adjustment ring, and protruding through the hole in the guide plate.
3. The beveler device of claim 2, wherein the shroud is retained in a fixed position in the direction parallel to the axis of rotation by said upper rim of said adaptor and said guide plate.
4. The beveler device of claim 1, wherein the adaptor is ring shaped and has a plurality of slots in the upper rim of the adaptor periphery.
5. The beveler device of claim 4, wherein there are a plurality of openings in the periphery of the adjustment ring, and the plurality of slots in the periphery of the adaptor align with the plurality of openings in the periphery of the adjustment ring.
6. The beveler device of claim 1, wherein the adaptor has a lateral saw cut and a vertical saw cut forming two annular fingers.
7. The beveler device of claim 6, wherein the adaptor further comprises a threaded hole, whereby the adaptor is clamped to the collar of the hand-held power tool by a screw inserted into the threaded hole drawing the annular fingers together.
8. A beveler device, comprising: an adaptor, said adaptor configured to attach said beveler device to a hand-held power tool, the hand-held power tool configured to receive, secure and rotate a working tool about an axis of rotation; an adjustment ring, the adjustment ring configured to fit over the adaptor and including an adjustment slot having a length extending in a direction parallel to the axis of rotation and a width extending in a direction perpendicular to the axis of rotation; an adjustment screw, the adjustment screw having a diameter smaller than the width of the adjustment slot in the adjustment ring and fitting into a threaded hole of the adaptor and, when tightened, the adjustment screw connects the adjustment ring to the adaptor; a guide plate having a flat face and attached to the adjustment ring so that the flat face of the guide plate lies in a plane perpendicular to the axis of rotation, the guide plate having a hole centered on the axis of rotation; and a shroud, fitting within and directly abutting said adjustment ring, and protruding through the hole in the

guide plate, wherein the position of said flat face of said guide plate relative to the hand-held power tool and a working tool secured in the power tool in the direction of the axis of rotation is determined by the position of the adjustment screw along the length of the adjustment slot in the adjustment ring when the adjustment screw is tightened.

9. The beveler device of claim 8, wherein the shroud is retained in a fixed position in the direction parallel to the axis of rotation.

10. The beveler device of claim 9, wherein the shroud is not attached to any part of the beveler attachment.

11. The beveler device of claim 8, wherein the adjustment ring has a plurality of openings in addition to the adjustment slot.

12. The beveler device of claim 11, wherein the plurality of openings in the adjustment ring align with a plurality of openings in the adaptor.
