

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416877
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Sakurai; Yuuta

Exposure device and image forming apparatus

Abstract

An exposure device that exposes a photoconductor, includes a substrate having one surface on which a plurality of light emitting elements is mounted and the other surface on which a contact is provided, a lens array that condenses light emitted from the light emitting elements on the photoconductor, a metal housing that has a lens support portion that supports the lens array, a first substrate support portion supports one end side of the substrate in a lateral direction, and a second substrate support portion supports the other end side of the substrate in the lateral direction, and a conductive member that has a first conductive portion in contact with the contact and a second conductive portion in contact with a surface of the first substrate support portion that supports the substrate, and allows conduction between the substrate and the metal housing.

Inventors:	Sakurai; Yuuta (Chiba, JP)
Applicant:	CANON KABUSHIKI KAISHA (Tokyo, JP)
Family ID:	1000008821629
Assignee:	CANON KABUSHIKI KAISHA (Tokyo, JP)
Appl. No.:	18/731748
Filed:	June 03, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240419094 A1	Dec. 19, 2024

Foreign Application Priority Data

JP	2023-098334	Jun. 15, 2023
----	-------------	---------------

Publication Classification

Int. Cl.: G03G15/04 (20060101); G03G15/043 (20060101); G03G21/16 (20060101)

U.S. Cl.:

CPC G03G15/04036 (20130101); G03G15/0435 (20130101); G03G21/1652 (20130101);

Field of Classification Search

CPC: G03G (15/04036); G03G (15/0435); G03G (21/1652)

USPC: 399/177; 399/218

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6809752	12/2003	Nagamine	N/A	N/A
9217946	12/2014	Okazaki	N/A	G03G 15/04054

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1325521	12/2009	TW	N/A

Primary Examiner: Tran; Hoan H

Attorney, Agent or Firm: ROSSI, KIMMS & McDOWELL LLP

Background/Summary

BACKGROUND OF THE INVENTION

Field of the Invention

(1) The present invention relates to an exposure device including a light emitting element that exposes a photoconductor and an image forming apparatus including the exposure device.

Description of the Related Art

(2) In an electrophotographic-system image forming apparatus, there is a solid exposure head as one of exposure devices including a light emitting element that exposes a photoconductive drum. The solid exposure head includes, as a light emitting element, a light emitting diode (LED), or an organic electro luminescence (EL) element.

(3) In the above exposure head, a substrate on which a plurality of light emitting elements arranged in a main scanning direction is mounted and a lens that condenses light emitted from the light emitting element on a photoconductive drum are held by a holder. A resin is used as a material of the holder, and a metal may be used to reduce deformation due to heat generated by light emission of the light emitting element.

(4) It is necessary to ground the substrate on which the light emitting element is provided in order to reduce the generation of noise. U.S. Pat. No. 6,809,752 discloses a configuration in which a conductive base that supports a substrate and the outside of a metallic holder are electrically connected via a clamp to ground the substrate.

(5) Incidentally, in an image forming apparatus using a solid exposure head, downsizing in the lateral direction of a substrate may be required depending on a positional relationship with

components existing around the exposure head. In the case of a configuration in which the outside of the holder is clamped as in U.S. Pat. No. 6,809,752, there is a possibility that the size of the exposure head in a substrate lateral direction will be increased. In view of the above problems, it is desirable to provide an exposure head that electrically connects a substrate and a holder while curbing a possibility of an increase in size of the exposure head in a lateral direction of the substrate.

SUMMARY OF THE INVENTION

(6) A representative configuration of the present invention is an exposure device that exposes a photoconductor, the exposure device including a substrate that has a longitudinal shape extending in an axis direction of the photoconductor, the substrate having one surface on which a plurality of light emitting elements arranged in a longitudinal direction of the substrate is mounted and the other surface on which a contact is provided; a lens array that condenses light emitted from the light emitting elements on the photoconductor; a metal housing that has a lens support portion that supports the lens array, a first substrate support portion that extends from the lens support portion in a direction away from the photoconductor and supports one end side of the substrate in a lateral direction, and a second substrate support portion that extends from the lens support portion in a direction away from the photoconductor and supports the other end side of the substrate in the lateral direction; and a conductive member that has a first conductive portion in contact with the contact and a second conductive portion in contact with a surface of the first substrate support portion that supports the substrate, and allows conduction between the substrate and the metal housing.

(7) Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic cross-sectional view of an image forming apparatus;
- (2) FIG. 2 is a schematic cross-sectional view of an exposure head;
- (3) FIG. 3 is a perspective view of the exposure head;
- (4) FIG. 4 is a perspective view of the exposure head;
- (5) FIG. 5 is a cross-sectional view of a ground configuration of an exposure head according to a first embodiment;
- (6) FIG. 6 is a cross-sectional view of a ground configuration of an exposure head according to a second embodiment;
- (7) FIG. 7 is a cross-sectional view of a ground configuration of the exposure head according to the second embodiment; and
- (8) FIG. 8 is a cross-sectional view of a ground configuration of the exposure head according to the first embodiment.

DESCRIPTION OF THE EMBODIMENTS

(9) Hereinafter, embodiments of the present invention will be exemplarily described in detail with reference to the drawings. Note that dimensions, materials, shapes, relative arrangements, and the like of the components described below are merely examples, and the scope of the present invention is not intended to be limited thereto.

First Embodiment

(10) (Image Forming Apparatus)

(11) First, a schematic configuration of an image forming apparatus will be described with reference to FIG. 1. FIG. 1 is a schematic cross-sectional view of an image forming apparatus.

(12) The image forming apparatus illustrated in FIG. 1 includes four image forming portions 102Y,

102M, **102C**, and **102K** that form toner images of respective colors of yellow (Y), magenta (M), cyan (C), and black (K). The image forming portions **102Y**, **102M**, **102C**, and **102K** include photoconductive drums (photoconductors) **103Y**, **103M**, **103C**, and **103K**, respectively. Chargers **104Y**, **104M**, **104C**, and **104K**, exposure devices **105Y**, **105M**, **105C**, and **105K**, and development devices **106Y**, **106M**, **106C**, and **106K** are provided around the photoconductive drum. Note that Y, M, C, and K appended to the reference numerals indicate the colors of the toner.

(13) Hereinafter, the photoconductive drums **103Y**, **103M**, **103C**, and **103K** will also be collectively referred to as simply “photoconductive drums **103**”. The exposure devices **105Y**, **105M**, **105C**, and **105K** that expose the photoconductive drums **103Y**, **103M**, **103C**, and **103K** will also be collectively and simply referred to as “exposure devices **105**”.

(14) (Image Forming Process)

(15) Next, an image forming process of the image forming apparatus will be briefly described.

(16) The photoconductive drums **103Y**, **103M**, **103C**, and **103K** uniformly charged by the chargers **104Y**, **104M**, **104C**, and **104K** are exposed by the exposure devices **105Y**, **105M**, **105C**, and **105K**, and electrostatic latent images are formed. The electrostatic latent images are developed as toner images of the respective colors by the development devices **106Y**, **106M**, **106C**, and **106K**. The toner images of the respective colors are sequentially transferred to be superimposed on an intermediate transfer belt **107** by primary transfer rollers **108Y**, **108M**, **108C**, and **108K** at primary transfer portions Ty, Tm, Tc, and Tk.

(17) The toner images of the respective colors superimposed on the intermediate transfer belt **107** are collectively transferred by a secondary transfer roller **109** onto a recording sheet P conveyed from a sheet feeder **101** at a secondary transfer portion T2. The recording sheet P to which the toner images have been transferred is conveyed to a fixing device **110**, and after the toner images are fixed by heat and pressure, the recording sheet P is discharged from a sheet discharge portion **111**.

(18) In the following description, a rotational axis direction of the photoconductive drum **103** coincides with a front-rear direction (near-far direction) of the image forming apparatus, and the near side in FIG. 1 is defined as being in a front direction and the far side is defined as being in a rear direction. The longitudinal direction of the exposure device **105** is also a direction coinciding with the front-rear direction of the image forming apparatus. That is, the rotational axis direction of the photoconductive drum **103** coincides with the longitudinal direction of the exposure device **105**. One end side of the photoconductive drum **103** in the rotational axis direction is the front side (near side) defined herein, and the other end side means the rear side (far side) defined herein. One end side and the other end side of the image forming apparatus in the front-rear direction also correspond to the near side and the far side defined here.

(19) When the photoconductive drum **103K** on which an electrostatic latent image related to a black (K) toner image is formed is used as a reference, a side on which the photoconductive drum **103Y** on which an electrostatic latent image related to a yellow (Y) toner image is formed is disposed is defined as a left side. When the photoconductive drum **103Y** on which an electrostatic latent image related to a yellow toner image is formed is used as a reference, a side on which the photoconductive drum **103K** on which an electrostatic latent image related to a black toner image is formed is disposed is defined as a right side. An upward side in a direction orthogonal to the front-rear direction and the left-right direction defined here is defined as an up direction, and a downward side in a direction orthogonal to the front-rear direction and the left-right direction defined here is defined as a down direction. The defined front direction F, rear direction B, left direction L, right direction R, up direction U, and down direction D are illustrated in FIGS. 2 and 3.

(20) (Exposure Head)

(21) The exposure device **105** includes an exposure head **501** described below. The exposure head **501** will be described with reference to FIGS. 2, 3, and 4. FIG. 2 is a schematic cross-sectional view of the exposure head. FIGS. 3 and 4 are perspective views of the exposure head.

(22) The exposure head **501** has an elongated shape (longitudinal shape) extending in the axis

direction of the photoconductive drum **103**. The exposure head **501** includes a substrate **502**, a light emitting element, a lens array **506**, and a metal housing **505** that holds the substrate **502** and the lens array **506**.

(23) Note that the exposure head **501** includes a light emitting diode (LED) **503** that is a light emitting diode as a light emitting element, but is not limited thereto. For example, an organic light emitting diode (OLED) may be used. This OLED is also called an organic electro-luminescence (EL) element, and is a current-driven light emitting element.

(24) The substrate **502** has a longitudinal shape extending in the axis direction (front-rear direction) of the photoconductive drum **103**.

(25) On one surface of the substrate **502**, a plurality of LED chips on which a plurality of LEDs **503** (an example of a light emitting element) is arranged is mounted side by side in a main scanning direction (the rotational axis direction of the photoconductive drum). One surface of the substrate **502** described here is a surface (a top surface or a front surface) on which the LED chip (LED **503**) is mounted, and is a surface facing the lens array **506**.

(26) The lens array **506** condenses light emitted from the light emitting element on the photoconductive drum **103**. The lens array **506** is a lens assembly including a plurality of lenses. The plurality of lenses is arranged in the arrangement direction of the plurality of LEDs **503**. Each lens is a cylindrical rod lens made of glass, and has a light incident surface **506a** to which the light emitted from the LED **503** is incident and a light emitting surface **506b** from which the light incident from the light incident surface **506a** is emitted. A material of the lens is not limited to glass, and may be plastic. A shape of the lens is not limited to a cylindrical shape, and may be, for example, a polygonal prism shape such as a hexagonal prism shape.

(27) The metal housing **505** holds the substrate **502** on which a plurality of LED chips is mounted side by side in the main scanning direction (rotational axis direction of the photoconductive drum) and the lens array **506** in which a plurality of cylindrical refractive index distribution type lenses is arranged side by side in the main scanning direction. The metal housing **505** holds the substrate **502** and the lens array **506** such that the LED **503** on the substrate **502** and the lens array **506** face each other. A material of the metal housing **505** is a plate material obtained by plating a galvanized steel plate or a cold-rolled steel plate later.

(28) The lens array **506** forms an image of the light flux emitted from the LED **503** on the photoconductive drum **103** as an equal-magnification erected image. In this case, a distance from the LED **503** to the light incident surface of the lens array **506** is substantially equal to a distance from the light emitting surface of the lens array **506** to the front surface of the photoconductive drum **103**.

(29) A distance between the LED **503** and the light incident surface of the lens array **506** is required to have high accuracy on the order of microns, and this distance is strictly adjusted. The substrate **502** is moved and adjusted to a predetermined position with respect to the metal housing **505** and fixed with an adhesive **507**, and the lens array **506** is adjusted in position with respect to the LED **503** on the substrate **502** and fixed to the metal housing **505** with the adhesive **507**. In the present embodiment, an LED is used as a light emitting element (solid light source), and the substrate **502**, the lens array **506**, and the metal housing **505** that are integrally unitized are referred to as the exposure head **501**.

(30) When the lens array **506** is deformed, a direction of light after passing through the lens changes, and thus, for example, an image defect such as color deviation occurs. Therefore, the metal housing **505** that holds the lens array **506** needs to curb deformation caused by heat. Therefore, in order to dissipate heat from the metal housing **505**, a material of the housing **505** in the exposure head **501** is a metal in the present embodiment.

(31) (Metal Housing)

(32) The metal housing **505** will be described. As illustrated in FIG. 2, the metal housing **505** holds the lens array **506** and the substrate **502** as described above. In the present embodiment, the metal

housing **505** is a metal member formed by bending a plate material obtained by plating a galvanized steel plate or a cold-rolled steel plate. In the present embodiment, the metal housing **505** is formed by pressing a sheet metal such as an iron thin plate into a U shape. Hereinafter, a shape of the metal housing **505** will be described.

(33) As illustrated in FIG. 2, the metal housing **505** has a planar portion (opposite surface) **505U** in which a first opening **505a** into which the lens array **506** is inserted is formed. The planar portion **505U** is a lens support portion that supports the lens array **506**. The planar portion **505U** faces the photoconductive drum **103** in the optical axis direction of the lens of the lens array **506**. Note that the planar portion **505U** is not limited to a flat surface, and may be a slightly curved surface. The optical axis of the lens here is a line connecting the center of the light emitting surface of the lens to a focal point of the lens. The metal housing **505** has an extension portion (first substrate support portion) **505L** extending in a direction away from the photoconductive drum **103** from one side of the planar portion **505U** in the lateral direction. The metal housing **505** has an extension portion (second substrate support portion) **505R** extending in a direction away from the photoconductive drum **103** from the other side of the planar portion **505U** in the lateral direction.

(34) The extension portion **505L** and the extension portion **505R** form a substrate support portion that supports the substrate **502** inserted from a second opening **505b** in the metal housing **505**. The planar portion **505U** and the substrate support portions (extension portions **505L** and **505R**) are integrated to form the metal housing **505** that holds the lens array **506** and the substrate **502**, and a cross section thereof is formed in a substantially U shape. Since the metal housing **505** is formed in a substantially U shape, the second opening **505b** is formed on the side opposite to the planar portion **505U**. The second opening **505b** is formed between the substrate support portions (extension portions **505L** and **505R**) extending from the planar portion **505U** to the side away from the photoconductive drum.

(35) The substrate **502** is inserted from the second opening **505b**, that is, from the lower side of the U-shaped metal housing **505**, and is adhered to the inside of each substrate support portion (the inside of the extension portion **505L** and the inside of the extension portion **505R**) with the adhesive **507**. Here, the inside of the extension portion **505L** is a surface side of the extension portion **505L** facing the extension portion **505R**, and the inside of the extension portion **505R** is a surface side of the extension portion **505R** facing the extension portion **505L**. Since a position of the substrate **502** in a focusing direction is determined by a jig (not illustrated), the exposure head **501** does not include a positioning portion of the substrate **502** in the focusing direction.

(36) The lens array **506** is also adhered to the planar portion **505U** with the adhesive **507** in a state of being inserted into the first opening **505a** formed in the planar portion **505U**. Note that the lens array **506** is fixed to the planar portion **505U** after a position and an inclination thereof in the focusing direction are adjusted by a jig such that a distance in the focusing direction between all the LED chips (LEDs **503**) mounted on the substrate **502** and the lens array **506** has a predetermined value. The lens array **506** is fixed to the planar portion **505U** at a plurality of positions in the longitudinal direction with the adhesive **507**. That is, the exposure head **501** of the present embodiment has a plurality of adhesive locations for adhering and fixing the lens array **506** inserted into the first opening **505a** to the planar portion **505U** in the longitudinal direction of the planar portion **505U**.

(37) After the substrate **502** and the lens array **506** are positionally adjusted and fixed to the metal housing **505**, a gap between the substrate **502** inserted into the second opening **505b** and the metal housing **505** (extension portions **505L** and **505R**) is sealed over the longitudinal direction by a sealant **508** as illustrated in FIG. 2. As a result, the LED **503** can be prevented from being contaminated by toner and dust from the outside, and a possibility that light emitted from the LED **503** is blocked by dust can be reduced.

(38) Similarly, the sealant **508** is applied to a gap between the lens array **506** inserted into the first opening **505a** and the metal housing **505** (planar portion **505U**), and the gap is sealed by the sealant

508 over the longitudinal direction as illustrated in FIG. 2. As a result, it is possible to reduce a possibility that dust such as toner flows in from the gap between the side wall of the lens array 506 and the first opening 505a and the light emitted from the LED 503 is blocked by the dust.

(39) (Resin Housing)

(40) The exposure head 501 has a resin housing 510 that supports the metal housing 505. FIG. 4 is a perspective view illustrating a state in which the resin housing 510 is assembled to the exposure head 501. As illustrated in FIG. 4, the resin housing 510 supports the metal housing 505 holding the substrate 502 and the lens array 506 in the longitudinal direction, and is provided integrally with the metal housing 505. The resin housing 510 is a member having a longitudinal shape extending in the axis direction of the photoconductive drum 103. As illustrated in FIG. 5, the resin housing 510 is formed in a U shape in a direction opposite to that of the metal housing 505. The resin housing 510 has a left side wall 510L that is a first side wall, a right side wall 510R that is a second side wall facing the left side wall 510L, and a bottom surface portion 510D facing the planar portion 505U of the metal housing 505 between the left side wall 510L and the right side wall 510R.

(41) The resin housing 510 has a function of connecting the exposure head 501 to a unit (not illustrated) provided inside the main body of the image forming apparatus in a detachably attachable manner. As a unit (not illustrated) to which the exposure head 501 is connected in a detachably attachable manner, for example, there is a moving mechanism that moves the exposure head to an exposure position and a retraction position. The moving mechanism moves the exposure head to an exposure position where the photoconductive drum is exposed, and moves the exposure head to a retraction position retracted from the exposure position.

(42) (Ground Configuration)

(43) Next, a ground configuration of the exposure head will be described with reference to FIG. 5. FIG. 5 is a cross-sectional view of a ground configuration of the exposure head according to the first embodiment.

(44) A conductive portion 509 as a contact is provided on the other surface of the substrate opposite to the one surface on which the LED 503 is mounted. The conductive portion 509 is provided to protrude toward a metal conductive member 701 side that will be described later from the opposite surface of the substrate 502 in the optical axis direction. In other words, the conductive portion 509 is attached to the opposite surface of the substrate 502, and has a height protruding closer to the metal conductive member 701 that will be described later in the optical axis direction than the opposite surface. Specifically, as illustrated in FIG. 8, the conductive portion 509 has a contact surface 509a serving as a contact in contact with the conductive member 701. The contact surface 509a is provided at an end portion of the conductive portion 509 farthest from the other surface of the substrate 502. The conductive portion 509 is a protrusion protruding from the other surface of the substrate 502 in a direction away from the lens array 506, and is a metal member having a height (protrusion amount h) in the optical axis direction of the lens. Since high accuracy is required for the protrusion amount h from the other surface of the substrate 502, the conductive portion 509 is provided separately from the substrate 502 and is configured to be attached to the other surface of the substrate 502. As a result, when the gap between the substrate 502 and the metal housing 505 is sealed with the sealant 508, the contact surface (contact) 509a of the conductive portion 509 can be prevented from being buried by the sealant 508, and stable conduction can be secured.

(45) The exposure head 501 includes a metal conductive member 701 that allows conduction between the substrate 502 and the metal housing 505. The metal conductive member 701 has a first conductive portion 701C, a second conductive portion 701L, and a third conductive portion 701R, and allows conduction between the substrate 502 and the metal housing 505.

(46) The first conductive portion 701C is biased in the first direction (up direction) and is in contact with the conductive portion 509 of the substrate 502 between the extension portion 505L and the

extension portion **505R**. The second conductive portion **701L** is biased on one side (left direction) of the second direction intersecting the first direction and is in contact with the inner surface of the extension portion **505L** of the metal housing **505** (the surface facing the extension portion **505R**). The third conductive portion **701R** is biased on the other side (right direction) opposite to the one side in the second direction and is in contact with the inner surface of the extension portion **505R** of the metal housing **505** (the surface facing the extension portion **505L**).

(47) In the present embodiment, the metal conductive member **701** is a plate spring in which the first conductive portion **701C**, the second conductive portion **701L**, and the third conductive portion **701R** are integrally molded.

(48) In the exposure head **501**, the metal housing **505** is electrically grounded to the frame body of the image forming apparatus.

(49) According to the present embodiment, conduction is allowed between the conductive portion **509** provided on the surface of the substrate **502** opposite to the LED mounting surface and the metal housing **505** via the metal conductive member **701**. The ground configuration using the metal conductive member **701** is installed to prevent noise generated in the image forming apparatus from affecting the substrate **502** when the exposure head **501** is installed and operated in the image forming apparatus. With the above configuration, even if cut powder is generated due to sliding or the like when the metal conductive member **701** and the substrate **502** come into contact with each other, it is possible to curb the cut powder from being mixed between the LED **503** and the lens array **506**, and it is possible to curb the occurrence of adverse effects on an image such as white streaks.

(50) In the metal housing **505**, the gap between one end side of the substrate **502** in the lateral direction and the extension portion **505L** and the gap between the other end side of the substrate **502** in the lateral direction and the extension portion **505R** are sealed with the sealant **508** over the longitudinal direction of the substrate **502**. As a result, it is possible to further curb dust from being mixed between the LED **503** and the lens array **506**.

(51) The substrate **502** has two or more conductive portions **509** as the contacts. In the present embodiment, as illustrated in FIG. 4, the conductive portions **509** are provided at two locations such as one end portion (a position **801** surrounded by a dotted line) and the other end portion (a position **802** surrounded by a dotted line) in the longitudinal direction of the substrate.

(52) The metal conductive member **701** is disposed for each conductive portion **509** of the substrate **502**. In the present embodiment, as illustrated in FIG. 4, the metal conductive member **701** is provided at two locations such as one end portion (the position **801** surrounded by a dotted line) and the other end portion (the position **802** surrounded by a dotted line) in the longitudinal direction of the substrate.

(53) As described above, by electrically connecting the exposure head **501** to the ground at a plurality of locations of two or more locations, the stability of the substrate **502** against noise can be enhanced. However, the number of locations for electrically connecting the substrate **502** of the exposure head **501** and the metal housing **505** to the ground may be one or three or more, and may be appropriately set.

(54) The metal housing **505** of the exposure head **501** is supported by the resin housing **510**. The metal conductive member **701** is held by the bottom surface portion **510D** of the resin housing **510**.

(55) The metal conductive member **701** held by the resin housing **510** includes a plate spring in the present embodiment, and includes the first conductive portion **701C**, the second conductive portion **701L**, and the third conductive portion **701R** which are three arms. Among them, the first conductive portion **701C**, which is one arm, is biased in the first direction to be in contact with the conductive portion **509** of the substrate **502**, and the second conductive portion **701L** and the third conductive portion **701R**, which are two arms, are biased in the second direction intersecting the first direction to be in contact with the metal housing **505**. As a result, stable conduction between the substrate **502** and the metal housing **505** can be secured. The metal housing **505** is electrically

connected to the frame body of the image forming apparatus with the ground configuration (not illustrated), and the substrate **502** is connected to the ground. As a result, it is possible to prevent noise generated in the image forming apparatus from affecting the substrate **502**.

(56) In the metal conductive member **701**, the top portion of the first conductive portion **701C** (the contact portion with the substrate **502**) on the upper side in the up-down direction is provided above the top portions of the second conductive portion **701L** and the third conductive portion **701R** on the upper side in the up-down direction. In the second conductive portion **701L** and the third conductive portion **701R**, the contact portion with the metal conductive member **701** is provided below the top portion on the upper side in the up-down direction. The top portions on the upper side of the second conductive portion **701L** and the third conductive portion **701R** are provided closer to the inside than the contact portion in the left-right direction. Thus, by inserting the metal conductive member **701** upward from the second opening **505b** side of the metal housing **505**, each conductive portion of the metal conductive member **701** is biased to the substrate and the metal housing, and conduction can be achieved. Thus, the metal conductive member **701** can be easily assembled to the exposure head **501**, and can easily and reliably allow conduction between the substrate **502** and the metal housing **505**.

(57) When the resin housing **510** is assembled to the exposure head **501**, even if cut powder is generated in the metal conductive member **701** held by the resin housing **510** due to rubbing or the like occurring between the conductive portion **509** of the substrate **502** and the metal housing **505**, the cut powder is not likely to go around to the LED **503** side because the cut powder is generated on the opposite side of the LED mounting surface of the substrate **502**.

(58) As described above, according to the present embodiment, even if cut powder is generated due to sliding or the like when the metal conductive member and the substrate come into contact with each other, it is possible to curb the cut powder from being mixed between the light emitting element and the lens array, and it is possible to curb the occurrence of adverse effects on an image such as white streaks.

(59) Note that the metal conductive member **701** is not limited to the above configuration. The metal conductive member **701** may have at least a first conductive portion in contact with the conductive portion **509** of the substrate **502** and a second conductive portion in contact with the metal housing **505**, and may be configured to conduct the substrate **502** and the metal housing **505**.

Second Embodiment

(60) An exposure head according to a second embodiment will be described. Other configurations of the exposure head except for the ground configuration are similar to those of the above-described embodiment, and thus, description thereof will be omitted here.

(61) (Ground Configuration)

(62) A ground configuration of the exposure head according to the second embodiment will be described with reference to FIG. 6. FIG. 6 is a cross-sectional view of a ground configuration of the exposure head according to a second embodiment.

(63) In the above-described embodiment, the metal conductive member **701** includes one conductive member (plate spring) integrally including the first conductive portion **701C**, the second conductive portion **701L**, and the third conductive portion **701R**. That is, in the above-described embodiment, the metal conductive member **701** that is one conductive member achieves a ground configuration. However, the metal conductive member **701** is not limited thereto.

(64) As illustrated in FIG. 6, the metal conductive member **701** according to the present example includes a first conductive member **702** having a first conductive portion **701C** and a second conductive member **703** connected to the first conductive portion **701C** and integrally having a second conductive portion **701L** and a third conductive portion **701R**. That is, the metal conductive member according to the present embodiment differs from the metal conductive member according to the above-described embodiment in the number of components, and a plurality of conductive members achieves a ground configuration.

(65) The resin housing **510** holds the first conductive member **702** and the second conductive member **703**. The first conductive member **702** has the first conductive portion **702C** in contact with the substrate **502**. The first conductive member **702** is a compression spring. The second conductive member **703** integrally includes the second conductive portion **703L** and the third conductive portion **703R** in contact with the metal housing **505**. The second conductive member **703** is a plate spring in which the second conductive portion **703L** and the third conductive portion **703R** are integrally molded. The metal conductive member **701** according to the present embodiment has a configuration in which a compression spring that is the first conductive member **702** and a plate spring that is the second conductive member **703** connected to the compression spring are integrally provided.

(66) The first conductive member **702** and the second conductive member **703** are biased against the plate spring that is the second conductive member **703** by using the repulsive force of the compression coil spring that is the first conductive member **702**, so that stable conduction can be secured.

(67) Since the focal depth of the lens array **506** is shallow, the substrate **502** needs to curb positional variation in the optical axis direction after fixation on the order of microns. As in the first embodiment, in the biasing to the substrate **502** by the plate spring which is one conductive member, it is necessary to increase a length of the arm and decrease a spring constant in order to curb a variation in the biasing due to an irregular position, and thus space saving may be difficult. Therefore, in the present embodiment, a compression coil spring is used for the first conductive member **702** having the first conductive portion in contact with the substrate **502**. As a result, not only the same effects as those of the above-described embodiment can be achieved, but also the spring constant can be lowered and space saving can be realized.

(68) In the metal conductive member **701**, a portion of the first conductive portion **702C** included in the first conductive member **702** in contact with the conductive portion **509** is not limited to the arc shape illustrated in FIG. 6. For example, a portion of the first conductive portion **702C** included in the first conductive member **702** in contact with the conductive portion **509** may be a flat surface. Specifically, as illustrated in FIG. 7, the portion of the first conductive portion **702C** in contact with the conductive portion **509** may have a planar shape in the lateral direction (left-right direction in FIG. 7) of the substrate **502**. As a result, stable conduction can be secured.

(69) While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

(70) This application claims the benefit of Japanese Patent Application No. 2023-098334, filed Jun. 15, 2023, which is hereby incorporated by reference herein in its entirety.

Claims

1. An exposure device that exposes a photoconductor, the exposure device comprising: a substrate that has a longitudinal shape extending in an axis direction of the photoconductor, the substrate having one surface on which a plurality of light emitting elements arranged in a longitudinal direction of the substrate is mounted and the other surface on which a contact is provided; a lens array that condenses light emitted from the light emitting elements on the photoconductor; a metal housing that has a lens support portion that supports the lens array, a first substrate support portion that extends from the lens support portion in a direction away from the photoconductor and supports one end side of the substrate in a lateral direction, and a second substrate support portion that extends from the lens support portion in a direction away from the photoconductor and supports the other end side of the substrate in the lateral direction; and a conductive member that has a first conductive portion in contact with the contact and a second conductive portion in contact

with a surface of the first substrate support portion that supports the substrate, and allows conduction between the substrate and the metal housing.

2. The exposure device according to claim 1, wherein the first conductive portion is biased toward the contact in a first direction that is an optical axis direction of the lens, and the second conductive portion is biased toward the first substrate support portion in a second direction orthogonal to the longitudinal direction and the first direction.

3. The exposure device according to claim 2, wherein the conductive member includes a first conductive portion that is biased in the first direction and is in contact with the contact of the substrate between the first substrate support portion and the second substrate support portion, the second conductive portion, and a third conductive portion that is in contact with a surface of the second substrate support portion that supports the substrate.

4. The exposure device according to claim 3, wherein the conductive member is a single conductive member integrally including the first conductive portion, the second conductive portion, and the third conductive portion.

5. The exposure device according to claim 4, wherein the single conductive member is a plate spring.

6. The exposure device according to claim 3, wherein the conductive member includes a first conductive member having the first conductive portion, and a second conductive member connected to the first conductive portion and integrally having the second conductive portion and the third conductive portion.

7. The exposure device according to claim 6, wherein the first conductive member is a compression spring, and the second conductive member is a plate spring.

8. The exposure device according to claim 1, wherein the metal housing is sealed with a sealant over the longitudinal direction of the substrate between the one end side of the substrate in the lateral direction and the first substrate support portion and between the other end side of the substrate in the lateral direction and the second substrate support portion.

9. The exposure device according to claim 1, wherein the exposure device has a resin housing that supports the metal housing, and the conductive member is held by the resin housing.

10. The exposure device according to claim 1, wherein the substrate has two or more of the contacts, and the conductive member is disposed at each of the contacts of the substrate.

11. The exposure device according to claim 1, further comprising a protrusion provided on the other surface of the substrate and protruding from the other surface of the substrate in a direction away from the lens, wherein the contact is provided at an end portion of the protrusion farthest from the substrate.

12. The exposure device according to claim 11, wherein the protrusion is a metal member having a height in an optical axis direction of the lens.

13. The exposure device according to claim 12, wherein the metal housing is sealed with a sealant over the longitudinal direction of the substrate between the one end side of the substrate in the lateral direction and the first substrate support portion and between the other end side of the substrate in the lateral direction and the second substrate support portion, and the sealant is not adhered to the end portion of the protrusion.

14. An image forming apparatus comprising: a photoconductor; and the exposure device according to claim 1.

15. The image forming apparatus according to claim 14, wherein the plurality of light emitting elements is organic EL elements.

16. The exposure device according to claim 1, wherein the plurality of light emitting elements is organic EL elements.
