

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12417586
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Sodagar; Iraj

Method for streaming dynamic 5G AR/MR experience to 5G devices with updatable scenes

Abstract

A method is provided. The method includes selecting media content including a full scene description, selecting a 5.sup.th generation (5G) media streaming downlink (5GMSd) application server (AS) to stream the media content based on the full scene description, deriving a simplified scene description based on the full scene description, and creating an augmented reality (AR)/mixed reality (MR) session based on the simplified scene description.

Inventors:	Sodagar; Iraj (Los Angeles, CA)
Applicant:	TENCENT AMERICA LLC (Palo Alto, CA)
Family ID:	1000008821631
Assignee:	TENCENT AMERICA LLC (Palo Alto, CA)
Appl. No.:	18/771459
Filed:	July 12, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240371103 A1	Nov. 07, 2024

Related U.S. Application Data

continuation parent-doc US 17705905 20220328 US 12045940 child-doc US 18771459
us-provisional-application US 63275358 20211103

Publication Classification

Int. Cl.: G06T19/00 (20110101); G06V20/00 (20220101); H04L65/60 (20220101); H04L65/75 (20220101); H04L67/00 (20220101); H04L67/131 (20220101); H04L67/14 (20220101); H04L67/2866 (20220101); H04L67/50 (20220101); H04W4/06 (20090101)

U.S. Cl.:

CPC G06T19/003 (20130101); G06T19/006 (20130101); G06V20/35 (20220101); H04L65/60 (20130101); H04L65/75 (20220501); H04L67/131 (20220501); H04L67/14 (20130101); H04L67/2866 (20130101); H04L67/34 (20130101); H04L67/50 (20220501); H04W4/06 (20130101);

Field of Classification Search

CPC: G06T (19/003); G06T (19/006); G06T (2210/08); G06V (20/35); H04L (65/60); H04L (65/75); H04L (67/131); H04L (67/14); H04L (67/2866); H04L (67/34); H04L (67/50); H04L (65/1059); H04L (65/1063); H04L (67/02); H04L (65/612); H04L (65/613); H04L (65/80); H04L (67/2869); H04L (65/1069); H04W (4/06); H04W (48/17)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6714201	12/2003	Grinstein et al.	N/A	N/A
2018/0285129	12/2017	Mangino	N/A	N/A
2019/0043209	12/2018	Nishimura et al.	N/A	N/A
2019/0114830	12/2018	Bouazizi	N/A	G06F 3/013
2019/0213784	12/2018	Schmalstieg et al.	N/A	N/A
2021/0044636	12/2020	Miller	N/A	N/A
2021/0051522	12/2020	Zhou	N/A	H04W 24/08
2021/0105451	12/2020	Oyman	N/A	N/A
2021/0203756	12/2020	Yerli	N/A	H04L 41/0806
2021/0274235	12/2020	Anderegg et al.	N/A	N/A
2021/0275915	12/2020	Fersch et al.	N/A	N/A
2021/0304503	12/2020	Bastov	N/A	G06T 19/006
2021/0320955	12/2020	Kolan	N/A	H04L 65/1101
2023/0011858	12/2022	Li et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
107909643	12/2017	CN	N/A
2019-535191	12/2018	JP	N/A
2018/064283	12/2017	WO	N/A

OTHER PUBLICATIONS

Communication dated Aug. 13, 2024, issued in Japanese Application No. 2023-552350. cited by applicant
International Search Report issued Jul. 27, 2022 in International Application No. PCT/US2022/022269. cited by applicant
Written Opinion of the International Searching Authority issued Jul. 27, 2022 in International Application No. PCT/US2022/022269. cited by applicant

“3rd Generation Partnership Project; Technical Specification Group SA; Support of 5G Glass-type Augmented Reality / Mixed Reality (AR/MR) devices; (Release 17)”, 3GPP TR 26.998, Oct. 2021, V1.0.3, 92 pages. cited by applicant

“3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; 5G Media Streaming (5GMS); General description and architecture (Release 16)”, 3GPP TS 26.501, Jun. 2021, 79 pages, V16.8.0. cited by applicant

Samsung Electronics Co., Ltd. “[FS_5GStar] Updates to 6.3.4 procedures and call flows for interactive immersive services” 3GPP TSG SA WG4 Video SWG Telco post 115-e, Oct. 26, 2021, S4aV210814, (6 pages). cited by applicant

Tencent “[FS_5GStar] Edgar-based media streaming update”, SA4, 3GPPSA4#115-e, Aug. 18-27, 2021, S4-211122, Version. 0.9.0, (10 pages). cited by applicant

Tencent Cloud: “[FS_5GStar] Updates to 6.2.4. procedures and call flows for Star and Edgar based media streaming”, 3GPP TSG 3GPPSA4#116-e, Nov. 10-19, 2021, S4-211407 (6 pages). cited by applicant

Extended European Search Report dated Feb. 4, 2025 in Application No. 22890569.1. cited by applicant

Primary Examiner: Taylor; Nicholas R

Assistant Examiner: De Rodriguez; Angela Widhalm

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a Continuation of U.S. application Ser. No. 17/705,905 filed Mar. 28, 2022, which claims priority from U.S. Provisional Application No. 63/275,358, filed on Nov. 3, 2021, in the United States Patent and Trademark Office, the disclosure of which is incorporated herein by reference in its entirety.

FIELD

(1) The disclosure generally relates to 5.sup.th generation (5G) augmented reality (AR)/mixed reality (MR), and, in particular, to a method and apparatus for providing AR/MR content to 5G devices in which the scenes are dynamically updated.

BACKGROUND

(2) The 3rd Generation Partnership Project (3GPP) TS26.501 defines the media streaming architecture for 5.sup.th generation (5G) networks. The 3GPP started a technical report on supporting augmented reality (AR)/mixed reality (MR) applications. 3GPP TR 26.998 defines the support for glass-type AR/MR devices in 5G networks. Two device classes are considered: devices that are fully capable of decoding and playing complex AR/MR content (i.e., stand-alone AR (STAR)), and devices that have smaller computational resources and/or smaller physical size (i.e., a smaller battery), and are only capable of running such applications if the larger portion of the computation is performed on 5G edge servers, networks, or clouds rather than on the device (edge dependent AR (EDGAR)). However, the call flow for the EDGAR device does not support scene updates.

SUMMARY

(3) In accordance with an aspect of the disclosure, a method may include selecting media content including a full scene description, selecting a 5.sup.th generation (5G) media streaming downlink (5GMSd) application server (AS) to stream the media content based on the full scene description,

deriving a simplified scene description based on the full scene description, and creating an augmented reality (AR)/mixed reality (MR) session based on the simplified scene description.

(4) In accordance with an aspect of the disclosure, a device may include at least one memory configured to store program code and at least one processor configured to read the program code and operate as instructed by the program code, the program code including first selecting code configured to cause the at least one processor to select media content including a full scene description, second selecting code configured to cause the at least one processor to select a 5GMSd AS to stream the media content based on the full scene description, first deriving code configured to cause the at least one processor to derive a simplified scene description based on the full scene description, and first creating code configured to cause the at least one processor to create an AR/MR session based on the simplified scene description.

(5) In accordance with an aspect of the disclosure, a non-transitory computer-readable medium may store instructions, the instructions including one or more instructions that, when executed by one or more processors of a device, cause the one or more processors to select media content including a full scene description, select a 5GMSd AS to stream the media content based on the full scene description, derive a simplified scene description based on the full scene description, and create an AR/MR session based on the simplified scene description.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Further features, the nature, and various advantages of the disclosed subject matter will be more apparent from the following detailed description and the accompanying drawings in which:
- (2) FIG. 1 is a diagram of an environment in which methods, apparatuses, and systems described herein may be implemented, according to embodiments.
- (3) FIG. 2 is a block diagram of example components of one or more devices of FIG. 1.
- (4) FIG. 3 is a diagram of a media architecture for media uplink streaming, according to embodiments.
- (5) FIG. 4 is a diagram of a media architecture for media downlink streaming, according to embodiments.
- (6) FIGS. 5A and 5B are diagrams of an edge dependent augmented reality (AR) (EDGAR) 5.sup.th Generation media streaming downlink (5GMSd) download architecture, according to embodiments.
- (7) FIGS. 6A, 6B, and 6C are diagrams of an operation flow for EDGAR-based 5G downlink streaming, according to embodiments.
- (8) FIG. 7 is a flowchart of a method for EDGAR-based 5G downlink streaming, according to embodiments.

DETAILED DESCRIPTION

- (9) FIG. 1 is a diagram of an environment **100** in which methods, apparatuses, and systems described herein may be implemented, according to embodiments. As shown in FIG. 1, the environment **100** may include a user device **110**, a platform **120**, and a network **130**. Devices of the environment **100** may interconnect via wired connections, wireless connections, or a combination of wired and wireless connections.
- (10) The user device **110** includes one or more devices capable of receiving, generating, storing, processing, and/or providing information associated with platform **120**. For example, the user device **110** may include a computing device (e.g., a desktop computer, a laptop computer, a tablet computer, a handheld computer, a smart speaker, a server, etc.), a mobile phone (e.g., a smart phone, a radiotelephone, etc.), a wearable device (e.g., a pair of smart glasses or a smart watch), or a similar device. In some implementations, the user device **110** may receive information from

and/or transmit information to the platform **120**.

(11) The platform **120** includes one or more devices as described elsewhere herein. In some implementations, the platform **120** may include a cloud server or a group of cloud servers. In some implementations, the platform **120** may be designed to be modular such that software components may be swapped in or out depending on a particular need. As such, the platform **120** may be easily and/or quickly reconfigured for different uses.

(12) In some implementations, as shown, the platform **120** may be hosted in a cloud computing environment **122**. Notably, while implementations described herein describe the platform **120** as being hosted in the cloud computing environment **122**, in some implementations, the platform **120** may not be cloud-based (i.e., may be implemented outside of a cloud computing environment) or may be partially cloud-based.

(13) The cloud computing environment **122** includes an environment that hosts the platform **120**. The cloud computing environment **122** may provide computation, software, data access, storage, etc. services that do not require end-user (e.g. the user device **110**) knowledge of a physical location and configuration of system(s) and/or device(s) that hosts the platform **120**. As shown, the cloud computing environment **122** may include a group of computing resources **124** (referred to collectively as “computing resources **124**” and individually as “computing resource **124**”).

(14) The computing resource **124** includes one or more personal computers, workstation computers, server devices, or other types of computation and/or communication devices. In some implementations, the computing resource **124** may host the platform **120**. The cloud resources may include compute instances executing in the computing resource **124**, storage devices provided in the computing resource **124**, data transfer devices provided by the computing resource **124**, etc. In some implementations, the computing resource **124** may communicate with other computing resources **124** via wired connections, wireless connections, or a combination of wired and wireless connections.

(15) As further shown in FIG. **1**, the computing resource **124** includes a group of cloud resources, such as one or more applications (APPS) **124-1**, one or more virtual machines (VMs) **124-2**, virtualized storage (VSs) **124-3**, one or more hypervisors (HYPs) **124-4**, or the like.

(16) The application **124-1** includes one or more software applications that may be provided to or accessed by the user device **110** and/or the platform **120**. The application **124-1** may eliminate a need to install and execute the software applications on the user device **110**. For example, the application **124-1** may include software associated with the platform **120** and/or any other software capable of being provided via the cloud computing environment **122**. In some implementations, one application **124-1** may send/receive information to/from one or more other applications **124-1**, via the virtual machine **124-2**.

(17) The virtual machine **124-2** includes a software implementation of a machine (e.g. a computer) that executes programs like a physical machine. The virtual machine **124-2** may be either a system virtual machine or a process virtual machine, depending upon use and degree of correspondence to any real machine by the virtual machine **124-2**. A system virtual machine may provide a complete system platform that supports execution of a complete operating system (OS). A process virtual machine may execute a single program, and may support a single process. In some implementations, the virtual machine **124-2** may execute on behalf of a user (e.g. the user device **110**), and may manage infrastructure of the cloud computing environment **122**, such as data management, synchronization, or long-duration data transfers.

(18) The virtualized storage **124-3** includes one or more storage systems and/or one or more devices that use virtualization techniques within the storage systems or devices of the computing resource **124**. In some implementations, within the context of a storage system, types of virtualizations may include block virtualization and file virtualization. Block virtualization may refer to abstraction (or separation) of logical storage from physical storage so that the storage system may be accessed without regard to physical storage or heterogeneous structure. The

separation may permit administrators of the storage system flexibility in how the administrators manage storage for end users. File virtualization may eliminate dependencies between data accessed at a file level and a location where files are physically stored. This may enable optimization of storage use, server consolidation, and/or performance of non-disruptive file migrations.

(19) The hypervisor **124-4** may provide hardware virtualization techniques that allow multiple operating systems (e.g., “guest operating systems”) to execute concurrently on a host computer, such as the computing resource **124**. The hypervisor **124-4** may present a virtual operating platform to the guest operating systems, and may manage the execution of the guest operating systems. Multiple instances of a variety of operating systems may share virtualized hardware resources.

(20) The network **130** includes one or more wired and/or wireless networks. For example, the network **130** may include a cellular network (e.g. a fifth generation (5G) network, a long-term evolution (LTE) network, a third generation (3G) network, a code division multiple access (CDMA) network, etc.), a public land mobile network (PLMN), a local area network (LAN), a wide area network (WAN), a metropolitan area network (MAN), a telephone network (e.g. the Public Switched Telephone Network (PSTN)), a private network, an ad hoc network, an intranet, the Internet, a fiber optic-based network, or the like, and/or a combination of these or other types of networks.

(21) The number and arrangement of devices and networks shown in FIG. **1** are provided as an example. In practice, there may be additional devices and/or networks, fewer devices and/or networks, different devices and/or networks, or differently arranged devices and/or networks than those shown in FIG. **1**. Furthermore, two or more devices shown in FIG. **1** may be implemented within a single device, or a single device shown in FIG. **1** may be implemented as multiple, distributed devices. Additionally, or alternatively, a set of devices (e.g. one or more devices) of the environment **100** may perform one or more functions described as being performed by another set of devices of the environment **100**.

(22) FIG. **2** is a block diagram of example components of one or more devices of FIG. **1**. The device **200** may correspond to the user device **110** and/or the platform **120**. As shown in FIG. **2**, the device **200** may include a bus **210**, a processor **220**, a memory **230**, a storage component **240**, an input component **250**, an output component **260**, and a communication interface **270**.

(23) The bus **210** includes a component that permits communication among the components of the device **200**. The processor **220** is implemented in hardware, firmware, or a combination of hardware and software. The processor **220** is a central processing unit (CPU), a graphics processing unit (GPU), an accelerated processing unit (APU), a microprocessor, a microcontroller, a digital signal processor (DSP), a field-programmable gate array (FPGA), an application-specific integrated circuit (ASIC), or another type of processing component. In some implementations, the processor **220** includes one or more processors capable of being programmed to perform a function. The memory **230** includes a random access memory (RAM), a read only memory (ROM), and/or another type of dynamic or static storage device (e.g. a flash memory, a magnetic memory, and/or an optical memory) that stores information and/or instructions for use by the processor **220**.

(24) The storage component **240** stores information and/or software related to the operation and use of the device **200**. For example, the storage component **240** may include a hard disk (e.g., a magnetic disk, an optical disk, a magneto-optic disk, and/or a solid state disk), a compact disc (CD), a digital versatile disc (DVD), a floppy disk, a cartridge, a magnetic tape, and/or another type of non-transitory computer-readable medium, along with a corresponding drive.

(25) The input component **250** includes a component that permits the device **200** to receive information, such as via user input (e.g. a touch screen display, a keyboard, a keypad, a mouse, a button, a switch, and/or a microphone). Additionally, or alternatively, the input component **250** may include a sensor for sensing information (e.g. a global positioning system (GPS) component, an accelerometer, a gyroscope, and/or an actuator). The output component **260** includes a component

that provides output information from the device **200** (e.g. a display, a speaker, and/or one or more light-emitting diodes (LEDs)).

(26) The communication interface **270** includes a transceiver-like component (e.g., a transceiver and/or a separate receiver and transmitter) that enables the device **200** to communicate with other devices, such as via a wired connection, a wireless connection, or a combination of wired and wireless connections. The communication interface **270** may permit the device **200** to receive information from another device and/or provide information to another device. For example, the communication interface **270** may include an Ethernet interface, an optical interface, a coaxial interface, an infrared interface, a radio frequency (RF) interface, a universal serial bus (USB) interface, a Wi-Fi interface, a cellular network interface, or the like.

(27) The device **200** may perform one or more processes described herein. The device **200** may perform these processes in response to the processor **220** executing software instructions stored by a non-transitory computer-readable medium, such as the memory **230** and/or the storage component **240**. A computer-readable medium is defined herein as a non-transitory memory device. A memory device includes memory space within a single physical storage device or memory space spread across multiple physical storage devices.

(28) Software instructions may be read into the memory **230** and/or the storage component **240** from another computer-readable medium or from another device via the communication interface **270**. When executed, software instructions stored in the memory **230** and/or the storage component **240** may cause the processor **220** to perform one or more processes described herein. Additionally, or alternatively, hardwired circuitry may be used in place of or in combination with software instructions to perform one or more processes described herein. Thus, implementations described herein are not limited to any specific combination of hardware circuitry and software.

(29) The number and arrangement of components shown in FIG. 2 are provided as an example. In practice, the device **200** may include additional components, fewer components, different components, or differently arranged components than those shown in FIG. 2. Additionally, or alternatively, a set of components (e.g., one or more components) of the device **200** may perform one or more functions described as being performed by another set of components of the device **200**.

(30) A 5G media streaming (5GMS) system may be an assembly of application functions, application servers, and interfaces from the 5G media streaming architecture that support either downlink media streaming services or uplink media streaming services, or both. A 5GMS Application Provider may include a party that interacts with functions of the 5GMS system and supplies a 5GMS Aware Application that interacts with functions of the 5GMS system. The 5GMS Aware Application may refer to an application in the user equipment (UE), provided by the 5GMS Application Provider, that contains the service logic of the 5GMS application service, and interacts with other 5GMS Client and Network functions via the interfaces and application programming interfaces (APIs) defined in the 5GMS architecture. A 5GMS Client may refer to a UE function that is either a 5GMS downlink (5GMSd) Client or a 5GMS uplink (5GMSu) Client, or both.

(31) The 5GMSd Client may refer to a UE function that includes at least a 5G media streaming player and a media session handler for downlink streaming and that may be accessed through well-defined interfaces/APIs. The 5GMSu Client may refer to an originator of a 5GMSu service that may be accessed through well-defined interfaces/APIs. A 5GMSu media streamer may refer to a UE function that enables uplink delivery of streaming media content to an Application Server (AS) function of the 5GMS Application Provider, and which interacts with both the 5GMSu Aware Application for media capture and subsequent streaming, and the Media Session Handler for media session control.

(32) A dynamic policy may refer to a dynamic policy and charging control (PCC) rule for an uplink or downlink application flow during a media session. An egest session may refer to an uplink media streaming session from the 5GMS AS towards the 5GMSu Application Provider. An ingest

session may refer to a session to upload the media content to a 5GMSd AS. A policy template may refer to a collection of (semi-static) Policy or Control Function (PCF)/Network Exposure Function (NEF) API parameters which are specific to the 5GMS Application Provider and also the resulting PCC rule. A policy template ID may identify the desired policy template, which is used by the 5GMSd Application Function (AF) to select the appropriate PCF/NEF API towards the 5G system so that the PCF can compile the desired PCC rule. The Media Player Entry may refer to a document or a pointer to a document that defines a media presentation (e.g., a media presentation description (MPD) for DASH or a uniform resource locator (URL) to a video clip file). A Media Streamer Entry may refer to a pointer (e.g., in the form of a URL) that defines an entry point of an uplink media streaming session. A presentation entry may refer to a document or a pointer to a document that defines an application presentation, such as an HTML5 document.

(33) A Provisioning Session may refer to a data structure supplied at an interface (M1d) by a 5GMSd Application provider that configures the 5GMSd features relevant to a set of 5GMSd Aware Applications. A 5GMSd Media Player may refer to a UE function that enables playback and rendering of a media presentation based on a media play entry and exposing some basic controls such as play, pause, seek, stop, to the 5GMSd Aware Application. Server Access Information may refer to a set of parameters and addresses (including 5GMSd AF and 5GMSd AS addresses) which are needed to activate the reception of a streaming session. A Service and Content Discovery may refer to functionality and procedures provided by a 5GMSd Application Provider to a 5GMS Aware Application that enables the end user to discover the available streaming service and content offerings and select a specific service or content item for access. A Service Announcement may refer to procedures conducted between the 5GMS Aware Application and the 5GMS Application Provider such that the 5GMS Aware Application is able to obtain 5GMS Service Access Information, either directly or in the form of a reference to that information.

(34) A third party player may refer to a part of an application that uses APIs to exercise selected 5GMSd functions to play back media content. A third party uplink streamer may refer to a part of an application that uses APIs to exercise selected 5GMSu functions to capture and stream media content.

(35) FIG. 3 is a diagram of a media architecture **300** for media uplink streaming according to embodiments. A 5GMSu Application Provider **301** may use 5GMSu for uplink streaming services. 5GMSu Application provider **301** may provide a 5GMSu Aware Application **302** on the UE **303** to make use of 5GMSu Client **304** and network functions using interfaces and APIs defined in 5GMSu. 5GMSu AS may be an AS dedicated to 5G Media Uplink Streaming. 5GMSu Client **304** may be a UE **303** internal function dedicated to 5G Media Uplink Streaming.

(36) 5GMSu AF **306** and 5GMSu AS **305** may be Data Network (DN) **307** functions. Functions in trusted DNs may be trusted by the operator's network. Therefore, AFs in trusted DNs may directly communicate with all 5G Core functions. Functions in external DNs may only communicate with 5G Core functions via the NEF **308** using link **320**.

(37) The media architecture **300** may connect UE **303** internal functions and related network functions for 5G Media Uplink Streaming. Accordingly, media architecture **300** may include a number of functions. For example, 5GMSu Client **304** on UE **303** may be an originator of 5GMSu service that may be accessed through interfaces/APIs. 5GMSu Client **304** may include two sub-functions, media session handler **309** and media streamer **310**. Media session handler **309** may communicate with the 5GMSu AF **306** in order to establish, control and support the delivery of a media session. The Media Session Handler **309** may expose APIs that can be used by the 5GMSu Aware Application **302**. Media Streamer **310** may communicate with 5GMSu AS **305** in order to stream the media content and provide a service to the 5GMSu Aware Application **302** for media capturing and streaming, and the Media Session Handler **309** for media session control. 5GMSu Aware Application **302** may control 5GMSu Client **304** by implementing external application or content service provider specific logic and enabling the establishment of a media session. 5GMSu

AS **305** may host 5G media functions and may be implemented as a content delivery network (CDN), for example. 5GMSu Application Provider **301** may be an external application or content specific media functionality, e.g., media storage, consumption, transcoding and redistribution that uses 5GMSu to stream media from 5GMSu Aware Application **302**. 5GMSu AF **306** may provide various control functions to the Media Session Handler **309** on the UE **303** and/or to 5GMSu Application Provider **301**. 5GMSu AF **306** may relay or initiate a request for different PCF **311** treatment or interact with other network functions.

(38) Media architecture **300** may include a number of different interfaces. For example, link **321** may relate to M1u, which may be a 5GMSu Provisioning API exposed by 5GMSu AF **306** to provision usage of media architecture **300** and to obtain feedback. Link **322** may relate to M2u, which may be a 5GMSu Publish API exposed by 5GMSu AS **305** and used when 5GMSu AS **305** in trusted DN, such as DN **307**, is selected to receive content for streaming service. Link **323** may relate to M3u, which may be an internal API used to exchange information for content hosting on 5GMSu AS **305** within a trusted DN such as DN **307**. Link **324** may relate to M4u, which may be a Media Uplink Streaming API exposed by 5GMSu AS **323** to Media Streamer **310** to stream media content. Link **325** may relate to M5u, which may be a Media Session Handling API exposed by 5GMSu AF **305** to Media Session Handler for media session handling, control and assistance that also include appropriate security mechanisms e.g. authorization and authentication. Link **326** may relate to M6u, which may be a UE **303** Media Session Handling API exposed by Media Session Handler **309** to 5GMSu Aware Application **302** to make use of 5GMSu functions. Link **327** may relate to M7u, which may be a UE Media Streamer API exposed by Media Streamer **310** to 5GMSu Aware Application **302** and Media Session Handler **309** to make use of Media Streamer **310**. Link **328** may relate to M8u, which may be an Application API which is used for information exchange between 5GMSu Aware Application **302** and 5GMSu Application Provider **301**, for example to provide service access information to the 5GMSu Aware Application **302**. The UE **303** may also be implemented in a self-contained manner such that interfaces M6u **326** and M7u **327** are not exposed.

(39) FIG. 4 is a diagram of a media architecture **400** for media downlink streaming, according to embodiments. A 5GMSd Application Provider **401** may use 5GMSd for downlink streaming services. 5GMSd Application provider **401** may provide a 5GMSd Aware Application **402** on the UE **403** to make use of 5GMSd Client **404** and network functions using interfaces and APIs defined in 5GMSd. 5GMSd AS may be an AS dedicated to 5G Media Downlink Streaming. 5GMSd Client **404** may be a UE **403** internal function dedicated to 5G Media Downlink Streaming.

(40) 5GMSd AF **406** and 5GMSd AS **405** may be DN **407** functions. Functions in trusted DNs may be trusted by the operator's network. Therefore, AFs in trusted DNs may directly communicate with all 5G Core functions. Functions in external DNs may only communicate with 5G Core functions via the NEF **408** using link **420**.

(41) The media architecture **400** may connect UE **403** internal functions and related network functions for 5G Media Downlink Streaming. Accordingly, media architecture **400** may include a number of functions. For example, 5GMSd Client **404** on UE **403** may be a receiver of 5GMSd service that may be accessed through interfaces/APIs. 5GMSd Client **404** may include two sub-functions, media session handler **409** and media Player **410**. Media session handler **409** may communicate with the 5GMSd AF **406** in order to establish, control and support the delivery of a media session. The Media Session Handler **409** may expose APIs that can be used by the 5GMSd Aware Application **402**. Media Player **410** may communicate with 5GMSd AS **405** in order to stream the media content and provide a service to the 5GMSd Aware Application **402** for media playback, and the Media Session Handler **409** for media session control. 5GMSd Aware Application **402** may control 5GMSd Client **404** by implementing external application or content service provider specific logic and enabling the establishment of a media session. 5GMSd AS **405**

may host 5G media functions. 5GMSd Application Provider **401** may be an external application or content specific media functionality, e.g., media creation, encoding, and formatting that uses 5GMSd to stream media to 5GMSd Aware Application **402**. 5GMSd AF **406** may provide various control functions to the Media Session Handler **409** on the UE **403** and/or to 5GMSd Application Provider **401**. 5GMSd AF **406** may relay or initiate a request for different PCF **411** treatment or interact with other network functions.

(42) Media architecture **400** may include a number of different interfaces. For example, link **421** may relate to M1d, which may be a 5GMSd Provisioning API exposed by 5GMSd AF **406** to provision usage of media architecture **400** and to obtain feedback. Link **422** may relate to M2d, which may be a 5GMSd Ingest API exposed by 5GMSd AS **405** and used when 5GMSd AS **405** in trusted DN, such as DN **407**, is selected to receive content for streaming service. Link **423** may relate to M3d, which may be an internal API used to exchange information for content hosting on 5GMSd AS **405** within a trusted DN such as DN **407**. Link **424** may relate to M4d, which may be a Media Downlink Streaming API exposed by 5GMSd AS **423** to Media Player **410** to stream media content. Link **425** may relate to M5d, which may be a Media Session Handling API exposed by 5GMSd AF **405** to Media Session Handler for media session handling, control and assistance that also include appropriate security mechanisms e.g. authorization and authentication. Link **426** may relate to M6d, which may be a UE **403** Media Session Handling API exposed by Media Session Handler **409** to 5GMSd Aware Application **402** to make use of 5GMSd functions. Link **427** may relate to M7d, which may be a UE Media Player API exposed by Media Player **410** to 5GMSd Aware Application **402** and Media Session Handler **409** to make use of Media Player **410**. Link **428** may relate to M8d, which may be an Application API which is used for information exchange between 5GMSd Aware Application **402** and 5GMSd Application Provider **401**, for example to provide service access information to the 5GMSd Aware Application **402**.

(43) FIGS. 5A and 5B are diagrams of an edge dependent augmented reality (AR) (EDGAR) 5GMSd download architecture **500**, according to embodiments. The AR EDGAR 5GMSd architecture **500** may be applied to mixed reality (MR) as well. The architecture **500** includes a 5G EDGAR UE **502**, a cloud/edge server **504** and an AR/MR application provider **506**. The 5G EDGAR UE **502** includes an AR runtime **508**, a lightweight scene manager **510**, a 5GMS client **512** and a basic AR/MR application **514**. The AR runtime **508** includes a vision engine/simultaneous localization and mapping (SLAM) **516**, a pose correction module **518**, and a soundfield mapping module **520**. The lightweight scene manager **510** includes a basic scene graph handler (SGH) **522** and a compositor **524**. The 5GMS client **512** includes a media session handler (including an edge session) **526** and a media client **528**. The media client **528** includes a scene description delivery module **530**, a content delivery module **532** and basic codecs **534**. The 5G EDGAR UE **502** includes a 5G lightweight system (Uu) **536** that is in communication with a 5G system (gNb) **538** of the cloud/edge server **504**.

(44) The cloud/edge server **504** includes an AR/MR application **540** and media delivery functions **542**. The media delivery functions **542** include a media AF **544** and a media AS **546**. The media AS **546** includes a content delivery function **548**, a scene description function (SDF) **550**, decoders **552** and encoders **554**. The AR/MR application **540** includes an AR scene manager **556**, AR functions **564**, a semantical perception module **566**, a social integration module **568**, and a media assets database **570**. The AR scene manager **556** includes a scene graph generator **558**, an immersive visual renderer **560** and an immersive audio renderer **562**.

(45) The AR/MR application provider **506** includes an immersive media server **574**. The immersive media server **574** includes a scene description module **576**, a manifest server **578**, and a segment server **580**.

(46) The media client **528** transmits to the content delivery module **548** by an M4 interface **582** (e.g., transmitting pose and interactions). The content delivery module **548** transmits to the media client **528** by an M4 interface **584** (e.g., transmitting pre-rendered media). The media session

handler **526** is in communication with the media AF **544** by an M5d interface **586**. The basic AR/MR application **514** is in communication with the AR/MR application **540** by an M8 interface **588**. The basic AR/MR application **514** may receive a user input **591** and AR data **590** from the AR runtime **508**. The AR runtime **508** may receive data from cameras **592** and sensors **593**, and may output data to a display **594** and to speakers **595**.

(47) Embodiments of the disclosure provide a call flow that includes two loops: streaming scene and scene updates as an outer loop, and streaming media objects of each scene as an inner loop.

(48) FIGS. **6A**, **6B**, and **6C** are diagrams of an operation flow for EDGAR-based 5G downlink streaming, according to embodiments. The system performing the operation flow of FIG. **6** may include a basic AR/MR application **606**, an AR runtime **608**, an AR/MR scene manager **610**, a media client **612**, and a media session handler **614**, which may be part of the EDGAR UE **602** (furthermore, the media client **612** and the media session handler **614** may be part of the media access functions). The system also includes a 5GMSd AF **616**, a 5GMSd AS **618**, which may be part of the cloud/edge server **604**. The system may also include an AR/MR application provider **620**. The application provider **620** may be referred to as a scene server.

(49) In operation **630**, scene content is ingested by the 5GMSd AS **618**. In operation **632**, a service announcement and content delivery is triggered by the AR/MR application **606**. The service access information includes the media client entry or a reference to the service access information is provided through the M8d interface. In operation **634**, media content/scenes are selected. In operation **636**, the service access information is acquired or updated as needed (i.e., operation **636** may be optional). In operation **638**, the AR/MR application **606** initializes the scene manager **610** with the entry point (i.e., the full scene description) URL. In operation **640**, the media client **612** establishes the transport session for receiving the entry point. In operation **641**, the media client **612** requests and receives the entry point or an update to the scene description. In operation **642**, the entry point is processed. As referred to herein, a scene description may be a data table that includes information on a scene, such as entry point, duration, resolution, bitrate, and/or other information related to a scene. A full scene description may include an entry point for the full scene, and a simplified scene description may include an entry point for the simplified scene. The full scene description may refer to an entry point at the beginning of the scene, and the simplified scene description may refer to an entry point for a portion of the full scene (e.g., the portion of the full scene may be the simplified scene). Thus, the simplified scene description may be derived based on the full scene description. For example, the full scene may include time points t_0 through t_4 , and the full scene description may indicate that the entry point of the full scene is time point t_0 . The simplified scene may include the portion of the full scene from time point t_2 to time point t_3 , and the simplified scene description may indicate that the that the entry point of the simplified scene is time point t_2 .

(50) In operation **644**, the system selects a 5GMSd AS based on the scene description and device capabilities, and instantiates edge processing. Based on the processed scene description and the device capabilities, the 5GMSd AS is selected, and edge processes are instantiated using the processes defined in the edge server **604**. The AR/MR scene manager **610** may send the scene description and the device capabilities to the 5GMSd AS **618**. The 5GMSd AS **618** derives the edge AS (EAS) key performance indicators (KPIs) and, if needed, selects a new AS/EAS (e.g., through the AF **616**) based on the new KPI. The edge processes are started and a new entry point URL is provided to the AR/MR scene manager **610**. Alternative, in some embodiments, the AR/MR scene manager **610** may derive the EAS KPIs from the scene description and device capabilities, and request the 5GMSd AF **616** to provide the list of suitable EASs. The AR/MR scene manager **610** may select the AS/EAS and request to start the edge processes in the AS (e.g., the selected AS may be the 5GMSd AS **618**). The edge processes are started, and a new entry point URL is provided to the AR/MR scene manager.

(51) In operation **646**, the AR/MR scene manager **610** requests the simplified scene entry

point/scene description. The edge processes derive the simplified scene entry/description from the full scene description and provide it to the AR/MR scene manager. In operation **648**, the simplified entry point (i.e., the simplified scene description) is processed.

(52) In operation **650**, the AR/MR scene manager **610** requests the creation of a new AR/MR session from the AR runtime **608**. In operation **652**, the AR runtime **608** creates the new AR/MR session. In operation **654**, a streaming session is created. The media client **612** and/or the AR/MR scene manager **610** may provide the necessary quality of service (QoS) information to the media session handler **614**. In operation **656**, the streaming session(s) are configured. The media session handler **614** may share the information with the 5GMSd AF **616**, including the desired QoS information in some embodiments. Based on existing provisioning by the AR/MR application provider **620**, the 5GMSd AF **616** may request QoS modifications to the protocol data unit (PDU) session.

(53) In operation **658**, the transport sessions for delivery manifests are established. For the required media content, the media client **612** establishes the transport sessions to acquire delivery manifest information. In operation **660**, the media client **612** requests and receives the delivery manifests from the 5GMSd AS **618**. In operation **662**, the media client **612** processes the delivery manifests. The media client **612**, for example, determines the number of needed transport sessions for media acquisition. The media client **612** is configured to use the delivery manifest information to initialize the media pipelines for each media stream. In operation **664**, the AR/MR scene manager **610** and the media client **612** configure the rendering and delivery media pipelines.

(54) In operation **666**, the media client **612** establishes the transport sessions to acquire the media content. In operation **668**, the 5GMSd AS **618** initiates and starts a media session. The media session forms a stateful session loop specific to the UE (i.e., operations **670**, **672**, **674** and **676**).

(55) In operation **670**, the latest pose information is acquired by the AR/MR scene manager **610** and is shared with the media client **612**. In operation **672**, the media client **612** sends the latest pose information to the 5GMSd AS **618**. In operation **674**, the 5GMSd AS **618** performs pre-rendering of the media base4d on the latest received pose information and possibly any original scene update. Pre-rendering may include decoding and rendering immersive media and encoding the rendered (i.e., two-dimensional) media. In operation **676**, the pre-rendered media is sent by the 5GMSd AS **618** to the media client **612**. In operation **678**, the media client **612** passes decodes and processes the media data. For encrypted media data, the media client **612** may also perform decryption. In operation **680**, the media client **612** passes the media data to the AR/MR scene manager **610**. In operation **682**, the AR/MR scene manager **610** renders the media and passes the rendered media to the AR runtime **608**. The AR runtime **608** performs further processing, such as registration of the AR content to the real world, composition, and pose correction.

(56) The AR/MR scene may be dynamically updated during the streaming to the EDGAR device and therefore the scenes can be changed completely during the streaming session. The scene updates for the EDGAR device are part of the same loop as the media object. However, the scene updates occur at the media application server on the edge network. Thus, the client sees any scene update as a continuous part of the video streaming session.

(57) FIG. 7 is a flowchart of a method for EDGAR-based 5G downlink streaming, according to embodiments. In operation **702**, the system selects media content including a full scene description. In operation **704**, the system selects a 5GMSd AS to stream the media content based on the full scene description. In operation **706**, the system derives a simplified scene description based on the full scene description. In operation **708**, the system creates an AR/MR session based on the simplified scene description.

(58) Although FIG. 7 shows example blocks of process **700**, in some implementations, process **700** may include additional blocks, fewer blocks, different blocks, or differently arranged blocks than those depicted in FIG. 7. Additionally, or alternatively, two or more of the blocks of process **700** may be performed in parallel.

(59) Further, the proposed methods may be implemented by processing circuitry (e.g., one or more processors or one or more integrated circuits). In one example, the one or more processors execute a program that is stored in a non-transitory computer-readable medium to perform one or more of the proposed methods.

(60) The techniques described above can be implemented as computer software using computer-readable instructions and physically stored in one or more computer-readable media.

(61) Embodiments of the present disclosure may be used separately or combined in any order. Further, each of the embodiments (and methods thereof) may be implemented by processing circuitry (e.g., one or more processors or one or more integrated circuits). In one example, the one or more processors execute a program that is stored in a non-transitory computer-readable medium.

(62) The foregoing disclosure provides illustration and description, but is not intended to be exhaustive or to limit the implementations to the precise form disclosed. Modifications and variations are possible in light of the above disclosure or may be acquired from practice of the implementations.

(63) As used herein, the term component is intended to be broadly construed as hardware, firmware, or a combination of hardware and software.

(64) Even though combinations of features are recited in the claims and/or disclosed in the specification, these combinations are not intended to limit the disclosure of possible implementations. In fact, many of these features may be combined in ways not specifically recited in the claims and/or disclosed in the specification. Although each dependent claim listed below may directly depend on only one claim, the disclosure of possible implementations includes each dependent claim in combination with every other claim in the claim set.

(65) No element, act, or instruction used herein should be construed as critical or essential unless explicitly described as such. Also, as used herein, the articles “a” and “an” are intended to include one or more items, and may be used interchangeably with “one or more.” Furthermore, as used herein, the term “set” is intended to include one or more items (e.g., related items, unrelated items, a combination of related and unrelated items, etc.), and may be used interchangeably with “one or more.” Where only one item is intended, the term “one” or similar language is used. Also, as used herein, the terms “has,” “have,” “having,” or the like are intended to be open-ended terms. Further, the phrase “based on” is intended to mean “based, at least in part, on” unless explicitly stated otherwise.

Claims

1. A method for video decoding in a decoder, the method comprising: selecting media content including a full scene description; requesting a 5.sup.th generation (5G) media streaming downlink (5GMSd) application server (AS) to stream the media content based on the full scene description; deriving a simplified scene description based on the full scene description; implementing at least part of an augmented reality (AR)/mixed reality (MR) session based on the simplified scene description, the AR/MR session comprising a double loop call flow of an outer loop, comprising streaming media objects of the simplified scene description of a scene of the full scene description, and an inner loop comprising updating the inner loop, while the media objects are streamed, to stream at least one other media object of the scene of the full scene description besides the objects of the simplified scene description; and decoding at least part of the media content based on the double loop call flow.

2. The method of claim 1, wherein selecting the AS to stream the media content comprises deriving at least one key performance indicator (KPI) of a first AS.

3. The method of claim 2, wherein selecting the AS to stream the media content further comprises selecting the first AS to stream the media content based on the at least one KPI.

4. The method of claim 2, further comprising providing a list of suitable edge application servers

(EASs) to stream the media content, wherein selecting the AS to stream the media content further comprises selecting an EAS from the list of EASs.

5. The method of claim 1, further comprising, after selecting the AS to stream the media content, providing a new entry point uniform resource locator (URL) to an AR/MR scene manager.

6. The method of claim 1, further comprising: receiving updated pose information of the media content; and pre-rendering the media content based on the updated pose information.

7. The method of claim 6, wherein the receiving the updated pose information and the pre-rendering the media content are performed during a media streaming session in which the media content is streamed.

8. A method for video encoding, the method comprising: obtaining media content including a full scene description; implementing at least part of an augmented reality (AR)/mixed reality (MR) session based on a simplified scene description of the full scene description, the AR/MR session comprising a double loop call flow of an outer loop, comprising streaming, from a 5.sup.th generation (5G) media streaming downlink (5GMSd) application server (AS), media objects of the simplified scene description of a scene of the full scene description, and an inner loop comprising updating the inner loop, while the media objects are streamed, to stream at least one other media object of the scene of the full scene description besides the objects of the simplified scene description; and encoding at least part of the media content based on the double loop call flow.

9. The method of claim 8, wherein the AS identifies at least one key performance indicator (KPI) of the AS.

10. The method of claim 9, wherein the AS is selected for the AR/MR session based on the at least one KPI.

11. The method of claim 9, further comprising providing a list of suitable edge application servers (EASs) to stream the media content, wherein the AS is selected for the AR/MR session as an EAS from the list of EASs.

12. The method of claim 8, further comprising providing a new entry point uniform resource locator (URL) to an AR/MR scene manager.

13. The method of claim 8, further comprising: implementing an immersive media delivery comprising providing the at least part of the media content based on pose information of the media content.

14. The method of claim 13, wherein the pose information is received during the AR/MR session.

15. A method of processing visual media data, the method comprising: performing a conversion between a visual media file and a bitstream of a visual media data according to a format rule, the format rule indicating to: obtain media content including a full scene description; and implement at least part of an augmented reality (AR)/mixed reality (MR) session based on a simplified scene description of the full scene description, the AR/MR session comprising a double loop call flow of an outer loop, comprising streaming, from a 5.sup.th generation (5G) media streaming downlink (5GMSd) application server (AS), media objects of the simplified scene description of a scene of the full scene description, and an inner loop comprising updating the inner loop, while the media objects are streamed, to stream at least one other media object of the scene of the full scene description besides the objects of the simplified scene description.

16. The method of claim 15, wherein the AS identifies at least one key performance indicator (KPI) of the AS.

17. The method of claim 16, wherein the AS is selected for the AR/MR session based on the at least one KPI.

18. The method of claim 16, the format rule further indicating to provide a list of suitable edge application servers (EASs) to stream the media content, wherein the AS is selected for the AR/MR session as an EAS from the list of EASs.

19. The method of claim 15, the format rule further indicating to provide a new entry point uniform resource locator (URL) to an AR/MR scene manager.

20. The method of claim 15, the format rule further indicating to implement an immersive media delivery comprising providing the at least part of the media content based on pose information of the media content.
