

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12418206
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Wang; Yin et al.

Stator core, motor, power assembly, automobile and vehicle

Abstract

A stator core, a motor, a power assembly, an automobile and a vehicle are provided. The motor includes: a casing; a stator core fixed in the casing, and a slit flow channel is formed between an outer side wall of the stator core and an inner side wall of the casing, and the slit flow channel is provided as a network-shaped cooling flow channel for cooling fluid to flow; a stator winding mounted on the stator core; and a rotor rotatably sleeved on an inner side of the stator core. A flow path of the cooling fluid in the network-shaped cooling channel is also network-shaped, and a flow form of the cooling fluid in the network-shaped path is turbulent.

Inventors:	Wang; Yin (Ningbo, CN), Xu; Zhanglu (Ningbo, CN), Wang; Zhen (Ningbo, CN), Fang; Liang (Ningbo, CN), Han; Tao (Ningbo, CN), Tan; Yanjun (Ningbo, CN), Lin; Xiaozhe (Ningbo, CN), Wang; Ruiping (Ningbo, CN), Scholten; Ingo (Ningbo, CN)
Applicant:	WUXI INFIMOTION TECHNOLOGY CO., LTD. (Jiangsu, CN)
Family ID:	1000008821547
Assignee:	WUXI INFIMOTION TECHNOLOGY CO., LTD. (Jiangsu, CN)
Appl. No.:	17/908242
Filed (or PCT Filed):	February 25, 2022
PCT No.:	PCT/CN2022/078079
PCT Pub. No.:	WO2022/257507
PCT Pub. Date:	December 15, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240223032 A1	Jul. 04, 2024

Foreign Application Priority Data

CN	202121285519.0	Jun. 09, 2021
CN	202111657979.6	Dec. 30, 2021

Publication Classification

Int. Cl.: H02K1/20 (20060101); H02K3/24 (20060101)

U.S. Cl.:

CPC H02K1/20 (20130101); H02K3/24 (20130101);

Field of Classification Search

CPC: H02K (1/20); H02K (3/24); H02K (9/19); H02K (5/203)

USPC: 310/64

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5491371	12/1995	Ooi	310/58	H02K 1/32
10230287	12/2018	Sever	N/A	H02K 5/203
2008/0100159	12/2007	Dawsey	310/59	H02K 1/20
2010/0320851	12/2009	Lambka	310/54	H02K 9/19
2013/0278092	12/2012	Coldwate et al.	N/A	N/A
2016/0294231	12/2015	Andres	N/A	H02K 5/18
2018/0191218	12/2017	Lee	N/A	H02K 1/20
2018/0358849	12/2017	Saint-Michel	N/A	H02K 7/14
2019/0157922	12/2018	Tangudu et al.	N/A	N/A
2020/0161938	12/2019	Fatemi	N/A	H02K 9/197

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2014241468	12/2015	AU	N/A
101232211	12/2007	CN	N/A
101790831	12/2009	CN	N/A
110492663	12/2018	CN	N/A
111030358	12/2019	CN	N/A
112104115	12/2019	CN	N/A
215733714	12/2021	CN	N/A
102012017293	12/2013	DE	N/A
2008109851	12/2007	JP	N/A
2020137269	12/2019	JP	N/A

OTHER PUBLICATIONS

Translation for WO-2014032876-A2 (Year: 2014). cited by examiner

Office Action dated Dec. 6, 2023 for KR Patent Application No. 10-2022-7031386 and English Translation. cited by applicant

Office Action dated Feb. 21, 2024 for Chinese Patent Application No. 202111657979.6 and English Translation. cited by applicant

European Search Report dated Jul. 12, 2023 for European Patent Application No. 22737362.8. cited by applicant

Office Action dated Aug. 22, 2023 for Japanese Patent Application No. 2022-548447 and English Translation. cited by applicant

Office Action dated Nov. 23, 2022 for Chinese Patent Application No. 202111657979.6 and English Translation. cited by applicant

Office Action dated Jul. 1, 2023 for Chinese Patent Application No. 202111657979.6 and English Translation. cited by applicant

International Search Report for PCT/CN2022/078079 Mailed May 19, 2022. cited by applicant

Primary Examiner: Kenerly; Terrance L

Assistant Examiner: Perkins; Theodore L

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) The present application is a U.S. National Phase Entry of International Application PCT/CN2022/078079 having an international filing date of Feb. 25, 2022, which claims priority of Chinese Patent Application No. 202111657979.6, filed to the CNIPA on Dec. 30, 2021, and priority of Chinese Patent Application No. 202121285519.0, filed to the CNIPA on Jun. 9, 2021, the contents disclosed in the above-mentioned applications are hereby incorporated as a part of this application.

TECHNICAL FIELD

(2) The present application relates to, but is not limited to, vehicle technology, and in particular a stator core, a motor, a power assembly, an automobile, and a vehicle.

BACKGROUND

(3) With improvement of power requirements of electric vehicles, torque density and power density of a power assembly, as one of the core components of power output of an electric vehicle, also increase, so as to realize lightweight and miniaturization of a motor. As a core component of power assembly, a motor is the key of power output of the power assembly, which directly determines the power output of the power assembly and power performance of the whole vehicle.

(4) At present, there are usually two methods for improving torque density and power density of motors in the market. The first method is to choose high-performance ferromagnetic materials. The second method is to increase heat dissipation capacity of the motor to protect electronic components and insulating materials. According to different cooling media, the existing cooling technologies for automobile motors may be divided into natural cooling, air cooling, water cooling and oil cooling. The heat dissipation technologies have their own advantages and disadvantages, but how to further improve the heat dissipation capacity of the motor is a direction and a research

hotspot on which those skilled in the art are working.

SUMMARY

(5) The following is a summary of subject matters described in detail herein. This summary is not intended to limit the protection scope of the claims.

(6) A motor includes: a casing; a stator core fixed in the casing, and a slit flow channel is formed between an outer side wall of the stator core and an inner side wall of the casing, and the slit flow channel is provided as a network-shaped cooling flow channel for a cooling fluid to flow; a stator winding mounted on the stator core; and a rotor rotatably sleeved on an inner side of the stator core.

(7) A stator core, wherein an outer side wall of the stator core is provided with multiple heat dissipation protrusions, and the multiple heat dissipation protrusions are staggeredly arranged in a network-shaped form.

(8) A power assembly, including the motor as described in any of the above embodiments.

(9) An automobile, including the power assembly as described in the above embodiment.

(10) A motor includes: a stator core and a housing; the stator core is formed by mutually staggeredly stacking multiple annular core punching sheets; wherein the core punching sheets include a first core punching sheet and a second core punching sheet, and the stator core is formed by mutually staggeredly stacking the first core punching sheet and the second core punching sheet; the housing is wrapped around an outer periphery of the stator core and the housing and the outer periphery of the stator core are mutually fitted to form a flow channel; structures of the first core punching sheet and the second core punching sheet at the outer peripheral surfaces are different so that the flow channel extends across the outer peripheral surfaces of the first core punching sheet and the second core punching sheet, thereby enabling the liquid to flow in series between the first and second core punching sheets and the housing.

(11) A motor includes: a stator core and a housing; the stator core is formed by mutually staggeredly stacking multiple annular core punching sheets; wherein an outer periphery of each core punching sheet is provided with multiple convex parts and multiple concave parts, the housing is wrapped around the outer periphery of the stator core, and the housing and the convex parts of the stator core are mutually fitted to form a flow channel; wherein a circumferential dimension of the convex part is smaller than a circumferential dimension of the concave part, and when the core punching sheets are mutually staggeredly stacked, the convex parts and the concave parts of two adjacent core punching sheets are staggeredly provided, enabling liquid to flow in series in the multiple core punching sheets.

(12) A vehicle, including the motor described above.

(13) Other aspects will become apparent upon reading and understanding of the drawings and detailed description.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a sectional schematic diagram of a structure of a motor according to an embodiment of the present application.

(2) FIG. 2 is a half-sectional schematic diagram of a motor according to an embodiment of the present application.

(3) FIG. 3 is a schematic diagram of assembling of a stator core and a stator winding according to an embodiment of the present application.

(4) FIG. 4 is a partial enlarged schematic diagram of an outer side wall of a stator core according to an embodiment of the present application.

(5) FIG. 5 is a schematic diagram of a principle of heat dissipation of the stator core shown in FIG.

4.

(6) FIG. 6 is a schematic diagram of a cooling mechanism of a motor according to an embodiment of the present application.

(7) FIG. 7 is a schematic diagram of a principle of the cooling mechanism shown in FIG. 6.

(8) FIG. 8 is a simulation schematic diagram of a flow rate distribution of cooling oil of the cooling mechanism shown in FIG. 6.

(9) FIG. 9 is a simulation schematic diagram of a cooling oil flow path of the cooling mechanism shown in FIG. 6.

(10) FIG. 10 is a sectional diagram of a structure of a casing according to an embodiment of the present application.

(11) FIG. 11 is a three-dimensional schematic diagram of a structure of an end cap according to an embodiment of the present application.

(12) FIG. 12 is a three-dimensional schematic diagram of a structure of a waterfall-spray heat dissipation ring according to an embodiment of the present application.

(13) FIG. 13 is a schematic diagram of a misplaced stacking assembling of a core assembly according to an embodiment of the present application.

(14) FIG. 14 is a schematic diagram of a misplaced stacking assembling of a stator core according to an embodiment of the present application.

(15) FIG. 15 is a schematic structural diagram of a front view of a stator punching sheet according to an embodiment of the present application.

(16) FIG. 16 is an enlarged schematic diagram of part A in FIG. 15.

(17) FIG. 17 is a schematic structural diagram of a motor according to another embodiment of the present application.

(18) FIG. 18 is a schematic structural diagram of a stator core of a motor according to another embodiment of the present application.

(19) FIG. 19 is a schematic exploded view of a stator core of a motor according to another embodiment of the present application.

(20) FIG. 20 is a schematic front view of a first core punching sheet according to another embodiment of the present application.

(21) FIG. 21 is a schematic perspective view of a first core punching sheet according to another embodiment of the present application.

(22) FIG. 22 is a schematic front view of a second core punching sheet according to another embodiment of the present application.

(23) FIG. 23 is a schematic perspective view of a second core punching sheet according to another embodiment of the present application;

(24) FIG. 24 is a schematic structural diagram of a motor according to another embodiment of the present application.

(25) FIG. 25 is a schematic structural diagram of a stator core of a motor according to another embodiment of the present application.

(26) FIG. 26 is a schematic exploded view of a stator core of a motor according to another embodiment of the present application.

(27) FIG. 27 is a schematic front view of a stator core according to another embodiment of the present application.

(28) FIG. 28 is a schematic structural diagram of a housing according to an embodiment of the present application.

(29) FIG. 29 is a schematic structural diagram of an oil slinger according to an embodiment of the present application.

DETAILED DESCRIPTION

(30) At present, most of power conversion devices of new energy vehicles rely on motors for energy conversion. Electrical energy is converted into mechanical energy or mechanical energy is

converted into electrical energy. Therefore, its advanced technology plays an important role in development of automobiles. In limited space of an automobile, size and weight of a motor affect power performance, cost and vehicle type. Especially, a volume size of the motor is the most sensitive.

(31) According to the different cooling media, the existing cooling technologies for automobile motors may be divided into natural cooling, air cooling, water cooling and oil cooling, wherein the oil cooling has the highest heat exchange efficiency, and at present, most cooling schemes for automobile motors adopt oil cooling. The oil cooling system improves heat dissipation capacity of the motor and protects insulating materials. With the same power, the volume size of a motor with oil cooling can be smaller, such a motor is convenient to be arranged and carried by the whole vehicle, and costs can also be reduced.

(32) Herein, oil cooling for a stator is performed by manners such as sprinkling oil on a surface and passing oil inside the stator core. These manners have limited heat dissipation area and average heat dissipation performance. The cooling effect is the preferred in a case that multiple axial oil grooves are formed on an outer side wall of a stator core and a cooling liquid is sprayed on an end winding of the stator after cooling the stator core. An advantage of such method is that of the multiple oil grooves is formed in an axial direction of the stator core, so that the heat dissipation area of the stator core is greatly increased.

(33) The motor according to the embodiment of the present application further taps the potential of the motor with oil cooling thus a more effective cooling mechanism is designed.

(34) In the cooling technologies for machine motor, since the cooling efficiency of oil is higher than that of other cooling media, in the embodiment of the present application, the cooling fluid and a liquid entering a flow channel (i.e., a slit flow channel) refer to the cooling oil. It may be understood that the cooling fluid is not limited to the cooling oil, but may also be other cooling media with insulating characteristics.

(35) Principles and features of the embodiments of the present application are described below with reference to the accompanying drawings, while the examples given are intended to explain the embodiments of the present application only and are not intended to limit the scope of the present application.

(36) As shown in FIG. 1 and FIG. 2, an embodiment of the present application provides a motor including a casing 1, a stator core 2, a stator winding 3 (or winding coil), and a rotor 4.

(37) Among them, the stator core 2 is fixed in the casing 1. A slit flow channel is formed between the outer side wall of the stator core 2 and the inner side wall of the casing 1. The slit flow channel is provided as a network-shaped cooling flow channel 22 for the cooling fluid to flow, as shown in FIG. 5 to FIG. 8. The rotor 4 is rotatably sleeved inside the stator core 2.

(38) Stator winding 3 is assembled with the stator core 2. The stator winding 3 may be made of enameled round copper wire or enameled flat copper wire wound according to motor winding rules. In a specific embodiment of the present application, the winding coil is made of enameled flat copper wire. The stator winding 3 is fixedly disposed in a cogging groove 25 of the stator core 2, and a portion of the stator winding 3 beyond the end face of the stator core 2 is defined as an end winding, wherein the end winding includes a front end winding 31 and a rear end winding 32, as shown in FIG. 2.

(39) The motor according to the embodiment of the present application includes a casing 1, a stator core 2, a stator winding 3, a rotor 4 and the like. The stator core 2 is sleeved outside the rotor 4, and the casing 1 is sleeved outside the stator core 2. The rotor 4 may be sleeved outside a rotating shaft 5, wherein the rotating shaft 5 may be configured to pass through the casing 1 and supported by the casing 1, the rotor 4 and the rotating shaft 5 are fixedly connected with each other, and the rotor 4 and the rotating shaft 5 are rotatable relative to the casing 1. Alternatively, a shaft sleeve is disposed between the rotating shaft 5 and the rotor 4, the rotating shaft 5 is fixedly connected with the casing 1, the rotor 4 is fixedly connected with the shaft sleeve, and the shaft sleeve is rotatable

relative to the rotating shaft 5. During operation of the motor, the stator winding 3 is electrified to generate an exciting magnetic field, and then energy conversion occurs to output mechanical energy or generate electricity. The stator winding 3 will generate a huge amount of resistance heat while energy conversion occurs. If the resistance heat cannot be dissipated away in time, a temperature of the stator winding 3 will rise rapidly, which will destroy an insulation system of the motor and causes the motor to be burnt. The embodiment of the present application is also devoted to improving heat dissipation capability of the stator winding 3 and improving performance of the motor.

(40) For this regard, in this scheme, a slit flow channel is formed between an outer side wall of the stator core 2 and an inner side wall of the casing 1, wherein the slit flow channel is in the form of a network-shaped cooling flow channel 22. Therefore, a cooling fluid (such as cooling oil) may enter the network-shaped cooling flow channel 22 to exchange heat with the stator core 2, and the stator core 2 also exchanges heat with the stator winding 3, thus ensuring that the cooling fluid can take away the heat of the stator core 2 and the stator winding 3, thereby bringing an effect of reducing temperatures of the stator core 2 and the stator winding 3 and cooling the motor.

(41) Compared with the scheme in which multiple axial oil grooves are formed on the outer side wall of the stator core 2, the network-shaped cooling flow channel 22 of this scheme has a larger heat dissipation surface area, which is conducive to further improving the heat dissipation capacity of the motor. In addition, a flow path of the cooling fluid in the network-shaped cooling flow channel 22 is also network-shaped, and a flow form of the cooling fluid in the network-shaped path is turbulent, so that the heat exchange efficiency of the turbulent flow is higher, and thus the heat dissipation capacity of the motor can be further improved.

(42) In the principle of the motor, the stator core 2 mainly functions as a fixed support for the winding coil, a magnetic circuit path and conduction for the resistance heat of the winding coil. In the embodiment of the present application, the heat generation and conduction path of the motor is as follows: operation of the stator winding 3 generates a large amount of resistance heat Q_1 , and the temperature reaches t_1 , the stator core 2 generates heat Q_2 under the action of an alternating magnetic field, and the temperature reaches t_2 . Since $t_1 > t_2$, heat conduction occurs between stator winding 3 and stator core 2, so that the temperature of the stator core 2 rises to t_3 . The cooling oil having a temperature of t_4 enters the network-shaped cooling flow channel 22 to exchange heat with the stator core 2, and the temperature of the stator core 2 is reduced to t_5 . Thus, the stator winding 3 of the motor is kept below an extreme temperature for a long period of time by the continuous circulation of the cooling oil in a low temperature.

(43) In an exemplary embodiment, multiple heat dissipation protrusions 21 are provided on the inner side wall of the casing 1, or on the outer side wall of the stator core 2, or on the inner side wall of the casing 1 and the outer side wall of the stator core 2, as shown in FIG. 3. As shown in FIG. 4 and FIG. 5, multiple heat dissipation protrusions 21 are staggeredly disposed in a network form, thus the slit flow channel are divided into the network-shaped cooling flow channel 22.

(44) Thus, the casing 1, or the stator core 2, or the casing 1 and the stator core 2 are processed into the desired shape during a manufacturing process, and then the casing 1 and the stator core 2 are assembled together to obtain the network-shaped cooling flow channel 22, without need of increasing the number of components, while assembling processes thereof are relatively simple.

(45) Herein, the heat dissipation protrusions 21 may be provided only on the inner side wall of the casing 1, or only on the outer side wall of the stator core 2 (as shown in FIG. 3), or partially on the inner side wall of the casing 1 and partially on the outer side wall of the stator core 2.

(46) In a case that the heat dissipation protrusions 21 are provided on the inner side wall of the casing 1, the casing 1 may be made of a windable material. Therefore, the heat dissipation protrusions 21 are processed on a flat plate, and then the flat plate structure is wound and fixed into a cylindrical structure by a process such as welding. In this way, the manufacturing processes of the casing 1 can be simplified, which facilitates batch production.

(47) A shape of each heat dissipation protrusion **21** is not limited and may be in a shape of a post, a rod, a plate, a block or the like.

(48) In one example, each heat dissipation protrusion **21** is a post structure, in this case, the heat dissipation protrusions **21** may be referred to as heat dissipation posts **211** as shown in FIG. 4. A specific shape of the heat dissipation post **211** may be, but is not limited to, a prism (such as a quadrangular prism, as shown in FIG. 4), a cylinder, an elliptical post, a semi-cylinder, a pyramid, a circular cone, an irregular shape, or the like.

(49) In an exemplary embodiment, multiple heat dissipation protrusions **21** are provided on the outer side wall of the stator core **2**, at least part of the heat dissipation protrusions **21** are against the inner side wall of the casing **1**, or all of the heat dissipation protrusions **21** may be against the inner side wall of the casing **1**, as shown in FIG. 1 and FIG. 2, so that the stator core **2** and the casing **1** are interference fitted.

(50) The heat dissipation protrusions **21** are provided on the outer side wall of the stator core **2**, so that a heat dissipation surface area of the stator core **2** can be significantly increased, thus the heat dissipation capability of the stator core **2** is improved. Moreover, the heat dissipation protrusions **21** of the stator core **2** are against the inner side wall of the casing **1**, thereby implementing the interference fit between the stator core **2** and the casing **1** and further implementing the fixed assembling between the stator core **2** and the casing **1**. During the assembling, the interference fit between the stator core **2** and the casing **1** can be achieved by using a hot sleeve process.

(51) In an exemplary embodiment, the stator core **2** includes multiple core assemblies **23** that are mutually stacked in the axial direction of the stator core **2**, as shown in FIG. 14. Each core assembly **23** is provided with multiple heat dissipation protrusions **21** spaced apart along its circumferential direction, as shown in FIG. 13, the heat dissipation protrusions **21** of adjacent core assemblies **23** are staggeredly arranged along the circumferential direction of the stator core **2**.

(52) This scheme means to divide the stator core **2** into multiple core assemblies **23** along its axial direction, wherein each of the multiple core assemblies **23** has an annular structure and each of the multiple core assemblies **23** is provided with multiple heat dissipation protrusions **21** along its circumferential direction. The stator core **2** with a novel structure (the outer side wall is provided with multiple heat dissipation protrusions **21** staggeredly arranged in a network-shaped form) is formed by stacking the multiple core assemblies **23** by misplaced stacking.

(53) Since the number of the heat dissipation protrusions **21** on the whole stator core **2** is very large, dividing the stator core **2** into multiple core assemblies **23** can greatly simplify the structure of each single core assembly **23**, and facilitate the production and processing of the single core assembly **23**, and further reduce the processing difficulty of components. Subsequently, the heat dissipation protrusions **21** staggeredly arranged in a network-shaped form may be obtained simply by misplaced assembling (as shown in FIG. 13 and FIG. 14). Compared with directly processing the heat dissipation protrusions **21** arranged in a network shape, this scheme can greatly reduce the processing difficulty of the stator core **2**. Moreover, by adjusting the number of the core assemblies **23**, a dimension of the stator core **2** in the axial direction can be adjusted, and various choices can be achieved, which is conducive to meeting requirements of different products.

(54) In an exemplary embodiment, a core assembly **23** is formed by stacking multiple stator punching sheets **24**. Each stator punching sheet **24** is provided with multiple heat dissipation teeth **241**, as shown in FIG. 15 and FIG. 16. Heat dissipation teeth **241** corresponding to the multiple stator punching sheets **24** are stacked to form the heat dissipation protrusions **21**.

(55) Compared with directly producing the core assembly **23** with a large thickness, the relatively thin stator punching sheets **24** are easier to be processed. Therefore, in this scheme, the core assembly **23** is formed by stacking of the multiple stator punching sheets **24**, and the heat dissipation protrusions **21** are formed by stacking the heat dissipation teeth **241** of the stator punching sheets **24**, so that the processing difficulty of the stator core **2** can be further reduced and the manufacturing costs can be further reduced.

(56) In addition, by adjusting the number of the stator punching sheets **24**, the thickness of the core assembly **23** may be adjusted, and then a dimension of the stator core **2** in the axial direction may be adjusted. Multiple core assemblies **23** of the same stator core **2** may also have different thicknesses, and then fine adjustment may be made the dimension of the stator core **2** in the axial direction may, which can further increase diversified choices and contribute to further meet the requirements of different products.

(57) In an actual design and manufacturing process, according to computer fluid dynamics simulation (CFD for short) analysis and simple consideration of working procedures, the scheme suitable for each motor system can be obtained.

(58) In an exemplary embodiment, the number and distribution of the heat dissipation protrusions **21** on the multiple core assemblies **23** are identical. Multiple heat dissipation protrusions **21** on each core assembly **23** are evenly divided into multiple heat dissipation groups. Each heat dissipation group includes at least one heat dissipation protrusion **21**.

(59) In this way, only one set of stator punching die is required to obtain various stator cores **2** with different specifications, which changes the present situation in the prior art that stator cores **2** require various punching dies, therefore reducing the manufacturing cost of the stator cores **2**.

(60) In an exemplary embodiment, the stator core **2** is provided with multiple cogging grooves **25** along its circumferential direction for mounting the stator winding **3**, as shown in FIG. **14**. The number of the cogging grooves **25** is an integer multiple of the number of the heat dissipation groups of each core assembly **23**.

(61) Thus, in a case that two adjacent core assemblies **23** are stacked, an angle misplaced along the circumferential direction is an integral multiple of an included angle between center lines of adjacent two cogging grooves **25**, which not only facilitates an accurate alignment of the core assemblies **23** when they are mutually stacked, but also ensures that the cogging grooves **25** of the adjacent core assemblies **23** still coincide with each other in the axial direction after stacking. Thus, by the misplaced stacking assembling, the heat dissipation protrusions **21** staggeredly arranged in a network-shaped form may be obtained without affecting the stacking of the cogging grooves **25** of the stator core **2**.

(62) In one example, the number of the cogging grooves **25** is twice of the number of the heat dissipation groups of each core assembly **23**, as may be seen with reference to FIG. **15** and FIG. **16**. In other words, for each core assembly **23**, the number of the heat dissipation groups is a half of the number of the cogging grooves **25**.

(63) This scheme not only does not affect the misplaced stacking assembling of the stator core **2**, but also ensures that the stator core **2** has a considerable number of heat dissipation posts **211** and simulation results prove its good heat dissipation effect.

(64) In an exemplary embodiment, each heat dissipation group includes multiple heat dissipation protrusions **21** spaced apart along the circumferential direction of the core assembly **23**. A circumferential spacing between adjacent heat dissipation groups is larger than a circumferential spacing between adjacent heat dissipation protrusions **21** in each heat dissipation group, as may be seen with reference to FIG. **15** and FIG. **16**.

(65) In this way, the spacing between two adjacent heat dissipation groups may be exactly used for aligning the heat dissipation groups of the adjacent core assemblies **23**, which is conducive to serving a certain function in marking and positioning when the core assemblies **23** are stacked.

(66) In an exemplary embodiment, each heat dissipation group includes multiple heat dissipation posts **211** spaced apart along the circumferential direction of the core assembly **23**. In each heat dissipation group, one of the heat dissipation protrusions **21** is provided as a positioning protrusion **212**, wherein a shape of the positioning protrusion **212** is different from other heat dissipation protrusions **21**, as shown in FIG. **4**.

(67) In this way, the adjacent core assemblies **23** may be rotated with reference to the positioning protrusions **212** during the misplaced stacking assembling, thereby achieving rapid and accurate

stacking of the core assemblies **23**.

(68) In one example, in each heat dissipation group, a sectional area of one of the heat dissipation protrusions **21** is larger than that of the other heat dissipation protrusions **21**, as shown in FIG. **4**.

(69) Thus, the heat dissipation protrusion **21** with the larger sectional area is the positioning protrusion **212**, which serves in positioning in addition to increasing the heat dissipation surface area of the stator core **2**, thus facilitating rapid and accurate stacking of the core assembly **23**.

(70) In one example, each heat dissipation group includes three heat dissipation protrusions **21**. Among them, the three heat dissipation protrusions **21** are distributed in a form of “large-small-small” (as shown in FIG. **4**), and may also be distributed in a form of “small-large-large” or “small-large-small”.

(71) In one example, an included angle α is formed between center lines of two adjacent cogging grooves **25**. A center line of the heat dissipation protrusion **21** with the larger sectional area passes through an angular bisector of α , as shown in FIG. **15** and FIG. **16**.

(72) In an exemplary embodiment, as shown in FIG. **1**, FIG. **2** and FIG. **10**, the casing **1** is further provided with an input channel **11** and at least one input hole **12** communicated with the input channel **11**. The input channel **11** is located radially outside the network-shaped cooling flow channel **22** and communicated with the network-shaped cooling flow channel **22** through at least one input hole **12** for inputting cooling fluid to the network-shaped cooling flow channel **22**. This facilitates the network-shaped cooling flow channel **22** to access the cooling flow path through the input channel **11**, thereby indirectly communicated with a low-temperature cooling fluid supply source (e.g. a cooling oil pool).

(73) As shown in FIG. **2** and FIG. **10**, the casing **1** is further provided with an output channel **13** and at least one first output hole **14** communicated with the output channel **13**. The output channel **13** is located radially outside the network-shaped cooling flow channel **22** and communicated with the network-shaped cooling flow channel **22** through the at least one first output hole **14** for outputting the cooling fluid discharged from the network-shaped cooling flow channel **22**. This facilitates the network-shaped cooling flow channel **22** to access and join an external cooling flow path through the output channel **13**, so as to be indirectly communicated with a cooling fluid collection device (such as an oil cooler).

(74) In one example, the number of input holes **12** is plural, as shown in FIG. **10**, and the multiple input holes **12** are provided at intervals along the axial direction of the stator core **2**. This facilitates the cooling fluid in the input channel **11** to rapidly enter the network-shaped cooling flow channel **22** from multiple positions, and improves uniformity of distribution of the cooling fluid in the network-shaped cooling flow channel **22**, thereby further improving the heat dissipation effect.

(75) The number of the first output holes **14** is plural, as shown in FIG. **10**, the multiple first output holes **14** are provided at intervals along the axial direction of the stator core **2**. This facilitates the cooling fluid of the network-shaped cooling flow channel **22** to flow into the output channel **13** from multiple positions, and the problem of local discharge blind angle in the network-shaped cooling flow channel **22** is avoided, which is conducive to further improving the heat dissipation effects.

(76) In an exemplary embodiment, the input channel **11** and the input hole **12** are provided at the top of the casing **1**, as shown in FIG. **1**, FIG. **7** and FIG. **10**, so that the input channel **11** is located above the network-shaped cooling flow channel **22**.

(77) The output channel **13** and a first output hole **14** are provided at the bottom of the casing **1**, as shown in FIG. **1**, FIG. **7** and FIG. **10**, so that the output channel **13** is located below the network-shaped cooling flow channel **22**.

(78) This facilitates the cooling fluid (such as cooling oil) in the input channel **11** to enter the network-shaped cooling flow channel **22** through the input hole **12** under the action of gravity, and flows downward along the network-shaped cooling flow channel **22** under the action of gravity, and is discharged through the output channel **13** at the bottom after heat exchange with the whole

stator core **2**. Therefore, this scheme is advantageous for the cooling fluid to cover the whole stator core **2**, thereby improving the heat dissipation effect and reducing power requirement on the power source (such as an oil pump) used for driving the cooling fluid to flow.

(79) In an exemplary embodiment, portions of two ends of the stator winding **3** protruding out of the stator core **2** are defined as end windings.

(80) The casing **1** is provided with an open end. The motor further includes an end cap **6** provided at the open end, as shown in FIG. **1** and FIG. **2**. The end cap **6** is provided with a first heat dissipation groove **61**, as shown in FIG. **11**. The first heat dissipation groove **61** communicates with the network-shaped cooling flow channel **22**. A bottom wall of the first heat dissipation groove **61** is provided with a first waterfall-spray slit **62** at a position corresponding to the end winding, as shown in FIG. **11**, for spraying a cooling fluid to the end winding corresponding to the first waterfall-spray slit **62**.

(81) The end cap **6** is further provided with a second output hole **63**, as shown in FIG. **1** and FIG. **11**. The second output hole **63** is configured to be in communication with the external cooling flow path for discharging the cooling fluid flowing through the end winding corresponding to the first waterfall-spray slit **62** into the external cooling flow path.

(82) In this way, one branch divided from the cooling fluid in the network-shaped cooling flow channel **22** may enter the first heat dissipation groove **61** and be sprayed to the end winding like a waterfall through the first waterfall-spray slit **62**. Compared with the conventional way of spraying cooling oil at multiple points, in this scheme oil sprinkling in a form of waterfall may be used for cooling the end winding, which covers a larger area of the end winding and achieves a more uniform cooling effect. The cooling oil after heat exchange with the end winding may be discharged from the casing **1** through the second output hole **63**.

(83) In one example, the second output hole **63** is provided at the bottom of the end cap **6**, as shown in FIG. **1**, to facilitate the cooling fluid to be collected in the second output hole **63** under the action of gravity and then discharged into the external cooling flow path.

(84) In one example, the casing **1** and the end cap **6** are assembled by nested centring and connecting parts. The inner side wall of the casing **1** is provided with a first supporting surface **171**, as shown in FIG. **10**. The first support surface **171** is perpendicular to the axial direction of the stator core **2**. The end cap **6** includes a cap body **64** and an annular flange **65**, as shown in FIG. **11**. The cap body **64** is against the open end of the casing **1**. One end of the annular flange **65** is connected with the cover **64**, and the other end of the annular flange **65** is against the first support surface **171**. Moreover, an end of the annular flange **65** that abuts against the first supporting surface **171** protrudes inward from the first supporting surface **171** in the radial direction of the stator core **2** and abuts against the end face of the stator core **2** to block an end of the network-shaped cooling flow channel **22** facing the end cap **6**. The first heat dissipation groove **61** is provided on an outer side wall of the annular flange **65** and extends across one end of the annular flange **65** away from the cap body **64** along the axial direction of the stator core **2**, so that the first heat dissipation groove **61** communicates with the network-shaped cooling flow channel **22**.

(85) Thus, one end of the network-shaped cooling flow channel **22** facing the end cap **6** is blocked by the end cap **6** at other positions in the circumferential direction except the position where the first heat dissipation groove **61** is located. The first heat dissipation groove **61** and the inner side wall of the casing **1** form the cooling flow channel on the end cap **6**. Therefore, one branch divided from the cooling fluid flowing through the network-shaped cooling flow channel **22** enters the first heat dissipation groove **61**, and is sprayed to an oil curtain through the first waterfall-spray slit **62** to the corresponding end winding in a form similar, so as to efficiently and uniformly dissipate heat from the end winding. The cooling fluid after the heat exchange with the end winding cannot flow back to the network-shaped cooling flow channel **22**, but is discharged into the external cooling flow path through the second output hole **6**.

(86) In an exemplary embodiment, the number of the open end is one. The motor further includes a

waterfall-spray heat dissipation ring 7, as shown in FIG. 1 and FIG. 2. The waterfall-spray heat dissipation ring 7 is sleeved in the casing 1 and is located at one end of the casing 1 away from the open end.

(87) The waterfall-spray heat dissipation ring 7 is provided with a second heat dissipation groove 71, as shown in FIG. 12. The second heat dissipation groove 71 communicates with the network-shaped cooling flow channel 22. A bottom wall of the second heat dissipation groove 71 is provided with a second waterfall-spray slit 72 at a position corresponding to the end winding, as shown in FIG. 12, for spraying cooling fluid to the end winding corresponding to the second heat dissipation groove 71.

(88) The casing 1 is further provided with a third output hole 15, as shown in FIG. 10, which is configured to be communicated with the external cooling flow path for discharging the cooling fluid flowing through the end winding corresponding to the second waterfall-spray slit 72 into the external cooling flow path.

(89) In one example, the third output hole 15 communicates with the output channel 13 for discharging cooling fluid flowing through the end winding corresponding to the second waterfall-spray slit 72 into the output channel 13. In other words, the third output hole 15 is indirectly communicated with the external cooling flow path through the output channel 13.

(90) In this way, one branch divided from the cooling fluid in the network-shaped cooling flow channel 22 may enter the second heat dissipation groove 71 and be sprayed through the second waterfall-spray slit 72 to the end winding on this side like a waterfall. Compared with the conventional way of spraying cooling oil at multiple points, in this scheme, oil sprinkling in a form of waterfall may be used for cooling the end winding on this side, which covers a larger area of the end winding and achieves a more uniform cooling effect. The cooling oil after the heat exchange with the end winding may enter the output channel 13 of the casing 1 through the third output hole 15 and be discharged from the casing 1.

(91) Compared with the end cap 6, the waterfall-spray heat dissipation ring 7 has lower manufacturing cost and simpler assembling procedure. Therefore, compared with the scheme in which two open ends are formed at two ends of the casing 1 and two end caps 6 are correspondingly provided, one end cap 6 and the assembling process between the end cap 6 and the casing 1 may be omitted in this scheme, which is conducive to reducing the manufacturing cost of the motor. Apparently, it is also possible to provide two open ends at two ends of the casing 1 and correspondingly provide two end caps 6, wherein each end cap 6 is provided with a first heat dissipation groove 61 and a first waterfall-spray slit 62, so as to efficiently and uniformly dissipate heat from the two end windings.

(92) In one example, the third output hole 15 is provided at the bottom of the casing 1, as shown in FIG. 10, to facilitate collecting cooling fluid in the third output hole 15 under the action of gravity, and then discharging the cooling fluid into the output channel 13.

(93) In one example, the casing 1 and the waterfall-spray heat dissipation ring 7 are fitted by hot sleeve. As shown in FIG. 10, the inner side wall of the casing 1 is provided with a second supporting surface 172, wherein the second supporting surface 172 is perpendicular to the axial direction of the stator core 2. One end of the waterfall-spray heat dissipation ring 7 abuts against the second supporting surface 172, and the other end of the waterfall-spray heat dissipation ring 7 abuts against the end face of the stator core 2 to block one end of the network-shaped cooling flow channel 22 facing the waterfall-spray heat dissipation ring 7. As shown in FIG. 12, the second heat dissipation groove 71 is provided on an outer side wall of the waterfall-spray heat dissipation ring 7, and extends across one end of the waterfall-spray heat dissipation ring 7 close to the stator core 2 along the axial direction of the stator core 2, so that the second heat dissipation groove 71 communicates with the network-shaped cooling flow channel 22.

(94) Thus, the end of the network-shaped cooling flow channel 22 facing the waterfall-spray heat dissipation ring 7 is blocked by the waterfall-spray heat dissipation ring 7 at other positions in the

circumferential direction except the position where the second heat dissipation groove **71** is located. The second heat dissipation groove **71** and the inner side wall of the casing **1** form the cooling flow channel on the waterfall-spray heat dissipation ring **7**. Therefore, one branch divided from the cooling fluid flowing through the network-shaped cooling flow channel **22** enters the second heat dissipation groove **71**, and is sprayed through the second waterfall-spray slit **72** to the corresponding end winding in a form similar to an oil curtain, so as to efficiently and uniformly dissipate heat from the end winding.

(95) In an exemplary embodiment, the number of the first water-spray slit **62** is one, as shown in FIG. **12**, the first waterfall-spray slit **62** is provided at the top of the end cap **6** and extends along the circumferential direction of the end cap **6**, wherein a radian of the first waterfall-spray slit **62** is in a range of 40° to 180° , so as to ensure that the cooling fluid sprayed from the first waterfall-spray slit **62** may cover the upper portion of the end winding in a large area, and then cover the middle and lower portions of the end winding under the action of gravity. In this scheme, only a relatively short first heat dissipation groove **61** and a first waterfall-spray slit **62** need to be provided, so that the structure of the end cap **6** can be simplified, which facilitates improving the strength of the end cap **6**.

(96) Alternatively, the number of the first waterfall-spray slits **62** is a plural and the multiple the first waterfall-spray slits **62** are provided at intervals along the circumferential direction of the end cap **6**. In this scheme, cooling fluid in a form of water fall may be sprayed to the end winding from many different positions, which is conducive to improving the heat dissipation effect on the end winding.

(97) Alternatively, the number of the first waterfall-spray slit **62** is one, and the first waterfall-spray slit **62** is provided around the end cap **6** along the circumferential direction of the end cap **6**. In this scheme, the cooling fluid may be sprayed to the end winding in 360° from all positions, which is conducive to improving the heat dissipation effect for the end winding.

(98) During manufacturing, the number, size and distribution form of the first waterfall-spray slit **62** and the first heat dissipation groove **61** may be reasonably selected according to requirements of different motor systems.

(99) Apparently, the number, size and distribution form of the first waterfall-spray slit **62** and the first heat dissipation groove **61** are not limited thereto, and may be reasonably adjusted as required.

(100) Similarly, as shown in FIG. **11**, the number of the second waterfall-spray slit **72** is one, and the second waterfall-spray slit **72** is provided at the top of the waterfall-spray heat dissipation ring **7** and extends along the circumferential direction of the waterfall-spray heat dissipation ring **7**, wherein a radian of the second waterfall-spray slit **72** is in a range of 40° to 180° .

(101) Alternatively, the number of second waterfall-spray slits **72** is plural, and the multiple the second waterfall-spray slits **72** are provided at intervals along the circumferential direction of the waterfall-spray heat dissipation ring **7**.

(102) Alternatively, the number of the second waterfall-spray slit **72** is one, and the second waterfall-spray slit **72** is provided around the waterfall-spray heat dissipation ring **7** along the circumferential direction of the waterfall-spray heat dissipation ring **7**.

(103) Design principle and effect of the second waterfall-spray slit **72** are the same as those of the first waterfall-spray slit **62**, which will not be described herein.

(104) In an exemplary embodiment, the motor further includes an oil cooling mechanism (not shown in figures) for the motor in communication with the network-shaped cooling flow channel **22** for supplying cooling oil to the network-shaped cooling flow channel **22** and recycling the cooling oil discharged from the network-shaped cooling flow channel **22**.

(105) In this scheme, the motor has an independent oil cooling mechanism, which can achieve cooling and heat dissipation without relying on other structures. The oil cooling mechanism for the motor may be integrated at the bottom of the casing **1**.

(106) In one example, the oil cooling mechanism for the motor includes a cooling oil pool, an oil

cooler, and an oil pump.

(107) Among them, the cooling oil pool is communicated with the network-shaped cooling flow channel for supplying the cooling oil to the network-shaped cooling flow channel **22**. The oil cooler is communicated with the network-shaped cooling flow channel **22** and the cooling oil pool, and is used for cooling the cooling oil discharged from the network-shaped cooling flow channel **22** and conveying it back to the cooling oil pool. The oil pump is used for driving the cooling oil to circulate between the cooling oil pool, the network-shaped cooling flow channel **22** and the oil cooler.

(108) In one specific embodiment, the motor includes a motor body and a cooling mechanism (as shown in FIG. **6**).

(109) As shown in FIG. **1** and FIG. **2**, the motor body includes a rotating shaft **5**, a rotor **4** fixedly sleeved on a rotating shaft **5**, a stator core **2** sleeved outside the rotor **4** with clearance, a stator winding **3** mounted on the stator core **2**, a casing **1** fixedly sleeved outside the stator core **2** for accommodating the above-mentioned components, a waterfall-spray heat dissipation ring **7** sleeved in the casing **1** and abutting an end face of the stator core **2**, and an end cap **6** mounted at an open end of the casing **1** for sealing an inner cavity of the motor and supporting the rotating shaft **5**. Among them, stator winding **3** extends from two ends of the stator core **2** to form a front end winding **31** and a rear end winding **32** respectively.

(110) As shown in FIG. **3**, FIG. **4**, and FIG. **6**, the cooling mechanism includes a large number of heat dissipation posts **211** provided on an outer side wall of the stator core **2** in a staggered arrangement. As shown in FIG. **4**, the heat dissipation posts **211** cuts the cylindrical surface of the outer side wall of the stator core **2** into a lower concave surface **26**, heat dissipation post side wall surfaces **2111**, and heat dissipation post top surfaces **2112**. The heat dissipation post top surfaces **2112** are attached to the inner wall of the casing **1**, and the lower concave surface **26** forms a slit flow channel with the inner wall of the casing **1**. The slit flow channel is cut by the heat dissipation posts **211** to form a network-shaped cooling flow channel **22**, as shown in FIG. **6**. During operation, the lower concave surface **26** of the stator core **2** and the heat dissipation post side wall surfaces **2111** both participate in heat conduction as heat exchange surfaces, as shown in FIG. **5**.

(111) As shown in FIG. **6** and FIG. **10**, the cooling mechanism further includes: an input channel **11** and multiple input holes **12** arranged along an axial direction at the top of the casing **1**, an output channel **13** and multiple first output holes **14** arranged along the axial direction at the bottom of the casing **1**, and a third output hole **15** arranged at the bottom of the casing **1** and located below the waterfall-spray heat dissipation ring **7**.

(112) As shown in FIG. **6** and FIG. **11**, the cooling mechanism further includes: a first heat dissipation groove **61** provided at an upper portion of the centring and connecting part of the end cap **6**, a first waterfall-spray slit **62** provided at a bottom wall of the first heat dissipation groove **61** and extending along the circumferential direction, and a second output hole **63** provided at the bottom of the end cap **6**.

(113) As shown in FIG. **6** and FIG. **12**, the cooling structure further includes: a second heat dissipation groove **71** provided on the waterfall-spray heat dissipation ring **7**, and a second heat waterfall-spray slit **72** provided on a bottom wall of the second heat dissipation groove **71** and extending along the circumferential direction.

(114) Herein, the input channel **11** is communicated with the input holes **12**, and the input holes **12** are communicated with the top of the network-shaped cooling flow channel **22**. A front end of the network-shaped cooling flow channel **22** is communicated with the second heat dissipation groove **71**, and a rear end of the network-shaped cooling flow channel **22** is communicated with the first heat dissipation groove **61**. The bottom of the network-shaped cooling flow channel **22** is communicated with the first output holes **14**, and the first output holes **14** are communicated with the output channel **13**. The third output hole **15** is communicated with the output channel **13**. The output channel **13** and the second output hole **63** are respectively connected to the cooling flow

path.

(115) In the embodiment of the present application, with the structural design of the heat dissipation posts **211**, the heat dissipation surface area of the stator core **2** is far larger than the original cylindrical outer surface. In principle, a larger number of the heat dissipation posts **211** will be more conducive to the heat dissipation of the stator core **2**. However, too many heat dissipation posts **211** cause the network-shaped cooling flow channel **22** to become more densely divided and hinder flowing of the cooling oil. Moreover, the large number of the heat dissipation posts **211** also causes each single heat dissipation post **211** to become smaller, which increases difficulty in the manufacturing processes of the stator punching sheets **24** and the stator core **2**. Therefore, in the embodiment of the present application, the number and height of the heat dissipation posts **211** are comprehensive fluid simulation results with flow resistance factors of the cooling oil taken into consideration.

(116) The aforementioned components are described separately in the following.

(117) As shown in FIG. 3, the stator core **2** has a hollow cylindrical shape in appearance. Stator cogging grooves **25** are uniformly provided in the circumferential direction of its inner diameter, with a number of the stator cogging grooves being $N1$. A main function of the stator cogging grooves **25** is to fix and support the winding coil. At the same time, during operation of the motor, resistance heat of the winding coil is transmitted to the stator core **2** through surfaces of the stator cogging grooves **25**.

(118) The stator core **2** is assembled by mutually and staggeredly stacking K core assemblies **23**, as shown in FIG. 13 and FIG. 14. $N2$ heat dissipation posts **211** are circumferentially provided on outer surface of the core assemblies **23**. The $N2$ heat dissipation posts **211** are equally divided into $N\frac{1}{2}$ heat dissipation groups, wherein each heat dissipation group includes A heat dissipation posts **211**. The stator core **2** is assembled by the performing misplaced stacking on the core assemblies **23**, so that the heat dissipation posts **211** of the adjacent core assemblies **23** are mutually staggered to form the stator core **2** in which the final heat dissipation posts **211** are staggeredly arranged.

(119) Due to the misplaced stacking of the core assemblies **23**, the number of the heat dissipation posts **211** in different manufacturing stages satisfies the following relationship:

$$D=N2\times P; N2=N1\times A\times\frac{1}{2}; A=1,2,3$$

(120) where D is the number of heat dissipation posts **211** of the stator core **2**, P is the number of the core assemblies **23**, $N2$ is the number of heat dissipation posts **211** of each core assembly **23**, $N1$ is the number of the stator cogging grooves **25**, and A is the number of heat dissipation posts **211** included in each heat dissipation group.

(121) A core assembly **23** includes U stator punching sheets **24**, as shown in FIG. 15. A stator punching sheet **24** is punched from electrical steel with a thickness of t. $N2$ heat dissipation teeth **241** are provided on an outer diameter of each stator punching sheet **24**, as shown in FIG. 16. The U stator punching sheets **24** are stacked and pressed axially at a same angle to form a core assembly **23** with a thickness of $Y=U\times T$. The heat dissipation teeth **241** of the stator punching sheets **24** are also changed into heat dissipation posts **211** after multiple sheets are stacked.

(122) The thickness of the core assembly **23** may not be unique. The thickness of a single core assembly **23** is calculated by multiplying the thickness of the stator punching sheets **24** by the number of the sheets. By selecting the number of the stator punching sheets **24**, the thickness adjustment of the core assembly **23** can be realized. Therefore, the stator core **2** composed of core assemblies **23** with different thicknesses may be obtained, thereby achieving diversified choices. Finally, by computer fluid dynamics simulation (CFD for short) analysis and simple consideration of working procedures, a better scheme for each motor system can be obtained.

(123) As shown in FIG. 1 and FIG. 2, the end cap **6** is provided at a rear end of the casing **1**, and a corresponding end winding is the rear end winding **32**. As shown in FIG. 11, the top of the end cap **6** is provided with a first heat dissipation groove **61** and a first waterfall-spray slit **62**, and the bottom of the end cap **6** is provided with a second output hole **63**. As shown in FIG. 1 and FIG. 2,

the waterfall-spray heat dissipation ring 7 is provided at the front end of the casing 1, and a corresponding end winding is the front end winding 31. As shown in FIG. 12, the top of the waterfall-spray heat dissipation ring 7 is provided with a second heat dissipation groove 71 and a second waterfall-spray slit 72. As shown in FIG. 10, the bottom of the casing 1 is provided with a third output hole 15. The end cap 6 is provided with a first support hole 66, as shown in FIG. 11. The front end of the casing 1 is provided with a second support hole 18, as shown in FIG. 10. Two ends of the rotating shaft 5 are rotatably inserted in the first support hole 66 and the second support hole 18 respectively, as shown in FIG. 1 and FIG. 2.

(124) As shown in FIG. 10, the input channel 11 is provided at the top of the casing 1 and an inlet of the input channel 11 is provided at a front end face of the casing 1. The output channel 13 is provided at the bottom of the casing 1, and an outlet of the output channel 13 is provided at the front end face of the casing 1.

(125) As shown in FIG. 10, an inner diameter of the second support surface 172 is less than a diameter of a main body portion of the inner side wall of the casing 1 which is less than an outer diameter of the first support surface 171, so that the inner side wall of the casing 1 forms a step-like structure. Regarding the two axial ends of the stator core 2 as the dividing interface, the inner side wall of the casing 1 includes a first inner wall 161, a second inner wall 162 and a third inner wall 163. The front end of the first inner wall 161 is connected with the second support surface 172, and the second inner wall 162 is connected with the third inner wall 163 by the first support surface 171.

(126) The first inner wall 161 of the casing 1 is in interference fit with the waterfall-spray heat dissipation ring 7 by heat sleeve. The second heat dissipation groove 71 on the waterfall-spray heat dissipation ring 7 and the first inner wall 161 form an oil sprinkling channel. The second waterfall-spray slit 72 on the waterfall-spray heat dissipation ring 7 is an oil sprinkling port for the front end winding 31. The cooling oil flows out through the oil sprinkling port, pours on an upper surface of the front end winding 31 in an oil curtain state, flows from the upper surface to a lower surface of the front end winding 31 relying on the action of gravity, and finally is collected at the bottom of the casing 1, and discharged through the third output hole 15.

(127) The second inner wall 162 of the casing 1 is fitted with the stator core 2 by hot sleeve, while the stator core 2 is also in planar contact with a rear end face of the waterfall-spray heat dissipation ring 7. The heat dissipation post top surfaces 2112 of the stator core 2 are in contact with the second inner wall 162 of the casing 1, and the stator core 2 is fixed by a clamping force of the second inner wall 162 of the casing 1 against the heat dissipation post top surfaces 2112. Under support of the heat dissipation posts 211, the lower concave surface 26 of the stator core 2 (i.e., a surface of the outer side wall of the stator core 2 lower than the heat dissipation posts 211) and the second inner wall 162 form a slit flow channel. The slit flow channel is cut by the staggeredly arranged heat dissipation posts 211 to form a network-shaped cooling flow channel 22 for cooling the stator core 2.

(128) The third inner wall 163 of the casing 1 is assembled with the end cap 6 by nested centring and connecting parts. The first heat dissipation groove 61 of the end cap 6 and the third inner wall 163 of the casing 1 form an oil sprinkling channel on the end cap 6. An end face of the centring and connecting part of the end cap 6 is in contact with the rear end face of the stator core 2, so as to block the slit flow channel between the stator core 2 and the second inner wall 162 except the position where the first heat dissipation groove 61 is located. The bottom of the first heat dissipation groove 61 is provided with a narrow circumferential oil sprinkling slit, i.e., a first waterfall-spray slit 62. After entering the oil sprinkling channel of the end cap 6, the cooling oil is sprayed on an upper portion of the rear end winding 32 at the first waterfall-spray slit 62. By the action of gravity, the cooling oil flows from the upper surface to the lower surface of the rear end winding 32, and finally collected at the bottom of an inner cavity of the motor, and discharged through the second output hole 63 at the bottom.

(129) When in use, the cooling oil enters the network-shaped cooling flow path and flows separately as four branches, as shown in FIG. 7.

(130) First branch: the cooling oil is sprayed to the upper portion of the front end winding **31** of the inner cavity of the motor through the second heat dissipation groove **71** and the second waterfall-spray slit **72**, then the cooling oil flows downward along a contour of winding coil under the action of gravity, and is collected at the bottom of the inner cavity of the motor, and discharged through the third output hole **15**.

(131) Second branch and third branch: the cooling oil is at the highest position after entering the network-shaped cooling flow channel **22**. Seen from a transverse section, the cooling oil is subjected to dual actions of the gravity and a high pressure of the oil path, and then flows separately to the left side and right side. The two branches on the left and right sides are the second branch and the third branch. The cooling oil of the second branch and the third branch flows downwards and is collected and discharged at the first output hole **14** at the bottom.

(132) Fourth branch: similar to the first branch, the cooling oil is sprayed on the upper portion of the rear end winding **32** through the first heat dissipation groove **61** and the first waterfall-spray slit **62**, and after cooling the winding coil, the cooling oil is discharged through the second output hole **63** at the bottom of the end cap **6**.

(133) In the second branch and the third branch, no matter whether the cooling oil flows in the left branch or the right branch, it is in sufficient contact with the heat dissipation surface of the stator core **2**, and the main heat exchange for cooling the stator takes place. From the relationship between the heat dissipation area of the stator core **2** and the number of the heat dissipation posts **211**, it may be seen that a larger number of the heat dissipation posts **211** will be more conducive for the heat dissipation of the stator.

(134) FIG. 6 and FIG. 7 are schematic diagrams of materializing the cooling mechanism for convenience of understanding. The network-shaped cooling flow channel **22** is a flow channel defined by space between the stator core **2** and the casing **1**, and is not an independent structure, but is schematically shown as an independent network in FIG. 6 and FIG. 7. The input channel **11** and the output channel **13** are two channels provided in the casing **1** and are schematically shown as two independent pipes in FIG. 6 and FIG. 7.

(135) Similarly, the first heat dissipation groove **61** and the first waterfall-spray slit **62** provided on the end cap **6** are also schematically shown in a materialized manner. The first heat dissipation groove **61** is connected behind the network-shaped cooling flow channel **22** and schematically shown as being in communication with the rear end of the network-shaped cooling flow channel **22**. The first waterfall-spray slit **62** is connected below the first heat dissipation groove **61**, and schematically shown as being in communication with the first heat dissipation groove **61**, and spraying cooling oil downward.

(136) The second heat dissipation groove **71** and the second heat dissipation groove **72** provided on the waterfall-spray heat dissipation ring **7** are also materialized accordingly. The second heat dissipation groove **71** is connected in front of the network-shaped cooling flow channel **22** and schematically shown as being in communication with the front end of the network-shaped cooling flow channel **22**. The second waterfall-spray slit **72** is connected below the second heat dissipation groove **71** and schematically shown as being in communication with the second heat dissipation groove **71** and spraying cooling oil downward.

(137) In this way, a flow path of the cooling oil may be clearly seen with reference to FIG. 6 and FIG. 7, and a cooling principle of the motor according to this embodiment may also be clearly known.

(138) FIG. 8 is a simulation schematic diagram of flow rate of cooling oil. In FIG. 8, lines at the top of the network-shaped cooling flow channel **22** indicating the cooling oil are darker and thicker, and it is clear that two thick black lines extend toward two ends in the axial direction, representing the first branch and the fourth branch respectively, and there are three leftward branches (indicating

the second branch) and three rightward branches (indicating the third branch).

(139) FIG. 9 is a simulation schematic diagram of a flow path of cooling oil. In FIG. 9, it may be clearly seen that the cooling oil enters the network-shaped cooling flow channel 22 downward from the input channel 11 at the top through the three input holes 12. The cooling oil on the lower side of the network-shaped cooling flow channel 22 enters the output channel 13 through three first output holes 14. The cooling oil in the output channel 13 is discharged through a front end outlet. A part of the cooling oil at the front end of the network-shaped cooling flow channel 22 flows downwards via the front end winding 31 and is discharged into the output channel 13 through the third output hole 15. A part of the cooling oil at the rear end of the network-shaped cooling flow channel 22 flows downwards via the rear end winding 32 and is discharged through the second output hole 63 at the bottom of the end cap 6.

(140) In this embodiment, a large number of staggeredly arranged heat dissipation posts 211 are provided on the stator core 2 of the motor, so that the heat dissipation surface area of the motor is significantly increased, thus a cooling model of network-shaped turbulence is implemented. A unique stator punching sheet die is employed, so that the manufacturing cost of the motor is low. The cooling mechanism sprays the cooling oil to an end winding in a manner of waterfall oil curtain, so that the cooling oil is in direct contact with the end winding evenly, ensuring sufficient cooling, thereby improving heat dissipation performance of the motor under high power, and expanding output performance and application scenarios of the motor.

(141) As shown in FIG. 3, an embodiment of the present application provides a stator core 2. An outer side wall of the stator core 2 is provided with multiple heat dissipation protrusions 21, wherein the multiple heat dissipation protrusions 21 are staggeredly arranged in a network-shaped form.

(142) The stator core 2 according to the embodiment of the present application, after being assembled with a casing 1, may form a network-shaped cooling flow channel 22 with the shell 1, which has a larger heat dissipation surface area, thus being conducive to further improving heat dissipation capacity of the motor. In addition, a flow path of a cooling fluid in the network-shaped cooling flow channel 22 is also network-shaped, and a flow form of the cooling fluid in the network-shaped path is turbulent, so that heat exchange efficiency of the turbulent flow is higher, and thus the heat dissipation capacity of the motor can be further improved.

(143) The heat dissipation protrusions 21 are provided on the outer side wall of the stator core 2, so that the heat dissipation surface area of the stator core 2 can be significantly increased, thereby the heat dissipation capability of the stator core 2 is further improved. Moreover, the heat dissipation protrusions 21 of the stator core 2 are against an inner side wall of the casing 1, thereby implementing interference fit between the stator core 2 and the casing 1 and further implementing fixed assembling between the stator core 2 and the casing 1. During the assembling, the interference fit between the stator core 2 and the casing 1 can be achieved by using a hot sleeve process.

(144) In an exemplary embodiment, as shown in FIG. 14, the stator core 2 includes multiple core assemblies 23 that are mutually stacked in an axial direction of the stator core 2. Each core assembly 23 is provided with multiple heat dissipation protrusions 21 spaced apart along its circumferential direction. Heat dissipation protrusions 21 of adjacent core assemblies 23 are staggeredly arranged along a circumferential direction of the stator core 2, as shown in FIG. 13. Technical effects of this scheme may be interpreted with reference to the above-mentioned embodiment of the motor, which will not be repeated here.

(145) In an exemplary embodiment, the core assembly 23 is formed by stacking multiple stator punching sheets 24, as shown in FIG. 15. Each stator punching sheet 24 is provided with multiple heat dissipation teeth 241, as shown in FIG. 16. Heat dissipation teeth 241 corresponding to the multiple stator punching sheets 24 are stacked to form the heat dissipation protrusions 21. Technical effects of this scheme may be interpreted with reference to the above-mentioned

embodiment of the motor, which will not be repeated here.

(146) In an exemplary embodiment, the number and distribution of the heat dissipation protrusions **21** on the multiple core assemblies **23** are identical. Multiple heat dissipation protrusions **21** on each core assembly **23** are equally divided into multiple heat dissipation groups, wherein each of the heat dissipation groups includes at least one heat dissipation protrusion **21**. Technical effects of this scheme may be interpreted with reference to the above-mentioned embodiment of motor, which will not be repeated here.

(147) In an exemplary embodiment, the stator core **2** is provided with multiple cogging grooves **25** along its circumferential direction for mounting a stator winding **3**, as shown in FIG. **14**. The number of the cogging grooves **25** is an integer multiple of the number of the heat dissipation groups of each core assembly **23**.

(148) In one example, for each core assembly **23**, the number of the heat dissipation groups is a half of the number of the cogging grooves **25**. Technical effects of this scheme may be interpreted with reference to the above-mentioned embodiment of the motor, which will not be repeated here.

(149) In an exemplary embodiment, each heat dissipation group includes multiple heat dissipation protrusions **21** spaced apart along the circumferential direction of the core assembly **23**. A circumferential spacing between adjacent heat dissipation groups is larger than a circumferential spacing between adjacent heat dissipation protrusions **21** in each heat dissipation group. Technical effects of this scheme may be interpreted with reference to the above-mentioned embodiment of the motor, which will not be repeated here.

(150) In an exemplary embodiment, each heat dissipation group includes multiple heat dissipation posts **211** spaced apart along the circumferential direction of the core assembly **23**. In each heat dissipation group, one of the heat dissipation protrusions **21** is provided as a positioning protrusion **212**, as shown in FIG. **4**. A shape of the positioning protrusion **212** is different from that of other heat dissipation protrusions **21**.

(151) In one example, in each heat dissipation group, a sectional area of one of the heat dissipation protrusions **21** is larger than that of the other heat dissipation protrusions **21**, as shown in FIG. **4**. Technical effects of this scheme may be interpreted with reference to the above-mentioned embodiment of the motor, which will not be repeated here.

(152) An embodiment of the present application provides a power assembly (not shown in figures) including the motor of any aforementioned embodiments, which thus has all of the aforementioned beneficial effects, which will not be repeated here.

(153) In an exemplary embodiment, the power assembly further includes a speed reducer and a controller.

(154) Herein, the speed reducer is mechanically connected with the motor. The controller is electrically connected with the motor.

(155) In one example, the speed reducer includes a gearbox, and a gear set, a cooling oil pool, an oil pump, and an oil cooler located within the gearbox. The gear set is connected with the rotating shaft **5** of the motor. The casing **1** of the motor is connected or integrated with a box body of the gearbox. The cooling oil pool, the oil pump, the oil cooler and the box body of the gear box cooperate with each other to form an oil cooling mechanism of the speed reducer.

(156) In a case that the motor does not have an independent oil cooling mechanism for the motor, the oil cooling mechanism of the speed reducer may provide low-temperature cooling oil for the motor and recycle high-temperature cooling oil.

(157) An embodiment of the present application provides an automobile (not shown in figures) including the power assembly according to any of the aforementioned embodiments, which thus has all the aforementioned beneficial effects, which will not be repeated here.

(158) To sum up, in the motor according to the embodiment of the present application, the heat dissipation surface area of the stator core is increased by disposing a large number of heat dissipation protrusions, changing the oil flow form to turbulence, and using cooling measures such

as waterfall-spray oil cooling for coil windings, so as to greatly improve the heat dissipation efficiency of the motor. Due to the improvement of the heat dissipation efficiency, the motor system can achieve higher power output under restriction of a same extreme temperature.

(159) In the aspect of manufacturing, only one stator punching die may be involved, and the stator core may be manufactured by misplaced assembling. Since there are few types of stator punching sheets, it may operate efficiently in manufacturing efficiency, warehouse logistics, quality control, and other aspects, which will greatly reduce the production cost of motor stator assembly.

(160) FIG. 17 to FIG. 23 are schematic structural diagrams of a motor and components thereof according to an embodiment of the present application. As shown in FIG. 17 to FIG. 23, this embodiment provides a motor **100**, wherein the motor **100** includes a stator core **10** and a housing **20** (i.e. the casing in the aforementioned embodiments). The stator core **10** is formed by mutually staggeredly stacking multiple annular core punching sheets **11**. A main body structure of the stator core **10** is formed by mutually stacking multiple core punching sheets **11**. After the multiple core punching sheets **11** are stacked, a flow channel (i.e., the slit flow channel in the aforementioned embodiments) is formed between the core punching sheets **11** and the housing **20**, and a liquid (e.g. a cooling liquid such as cooling oil) may flow in the flow channel, thereby cooling the motor **100**.

(161) Since the stator core **10** of this embodiment is formed by mutually stacking multiple core punching sheets **11**, the manufacturing process of the core punching sheets **11** is simple with a low manufacturing cost.

(162) In an exemplary embodiment, the stator core **10** may be formed by mutually staggeredly stacking at least one annular first core punching sheet **111** and at least one annular second core punching sheet **112**, as shown in FIG. 18 and FIG. 19. The housing **20** is wrapped around an outer periphery of the stator core **10**, and forms a flow channel with the outer periphery of the stator core **10** by mutually attachment, so that liquid flows in the flow channel. Structures of the first core punching sheet **111** and the second core punching sheet **112** at the outer peripheral surfaces are different, such that the flow channel extends across the outer periphery of the first core punching sheet **111** and the second core punching sheet **112**, thereby enabling the liquid to flow in series between the first core punching sheet **111** and the second core punching sheet **112** (i.e., the flow channels form the network-shaped cooling flow channel in the aforementioned embodiments).

(163) The motor **100** in this embodiment includes a stator core **10** and a housing **20**, wherein the stator core **10** is formed by mutually staggeredly stacking a first core punching sheet **111** and a second core punching sheet **112**, such that liquid may flow in series in the flow channel formed between the first core punching sheet **111** and the second core punching sheet **112** and the housing **20**, so that the cooling liquid may carry away heat of the stator core **10** to achieve the purpose of cooling. Since the flow channel in this embodiment extends across the first core punching sheet **111** and the second core punching sheet **112**, the motor **100** of this embodiment has strong heat dissipation capability.

(164) Since the flow channel in this embodiment is directly formed between the outer surface of the stator core **10** and the housing, the heat exchange area is greatly increased.

(165) In an exemplary embodiment, as shown in FIG. 20 and FIG. 21, multiple convex parts **113** and multiple concave parts **114** arranged at intervals are distributed at the outer peripheral surface of the first core punching sheet **111** of this embodiment. The outer peripheral surface of the second core punching sheet **112** has a smooth structure (as shown in FIG. 22 and FIG. 23). The flow channel is formed by the concave parts **114** of the first core punching sheet **111** and the outer periphery of the second core punching sheet **112** and the inner wall of the housing **20**.

(166) Structures of the convex parts **113** and the concave parts **114** at the outer periphery of the first core punching sheet **111** of this embodiment may be freely designed according to actual needs. For example, the convex parts **113** in this embodiment have a cubic shape. In other embodiments, a structure of the convex parts **113** may be a stepped terrace or another three-dimensional structure. The structure of the convex parts **113** only needs to be platform-shaped at the outermost part. The

outermost parts of the convex parts **113** of the first core punching sheet **111** are all in contact with the inner wall of the housing **20**. The structure design of the outer periphery of the first core punching sheet **111** in this embodiment can greatly increase the heat exchange area, thereby improving the heat exchange effect.

(167) In addition, the structure of the outer periphery of the second core punching sheet **112** in this embodiment may be other structures other than a smooth structure, only if a structure height at the outer periphery of the second core punching sheet **112** does not exceed a height of the convex parts **113** of the first core punching sheet **111**, and a communicated flow channel may be formed between the second core punching sheet **112** and the concave parts **114** and the housing **20**. In a case that the outer periphery of the second core punching sheet **112** is designed as other structures, the structure of the second core punching sheet **112** is different from that of the first core punching sheet **111**. The outer periphery of the second core punching sheet **112** is designed to have other structure instead of a smooth structure, such that the heat exchange area can be increased and the heat exchange efficiency of the motor **100** can be improved.

(168) In an exemplary embodiment, a thickness of the first core punching sheet **111** and a thickness of the second core punching sheet **112** may be freely designed according to actual needs.

(169) In an exemplary embodiment, in a case that the first core punching sheet **111** and the second core punching sheet **112** are mutually stacked at intervals, the outer peripheral surface of the second core punching sheet **112** is flush with the concave parts **114**. That is, the concave parts **114** of the first core punching sheet **111** and the outer periphery of the second core punching sheet **112** are on a same smooth plane, so that the cooling liquid can flow smoothly in series between the first core punching sheet **111** and the second core punching sheet **112**, thereby improving the cooling efficiency.

(170) In an exemplary embodiment, a first protrusion **115** is further provided at a concave part **114** of the outer peripheral surface of the first core punching sheet **111**, as shown in FIG. **20** and FIG. **21**, wherein the first protrusion **115** extends in a direction in which the axial direction of the first core punching sheet **111** is located. A second protrusion **116** is provided at the outer peripheral surface of the second core punching sheet **112**, as shown in FIG. **22** and FIG. **23**, wherein the second protrusion **116** extends in the axial direction of the second core punching sheet **112**. Herein, the first protrusion **115** and the second protrusion **116** are mated when the first core punching sheet **111** and the second core punching sheet **112** are mutually stacked at intervals. In this embodiment, the first protrusion **115** and the second protrusion **116** are designed to enable accurate positioning when the first core punching sheet **111** and the second core punching sheet **112** are mutually stacked.

(171) FIG. **24** to FIG. **27** are schematic structural diagrams of a motor and components thereof according to another embodiment of the present application. As shown in FIG. **24**, the motor **100** of this embodiment may include a stator core **10** and a housing **20** (i.e., the casing in the foregoing embodiments), and further, the stator core **10** is formed by mutually stacking multiple core punching sheets **11**, as shown in FIG. **25** and FIG. **26**. Multiple convex parts **101** and multiple concave parts **102** are provided on an outer periphery of the core punching sheets **11** in this embodiment. The housing **20** is wrapped around an outer periphery of the stator core **10**, and forms a flow channel (i.e., the slit flow channel in the aforementioned embodiments) with the convex parts **101** of the stator core **10** by mutually attachment. Herein, in a case that a circumferential dimension of a convex part **101** is smaller than a circumferential dimension of a concave part **102**, and the core punching sheets **11** are mutually staggeredly stacked, the convex parts **101** and the concave part **102** of two adjacent core punching sheets **11** are staggeredly arranged so that liquid can flow in series within multiple core punching sheets **11**.

(172) In this embodiment, the multiple core punching sheets **11** have same structures, however, since dimension of a convex part **101** is smaller than that of a concave part **102**. Therefore, in a case that different core punching sheets **11** are attached in an mutually staggeredly and the convex

parts **101** and the concave parts **102** are staggeredly arranged, the flow channel is mainly composed of the concave parts **102** and the housing **20**, and the convex parts **101** are interspersed in the flow channel, so that liquid may mutually flow in series (i.e., the flow channel forms the network-shaped cooling flow channel in the aforementioned embodiments), and the cooling effect of the stator core **10** is improved.

(173) The core punching sheet **11** in this embodiment may have the same structure as the first core punching sheet **111** in the aforementioned embodiment. Apparently, it may be designed into different shapes as required.

(174) In an exemplary embodiment, a structure of each concave part **101** of this embodiment may be cubic in shape. In other embodiments, the structure of a convex part **101** may be a stepped terrace or another three-dimensional structure. The structure of the convex part **101** only needs to be platform-shaped at the outermost part. The outermost parts of the convex parts **101** of the core punching sheet **11** are all in contact with the inner wall of the housing **20**. Since all the core punching sheets **11** in this embodiment include structures of the convex part **101**, and the structures of the convex parts **101** are all in contact with the housing **20**, the core punching sheet **11** is subjected to a force around the housing **20**, thereby preventing the core punching sheet **11** from being deformed.

(175) In the example of this embodiment, a protrusion **103** is provided at the core punching sheet **11**, as shown in FIG. 25 and FIG. 27. The protrusion **103** extends along the axial direction of the core punching sheet **11**. In a case that multiple core punching sheets **11** are stacked to form a stator core **10**, the protrusions **103** at the multiple core punching sheets **11** are connected with each other to form a line.

(176) In this embodiment, in a case that two adjacent core punching sheets **11** are staggeredly provided, a convex part **101** of one core punching sheet **11** may be provided on a side of a middle position of a concave part **102** of another core punching sheet **11**, and the flow channel formed in this case is relatively regular.

(177) The thickness of the core punching sheet **11** and the number and dimension of the convex parts **101** and the concave parts **102** in this embodiment may be designed as required. A larger number of convex parts **101** and concave parts **102** and a larger number of flow channels will bring a better cooling effect.

(178) In an exemplary embodiment, an inner periphery of each core punching sheet **11** is provided with winding grooves **13** (i.e., the cogging grooves in the aforementioned embodiments), and a large number of windings are provided in the winding grooves **13**, so that the design of the protrusions **103** can make the winding grooves **13** remain aligned when different core punching sheets **11** are mutually stacked.

(179) In an exemplary embodiment, FIG. 28 is a schematic structural diagram of a housing according to an embodiment of the present application. In the above two embodiments (the motors illustrated in FIG. 17 to FIG. 23 and the motors illustrated in FIG. 24 to FIG. 27), different stator cores **10** may be equipped with the same housing **20**. As shown in FIG. 28, the housing **20** in this embodiment includes a body **21**, wherein the body **21** has a cylindrical shape, and a step **22** with a smaller size than other positions is provided at one end of the cylindrical shape. In a case that the stator core **10** is provided in the housing **20**, the outer periphery of the stator core **10** is attached to the inner wall of the housing **20**, and one end of the stator core **10** abuts against the step **22**.

(180) In an exemplary embodiment, as shown in FIG. 28, a liquid inflow channel **23** (i.e. the input channel in the foregoing embodiments) and a liquid outflow channel **24** (i.e. the output channel in the foregoing embodiments) are further included at the housing **20**. In a case that the housing **20** and the stator core **10** are fixedly disposed, the liquid inflow channel **23** and the liquid outflow channel **24** are communicated with the flow channel, and the liquid flows in the liquid inflow channel **23** passes through the flow channel and then flows out from the liquid outflow channel **24**.

(181) As shown in FIG. 28, the liquid inflow channel **23** and the liquid outflow channel **24** may be

provided outside the housing **20**, and the wall of the housing **20** is a portion of each of the liquid inflow channel **23** and the liquid outflow channel **24**, and the housing **20** are provided with through holes **25** (i.e. the input hole and the first output hole in the foregoing embodiment) at the liquid inflow channel **23** and the liquid outflow channel **24**. In this embodiment, the through holes **25** of the liquid inflow channel **23** (i.e. the input holes in the foregoing embodiments) is plural and the multiple through holes **25** may be arranged in juxtaposition. Similarly, the through holes **25** at the liquid outflow channel **24** (i.e. the first output holes in the aforementioned embodiments) is also plural and the multiple through holes **25** may be arranged in juxtaposition.

(182) Cross sections of the liquid inflow channel **23** and the liquid outflow channel **24** of this embodiment may be any shape, for example, semicircular, rectangular, or the like.

(183) A shape of a through hole **25** in this embodiment may be any shape, for example, round, square, diamond, or the like. The cooling liquid entering the liquid inflow channel **23** first enters the flow channel through the through hole **25** at the liquid inflow channel **23**, then flows through the liquid outflow channel **24** via the through hole **25** at the liquid outflow channel **24** and then flows out.

(184) The liquid inflow channel **23** and the liquid outflow channel **24** may extend along the axial direction of the stator core **10**, and the liquid inflow channel **23** and the liquid outflow channel **24** are located at opposite positions at the outer periphery of the stator core **10**, respectively. This position design can increase the heat dissipation capacity of the motor **100**.

(185) FIG. **29** is a schematic structural diagram of an oil slinger according to an embodiment of the present application. The motor **100** of this embodiment may further include an oil slinger **30** provided in the housing **20** at an end of the stator core **10** opposite to the end abutting against the step **22**, as shown in FIG. **29**, and the step **22**, the concave parts **102**, the inner wall of the housing **20** and the oil slinger **30** together form a sealed flow channel.

(186) An embodiment of the present application further provides a vehicle (not shown in figures) including the aforementioned motor **100**.

(187) In the description of embodiments of the present application, it is to be understood that, the terms “center”, “longitudinal”, “transverse”, “length”, “width”, “thickness”, “up”, “down”, “front”, “rear”, “left”, “right”, “vertical”, “horizontal”, “top”, “bottom”, “inner”, “outer”, “clockwise”, “counterclockwise”, “axial”, “radial”, “circumferential”, etc. indicate orientation or positional relationships based on the orientation or positional relationships shown in drawings. They are intended for ease of description of the embodiments of the present application and for simplified description only, and are not intended to indicate or imply that the referred device or element must have a particular orientation, be constructed and operate in a particular orientation, and therefore cannot be construed as limitations on the present application.

(188) Furthermore, the terms “first” and “second” are used for purposes of description only and cannot be understood as indicating or implying relative importance or implying the number of technical features indicated. Thus, the features defined with “first”, “second” may explicitly or implicitly include at least one of the features. In the description of embodiments of the present application, “a plurality” means at least two, e.g. two, three, etc. unless otherwise explicitly and specifically defined.

(189) In the description of the embodiments of the present application, unless otherwise specified and defined, the terms “mount”, “connected with”, “connection”, “fixed” should be understood in a broad sense, for example, a connection may be a fixed connection, a detachable connection or an integrated connection, it may be a mechanical connection, or an electrical connection, it may be a direct connection, or an indirect connection through an intermediary, or may be an internal communication between two elements or an interaction relationship between two elements unless otherwise explicitly defined. For those of ordinary skills in the art, the specific meanings of the above terms in the embodiments of the present application can be understood according to specific situations.

(190) In embodiments of the present application, the first feature being “above” or “below” the second feature may be a direct contact between the first feature and second feature, or an indirect contact between the first feature and second feature via an intermediary, unless otherwise explicitly specified and defined. Moreover, the first feature is “above” the second feature may be that the first feature is directly above or obliquely above the second feature, or simply indicate that a horizontal height of the first feature is higher than that of the second feature. The first feature being “below” the second feature may be that the first feature is directly below or obliquely below the second feature, or simply indicate the horizontal height of first feature is small than that of the second feature.

(191) In the description of this specification, descriptions of the reference terms “an embodiment,” “some embodiments,” “example,” “specific example,” or “some examples,” and the like mean that specific features, structures, materials, or characteristics described in combination with the embodiment or example are included in at least an embodiment or example of the present application. In this specification, the schematic demonstration of the above terms need not be directed to the same embodiments or examples. In addition, the specific features, structures, materials, or characteristics described may be combined in a suitable manner in any one or more embodiments or examples. Besides, without mutual confliction, those skilled in the art may be in combination and conjunction with different embodiments or examples described in this specification and features of different embodiments or examples.

(192) Although the embodiments of the present application have been shown and described above, it is to be understood that the aforementioned embodiments are exemplary and cannot be construed as limit to the present application, and change, modification, substitution and variation may be made to the aforementioned embodiments by those of ordinary skilled in the art within the scope of the present application.

Claims

1. A motor comprising: a casing; a stator core fixed in the casing, wherein a slit flow channel is formed between an outer side wall of the stator core and an inner side wall of the casing, and the slit flow channel is provided as a network-shaped cooling flow channel for a cooling fluid to flow; a stator winding mounted on the stator core; and a rotor rotatably sleeved on an inner side of the stator core, wherein the stator core comprises a plurality of core assemblies mutually stacked along an axial direction of the stator core; on an outer peripheral surface of each of the core assemblies that forms the outer side wall of the stator core, each of the core assemblies is provided with a plurality of heat dissipation protrusions spaced apart along a circumferential direction of the core assembly, and the heat dissipation protrusions of adjacent core assemblies are staggeredly arranged along a circumferential direction of the stator core, to form the network-shaped cooling flow channel; number and distribution form of the heat dissipation protrusions on the plurality of the core assemblies are same, each of the core assemblies is provided with a plurality of heat dissipation groups, and each of the heat dissipation groups comprises at least one of the heat dissipation protrusions; on each of the core assemblies, a circumferential spacing between adjacent heat dissipation groups is larger than a circumferential spacing between adjacent heat dissipation protrusions in each heat dissipation group; and the circumferential spacing between adjacent heat dissipation groups on each of the plurality of core assemblies have identical alignment with the heat dissipation group on an adjacent core assembly, and a length of the circumferential spacing between the adjacent heat dissipation groups on each of the plurality of core assemblies is larger than a length of the heat dissipation group on the adjacent core assembly in the circumferential direction.

2. The motor according to claim 1, wherein the inner side wall of the casing is provided with a plurality of heat dissipation protrusions; the plurality of heat dissipation protrusions are staggeredly

arranged in a network-shaped form, so that the slit flow channel is divided into the network-shaped cooling flow channel.

3. The motor according to claim 2, wherein the casing is further provided with an input channel and at least one input hole communicated with the input channel, wherein the input channel is located radially outward of the network-shaped cooling flow channel and is communicated with the network-shaped cooling flow channel through the at least one input hole for inputting the cooling fluid into the network-shaped cooling flow channel; the casing is further provided with an output channel and at least one first output hole communicated with the output channel, wherein the output channel is located radially outward of the network-shaped cooling flow channel and is communicated with the network-shaped cooling flow channel through the at least one first output hole for outputting the cooling fluid discharged from the network-shaped cooling flow channel.

4. The motor according to claim 1, wherein at least part of the heat dissipation protrusions on the outer side wall of the stator core abut against the inner side wall of the casing, so that the stator core and the casing are in interference fit.

5. The motor according to claim 1, wherein the core assembly is formed by stacking a plurality of stator punching sheets, each stator punching sheet is provided with a plurality of heat dissipation teeth, and the heat dissipation teeth corresponding to the plurality of stator punching sheets are stacked to form the heat dissipation protrusions.

6. The motor according to claim 1, wherein the stator core is provided with a plurality of cogging grooves for mounting the stator winding along the circumferential direction of the stator core, and the number of the cogging grooves is an integer multiple of the number of the heat dissipation groups of each core assembly.

7. The motor according to claim 6, wherein each of the heat dissipation groups comprises a plurality of heat dissipation posts provided at intervals along the circumferential direction of the core assembly; in each of the heat dissipation groups, one of the heat dissipation protrusions is provided as a positioning protrusion, the positioning protrusion has a shape different from shapes of other heat dissipation protrusions.

8. The motor according to claim 1, wherein two end portions of the stator winding protruding from the stator core are defined as end windings; the casing is provided with an open end, and the motor further comprises an end cap provided at the open end, wherein the end cap is provided with a first heat dissipation groove, and the first heat dissipation groove is communicated with the network-shaped cooling flow channel; a bottom wall of the first heat dissipation groove corresponding to an end winding is provided with a first waterfall-spray slit for spraying the cooling fluid to the end winding corresponding to the first waterfall-spray slit; the end cap is further provided with a second output hole, and the second output hole is configured to be communicated with an external cooling flow path for discharging the cooling fluid flowing through the end winding corresponding to the first waterfall-spray slit into the external cooling flow path.

9. The motor according to claim 8, wherein the number of the open end is one, and the motor further comprises a waterfall-spray heat dissipation ring sleeved in the casing and located at one end of the casing away from the open end; the waterfall-spray heat dissipation ring is provided with a second heat dissipation groove communicated with the network-shaped cooling flow channel; a bottom wall of the second heat dissipation groove corresponding to an end winding is provided with a second waterfall-spray slit for spraying the cooling fluid to the end winding corresponding to the second heat dissipation groove; the casing is further provided with a third output hole configured to be communicated with the external cooling flow path for discharging the cooling fluid flowing through the end winding corresponding to the second waterfall-spray slit into the external cooling flow path.

10. The motor according to claim 9, wherein the number of the first waterfall-spray slit is one, and the first waterfall-spray slit is provided at a top of the end cap and extends along a circumferential direction of the end cap, and a radian of the first waterfall-spray slit is in a range of 40° to 180°; or,

a plurality of first waterfall-spray slits are provided and the plurality of first waterfall-spray slits are provided at intervals along the circumferential direction of the end cap; or, the number of the first waterfall-spray slit is one, and the first waterfall-spray slit surrounds the end cap along the circumferential direction of the end cap; and the number of the second waterfall-spray slit is one, the second waterfall-spray slit is provided at a top of the waterfall-spray heat dissipation ring and extends along a circumferential direction of the waterfall-spray heat dissipation ring, and a radian of the second waterfall-spray slit is in the range of 40° to 180°; or, a plurality of second waterfall-spray slits are provided, and the plurality of second waterfall-spray slits are provided at intervals along the circumferential direction of the waterfall-spray heat dissipation ring; or, the number of the second waterfall-spray slit is one, and the second waterfall-spray slit surrounds the waterfall-spray heat dissipation ring along the circumferential direction of the waterfall-spray heat dissipation ring.

11. A power assembly comprising the motor according to claim 1.

12. An automobile comprising the power assembly according to claim 11.

13. A stator core, wherein the stator core comprises a plurality of core assemblies mutually stacked along an axial direction of the stator core; on an outer peripheral surface of each of the core assemblies that forms an outer side wall of the stator core, each of the core assemblies is provided with a plurality of heat dissipation protrusions spaced apart along a circumferential direction of the core assembly, and the heat dissipation protrusions of adjacent core assemblies are staggeredly arranged along a circumferential direction of the stator core, to form a slit flow channel in a network shape; number and distribution form of the heat dissipation protrusions on the plurality of the core assemblies are same, each of the core assemblies is provided with a plurality of heat dissipation groups, and each of the heat dissipation groups comprises at least one of the heat dissipation protrusions; and on each of the core assemblies, a circumferential spacing between adjacent heat dissipation groups is larger than a circumferential spacing between adjacent heat dissipation protrusions in each heat dissipation group; and the circumferential spacing between adjacent heat dissipation groups on each of the plurality of core assemblies have identical alignment with the heat dissipation group on an adjacent core assembly, and a length of the circumferential spacing between the adjacent heat dissipation groups on each of the plurality of core assemblies is larger than a length of the heat dissipation group on the adjacent core assembly in the circumferential direction.

14. A motor comprising: a stator core and a housing; the stator core is formed by mutually stacking a plurality of annular core punching sheets; wherein the core punching sheets comprise a first core punching sheet, a second core punching sheet, and a third core punching sheet, and the stator core is formed by mutually staggeredly stacking the first core punching sheet, the second core punching sheet and the third core punching sheet, the second core punching sheet is arranged between the first core punching sheet and the third core punching sheet; the housing is wrapped around an outer periphery of the stator core, and the housing and the outer periphery of the stator core are mutually fitted to form a flow channel; the outer peripheral surface of the second core punching sheet has a smooth structure; each of the first core punching sheet and the third core punching sheet is provided with a plurality of heat dissipation protrusions spaced apart along a circumferential direction of the core punching sheet; number and distribution form of the heat dissipation protrusions on the first core punching sheet is the same as number and distribution form of the heat dissipation protrusions on the third core punching sheet, each of the first core punching sheet and the third core punching sheet is provided with a plurality of heat dissipation groups, and each of the heat dissipation groups comprises at least one of the heat dissipation protrusions; on each of the first core punching sheet and the third core punching sheet, a circumferential spacing between adjacent heat dissipation groups is larger than a circumferential spacing between adjacent heat dissipation protrusions in each heat dissipation group; and the circumferential spacing between adjacent heat dissipation groups on the first core punching sheet have identical alignment with the

heat dissipation group on the third core punching sheet, and a length of the circumferential spacing between the adjacent heat dissipation groups on the first core punching sheet is larger than a length of the heat dissipation group on the third core punching sheet in the circumferential direction.

15. A vehicle comprising the motor according to claim 14.
