

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414712
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Machida; Hidekazu et al.

Information processing system

Abstract

A technique is provided that is capable of obtaining image data for personal identification clearly in a short time at an arbitrary position in an area region at least about several times greater than a fingertip. In addition, a technique is provided that allows smooth progress of a series of process flow in a reservation site and an electronic commerce site for excellent user experience. An information processing system is provided that includes: an input section having a surface and configured to allow a user to contact or approximate a position specifier to the surface for information input; and a processing section configured to perform processing based on the information input to the input section, wherein the input section includes a position detection mechanism configured to detect a position of the position specifier on the surface and a reading mechanism configured to read biometric information of the user.

Inventors:	Machida; Hidekazu (Myoukou, JP), Shimoishizaka; Nozomi (Myoukou, JP), Komatsu; Hiroshi (Myoukou, JP)
Applicant:	CONNECTEC JAPAN CORPORATION (Myoukou, JP); FUJIKIN INCORPORATED (Osaka, JP)
Family ID:	1000008818326
Assignee:	CONNECTEC JAPAN Corporation (Niigata, JP); FUJIKIN INCORPORATED (Osaka, JP)
Appl. No.:	16/772652
Filed (or PCT Filed):	December 06, 2018
PCT No.:	PCT/JP2018/044838
PCT Pub. No.:	WO2019/117002
PCT Pub. Date:	June 20, 2019

Prior Publication Data

Document Identifier

US 20210278925 A1

Publication Date

Sep. 09, 2021

Foreign Application Priority Data

JP

2017-238177

Dec. 12, 2017

Publication Classification

Int. Cl.: **G06F3/041** (20060101); **A61B5/1171** (20160101); **G06F3/042** (20060101); **G06F21/32** (20130101); **G06V40/10** (20220101); **G06V40/13** (20220101); **G06V40/70** (20220101)

U.S. Cl.:

CPC **A61B5/1171** (20160201); **G06F3/0412** (20130101); **G06F3/0425** (20130101); **G06F21/32** (20130101); **G06V40/13** (20220101); **G06V40/70** (20220101); G06V40/15 (20220101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2009/0102788	12/2008	Nishida et al.	N/A	N/A
2012/0223916	12/2011	Kukulj	178/18.09	G06F 3/0428
2016/0092018	12/2015	Lee	345/173	G06F 1/1684
2016/0349882	12/2015	Liu et al.	N/A	N/A
2017/0220838	12/2016	He et al.	N/A	N/A
2018/0157395	12/2017	Mhun	N/A	G06F 3/04883
2019/0095672	12/2018	Yeke Yazdandoost	N/A	H01L 27/14685

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
106233295	12/2015	CN	N/A
3168782	12/2016	EP	N/A
2004-39909	12/2003	JP	N/A
2004-178166	12/2003	JP	N/A
2004-334788	12/2003	JP	N/A
2006-92428	12/2005	JP	N/A
2007-293539	12/2006	JP	N/A
2016-212843	12/2015	JP	N/A

2017-33499	12/2016	JP	N/A
2013-511100	12/2017	JP	N/A
10-2010-0038157	12/2009	KR	N/A
10-2016-0003272	12/2015	KR	N/A
2011/060487	12/2010	WO	N/A
2017/110218	12/2016	WO	N/A

OTHER PUBLICATIONS

English machine translation of Japanese patent publication JP2007293539 (Year: 2007). cited by examiner

English machine translation of Japanese patent publication JP2006092428 (Year: 2006). cited by examiner

English machine translation of WIPO patent publication WO2017110218 (Year: 2017). cited by examiner

International Search Report and Written Opinion, International Patent Application No.

PCT/JP2018/044838, Mar. 5, 2018, with English translation of Search Report (10 pages). cited by applicant

Primary Examiner: Lee; Nicholas J

Attorney, Agent or Firm: Maine Cernota & Curran

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to an information processing system.

BACKGROUND ART

(2) PTL 1 discloses an imaging device to obtain an optical image of a subject, particularly to an imaging device suitable for obtaining a fingerprint image for personal identification. A fingerprint at a fingertip may have low ridges depending on a person, and in such a case, a fingerprint reader is sometimes not capable of obtaining fingerprint image data, or even when being capable of obtaining, the obtained data is sometimes not clear. The imaging device in PTL 1, however, is supposed to achieve an object of the invention to “allow clear imaging of a subject” by providing a configuration of “an imaging device, configured to obtain an optical image of a subject (e.g., a fingertip) from below a contact surface that contacts the subject, wherein a light diffusing film to diffuse light is formed on the contact surface”.

(3) PTL 2 discloses a contact sensor to sense a test object. Similar to the case of PTL 1 above, a fingerprint reader is sometimes not capable of obtaining fingerprint image data, or even when being capable of obtaining, the obtained data is sometimes not clear. The contact sensor in PTL 2, however, is supposed to achieve an object of the invention to “allow clear imaging of a subject” by providing a configuration of “a contact sensor, configured to sense a test object placed on a placement surface, wherein a liquid repellent coating is formed on the placement surface”.

(4) In sites to reserve tickets for hotels, flights, and the like and electronic commerce sites for purchase of goods and the like, personal identification is generally required for, in addition to login to start providing the service, an important procedure such as a payment procedure during a series of process of reservation or purchase of goods.

CITATION LIST

Patent Literature

SUMMARY OF INVENTION

Technical Problem

(6) Use of the techniques described in PTLs 1 and 2 allows clear fingerprint image data to be obtained for personal identification.

(7) However, the inventions described in PTLs 1 and 2 assume obtaining fingerprint image data in a limited area region of about a fingertip, for example a region of approximately 10 mm×10 mm, and thus to obtain clear fingerprint image data at an arbitrary position in a large area region of, for example, 10 inches or more, the number of scanning lines for data detection becomes enormous and it is difficult to quickly obtain image data.

(8) For example, to obtain fingerprint image data with a resolution equivalent to PTLs 1 and 2, read sensors have to be arranged in an array with a 50 μm pitch, and the number of drivers for horizontal and vertical scanning is 5940×4200 for A4 size and 8400×5940 for A3 size. Such a large number of drivers has to be driven to read a fingerprint one time, causing a problem that the time taken to obtain the entire data becomes longer. Moreover, not all the data thus obtained is used for personal identification and the data used for personal identification is limited to the data in the region touched by the fingertip and thus a large amount of data in the other regions turns out to be useless data not used for personal identification.

(9) It is an object of the present invention to provide a technique capable of obtaining image data for personal identification clearly in a short time at an arbitrary position in an area region about several times greater than a fingertip. It is another object of the present invention to provide a technique capable of obtaining image data for personal identification efficiently with no waste in an area region about several times greater than a fingertip.

(10) As described above, reservation sites or electronic commerce sites may require personal identification every time a user selects a process of an important procedure, such as payment processing. The security of transactions is thus ensured by requiring personal identification every time processing an important procedure.

(11) However, it is not convenient for the user required to provide personal identification for each important procedure due to interruption of a series of process flow for reservation or shopping. In addition, shopping in electronic commerce is, no different from shopping in a real store, to enjoy shopping and thus process interruption in a series of procedures by personal identification is not preferred from the perspective of user experience.

(12) It is thus still another object of the present invention to provide a technique capable of smooth progress of a series of process flow in a reservation site or an electronic commerce site for excellent user experience.

Solution to Problem

(13) To achieve the above problems, a first aspect of the present invention provides an information processing system, including: an input section having a surface and configured to allow a user to contact or approximate a position specifier to the surface for information input; and a processing section configured to perform processing based on the information input to the input section, wherein the input section includes a position detection mechanism configured to detect a position of the position specifier on the surface and a reading mechanism configured to read biometric information of the user.

(14) The above information processing system may have a configuration in which the processing section narrows down a region to be read by the reading mechanism based on position information of the position specifier obtained from the position detection mechanism and activates the reading mechanism in the reading region to obtain the biometric information.

(15) The above information processing system may have another configuration in which the processing section configured to perform next processing based on position information of the position specifier obtained from the position detection mechanism and attribute information of the

user associated with the biometric information obtained from the reading mechanism. In this case, the above information processing system may further include a display section **210** arranged facing the input section, wherein the processing section selects and performs, in the next processing, a function in accordance with the attribute information among functions assigned to the position of the display section **210** specified in the position information.

(16) The above information processing system may have a configuration in which the position detection mechanism is a device configured to cause the reading mechanism to function with reduced reading accuracy, a touch screen, or a single or a plurality of imaging devices. In this case, the above information processing system may have a configuration in which the reading mechanism has detection elements arranged in a matrix on the surface, first lines connecting the detection elements in a first direction, and second lines connecting the detection elements in a second direction different from the first direction and is configured to cause the reading mechanism to function as the position detection mechanism by reducing the first lines, the second lines, or both the first lines and the second lines during their function. The above information processing system may have another configuration in which the position detection mechanism is the plurality of imaging devices, and each of the imaging devices takes an image of a region different from each other on the surface.

(17) The above information processing system may have a configuration in which the biometric information is a pattern or a feature corresponding to a single or a plurality of biometric areas selected from a fingerprint, a vein pattern, face, an iris, and a voiceprint of the user.

(18) It should be noted that the summary of the invention described above does not list all characteristics necessary for the present invention. In addition, subcombinations of the groups of characteristics may also be the invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. **1** is a conceptual diagram illustrating an information processing system **100**.

(2) FIG. **2** is a diagram illustrating an example of an input section **110**.

(3) FIG. **3** is a partial enlarged view of the input section **110**.

(4) FIG. **4** is a diagram illustrating functions of the information processing system **100**.

(5) FIG. **5** is a diagram illustrating functions of the information processing system **100**.

(6) FIG. **6** is a diagram illustrating another example of the input section **110**.

(7) FIG. **7** is a diagram illustrating still another example of the input section **110**.

(8) FIG. **8** is a conceptual diagram illustrating an information processing system **200**.

(9) FIG. **9** is a flow chart illustrating processing of the information processing system **200**.

(10) FIG. **10** is a diagram illustrating an example of a display of the information processing system **200**.

(11) FIG. **11** is a diagram illustrating an example of a display of the information processing system **200**.

(12) FIG. **12** is a flow chart illustrating processing of the information processing system **200**.

(13) FIG. **13** is a diagram illustrating an example of a display of the information processing system **200**.

(14) FIG. **14** is a diagram illustrating an example of a display of the information processing system **200**.

(15) FIG. **15** is a flow chart illustrating processing of the information processing system **200**.

(16) FIG. **16** is a diagram illustrating an example of a display of the information processing system **200**.

(17) FIG. **17** is a diagram illustrating an example of a display of the information processing system

200.

(18) FIG. **18** is a flow chart illustrating processing of the information processing system **200**.

(19) FIG. **19** is a diagram illustrating an example of a display of the information processing system **200**.

(20) FIG. **20** is a diagram illustrating an example of a display of the information processing system **200**.

DESCRIPTION OF EMBODIMENTS

(21) The present invention is described below with reference to embodiments while the following embodiments do not limit the invention defined in the appended claims. Not all combinations of the characteristics described in the following embodiments are essential to the solutions of the invention.

First Embodiment

(22) FIG. **1** is a conceptual diagram illustrating an information processing system **100**. The information processing system **100** has an input section **110** and a processing section **160**, and the input section **110** has a position detection mechanism **112** and a biometric information reading mechanism **114**.

(23) The input section **110** has a surface and allows a user to contact or approximate a position specifier, such as a finger, to the surface for information input. The position detection mechanism **112** detects the position of the position specifier on the surface, and the biometric information reading mechanism **114** reads biometric information of the user. The processing section **160** performs processing based on the information input to the input section **110**.

(24) For example, when the user approximates or contacts, for example, a finger (position specifier) to a region A, the position detection mechanism **112** detects the region A and transmits the position information of the detected region A to the processing section **160**. The biometric information reading mechanism **114** reads the biometric information from the body of the user, such as the fingerprint of the finger approximated or contacted to the region A and transmits the biometric information thus read to the processing section **160**. When the user approximates or contacts a finger to a region B, the position information of the region B is transmitted to the processing section **160**, and at the same time, the biometric information of the user is transmitted to the processing section **160**.

(25) FIG. **2** is a diagram illustrating an example of the input section **110**, and FIG. **3** is a partial enlarged view of the input section **110**. The input section **110** illustrated in FIGS. **2** and **3** is illustrated as an example of the position detection mechanism **112** and the biometric information reading mechanism **114**, where the position detection mechanism **112** is exemplified by a device causing the biometric information reading mechanism **114** to function with reduced reading accuracy.

(26) The input section **110** has a detection element formation region **120**, vertical driver formation regions **122** and **124**, and a signal readout circuit formation region **126**, where the vertical driver formation regions **122** and **124** are arranged respectively to the right and left of the detection element formation region **120** and the signal readout circuit formation region **126** is arranged below the detection element formation region **120**. It should be noted that the above expressions of the right and left and above and below merely express the directions in FIG. **2** and do not mean directions in an actual product.

(27) In the detection element formation region **120**, detection elements **120a**, first lines **120b**, and second lines **120c** are formed. In the vertical driver formation regions **122** and **124**, respective vertical drivers **122a** and **124a** are formed. In the signal readout circuit formation region **126**, signal readout circuits **126a** are formed.

(28) The detection elements **120a** are arranged in a matrix on a surface of the input section **110** and are exemplified by, for example, photosensitive thin-film transistors. To obtain fingerprint image data with a resolution for personal identification, the detection elements **120a** are preferably

arranged with a pitch of, for example, 50 μm approximately.

(29) The first lines **120b** connect the detection elements **120a** in a first direction and the second lines **120c** connect the detection elements **120a** in a second direction different from the first direction. For example, as illustrated in FIG. 3, the first lines **120b** connect gate electrodes of the detection elements **120a** in a horizontal row to each other and are connected to the vertical drivers **122a**. The first lines **120b** also connect source electrodes (or drain electrodes) of the detection elements **120a** in a horizontal row to each other and are connected to the vertical drivers **124a**. The second lines **120c** connect drain electrodes (or source electrodes) of the detection elements **120a** in a vertical row to each other and are connected to the signal readout circuits **126a**.

(30) FIGS. 4 and 5 are diagrams illustrating functions of the information processing system **100**. In the information processing system **100**, the processing section **160** narrows down a region to be read by the biometric information reading mechanism **114** based on the position information of the position specifier obtained from the position detection mechanism **112** and activates the biometric information reading mechanism **114** in the reading region thus narrowed down to obtain the biometric information. That is, when a user contacts a finger as the position specifier to the region A, the processing section **160** causes the position detection mechanism **112** to specify the region A to narrow down the region to be read by the biometric information reading mechanism **114** to the region A and causes the biometric information reading mechanism **114** to be activated in the region A to obtain the biometric information.

(31) For example, at the point when the processing section **160** obtains the position information of the position specifier (e.g., a finger of the user) by the position detection mechanism **112**, as illustrated in FIG. 4, the detection elements **120a** are activated only on horizontal coarse lines **128** prepared by reducing the first lines **120b** and vertical coarse lines **130** prepared by reducing the second lines **120c** to obtain the region A as the position information. Then, first lines **132** in the region A and second lines **134** in the region A are activated to obtain detailed fingerprint image data in the region A. That is, functioning the first lines **120b** and the second lines **120c** by reducing them allows the biometric information reading mechanism **114** to function as the position detection mechanism **112**.

(32) Functioning the first lines **120b** and the second lines **120c** by reducing them thus allows the biometric information reading mechanism **114** to function as the position detection mechanism **112** and detailed fingerprint image data to be obtained in the region narrowed down by the position detection mechanism **112** to obtain image data clearly in a short time with a resolution for personal identification at an arbitrary position in a large area region. In addition, the detailed image data for personal identification is obtained only in a recommended region, allowing image data for personal identification to be obtained efficiently with no waste.

(33) In the above case, the detection elements **120a**, the first lines **120b**, and the second lines **120c** formed in the detection element formation region **120**, the vertical drivers **122a** and **124a** formed in the vertical driver formation regions **122** and **124**, and the signal readout circuits **126a** formed in the signal readout circuit formation region **126** form the biometric information reading mechanism **114** and some of them also form the position detection mechanism **112**. The position detection mechanism **112** may be expressed as a mechanism configured to cause the biometric information reading mechanism **114** to function with reduced reading accuracy.

(34) Although the example has been described that both the first lines **120b** and the second lines **120c** are reduced in the operation of the processing section **160**, it should be noted that only either the first lines **120b** or the second lines **120c** may be reduced to function.

(35) FIG. 6 is a diagram illustrating another example of the input section **110**. The input section **110** illustrated in FIG. 6 has a touch screen **140** as the position detection mechanism **112**. The touch screen **140** allows detection of the position of the position specifier, such as a finger of the user, and reading of the biometric information by narrowing down to the position. In this case, the detection elements **120a**, the first lines **120b**, and the second lines **120c** formed in the detection element

formation region **120**, the vertical drivers **122a** and **124a** formed in the vertical driver formation regions **122** and **124**, and the signal readout circuits **126a** formed in the signal readout circuit formation region **126** form the biometric information reading mechanism **114**.

(36) FIG. **7** is a diagram illustrating still another example of the input section **110**. The input section **110** illustrated in FIG. **7** has a plurality of imaging devices **150** as the position detection mechanism **112**. Each imaging device **150** takes an image of a region **152** different from each other on the surface of the input section **110**. Detecting in which region **152** corresponding to each imaging device **150** the position specifier, such as a finger of the user, is located allows detection of the position of the position specifier and reading of the biometric information by narrowing down to the position.

(37) Although the detection elements **120a** and the like formed in the detection element formation region **120** may be the biometric information reading mechanism **114**, it should be noted that the image data taken by the imaging device **150** may be used as the fingerprint image data for obtaining the biometric information. In this case, the imaging device **150** also functions as the biometric information reading mechanism **114**. When used as the biometric information reading mechanism **114**, the imaging device **150** is preferably provided with a prism to contact a finger and the like. Although the case of the plurality of imaging devices **150** is described above as an example, a single imaging device **150** may be applied when the imaging device **150** is capable of covering the entire area of the input section **110** by adjusting the direction of imaging, the depth of focus, and the like.

Second Embodiment

(38) FIG. **8** is a conceptual diagram illustrating an information processing system **200**. The information processing system **200** has, in addition to a display section **210**, the same configuration as the information processing system **100** in the first embodiment. The description on the same configuration as the information processing system **100** is omitted.

(39) The display section **210** is a display device, such as a liquid crystal display device and an electroluminescent display device, and is arranged facing the input section **110**. The input section **110** is transparent or semitransparent to allow a user to visually recognize the display contents of the display section **210** through the input section **110**.

(40) The processing section **160** is provided with, in addition to the functions described in the first embodiment, a function to control the display section **210**. The processing section **160** performs next processing based on the position information of the position specifier obtained from the position detection mechanism **112** and the user attribute information, for example user identification information, associated with the biometric information obtained from the biometric information reading mechanism **114**. For example, in the next processing, the processing section **160** selects and performs a function in accordance with the attribute information (e.g., payment processing in accordance with the user identification) among functions assigned to the position of the display section **210** specified in the position information (e.g., function of product selection in a shopping site and seat selection in a ticket reservation site). Specific examples are described below.

(41) FIGS. **9**, **12**, **15**, and **18** are flow charts illustrating processing of the information processing system **200**. FIGS. **10**, **11**, **13**, **14**, **16**, **17**, **19**, and **20** are diagrams illustrating examples of a display of the information processing system **200**.

(42) In the information processing system **200**, when the process is started (S220), a login screen is displayed as illustrated in FIG. **10** (S222), and for example, a user contacts a finger to the region A to perform touch detection and fingerprint identification (S224). When the user is identified by the fingerprint identification (S226), a menu screen as illustrated in FIG. **11** is displayed (S228). When not identified, the process goes back to the login screen at S222. On the menu screen in FIG. **11**, menus of, for example, "Folder", "Shopping", and "Seat Reservation" are displayed and the process is branched to folder processing (S232), shopping processing (S234), and seat reservation processing (S236) in accordance with menu selection (S230) by the user. After performing the

relevant processing, the process is terminated (S238).

(43) The menu selection by the user is performed by, for example, contacting a finger of the user to any of the menu regions. For example, when the contacted region A is in a display region for the folder processing as illustrated in FIG. 11, the folder processing is selected.

(44) FIG. 12 is an example of a process flow when the folder processing is selected. When the folder processing is started (S240), a folder selection screen is displayed (S242) as illustrated in FIG. 13 and touch detection is performed by, for example, contacting a finger to the region A by the user (S244). Whether the selected folder is a folder exclusive for the user is determined (S246), and when it is the exclusive folder, fingerprint identification is performed (S248). Whether the identification is passed in the fingerprint identification is determined (S250), and when the identification is passed, the selected exclusive A folder is opened (S252) as illustrated in FIG. 14. When the identification is not passed, the process is terminated (S258). When the selected folder is determined not as an exclusive folder at S246, whether it is a shared folder is determined (S254). A selection folder is then opened (S256) when it is a shared folder, while the process is terminated (S258) when it is not.

(45) According to the flow in FIG. 12, one operation of contacting a finger (folder selection) by the user simultaneously allows selecting a folder and obtaining image data for passing the personal identification and thus allows the process to be performed without requesting data input and the like of the user for personal identification even when the selected folder is an exclusive folder. As a result, the process flow seen by the user is extremely smooth and it is thus possible to provide good user experience.

(46) FIG. 15 is an example of a process flow when the shopping processing is selected. When the shopping processing is started (S260), a product selection screen is displayed (S262) as illustrated in FIG. 16 and touch detection and fingerprint identification are performed by, for example, contacting a finger to the region A by the user (S264). Whether the identification is passed in the fingerprint identification is determined (S266), and when the identification is passed, a product at a touched position is selected (S268) and product purchase processing and payment processing are performed (S270). As illustrated in FIG. 17, a purchase confirmation screen is then displayed (S272) and the process is terminated (S274). When the identification is determined not to be passed at S266, the process is terminated (S274).

(47) As just described, one operation of contacting a finger (product selection) by the user simultaneously allows selecting a product and obtaining image data for passing the personal identification and thus allows the process to be performed without requesting data input and the like of the user for user identification in the payment processing during the product purchase. As a result, the process flow seen by the user is extremely smooth and it is thus possible to provide good user experience.

(48) FIG. 18 is an example of a process flow when the reservation processing is selected. When the reservation processing is started (S276), a seat selection screen is displayed (S278) as illustrated in FIG. 19 and touch detection and fingerprint identification are performed by, for example, contacting a finger to the region A by the user (S280). Whether the identification is passed in the fingerprint identification is determined (S282), and when the identification is passed, a seat "B9" at a touched position is selected (S284) and seat reservation processing and payment processing are performed (S286). As illustrated in FIG. 20, a reservation confirmation screen is then displayed (S288) and the process is terminated (S290). When the identification is determined not to be passed at S282, the process is terminated (S290).

(49) As just described, one operation of contacting a finger (seat selection) by the user simultaneously allows selecting a seat and obtaining image data for passing the personal identification and thus allows the process to be performed without requesting data input and the like of the user for user identification in the payment processing during the seat reservation. As a result, the process flow seen by the user is extremely smooth and it is thus possible to provide good

user experience.

(50) As described above, the information processing system **200** in the second embodiment does not require a user to input data for personal identification during access to a personally exclusive file, product purchase, and seat reservation and thus allows smooth progress of a series of process flow in file operation, a reservation site, and an electronic commerce site to achieve excellent user experience.

(51) Although the present invention has been described with reference to the above embodiments, the technical scope of the present invention is not limited to the scope of the above embodiments. It will become apparent to those skilled in the art that the above embodiments may be variously modified or improved. From the appended claims, it will be apparent that the technical scope of the present invention may include such modified or improved embodiments.

(52) For example, although exemplified by a finger of the user in the above embodiments, the position specifier is not limited to this example. In addition, although exemplified by a fingerprint of the user, the body for biometric identification is not limited to this example. For example, it is possible to use, as the biometric information, a pattern or a feature corresponding to a single or a plurality of biometric areas selected from a fingerprint, a vein pattern, the face, an iris, and a voiceprint of the user.

(53) It should be noted that the order of performing each process of the operations, the procedures, the steps, the stages, and the like in the devices, the systems (, programs), and the methods in the appended claims, the description, and the drawings may be achieved in an arbitrary order unless explicitly indicated as “before”, “prior to”, and the like in particular or unless using an output of previous processing for later processing. Even when the operation flow in the claims, the description, and the drawings is described for convenience using “first”, “then”, and the like, it does not mean execution in this order is essential.

REFERENCE SIGNS LIST

(54) **100** Information Processing System, **110** Input Section, **112** Position Detection Mechanism, **114** Biometric Information Reading Mechanism, **120** Detection Element Formation Region, **120a** Detection Element, **120b** First Line, **120c** Second Line, **122**, **124** Vertical Driver Formation Region, **122a**, **124a** Vertical Driver, **126** Signal Readout Circuit Formation Region, **126a** Signal Readout Circuit, **128** Horizontal Coarse Line, **130** Vertical Coarse Line, **132** First Line in Region A, **134** Second Line in Region A, **140** Touch Screen, **150** Imaging Device, **152** Region, **160** Processing Section, **200** Information Processing System, **210** Display Section.

Claims

1. An information processing system, comprising: an input section having a surface and being configured to allow a user to contact or approximate a finger to the surface to input information; wherein the input section comprises: a position detection mechanism configured to detect a position of the finger approximate to the surface, and a reading mechanism configured to read biometric information of the user; and a processing section configured to perform processing based on the information input to the input section; and a display section displaying a menu screen, wherein the input section transmits a position information of a region where a finger contacts to the processing section, and at the same time, the biometric information of the user is transmitted to the processing section, when a menu selection by the user is performed by contacting a screen of the display section with the user's finger, wherein the reading mechanism and the position detection mechanism comprise a plurality of imaging devices wherein each of the imaging devices is configured to take an image of a region different from each other on the surface, and wherein optical resolving of biometric information of the user is performed using only one imaging device, which corresponds to the position of the plurality of the imaging devices.

2. The information processing system according to claim 1, wherein the processing section:

narrows down a region to be read by the reading mechanism based on position information of the finger obtained from the position detection mechanism, and activates the reading mechanism in the reading region to obtain the biometric information.

3. The information processing system according to claim 1, wherein the processing section is configured to perform next processing based on position information of the finger obtained from the position detection mechanism and attribute information of the user associated with the biometric information obtained from the reading mechanism.

4. The information processing system according to claim 3, wherein the processing section selects and performs, in the next processing, a function in accordance with the attribute information among functions assigned to the position of the display section specified in the position information.

5. The information processing system according to claim 1, wherein the position detection mechanism is a device configured to cause the reading mechanism to function with reduced reading accuracy, a touch screen, or a single or a plurality of imaging devices.

6. The information processing system according to claim 5, wherein the reading mechanism has detection elements arranged in a matrix on the surface, first lines connecting the detection elements in a first direction, and second lines connecting the detection elements in a second direction different from the first direction and is configured to cause the reading mechanism to function as the position detection mechanism by reducing the first lines, the second lines, or both the first lines and the second lines during their function.

7. An information processing system, comprising: an input section having a surface and being configured to allow a user to contact or approximate a finger to the surface to input information; wherein the input section comprises: a position detection mechanism configured to detect a position of the finger approximate to the surface, and a reading mechanism configured to read biometric information of the user; and a processing section configured to perform processing based on the information input to the input section; and a display section displaying a menu screen, wherein the input section transmits a position information of a region where a finger contacts to the processing section, and at the same time, the biometric information of the user is transmitted to the processing section, when a menu selection by the user is performed by contacting a screen of the display section with the user's finger, wherein the position detection and reading mechanisms comprise a plurality of imaging devices, wherein each of the imaging devices is configured to take an image of a distinct, substantially non-overlapping or intersecting region of the input section, and wherein optical resolving of biometric information of the user is performed using only one imaging device, which corresponds to the position, of the plurality of the imaging devices.

8. The information processing system of claim 7, wherein each of the imaging devices is configured to take an image of a distinct, substantially non-overlapping or intersecting region of the input section.
