

(12) **United States Patent**
Adie et al.

(10) **Patent No.:** **US 12,414,878 B2**
(45) **Date of Patent:** **Sep. 16, 2025**

(54) **WOUND DRESSING AND METHOD OF USE**

(71) Applicant: **Smith & Nephew PLC**, Watford (GB)

(72) Inventors: **Gordon Campbell Adie**, Cottingham (GB); **Sarah Jenny Collinson**, Hull (GB); **Christopher John Fryer**, York (GB); **Edward Yerbury Hartwell**, Hull (GB); **Derek Nicolini**, Hull (GB); **Yannick Louis Peron**, East Yorkshire (GB)

(73) Assignee: **Smith & Nephew PLC**, Watford (GB)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 453 days.

(21) Appl. No.: **17/565,840**

(22) Filed: **Dec. 30, 2021**

(65) **Prior Publication Data**

US 2022/0117797 A1 Apr. 21, 2022

Related U.S. Application Data

(63) Continuation of application No. 17/372,252, filed on Jul. 9, 2021, which is a continuation of application (Continued)

(30) **Foreign Application Priority Data**

Apr. 27, 2010 (GB) 1006983

Apr. 27, 2010 (GB) 1006985

(Continued)

(51) **Int. Cl.**

A61F 13/05 (2024.01)

A61F 13/00 (2024.01)

(Continued)

(52) **U.S. Cl.**

CPC **A61F 13/05** (2024.01); **A61F 13/0206** (2013.01); **A61F 13/0209** (2013.01); (Continued)

(58) **Field of Classification Search**

CPC .. **A61F 13/05**; **A61F 13/0206**; **A61F 13/0209**; **A61F 13/022**; **A61F 13/01012**; (Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,280,915 A 4/1942 Johnson

2,568,933 A 9/1951 Robbins

(Continued)

FOREIGN PATENT DOCUMENTS

AU 2015201022 B2 9/2016

CA 2705898 A1 5/2009

(Continued)

OTHER PUBLICATIONS

Brief communication—Letter from the Opponent of Feb. 24, 2023 for European Patent No. 3628289, mailed on Mar. 1, 2023, 11 pages.

(Continued)

Primary Examiner — Rebecca E Eisenberg

Assistant Examiner — Matthew Wrubleski


(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear, LLP

(57)

ABSTRACT

A system, method, and apparatus are disclosed for dressing a wound. The apparatus comprises a liquid and gas permeable transmission layer, an absorbent layer for absorbing wound exudate, the absorbent layer overlying the transmission layer, a gas impermeable cover layer overlying the absorbent layer and comprising a first orifice, wherein the cover layer is moisture vapor permeable.

19 Claims, 21 Drawing Sheets



Related U.S. Application Data

No. 16/118,339, filed on Aug. 30, 2018, now Pat. No. 11,058,587, which is a continuation of application No. 15/633,670, filed on Jun. 26, 2017, now Pat. No. 10,159,604, which is a continuation of application No. 14/715,399, filed on May 18, 2015, now Pat. No. 9,808,561, which is a continuation of application No. 13/092,042, filed on Apr. 21, 2011, now Pat. No. 9,061,095.

(30) Foreign Application Priority Data

Apr. 27, 2010 (GB) 1006986
 Apr. 27, 2010 (GB) 1006988
 May 19, 2010 (GB) 1008347

(51) Int. Cl.

A61F 13/01 (2024.01)
A61F 13/0203 (2024.01)
A61F 13/0206 (2024.01)
A61M 1/00 (2006.01)

(52) U.S. Cl.

CPC *A61F 13/022* (2013.01); *A61M 1/913* (2021.05); *A61M 1/915* (2021.05); *A61M 1/985* (2021.05); *A61F 2013/00174* (2013.01); *A61F 2013/00238* (2013.01); *A61F 2013/00536* (2013.01); *A61F 2013/0054* (2013.01); *A61F 13/01012* (2024.01); *A61M 1/912* (2021.05); *A61M 1/916* (2021.05); *A61M 1/918* (2021.05); *A61M 1/962* (2021.05); *A61M 2202/0014* (2013.01); *A61M 2205/7536* (2013.01)

(58) Field of Classification Search

CPC .. *A61F 2013/00174*; *A61F 2013/00238*; *A61F 2013/00536*; *A61F 2013/0054*; *A61F 2013/530875*; *A61F 13/533*; *A61F 13/536*; *A61F 2013/53782*; *A61F 2013/00255*; *A61F 13/01029*; *A61M 1/913*; *A61M 1/915*; *A61M 1/985*; *A61M 1/912*; *A61M 1/916*; *A61M 1/918*; *A61M 1/962*; *A61M 2202/0014*; *A61M 2205/7536*

See application file for complete search history.

(56) References Cited**U.S. PATENT DOCUMENTS**

2,632,443 A 3/1953 Leshner
 2,682,873 A 7/1954 Idnis et al.
 2,877,765 A 3/1959 John et al.
 2,889,039 A 6/1959 Peter et al.
 2,923,298 A 2/1960 Dockstadter et al.
 3,073,304 A 1/1963 Schaar
 3,115,138 A 12/1963 McElvenny et al.
 3,367,332 A 2/1968 Groves
 3,572,340 A 3/1971 Lloyd et al.
 3,874,387 A 4/1975 Barbieri
 3,903,882 A 9/1975 Augurt
 3,972,328 A 8/1976 Chen
 3,993,080 A 11/1976 Loseff
 4,029,598 A 6/1977 Neisius et al.
 4,112,947 A 9/1978 Nehring
 4,117,551 A 9/1978 Brooks et al.
 4,136,696 A 1/1979 Nehring
 4,181,127 A * 1/1980 Linsky A61L 15/24
 4,184,510 A 1/1980 Murry et al.
 4,217,894 A 8/1980 Franetzki

4,219,019 A 8/1980 Coates
 4,224,945 A 9/1980 Cohen
 4,294,240 A 10/1981 Thill
 4,316,466 A 2/1982 Babb
 4,382,441 A 5/1983 Svedman
 4,465,485 A 8/1984 Kashmer et al.
 4,534,356 A 8/1985 Papadakis
 4,538,920 A 9/1985 Drake
 4,541,426 A 9/1985 Webster
 4,573,965 A 3/1986 Russo
 4,592,751 A 6/1986 Gegelys
 4,655,754 A 4/1987 Richmond et al.
 4,655,766 A 4/1987 Theeuwes et al.
 4,710,165 A 12/1987 McNeil et al.
 4,728,499 A 3/1988 Fehder
 4,753,536 A 6/1988 Spehar et al.
 4,767,026 A 8/1988 Keller et al.
 4,771,919 A 9/1988 Ernst
 4,778,446 A 10/1988 Jensen
 4,792,328 A 12/1988 Beck et al.
 4,813,942 A 3/1989 Alvarez
 4,826,494 A 5/1989 Richmond et al.
 4,828,546 A 5/1989 McNeil et al.
 4,846,164 A 7/1989 Martz
 4,872,450 A 10/1989 Austad
 4,921,488 A 5/1990 Maitz et al.
 4,929,477 A 5/1990 Will
 4,936,834 A 6/1990 Beck et al.
 4,969,880 A 11/1990 Zamierowski
 4,972,829 A 11/1990 Knerr
 4,994,022 A 2/1991 Steffler et al.
 5,010,115 A 4/1991 Grisoni
 5,010,883 A 4/1991 Rawlings et al.
 5,055,198 A 10/1991 Shettigar
 5,056,510 A 10/1991 Gilman
 5,064,653 A 11/1991 Sessions et al.
 5,073,172 A 12/1991 Fell
 5,080,493 A 1/1992 McKown et al.
 5,100,396 A 3/1992 Zamierowski
 5,115,801 A 5/1992 Cartmell et al.
 5,134,994 A 8/1992 Say
 5,145,906 A 9/1992 Chambers et al.
 5,152,757 A 10/1992 Eriksson
 5,160,328 A 11/1992 Cartmell et al.
 5,167,613 A 12/1992 Karami et al.
 5,176,663 A 1/1993 Svedman et al.
 5,181,905 A 1/1993 Flam
 5,197,945 A 3/1993 Cole et al.
 5,215,519 A 6/1993 Shettigar
 5,234,419 A 8/1993 Bryant et al.
 5,238,732 A 8/1993 Krishnan
 5,249,709 A 10/1993 Duckworth et al.
 5,261,893 A 11/1993 Zamierowski
 5,266,326 A 11/1993 Barry et al.
 5,266,928 A 11/1993 Johnson
 5,267,952 A 12/1993 Gardner
 5,279,608 A 1/1994 Cherif Cheikh
 5,308,313 A 5/1994 Karami et al.
 5,328,614 A 7/1994 Matsumura
 5,333,760 A 8/1994 Simmen
 5,336,219 A 8/1994 Krantz
 5,354,261 A 10/1994 Clark et al.
 5,358,494 A 10/1994 Svedman
 5,364,381 A 11/1994 Soga et al.
 5,380,280 A 1/1995 Peterson
 5,380,294 A 1/1995 Persson
 5,397,316 A 3/1995 LaVon et al.
 5,437,651 A 8/1995 Todd et al.
 5,445,604 A 8/1995 Lang
 5,447,492 A 9/1995 Cartmell et al.
 5,456,660 A 10/1995 Reich et al.
 5,456,745 A 10/1995 Roreger et al.
 5,480,377 A 1/1996 Cartmell et al.
 5,489,280 A 2/1996 Russell
 5,497,788 A 3/1996 Inman et al.
 5,498,338 A 3/1996 Kruger et al.
 5,527,293 A 6/1996 Zamierowski
 5,538,500 A 7/1996 Peterson
 5,540,922 A 7/1996 Fabo

(56)

References Cited

U.S. PATENT DOCUMENTS

5,549,584	A	8/1996	Gross	6,450,773	B1	9/2002	Upton
5,553,998	A	9/1996	Muhlhoff et al.	6,458,109	B1	10/2002	Henley et al.
5,562,107	A	10/1996	Lavender et al.	6,465,708	B1	10/2002	Augustine
5,579,765	A	12/1996	Cox et al.	6,468,295	B2	10/2002	Augustine et al.
5,582,596	A	12/1996	Fukunaga et al.	6,471,982	B1	10/2002	Lydon et al.
5,583,114	A	12/1996	Barrows et al.	6,486,285	B2	11/2002	Fujita
5,603,946	A	2/1997	Constantine	6,491,684	B1	12/2002	Joshi et al.
5,609,271	A	3/1997	Keller et al.	6,495,127	B1	12/2002	Wallace et al.
5,612,050	A	3/1997	Rowe et al.	6,506,175	B1	1/2003	Goldstein
5,624,423	A	4/1997	Anjur et al.	6,509,031	B1	1/2003	Miller et al.
5,636,643	A	6/1997	Argenta et al.	6,521,251	B2	2/2003	Askill et al.
5,637,080	A	6/1997	Geng	6,528,696	B1	3/2003	Ireland
5,643,189	A	7/1997	Masini	6,547,467	B2	4/2003	Quintero
5,645,081	A	7/1997	Argenta et al.	6,553,998	B2	4/2003	Heaton et al.
5,660,823	A	8/1997	Chakrabarti et al.	6,566,575	B1	5/2003	Stickels et al.
5,662,599	A	9/1997	Reich et al.	6,575,940	B1	6/2003	Levinson et al.
5,702,356	A	12/1997	Hathman	6,586,653	B2	7/2003	Graeme, III et al.
5,704,905	A	1/1998	Jensen et al.	6,596,704	B1	7/2003	Court et al.
5,707,499	A	1/1998	Joshi et al.	6,599,262	B1	7/2003	Masini
5,713,384	A	2/1998	Roach et al.	6,613,953	B1	9/2003	Altura
5,717,030	A	2/1998	Dunn et al.	6,626,891	B2	9/2003	Ohmstede
5,747,064	A	5/1998	Burnett et al.	6,627,216	B2	9/2003	Brandt et al.
5,759,570	A	6/1998	Arnold	6,629,774	B1	10/2003	Gruendeman
5,776,193	A	7/1998	Kwan et al.	6,648,862	B2	11/2003	Watson
5,785,688	A	7/1998	Joshi et al.	6,653,520	B1	11/2003	Mouton
5,795,439	A	8/1998	Euripides et al.	6,673,028	B1	1/2004	Argenta et al.
5,804,021	A	9/1998	Abuto et al.	6,685,681	B2	2/2004	Lockwood et al.
5,827,213	A	10/1998	Jensen	6,695,823	B1	2/2004	Lina et al.
5,833,646	A	11/1998	Masini	6,695,824	B2	2/2004	Howard et al.
5,834,007	A	11/1998	Kubota	6,706,940	B2	3/2004	Worthley
5,840,052	A	11/1998	Johns	6,719,742	B1	4/2004	McCormack et al.
5,843,011	A	12/1998	Lucas	6,730,299	B1	5/2004	Tayot et al.
5,843,025	A	12/1998	Shaari	6,752,794	B2	6/2004	Lockwood et al.
5,852,126	A	12/1998	Barnard et al.	6,755,807	B2	6/2004	Risk, Jr. et al.
5,868,724	A	2/1999	Dierckes, Jr. et al.	6,762,337	B2	7/2004	Boukanov et al.
5,868,933	A	2/1999	Patrick et al.	6,764,459	B1	7/2004	Donaldson
5,874,500	A	2/1999	Rhee et al.	6,764,462	B2	7/2004	Risk, Jr. et al.
5,876,611	A	3/1999	Shettigar	6,767,334	B1	7/2004	Randolph
5,897,541	A	4/1999	Uitenbroek et al.	6,775,807	B2	8/2004	Lowther et al.
5,945,115	A	8/1999	Dunn et al.	6,776,769	B2	8/2004	Smith
5,962,010	A	10/1999	Greff et al.	6,787,682	B2	9/2004	Gilman
5,964,723	A	10/1999	Augustine	6,790,438	B1	9/2004	Constancis et al.
5,981,822	A	11/1999	Addison	6,814,079	B2	11/2004	Heaton et al.
5,998,472	A	12/1999	Berger et al.	6,824,533	B2	11/2004	Risk, Jr. et al.
6,040,493	A	3/2000	Cooke et al.	6,838,589	B2	1/2005	Liedtke et al.
6,071,267	A	6/2000	Zamierowski	6,855,135	B2	2/2005	Lockwood et al.
6,075,177	A	6/2000	Bahia et al.	6,856,821	B2	2/2005	Johnson
6,103,951	A	8/2000	Freeman	6,936,037	B2	8/2005	Bubb et al.
6,124,520	A	9/2000	Roberts	6,951,553	B2	10/2005	Bubb et al.
6,124,521	A	9/2000	Roberts	6,960,179	B2	11/2005	Gura
6,135,116	A	10/2000	Vogel et al.	6,977,323	B1	12/2005	Swenson
6,142,982	A	11/2000	Hunt et al.	6,979,324	B2	12/2005	Bybordi et al.
6,143,352	A	11/2000	Clark et al.	6,994,702	B1	2/2006	Johnson
6,165,201	A	12/2000	Sawhney et al.	6,998,511	B2	2/2006	Worthley
6,167,613	B1	1/2001	Jarrett et al.	7,004,915	B2	2/2006	Boynton et al.
6,168,788	B1	1/2001	Wortham	7,022,113	B2	4/2006	Lockwood et al.
6,168,800	B1	1/2001	Dobos et al.	7,049,478	B1	5/2006	Smith
6,203,654	B1	3/2001	McFall et al.	7,067,709	B2	6/2006	Murata et al.
6,207,875	B1	3/2001	Lindqvist et al.	7,070,584	B2	7/2006	Johnson et al.
6,214,332	B1	4/2001	Askill et al.	7,077,832	B2	7/2006	Fleischmann
6,225,523	B1	5/2001	Masini	7,087,806	B2	8/2006	Scheinberg et al.
6,252,129	B1	6/2001	Coffee	7,108,683	B2	9/2006	Zamierowski
6,254,567	B1	7/2001	Treu et al.	7,117,869	B2	10/2006	Heaton et al.
6,255,552	B1	7/2001	Cummings et al.	7,118,545	B2	10/2006	Boyde
6,287,521	B1	9/2001	Quay et al.	7,128,735	B2	10/2006	Weston
6,291,050	B1	9/2001	Cree et al.	7,129,210	B2	10/2006	Lowinger et al.
6,297,422	B1	10/2001	Hansen et al.	7,195,624	B2	3/2007	Lockwood et al.
6,297,423	B1	10/2001	Schoenfeldt et al.	7,214,202	B1	5/2007	Vogel et al.
6,345,623	B1	2/2002	Heaton et al.	7,216,651	B2	5/2007	Argenta et al.
6,362,390	B1	3/2002	Carlucci et al.	7,238,850	B2	7/2007	Shimanuki
6,391,294	B1	5/2002	Dettmar et al.	7,294,751	B2	11/2007	Propp et al.
6,398,761	B1	6/2002	Bills et al.	7,294,752	B1	11/2007	Propp
6,398,767	B1	6/2002	Fleischmann	7,303,757	B2	12/2007	Schankereli et al.
6,440,167	B2	8/2002	Shimizu	7,335,809	B2	2/2008	Riesinger
6,447,802	B2	9/2002	Sessions et al.	7,338,482	B2	3/2008	Lockwood et al.
				7,361,184	B2	4/2008	Joshi
				7,381,211	B2	6/2008	Zamierowski
				7,381,859	B2	6/2008	Hunt et al.
				7,401,394	B1	7/2008	Muller

(56)

References Cited

U.S. PATENT DOCUMENTS

7,429,689 B2	9/2008	Chen et al.	7,988,673 B2	8/2011	Wright et al.
7,438,705 B2	10/2008	Karpowicz et al.	7,998,125 B2	8/2011	Weston
7,468,471 B2	12/2008	Sigurjonsson et al.	8,007,164 B2	8/2011	Miyano et al.
7,470,830 B2	12/2008	Sigurjonsson et al.	8,007,257 B2	8/2011	Heaton et al.
7,476,205 B2	1/2009	Erdmann	8,021,347 B2	9/2011	Vitaris et al.
7,485,112 B2	2/2009	Karpowicz et al.	8,025,650 B2	9/2011	Anderson et al.
7,494,482 B2	2/2009	Orgill et al.	8,034,037 B2	10/2011	Adams et al.
7,503,910 B2	3/2009	Adahan	8,062,272 B2	11/2011	Weston
7,507,870 B2	3/2009	Nielsen et al.	8,062,331 B2	11/2011	Zamierowski
7,511,187 B2	3/2009	Kelly	8,080,702 B2	12/2011	Blott et al.
7,524,286 B2	4/2009	Johnson	8,084,663 B2	12/2011	Watson, Jr.
7,524,315 B2	4/2009	Blott et al.	8,092,436 B2	1/2012	Christensen
7,534,240 B1	5/2009	Johnson	8,097,272 B2	1/2012	Addison
7,534,927 B2	5/2009	Lockwood et al.	8,100,887 B2	1/2012	Weston et al.
7,563,940 B2	7/2009	Kurata	8,105,295 B2	1/2012	Blott et al.
7,569,742 B2	8/2009	Haggstrom et al.	8,118,794 B2	2/2012	Weston
7,576,256 B2	8/2009	Bjornberg et al.	8,119,160 B2	2/2012	Looney et al.
7,601,129 B2	10/2009	Aali	8,133,211 B2	3/2012	Cavanaugh, II et al.
7,605,298 B2	10/2009	Bechert et al.	8,147,468 B2	4/2012	Barta et al.
7,612,247 B2	11/2009	Oyaski	8,152,785 B2	4/2012	Vitaris
7,615,036 B2	11/2009	Joshi et al.	8,158,844 B2	4/2012	McNeil
7,622,629 B2	11/2009	Aali	8,162,907 B2	4/2012	Heagle
7,625,362 B2	12/2009	Boehringer et al.	8,162,909 B2	4/2012	Blott et al.
7,645,269 B2	1/2010	Zamierowski	8,168,848 B2	5/2012	Lockwood et al.
7,676,400 B1	3/2010	Dillon	8,188,331 B2	5/2012	Barta et al.
7,699,823 B2	4/2010	Haggstrom et al.	8,202,261 B2	6/2012	Kazala, Jr. et al.
7,699,830 B2	4/2010	Martin	8,207,392 B2	6/2012	Haggstrom et al.
7,700,819 B2	4/2010	Ambrosio et al.	8,211,071 B2	7/2012	Mormino et al.
7,708,724 B2	5/2010	Weston	8,212,101 B2	7/2012	Propp
7,717,313 B2	5/2010	Crisuolo et al.	8,215,929 B2	7/2012	Shen et al.
7,718,249 B2	5/2010	Russell et al.	8,226,942 B2	7/2012	Charier et al.
7,722,582 B2	5/2010	Lina et al.	8,235,955 B2	8/2012	Blott et al.
7,723,560 B2	5/2010	Lockwood et al.	8,235,972 B2	8/2012	Adahan
7,723,561 B2	5/2010	Propp	8,241,261 B2	8/2012	Randolph et al.
7,731,702 B2	6/2010	Bybordi et al.	8,246,607 B2	8/2012	Karpowicz et al.
7,745,681 B1	6/2010	Ferguson	8,251,979 B2	8/2012	Malhi
7,749,531 B2	7/2010	Booher	8,252,971 B2	8/2012	Aali et al.
7,753,894 B2	7/2010	Blott et al.	8,257,327 B2	9/2012	Blott et al.
7,759,537 B2	7/2010	Bishop et al.	8,257,328 B2	9/2012	Augustine et al.
7,759,538 B2	7/2010	Fleischmann	8,267,908 B2	9/2012	Coulthard
7,759,539 B2	7/2010	Shaw et al.	8,273,368 B2	9/2012	Ambrosio et al.
7,775,998 B2	8/2010	Riesinger	8,282,611 B2	10/2012	Weston
7,776,028 B2	8/2010	Miller et al.	8,294,586 B2	10/2012	Pidgeon et al.
7,779,625 B2	8/2010	Joshi et al.	8,303,552 B2	11/2012	Weston
7,790,945 B1	9/2010	Watson, Jr.	8,308,714 B2	11/2012	Weston et al.
7,794,438 B2	9/2010	Henley et al.	8,314,283 B2	11/2012	Kingsford et al.
7,794,450 B2	9/2010	Blott et al.	8,317,774 B2	11/2012	Adahan
7,803,980 B2	9/2010	Griffiths et al.	8,323,264 B2	12/2012	Weston et al.
7,811,269 B2	10/2010	Boynton et al.	8,328,858 B2	12/2012	Barsky et al.
7,815,616 B2	10/2010	Boehringer et al.	8,348,910 B2	1/2013	Blott et al.
7,816,577 B2	10/2010	Aali	8,372,049 B2	2/2013	Jaeb et al.
7,828,782 B2	11/2010	Suzuki	8,372,050 B2	2/2013	Jaeb et al.
7,838,716 B2	11/2010	De Luis et al.	8,376,972 B2	2/2013	Fleischmann
7,838,717 B2	11/2010	Haggstrom et al.	8,382,731 B2	2/2013	Johannison
7,846,141 B2	12/2010	Weston	8,403,899 B2	3/2013	Sherman
7,857,806 B2	12/2010	Karpowicz et al.	8,404,921 B2	3/2013	Lee et al.
7,858,838 B2	12/2010	Holm et al.	D679,819 S	4/2013	Peron
7,862,831 B2	1/2011	Wang et al.	D679,820 S	4/2013	Peron
7,880,050 B2	2/2011	Robinson et al.	8,409,159 B2	4/2013	Hu et al.
7,884,258 B2	2/2011	Boehringer et al.	8,410,189 B2	4/2013	Carnahan et al.
7,896,823 B2	3/2011	Mangrum et al.	8,425,478 B2	4/2013	Olson
7,896,856 B2	3/2011	Petrosenko et al.	8,444,612 B2	5/2013	Patel et al.
7,909,805 B2	3/2011	Weston	8,449,509 B2	5/2013	Weston
7,910,135 B2	3/2011	St. John et al.	8,460,255 B2	6/2013	Joshi et al.
7,910,791 B2	3/2011	Coffey	8,494,349 B2	7/2013	Gordon
7,922,703 B2	4/2011	Riesinger	8,506,554 B2	8/2013	Adahan
7,927,318 B2	4/2011	Risk, Jr. et al.	8,535,283 B2	9/2013	Heaton et al.
7,931,630 B2	4/2011	Nishtala et al.	8,535,296 B2	9/2013	Blott et al.
7,935,066 B2	5/2011	Shives et al.	8,540,687 B2	9/2013	Henley et al.
7,959,624 B2	6/2011	Riesinger	8,545,466 B2	10/2013	Andresen et al.
7,964,766 B2	6/2011	Blott et al.	8,556,871 B2	10/2013	Mormino et al.
7,976,519 B2	7/2011	Bubb et al.	8,568,386 B2	10/2013	Malhi
7,982,087 B2	7/2011	Greener et al.	8,569,566 B2	10/2013	Blott et al.
7,985,209 B2	7/2011	Villanueva et al.	8,624,077 B2	1/2014	Rosenberg
D642,594 S	8/2011	Mattson et al.	8,628,505 B2	1/2014	Weston
			8,641,691 B2	2/2014	Fink et al.
			8,663,198 B2	3/2014	Buan et al.
			8,679,079 B2	3/2014	Heaton et al.
			8,680,360 B2	3/2014	Greener et al.

(56)	References Cited			2003/0153860 A1 *	8/2003	Nielsen	A61F 13/0259 602/58
	U.S. PATENT DOCUMENTS			2003/0171675 A1	9/2003	Rosenberg	
				2003/0175798 A1	9/2003	Raees et al.	
	8,715,256 B2	5/2014	Greener	2003/0180341 A1	9/2003	Gooch et al.	
	8,734,410 B2	5/2014	Hall et al.	2003/0183653 A1	10/2003	Bills	
	8,753,670 B2	6/2014	Delmotte	2003/0199800 A1	10/2003	Levin	
	8,764,732 B2	7/2014	Hartwell	2003/0203011 A1	10/2003	Abuelyaman et al.	
	8,784,392 B2	7/2014	Vess et al.	2003/0212357 A1	11/2003	Pace	
	8,791,316 B2	7/2014	Greener	2003/0212359 A1	11/2003	Butler	
	8,795,243 B2	8/2014	Weston	2003/0212431 A1	11/2003	Brady et al.	
	8,795,244 B2	8/2014	Randolph et al.	2003/0219469 A1	11/2003	Johnson et al.	
	8,795,247 B2	8/2014	Bennett et al.	2003/0225347 A1	12/2003	Argenta et al.	
	8,795,635 B2	8/2014	Tamarkin et al.	2004/0019337 A1	1/2004	Moberg-Alehammar et al.	
	8,795,713 B2	8/2014	Makower et al.	2004/0019342 A1	1/2004	Nagasuna et al.	
	8,795,800 B2	8/2014	Evans	2004/0033466 A1	2/2004	Shellard et al.	
	8,801,685 B2	8/2014	Armstrong et al.	2004/0037897 A1	2/2004	Benjamin et al.	
	8,808,274 B2	8/2014	Hartwell	2004/0039391 A1	2/2004	Argenta et al.	
	8,814,842 B2	8/2014	Coulthard et al.	2004/0049187 A1	3/2004	Burnett et al.	
	8,829,263 B2	9/2014	Haggstrom et al.	2004/0054338 A1	3/2004	Bybordi et al.	
	8,834,451 B2	9/2014	Blott et al.	2004/0057855 A1	3/2004	Gerlach et al.	
	8,834,452 B2	9/2014	Hudspeth et al.	2004/0064111 A1	4/2004	Lockwood et al.	
	8,843,327 B2	9/2014	Vernon-Harcourt et al.	2004/0073152 A1	4/2004	Karason et al.	
	8,864,748 B2	10/2014	Coulthard et al.	2004/0078011 A1	4/2004	Stevens	
	8,915,895 B2	12/2014	Jaeb et al.	2004/0106888 A1	6/2004	Lutri et al.	
	8,916,742 B2	12/2014	Smith	2004/0122434 A1	6/2004	Argenta et al.	
	8,956,336 B2	2/2015	Haggstrom et al.	2004/0127863 A1	7/2004	Bubb et al.	
	8,968,773 B2	3/2015	Thomas et al.	2004/0138602 A1	7/2004	Rossen	
	9,012,714 B2	4/2015	Fleischmann	2004/0167617 A1	8/2004	Voellmicke et al.	
	9,028,872 B2	5/2015	Gaserod et al.	2004/0171998 A1	9/2004	Marasco, Jr.	
	9,033,942 B2	5/2015	Vess	2004/0193218 A1	9/2004	Butler	
	9,044,579 B2	6/2015	Blott et al.	2004/0200094 A1	10/2004	Baychar	
	9,061,095 B2	6/2015	Adie et al.	2004/0241214 A1	12/2004	Kirkwood et al.	
	9,168,330 B2	10/2015	Joshi et al.	2004/0243042 A1	12/2004	Lipman	
	9,180,231 B2	11/2015	Greener	2005/0015036 A1	1/2005	Lutri et al.	
	9,198,801 B2	12/2015	Weston	2005/0020955 A1	1/2005	Sanders et al.	
	9,199,012 B2	12/2015	Vitaris et al.	2005/0131327 A1	6/2005	Lockwood et al.	
	9,220,822 B2	12/2015	Hartwell	2005/0230422 A1	10/2005	Muller et al.	
	9,302,033 B2	4/2016	Riesinger	2005/0234417 A1	10/2005	Yoshimasa et al.	
	9,375,353 B2	6/2016	Vitaris et al.	2006/0009744 A1	1/2006	Erdman et al.	
	9,375,521 B2	6/2016	Hudspeth et al.	2006/0020234 A1	1/2006	Chou et al.	
	9,381,283 B2	7/2016	Adams et al.	2006/0029650 A1	2/2006	Coffey	
	9,421,309 B2	8/2016	Robinson et al.	2006/0070458 A1	4/2006	Jones et al.	
	9,446,178 B2	9/2016	Blott et al.	2006/0079599 A1	4/2006	Arthur	
	9,452,248 B2	9/2016	Blott et al.	2006/0100586 A1	5/2006	Karpowicz et al.	
	9,629,986 B2	4/2017	Patel et al.	2006/0100597 A1	5/2006	Miskie	
	9,820,888 B2	11/2017	Greener et al.	2006/0122548 A1	6/2006	Abrams	
	10,080,689 B2	9/2018	Hall et al.	2006/0161123 A1	7/2006	Kudo et al.	
	2001/0004082 A1	6/2001	Keller et al.	2006/0173514 A1	8/2006	Biel et al.	
	2001/0034499 A1	10/2001	Sessions et al.	2006/0206047 A1	9/2006	Lampe et al.	
	2001/0043913 A1	11/2001	Spaans et al.	2006/0253082 A1	11/2006	McIntosh et al.	
	2001/0043943 A1	11/2001	Coffey	2006/0273109 A1	12/2006	Keller	
	2001/0051178 A1	12/2001	Blatchford et al.	2006/0282028 A1	12/2006	Howard et al.	
	2002/0002209 A1	1/2002	Mork	2007/0003604 A1	1/2007	Jones	
	2002/0019602 A1	2/2002	Geng	2007/0004896 A1	1/2007	Ito et al.	
	2002/0038826 A1	4/2002	Hurray et al.	2007/0009580 A1	1/2007	DiCosmo et al.	
	2002/0052570 A1	5/2002	Naimer	2007/0027414 A1	2/2007	Hoffman et al.	
	2002/0087136 A1	7/2002	Widlund	2007/0032762 A1	2/2007	Vogel	
	2002/0110672 A1	8/2002	Muratore-Pallatino et al.	2007/0032763 A1	2/2007	Vogel	
	2002/0122771 A1	9/2002	Holland et al.	2007/0038172 A1	2/2007	Zamierowski	
	2002/0143286 A1	10/2002	Tumey	2007/0040454 A1	2/2007	Freudenberger et al.	
	2002/0145007 A1	10/2002	Sawhney et al.	2007/0055209 A1	3/2007	Patel et al.	
	2002/0169405 A1	11/2002	Roberts	2007/0078467 A1	4/2007	Mullen	
	2002/0183702 A1	12/2002	Henley et al.	2007/0100308 A1	5/2007	Miyairi	
	2002/0187182 A1	12/2002	Kramer et al.	2007/0141101 A1	6/2007	Nugent et al.	
	2002/0198490 A1	12/2002	Wirt et al.	2007/0147947 A1	6/2007	Stenton et al.	
	2003/0009122 A1	1/2003	Veras	2007/0164047 A1	7/2007	Reidt et al.	
	2003/0021775 A1	1/2003	Freeman	2007/0185463 A1	8/2007	Mulligan	
	2003/0040478 A1	2/2003	Drucker et al.	2007/0203062 A1	8/2007	Ellis-Behnke et al.	
	2003/0045825 A1 *	3/2003	Etheredge, III	2007/0225663 A1	9/2007	Watt et al.	A61F 13/0226 602/45
				2007/0239232 A1	10/2007	Kurtz et al.	
	2003/0050590 A1	3/2003	Kirsch	2007/0260207 A1	11/2007	Ugander et al.	
	2003/0069535 A1	4/2003	Shalaby	2007/0282236 A1	12/2007	LaGreca	
	2003/0069563 A1	4/2003	Johnson	2008/0004549 A1	1/2008	Anderson et al.	
	2003/0114818 A1	6/2003	Benecke et al.	2008/0031748 A1	2/2008	Ihle et al.	
	2003/0125646 A1	7/2003	Whitlock	2008/0058691 A1	3/2008	Sorensen	
	2003/0125649 A1	7/2003	McIntosh et al.	2008/0060550 A1	3/2008	MacDonald et al.	
	2003/0143189 A1	7/2003	Askill et al.	2008/0089173 A1	4/2008	Lu et al.	
	2003/0144619 A1	7/2003	Augustine	2008/0132821 A1	6/2008	Propp et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0167592	A1	7/2008	Greer		2010/0168633	A1	7/2010	Bougherara et al.
2008/0167593	A1 *	7/2008	Fleischmann	 A61M 1/964 604/304	2010/0191196	A1	7/2010	Heagle
2008/0200905	A1	8/2008	Heaton et al.		2010/0191198	A1	7/2010	Heagle
2008/0206155	A1	8/2008	Tamarkin et al.		2010/0196106	A1	8/2010	Allen
2008/0208147	A1	8/2008	Argenta et al.		2010/0210986	A1	8/2010	Sanders et al.
2008/0208163	A1	8/2008	Wilkie		2010/0217177	A1	8/2010	Cali et al.
2008/0223378	A1	9/2008	Henderson et al.		2010/0230467	A1	9/2010	Criscuolo et al.
2008/0254103	A1	10/2008	Harris et al.		2010/0249733	A9	9/2010	Blott et al.
2008/0287880	A1	11/2008	Keller		2010/0259406	A1	10/2010	Caso et al.
2008/0294147	A1	11/2008	Radl et al.		2010/0262090	A1	10/2010	Riesinger
2008/0300555	A1	12/2008	Olson et al.		2010/0262091	A1	10/2010	Larsson
2008/0306407	A1	12/2008	Taylor		2010/0280468	A1	11/2010	Haggstrom et al.
2008/0306456	A1	12/2008	Riesinger		2010/0305490	A1	12/2010	Coulthard et al.
2008/0312572	A1	12/2008	Riesinger		2010/0318043	A1	12/2010	Malhi et al.
2008/0314929	A1	12/2008	Keller		2010/0318052	A1	12/2010	Ha et al.
2009/0005746	A1	1/2009	Nielsen et al.		2011/0004172	A1	1/2011	Eckstein et al.
2009/0012441	A1	1/2009	Mulligan		2011/0015593	A1	1/2011	Svedman et al.
2009/0020561	A1	1/2009	Keller		2011/0021431	A1	1/2011	Jones et al.
2009/0022779	A1	1/2009	Kelly et al.		2011/0021964	A1	1/2011	Larsen et al.
2009/0030086	A1	1/2009	Eady et al.		2011/0028919	A1	2/2011	Johnnison et al.
2009/0036873	A1	2/2009	Nielsen et al.		2011/0028921	A1	2/2011	Hartwell et al.
2009/0054855	A1	2/2009	Blott et al.		2011/0033503	A1	2/2011	Sinko et al.
2009/0082740	A1	3/2009	Lockwood et al.		2011/0034888	A1	2/2011	Aali
2009/0093550	A1	4/2009	Rolfes et al.		2011/0034892	A1	2/2011	Buan
2009/0098073	A1	4/2009	MacDonald et al.		2011/0052664	A1	3/2011	Tennican et al.
2009/0125004	A1	5/2009	Shen et al.		2011/0054422	A1	3/2011	Locke et al.
2009/0131892	A1	5/2009	Karpowicz et al.		2011/0054423	A1	3/2011	Blott et al.
2009/0134186	A1	5/2009	Keller		2011/0086077	A1	4/2011	McCrea et al.
2009/0137973	A1	5/2009	Karpowicz et al.		2011/0092927	A1	4/2011	Wilkes et al.
2009/0157017	A1	6/2009	Ambrosio		2011/0092958	A1	4/2011	Jacobs
2009/0157024	A1	6/2009	Song		2011/0098621	A1	4/2011	Fabo et al.
2009/0196844	A1	8/2009	Choi et al.		2011/0105963	A1	5/2011	Hu et al.
2009/0198201	A1	8/2009	Adahan		2011/0106030	A1	5/2011	Scholz
2009/0204085	A1	8/2009	Biggie et al.		2011/0112492	A1	5/2011	Bharti et al.
2009/0216170	A1	8/2009	Robinson et al.		2011/0118683	A1	5/2011	Weston
2009/0221977	A1	9/2009	Blott et al.		2011/0125066	A1	5/2011	Robinson et al.
2009/0221990	A1	9/2009	Jaeb et al.		2011/0130712	A1	6/2011	Topaz
2009/0227935	A1	9/2009	Zanella et al.		2011/0137222	A1	6/2011	Masini
2009/0234306	A1	9/2009	Vitaris		2011/0172617	A1	7/2011	Riesinger
2009/0254053	A1	10/2009	Svensby et al.		2011/0178375	A1	7/2011	Forster
2009/0270820	A1	10/2009	Johnson et al.		2011/0218509	A1	9/2011	Dontas
2009/0275872	A1	11/2009	Addison et al.		2011/0224631	A1	9/2011	Simmons et al.
2009/0275922	A1	11/2009	Coulthard et al.		2011/0245682	A1	10/2011	Robinson et al.
2009/0293887	A1	12/2009	Wilkes et al.		2011/0245788	A1	10/2011	Marquez
2009/0299249	A1	12/2009	Wilkes et al.		2011/0247636	A1	10/2011	Pollack
2009/0299251	A1	12/2009	Buan		2011/0257572	A1	10/2011	Locke et al.
2009/0299255	A1	12/2009	Kazala, Jr. et al.		2011/0295220	A1	12/2011	Heaton et al.
2009/0299257	A1	12/2009	Long et al.		2012/0041402	A1	2/2012	Greener
2009/0299306	A1	12/2009	Buan		2012/0051945	A1	3/2012	Orndorff et al.
2009/0299308	A1	12/2009	Kazala, Jr. et al.		2012/0065664	A1	3/2012	Avitable et al.
2009/0299340	A1	12/2009	Kazala, Jr. et al.		2012/0095380	A1	4/2012	Gergely et al.
2009/0312723	A1	12/2009	Blott et al.		2012/0095426	A1	4/2012	Visscher et al.
2010/0004611	A1	1/2010	Aali		2012/0101465	A1	4/2012	McGuire, Jr.
2010/0010462	A1	1/2010	Kurata		2012/0123311	A1	5/2012	Weidemann-Hendrickson et al.
2010/0016767	A1	1/2010	Jones et al.		2012/0123358	A1	5/2012	Hall et al.
2010/0022972	A1	1/2010	Lina et al.		2012/0172778	A1	7/2012	Rastegar et al.
2010/0030170	A1	2/2010	Keller et al.		2012/0203145	A1	8/2012	Nilsson
2010/0030171	A1	2/2010	Canada et al.		2012/0203189	A1	8/2012	Barta et al.
2010/0030178	A1	2/2010	Macmeccan et al.		2012/0222687	A1	9/2012	Czajka, Jr. et al.
2010/0036305	A1	2/2010	Green		2012/0232502	A1	9/2012	Lowing
2010/0036334	A1	2/2010	Heagle et al.		2012/0238932	A1	9/2012	Atteia et al.
2010/0055158	A1	3/2010	Vitaris et al.		2012/0253302	A1	10/2012	Corley
2010/0069858	A1	3/2010	Olson		2013/0090615	A1	4/2013	Jaeb et al.
2010/0069863	A1	3/2010	Olson		2013/0090616	A1	4/2013	Neubauer
2010/0084074	A1	4/2010	McClermon et al.		2013/0102979	A1	4/2013	Coulthard et al.
2010/0106112	A1	4/2010	Vogel		2013/0138054	A1	5/2013	Fleischmann
2010/0106120	A1	4/2010	Holm		2013/0150814	A1	6/2013	Buan
2010/0106121	A1	4/2010	Holm		2013/0165878	A1	6/2013	Heagle
2010/0121286	A1	5/2010	Locke et al.		2013/0274688	A1	10/2013	Weston
2010/0122417	A1	5/2010	Vrzalik et al.		2013/0296762	A1	11/2013	Toth
2010/0125234	A1	5/2010	Smith		2013/0302545	A1	11/2013	Schnelker et al.
2010/0125258	A1	5/2010	Coulthard et al.		2013/0338614	A1	12/2013	Heaton et al.
2010/0150991	A1	6/2010	Bernstein		2014/0114268	A1	4/2014	Auguste et al.
2010/0159192	A1	6/2010	Cotton		2014/0155849	A1	6/2014	Heaton et al.
					2014/0228791	A1	8/2014	Hartwell
					2014/0236109	A1	8/2014	Greener
					2014/0309601	A1	10/2014	Hall et al.
					2015/0065965	A1	3/2015	Haggstrom et al.
					2015/0209492	A1	7/2015	Blott et al.

(56)	References Cited			EP	1807032	A1	7/2007
	U.S. PATENT DOCUMENTS			EP	1880840	A1	1/2008
				EP	1476217	B1	3/2008
				EP	1897569	A1	3/2008
2015/0320604	A1	11/2015	Adie et al.	EP	1904137	A2	4/2008
2016/0051737	A1	2/2016	Joshi et al.	EP	1922045	A2	5/2008
2016/0081859	A1	3/2016	Hartwell	EP	1923077	A1	5/2008
2016/0317357	A1	11/2016	Vitaris et al.	EP	1931413	A2	6/2008
2016/0354086	A1	12/2016	Dunn	EP	1955887	A2	8/2008
2017/0095598	A1	4/2017	Joshi et al.	EP	1985270	A2	10/2008
2017/0128642	A1	5/2017	Buan	EP	1121163	B1	11/2008
2017/0181896	A1	6/2017	Hartwell	EP	2059204	A2	5/2009
2017/0181897	A1	6/2017	Hartwell	EP	2079507	A2	7/2009
2017/0312407	A1	11/2017	Coulthard et al.	EP	2098257	A1	9/2009
2018/0147091	A1	5/2018	Greener et al.	EP	2106255	A2	10/2009
2018/0369462	A1	12/2018	Anderson et al.	EP	2109472	A1	10/2009
2019/0008690	A1	1/2019	Adie et al.	EP	2111804	A2	10/2009
				EP	2140968	A2	1/2010
				EP	2161011	A1	3/2010
				EP	2172164	A1	4/2010
				EP	2185206	A2	5/2010
CA	2653146	A1	9/2009	EP	1807031	B1	7/2010
CA	2739243	A1	4/2010	EP	2203137	A1	7/2010
CN	101385887	A	3/2009	EP	2244746	A2	11/2010
CN	101404965	A	4/2009	EP	2253353	A1	11/2010
DE	847475	C	8/1952	EP	2254537	A2	12/2010
DE	3137839	A1	3/1983	EP	2004116	B1	6/2011
DE	3032092	C2	10/1984	EP	2326295	A1	6/2011
DE	3443101	A1	5/1986	EP	2335749	A1	6/2011
DE	3935818	A1	5/1991	EP	2349155	A2	8/2011
DE	4012232	A1	10/1991	EP	1578477	B1	9/2011
DE	9017289	U1	4/1992	EP	2420214	A1	2/2012
DE	19700271	A1	9/1997	EP	2021046	B1	3/2012
DE	19832634	A1 *	1/2000	EP	2178573	B1	6/2012
DE	19844355	A1	4/2000	EP	2462908	A1	6/2012
DE	202004017052	U1	6/2005	EP	2021047	B1	10/2013
EP	0091800	A1	10/1983	EP	2711034	A1	3/2014
EP	0020662	B1	7/1984	EP	2305325	B1	4/2014
EP	0122042	A2	10/1984	EP	2345437	B1	4/2014
EP	0257916	A1	3/1988	EP	1339366	B1	6/2014
EP	0340018	A2	11/1989	EP	2544642	B1	1/2015
EP	0355186	A1	2/1990	EP	2648668	A4	1/2015
EP	0507459	A1	10/1992	EP	2931197	A1	10/2015
EP	0521434	A1	1/1993	EP	2687245	B1	2/2016
EP	0541251	A1	5/1993	EP	3085344	A1	10/2016
EP	0617152	A1 *	9/1994	EP	3139878	A1	3/2017
EP	0619105	A1	10/1994	FR	1163907	A	10/1958
EP	0752839	B1 *	5/1998	GB	114754	A	4/1918
EP	0858810	A2	8/1998	GB	236350	A	7/1925
EP	0777504	B1	10/1998	GB	641061	A	8/1950
EP	0888141	A1	1/1999	GB	821959	A	10/1959
EP	0782421	B1	7/1999	GB	1224009	A	3/1971
EP	0941726	A1	9/1999	GB	1255395	A	12/1971
EP	1007015	A1	6/2000	GB	1400124	A	7/1975
EP	1013290	A1	6/2000	GB	1549756	A	8/1979
EP	1029585	A1	8/2000	GB	2021241	A	11/1979
EP	1068451	A1	1/2001	GB	2093190	A	8/1982
EP	1105171	A2	6/2001	GB	2099306	A	12/1982
EP	1105180	A1	6/2001	GB	2195255	A	4/1988
EP	1107813	A1	6/2001	GB	2288734	A	11/1995
EP	1030657	B1	10/2001	GB	2307180	A	5/1997
EP	1169071	A1	1/2002	GB	2378392	A	2/2003
EP	1283702	A1	2/2003	GB	2415908	A	1/2006
EP	0708620	B1	5/2003	GB	2424582	A	10/2006
EP	1306123	A1	5/2003	GB	2435419	A	8/2007
EP	1088569	B1	8/2003	GB	2435422	A	8/2007
EP	1411874	A1	4/2004	GB	2468905	A	9/2010
EP	1440737	A1	7/2004	JP	S5987824	U	6/1984
EP	1018967	B1	8/2004	JP	S61288860	A	12/1986
EP	0999858	B1	9/2004	JP	H02139624	U	11/1990
EP	1452156	A1	9/2004	JP	H09505752	A	6/1997
EP	1565219	A2	8/2005	JP	2001011759	A	1/2001
EP	1440667	B1	3/2006	JP	2004521665	A *	2/2002
EP	1637088	A2	3/2006	JP	2003165843	A	6/2003
EP	1284777	B1	4/2006	JP	2003250879	A	9/2003
EP	1263366	B1	7/2006	JP	2003532504	A	11/2003
EP	0982015	B1	8/2006	JP	2004509658	A	4/2004
EP	1448261	B1	2/2007	JP	2009506878	A	2/2009
EP	1171065	B1	3/2007	JP	2009509570	A	3/2009
EP	1767177	A1	3/2007				

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	2009536852	A	10/2009	WO	WO-2005070480	A1	8/2005
JP	2010504816	A	2/2010	WO	WO-2005082435	A1	9/2005
JP	2010516387	A	5/2010	WO	WO-2005105180	A1	11/2005
JP	2012024124	A	2/2012	WO	WO-2005118011	A1	12/2005
JP	2014518651	A	8/2014	WO	WO-2005123170	A1	12/2005
SU	1251912	A1	8/1986	WO	WO-2006014534	A2	2/2006
WO	WO-8300742	A1	3/1983	WO	WO-2006030054	A1	3/2006
WO	WO-8401904	A1	5/1984	WO	WO-2006034128	A2	3/2006
WO	WO-9011795	A1	10/1990	WO	WO-2006048246	A1	5/2006
WO	WO-9100718	A1	1/1991	WO	WO-2006052745	A2	5/2006
WO	WO-9209301	A1	6/1992	WO	WO-2006052839	A2	5/2006
WO	WO-9209651	A1	6/1992	WO	WO-2006056294	A1	6/2006
WO	WO-9216245	A1	10/1992	WO	WO-2006081403	A1	8/2006
WO	WO-9220299	A2	11/1992	WO	WO-2006087021	A1	8/2006
WO	WO-9306802	A1	4/1993	WO	WO-2006116992	A1	11/2006
WO	WO-9309176	A2	5/1993	WO	WO-2006135506	A2	12/2006
WO	WO-9420133	A1	9/1994	WO	WO-2007002835	A2	1/2007
WO	WO-9423677	A2	10/1994	WO	WO-2007013064	A1	2/2007
WO	WO-9504511	A1	2/1995	WO	WO-2007019038	A2	2/2007
WO	WO-9514451	A1	6/1995	WO	WO-2007024230	A1	3/2007
WO	WO-9516416	A1	6/1995	WO	WO-2007030598	A2	3/2007
WO	WO-9529959	A1	11/1995	WO	WO-2007030601	A2	3/2007
WO	WO-9605873	A1	2/1996	WO	WO-2007059742	A1	5/2007
WO	WO-9621410	A1	7/1996	WO	WO-2007082538	A1	7/2007
WO	WO-9640174	A1	12/1996	WO	WO-2007084792	A2	7/2007
WO	WO-9703717	A1	2/1997	WO	WO-2007085396	A1	8/2007
WO	WO-9711658	A1	4/1997	WO	WO-2007092397	A2	8/2007
WO	WO-9733922	A1	9/1997	WO	WO-2007106592	A2	9/2007
WO	WO-9742986	A1	11/1997	WO	WO-2007106594	A2	9/2007
WO	WO-9803267	A1	1/1998	WO	WO-2007124198	A2	11/2007
WO	WO-9806444	A1	2/1998	WO	WO-2007133618	A2	11/2007
WO	WO-9901173	A1	1/1999	WO	WO-2008013896	A2	1/2008
WO	WO-9917698	A1	4/1999	WO	WO-2008027449	A2	3/2008
WO	WO-9930629	A1	6/1999	WO	WO-2008036225	A2	3/2008
WO	WO-9939671	A1	8/1999	WO	WO-2008039223	A1	4/2008
WO	WO-9947097	A2	9/1999	WO	WO-2008039314	A2	4/2008
WO	WO-9965536	A1	12/1999	WO	WO-2008039839	A2	4/2008
WO	WO-0007653	A1	2/2000	WO	WO-2008040020	A2	4/2008
WO	WO-0038752	A1	7/2000	WO	WO-2008041926	A1	4/2008
WO	WO-0042957	A1	7/2000	WO	WO-2008049277	A1	5/2008
WO	WO-0050143	A1	8/2000	WO	WO-2008064502	A1	6/2008
WO	WO-0059424	A1	10/2000	WO	WO-2008076407	A2	6/2008
WO	WO-0061206	A1	10/2000	WO	WO-2008082444	A2	7/2008
WO	WO-0062827	A2	10/2000	WO	WO-2008091251	A2	7/2008
WO	WO-0064396	A1	11/2000	WO	WO-2008100437	A1	8/2008
WO	WO-0119430	A1	3/2001	WO	WO-2008100440	A1	8/2008
WO	WO-0134223	A1	5/2001	WO	WO-2008104609	A1	9/2008
WO	WO-0162312	A1	8/2001	WO	WO-2008112304	A1	9/2008
WO	WO-0166017	A1	9/2001	WO	WO-2008131895	A1	11/2008
WO	WO-0185248	A1	11/2001	WO	WO-2008134544	A1	11/2008
WO	WO-0202079	A1	1/2002	WO	WO-2008134774	A2	11/2008
WO	WO-0217840	A1	3/2002	WO	WO-2009002260	A1	12/2008
WO	WO-0226180	A1	4/2002	WO	WO-2009019227	A2	2/2009
WO	WO-0238096	A2	5/2002	WO	WO-2009019229	A2	2/2009
WO	WO-02076379	A2	10/2002	WO	WO-2009021523	A1	2/2009
WO	WO-02083046	A1	10/2002	WO	WO-2009042514	A1	4/2009
WO	WO-02092783	A2	11/2002	WO	WO-2009047524	A2	4/2009
WO	WO-02094256	A1	11/2002	WO	WO-2009052193	A1	4/2009
WO	WO-02102864	A1	12/2002	WO	WO-2009060097	A2	5/2009
WO	WO-03045492	A1	6/2003	WO	WO-2009060327	A2	5/2009
WO	WO-03057307	A1	7/2003	WO	WO-2009062327	A1	5/2009
WO	WO-03092620	A2	11/2003	WO	WO-2009066104	A1	5/2009
WO	WO-2004024300	A1	3/2004	WO	WO-2009066105	A1	5/2009
WO	WO-2004037334	A1	5/2004	WO	WO-2009066106	A1	5/2009
WO	WO-2004054632	A1	7/2004	WO	WO-2009071932	A2	6/2009
WO	WO-2004073566	A1	9/2004	WO	WO-2009089390	A2	7/2009
WO	WO-2004077387	A1	9/2004	WO	WO-2009097534	A1	8/2009
WO	WO-2005009488	A2	2/2005	WO	WO-2009103031	A1	8/2009
WO	WO-2005016179	A2	2/2005	WO	WO-2009111655	A2	9/2009
WO	WO-2005017000	A1	2/2005	WO	WO-2009111657	A2	9/2009
WO	WO-2005018695	A1	3/2005	WO	WO-2009114790	A2	9/2009
WO	WO-2005025447	A2	3/2005	WO	WO-2009117635	A1	9/2009
WO	WO-2005025666	A2	3/2005	WO	WO-2009122989	A1	10/2009
WO	WO-2005046761	A1	5/2005	WO	WO-2009124100	A1	10/2009
WO	WO-2005051461	A1	6/2005	WO	WO-2009124125	A2	10/2009
				WO	WO-2009126102	A1	10/2009
				WO	WO-2009126103	A1	10/2009
				WO	WO-2009126833	A2	10/2009
				WO	WO-2009145703	A1	12/2009

(56)

References Cited**FOREIGN PATENT DOCUMENTS**

WO	WO-2009146441	A1	12/2009
WO	WO-2009147402	A2	12/2009
WO	WO-2009151380	A1	12/2009
WO	WO-2009156709	A1	12/2009
WO	WO-2009158124	A1	12/2009
WO	WO-2009158127	A1	12/2009
WO	WO-2009158128	A2	12/2009
WO	WO-2009158130	A1	12/2009
WO	WO-2010008167	A2	1/2010
WO	WO-2010026251	A1	3/2010
WO	WO-2010033574	A1	3/2010
WO	WO-2010033613	A1	3/2010
WO	WO-2010035017	A1	4/2010
WO	WO-2010051418	A2	5/2010
WO	WO-2010059849	A2	5/2010
WO	WO-2010072309	A1	7/2010
WO	WO-2010072395	A1	7/2010
WO	WO-2010082872	A1	7/2010
WO	WO-2010089448	A1	8/2010
WO	WO-2010120776	A1	10/2010
WO	WO-2010139926	A1	12/2010
WO	WO-2010141271	A1	12/2010
WO	WO-2010142959	A2	12/2010
WO	WO-2010147533	A1	12/2010
WO	WO-2010147592	A1	12/2010
WO	WO-2011019476	A1	2/2011
WO	WO-2011023275	A1	3/2011
WO	WO-2011023650	A1	3/2011
WO	WO-2011063818	A1	6/2011
WO	WO-2011115908	A1	9/2011
WO	WO-2011128651	A1	10/2011
WO	WO-2011135284	A1	11/2011
WO	WO-2011135285	A1	11/2011
WO	WO-2011135286	A1	11/2011
WO	WO-2011135287	A1	11/2011
WO	WO-2011144888	A1	11/2011
WO	WO-2012009370	A2	1/2012
WO	WO-2012022484	A1	2/2012
WO	WO-2012028842	A1	3/2012
WO	WO-2012041296	A2	4/2012
WO	WO-2012074512	A1	6/2012
WO	WO-2012131237	A1	10/2012
WO	WO-2012140378	A1	10/2012
WO	WO-2012143665	A1	10/2012
WO	WO-2012146656	A1	11/2012
WO	WO-2012150235	A1	11/2012
WO	WO-2015172108	A1	11/2015

OTHER PUBLICATIONS

Brief communication—Letter from the Proprietor of the Patent of Mar. 17, 2023 for European Patent No. 3628289, mailed on Mar. 23, 2023, 5 pages.

Board of Appeal—Letter of the Patent Proprietor dated May 22, 2023 for European Patent No. 2821035, mailed on May 26, 2023, 10 pages.

Achterberg V., et al., “Hydroactive Dressings and Serum Proteins: An In Vitro Study,” *Journal of Wound Care*, vol. 5 (2), Feb. 1996, pp. 79-82.

Advantec MFS, Inc., “Membrane Filters” (catalog), retrieved from <http://www.advantecmfs.com/catalog/filt/membrane.pdf>, on Jan. 29, 2016, Copyright 2001-2011, 17 pages.

Annex to the Communication, the Opposition of European Patent No. 2563306, mailed on Oct. 6, 2017, 15 pages.

Argenta L.C., et al., “Vacuum-Assisted Closure: A New Method for Wound Control and Treatment: Clinical Experience,” *Annals of Plastic Surgery*, vol. 38 (6), Jun. 1997, pp. 563-577.

Arnljots B., et al., “Irrigation Treatment in Split-Thickness Skin Grafting of Intractable Leg Ulcers,” *Scandinavian Journal of Plastic and Reconstructive Surgery*, vol. 19, 1985, pp. 211-213.

Aubrey D.A., et al., “Treatment of the Perineal Wound after Proctectomy by Intermittent Irrigation,” *Arch. Surg.*, vol. 119, Oct. 1984, pp. 1141-1144.

Bagautdinov N.A., “Variant of External Vacuum Aspiration in the Treatment of Purulent Diseases of Soft Tissues,” in *Current Problems in Modern Clinical Surgery*, Interdepartmental Collection, 1986, pp. 94-96.

Bevan D., et al., “Diverse and potent activities of HGF/SF in skin wound repair,” *Journal of Pathology*, vol. 203, 2004, pp. 831-838. Brief Communication of Letter from the proprietor of the patent and copies of Auxiliary requests 1-2 for European Patent No. 2821035 mailed on Feb. 12, 2021, 27 pages.

Chariker M.E., et al., “Effective Management of Incisional and Cutaneous Fistulae with Closed Suction Wound Drainage,” *Contemporary Surgery*, vol. 34, Jun. 1989, pp. 59-63.

Chintamani et al., “Half Versus Full Vacuum Suction Drainage After Modified Radical Mastectomy for Breast Cancer—a Prospective Randomized Clinical Trial,” *BMC Cancer*, Research Article, vol. 5(11), Jan. 27, 2005, 5 pages.

Communication of Notice of Opposition dated Dec. 17, 2015, and Opposition of European patent EP2563308 B1, dated Dec. 11, 2015, on behalf of KCI Licensing, Inc., and cited publications D1-D6, 250 pages.

Communication of the Board of Appeal to Patent Proprietor for European Patent No. 2563308, mailed on Jul. 2, 2021, 6 pages.

Data Sheet for the decision for Jul. 17, 2020 cited during the appeal procedure for European Patent No. 2563308, mailed on Jan. 22, 2021, 37 pages.

Davydov Y.A., et al., “Concepts for Clinical Biological Management of the Wound Process in the Treatment of Purulent Wounds Using Vacuum Therapy,” *Vestnik Khirurgii*, Feb. 1991, pp. 15-17.

Davydov Y.A., et al., “The Bacteriological and Cytological Assessment of Vacuum Therapy of Purulent Wounds,” *Vestnik Khirurgii*, Oct. 1988, pp. 11-14.

Davydov Y.A., et al., “Vacuum Therapy in the Treatment of Purulent Lactation Mastitis,” *The Kremlin Papers: Perspectives in Wound Care*, *Vestnik Khirurgii*, BlueSky Publishing, 2004, pp. 5-7.

De Lange M.Y., et al., “Vacuum-Assisted Closure: Indications and Clinical Experience,” *Eur J Plast Surg* (2000), vol. 23, Feb. 9, 2000, pp. 178-182.

Declaration of Chris Locke in support of the opposition to European Patent No. 2563308 dated Sep. 7, 2016, 1 page.

Declaration of Chris Locke Submitted in the Opposition against European Patent No. 2231221, mailed on Sep. 7, 2016, 1 page.

Declaration of Chris Locke submitted in the Opposition against European Patent No. EP2563308, dated Sep. 7, 2016, 6 pages.

Dilmaghani A., et al., “A Method for Closed Irrigation and Suction Therapy in Deep Wound Infections,” *Journal of Bone and Joint Surgery*, Mar. 1969, vol. 51-A(2), pp. 323-342.

Grounds for the Decision, the Opposition of European Patent No. 2563306, mailed on Sep. 7, 2018, 101 pages.

Hartz R.S., et al., “Healing of the Perineal Wound,” *The Archives of Surgery*, Apr. 1980, vol. 115, pp. 471-474.

Health Technology Literature Review, “Vacuum Assisted Closure Therapy for Wound Care,” *The Medical Advisory Secretariat*, Dec. 2004, pp. 1-57.

Hersle K., et al., “Uses of Dextranomer Absorbent Pads After Cryosurgery of Cutaneous Malignancies,” *The Journal of Dermatologic Surgery and Oncology*, vol. 8, Jan. 1982, pp. 35-37.

Information about the Result of Oral Proceedings for the Opposition of European Patent No. EP2563306, dated Jun. 21, 2018, 1 page.

Information about the Result of Oral Proceedings for the Opposition of European Patent No. EP2563308, dated Jul. 21, 2017, 3 pages.

Interlocutory Decision and Annex to the Communication for the Opposition of European Patent No. EP2563308, dated Aug. 14, 2017, 76 pages.

International Preliminary Report on Patentability for Application No. PCT/GB2011/000622, mailed on Nov. 8, 2012, 7 pages.

International Preliminary Report on Patentability for Application No. PCT/GB2011/000625, mailed on Nov. 8, 2012, 8 pages.

International Preliminary Report on Patentability for Application No. PCT/GB2011/000626, mailed on Nov. 8, 2012, 8 pages.

International Preliminary Report on Patentability for Application No. PCT/GB2011/000628, mailed on Nov. 8, 2012, 8 pages.

International Preliminary Report on Patentability for Application No. PCT/GB2011/000629, mailed on Oct. 31, 2013, 8 pages.

(56)

References Cited**OTHER PUBLICATIONS**

International Preliminary Report on Patentability for Application No. PCT/GB2011/00621, mailed on Nov. 29, 2012, 7 pages.

International Search Report for Application No. PCT/GB2008/051088, mailed on Mar. 4, 2009, 2 pages.

International Search Report for Application No. PCT/GB2008/051089, mailed on Mar. 4, 2009, 3 pages.

International Search Report for Application No. PCT/GB2008/051090, mailed on Mar. 4, 2009, 2 pages.

International Search Report for Application No. PCT/GB2011/000621, mailed on Jul. 26, 2011, 4 pages.

International Search Report for Application No. PCT/GB2011/000622, mailed on Jul. 28, 2011, 4 pages.

International Search Report for Application No. PCT/GB2011/000625, mailed on Aug. 10, 2011, 5 pages.

International Search Report for Application No. PCT/GB2011/000626, mailed on Aug. 4, 2011, 5 pages.

International Search Report for Application No. PCT/GB2011/000628, mailed on Sep. 6, 2011, 7 pages.

International Search Report for Application No. PCT/GB2011/000629, mailed on Dec. 23, 2011, 6 pages.

Invalidity Suit by *KCI Medizinprodukte GmbH* versus *Kalypto Medical, Inc.*, concerning declaration of invalidity of the German part of the European Patent No. 2021046 (German application No. 602007021330.4) dated Mar. 11, 2015 in 66 pages. EP2021046 is related to the present application by virtue of a common priority claim to U.S. Appl. No. 11/432,855, now U.S. Pat. No. 7,615,036, and U.S. Appl. No. 11/610,458, now U.S. Pat. No. 7,779,625.

Kalypto Medical, "NPD 1000 Negative Pressure Wound Care System," Clinician & Patient Instructions for Use, Feb. 2010, 36 pages.

Kalypto Medical, NPD 1000 Product Brochure (publication date unknown, believed to be Nov. 2010), 4 pages.

KCI Licensing Inc., "Prevena™ Incision Management System—Clinician Guide—Instructions for Use," 390061 Rev D, Jan. 2010, 10 pages.

KCI, "Prevena—Incision Management System Patient Guide," Jan. 2010, 2 pages.

Kendall ULTEC Hydrocolloid Dressing (4x4"), Product Ordering Page, web page downloaded on Jul. 13, 2014, 1 page.

Khirurgii V., "A Collection of Published Studies Complementing the Research and Innovation of Wound Care," The Kremlin Papers, Perspectives in Wound Care, Russian Medical Journal, Blue Sky Publishing, 2004, pp. 2-17.

Kostiuchenok B.M., et al., "The Vacuum Effect in the Surgical Treatment of Purulent Wounds," Russian Journal: Vestnik Khirurgii, Sep. 1986, pp. 18-21.

Letter of the opponent relating to oral proceedings during the appeal procedure for European Patent No. 2563308, mailed on Feb. 26, 2021, 3 pages. <div class="ginger-extension-definitionpopup" style="left: 163.463px; top: 17.6px; z-index: 2147483646; display: none;"><div class="ginger-dp"> <div class="ginger-dp-content"> <div class="ginger-dp-title">with/></div> <div class="ginger-dp-description" id="dp-description">accompanying</div> <div class="ginger-dp-more">More(Definitions, Synonyms, Translation)</div> .</div></div></div>.

Letter of the opponent relating to oral proceedings during the appeal procedure for European Patent No. 2563308, mailed on Sep. 6, 2021, 4 pages.

Letter of the Patent Proprietor dated Jan. 22, 2021 relating to the appeal procedure for European Patent No. 2563308, 9 pages.

Letter regarding the Opposition Procedure from the Opponent for the Opposition of European Patent No. 2563308, dated Nov. 10, 2016, 10 pages.

Letter relating to the Appeal Procedure for the Opposition of the European Patent No. 2563306, mailed on Jan. 17, 2019, 3 pages.

Letter relating to the Appeal Procedure for the Opposition of the European Patent No. 2563308, mailed on Apr. 17, 2018, in 6 pages.

Letter relating to the Appeal Procedure for the Opposition of the European Patent No. 2563308, mailed on Jun. 22, 2018, in 4 pages.

MacMillan Dictionary, "Comprise," Retrieved from <https://www.macmillandictionary.com/us/dictionary/american/comprise> on Jan. 29, 2020, 4 pages.

Merriam-Webster, "Comprise," Retrieved from <https://www.merriam-webster.com/dictionary/comprise> on Jan. 29, 2020, 8 pages.

Merriam-Webster, Definition of "Port", retrieved from URL: <https://www.merriam-webster.com/dictionary/port>, on Oct. 26, 2020, 6 pages.

Minutes of the Oral Proceedings—Boards of Appeal, re the Opposition of European Patent No. 2563308, mailed on Nov. 4, 2021, 3 pages.

Mitchell R.N., et al., "Role of Stem Cells in Tissue Homeostasis," Pocket Companion to Robbins and Cotran Pathologic Basis of Disease, 7th Edition, 2006, p. 55 (3 pages).

Morykwas M.J., et al., "Vacuum-Assisted Closure: A New Method for Wound Control and Treatment: Animal Studies and Basic Foundation," Annals Plastic Surgery, vol. 38 (6), Jun. 1997, pp. 553-562.

Notice of Appeal by Appellant for the Opposition of the European Patent No. 2563308, mailed on Oct. 9, 2017, 4 pages.

Notice of Appeal by Proprietor for the Opposition of the European Patent No. 2563308, mailed on Oct. 10, 2017, 5 pages.

Notice of Opposition—Opponent's Statement of Facts and Arguments for the European Patent No. 2821035, mailed on Sep. 7, 2020, 12 pages.

Notice of Opposition—Statement of Facts and Evidence for the European Patent No. 2563306, mailed on Dec. 30, 2016, 19 pages.

Notice of Opposition—Statement of Facts and Evidence for the European Patent No. 2699276, mailed on May 3, 2017, 14 pages.

Notice of Oppositions from Opponent for the European Patent No. 2821035, mailed on Sep. 8, 2020, 73 pages.

Nursing75, "Wound Suction: Better Drainage with Fewer Problems," vol. 5(10), Oct. 1975, pp. 52-55.

Office Action mailed Aug. 22, 2011 for Canadian Application No. 2739605, 2 pages.

Opponent's letter relating to the Appeal Procedure for the Opposition of the European Patent No. 2563306, mailed on Aug. 20, 2020, 37 pages.

Opponent's Written Submission in Preparation for the Oral Proceedings for the Opposition of European Patent No. 2563308, mailed on May 19, 2017, 10 pages.

Opponent's Written Submission in Preparation for the Oral Proceedings for the Opposition of European Patent No. EP2563306, dated Apr. 20, 2018, 14 pages.

Opponent's Written Submission in Preparation for the Oral Proceedings for the Opposition of European Patent No. EP2563306, dated Jun. 11, 2018, 7 pages.

Opponent's Written Submission in Preparation for the Oral Proceedings for the Opposition of European Patent No. EP2699276, dated Jul. 11, 2018, 3 pages.

Preparation for Oral Proceedings and Annex to the Communication for the Opposition of European Patent No. 2563308, mailed on Dec. 19, 2016, 18 pages.

Preparation for Oral Proceedings and Annex to the Communication for the Opposition of European Patent No. 2699276, mailed on Jan. 12, 2018, 19 pages.

Priority Document filed Apr. 27, 2010 for Great Britain Application No. 1006986.2, by Smith & Nephew PLC, 40 pages.

Proprietor's letter relating to the Appeal Procedure for the Opposition of the European Patent No. 2563306, mailed on Aug. 6, 2020, 32 pages.

Proprietor's Written Submission in Preparation for the Oral Proceedings, the Opposition of European Patent No. 2563306, mailed on Apr. 19, 2018, 39 pages.

Proprietor's Written Submission in Preparation for the Oral Proceedings, the Opposition of European Patent No. 2563308, mailed on Jul. 10, 2017, 12 pages.

Proprietor's Written Submission in Preparation for the Oral Proceedings, the Opposition of European Patent No. 2563308, mailed on May 17, 2017, 37 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Proprietor's Written Submission in Preparation for the Oral Proceedings, the Opposition of European Patent No. 2699276, mailed on Jul. 10, 2018, 39 pages.

Protz K., "Modern Wound Dressings Support the Healing Process," Wound care: Indications and Application, *Geriatric Journal*, Apr. 2005, pp. 3333-3339 (17 pages with English translation).

Reply of the Patent Proprietor to the Notice of Opposition for the European Patent No. 2563306, mailed on Jun. 5, 2017, 44 pages.

Reply of the Patent Proprietor to the Notice of Opposition for the European Patent No. 2563308, mailed on Aug. 15, 2016, 35 pages.

Reply of the Patent Proprietor to the Notice of Opposition for the European Patent No. 2699276, mailed on Oct. 19, 2017, 5 pages.

Reply to Appeal—Letter of the patent proprietor for the European Patent No. 2563308, mailed on Aug. 17, 2021, 13 pages.

Reply to Appeal, in Opposition by KCI Licensing Inc. to Smith & Nephew PLC, the European Patent No. 2563308, mailed on May 24, 2018, 9 pages.

Reply to Grounds of Appeal, in Opposition by KCI Licensing Inc. to Smith & Nephew PLC for the European Patent No. 2563308, dated Apr. 27, 2018, 4 pages.

Reply to the Appeal mailed on May 21, 2019 for the Opposition of European Patent No. 2563306, 18 pages.

Smith & Nephew, "PICO Single Use Negative Pressure Wound Therapy System," Spiral Booklet, Mar. 2011, 7 pages.

Solovev V. A., et al., "The Method of Treatment of Immature External Fistulas in the Upper Gastrointestinal Tract—Guidelines," USSR Ministry of Health, S. M. Kirov Gorky State Medical Institute, 1987, 19 pages.

Solovev V.A., "Treatment and Prevention of Suture Failures after Gastric Resection," Dissertation Abstract, Gorky, 1988, 51 pages. Specification and drawings filed in application No. EP14187266.3, file on Jan. 8, 2010, 46 pages.

Statement of Grounds of Appeal by Appellant-Opponent for the Opposition of European Patent No. 2563308, dated Dec. 12, 2017, 6 pages.

Statement of Grounds of Appeal by Appellant-Proprietor for the Opposition of European Patent No. 2563308, mailed on Dec. 5, 2017, 26 pages.

Statement of Grounds of Appeal for the Opposition of European Patent No. 2563306, mailed on Jan. 16, 2019, 90 pages.

Stewart J., "World Wide Wounds—Next Generation of Products for Wound Management," Nov. 2002, <http://www.worldwidewounds.com/2003/aprii/Stewart/Next-Generation-Products.html>, 13 pages.

Summons to attend oral proceedings pursuant to Rule 115(1) EPC for Patent No. 2821035, mailed on Jul. 5, 2021, 18 pages.

Svedman P., "A Dressing Allowing Continuous Treatment of a Biosurface," *IRCS Medical Science: Biomedical Technology; Clinical Medicine; Surgery and Transplantation*, vol. 7, 1979, p. 221.

Svedman P., et al., "A Dressing System Providing Fluid Supply and Suction Drainage Used for Continuous or Intermittent Irrigation," *Annals of Plastic Surgery*, vol. 17 (2), Aug. 1986, 9 pages.

Svedman P., "Irrigation Treatment of Leg Ulcers," *The Lancet*, Sep. 3, 1983, pp. 532-534.

Swift S., et al., "Quorum Sensing in *Aeromonas Hydrophila* and *Aeromonas Salmonicida*: Identification of LuxRI Homologs AhyRI and AsaRI and Their Cognate N-Acylhomoserine Lactone Signal Molecules," *Journal of Bacteriology*, Sep. 1997, vol. 179, No. 17, pp. 5271-5281.

Technology Watch, May 1989, 1 page.

Teder H., et al., "Continuous Wound Irrigation in the Pig," *Journal of Investigative Surgery*, 1990, vol. 3, pp. 399-407.

Termination of the Opposition Proceedings with Maintenance of European Patent No. 2699276, dated Nov. 29, 2018, 1 page.

The Free Dictionary, "Welding," *The American Heritage®*, Fourth Edition, 2000, 2 pages.

The Wayback Machine, "Comfort advantages with AirX™," retrieved from <http://web.archive.org/web/20090121000205/http://www.airx.eu:80/content/view/2/3/lang,en/>, on Jan. 21, 2009, 1 page.

The Wayback Machine, "Moisture-Transporting Material," retrieved from <http://web.archive.org/web/20090121001036/http://www.airx.eu/content/view/1/14/lang,en/>, on Jan. 21, 2009, 1 page.

Tribble D E., "An Improved Sump Drain-Irrigation Device of Simple Construction," *Archives of Surgery*, vol. 105, Sep. 1972, pp. 511-513.

Usupov Y. N., et al., "Active Wound Drainage," *Russian Journal: Vestnik Khirurgii*, Apr. 1987 (p. 42-45), Perspectives in Wound Care, BlueSky Publishing, pp. 8-10.

Venturi M L., et al., "Mechanisms and Clinical Applications of the Vacuum-Assisted Closure (VAC) Device," *Am J Clin Dermatol*, 2005, vol. 6, No. 3, pp. 185-194.

Viljanto J., et al., "Local Hyperalimentation of Open Wounds," *Br. J. Surg.*, vol. 63, 1976, pp. 427-430.

Webb L X., "New Techniques in Wound Management: Vacuum-Assisted Wound Closure," *Journal of the American Academy of Orthopaedic Surgeons*, vol. 10, No. 5, Sep./Oct. 2002, pp. 303-311.

Westaby S., et al., "A Wound Irrigation Device," *The Lancet*, Sep. 2, 1978, pp. 503-504.

Withdrawal of an Opposition for the European Patent No. 2699276, dated Jul. 31, 2018, in 3 pages.

Wooding-Scott M., et al., "No Wound is Too Big for Resourceful Nurses," *RN*, Dec. 1988, pp. 22-25.

Datasheet for the Decision for Oct. 14, 2021 cited during the Appeal Procedure for European Patent No. 2563308, mailed on Dec. 17, 2021, 24 pages.

Boards of Appeal—Letter of the Opponent dated Jan. 20, 2023 for European Patent No. 2821035 mailed on Jan. 25, 2023, 52 pages.

Jack L., et al., "Training Curriculum for Alternative Clothes Cleaning, vol. I: Curriculum and vol. II: Instructor's Manual and Presentation Materials," Massachusetts Toxics Use Reduction Institute, 1997, 306 pages.

Reply of the Patent Proprietor to the Notice of Opposition for European Patent No. 3628289, mailed on Dec. 28, 2022, 34 pages.

Reply to Appeal for European Patent No. 2821035 mailed on Feb. 1, 2023, 7 pages.

Statement of Grounds of Appeal by Appellant, re the Opposition of European Patent No. EP2563308, mailed on Dec. 5, 2017, 26 pages.

Statement of Grounds of Appeal for the European Patent No. 2821035, mailed on Sep. 28, 2022, 73 pages.

Termination of the Opposition Proceedings with Revocation of the Patent for European Patent No. 2563306, dated Sep. 13, 2022, 1 page.

Brief Communication—Oral Proceedings and Letter from the opponent for European Patent No. 2821035, mailed on Mar. 7, 2022, 3 pages.

Brief Communication—Oral proceedings and Letter from the Opponent, re the Opposition of European Patent No. 2821035, mailed on Feb. 9, 2022, 4 pages.

Brief Communication—Oral proceedings and Letter from the Opponent, re the Opposition of European Patent No. 2821035, mailed on Jan. 28, 2022, 31 pages.

Brief Communication—Oral proceedings, Letter from the proprietor of the patent and Main and Auxiliary requests, re the Opposition of European Patent No. 2821035, mailed on Feb. 8, 2022, 30 pages.

Claims as Originally filed in Divisional Application 19201361.3, filed in the Opposition of European Patent No. 3628289 on Jul. 18, 2022, 2 pages.

Communication of a Notice of Opposition for the European patent No. 3628289, dated Aug. 12, 2022, 56 pages.

Communication of a Notice of Opposition including Statement of Facts and Evidence for European Patent No. 3628289, dated Jul. 22, 2022, 21 pages.

Communication of a Notice of Opposition including Statement of Facts and Evidence for European Patent No. 3628289, dated Jul. 22, 2022, 41 pages.

Decision revoking the European Patent (Art. 101(3)(b) EPC) for European Patent No. 2821035, mailed on May 19, 2022, 16 pages.

Information about the result of oral proceedings for European Patent No. 2821035, mailed on Apr. 6, 2022, 2 pages.

KCI Licensing, Inc., "V.A.C. Drape® Instructions For Use," Oct. 2003, 2 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Merriam-Webster, Definition of "Port", retrieved from URL: <https://www.merriam-webster.com/dictionary/port>, on Jun. 20, 2022, 3 pages.

Moore A.T., et al., "The Swelling of Cotton in Water: A Microscopical Study," Textile Research Journal, Sep. 1950, pp. 620-630.

Provision of the minutes in accordance with Rule 124(4) EPC for European Patent No. 2821035, mailed on May 17, 2022, 9 pages.

Silverlon, "Negative Pressure Contact Dressings," retrieved from Internet URL: <https://www.silverlon.com/products/negative-pressure-contact-dressings>, accessed on Jan. 24, 2022, 10 pages.

Smith & Nephew, "Allevyn: Technical Information Sheet," Dec. 2013, 2 pages.

"System," Cambridge English Dictionary, Retrieved from the Internet: URL: <https://dictionary.cambridge.org/dictionary/english/system> on Jul. 28, 2022, 1 page.

Termination of Opposition Proceedings for European Patent No. 2563308, dated Jan. 25, 2022, 1 page.

Wikipedia, "Breathability," Retrieved from the Internet: URL: <https://en.wikipedia.org/wiki/Breathability> on Aug. 2, 2022, 3 pages.

Withdrawal of an appeal for the European Patent No. 2563306, mailed on Apr. 29, 2022, 3 pages.

BASF., "Thermoplastic Polyurethane Elastomers," Elastollan—Material Properties, 2017, 52 pages, Retrieved from the Internet: URL: https://www.basf.com/kr/documents/ko/product/Elastollan_Material%20Properties.pdf.

BASF., "Thermoplastic Polyurethane Elastomers (TPU)," Elastollan—Product Range, 2016, 40 pages, Retrieved from the Internet: URL: https://www.basf.com/kr/documents/ko/product/Thermoplastic%20Polyurethane_Elastollan_Product%20Range.pdf.

3M United States, "3M™ Tegaderm™ Transparent Film Dressing Frame Style," retrieved Jul. 21, 2022 from https://www.3m.com/3M/en_US/p/d/b00035590/, 4 pages.

Allevyn Adhesive., "SMI Dressings Datasheet," Smith and Nephew Healthcare Ltd, last modified May 11, 2007, 3 pages.

Annex to the Communication filed in the opposition against European Patent No. 4023197, mailed on Jul. 26, 2024, 27 pages.

Brief Communication—Letter from the Opponent O1 of Jun. 28, 2024 filed in the Opposition against European Patent No. 4023197, dated Jul. 4, 2024, 25 pages.

Brief Communication—Letter from the Proprietor of the Patent of Apr. 29, 2024 for European Patent No. 4023197, mailed May 3, 2024, 56 pages.

Communication of a Notice of Opposition for the European patent No. 4023197, dated Dec. 20, 2023, 50 pages.

Communication of a Notice of Opposition for the European patent No. 4023197, dated Jan. 8, 2024, 44 pages.

Communication of a Notice of Opposition for the European patent No. 4023197, dated Nov. 20, 2023, 49 pages.

Communication of Further Notices of Opposition Pursuant to Rule 79(2) for the European patent No. 4023197, dated Jan. 12, 2024, 98 pages.

Communication of the Board of Appeal pursuant to Article 15(1) of the Rules of Procedure filed in the Opposition against European Patent No. 2821035, mailed on Jul. 23, 2024, 8 pages.

Definition of "Strand," Collins English Dictionary, accessed Apr. 11, 2024, 15 pages, URL: <https://www.collinsdictionary.com/dictionary/english/strand>.

Definition of "System," Cambridge Dictionary, accessed Apr. 11, 2024, 8 pages, URL: <https://dictionary.cambridge.org/dictionary/english/system>.

"Search Results from UK Intellectual Property Office Trade Mark Register," filed in the Opposition for the European Patent No. 4023197 on Dec. 15, 2023, 3 pages.

"Handbook of Medical Textiles," Woodhead Publishing Limited, 2011, 41 pages.

Hutten I.M., "Introduction to Nonwoven Filter Media", in Handbook of Nonwoven Filter Media, 2007, 1 page.

Riedel E., et al., "Verbandstoff-Fibel," 5. Auflage, Stuttgart, 1995, Seiten 23-35 and 82-95.

Summons to Attend Oral Proceedings Pursuant to Rule 115(1) EPC for the Opposition of European Patent No. 3628289, mailed on Feb. 9, 2024, 12 pages.

"Technical datasheet for the Chem-Posite™ 11C—450 material," Emerging Technologies, filed in the Opposition for the European Patent No. 4023197 on Apr. 29, 2024 (publication date unknown), 1 page.

"Strand," Wiktionary, last edited Mar. 25, 2024 (accessed Apr. 11, 2024), 10 pages, URL: <https://en.wiktionary.org/wiki/strand>.

Transmittal of Decision Summons for the Opposition of European Patent No. 3628289, mailed on Jan. 19, 2024, 12 pages.

Brief Communication—the EPO-form 2310 filed in the Opposition against European Patent No. 4023197, mailed on Aug. 19, 2024, 29 pages.

Brief Communication—Letter from the Opponent O1 of Oct. 9, 2024 filed in the Opposition against European Patent No. 3628289, dated Oct. 16, 2024, 3 pages.

Brief Communication—Letter from the Opponent O1 of Sep. 6, 2024 filed in the Opposition against European Patent No. 3628289, dated Sep. 16, 2024, 4 pages.

Brief communication—Letter from the proprietor of the patent of Sep. 11, 2024 for European Patent No. 3628289, mailed on Sep. 18, 2024, 54 pages.

Brief communication—Opposition Proceedings for European Patent No. 3628289, mailed on Dec. 2, 2024, 35 pages.

Brief Communication of Opposition—Letter from the proprietor from the patent to the opponent Simmons & Simmons for the Opposition of European Patent No. 3628289, mailed on Sep. 13, 2024, 33 pages.

Information concerning the result of oral proceedings for the Opposition of European Patent No. 3628289, dated Nov. 11, 2024, 2 pages.

Notification of Cancellation of Oral Proceedings for Oct. 10, 2024, filed in the Opposition against European Patent No. 2821035, mailed on Aug. 16, 2024, 2 pages.

Withdrawal of Appeal—Letter of the Patent Proprietor dated Aug. 9, 2024 filed in the Opposition against European Patent No. 2821035, mailed on Aug. 14, 2024, 4 pages.

Written Submission in Preparation for the Oral Proceedings, for the Opposition of European Patent No. 3628289, dated Oct. 21, 2024, 9 pages.

Brief Communication—Letter from the Opponent O1 of Mar. 14, 2025 filed in the Opposition against European Patent No. 4023197, dated Mar. 19, 2025, 36 pages.

Brief Communication—Letter from the Opponent O2 of Mar. 19, 2025 filed in the Opposition against European Patent No. 4023197, dated Mar. 24, 2025, 22 pages.

Brief Communication—Letter from the Opponent O3 of Apr. 25, 2025 filed in the Opposition against European Patent No. 4023197, dated May 2, 2025, 08 pages.

Brief Communication—Letter from the Opponent O3 of Mar. 19, 2025 filed in the Opposition against European Patent No. 4023197, dated Mar. 24, 2025, 24 pages.

Brief Communication—Letter from the proprietor of the patent of Mar. 19, 2025 filed in the Opposition against European Patent No. 4023197, mailed on Mar. 24, 2025, 45 pages.

Brief Communication—Letter from the Proprietor of the Patent of May 13, 2025 for European Patent No. 4023197, mailed May 14, 2025, 06 pages.

Information about the Result of Oral Proceedings, for the European Patent No. 4023197, dated May 19, 2025, 2 pages.

Statement of Grounds of Appeal for European Patent No. 3628289, mailed on Apr. 2, 2025, 115 pages.

"The Allevyn Wound Dressings Range" 1 page, Product brochure obtained from: <https://www.smith-nephew.com/en-pb/health-care-professionals/products/advanced-wound-management/allevynborder-gilobal-new#relatedtechnologies>.

The Wyback Machine, "Rayon Fiber," Extract from Conservation and Art Material Encyclopaedia Online, on Mar. 13, 2006, 1 page.

Affidavit of Dr. Viktoria Skeppstedt filed in the Opposition against European Patent No. 4223265, dated May 19, 2025, 2 pages.

(56)

References Cited

OTHER PUBLICATIONS

Anonymous, "3M™ Tegaderm™ Transparent Film Dressings—Product Profile," Retrieved from <http://multimedia.3m.com/mws/media/4479830/tegaderm-transparent-film-dressing-brochure.pdf>, Jan. 1, 2012, 8 pages.

Communication of a Notice of Opposition for European Patent No. 4223265, mailed on May 26, 2025, 67 pages.

Decision revoking the European Patent (Art. 101 (3)(b) EPC) for European Patent No. 4023197, mailed on Jun. 5, 2025, 51 pages.

Notice of Opposition for European Patent No. 4223265, mailed on May 28, 2025, 62 pages.

Phan T T., et al., "Evaluation of cell culture on the polyurethane-based membrane (Tegaderm): implication for tissue engineering of skin," Cell Tissue Bank. 2005; 6(2), 1 page.

Russell S.J., et al., "18—Anisotropic Fluid Transmission in Non-woven Wound Dressings," Proceedings of the 2nd International Conference, Aug. 24, 25, 1999, Woodhead Publishing Series in Textiles, 2001, 1 page.

The Wayback Machine, "Cellulose fiber," Extract from Wikipedia, the free encyclopedia, Retrieved from the Internet: URL: http://en.wikipedia.org/wiki/Cellulose_fiber, Online, on 2009, 1 page.

Wikipedia, Definition of "Rayon" being Regenerated Cellulose, Retrieved from the Internet: <https://en.wikipedia.org/wiki/Rayon>, on Feb. 7, 2025, 1 page.

Reply to Appeal for the Opposition of European Patent No. 3628289, mailed on Aug. 5, 2025, 68 pages.

Reply to Appeal for the Opposition of European Patent No. 3628289, mailed on Aug. 7, 2025, 16 pages.

Reply to Appeal for the Opposition of European Patent No. 3628289, mailed on Aug. 8, 2025, 88 pages.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14A




FIG. 14B




FIG. 14C




FIG. 14D




FIG. 14E




FIG. 14F




FIG. 14G




FIG. 14H




FIG. 14I




FIG. 14J




FIG. 14K




FIG. 14L




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29A






FIG. 29B



1

WOUND DRESSING AND METHOD OF USE**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 17/372,252, filed on Jul. 9, 2021, which is a continuation of U.S. patent application Ser. No. 16/118,339, filed on Aug. 30, 2018 and issued as U.S. Pat. No. 11,058,587, which is a continuation of U.S. patent application Ser. No. 15/633,670, filed on Jun. 26, 2017 and issued as U.S. Pat. No. 10,159,604, which is a continuation of U.S. patent application Ser. No. 14/715,399, filed on May 18, 2015 and issued as U.S. Pat. No. 9,808,561, which is a continuation of U.S. patent application Ser. No. 13/092,042, filed on Apr. 21, 2011 and issued as U.S. Pat. No. 9,061,095, which claims priority to Great Britain Patent Application No. 1006986.2, filed Apr. 27, 2010; Great Britain Patent Application No. 1006983.9, filed Apr. 27, 2010; Great Britain Patent Application No. 1006985.4, filed Apr. 27, 2010; Great Britain Patent Application No. 1006988.8, filed Apr. 27, 2010; and Great Britain Patent Application No. 1008347.5, filed May 19, 2010; all of which are hereby incorporated by reference in their entirety.

BACKGROUND OF THE INVENTION**Field of the Invention**

Embodiments of the present invention relate to methods and apparatuses for dressing and treating a wound with topical negative pressure (TNP) therapy. In particular, but not exclusively, embodiments disclosed herein relate to a wound dressing for providing protection to a wound site, in which the wound dressing acts as a buffer to help prevent compression or shear forces exerted on the wound dressing, for example due to patient movement, from harming a healing wound. Embodiments of the wound dressing may act as a waste canister to collect and store wound exudate removed from a wound site, and also relate to the management of solid build-up in a wound dressing covering a wound site whilst TNP therapy is applied. Further, embodiments disclosed herein relate to a method and suction port for applying negative pressure to a wound dressing and a method of manufacturing a suction port and wound dressing.

Description of the Related Art

Many different types of wound dressing are known for aiding in the healing process of a human or animal. These different types of wound dressing include many different types of materials and layers, for example, gauze, pads, foam pads or multi-layer wound dressings.

In addition, TNP therapy, sometimes referred as vacuum assisted closure or negative pressure wound therapy, has recently been proposed as a successful mechanism for improving the healing rate of a wound. Such therapy is applicable to a broad range of wounds such as incisional wounds, open wounds and abdominal wounds or the like.

TNP therapy assists in the closure and healing of wounds by reducing tissue oedema; encouraging blood flow; stimulating the formation of granulation tissue; removing excess exudates and may reduce bacterial load and thus, infection to the wound. Furthermore, TNP therapy permits less outside disturbance of the wound and promotes more rapid healing.

2

During TNP therapy, a suction source such as a vacuum pump or the like is utilized to create a negative pressure region. That is to say, a region where an experienced pressure is below that of the surroundings. Wound exudate and other potentially harmful material is extracted from the wound region and must be stored for later disposal. A problem associated with many known techniques is that a separate canister must be provided for storage of such exudate. Provision of such canisters is costly and bulky and prone to failure.

A proposal has been suggested to store extracted wound exudate in the wound dressing itself that is used to cover a wound site and create the wound chamber region where negative pressure is established. However, it is known that many different wound types can exude high flow rates of exudate and therefore storage of exuding material in a wound dressing can be problematical since the wound dressing will only have a limited capacity for fluid uptake before a dressing change is required. This can limit a time of use between dressing changes and can prove costly if many wound dressings are required to treat a given wound.

It has been suggested as a solution to this problem, that a liquid impermeable moisture vapor permeable cover layer can be utilized as an uppermost cover layer for the wound dressing. The air impermeable nature of the cover layer provides a sealing layer over the wound site so that negative pressure can be established below the dressing in the region of the wound. The moisture vapor permeability of this covering layer is selected so that liquid can constantly evaporate away from the top of the dressing. This means that as therapy is continued the dressing does not have to take up and hold all liquid exuding from the wound. Rather, some liquid is constantly escaping in the form of moisture vapor from the upper environs of the dressing.

Whilst such dressings work well in practice, the continuous evaporation of moisture vapor from the dressing can lead to the problem of crust formation in the dressing. That is to say, because of the continuous drawing of liquid away from the wound site solid particulate matter is more prone to formation and accumulation in the dressing. Under certain circumstances the build-up of such solid material can lead to blockages forming in the wound dressing in the flowpath between the wound and the source of negative pressure. This can potentially cause problems in that therapy may need to be halted to change a dressing if the blockages reach a critical level.

Further, there is much prior art available relating to the provision of apparatuses and methods of use thereof for the application of TNP therapy to wounds together with other therapeutic processes intended to enhance the effects of the TNP therapy.

It will be appreciated that from time to time accidents may happen to patients undergoing negative pressure wound therapy. Such accidents might cause short term or long term forces to be applied to a dressing covering a wound. Alternatively patient movement may bring the patient and any dressing covering a healing wound into contact with an external object. In such occurrences compressive forces or lateral forces may occur. Such force can cause disturbance of a wound bed which can damage a wound site. A particular cause for concern is during the treatment of skin graft wounds. Under such conditions lateral forces can entirely upset or tear apart a healing skin graft region.

SUMMARY OF THE INVENTION

It is an aim of certain embodiments of the present invention to at least partly mitigate the above-mentioned problems.

3

It is an aim of certain embodiments of the present invention to provide a method for providing negative pressure at a wound site to aid in wound closure and healing in which wound exudate drawn from a wound site during the therapy is collected and stored in a wound dressing.

It is an aim of certain embodiments of the present invention to provide a wound dressing having an increased capacity for absorbing wound exudate reducing the frequency with which the dressings must be changed.

It is further an aim of certain embodiments of the invention to manage the movement of wound exudate through a dressing to avoid blockages occurring that lead to reduced life of the dressing.

It is an aim of certain embodiments of the present invention to provide a wound dressing having an increased capacity to absorb compressive forces exerted on the wound dressing.

It is an aim of certain embodiments of the present invention to provide a wound dressing having an increased capacity to prevent shear forces from an outer surface of a wound dressing from being translated into corresponding shear forces at a wound site.

It is an aim of certain embodiments of the present invention to provide a wound dressing which can “give” in a direction perpendicular to and parallel to a wound site surface even when the dressing experiences negative pressure.

It is an aim of certain embodiments of the present invention to provide a wound dressing able to be used with topical negative pressure therapy which helps maintain an open flow path so that therapy can be continued unhindered by blockages caused by build-up of solid matter.

It is an aim of certain embodiments of the present invention to provide a method and apparatus for treating a wound with topical negative pressure therapy by preventing blockage of a flowpath region of a wound dressing.

Embodiments disclosed herein are directed toward the treatment of wounds with TNP. In particular, certain embodiments disclose a wound dressing capable of absorbing and storing wound exudate in conjunction with a pump, for example a miniaturized pump. Some wound dressing embodiments further comprise a transmission layer configured to transmit wound exudates to an absorbent layer disposed in the wound dressing. Additionally, some embodiments provide for a port or other fluidic connector configured to retain wound exudate within the wound dressing while transmitting negative pressure to the wound dressing.

According to a first embodiment of the present invention there is provided a wound treatment apparatus comprising:

- a transmission layer comprising a 3D knitted or fabric material configured to remain open upon application of negative pressure to the wound dressing;
- an absorbent layer for absorbing wound exudate, the absorbent layer overlying the transmission layer;
- a cover layer overlying the absorbent layer and comprising an orifice,
- wherein the cover layer is moisture vapor permeable;
- a pump; and
- a suction port for applying negative pressure to the wound dressing for the application of topical negative pressure at a wound site, the suction port comprising:
- a connector portion for connecting the suction port to the pump;
- a sealing surface for sealing the suction port to the cover layer of the wound dressing; and

4

a liquid impermeable gas permeable filter element arranged to prevent a liquid from entering the connector portion.

According to a second embodiment of the present invention there is provided a method for the treatment of a wound comprising:

providing a wound dressing comprising:

- a transmission layer comprising a 3D knitted or fabric material;
- an absorbent layer for absorbing wound exudate, the absorbent layer overlying the transmission layer;
- a cover layer overlying the absorbent layer and comprising an orifice,

wherein the cover layer is moisture vapor permeable; positioning the dressing over a wound site to form a sealed cavity over the wound site; and applying negative pressure to the wound site to draw fluid through the transmission layer into the absorbent layer.

According to a another embodiment of the present invention there is provided a wound dressing for providing protection at a wound site, comprising:

- a transmission layer comprising a first surface and a further surface spaced apart from the first surface by a relax distance in a relaxed mode of operation; and
- a plurality of spacer elements extending between the first and further surfaces and, in a forced mode of operation, locatable whereby the first and further surfaces are spaced apart by a compression distance less than the relax distance.

According to a one embodiment of the present invention there is provided a method for providing protection at a wound site, comprising:

- locating a wound dressing comprising a transmission layer over a wound site; and
- responsive to a force on the wound dressing, displacing a plurality of spacer elements extending between a first surface and a further surface of the transmission layer whereby;
- a distance between the first and further surfaces is reduced as the spacer elements are displaced.

According to another embodiment of the present invention there is provided an apparatus for dressing a wound for the application of topical negative pressure at a wound site, comprising:

- a liquid and gas permeable transmission layer;
- an absorbent layer for absorbing wound exudate, the absorbent layer overlying the transmission layer;
- a gas impermeable cover layer overlying the absorbent layer and comprising a first orifice, wherein the cover layer is moisture vapor permeable.

According to a further embodiment of the present invention there is provided a method of applying TNP at a wound site, comprising the steps of:

- applying negative pressure at an orifice of a cover layer of a wound dressing, a peripheral region around the wound site being sealed with the wound dressing, such that air and wound exudate are drawn towards the orifice;
- collecting wound exudate, drawn from the wound site, through a transmission layer of the wound dressing, in an absorbent layer of the wound dressing; and
- transpiring a water component of the wound exudate collected in the absorbent layer through the cover layer of the wound dressing.

5

According to an additional embodiment of the present invention there is provided apparatus for dressing a wound for the application of topical negative pressure at a wound site, comprising:

- a liquid and gas permeable transmission layer;
- an absorbent layer for absorbing wound exudate;
- a gas impermeable cover layer overlying the absorbent layer and the transmission layer, the cover layer comprising an orifice connected to the transmission layer; and
- at least one element configured to reduce the rate at which wound exudate moves towards the orifice when a negative pressure is applied at the orifice.

According to another embodiment of the present invention there is provided a method of applying TNP at a wound site, comprising the steps of:

- applying negative pressure at an orifice of a cover layer of a wound dressing, a peripheral region around the wound site being sealed with the wound dressing such that air and wound exudate move towards the orifice;
- collecting wound exudate, from the wound site, through a transmission layer of the wound dressing, in an absorbent layer of the wound dressing; and
- reducing the rate at which wound exudate moves towards the orifice.

According to still another embodiment of the present invention there is provided apparatus for dressing a wound for the application of topical negative pressure at a wound site, comprising:

- an absorbent layer for absorbing wound exudate;
- a gas impermeable cover layer overlying the absorbent layer the cover layer comprising at least one orifice configured to allow negative pressure to be communicated through the cover layer in at least two spaced apart regions.

According to an additional embodiment of the present invention there is provided a method of applying TNP at a wound site, comprising the steps of:

- sealing a cover layer of a wound dressing around the wound site;
- applying negative pressure at at least one orifice in the cover layer, said at least one orifice configured to allow negative pressure to be communicated through the cover layer in at least two spaced apart regions; and
- collecting wound exudate, from the wound site, in an absorbent layer of the wound dressing.

According to one embodiment of the present invention there is provided a suction port for applying negative pressure to a wound dressing for the application of topical negative pressure at a wound site, the suction port comprising:

- a connector portion for connecting the suction port to a source of negative pressure;
- a sealing surface for sealing the suction port to a cover layer of a wound dressing; and
- a liquid impermeable gas permeable filter element arranged to prevent a liquid entering the connector portion.

According to an additional embodiment of the present invention there is provided a method of communicating negative pressure to a wound dressing for the application of topical negative pressure at a wound site, comprising the steps of:

- applying negative pressure at a connecting portion of a suction port sealed around a perimeter of an orifice in a cover layer of the wound dressing;

6

filtering gas drawn from within the wound dressing through a liquid impermeable gas permeable filter element of the suction port.

According to another embodiment of the invention there is provided a method of manufacturing a suction port for applying negative pressure to a wound dressing for the application of topical negative pressure at a wound site, the suction port having a connector portion for connecting the suction port to a source of negative pressure and a sealing surface for sealing the suction port to a cover layer of a wound dressing, the method comprising:

- disposing a liquid impermeable gas permeable filter element of the suction port at a location to prevent a liquid entering the connector portion.

According to yet another embodiment of the present invention there is provided apparatus for the application of TNP therapy to a wound site, comprising:

- a first layer comprising a plurality of openings each having a first open area;
- a further layer spaced apart from the first layer comprising a plurality of further openings each having a further open area; and
- an air impermeable, moisture vapor permeable cover layer over the first and further layers; wherein a region between the first and further layers comprises a portion of a flow path for air and/or wound exudate flowing from a wound site and said first open area is less than said further open area.

According to still another embodiment of the present invention there is provided a method of applying TNP therapy to a wound site, comprising:

- via a vacuum pump in fluid communication with a wound dressing located over a wound site, applying a negative pressure at the wound site; and
- as liquid evaporates through a cover layer of the dressing, preventing blockage of a fluid flowpath region of the wound dressing.

Certain embodiments provide a wound dressing which even when under negative pressure conditions is able to provide further "give" to buffer compression forces from harming a wound.

Certain embodiments provide a wound dressing able to disconnect shear forces applied to the dressing from the wound site covered by the dressing. As a result damage to the wound can be wholly or at least partially avoided.

Certain embodiments provide the advantage that a wound site can be covered with a wound dressing which is simultaneously able to deliver negative pressure wound therapy to a wound site, collect exudate and provide protection from forces operating on the dressing.

Certain embodiments provide the advantage that forces operating on a dressing can be offset by dissipating loads operating over a relatively small distance on an upper layer of the dressing to a relatively larger area on a lower surface of the dressing. The force is thus dissipated over a larger area thus reducing the effect of the force.

Certain embodiments provide the advantage that a wound dressing can be used to collect wound exudate generated during a negative pressure therapy process, whilst extending the useful lifetime of the dressing by transpiring a water component of the wound exudate. A pump remote from the wound dressing can be connected to the wound dressing and reused whilst the wound dressing itself is used to collect wound exudate and may then be disposed of after use.

Certain embodiments provide a wound dressing and/or method of applying topical negative pressure in which a

7

flowpath through a wound dressing is kept open so that therapy can be continued for as long as desired by a care giver.

Certain embodiments prevent solid material, which may cause a blockage, from entering a flowpath region in the wound dressing by using a layer of the dressing to act as a bar to such material.

Certain embodiments prevent build-up of solid material in a flowpath region of a wound dressing by ensuring that any solid material that enters into that flowpath region can always escape into a further region of the dressing.

Certain embodiments provide the advantage that the build-up of solid material in a flowpath in a wound dressing is avoided by having an absorbent layer close to the flowpath region store liquid over time. This helps keep the environment of the flowpath region moist which helps avoid crusting.

Certain embodiments provide the advantage that a wound dressing can be used to collect wound exudate generated during a negative pressure therapy process, whilst extending the useful lifetime of the dressing by transpiring a water component of the wound exudate. A pump remote from the wound dressing can be connected to the wound dressing and reused whilst the wound dressing itself is used to collect wound exudate and may then be disposed of after use.

BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments of the present invention will now be described hereinafter, by way of example only, with reference to the accompanying drawings in which:

FIG. 1A illustrates a wound dressing;

FIG. 1B illustrates another embodiment of a wound dressing;

FIG. 2 illustrates a top view of a wound dressing;

FIG. 3 illustrates a top view of a wound dressing including baffle elements;

FIG. 4 illustrates a top view of a further wound dressing including baffle elements;

FIG. 5 illustrates a baffle element according to one embodiment;

FIG. 6 illustrates a top view of a wound dressing including a single baffle element;

FIG. 7 illustrates a top view of a wound dressing including an air channel;

FIG. 8 illustrates a top view of a wound dressing including two air channels;

FIG. 9 illustrates a top view of a wound dressing including two orifices in a cover layer coupled through a fluid communication passage;

FIG. 10 illustrates an embodiment of the fluid communication passage;

FIG. 11 illustrates a top view of a suction port;

FIG. 12 illustrates a suction port including a filter element;

FIG. 13 illustrates a further suction port including a filter element;

FIGS. 14A-L illustrate a range of exemplifying configurations of baffle elements in a wound dressing;

FIG. 15 illustrates an exemplifying configuration of vias in a transmission layer of a wound dressing;

FIG. 16 illustrates a top view of a wound dressing including an elongate orifice in a cover layer;

FIG. 17 illustrates a transmission layer in a relaxed mode of operation;

FIG. 18 illustrates a transmission layer in a forced mode of operation;

8

FIG. 19 illustrates pressure offsetting;

FIG. 20 illustrates a transmission layer and overlying absorbent layer in a relaxed mode of operation;

FIG. 21 illustrates an absorbent layer and transmission layer experiencing a compressive force;

FIG. 22 illustrates an absorbent layer and transmission layer experiencing a shear force;

FIG. 23 illustrates a cross-section of a region of an embodiment of a wound dressing;

FIG. 24 illustrates a lower layer of a transmission layer used in an embodiment of a wound dressing;

FIG. 25 illustrates an upper layer of a transmission layer used in an embodiment of a wound dressing;

FIG. 26 illustrates a lower surface of a transmission layer used in another embodiment of a wound dressing;

FIG. 27 illustrates an upper surface of a transmission layer used in another embodiment of a wound dressing;

FIG. 28 illustrates an embodiment of a wound treatment system; and,

FIGS. 29A-D illustrate the use and application of an embodiment of a wound treatment system onto a patient.

In the drawings like reference numerals refer to like parts.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIGS. 1A-B illustrate cross sections through a wound dressing **100** according to an embodiment of the invention. A plan view from above the wound dressing **100** is illustrated in FIG. 2 with the line A-A indicating the location of the cross section shown in FIGS. 1A and 1B. It will be understood that FIGS. 1A-B illustrate a generalized schematic view of an apparatus **100**. It will be understood that embodiments of the present invention are generally applicable to use in TNP therapy systems. Briefly, negative pressure wound therapy assists in the closure and healing of many forms of "hard to heal" wounds by reducing tissue oedema; encouraging blood flow and granular tissue formation; removing excess exudate and may reduce bacterial load (and thus infection risk). In addition, the therapy allows for less disturbance of a wound leading to more rapid healing. TNP therapy systems may also assist on the healing of surgically closed wounds by removing fluid and by helping to stabilize the tissue in the apposed position of closure. A further beneficial use of TNP therapy can be found in grafts and flaps where removal of excess fluid is important and close proximity of the graft to tissue is required in order to ensure tissue viability.

The wound dressing **100** can be located over a wound site to be treated. The dressing **100** forms a sealed cavity over the wound site. It will be appreciated that throughout this specification reference is made to a wound. In this sense it is to be understood that the term wound is to be broadly construed and encompasses open and closed wounds in which skin is torn, cut or punctured or where trauma causes a contusion. A wound is thus broadly defined as any damaged region of tissue where fluid may or may not be produced. Examples of such wounds include, but are not limited to, incisions, lacerations, abrasions, contusions, burns, diabetic ulcers, pressure ulcers, stoma, surgical wounds, trauma and venous ulcers or the like.

In some embodiments, it may be preferable for the wound site to be filled partially or completely with a wound packing material. This wound packing material is optional, but may be desirable in certain wounds, for example deeper wounds. The wound packing material can be used in addition to the wound dressing **100**. The wound packing material generally

may comprise a porous and conformable material, for example foam (including reticulated foams), and gauze. Preferably, the wound packing material is sized or shaped to fit within the wound site so as to fill any empty spaces. The wound dressing **100** may then be placed over the wound site and wound packing material overlying the wound site. When a wound packing material is used, once the wound dressing **100** is sealed over the wound site, TNP is transmitted from a pump through the wound dressing **100**, through the wound packing material, and to the wound site. This negative pressure draws wound exudate and other fluids or secretions away from the wound site.

It is envisaged that the negative pressure range for the apparatus embodying the present invention may be between about -20 mmHg and -200 mmHg (note that these pressures are relative to normal ambient atmospheric pressure thus, -200 mmHg would be about 560 mmHg in practical terms). In one embodiment, the pressure range may be between about -40 mmHg and -150 mmHg. Alternatively a pressure range of up to -75 mmHg, up to -80 mmHg or over -80 mmHg can be used. Also in other embodiments a pressure range of below -75 mmHg could be used. Alternatively a pressure range of over -100 mmHg could be used or over -150 mmHg.

It will be appreciated that according to certain embodiments of the present invention the pressure provided may be modulated over a period of time according to one or more desired and predefined pressure profiles. For example such a profile may include modulating the negative pressure between two predetermined negative pressures P1 and P2 such that pressure is held substantially constant at P1 for a pre-determined time period T1 and then adjusted by suitable means such as varying pump work or restricting fluid flow or the like, to a new predetermined pressure P2 where the pressure may be held substantially constant for a further predetermined time period T2. Two, three or four or more predetermined pressure values and respective time periods may be optionally utilized. Other embodiments may employ more complex amplitude/frequency wave forms of pressure flow profiles may also be provided e.g. sinusoidal, saw tooth, systolic-diastolic or the like.

As illustrated in FIGS. 1A-B a lower surface **101** of the wound dressing **100** is provided by an optional wound contact layer **102**. The wound contact layer **102** can be a polyurethane layer or polyethylene layer or other flexible layer which is perforated, for example via a hot pin process, laser ablation process, ultrasound process or in some other way or otherwise made permeable to liquid and gas. The wound contact layer has a lower surface **101** and an upper surface **103**. The perforations **104** are through holes in the wound contact layer which enables fluid to flow through the layer. The wound contact layer helps prevent tissue ingrowth into the other material of the wound dressing. The perforations are small enough to meet this requirement but still allow fluid through. For example, perforations formed as slits or holes having a size ranging from 0.025 mm to 1.2 mm are considered small enough to help prevent tissue ingrowth into the wound dressing while allowing wound exudate to flow into the dressing. The wound contact layer helps hold the whole wound dressing together and helps to create an air tight seal around the absorbent pad in order to maintain negative pressure at the wound. The wound contact layer also acts as a carrier for an optional lower and upper adhesive layer (not shown). For example, a lower pressure sensitive adhesive may be provided on the underside surface **101** of the wound dressing whilst an upper pressure sensitive adhesive layer may be provided on the upper surface **103** of

the wound contact layer. The pressure sensitive adhesive, which may be a silicone, hot melt, hydrocolloid or acrylic based adhesive or other such adhesives, may be formed on both sides or optionally on a selected one or none of the sides of the wound contact layer. When a lower pressure sensitive adhesive layer is utilized this helps adhere the wound dressing to the skin around a wound site.

A layer **105** of porous material is located above the wound contact layer. This porous layer, or transmission layer, **105** allows transmission of fluid including liquid and gas away from a wound site into upper layers of the wound dressing. In particular, the transmission layer **105** ensures that an open air channel can be maintained to communicate negative pressure over the wound area even when the absorbent layer has absorbed substantial amounts of exudates. The layer should remain open under the typical pressures that will be applied during negative pressure wound therapy as described above, so that the whole wound site sees an equalized negative pressure. The layer **105** is formed of a material having a three dimensional structure. For example, a knitted or woven spacer fabric (for example B altex 7970 weft knitted polyester) or a non-woven fabric could be used. Other materials could of course be utilized, and examples of such materials are described below with respect to FIGS. 23-27.

In some embodiments, the transmission layer comprises a 3D polyester spacer fabric layer including a top layer (that is to say, a layer distal from the wound-bed in use) which is a 84/144 textured polyester, and a bottom layer (that is to say, a layer which lies proximate to the wound bed in use) which is a 100 denier flat polyester and a third layer formed sandwiched between these two layers which is a region defined by a knitted polyester viscose, cellulose or the like monofilament fiber. Other materials and other linear mass densities of fiber could of course be used.

Whilst reference is made throughout this disclosure to a monofilament fiber it will be appreciated that a multistrand alternative could of course be utilized.

The top spacer fabric thus has more filaments in a yarn used to form it than the number of filaments making up the yarn used to form the bottom spacer fabric layer.

This differential between filament counts in the spaced apart layers helps control moisture flow across the transmission layer. Particularly, by having a filament count greater in the top layer, that is to say, the top layer is made from a yarn having more filaments than the yarn used in the bottom layer, liquid tends to be wicked along the top layer more than the bottom layer. In use, this differential tends to draw liquid away from the wound bed and into a central region of the dressing where the absorbent layer helps lock the liquid away or itself wicks the liquid onwards towards the cover layer where it can be transpired.

Preferably, to improve the liquid flow across the transmission layer (that is to say perpendicular to the channel region formed between the top and bottom spacer layers, the 3D fabric is treated with a dry cleaning agent (such as, but not limited to, Perchloro Ethylene) to help remove any manufacturing products such as mineral oils, fats and/or waxes used previously which might interfere with the hydrophilic capabilities of the transmission layer. In some embodiments, an additional manufacturing step can subsequently be carried in which the 3D spacer fabric is washed in a hydrophilic agent (such as, but not limited to, Feran Ice 30 g/l available from the Rudolph Group). This process step helps ensure that the surface tension on the materials is so low that liquid such as water can enter the fabric as soon as

it contacts the 3D knit fabric. This also aids in controlling the flow of the liquid insult component of any exudates.

A layer **110** of absorbent material is provided above the transmission layer **105**. The absorbent material which may be a foam or non-woven natural or synthetic material and which may optionally include or be super-absorbent material forms a reservoir for fluid, particularly liquid, removed from the wound site and draws those fluids towards a cover layer **140**. The material of the absorbent layer also prevents liquid collected in the wound dressing from flowing in a sloshing manner. The absorbent layer **110** also helps distribute fluid throughout the layer via a wicking action so that fluid is drawn from the wound site and stored throughout the absorbent layer. This helps prevent agglomeration in areas of the absorbent layer. The capacity of the absorbent material must be sufficient to manage the exudates flow rate of a wound when negative pressure is applied. Since in use the absorbent layer experiences negative pressures the material of the absorbent layer is chosen to absorb liquid under such circumstances. A number of materials exist that are able to absorb liquid when under negative pressure, for example superabsorber material. The absorbent layer **110** may typically be manufactured from ALLEVYN™ foam, Freudenberg 114-224-4 and/or Chem-Posite™ 11C-450.

In some embodiments, the absorbent layer is a layer of non-woven cellulose fibers having super-absorbent material in the form of dry particles dispersed throughout. Use of the cellulose fibers introduces fast wicking elements which help quickly and evenly distribute liquid taken up by the dressing. The juxtaposition of multiple strand-like fibers leads to strong capillary action in the fibrous pad which helps distribute liquid. In this way, the super-absorbent material is efficiently supplied with liquid. Also, all regions of the absorbent layer are provided with liquid.

The wicking action also assists in bringing liquid into contact with the upper cover layer to aid increase transpiration rates of the dressing.

The wicking action also assists in delivering liquid downwards towards the wound bed when exudation slows or halts. This delivery process helps maintain the transmission layer and lower wound bed region in a moist state which helps prevent crusting within the dressing (which could lead to blockage) and helps maintain an environment optimized for wound healing.

In some embodiments, the absorbent layer may be an air-laid material. Heat fusible fibers may optionally be used to assist in holding the structure of the pad together. It will be appreciated that rather than using super-absorbing particles or in addition to such use, super-absorbing fibers may be utilized according to certain embodiments of the present invention. An example of a suitable material is the Product Chem-Posite™ 11 C available from Emerging Technologies Inc (ETi) in the USA.

Optionally, according to certain embodiments of the present invention, the absorbent layer may include synthetic stable fibers and/or bi-component stable fibers and/or natural stable fibers and/or super-absorbent fibers. Fibers in the absorbent layer may be secured together by latex bonding or thermal bonding or hydrogen bonding or a combination of any bonding technique or other securing mechanism. In some embodiments, the absorbent layer is formed by fibers which operate to lock super-absorbent particles within the absorbent layer. This helps ensure that super-absorbent particles do not move external to the absorbent layer and towards an underlying wound bed. This is particularly helpful because when negative pressure is applied there is a tendency for the absorbent pad to collapse downwards and

this action would push super-absorbent particle matter into a direction towards the wound bed if they were not locked away by the fibrous structure of the absorbent layer.

The absorbent layer may comprise a layer of multiple fibers. Preferably, the fibers are strand-like and made from cellulose, polyester, viscose or the like. Preferably, dry absorbent particles are distributed throughout the absorbent layer ready for use. In some embodiments, the absorbent layer comprises a pad of cellulose fibers and a plurality of super absorbent particles. In additional embodiments, the absorbent layer is a non-woven layer of randomly orientated cellulose fibers.

Super-absorber particles/fibers may be, for example, sodium polyacrylate or carbomethoxycellulose materials or the like or any material capable of absorbing many times its own weight in liquid. In some embodiments, the material can absorb more than five times its own weight of 0.9% W/W saline, etc. In some embodiments, the material can absorb more than 15 times its own weight of 0.9% W/W saline, etc. In some embodiments, the material is capable of absorbing more than 20 times its own weight of 0.9% W/W saline, etc. Preferably, the material is capable of absorbing more than 30 times its own weight of 0.9% W/W saline, etc.

Preferably, the particles of superabsorber are very hydrophilic and grab the fluid as it enters the dressing, swelling up on contact. An equilibrium is set up within the dressing core whereby moisture passes from the superabsorber into the dryer surrounding area and as it hits the top film the film switches and the fluid vapor starts to be transpired. A moisture gradient is established within the dressing to continually remove fluid from the wound bed and ensure the dressing does not become heavy with exudate.

Preferably the absorbent layer includes at least one through hole located so as to underly the suction port. As illustrated in FIGS. 1A-B a single through hole can be used to produce an opening underlying the port **150**. It will be appreciated that multiple openings could alternatively be utilized. Additionally should more than one port be utilized according to certain embodiments of the present invention one or multiple openings may be made in the super-absorbent layer in registration with each respective port. Although not essential to certain embodiments of the present invention the use of through holes in the super-absorbent layer provide a fluid flow pathway which is particularly unhindered and this is useful in certain circumstances.

Where an opening is provided in the absorbent layer the thickness of the layer itself will act as a stand-off separating any overlying layer from the upper surface (that is to say the surface facing away from a wound in use) of the transmission layer **105**. An advantage of this is that the filter of the port is thus decoupled from the material of the transmission layer. This helps reduce the likelihood that the filter will be wetted out and thus will occlude and block further operation.

Use of one or more through holes in the absorption layer also has the advantage that during use if the absorbent layer contains a gel forming material, such as superabsorber, that material as it expands to absorb liquid, does not form a barrier through which further liquid movement and fluid movement in general cannot pass. In this way each opening in the absorbent layer provides a fluid pathway between the transmission layer directly to the wound facing surface of the filter and then onwards into the interior of the port.

A gas impermeable, but moisture vapor permeable, cover layer **140** extends across the width of the wound dressing. The cover layer, which may for example be a polyurethane film (for example, Elastollan SP9109) having a pressure sensitive adhesive on one side, is impermeable to gas and

13

this layer thus operates to cover the wound and to seal a wound cavity over which the wound dressing is placed. In this way an effective chamber is made between the cover layer and a wound site where a negative pressure can be established. The cover layer **140** is sealed to the wound contact layer **102** in a border region **200** around the circumference of the dressing, ensuring that no air is drawn in through the border area, for example via adhesive or welding techniques. The cover layer **140** protects the wound from external bacterial contamination (bacterial barrier) and allows liquid from wound exudates to be transferred through the layer and evaporated from the film outer surface. The cover layer **140** typically comprises two layers; a polyurethane film and an adhesive pattern spread onto the film. The polyurethane film is moisture vapor permeable and may be manufactured from a material that has an increased water transmission rate when wet.

The absorbent layer **110** may be of a greater area than the transmission layer **105**, such that the absorbent layer overlaps the edges of the transmission layer **105**, thereby ensuring that the transmission layer does not contact the cover layer **140**. This provides an outer channel **115** of the absorbent layer **110** that is in direct contact with the wound contact layer **102**, which aids more rapid absorption of exudates to the absorbent layer. Furthermore, this outer channel **115** ensures that no liquid is able to pool around the circumference of the wound cavity, which may otherwise seep through the seal around the perimeter of the dressing leading to the formation of leaks.

In order to ensure that the air channel remains open when a vacuum is applied to the wound cavity, the transmission layer **105** must be sufficiently strong and non-compliant to resist the force due to the pressure differential. However, if this layer comes into contact with the relatively delicate cover layer **140**, it can cause the formation of pin-hole openings in the cover layer **140** which allow air to leak into the wound cavity. This may be a particular problem when a switchable type polyurethane film is used that becomes weaker when wet. The absorbent layer **110** is generally formed of a relatively soft, non-abrasive material compared to the material of the transmission layer **105** and therefore does not cause the formation of pin-hole openings in the cover layer. Thus by providing an absorbent layer **110** that is of greater area than the transmission layer **105** and that overlaps the edges of the transmission layer **105**, contact between the transmission layer and the cover layer is prevented, avoiding the formation of pin-hole openings in the cover layer **140**.

The absorbent layer **110** is positioned in fluid contact with the cover layer **140**. As the absorbent layer absorbs wound exudate, the exudate is drawn towards the cover layer **140**, bringing the water component of the exudate into contact with the moisture vapor permeable cover layer. This water component is drawn into the cover layer itself and then evaporates from the top surface of the dressing. In this way, the water content of the wound exudate can be transpired from the dressing, reducing the volume of the remaining wound exudate that is to be absorbed by the absorbent layer **110**, and increasing the time before the dressing becomes full and must be changed. This process of transpiration occurs even when negative pressure has been applied to the wound cavity, and it has been found that the pressure difference across the cover layer when a negative pressure is applied to the wound cavity has negligible impact on the moisture vapor transmission rate across the cover layer.

An orifice **145** is provided in the cover film **140** to allow a negative pressure to be applied to the dressing **100**. A

14

suction port **150** is sealed to the top of the cover film **140** over the orifice **145**, and communicates negative pressure through the orifice **145**. A length of tubing **220** may be coupled at a first end to the suction port **150** and at a second end to a pump unit (not shown) to allow fluids to be pumped out of the dressing. The port may be adhered and sealed to the cover film **140** using an adhesive such as an acrylic, cyanoacrylate, epoxy, UV curable or hot melt adhesive. The port **150** is formed from a soft polymer, for example a polyethylene, a polyvinyl chloride, a silicone or polyurethane having a hardness of 30 to 90 on the Shore A scale.

An aperture or through-hole **146** is provided in the absorbent layer **110** beneath the orifice **145** such that the orifice is connected directly to the transmission layer **105**. This allows the negative pressure applied to the port **150** to be communicated to the transmission layer **105** without passing through the absorbent layer **110**. This ensures that the negative pressure applied to the wound site is not inhibited by the absorbent layer as it absorbs wound exudates. In other embodiments, no aperture may be provided in the absorbent layer **110**, or alternatively a plurality of apertures underlying the orifice **145** may be provided.

As shown in FIG. 1A, one embodiment of the wound dressing **100** comprises an aperture **146** in the absorbent layer **110** situated underneath the port **150**. In use, for example when negative pressure is applied to the dressing **100**, a wound facing portion of the port **150** may thus come into contact with the transmission layer **105**, which can thus aid in transmitting negative pressure to the wound site even when the absorbent layer **110** is filled with wound fluids. Some embodiments may have the cover layer **140** be at least partly adhered to the transmission layer **105**. In some embodiments, the aperture **146** is at least 1-2 mm larger than the diameter of the wound facing portion of the port **150**, or the orifice **145**.

A filter element **130** that is impermeable to liquids, but permeable to gases is provided to act as a liquid barrier, and to ensure that no liquids are able to escape from the wound dressing. The filter element may also function as a bacterial barrier. Typically the pore size is 0.2 μm . Suitable materials for the filter material of the filter element **130** include 0.2 micron GoreTM expanded PTFE from the MMT range, PALL VersaporeTM 200R, and DonaldsonTM TX6628. Larger pore sizes can also be used but these may require a secondary filter layer to ensure full bioburden containment. As wound fluid contains lipids it is preferable, though not essential, to use an oleophobic filter membrane for example 1.0 micron MMT-332 prior to 0.2 micron MMT-323. This prevents the lipids from blocking the hydrophobic filter. The filter element can be attached or sealed to the port and/or the cover film **140** over the orifice **145**. For example, the filter element **130** may be molded into the port **150**, or may be adhered to both the top of the cover layer **140** and bottom of the port **150** using an adhesive such as, but not limited to, a UV cured adhesive.

It will be understood that other types of material could be used for the filter element **130**. More generally a microporous membrane can be used which is a thin, flat sheet of polymeric material, this contains billions of microscopic pores. Depending upon the membrane chosen these pores can range in size from 0.01 to more than 10 micrometers. Microporous membranes are available in both hydrophilic (water filtering) and hydrophobic (water repellent) forms. In some embodiments of the invention, filter element **130** comprises a support layer and an acrylic co-polymer membrane formed on the support layer. Preferably the wound dressing **100** according to certain embodiments of the pres-

15

ent invention uses microporous hydrophobic membranes (MHMs). Numerous polymers may be employed to form MHMs. For example, PTFE, polypropylene, PVDF and acrylic copolymer. All of these optional polymers can be treated in order to obtain specific surface characteristics that can be both hydrophobic and oleophobic. As such these will repel liquids with low surface tensions such as multi-vitamin infusions, lipids, surfactants, oils and organic solvents.

MHMs block liquids whilst allowing air to flow through the membranes. They are also highly efficient air filters eliminating potentially infectious aerosols and particles. A single piece of MHM is well known as an option to replace mechanical valves or vents. Incorporation of MHMs can thus reduce product assembly costs improving profits and costs/benefit ratio to a patient.

The filter element **130** may also include an odor absorbent material, for example activated charcoal, carbon fiber cloth or Vitec Carbotec-RT Q2003073 foam, or the like. For example, an odor absorbent material may form a layer of the filter element **130** or may be sandwiched between microporous hydrophobic membranes within the filter element.

The filter element **130** thus enables gas to be exhausted through the orifice **145**. Liquid, particulates and pathogens however are contained in the dressing.

In FIG. 1B, an embodiment of the wound dressing **100** is illustrated which comprises spacer elements **152**, **153** in conjunction with the port **150** and the filter **130**. With the addition of such spacer elements **152**, **153**, the port **150** and filter **130** may be supported out of direct contact with the absorbent layer **110** and/or the transmission layer **105**. The absorbent layer **110** may also act as an additional spacer element to keep the filter **130** from contacting the transmission layer **105**. Accordingly, with such a configuration contact of the filter **130** with the transmission layer **105** and wound fluids during use may thus be minimized. As contrasted with the embodiment illustrated in FIG. 1A, the aperture **146** through the absorbent layer **110** may not necessarily need to be as large or larger than the port **150**, and would thus only need to be large enough such that an air path can be maintained from the port to the transmission layer **105** when the absorbent layer **110** is saturated with wound fluids.

In particular for embodiments with a single port **150** and through hole, it may be preferable for the port **150** and through hole to be located in an off-center position as illustrated in FIGS. 1A-B and in FIG. 2. Such a location may permit the dressing **100** to be positioned onto a patient such that the port **150** is raised in relation to the remainder of the dressing **100**. So positioned, the port **150** and the filter **130** may be less likely to come into contact with wound fluids that could prematurely occlude the filter **130** so as to impair the transmission of negative pressure to the wound site.

FIG. 11 shows a plan view of a suction port **150** according to some embodiments of the invention. The suction port comprises a sealing surface **152** for sealing the port to a wound dressing, a connector portion **154** for connecting the suction port **150** to a source of negative pressure, and a hemispherical body portion **156** disposed between the sealing surface **152** and the connector portion **154**. Sealing surface **152** comprises a flange that provides a substantially flat area to provide a good seal when the port **150** is sealed to the cover layer **140**. Connector portion **154** is arranged to be coupled to the external source of negative pressure via a length of tube **220**.

According to some embodiments, the filter element **130** forms part of the bacterial barrier over the wound site, and therefore it is important that a good seal is formed and

16

maintained around the filter element. However, it has been determined that a seal formed by adhering the filter element **130** to the cover layer **140** is not sufficiently reliable. This is a particular problem when a moisture vapor permeable cover layer is used, as the water vapor transpiring from the cover layer **140** can affect the adhesive, leading to breach of the seal between the filter element and the cover layer. Thus, according to some embodiments of the invention an alternative arrangement for sealing the filter element **130** to stop liquid from entering the connector portion **154** is employed.

FIG. 12 illustrates a cross section through the suction port **150** of FIG. 11 according to some embodiments of the invention, the line A-A in FIG. 11 indicating the location of the cross section. In the suction port of FIG. 12, the suction port **150** further comprises filter element **130** arranged within the body portion **156** of the suction port **150**. A seal between the suction port **150** and the filter element **130** is achieved by molding the filter element within the body portion of the suction port **150**.

FIG. 13 illustrates a cross section through the suction port **150** of FIG. 11 according to some embodiments of the invention. In the suction port of FIG. 13, the filter element **130** is sealed to the sealing surface **152** of the suction port **150**. The filter element may be sealed to the sealing surface using an adhesive or by welding the filter element to the sealing surface.

By providing the filter element **130** as part of the suction port **150**, as illustrated in FIGS. 12 and 13, the problems associated with adhering the filter element to the cover layer **140** are avoided allowing a reliable seal to be provided. Furthermore, providing a sub-assembly having the filter element **130** included as part of the suction port **150** allows for simpler and more efficient manufacture of the wound dressing **100**.

While the suction port **150** has been described in the context of the wound dressing **100** of FIG. 1, it will be understood that the embodiments of FIGS. 12 and 13 are applicable to any wound dressing for applying a negative pressure to a wound, wherein wound exudate drawn from the wound is retained within the dressing. According to some embodiments of the invention, the suction port **150** may be manufactured from a transparent material in order to allow a visual check to be made by a user for the ingress of wound exudate into the suction port **150**.

The wound dressing **100** and its methods of manufacture and use as described herein may also incorporate features, configurations and materials described in the following patents and patent applications incorporated by reference in their entireties: U.S. Pat. Nos. 7,524,315, 7,708,724, and 7,909,805; U.S. Patent Application Publication Nos. 2005/0261642, 2007/0167926, 2009/0012483, 2009/0254054, 2010/0160879, 2010/0160880, 2010/0174251, 2010/0274207, 2010/0298793, 2011/0009838, 2011/0028918, 2011/0054421, and 2011/0054423; as well as U.S. application Ser. No. 12/941,390, filed Nov. 8, 2010, Ser. No. 29/389,782, filed Apr. 15, 2011, and Ser. No. 29/389,783, filed Apr. 15, 2011. From these incorporated by reference patents and patent applications, features, configurations, materials and methods of manufacture or use for similar components to those described in the present disclosure may be substituted, added or implemented into embodiments of the present application.

In operation the wound dressing **100** is sealed over a wound site forming a wound cavity. A pump unit (illustrated in FIG. 28 and described in further detail below) applies a negative pressure at a connection portion **154** of the port **150** which is communicated through the orifice **145** to the

17

transmission layer **105**. Fluid is drawn towards the orifice through the wound dressing from a wound site below the wound contact layer **102**. The fluid moves towards the orifice through the transmission layer **105**. As the fluid is drawn through the transmission layer **105** wound exudate is absorbed into the absorbent layer **110**.

Turning to FIG. 2 which illustrates a wound dressing **100** in accordance with an embodiment of the present invention one can see the upper surface of the cover layer **140** which extends outwardly away from a centre of the dressing into a border region **200** surrounding a central raised region **201** overlying the transmission layer **105** and the absorbent layer **110**. As indicated in FIG. 2 the general shape of the wound dressing is rectangular with rounded corner regions **202**. It will be appreciated that wound dressings according to other embodiments of the present invention can be shaped differently such as square, circular or elliptical dressings, or the like.

The wound dressing **100** may be sized as necessary for the size and type of wound it will be used in. In some embodiments, the wound dressing **100** may measure between 20 and 40 cm on its long axis, and between 10 to 25 cm on its short axis. For example, dressings may be provided in sizes of 10×20 cm, 10×30 cm, 10×40 cm, 15×20 cm, and 15×30 cm. In some embodiments, the wound dressing **100** may be a square-shaped dressing with sides measuring between 15 and 25 cm (e.g., 15×15 cm, 20×20 cm and 25×25 cm). The absorbent layer **110** may have a smaller area than the overall dressing, and in some embodiments may have a length and width that are both about 3 to 10 cm shorter, more preferably about 5 cm shorter, than that of the overall dressing **100**. In some rectangular-shape embodiments, the absorbent layer **110** may measure between 10 and 35 cm on its long axis, and between 5 and 10 cm on its short axis. For example, absorbent layers may be provided in sizes of 5.6×15 cm or 5×10 cm (for 10×20 cm dressings), 5.6×25 cm or 5×20 cm (for 10×30 cm dressings), 5.6×35 cm or 5×30 cm (for 10×40 cm dressings), 10×15 cm (for 15×20 cm dressings), and 10×25 cm (for 15×30 cm dressings). In some square-shape embodiments, the absorbent layer **110** may have sides that are between 10 and 20 cm in length (e.g., 10×10 cm for a 15×15 cm dressing, 15×15 cm for a 20×20 cm dressing, or 20×20 cm for a 25×25 cm dressing). The transmission layer **105** is preferably smaller than the absorbent layer, and in some embodiments may have a length and width that are both about 0.5 to 2 cm shorter, more preferably about 1 cm shorter, than that of the absorbent layer. In some rectangular-shape embodiments, the transmission layer may measure between 9 and 34 cm on its long axis and between 3 and 5 cm on its short axis. For example, transmission layers may be provided in sizes of 4.6×14 cm or 4×9 cm (for 10×20 cm dressings), 4.6×24 cm or 4×19 cm (for 10×30 cm dressings), 4.6×34 cm or 4×29 cm (for 10×40 cm dressings), 9×14 cm (for 15×20 cm dressings), and 9×24 cm (for 15×30 cm dressings). In some square-shape embodiments, the transmission layer may have sides that are between 9 and 19 cm in length (e.g., 9×9 cm for a 15×15 cm dressing, 14×14 cm for a 20×20 cm dressing, or 19×19 cm for a 25×25 cm dressing).

It will be understood that according to embodiments of the present invention the wound contact layer is optional. This layer is, if used, porous to water and faces an underlying wound site. A transmission layer **105** such as an open celled foam, or a knitted or woven spacer fabric is used to distribute gas and fluid removal such that all areas of a wound are subjected to equal pressure. The cover layer together with the filter layer forms a substantially liquid tight

18

seal over the wound. Thus when a negative pressure is applied to the port **150** the negative pressure is communicated to the wound cavity below the cover layer. This negative pressure is thus experienced at the target wound site. Fluid including air and wound exudate is drawn through the wound contact layer and transmission layer **105**. The wound exudate drawn through the lower layers of the wound dressing is dissipated and absorbed into the absorbent layer **110** where it is collected and stored. Air and moisture vapor is drawn upwards through the wound dressing through the filter layer and out of the dressing through the suction port. A portion of the water content of the wound exudate is drawn through the absorbent layer and into the cover layer **140** and then evaporates from the surface of the dressing.

As discussed above, when a negative pressure is applied to a wound dressing sealed over a wound site, fluids including wound exudate are drawn from the wound site and through the transmission layer **105** towards the orifice **145**. Wound exudate is then drawn into the absorbent layer **110** where it is absorbed. However, some wound exudate may not be absorbed and may move to the orifice **145**. Filter element **130** provides a barrier that stops any liquid in the wound exudate from entering the connection portion **154** of the suction port **150**. Therefore, unabsorbed wound exudate may collect underneath the filter element **130**. If sufficient wound exudate collects at the filter element, a layer of liquid will form across the surface of filter element **130** and the filter element will become blocked as the liquid cannot pass through the filter element **130** and gases will be stopped from reaching the filter element by the liquid layer. Once the filter element becomes blocked, negative pressure can no longer be communicated to the wound site, and the wound dressing must be changed for a fresh dressing, even though the total capacity of the absorbent layer has not been reached.

In a preferred embodiment, the port **150**, along with any aperture **146** in the absorbing layer **110** situated below it, generally aligns with the mid-longitudinal axis A-A illustrated in FIG. 2. Preferably, the port **150** and any such aperture **146** are situated closer to one end of the dressing, contrasted with a central position. In some embodiments, the port may be located at a corner of the dressing **100**. For example, in some rectangular embodiments, the port **150** may be located between 4 and 6 cm from the edge of the dressing, with the aperture **146** located 2 to 3 cm from the edge of the absorbent layer. In some square embodiments, the port **150** may be located between 5 to 8 cm from the corner of the dressing, with the aperture **146** located 3 to 5 cm from the corner of the absorbent layer.

Certain orientations of the wound dressing may increase the likelihood of the filter element **130** becoming blocked in this way, as the movement of the wound exudate through the transmission layer may be aided by the effect of gravity. Thus, if due to the orientation of the wound site and wound dressing, gravity acts to increase the rate at which wound exudate is drawn towards the orifice **145**, the filter may become blocked with wound exudate more quickly. Thus, the wound dressing would have to be changed more frequently and before the absorbent capacity of the absorbent layer **110** has been reached.

In order to avoid the premature blocking of the wound dressing **100** by wound exudate drawn towards the orifice **145** some embodiments of the invention include at least one element configured to reduce the rate at which wound exudate moves towards the orifice **145**. The at least one element may increase the amount of exudate that is absorbed into the absorbent layer before reaching the orifice **145**

and/or may force the wound exudate to follow a longer path through the dressing before reaching the orifice **145**, thereby increasing the time before the wound dressing becomes blocked.

FIG. **3** shows a plan view of a wound dressing including baffle elements that reduce the rate at which wound exudate moves towards the orifice according to one embodiment of the invention. The wound dressing illustrated in FIG. **3** is similar to that shown in FIGS. **1** and **2**, but includes a number of baffle elements **310** disposed across the central raised region **201**. The baffle elements **310** form barriers in the central region of the dressing, which arrest the movement of wound exudate towards the orifice.

Embodiments of baffle elements that may be used in the wound dressing described herein are preferably at least partly flexible, so as to permit the wound dressing to flex and conform with the skin of the patient surrounding the wound site. When so present in the wound dressing, the baffle elements are preferably constructed so as to at least partially prevent liquid from flowing directly to the wound dressing port or orifice and its associated filter, if so provided. The baffle elements thus increase the distance that liquids may require to reach the port, which may help in absorbing these fluids into the absorbent or superabsorbent material of the wound dressing.

According to some embodiments of the invention, the baffle element may comprise a sealing region in which the absorbent layer **110** and transmission layer **105** are absent and cover layer **140** is sealed to the wound contact layer **101**. Thus, the baffle element presents a barrier to the motion of the wound exudate, which must therefore follow a path that avoids the baffle element. Thus the time taken for the wound exudate to reach the orifice is increased.

In some embodiments, the baffle elements may be an insert of a substantially non-porous material, for example a closed-cell polyethylene foam, placed inside the dressing. In some cases, it may be preferable to place such an inserted baffle element in a sealing region where one or more of the absorbent layer **110** and/or transmission layer **105** are absent. A sealant, for example a viscous curing sealant such as a silicone sealant, could be placed or injected as a thin strip so as to form a baffle element that is substantially liquid impermeable. Such a baffle element could be placed or injected into a region of the transmission layer **105** and/or absorbent layer **110**, or also a sealing region where the absorbent layer **110** and/or transmission layer **105** are absent.

FIG. **6** illustrates a wound dressing including a baffle element according to a further embodiment of the invention. A single baffle element **610** provides a cup shaped barrier between the bulk of the absorbent layer **110** and the orifice **145**. Thus wound exudate that is initially drawn from the wound site within the region defined by the baffle element **610**, must follow a path around the outside of the cup shaped barrier to reach the orifice **145**. As will be recognized, the baffle element **610** reduces the effect of gravity on reducing the time taken for the wound exudate to move to the orifice **145**, as for most orientations of the wound dressing at least a part of the path taken by the wound exudate will be against the force of gravity.

The embodiments of FIGS. **3** and **6** have been described with respect to a wound dressing having a structure as shown in FIG. **1**. However, it will be understood that the baffle elements could equally be applied to a wound dressing in which the transmission layer **105** was absent.

FIG. **4** shows a plan view of a wound dressing including the at least one element according to one embodiment of the

invention in which a number of baffle elements **410** are provided that extend across the width of the central region **201** of the wound dressing, with further baffle elements **412** formed in a semi-circular path around the orifice **145**.

FIG. **5** illustrates the configuration of baffle elements **410** according to some embodiments of the invention. The baffle element comprises a channel of absorbent material **510** underlying the transmission layer **105**. A channel in the absorbent layer **110** is located over the baffle element **410** so that the transmission layer is in contact with the cover layer **140** in the region of the baffle element **410**. Thus, wound exudate that is moving along a lower surface of the transmission layer **105**, and has therefore not been drawn into absorbent layer **110**, will come into contact with and be absorbed by the channel of absorbent material **510**.

Alternatively, or additionally, baffle elements may comprise one or more channels provided in the surface of the transmission layer **105** underlying and abutting the absorbent layer **110**. In use, when negative pressure is applied to the wound dressing, the absorbent layer **110** will be drawn into the channel. The channel in the transmission layer may have a depth substantially equal to the depth of the transmission layer, or may have a depth less than the depth of the transmission layer. The dimensions of the channel may be chosen to ensure that the channel is filled by the absorbent layer **110** when negative pressure is applied to the wound dressing. According to some embodiments, the channel in the transmission layer comprises a channel of absorbent material in the transmission layer **105**.

The baffle elements may be formed into a range of shapes and patterns, for example FIGS. **14A** to **14L** illustrate wound dressings having a number of different exemplifying configurations of baffle elements. FIG. **14A** illustrates a linear baffle element in a vertical configuration aligned in the direction of the port or orifice. FIG. **14B** illustrates an X-shaped baffle element. FIGS. **14C-E** illustrate embodiments of wound dressings with multiple baffle elements, aligned in a generally diagonal, horizontal, or vertical manner.

FIG. **14F** illustrates baffle elements arranged in a six-armed starburst configuration, with a center portion left open. FIG. **14G** illustrates a W-shaped baffle element on the wound dressing in a position distal to the port or orifice. In FIG. **14H**, an 3-by-3 array of X-shaped baffle elements is provided on the wound dressing, although it will be understood that more or less X-shaped baffle elements may be used. FIG. **14I** shows an embodiment with a plurality of rectangular baffle elements, and wherein one or more baffle elements are located underneath the port in the wound dressing. FIGS. **14J-K** illustrate wound dressing embodiments with longer diagonal and horizontal baffle elements. In FIG. **14L**, rectangular baffle elements are present on this embodiment of a wound dressing, wherein the baffle elements are of different sizes.

According to some embodiments of the invention, the at least one element comprises an array of vias, or troughs, in the transmission layer **105**. FIG. **15** illustrates a transmission layer **105** that is perforated with diamond shaped vias **210**. The vias **210** are arranged such that no linear pathway exists through the pattern of vias that does not intersect with one or more of the vias **210**.

When negative pressure is applied to the wound dressing, the absorbent layer **110** is drawn into the vias **210**, increasing the area of the absorbent layer that comes into contact with wound exudate being drawn through the transmission layer **105**. Alternatively, the vias **210** may be filled with further absorbent material for absorbing wound exudate being

21

drawn through the transmission layer **105**. The vias may extend through the depth of the transmission layer **105**, or may extend through only part of the transmission layer.

Wound exudate moving through the transmission layer **105** under the influence of gravity will fall through the transmission layer in a substantially linear manner. Any such linear pathways will, at some point, intersect with one of the vias **210**, and thus the exudate will be brought into contact with absorbent material within the vias **210**. Wound exudate coming into contact with absorbent material will be absorbed, stopping the flow of the wound exudate through the transmission layer **105**, and reducing the amount of unabsorbed wound exudate that may otherwise pool around the orifice. It will be appreciated that the vias are not limited to diamond shapes, and that any pattern of vias may be used. Preferably, the vias will be arranged to ensure that all linear paths through the transmission layer **105** intersect with at least one via. The pattern of vias may be chosen to minimize the distance that wound exudate is able to travel through the transmission layer before encountering a via and being absorbed.

FIG. 7 illustrates a wound dressing in accordance with some embodiments of the invention in which the at least one element comprises an air channel **710** connecting the central region **201** of the wound dressing to the orifice **145**. In the embodiment of FIG. 7, the air channel **710** extends from an edge region of the transmission layer **105** and connects the transmission layer to the orifice **145**.

In use, wound exudate is drawn towards the orifice **145** by the application of negative pressure at the suction port **150**. However, the air channel **710** presents a relatively long serpentine path to be followed by the wound exudate before it reaches the orifice **145**. This long path increases the time that negative pressure can be applied to the dressing before wound exudate traverses the distance between the transmission layer and the orifice and blocks the filter element **130**, thereby increasing the time the dressing can be in use before it must be replaced.

FIG. 8 illustrates a wound dressing in accordance with one embodiment of the invention in which the at least one element comprises air channels **810** and **812** connecting the central region **201** of the wound dressing to the orifice **145**. Channels **810** and **812** are coupled to the transmission layer at substantially opposite corners of the central region **201**.

The wound dressing shown in FIG. 8 reduces the effect of gravity on the time taken for the orifice to become blocked. If the wound dressing is in an orientation in which wound exudate moves under the influence of gravity towards the edge region of the transmission layer connected to air channel **810**, the effect of gravity will be to move wound exudate away from the edge region of the transmission layer coupled to air channel **812**, and vice versa. Thus, the embodiment of FIG. 8 provides alternative air channels for coupling the negative pressure to the transmission layer such that, should one air channel become blocked a remaining air channel should remain open and able to communicate the negative pressure to the transmission layer **105**, thereby increasing the time before negative pressure can no longer be applied to the wound dressing and the dressing must be changed.

Further embodiments of the invention may comprise greater numbers of air channels connecting the transmission layer **105** to the orifice.

According to some embodiments of the invention, two or more orifices may be provided in the cover layer **140** for applying the negative pressure to the wound dressing. The two or more orifices can be distributed across the cover layer

22

140 such that if one orifice becomes blocked by wound exudate due to the wound dressing being in a particular orientation, at least one remaining orifice would be expected to remain unblocked. Each orifice is in fluid communication with a wound chamber defined by the wound dressing, and is therefore able to communicate the negative pressure to the wound site.

FIG. 9 illustrates a wound dressing in accordance with a further embodiment of the invention. The wound dressing of FIG. 9 is similar to that of FIGS. 1A-B but includes two orifices **145** and **845** provided in the cover layer **140**. A fluid communication passage connects the two orifices such that a negative pressure applied to one of the orifices is communicated to the remaining orifice via the fluid communication passage. The orifices **145**, **845** are located in opposite corner regions of the cover layer **140**. The fluid communication passage is formed using a flexible molding **910** on the upper surface of the cover layer **140**. It will be appreciated that the flexible molding may be formed from other suitable means for example a strip of transmission or open porous foam layer placed on the cover layer **140** between the orifices **145** and **845** and a further film welded or adhered over the strip thus sealing it to the cover layer and forming a passageway through the foam. A conduit may then be attached in a known manner to the sealing film for application of negative pressure.

In use, the wound dressing having two orifices is sealed over a wound site to form a wound cavity and an external source of negative pressure is applied to one of the orifices **145**, **845**, and the negative pressure will be communicated to the remaining orifice via the fluid communication passage. Thus, the negative pressure is communicated via the two orifices **145**, **845** to the transmission layer **105**, and thereby to the wound site. If one of the orifices **145**, **845** becomes blocked due to wound exudate collecting at the orifice under the influence of gravity, the remaining orifice should remain clear, allowing negative pressure to continue to be communicated to the wound site. According to some embodiments, the transmission layer **105** may be omitted, and the two orifices will communicate the negative pressure to the wound site via the absorbent layer **110**.

FIG. 10 illustrates a side view of the fluid communication passage of the embodiment of FIG. 9. Molding **910** is sealed to the top surface of the cover layer **140**, and covering orifices **145** and **845**. Gas permeable liquid impermeable filter elements **130** are provided at each orifice. The molding **910** is coupled to an external source of negative pressure via a tube element **220**.

According to some embodiments, a single filter element may be used extending underneath the length of the fluid communication passage and the two orifices. While the above example embodiment has been described as having two orifices, it will be understood that more than two orifices could be used, the fluid communication passage allowing the negative pressure to be communicated between the orifices.

FIG. 16 illustrates an alternative arrangement in which a single elongate orifice **350** is provided in the cover layer **140**. First and second ends **355**, **356** of the orifice **350** are located in opposite corner regions of the cover layer **140**. A flexible molding **360** is sealed around the orifice **350** and allows negative pressure to be communicated through the cover layer **140** along the length of the orifice **350**. The flexible molding **360** may be formed by any suitable means as described above in relation to flexible molding **910**.

In use, the wound dressing is sealed over a wound site to form a wound cavity and an external source of negative pressure is applied to the orifice. If, due to the orientation of

23

the wound dressing, wound exudate moves under the influence of gravity to collect around one end **355** of the orifice **350**, a portion of the orifice **350** near to the end **355** will become blocked. However, a portion of the orifice near to the remaining end **356** should remain clear, allowing continued application of negative pressure to the wound site.

As still further options the dressing can contain antimicrobial e.g. nanocrystalline silver agents on the wound contact layer and/or silver sulphur diazine in the absorbent layer. These may be used separately or together. These respectively kill micro-organisms in the wound and micro-organisms in the absorption matrix. As a still further option other active components, for example, pain suppressants, such as ibuprofen, may be included. Also agents which enhance cell activity, such as growth factors or that inhibit enzymes, such as matrix metalloproteinase inhibitors, such as tissue inhibitors of metalloproteinase (TIMPS) or zinc chelators could be utilized. As a still further option odor trapping elements such as activated carbon, cyclodextrine, zeolite or the like may be included in the absorbent layer or as a still further layer above the filter layer.

FIG. 17 illustrates a first, upper surface **1700** and a further, lower surface **1702** of a transmission layer **105** according to an embodiment of the present invention. In the embodiment illustrated in FIG. 17 fibers **1703** of a woven layer extend between the first surface **1700** and the further surface **1702**. It will be appreciated that according to further embodiments of the present invention if a foam layer is used as a transmission layer **105** the connected strands forming the foam will act as spacer elements. As illustrated in FIG. 17 in a relaxed mode of operation, that is to say when in use, no negative pressure is applied to the wound dressing or negative pressure is applied to the wound dressing but no external force acts on the wound dressing then the fibers **1703** extend substantially perpendicular to the upper and lower surfaces keeping the surfaces in a spaced apart substantially parallel configuration.

FIG. 18 illustrates the transmission layer **105** when an external force is exerted on the outside of the dressing. The external force can be a compressive force indicated by arrow **A** and/or a lateral force illustrated by arrow **B** in FIG. 18. As indicated either a compressive force or a lateral force acts to cause the fibers **1703** to lean to one side. This causes the upper and lower surfaces to become laterally offset with respect to each other as well as causing the thickness of the layer to reduce from a separation distance **r** indicated in FIG. 17 in a relaxed mode of operation to a compression distance **c** illustrated in FIG. 18. The reduction in thickness effectively provides some "give" in the dressing even when the dressing is subject to negative pressure. It will be appreciated that the forces acting on the dressing may occur throughout the whole of the surface area of the dressing or only in one or more particular regions. In such a situation regions of the dressing can be in a relaxed mode of operation and further regions can be in a compressed mode of operation. As illustrated in FIG. 18 when a force is exerted on the transmission layer the fibers separating the upper and lower surfaces tend to lean to one side sharing a common lean angle.

Throughout this specification reference will be made to a relaxed mode of operation and a forced mode of operation. It is to be understood that the relaxed mode of operation corresponds to a natural state of the material either when no negative pressure is applied or when negative pressure is applied. In either situation no external force, caused for example by motion of a patient or an impact is in evidence. By contrast a forced mode of operation occurs when an

24

external force whether compressive, lateral or other is brought to bear upon the wound dressing. Such forces can cause serious damage/prevent healing or a wound.

FIG. 19 illustrates how certain embodiments of the present invention can also operate to offset load forces. As illustrated in FIG. 19 if a force is exerted over a contact area **1900** in an upper surface **1700** of the transmission layer **105** then this force is transmitted across and through the transmission layer and is exerted over a larger dissipation area **1901** against an underlying wound site. In the case of use of a 3D knit as a transmission layer this is because the relatively stiff spacer elements provide at least some lateral stiffness to the layer.

FIG. 20 illustrates the transmission layer **105** and absorbent layer **110** of some embodiments in more detail. The absorbent layer **110** is located proximate to the upper surface **1700** of the transmission layer **105** and is unbonded thereto according to certain embodiments of the present invention. When unbonded the absorbent layer **110** is also able to move laterally with respect to the underlying transmission layer when a lateral or shear force is applied to the wound dressing. Also the absorbent layer is able to further compress when a compressive force illustrated in FIG. 21 acts on the wound dressing. As illustrated in FIG. 21 the absorbent layer **110** decreases in thickness under a compressive force from a non-compressed thickness **x** illustrated in FIG. 20 to a compressed distance **y** illustrated in FIG. 21. The compressive force also acts to offset the upper and lower surfaces of the transmission layer as described above thus enhancing the "give" of the dressing. The ability for an upper surface **2201** to translate laterally with respect to a lower surface **2202** of the absorbent layer under a lateral or shearing force exerted on the wound dressing is illustrated in more detail in FIG. 22. This lateral motion causes the thickness **x** of the absorbent layer **110** to reduce and the upper surface and lower surface of the absorbent layer to be offset with respect to each other. This effect can itself be sufficient to prevent shear forces exerted on the whole or part of the wound dressing from being transferred to an underlying wound bed. As can the corresponding effect in the transmission layer. However a combination enhances the cushioning effect. If the wound bed comprises a skin graft region the reduction of shear forces can be particularly advantageous.

It is to be noted that in use the dressing may be used "up-side down", at an angle or vertical. References to upper and lower are thus used for explanation purposes only.

FIG. 23 illustrates a cross-section of a portion of an embodiment of a dressing shown in FIGS. 1A-2. In particular, FIG. 23 illustrates a magnified view of the wound contact layer **102** which includes a lower surface **101** and multiple perforations **104** formed as through holes. An upper surface **104** of the wound contact layer abuts a first layer **300** of the transmission layer **105**. A further, upper, layer **301** of the transmission layer **105** is spaced apart from the first layer. The first and further layers of the transmission layer are kept apart in a spaced apart relationship by multiple mono-filament fiber spacers **302** which act as resilient flexible pillars separating the two layers of the transmission layer. The upper layer **301** of the transmission layer is adjacent a lower surface of the absorbent **110** which, for example, is formed as a pad of fibrous cellulose material interspaced with super-absorbent particulate matter.

FIG. 24 illustrates the lower layer of the 3D fabric transmission layer in more detail. The 3D fabric layer **105** is formed as a lower and upper knitted layer given a loft by the knitted structure. Rows of the knitted stitches may be referred to as a course of stitches. Columns of stitches may

25

be referred to as a whale. A single monofilament fiber is knitted into the 3D fabric to form the multiple separating strands.

As illustrated in FIG. 24 there are apertures or openings formed between interlocked stitches in the lower layer of the transmission layer 105. In use, wound exudate including liquid and semi-solid e.g. viscous slurry, suspensions of biological debris or the like and solid material will pass upwards through the perforations 104 in the wound contact layer and through the openings in the inter knitted structure of the first layer 300 of the transmission layer. The openings between the interconnected stitches have an average open area ranging from around 250 microns to 450 microns. The particular open area in the first layer of the transmission layer will be determined by the materials and method of manufacture of the lower layer. FIG. 25 illustrates how an open area of openings in the further layer above the first layer (that is to say further away from the wound) can include openings which have a greater open area than the openings in the lower layer. In this way as wound exudate which includes semi-solid and solid matter moves from the wound bed at the wound site upwards into the wound dressing any particulate matter which is of a size small enough to pass through the relative small openings 400 in the lower layer will certainly be able to pass through the larger area openings 501 in the upper area. This helps avoid debris in the form of solid material collecting in the interstitial region between the monofilament fibers between the upper and lower layer. As shown in FIG. 25, the upper layer 301 may include openings 500 similar to the openings 400 in the lower layer 300. However, during the knitting process the upper surface is knitted so that larger open area openings 501 are interspersed across the whole surface of the upper layer. As illustrated in FIG. 25 the larger open area openings 501 can have an open range considerably larger (shown between 700 to 800 microns). The lower layer 300 thus acts to some extent as a filtering layer having openings 400 which enable gas and liquid to pass freely therethrough but to prevent solid and semi-solid particulate matter which is too large from passing in to the interstitial region in the transmission layer 105. This helps keep a flowpath along the transmission layer open.

By providing openings in an upper layer in the transmission layer which have a greater open area than any openings in the lower area build-up of solid particulate matter in the interstitial region between the upper and lower layers of the transmission layer is avoided since any solid or semi-solid matter will flow along the channel and eventually be enabled to pass upwards through the larger openings where the material is taken up by the super-absorber/absorbent material.

The absorbent layer 110 holds liquid collected during the application of negative pressure therapy. By having this layer in fluid communication with, and preferably in contact with, the layer of the transmission layer, the region of the transmission layer 105 is kept at a moist environment. This helps avoid build-up and crusting of the exudate during use.

FIG. 26 illustrates an alternative material which could be utilized as the transmission layer in a wound dressing. In particular, FIG. 26 illustrates a lower surface of a 3D knit material which may be utilized as the transmission layer. Openings 600 are formed in the surface which enables wound exudate and air to pass from the wound through a wound contact layer which would be located on the surface shown in FIG. 6 and through those openings. FIG. 27

26

illustrates an upper surface of the material shown in FIG. 26 and illustrates how larger openings 700 may be formed in the upper surface.

Whilst certain embodiments of the present invention have so far been described in which the transmission layer is formed as a 3D knit layer, e.g., two layers spaced apart by a monofilament layer, it will be appreciated that certain embodiments of the present invention are not restricted to the use of such a material. In some embodiments, as an alternative to such a 3D knit material one or more layers of a wide variety of materials could be utilized. In each case, according to embodiments of the present invention, the openings presented by layers of the transmission layer are wider and wider as one moves away from the side of the dressing which, in use will be located proximate to the wound. In some embodiments, the transmission layer may be provided by multiple layers of open celled foam. In some embodiments, the foam is reticulated open cell foam. Preferably, the foam is hydrophilic or able to wick aqueous based fluids. The pore size in each layer is selected so that in the foam layer most proximate to the wound side in use the pores have a smallest size. If only one further foam layer is utilized that includes pore sizes which are greater than the pore sizes of the first layer. This helps avoid solid particulate being trapped in the lower layer which thus helps maintain the lower layer in an open configuration in which it is thus able to transmit air throughout the dressing. In certain embodiments, two, three, four or more foam layers may be included. The foam layers may be integrally formed, for example, by selecting a foam having a large pore size and then repeatedly dipping this to a lesser and lesser extent into material which will clog the pores or alternatively, the transmission layer formed by the multiple foam layers may be provided by laminating different types of foam in a layered arrangement or by securing such layers of foam in place in a known manner.

According to certain embodiments of the present invention, the transmission layer is formed by multiple layers of mesh instead of foam or 3D knit materials. For example, fine gauze mesh may be utilized for a wound facing side of the transmission layer and a Hessian mesh having a larger pore size may be located on a distal side of the gauze mesh facing away from the wound in use. The one, two, three or more layers of mesh can be secured together in an appropriate manner, such as being stitched or adhered together or the like. The resultant mat of fibers provides a transmittal layer through which air can be transmitted in the dressing but by selecting the opening sizes in the meshes as one moves through the dressing away from the wound contact side, the accumulation of solid particulate matter in lower layers can be avoided.

FIG. 28 illustrates an embodiment of a TNP wound treatment comprising a wound dressing 100 in combination with a pump 800. Here, the dressing 100 may be placed over a wound as described previously, and a conduit 220 may then be connected to the port 150, although in some embodiments the dressing 100 may be provided with at least a portion of the conduit 220 preattached to the port 150. Preferably, the dressing 100 is provided as a single article with all wound dressing elements (including the port 150) pre-attached and integrated into a single unit. The wound dressing 100 may then be connected, via the conduit 220, to a source of negative pressure such as the pump 800. Preferably, the pump 800 is miniaturized and portable, although larger conventional pumps may also be used with the dressing 100. In some embodiments, the pump 800 may be attached or mounted onto or adjacent the dressing 100. A

27

connector **221** may also be provided so as to permit the conduit **220** leading to the wound dressing **100** to be disconnected from the pump, which may be useful for example during dressing changes.

FIGS. **29A-D** illustrate the use of an embodiment of a TNP wound treatment system being used to treat a wound site on a patient. FIG. **29A** shows a wound site **190** being cleaned and prepared for treatment. Here, the healthy skin surrounding the wound site **190** is preferably cleaned and excess hair removed or shaved. The wound site **190** may also be irrigated with sterile saline solution if necessary. Optionally, a skin protectant may be applied to the skin surrounding the wound site **190**. If necessary, a wound packing material, such as foam or gauze, may be placed in the wound site **190**. This may be preferable if the wound site **190** is a deeper wound.

After the skin surrounding the wound site **190** is dry, and with reference now to FIG. **29B**, the wound dressing **100** may be positioned and placed over the wound site **190**. Preferably, the wound dressing **100** is placed with the wound contact layer **102** over and/or in contact with the wound site **190**. In some embodiments, an adhesive layer is provided on the lower surface **101** of the wound contact layer **102**, which may in some cases be protected by an optional release layer to be removed prior to placement of the wound dressing **100** over the wound site **190**. Preferably, the dressing **100** is positioned such that the port **150** is in a raised position with respect to the remainder of the dressing **100** so as to avoid fluid pooling around the port. In some embodiments, the dressing **100** is positioned so that the port **150** is not directly overlying the wound, and is level with or at a higher point than the wound. To help ensure adequate sealing for TNP, the edges of the dressing **100** are preferably smoothed over to avoid creases or folds.

With reference now to FIG. **29C**, the dressing **100** is connected to the pump **800**. The pump **800** is configured to apply negative pressure to the wound site via the dressing **100**, and typically through a conduit. In some embodiments, and as described above in FIG. **28**, a connector may be used to join the conduit from the dressing **100** to the pump **800**. Upon the application of negative pressure with the pump **800**, the dressing **100** may in some embodiments partially collapse and present a wrinkled appearance as a result of the evacuation of some or all of the air underneath the dressing **100**. In some embodiments, the pump **800** may be configured to detect if any leaks are present in the dressing **100**, such as at the interface between the dressing **100** and the skin surrounding the wound site **190**. Should a leak be found, such leak is preferably remedied prior to continuing treatment.

Turning to FIG. **29D**, additional fixation strips **195** may also be attached around the edges of the dressing **100**. Such fixation strips **195** may be advantageous in some situations so as to provide additional sealing against the skin of the patient surrounding the wound site **190**. For example, the fixation strips **195** may provide additional sealing for when a patient is more mobile. In some cases, the fixation strips **195** may be used prior to activation of the pump **800**, particularly if the dressing **100** is placed over a difficult to reach or contoured area.

Treatment of the wound site **190** preferably continues until the wound has reached a desired level of healing. In some embodiments, it may be desirable to replace the dressing **100** after a certain time period has elapsed, or if the dressing is full of wound fluids. During such changes, the pump **800** may be kept, with just the dressing **100** being changed.

28

Throughout the description and claims of this specification, the words “comprise” and “contain” and variations of the words, for example “comprising” and “comprises”, mean “including but not limited to”, and is they are not intended to (and does not) exclude other moieties, additives, components, integers or steps.

Throughout the description and claims of this specification, the singular encompasses the plural unless the context otherwise requires. In particular, where the indefinite article is used, the specification is to be understood as contemplating plurality as well as singularity, unless the context requires otherwise.

Features, integers, characteristics, compounds, chemical moieties or groups described in conjunction with a particular aspect, embodiment or example of the invention are to be understood to be applicable to any other aspect, embodiment or example described herein unless incompatible therewith. All of the features disclosed in this specification (including any accompanying claims, abstract and drawings), and/or all of the steps of any method or process so disclosed, may be combined in any combination, except combinations where at least some of such features and/or steps are mutually exclusive. The invention is not restricted to the details of any foregoing embodiments. The invention extends to any novel one, or any novel combination, of the features disclosed in this specification (including any accompanying claims, abstract and drawings), or to any novel one, or any novel combination, of the steps of any method or process so disclosed.

What is claimed is:

1. A transmission layer for use in a wound dressing, the transmission layer comprising:

a knitted or woven spacer fabric comprising a three dimensional structure, the knitted or woven spacer fabric comprising a hydrophilic agent configured such that liquid enters the knitted or woven spacer fabric as soon as liquid contacts the knitted or woven spacer fabric,

wherein the three dimensional structure comprises a top spacer fabric layer and a bottom spacer fabric layer separated from the top spacer fabric layer by a plurality of perpendicular spacer elements, and

wherein the filament count in the top spacer fabric layer is greater than the filament count in the bottom spacer fabric layer.

2. The transmission layer of claim 1, further comprising a knitted layer of at least partially elastomeric material, the elastomeric material comprising polyester.

3. The transmission layer of claim 1, wherein the transmission layer is configured to allow transmission of liquid and gas away from a wound site into upper layers of a wound dressing.

4. The transmission layer of claim 1, wherein the top spacer fabric layer is spaced apart from the bottom spacer fabric layer by a relax distance in a relaxed mode of operation; and

the plurality of spacer elements extend between the top spacer fabric layer and the bottom spacer fabric layer and, in a forced mode of operation, locatable whereby the top spacer fabric layer and the bottom spacer fabric layer are spaced apart by a compression distance less than the relax distance.

5. A wound dressing for use in topical negative pressure therapy, comprising the transmission layer of claim 1.

6. The wound dressing of claim 5, further comprising a layer of absorbent material above the transmission layer.

29

7. The wound dressing of claim 6, wherein the layer of absorbent material is not bonded to the transmission layer.

8. The wound dressing of claim 6, wherein the layer of absorbent material comprises super-absorbent material.

9. The wound dressing of claim 5, further comprising:
a moisture vapour permeable drape layer over the transmission layer; and
a suction port configured to be connected to a source of negative pressure.

10. A process for preparing a transmission layer for use in a wound dressing, the process comprising:

providing a transmission layer comprising a knitted or woven spacer fabric having a three dimensional structure comprising a top fabric layer and a bottom fabric layer separated from the top fabric layer by a plurality of perpendicular spacer elements, wherein the filament count in the top fabric layer is greater than the filament count in the bottom fabric layer, and

washing the transmission layer in a hydrophilic agent such that liquid enters the knitted or woven spacer fabric as soon as liquid contacts the knitted or woven spacer fabric.

11. The process of claim 10, wherein the transmission layer comprises a knitted layer of at least partially elastomeric material comprising polyester.

12. The process of claim 10, wherein the process further comprises treating the transmission layer with a dry cleaning agent to remove manufacturing products such as mineral

30

oils, fats and/or waxes that would otherwise interfere with the hydrophilic capabilities of the transmission layer.

13. The process of claim 10, wherein the top fabric layer is spaced apart from the bottom fabric layer by a relax distance in a relaxed mode of operation; and

the plurality of spacer elements extend between the top fabric layer and the bottom fabric layer and, in a forced mode of operation, locatable whereby the top fabric layer and the bottom fabric layer are spaced apart by a compression distance less than the relax distance.

14. A transmission layer as treated by the process of claim 10.

15. A wound dressing for use in topical negative pressure therapy comprising a transmission layer treated by the process of claim 10.

16. A wound dressing comprising a transmission layer treated by the process of claim 10, further comprising a layer of absorbent material above the transmission layer.

17. The wound dressing of claim 16, wherein the layer of absorbent material is disposed proximate to transmission layer and unbonded thereto.

18. The wound dressing of claim 16, wherein the layer of absorbent material comprises super-absorbent material.

19. The wound dressing of claim 16, further comprising a moisture vapor permeable drape layer over the transmission layer, and a suction port connectable to a source of negative pressure.

* * * * *