

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416261
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Miller; Brandon Wayne et al.

Gas turbine engine

Abstract

A gas turbine engine including: a fan assembly comprising a fan; and a turbomachine drivingly coupled to the fan and including a compressor section, a combustion section, and a turbine section arranged in serial flow order and defining in part a working gas flowpath, the gas turbine engine defining a bypass passage over the turbomachine; the turbomachine further including a heat exchanger and defining an annular cooling passage extending between an inlet and an outlet, the inlet in airflow communication with the working gas flowpath at a location upstream of the compressor section and the outlet in airflow communication with the bypass passage, the heat exchanger in thermal communication with an airflow through the cooling passage.

Inventors: Miller; Brandon Wayne (Liberty Township, OH), Hudecki; Andrew (Milford, OH), Johnson; Steven Douglas (Milford, OH), Barre; Eric (Cincinnati, OH), Glessner; John Carl (Kings Mills, OH), Souza Chavez; Efren (Queretaro, MX)

Applicant: General Electric Company (Schenectady, NY)

Family ID: 1000008818369

Assignee: General Electric Company (Evendale, OH)

Appl. No.: 18/071722

Filed: November 30, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240110515 A1	Apr. 04, 2024

Related U.S. Application Data

us-provisional-application US 63411180 20220929

Publication Classification

Int. Cl.: F02C7/18 (20060101); F01D25/12 (20060101); F02C6/08 (20060101)

U.S. Cl.:

CPC F02C6/08 (20130101); F01D25/12 (20130101); F02C7/18 (20130101); F05D2220/323 (20130101); F05D2260/232 (20130101)

Field of Classification Search

CPC: F02C (6/08); F01D (25/12)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3638428	12/1971	Shipley et al.	N/A	N/A
4698964	12/1986	Glancy	N/A	N/A
5269135	12/1992	Vermejan et al.	N/A	N/A
5279109	12/1993	Liu et al.	N/A	N/A
7966831	12/2010	Kraft et al.	N/A	N/A
9127598	12/2014	Snook et al.	N/A	N/A
9623354	12/2016	Kumar et al.	N/A	N/A
9982598	12/2017	Pritchard, Jr. et al.	N/A	N/A
10107200	12/2017	Miller et al.	N/A	N/A
10208676	12/2018	Johnson et al.	N/A	N/A
10287992	12/2018	Tan et al.	N/A	N/A
10494949	12/2018	Rambo	N/A	F01D 25/14
10590856	12/2019	Howarth	N/A	N/A
10794281	12/2019	Nestico et al.	N/A	N/A
10794288	12/2019	Schwarz et al.	N/A	N/A
10830179	12/2019	Hatim	N/A	N/A
10934939	12/2020	Miller et al.	N/A	N/A
12044194	12/2023	Ostdiek	N/A	F02C 3/067
2021/0108597	12/2020	Ostdiek	N/A	F02K 1/34
2021/0269168	12/2020	Shaner et al.	N/A	N/A

Primary Examiner: Wolcott; Brian P

Assistant Examiner: Hunter, Jr.; John S

Attorney, Agent or Firm: Dority & Manning, P.A.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a non-provisional application claiming the benefit of priority under 35 U.S.C. § 119(e) to U.S. Provisional

FIELD

(1) The present disclosure relates to a gas turbine engine.

BACKGROUND

(2) A gas turbine engine generally includes a turbomachine and a rotor assembly. Gas turbine engines, such as turbofan engines, may be used for aircraft propulsion. In the case of a turbofan engine, the rotor assembly may be configured as a fan assembly, and the fan assembly may be enclosed by an outer nacelle. The outer nacelle may define a bypass passage with the turbomachine.

(3) Generally, improvements to a turbofan engine in the fields of thermal management and aerodynamics would be welcomed in the art.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) A full and enabling disclosure of the present disclosure, including the best mode thereof, directed to one of ordinary skill in the art, is set forth in the specification, which makes reference to the appended figures, in which:

(2) FIG. 1 is a cross-sectional view of a gas turbine engine in accordance with an exemplary aspect of the present disclosure.

(3) FIG. 2 is a schematic view of a portion of a turbomachine in accordance with an exemplary embodiment of the present disclosure.

(4) FIG. 3 is a schematic, cross-sectional view of a cooling passage of the turbomachine of FIG. 2 in accordance with an exemplary embodiment of the present disclosure.

(5) FIG. 4 is a schematic view of a portion of a turbomachine in accordance with another exemplary embodiment of the present disclosure.

(6) FIG. 5 is a schematic view of a hood of the exemplary turbomachine of FIG. 4.

(7) FIG. 6 is a schematic view of a hood of a turbomachine in accordance with an exemplary embodiment of the present disclosure.

(8) FIG. 7 is a schematic view of a portion of a turbomachine in accordance with another exemplary embodiment of the present disclosure.

(9) FIG. 8 is a schematic view of an ejector in accordance with another exemplary embodiment of the present disclosure.

(10) FIG. 9 is a schematic, cross-sectional view of a cooling passage and variable bleed assembly in accordance with an exemplary embodiment of the present disclosure.

(11) FIG. 10 is a flow diagram of a method of operating a gas turbine engine in accordance with an exemplary aspect of the present disclosure.

(12) FIG. 11 is a cross-sectional view of a gas turbine engine in accordance with another exemplary aspect of the present disclosure.

(13) FIG. 12 is a schematic view of a portion of a turbomachine in accordance with another exemplary embodiment of the present disclosure.

(14) FIG. 13 is an isometric, cross-sectional view of a variable bleed assembly in accordance with an exemplary embodiment of the present disclosure.

(15) FIG. 14 is a schematic view of a hinged cowl assembly.

(16) FIG. 15 is a schematic view of a portion of a turbomachine in accordance with another exemplary embodiment of the present disclosure.

DETAILED DESCRIPTION

(17) Reference will now be made in detail to present embodiments of the disclosure, one or more

examples of which are illustrated in the accompanying drawings. The detailed description uses numerical and letter designations to refer to features in the drawings. Like or similar designations in the drawings and description have been used to refer to like or similar parts of the disclosure.

(18) The word “exemplary” is used herein to mean “serving as an example, instance, or illustration.” Any implementation described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other implementations. Additionally, unless specifically identified otherwise, all embodiments described herein should be considered exemplary.

(19) The singular forms “a”, “an”, and “the” include plural references unless the context clearly dictates otherwise.

(20) The term “at least one of” in the context of, e.g., “at least one of A, B, and C” refers to only A, only B, only C, or any combination of A, B, and C.

(21) The term “turbomachine” refers to a machine including one or more compressors, a heat generating section (e.g., a combustion section), and one or more turbines that together generate a torque output.

(22) The term “gas turbine engine” refers to an engine having a turbomachine as all or a portion of its power source. Example gas turbine engines include turbofan engines, turboprop engines, turbojet engines, turboshaft engines, etc., as well as hybrid-electric versions of one or more of these engines.

(23) The term “combustion section” refers to any heat addition system for a turbomachine. For example, the term combustion section may refer to a section including one or more of a deflagrative combustion assembly, a rotating detonation combustion assembly, a pulse detonation combustion assembly, or other appropriate heat addition assembly. In certain example embodiments, the combustion section may include an annular combustor, a can combustor, a cannular combustor, a trapped vortex combustor (TVC), or other appropriate combustion system, or combinations thereof.

(24) The terms “low” and “high”, or their respective comparative degrees (e.g., -er, where applicable), when used with a compressor, a turbine, a shaft, or spool components, etc. each refer to relative speeds within an engine unless otherwise specified. For example, a “low turbine” or “low speed turbine” defines a component configured to operate at a rotational speed, such as a maximum allowable rotational speed, lower than a “high turbine” or “high speed turbine” of the engine.

(25) The terms “forward” and “aft” refer to relative positions within a gas turbine engine or vehicle, and refer to the normal operational attitude of the gas turbine engine or vehicle. For example, with regard to a gas turbine engine, forward refers to a position closer to an engine inlet and aft refers to a position closer to an engine nozzle or exhaust.

(26) The terms “upstream” and “downstream” refer to the relative direction with respect to fluid flow in a fluid pathway. For example, “upstream” refers to the direction from which the fluid flows, and “downstream” refers to the direction to which the fluid flows.

(27) As used herein, the terms “first”, “second”, and “third” may be used interchangeably to distinguish one component from another and are not intended to signify location or importance of the individual components.

(28) The present disclosure is generally related to a gas turbine engine, such as a turbofan engine.

(29) As design criteria for turbofan engines drives operating conditions to higher pressures and temperatures, it has been recognized that increased cooling capacity would be welcomed in the art. Certain gas turbine engines bleed air from, e.g., a high pressure compressor, and use the bleed air to cool various accessory systems of the turbofan engine. However, such a configuration may result in inefficiencies as the air bled from the high pressure compressor undergoes a relatively high amount of work, and further is generally at an elevated temperature.

(30) Accordingly, in one exemplary aspect, a gas turbine engine is provided having a turbomachine that defines a cooling passage extending between an inlet and an outlet, the inlet in airflow

communication with a working gas flowpath of the turbomachine at a location upstream of a compressor section and the outlet in airflow communication with a bypass passage. A heat exchanger is provided in thermal communication with an airflow through the cooling passage. The heat exchanger may be utilized to cool one or more accessory systems of the gas turbine engine.

(31) In such an exemplary aspect, the airflow provided to the heat exchanger may be relatively cool and may be provided from a location upstream of a significant amount of compression (which would result in lost work).

(32) In another exemplary aspect of the present disclosure, a means is provided for urging an airflow through a cooling passage, such as the cooling passage discussed above. In particular, with one exemplary aspect of the present disclosure, a turbomachine of a gas turbine engine is provided, having a variable bleed assembly with a variable bleed duct extending between a variable bleed (VB) inlet and a VB outlet. The VB inlet is in airflow communication with the working gas flowpath at a location downstream of a cooling passage inlet of a cooling passage, and the VB outlet in airflow communication with the cooling passage for urging an airflow through the annular cooling passage.

(33) In such a manner, a small amount of high pressure airflow may be utilized to urge a low pressure airflow through the cooling passage. Such may allow for the low pressure airflow to be used for cooling various components of the turbomachine, which may result in an overall more efficient cooling system and gas turbine engine.

(34) Further, in certain exemplary aspects, an amount of the airflow from the variable bleed assembly may be controlled based on a condition of the engine, such that the cooling passage may have a variable cooling capacity based on a cooling need of the turbomachine.

(35) Moreover, it will be appreciated that in still other exemplary aspects, a gas turbine engine having a turbomachine and a fan assembly, with the turbomachine driving the fan assembly across a reduction gearbox. Inclusion of the reduction gearbox may allow for the driving turbine to operate at higher speeds while maintaining a low fan pressure ratio, allowing for an overall length of the turbomachine to be reduced. In certain exemplary embodiments, the gas turbine engine may further include a thrust reverser assembly and a variable bleed assembly. The variable bleed assembly typically pulls an airflow from a working gas flowpath of the turbomachine between an LP compressor and an HP compressor, and extracts the airflow radially outward through a compressor mid-frame. The thrust reverser assembly may include an inner thrust reverser support member attached to an aft portion of the compressor mid-frame to allow the variable bleed assembly to exhaust in such a manner (and without risking a high pressure airflow getting beneath the inner thrust reverser support member and pushing it outward along a radial direction.

(36) However, with such a configuration, the inner thrust reverser support member may limit how short the turbomachine may be to allow for a desired aerodynamic line. Accordingly, in one aspect of the present disclosure, the inner thrust reverser support member may be moved forward to attach to a forward end of the compressor mid-frame, allowing the turbomachine to be shortened without compromising the aerodynamic lines. Various features may be provided to accommodate integration of the inner thrust reverser support member with the variable bleed assembly to avoid the issues noted above.

(37) In certain exemplary aspects the embodiments discussed above may be provided as stand-alone embodiments, or may be combined in any suitable manner. For example, the integration of the inner thrust reverser support member with the variable bleed assembly may be a stand-alone embodiment, or it may be integrated with the cooling passage discussed above to provide even further benefits as will be described below.

(38) Referring now to the drawings, wherein identical numerals indicate the same elements throughout the figures, FIG. 1 is a schematic cross-sectional view of a gas turbine engine 10 in accordance with an exemplary embodiment of the present disclosure. More particularly, for the embodiment of FIG. 1, the gas turbine engine 10 is a high-bypass turbofan jet engine, sometimes

also referred to as a “turbofan engine.” As shown in FIG. 1, the gas turbine engine **10** defines an axial direction A (extending parallel to a longitudinal centerline **12** provided for reference), a radial direction R, and a circumferential direction C extending about the longitudinal centerline **12**. In general, the gas turbine engine **10** includes a fan section **14** and a turbomachine **16** disposed downstream from the fan section **14**, the turbomachine **16** drivingly coupled to a fan **38** of the fan section **14**.

(39) The exemplary turbomachine **16** depicted generally includes a substantially tubular outer casing **18** that defines an annular turbomachine inlet **20**. The outer casing **18** encases, in serial flow relationship, a compressor section including a booster or low pressure (LP) compressor **22** and a high pressure (HP) compressor **24**; a combustion section **26**; a turbine section including a high pressure (HP) turbine **28** and a low pressure (LP) turbine **30**; and a jet exhaust nozzle section **32**. A high pressure (HP) shaft **34** (which may additionally or alternatively be a spool) drivingly connects the HP turbine **28** to the HP compressor **24**. A low pressure (LP) shaft **36** (which may additionally or alternatively be a spool) drivingly connects the LP turbine **30** to the LP compressor **22**. The compressor section, combustion section **26**, turbine section, and jet exhaust nozzle section **32** together define a working gas flowpath **37**. In such a manner, it will be appreciated that the turbomachine inlet **20** is an inlet to the working gas flowpath **37**.

(40) In the embodiment shown, the turbomachine inlet **20** is positioned immediately downstream of the fan **38** (i.e., no intervening structure, such as blades, vanes, or struts, therebetween). Further, it will be appreciated that for the embodiment depicted, the LP compressor **22** is located downstream of the fan **38**, and there are no intermediate stages of compression between the fan **38** and the LP compressor **22**.

(41) For the embodiment depicted, the fan section **14** includes a fan **38** having a plurality of fan blades **40** coupled to a disk **42** in a spaced apart manner. As depicted, the fan **38** is a single stage fan and the fan blades **40** extend outwardly from disk **42** generally along the radial direction R. Each fan blade **40** is rotatable relative to the disk **42** about a pitch axis P by virtue of the fan blades **40** being operatively coupled to a suitable pitch change mechanism **44** configured to collectively vary the pitch of the fan blades **40**, e.g., in unison. The gas turbine engine **10** further includes a reduction gearbox **46**, and the fan blades **40**, disk **42**, and pitch change mechanism **44** are together rotatable about the longitudinal centerline **12** by LP shaft **36** across the reduction gearbox **46**. The reduction gearbox **46** includes a plurality of gears for adjusting a rotational speed of the fan **38** relative to a rotational speed of the LP shaft **36**, such that the fan **38** may rotate at a more efficient fan speed.

(42) Referring still to the exemplary embodiment of FIG. 1, the disk **42** is covered by a rotatable front hub **48** of the fan section **14** (sometimes also referred to as a “spinner”). The front hub **48** is aerodynamically contoured to promote an airflow through the plurality of fan blades **40**.

(43) Additionally, the exemplary fan section **14** includes an annular fan casing or outer nacelle **50** that circumferentially surrounds the fan **38** and/or at least a portion of the turbomachine **16**. It should be appreciated that the outer nacelle **50** is supported relative to the turbomachine **16** by a plurality of circumferentially-spaced outlet guide vanes **52** in the embodiment depicted. Moreover, a downstream section **54** of the outer nacelle **50** extends over an outer portion of the turbomachine **16** so as to define a bypass passage **56** therebetween. The bypass passage **56** is defined at least partially over the turbomachine **16**.

(44) During operation of the gas turbine engine **10**, a volume of air **58** enters the gas turbine engine **10** through an associated inlet **60** of the outer nacelle **50** and fan section **14**. As the volume of air **58** passes across the fan blades **40**, a first portion of air **62** is directed or routed into the bypass passage **56** and a second portion of air **64** as indicated by arrow **64** is directed or routed into the working gas flowpath **37**, or more specifically into the LP compressor **22**. The ratio between the first portion of air **62** and the second portion of air **64** is commonly known as a bypass ratio. A pressure of the second portion of air **64** is then increased as it is routed through the HP compressor **24** and into the

combustion section **26**, where it is mixed with fuel and burned to provide combustion gases **66**.

(45) The combustion gases **66** are routed through the HP turbine **28** where a portion of thermal and/or kinetic energy from the combustion gases **66** is extracted via sequential stages of HP turbine stator vanes **68** that are coupled to the outer casing **18** and HP turbine rotor blades **70** that are coupled to the HP shaft **34**, thus causing the HP shaft **34** to rotate, thereby supporting operation of the HP compressor **24**. The combustion gases **66** are then routed through the LP turbine **30** where a second portion of thermal and kinetic energy is extracted from the combustion gases **66** via sequential stages of LP turbine stator vanes **72** that are coupled to the outer casing **18** and LP turbine rotor blades **74** that are coupled to the LP shaft **36**, thus causing the LP shaft **36** to rotate, thereby supporting operation of the LP compressor **22** and/or rotation of the fan **38**.

(46) The combustion gases **66** are subsequently routed through the jet exhaust nozzle section **32** of the turbomachine **16** to provide propulsive thrust. Simultaneously, the pressure of the first portion of air **62** is substantially increased as the first portion of air **62** is routed through the bypass passage **56** before it is exhausted from a fan nozzle exhaust section **76** of the gas turbine engine **10**, also providing propulsive thrust. The HP turbine **28**, the LP turbine **30**, and the jet exhaust nozzle section **32** at least partially define a hot gas path **78** for routing the combustion gases **66** through the turbomachine **16**.

(47) It should be appreciated, however, that the exemplary gas turbine engine **10** depicted in FIG. **1** is by way of example only, and that in other exemplary embodiments, the gas turbine engine **10** may have any other suitable configuration. For example, although the gas turbine engine **10** depicted is configured as a ducted gas turbine engine (i.e., including the outer nacelle **50**), in other embodiments, the gas turbine engine **10** may be an unducted gas turbine engine (such that the fan **38** is an unducted fan, and the outlet guide vanes **52** are cantilevered from the outer casing **18**). Additionally, or alternatively, although the gas turbine engine **10** depicted is configured as a geared gas turbine engine (i.e., including the reduction gearbox **46**) and a variable pitch gas turbine engine (i.e., including a fan **38** configured as a variable pitch fan), in other embodiments, the gas turbine engine **10** may additionally or alternatively be configured as a direct drive gas turbine engine (such that the LP shaft **36** rotates at the same speed as the fan **38**), as a fixed pitch gas turbine engine (such that the fan **38** includes fan blades **40** that are not rotatable about a pitch axis **P**), or both. It should also be appreciated, that in still other exemplary embodiments, aspects of the present disclosure may be incorporated into any other suitable gas turbine engine. For example, in other exemplary embodiments, aspects of the present disclosure may (as appropriate) be incorporated into, e.g., a turboprop gas turbine engine, a turboshaft gas turbine engine, or a turbojet gas turbine engine.

(48) Referring now to FIG. **2**, a close-up, schematic view is depicted of a portion of the exemplary gas turbine engine **10** of FIG. **1**. In particular, the view of FIG. **2** is a close-up of the turbomachine **16** of FIG. **1**, depicting the turbomachine inlet **20**, the compressor section including the LP compressor **22** and the HP compressor **24**, the LP shaft **36**, and the reduction gearbox **46**. Further, the outer casing **18** of the turbomachine **16** is depicted extending around at least a portion of the compressor section, with the bypass passage **56** defined in part thereby.

(49) As will be appreciated from the view of FIG. **2**, the turbomachine **16** further includes a compressor forward frame **100** and a compressor mid-frame **102**. The compressor forward frame **100** includes a strut **104** extending through the working gas flowpath **37** at a location upstream of the LP compressor **22** and downstream of the turbomachine inlet **20**. Similarly, the compressor mid-frame **102** includes a strut **106** extending through the working gas flowpath **37** at a location downstream of the LP compressor **22** and upstream of the HP compressor **24**. The compressor forward frame **100** and the compressor mid-frame **102** may provide structural support to various components of the gas turbine engine **10**.

(50) As will be appreciated, the exemplary gas turbine engine **10** depicted includes one or more accessory systems **108** for facilitating operations of the gas turbine engine **10**. The one or more

accessory systems **108** may include one or more of an oil lubrication system, a fuel delivery system, a cooled cooling air (CCA) system, an engine controller cooling system, etc. A single accessory system **108** is depicted schematically in FIG. 2 by way of example.

(51) Moreover, in order to assist with cooling the one or more accessory systems **108**, such as the accessory system **108** depicted, the turbomachine **16** further defines an annular cooling passage **110** extending between a cooling passage (CP) inlet **112** and a CP outlet **114**.

(52) The CP inlet **112** is in airflow communication with the working gas flowpath **37** at a location upstream of the compressor section of the turbomachine **16**. More specifically, for the embodiment depicted, the CP inlet **112** is in airflow communication with the working gas flowpath **37** at a location upstream of the LP compressor **22** and downstream of the turbomachine inlet **20**. More specifically, still, for the embodiment shown, the CP inlet **112** is aligned with the compressor forward frame **100** along the axial direction A of the gas turbine engine **10**. In such a manner, the CP inlet **112** is configured to receive an airflow from the working gas flowpath **37** that is been compressed by the fan **38** of the fan section **14** (see FIG. 1). For example, a pressure of an airflow received through the CP inlet **112** and provided to the cooling passage **110** may be substantially equal (e.g., within 10% of) to a pressure of the airflow provided through the turbomachine inlet **20**.

(53) Referring still to FIG. 2, the CP outlet **114** is in airflow communication with the bypass passage **56**. In particular, for the embodiment shown, the CP outlet **114** is in airflow communication with the bypass passage **56** at a location aft of the CP inlet **112** and forward of the compressor mid-frame **102**. In particular, for the embodiment shown, the CP outlet **114** is aligned with the compressor section along the axial direction A.

(54) Further, the turbomachine **16** includes a heat exchanger **116** that is in thermal communication with the airflow through the cooling passage **110**. In particular, the heat exchanger **116** is positioned within the cooling passage **110** or defines a portion of the cooling passage **110**. In such a manner, the heat exchanger **116** may be configured to transfer heat from a fluid to the airflow through the cooling passage **110**.

(55) In particular, for the embodiment shown the heat exchanger **116** is further in thermal communication with the accessory system **108** of the gas turbine engine **10** for transferring heat from the accessory system **108** to the airflow through the cooling passage **110**. In such a manner the cooling passage **110** may provide cooling for the accessory system **108**.

(56) It will be appreciated that for the embodiment shown, although a single heat exchanger **116** and a single accessory system **108** are depicted, in other exemplary embodiments, other suitable configurations may be provided.

(57) For example, referring now briefly to FIG. 3, a schematic, cross-sectional view of a turbomachine **16** including a cooling passage **110** in accordance with an exemplary aspect of the present disclosure is provided. The exemplary cooling passage **110** and heat exchanger **116** of FIG. 3 may be configured in a similar manner as exemplary cooling passage **110** and heat exchanger **116** described above with reference to FIG. 2.

(58) However, for the embodiment shown, the heat exchanger **116** is a first heat exchanger **116A** of a plurality of heat exchangers **116** arranged along a circumferential direction C of the gas turbine engine **10**. The plurality of heat exchangers **116** are each positioned within the cooling passage **110**.

(59) Notably, for the embodiment shown, the accessory system **108** is also a first accessory system **108A** of a plurality of accessory systems **108**. Each of the plurality of accessory systems **108** utilizes one or more of the plurality of heat exchangers **116**. For example, the first accessory system **108A** is in thermal communication with the first heat exchanger **116A**. A second accessory system **108B** of the plurality of accessory systems **108** is in thermal communication with a second heat exchanger **116B**, a third heat exchanger **116C**, and a fourth heat exchanger **116D**. Notably, the second heat exchanger **116B**, the third heat exchanger **116C**, and the fourth heat exchanger **116D** are arranged in serial flow order. Further, a third accessory system **108C** of the plurality of accessory systems **108** is in thermal communication with a fifth heat exchanger **116E** and a sixth

heat exchanger **116F**.

(60) In such a manner, it will be appreciated that an airflow through the cooling passage **110** may be utilized as a heat sink for a variety of accessory systems **108** of the gas turbine engine **10**.

(61) Moreover, it will be appreciated that in other exemplary embodiments, other suitable structures may be provided to assist with generating an airflow through the cooling passage **110** of the present disclosure.

(62) For example, referring now to FIG. 4, a close-up, schematic view of a gas turbine engine **10** in accordance with another exemplary aspect of the present disclosure is provided. The exemplary gas turbine engine **10** depicted in FIG. 4 may be configured in a similar manner as the exemplary gas turbine engine **10** described above with reference to FIGS. 1 and 2. The same or similar numbers may refer to the same or similar part.

(63) For example, the exemplary gas turbine engine **10** depicted in FIG. 4 generally includes a turbomachine **16** defining a cooling passage **110** extending between a CP inlet **112** and a CP outlet **114**. The CP inlet **112** is in airflow communication with a working gas flowpath **37** of the turbomachine **16** at a location upstream of a compressor section of the turbomachine **16**. The CP outlet **114** is in airflow communication with a bypass passage **56** of the gas turbine engine **10** defined between an outer nacelle **50** and the turbomachine **16**.

(64) Notably, as with the embodiment above, the CP inlet **112** is configured to receive an airflow compressed by a fan **38** of the gas turbine engine **10** (see FIG. 1), but is positioned upstream of any additional stages of compression. Accordingly, in order to assist with generating an airflow through the cooling passage **110**, the turbomachine **16** includes a means for urging the airflow through the cooling passage **110**.

(65) More specifically, for the embodiment depicted, the means includes an inlet scoop **118** extending into the working gas flowpath **37** at the CP inlet **112** to divert a portion of an airflow through the working gas flowpath **37** through the CP inlet **112** of the cooling passage **110**. In the embodiment depicted, the inlet scoop **118** is an annular scoop extending 360° about a longitudinal centerline **12** of the gas turbine engine **10**. Further, for the embodiment depicted, the inlet scoop **118** is a fixed structure.

(66) However, it will be appreciated that in other exemplary embodiments, the inlet scoop **118** may instead be configured in any other suitable manner (e.g., may be configured as a plurality of individual inlet scoops **118** arranged along a circumferential direction C of the gas turbine engine **10**, may be a variable scoop capable of being deployed and retracted, etc.).

(67) Further, for the embodiment depicted, the means for urging the airflow through the cooling passage **110** additionally includes a hood **120** extending over the CP outlet **114** of the cooling passage **110**. The hood **120** extends into the bypass passage **56**, such that a cross-sectional area of the bypass passage **56** at the hood **120** is less than a cross-sectional area of the bypass passage **56** immediately upstream of the hood **120**. In such a manner, the hood **120** may form a nozzle to increase a speed of an airflow through the bypass passage **56**, reducing a static pressure at the CP outlet **114** of the cooling passage **110**. As such, the hood **120** may generate a delta pressure to urge the airflow through the cooling passage **110**.

(68) Briefly, referring to FIG. 5, a partial, schematic, cross-sectional view of the hood **120** is depicted, as viewed along the axial direction A. As shown, for the embodiment depicted, the hood **120** is a relatively smooth hood **120**.

(69) Alternatively, referring briefly to FIG. 6, partial, schematic, cross-sectional view of a hood **120** in accordance with another exemplary embodiment of the present disclosure, as may be incorporated into the gas turbine engine **10** of FIG. 4 is depicted. For the embodiment of FIG. 6, the hood **120** is configured as a mixer having a plurality of lobes **121** spaced along a circumferential direction C having sequential peaks and valleys, such that a radial height of the hood **120** (and lobes **121**) defines a sinusoidal pattern along the circumferential direction C. The plurality of lobes **121** may raise the radial height of the hood **120** locally along the circumferential

direction C and therefore maximally reduce an exit static pressure at the CP outlet **114** at such local position by increasing the fan airflow Mach number at the local position over the lobe **121** of the hood **120**.

(70) Further, still, in other exemplary embodiments, the means for urging the airflow through the cooling passage **110** may be any other suitable means, such as a pump or compressor, or an ejector in airflow communication with a high-pressure air source. For example, in certain exemplary embodiments, the means may include an ejector in airflow communication with a variable bleed assembly, and further in airflow communication with the cooling passage **110** (see, e.g., FIG. **8** below). Alternatively, in other embodiments, the high pressure air source may be any other suitably high pressure air source, such as an LP compressor bleed, an HP compressor bleed, a turbine exhaust bleed, or a combination thereof. In certain embodiments, the ejector may be positioned downstream of the heat exchanger **116** (as shown in FIG. **8**). Alternatively, in other embodiments, the ejector may be positioned upstream of the heat exchanger **116** (FIGS. **2** and **4**).

(71) Referring again to FIGS. **2** and **4**, in one or more of the above exemplary embodiments, it will be appreciated that the cooling passage **110** may be configured to receive sufficient air flow therethrough to provide a desired amount of cooling to the one or accessory systems **108** of the gas turbine engine **10**. For example, in certain exemplary embodiments, it will be appreciated that during operation of the gas turbine engine **10** at a first operating condition, the cooling passage **110** may be configured to receive between 2% and 20% of the total airflow through the working gas flowpath **37** at a location upstream of the CP inlet **112** and downstream of the turbomachine inlet **20**. For example, in certain exemplary embodiments, the cooling passage **110** may be configured to receive between 4% and 12% of the total airflow through the working gas flowpath **37** at the location upstream of the CP inlet **112** and downstream of the turbomachine inlet **20**. In certain exemplary aspects, the first operating condition may be a high power operating condition (e.g., a takeoff operating condition), wherein a relatively high amount of cooling may be desirable for the gas turbine engine **10**.

(72) It will be appreciated that including a turbomachine defining a cooling passage in accordance with one or more exemplary aspects of the present disclosure may allow for a relatively cool airflow to be utilized for cooling one or accessory systems of the gas turbine engine prior to such airflow being subjected to additional stages of compression. In such a manner, the cooling passage may provide for a relatively efficient way to cool the various accessory systems, as the airflow is utilized prior to work in the form of compression having been applied thereto. Further, by transferring heat to such airflow prior to such airflow being provided to the bypass passage, additional energy may be transferred to the bypass passage, which may increase an overall propulsive efficiency of the gas turbine engine.

(73) Referring now to FIG. **7**, a close-up, schematic view of a gas turbine engine **10** in accordance with yet another exemplary aspect of the present disclosure is provided. The exemplary gas turbine engine **10** depicted in FIG. **7** may be configured in a similar manner as exemplary gas turbine engine **10** described above with reference to FIGS. **1** and **2**. The same or similar numbers may refer to the same or similar part.

(74) For example, the exemplary gas turbine engine **10** depicted in FIG. **7** generally includes a turbomachine **16** defining a cooling passage **110** extending between a CP inlet **112** and a CP outlet **114**. The CP inlet **112** is in airflow communication with a working gas flowpath **37** of the turbomachine **16** at a location upstream of a compressor section of the turbomachine **16**. The CP outlet **114** is in airflow communication with a bypass passage **56** of the gas turbine engine **10** defined between an outer nacelle **50** (not shown; see FIG. **1**) and the turbomachine **16**.

(75) Notably, as with the embodiment above, the CP inlet **112** is configured to receive an airflow compressed by a fan **38** of the gas turbine engine **10** (see FIG. **1**), but is positioned upstream of any additional stages of compression. Accordingly, in order to assist with generating an airflow through the cooling passage **110**, the turbomachine **16** includes a means for urging the airflow through the

cooling passage **110**.

(76) More specifically, for the embodiment of FIG. 7, the gas turbine engine **10** further includes a variable bleed assembly **122**. The variable bleed assembly **122** includes a variable bleed duct **124** extending between a VB inlet **126** and a VB outlet **128**.

(77) The VB inlet **126** is in airflow communication with the working gas flowpath **37** at a location downstream the CP inlet **112**. In particular, for the embodiment depicted, the CP inlet **112** is in airflow communication with the working gas flowpath **37** at a location upstream of a compressor of the compressor section, and more specifically, of an LP compressor **22** of the compressor section, and the VB inlet **126** is in airflow communication with the working gas flowpath **37** at a location downstream of the LP compressor **22**. More specifically, still, for the embodiment shown, the VB inlet **126** is in airflow communication with the working gas flowpath **37** at a location upstream of an HP compressor **24** and aligned with a compressor mid-frame **102** of the turbomachine **16** along an axial direction A of the gas turbine engine **10**.

(78) Referring still to FIG. 7, the VB outlet **128** is in airflow communication with the cooling passage **110**. More specifically, for the embodiment depicted the VB outlet **128** is in airflow communication with the cooling passage **110** at a location downstream of a heat exchanger **116** (the heat exchanger **116** being in thermal communication with an airflow through the cooling passage **110**).

(79) As will be appreciated from the exemplary embodiment depicted in FIG. 7, in the embodiment depicted, substantially all of an airflow through the variable bleed duct **124** (i.e., at least 90% of the airflow through the variable bleed duct **124**) is provided through the VB outlet **128** to the cooling passage **110**.

(80) It will be appreciated, however, that in other embodiments, it may not be necessary to provide substantially all of the airflow through the variable bleed duct **124** to the cooling passage **110** through the VB outlet **128**. In such a manner, the VB outlet **128** may be a first VB outlet, and the variable bleed duct **124** may further include a second VB outlet **128'**. The second VB outlet **128'**, as is depicted in phantom may be in direct airflow communication with the bypass passage **56** (i.e., may provide the airflow from the variable bleed duct **124** to the bypass passage **56** without merging or mixing with any other airflow upstream of the bypass passage **56**). In the embodiment depicted, the variable bleed duct **124** splits to extend to both the first VB outlet **128** and the second VB outlet **128'**.

(81) As will be appreciated, providing the airflow through the variable bleed duct **124** to the cooling passage **110** through the VB outlet **128** may urge the airflow through the cooling passage **110**. In such a manner, the variable bleed assembly **122** may be a means for urging the airflow through the cooling passage **110**.

(82) In order to modulate the amount of airflow through the cooling passage **110**, the variable bleed assembly **122** may be capable of varying an amount of airflow provided therethrough to the cooling passage **110**. In particular, for the embodiment of FIG. 7, the variable bleed assembly **122** includes a variable bleed valve **130** for varying the amount of airflow through the variable bleed duct **124**. In the embodiment depicted, the variable bleed valve **130** is located at an upstream end of the variable bleed duct **124** and includes the VB inlet **126**.

(83) More specifically, for the embodiment depicted the variable bleed assembly **122** further includes an actuator **132** coupled to the variable bleed valve **130** configured to actuate the variable bleed valve **130** about a pin **134**, to pivot the variable bleed valve **130** between a deployed position (shown) and a stowed position (not shown), and optionally various positions therebetween, as is illustrated by arrow **135**. The variable bleed valve **130** may be moved from the deployed position to the stowed position by rotating in a clockwise direction about the pin **134** in the view depicted, such that the VB inlet **126** is no longer exposed to the working gas flowpath **37**.

(84) The variable bleed valve **130** may be moved between the fully deployed position (shown) whereby the variable bleed duct **124** extracts a maximum amount of airflow from the working gas

flowpath **37**, the fully stowed position whereby the variable bleed valve **130** extracts substantially no airflow from the working gas flowpath **37** (i.e., less than 5% of the maximum amount of airflow extracted), and any suitable position therebetween (one or more partially deployed positions).

(85) The airflow from the variable bleed duct **124** may be provided to the cooling passage **110** from the VB outlet **128** in any suitable manner. For example, referring briefly to FIG. **8**, it will be appreciated that in certain exemplary embodiments, the VB outlet **128** forms at least in part an ejector **136** with the cooling passage **110**. In particular, for the embodiment of FIG. **8**, the VB outlet **128** includes a fluid nozzle **138** configured to provide a relatively high pressure fluid flow. Further, the cooling passage **110** includes a nozzle portion **140** that includes a converging inlet nozzle **142**, a diffuser throat **144**, and a diverging outlet diffuser **146** arranged in serial order, with the fluid nozzle **138** of the VB outlet **128** oriented to provide the relatively high pressure fluid into the converging inlet nozzle **142**. As will be appreciated, providing the high pressure fluid flow through the fluid nozzle **138** with the nozzle portion **140** located downstream, may urge a relatively low pressure fluid flow therethrough to increase the amount of airflow through the cooling passage **110**.

(86) Moreover, it should be appreciated from the description herein and the Figures, that the variable bleed duct **124** having the VB inlet **126** and the VB outlet **128** may be a first variable bleed duct **124** of a plurality of variable bleed ducts **124** of the variable bleed assembly **122**. For example, referring briefly to FIG. **9**, a schematic, cross-sectional view is provided showing the variable bleed assembly **122** and the cooling passage **110** described above with reference to FIG. **7**. As noted, the cooling passage **110** is an annular cooling passage. Further, the variable bleed assembly **122** includes the plurality of variable bleed ducts **124** spaced along the circumferential direction C of the gas turbine engine **10**. Each of the variable bleed ducts **124** generally extends between the respective VB inlets **126** in airflow communication with the working gas flowpath **37** (FIG. **7**) and respective VB outlets **128** in airflow communication with the cooling passage **110**. Each of the plurality of variable bleed ducts **124** depicted in FIG. **9** may be configured in a similar manner as the exemplary variable bleed duct **124** described above with reference to FIGS. **7** and **8**.

(87) Referring now back to FIG. **7**, it will be appreciated for the embodiment depicted, the gas turbine engine **10** further includes a controller **150** operably coupled to the variable bleed assembly **122**, and one or more sensors **152**. The one or more sensors **152** may be configured to sense data indicative of an operating condition of the gas turbine engine **10**. For example, the one or more sensors **152** generally includes a bypass passage sensor **152A** (e.g., configured to sense one or more of a pressure, a temperature, or an airflow rate of airflow through the bypass passage **56**), an accessory system sensor **152B** (e.g., configured to sense data indicative of a condition of the accessory system **108**), a turbomachine sensor **152C** (e.g., configured to sense data indicative of an operating condition of the turbomachine, such as a rotational speed sensor, a temperature sensor, a pressure sensor, etc.).

(88) As noted, the exemplary controller **150** depicted in FIG. **7** is configured to receive the data sensed from the one or more sensors (sensors **152A**, **152B**, **152C**) for the embodiment shown) and, e.g., may make control decisions for the variable bleed assembly **122** based on the received data.

(89) In one or more exemplary embodiments, the controller **150** depicted in FIG. **7** may be a stand-alone controller **150** for the variable bleed assembly **122**, or alternatively, may be integrated into one or more of a controller for the gas turbine engine **10** with which the variable bleed assembly **122** is integrated, a controller for an aircraft including the gas turbine engine **10** with which the variable bleed assembly **122** is integrated, etc.

(90) Referring particularly to the operation of the controller **150**, in at least certain embodiments, the controller **150** can include one or more computing device(s) **154**. The computing device(s) **154** can include one or more processor(s) **154A** and one or more memory device(s) **154B**. The one or more processor(s) **154A** can include any suitable processing device, such as a microprocessor, microcontroller, integrated circuit, logic device, and/or other suitable processing device. The one or more memory device(s) **154B** can include one or more computer-readable media, including, but not

limited to, non-transitory computer-readable media RAM, ROM, hard drives, flash drives, and/or other memory devices.

(91) The one or more memory device(s) **154B** can store information accessible by the one or more processor(s) **154A**, including computer-readable instructions **154C** that can be executed by the one or more processor(s) **154A**. The instructions **154C** can be any set of instructions that when executed by the one or more processor(s) **154A**, cause the one or more processor(s) **154A** to perform operations. In some embodiments, the instructions **154C** can be executed by the one or more processor(s) **154A** to cause the one or more processor(s) **154A** to perform operations, such as any of the operations and functions for which the controller **150** and/or the computing device(s) **154** are configured, the operations for operating a variable bleed assembly **122** (e.g., method **200**), as described herein, and/or any other operations or functions of the one or more computing device(s) **154**. The instructions **154C** can be software written in any suitable programming language or can be implemented in hardware. Additionally, and/or alternatively, the instructions **154C** can be executed in logically and/or virtually separate threads on the one or more processor(s) **154A**. The one or more memory device(s) **154B** can further store data **154D** that can be accessed by the one or more processor(s) **154A**. For example, the data **154D** can include data indicative of power flows, data indicative of engine/aircraft operating conditions, and/or any other data and/or information described herein.

(92) The computing device(s) **154** can also include a network interface **154E** used to communicate, for example, with the other components of the variable bleed assembly **122**, the gas turbine engine **10** incorporating variable bleed assembly **122**, the aircraft incorporating the gas turbine engine **10**, etc. For example, in the embodiment depicted, as noted above, the gas turbine engine **10** and/or variable bleed assembly **122** includes one or more sensors for sensing data indicative of one or more parameters of the gas turbine engine, the variable bleed assembly **122**, the cooling passage **110**, the accessory system(s) **108**, or a combination thereof. The controller **150** of the variable bleed assembly **122** is operably coupled to the one or more sensors through, e.g., the network interface **154E**, such that the controller **150** may receive data indicative of various operating parameters sensed by the one or more sensors during operation. Further, for the embodiment shown the controller **150** is operably coupled to, e.g., actuator **132**. In such a manner, the controller **150** may be configured to vary an amount of airflow through the variable bleed assembly **122** and into the cooling passage **110** in response to, e.g., the data sensed by the one or more sensors.

(93) The network interface **154E** can include any suitable components for interfacing with one or more network(s), including for example, transmitters, receivers, ports, controllers, antennas, and/or other suitable components.

(94) The technology discussed herein makes reference to computer-based systems and actions taken by and information sent to and from computer-based systems. One of ordinary skill in the art will recognize that the inherent flexibility of computer-based systems allows for a great variety of possible configurations, combinations, and divisions of tasks and functionality between and among components. For instance, processes discussed herein can be implemented using a single computing device or multiple computing devices working in combination. Databases, memory, instructions, and applications can be implemented on a single system or distributed across multiple systems. Distributed components can operate sequentially or in parallel.

(95) For the embodiment depicted, the controller **150** is configured to actuate the variable bleed valve **130** to increase or decrease the amount of airflow through the variable bleed duct **124**. In certain exemplary aspects, the controller **150** may further be configured to receive data indicative of an operating condition of the gas turbine engine **10** (e.g., sensed data from the one or more sensors **152**). In certain exemplary aspects, the controller **150** may actuate the variable bleed valve **130** to increase or decrease the amount of airflow through the variable bleed duct **124** in response to the data indicative of the operating condition.

(96) For example, in response to receiving data indicative of an operating condition whereby a

relatively high amount of cooling may be needed, the controller **150** may be configured to actuate the variable bleed valve **130** to increase the amount of airflow through the variable bleed duct **124** (e.g., move the variable bleed valve **130** to a fully deployed position) to increase the amount of airflow through the annular cooling passage **110**. By contrast, in response to receiving data indicative of an operating condition whereby a relatively low amount of cooling may be needed, the controller **150** may be configured to actuate the variable bleed valve **130** to decrease the amount of airflow through the variable bleed duct **124** (e.g., move the variable bleed valve **130** to a fully stowed position) to decrease the amount of airflow through the annular cooling passage **110**.

(97) Referring now to FIG. **10**, a method **200** of operating a gas turbine engine **10** in accordance with an exemplary aspect of the present disclosure is provided. The method **200** may generally be utilized with one or more of the exemplary gas turbine engines **10** described above with reference to FIGS. **1** through **9**. Alternatively, the exemplary method **200** may be utilized with any other suitable gas turbine engine **10**.

(98) The method **200** generally includes at **(202)** receiving data indicative of an operating condition of the gas turbine engine, and at **(204)** varying an amount of variable bleed airflow through a variable bleed duct provided to an annular cooling passage in response to the data received at **(202)**. The annular cooling passage extends between a CP inlet in airflow communication with a working gas flowpath of the turbomachine and a CP outlet in airflow communication with a bypass passage of the gas turbine engine.

(99) In certain exemplary aspects of the present disclosure, the operating condition is a low fan power operating condition. For example, the low fan power operating condition may be a ground idle operating condition or a flight idle descent operating condition. With such an exemplary aspect, varying the amount of variable bleed airflow through the variable bleed duct provided to the annular cooling passage at **(204)** may include at **(206)** increasing the amount of variable bleed airflow through the variable bleed duct provided to the annular cooling passage.

(100) In certain exemplary aspects of the present disclosure, the operating condition is indicative of an ambient temperature. For example, the data received may be indicative of the ambient temperature being above a predetermined threshold. With such an exemplary aspect, varying the amount of variable bleed airflow through the variable bleed duct provided to the annular cooling passage at **(204)** may include at **(208)** increasing the amount of variable bleed airflow through the variable bleed duct provided to the annular cooling passage.

(101) Referring now to FIG. **11**, a gas turbine engine **10** in accordance with another exemplary aspect of the present disclosure is provided. The exemplary gas turbine engine **10** of FIG. **11** may be configured in a similar manner as exemplary gas turbine engine **10** described above with reference to FIG. **1**. For example, the exemplary gas turbine engine **10** of FIG. **11** generally includes a fan section **14** having a fan **38**, a turbomachine **16** (depicted schematically), and an outer nacelle **50**.

(102) For the embodiment depicted, the outer nacelle **50** generally includes an inlet assembly **160** and a fan cowl **162**, and the gas turbine engine **10** further includes a thrust reverser assembly **164** at least partially integrated into the outer nacelle **50**. A top half of the exemplary gas turbine engine **10** in FIG. **11** is depicted with the thrust reverser assembly **164** in a stowed configuration, and a bottom half of the exemplary gas turbine engine **10** of FIG. **11** is depicted with the thrust reverser assembly **164** in a deployed configuration.

(103) The inlet assembly **160** is positioned at a forward end of the outer nacelle **50** and the fan cowl **162** is positioned aft of the inlet assembly **160** and at least partially surrounds the fan **38**. The thrust reverser assembly **164** may, in turn, be positioned at least partially or substantially completely within the fan cowl **162** when in the stowed configuration. As is depicted, an outer casing **18** of the turbomachine **16** defines a radially inward boundary of a bypass passage **56** and the outer nacelle **50** defines a radially outward boundary of the bypass passage **56**. Bypass air of the gas turbine engine **10** passes through the bypass passage **56** and exits through a fan exit nozzle **166** during

certain operations.

(104) The thrust reverser assembly **164** of FIG. **11** may include a translating cowl (transcowl) **168** slidably mounted to the fan cowl **162**, and a cascade assembly **170**. The transcowl **168** is located aft of the fan cowl **162** and circumscribes an outer casing **18** of the turbomachine **16**. When in the deployed configuration, the cascade assembly **170** is also located at least partially aft of the fan cowl **162** and circumscribes the turbomachine **16**. By contrast, when in the stowed configuration the cascade assembly **170** is stowed substantially completely within the fan cowl **162**.

(105) Referring still to FIG. **11**, the cascade assembly **170** depicted is formed of and includes a plurality of individual cascade segments **172** that are circumferentially spaced around a circumference of the outer nacelle **50**. As is evident from FIG. **11**, the cascade segments **172** of the cascade assembly **170** may be adapted to deploy from an axially stowed configuration, shown in the upper half of FIG. **11**, to an axially deployed configuration shown in the lower half of FIG. **11**. For the embodiment depicted, the transcowl **168** and cascade assembly **170** are adapted to be translated in unison in an aft direction of the gas turbine engine **10**, generally along the axial direction A, when the thrust reverser assembly **164** is moved from the stowed configuration to the deployed configuration (i.e., is deployed). More particularly, to deploy the cascade assembly **170** into the bypass passage **56**, the transcowl **168** is moved aft from the fan cowl **162** generally along the axial direction A and the cascade assembly **170** is translated and pivoted, causing a flow of bypass air within the bypass passage **56** to be diverted through the deployed cascade assembly **170** to provide a thrust reversal effect.

(106) In order to facilitate the above movement of the thrust reverser assembly **164**, the thrust reverser assembly **164** includes one or more actuation assemblies **174**. The actuation assemblies **174** are configured to move the thrust reverser assembly **164** from the stowed configuration to the deployed configuration. The actuation assemblies **174** can be of any suitable type and can be driven by, e.g., pneumatic, hydraulic, or electric motors. Additionally, the cascade segments **172** are depicted as coupled to a fixed structure of the outer nacelle **50** with guided connections **176**. Further, FIG. **11** represents the cascade segments **172** as pivotally coupled to the outer casing **18** of the turbomachine **16** with drag links **178**, and represent the transcowl **168** as pivotally coupled to the cascade segments **172** through drag links **178** for translation therewith.

(107) More specifically, for the embodiment shown, the thrust reverser assembly **164** further includes an inner thrust reverser support **180** positioned on, coupled to, or integrated with the turbomachine **16**. The exemplary inner thrust reverser support **180** depicted generally includes a plurality of thrust reverser link attachments **182** arranged along the circumferential direction C of the gas turbine engine **10**. For the embodiment shown, the drag links **178** are attachable to the plurality of thrust reverser link attachments **182**, such that the inner thrust reverser support **180** may provide axial and radial support for the cascade assembly **170** through the plurality of drag links **178**.

(108) Referring now to FIG. **12**, a close-up, schematic view is depicted of a portion of the exemplary gas turbine engine **10** described above with reference to FIG. **11**. In particular, the view of FIG. **12** depicts a close-up of the turbomachine **16** of FIG. **1**. The turbomachine **16** generally includes a compressor section having an LP compressor **22** and an HP compressor **24**, defining at least in part a working gas flowpath **37**. The turbomachine **16** further defines a turbomachine inlet **20** to the working gas flowpath **37**. Further, for the embodiment depicted, the turbomachine **16** includes a compressor forward frame **100** and a compressor mid-frame **102**. The compressor forward frame **100** includes a strut **104** extending through the working gas flowpath **37** at a location upstream of the LP compressor **22** and downstream of the turbomachine inlet **20**. Similarly, the compressor mid-frame **102** includes a strut **106** extending through the working gas flowpath **37** at a location downstream of the LP compressor **22** and upstream of the HP compressor **24**. Moreover, in the embodiment depicted the compressor mid-frame **102** generally includes a forward member **184** and an aft member **186** spaced apart from one another along an axial direction

A of the gas turbine engine **10**.

(109) The compressor forward frame **100** and the compressor mid-frame **102** may provide structural support to various components of the gas turbine engine **10**.

(110) Moreover, the exemplary gas turbine engine **10** depicted schematically in FIG. **12** further includes a variable bleed assembly **122** and the thrust reverser assembly **164**, with the thrust reverser assembly **164** including the inner thrust reverser support **180**. The variable bleed assembly **122** generally includes a variable bleed duct **124** extending between a VB inlet **126** and a VB outlet **128**. The VB inlet **126** is in airflow communication with the working gas flowpath **37** at a location aligned with the compressor mid-frame **102**. Moreover, for the embodiment depicted, the VB outlet **128** is in airflow communication with the bypass passage **56** at a location aft of the forward member **184** of the compressor mid-frame **102**, and forward of the aft member **186** of the compressor mid-frame **102**.

(111) Further, for the embodiment depicted, the inner thrust reverser support **180** includes a forward interface **188** coupled to the forward member **184** of the compressor mid-frame **102**. The forward interface **188** is configured to provide axial support for the inner thrust reverser support **180**, as will be explained in more detail below. In such a manner, the inner thrust reverser support **180** extends from the forward member **184** of the compressor mid-frame **102**, past the aft member **186** of the compressor mid-frame **102**. With such a configuration, it will be appreciated that the VB outlet **128** is in airflow communication with the bypass passage **56** through the inner thrust reverser support **180**. In at least certain exemplary embodiments, as is depicted in the callout Circle A in FIG. **12**, the variable bleed assembly **122** may additionally include a cover **129** at the VB outlet **128** with one or more features to turn an airflow from the VB outlet **128** axially. The cover **129** depicted includes a plurality of louvers **131** that may be fixed or rotatable to provide such functionality.

(112) More specifically, referring now to FIG. **13**, a cross-sectional, isometric view is provided of the compressor mid-frame **102**, variable bleed assembly **122**, and inner thrust reverser support **180** of FIG. **12**.

(113) As noted above, the inner thrust reverser support **180** includes the forward interface **188** coupled to the forward member **184** of the compressor mid-frame **102**. More specifically, for the embodiment depicted, the forward interface **188** includes a radial member (not separately labeled) extending inwardly along a radial direction **R** of the gas turbine engine **10**. The forward member **184** of the compressor mid-frame **102** defines a circumferential groove **190** extending along the circumferential direction **C** in defining a radial depth. The radial member of the forward interface **188** is positioned within the circumferential groove **190** to couple the inner thrust reverser support **180** to the compressor mid-frame **102**. As will be appreciated from the view of FIG. **13**, the inner thrust reverser support **180** defines an annular shape, and extends substantially 360° (i.e., at least about 90%) around the turbomachine **16**.

(114) As is also briefly mentioned above, the VB outlet **128** of the variable bleed duct **124** is in airflow communication with the bypass passage **56** through the inner thrust reverser support **180**, and more specifically through an opening **191** defined in the inner thrust reverser support **180**. Although not depicted for clarity in FIG. **13**, the cover **129** described above with reference to FIG. **12** may be positioned in or across the opening **191** defined in the inner thrust reverser support **180**.

(115) Referring still to FIG. **13**, in the embodiment depicted, the thrust reverser assembly **164** includes a seal **192** positioned between the inner thrust reverser support **180** and one or both of the compressor mid-frame **102** and the variable bleed duct **124**. In particular, for the embodiment depicted, the seal **192** is positioned between the inner thrust reverser support **180** and the compressor mid-frame **102**. The seal **192** may prevent undesirable airflow leakage into the compressor mid-frame **102**, and/or aft the compressor mid-frame **102**, which may urge the inner thrust reverser support **180** out of alignment (e.g., the radial member out of the circumferential groove **190**).

(116) Briefly, it will further be appreciated that for the embodiment depicted, the thrust

turbomachine **16** further includes a fire seal **194** positioned between an extension of the aft member **186** of the compressor mid-frame **102** and the inner thrust reverser support **180**. The fire seal **194** is an annular seal, extending 360° in the circumferential direction C.

(117) It will be appreciated that in order to facilitate assembly of the inner thrust reverser support **180**, the inner thrust reverser support **180** may be configured as a two-piece assembly. For example, referring briefly to FIG. **14**, a schematic view is provided of the inner thrust reverser support **180**, as viewed along an axial direction A of the gas turbine engine **10** with which the inner thrust reverser support **180** may be installed. As will be appreciated, the inner thrust reverser support **180** includes a first member **196** and a second member **198**. The first member **196** and the second member **198** together extend substantially 360° when coupled together. In order to install, e.g., the radial member of the inner thrust reverser support **180** into the circumferential groove **190** of the forward member **184** of the compressor mid-frame **102** (see FIG. **13**), the first member **196** and the second member **198** of the inner thrust reverser support **180** may be individually installed (as is depicted in phantom in FIG. **14**).

(118) In such a manner, it will be appreciated that the first member **196** and the second member **198** may together define a hinged connection **197** (i.e., any mechanical connection that allows for the first member to pivot relative to the second member, such as a pinned connection) on one side and a releasable mechanical connection **199** (i.e., any mechanical connection that allows for a release without damaging the connection during a normal course, such as a bolted connection, a ratcheted connection, a latched connection, or the like) on an opposite side.

(119) It will be appreciated, however, that in other exemplary embodiments, the forward interface **188** (FIG. **13**) of the inner thrust reverser support **180** may be configured in any other suitable manner. For example, in other embodiments, the forward interface **188** may utilize any other suitable mechanical connection, such as, e.g., bolts, screws, rivets, welding, complementary geometries (e.g., dovetails), etc.

(120) Further, it will be appreciated that although the exemplary variable bleed assembly **122** depicted in FIGS. **11** and **12** includes a single variable bleed duct **124** extending between a single VB inlet **126** and a single VB outlet **128**, in other exemplary embodiments, the variable bleed assembly **122** may include a plurality of variable bleed ducts **124** spaced along a circumferential direction C (each with a respective VB inlet **126**). The plurality of variable bleed ducts **124** may be in fluid communication with a plenum, with the plenum defining the VB outlet **128**, and a seal **192** around the VB outlet **128**. Alternatively, the plurality of variable bleed ducts **124** may each define a separate VB outlet **128**, and the seal **192** may extend around the plurality of VB outlets **128**.

(121) Further, still, it will be appreciated that although exemplary VB outlet **128** of the exemplary variable bleed duct **124** of FIGS. **12** and **13** extends through the inner thrust reverser support **180**, in other exemplary embodiments, any other suitable configuration may be provided.

(122) For example, referring now to FIG. **15**, a close-up, schematic view of a gas turbine engine **10** in accordance with another exemplary aspect of the present disclosure is provided. The exemplary gas turbine engine **10** depicted in FIG. **15** may be configured in a similar manner as exemplary gas turbine engine **10** described above with reference to FIGS. **12** and **13**. The same or similar numbers may refer to the same or similar part.

(123) For example, the exemplary gas turbine engine **10** depicted in FIG. **15** generally includes a gas turbine engine **10** having a turbomachine **16** and an outer nacelle **50**, and defines a bypass passage **56** therebetween. The gas turbine engine **10** further includes a thrust reverser assembly **164** having an inner thrust reverser support **180** coupled to or formed integrally with the turbomachine **16** and including a forward interface **188** coupled to a forward member **184** of a compressor mid-frame **102** of the turbomachine **16**. The inner thrust reverser support **180** includes a plurality of thrust reverser link attachments **182**. The thrust reverser assembly **164** further includes a cascade assembly **170** having a plurality of cascade segments **172**, and a plurality of drag links **178** extending from the cascade assembly **170** and attached to a plurality of thrust reverser link

attachments **182** on the inner thrust reverser support **180**.

(124) Further, the exemplary turbomachine **16** generally includes a variable bleed assembly **122** having a variable bleed duct **124** extending between a VB inlet **126** and a VB outlet **128**. However, for the embodiment of FIG. **15**, the VB outlet **128** is not in airflow communication with the bypass passage **56** through the inner thrust reverser support **180**. Instead, for the embodiment of FIG. **15**, the turbomachine **16** defines a cooling passage **110** extending between a CP inlet **112** and a CP outlet **114**. The CP inlet **112** is in airflow communication with a working gas flowpath **37** of the turbomachine **16** at a location upstream of a compressor section of the turbomachine **16**, and the CP outlet **114** is in airflow communication with the bypass passage **56** of the gas turbine engine **10** defined between the outer nacelle **50** and the turbomachine **16**. The VB outlet **128** is in airflow communication with the cooling passage **110**. More specifically, for the embodiment shown, the variable bleed duct **124** of the variable bleed assembly **122** extends forward of the forward member **184** of the compressor mid-frame **102** to the cooling passage **110**. In such a manner, it will be appreciated that the VB outlet **128** is in airflow communication with the bypass passage **56** through the cooling passage **110** and CP outlet **114** of the cooling passage **110**, which is positioned at a location forward of the forward interface **188** of the thrust reverser support.

(125) Moreover, it will be appreciated that although for the embodiments of FIGS. **11** through **15**, an inner thrust reverser support **180** is depicted and described as being attached to the forward member **184** of the compressor mid-frame **102**, in other embodiments, any other suitable hinged cowl assembly extending at least partially around a compressor section of a turbomachine may be provided, with the hinged cowl assembly including a forward interface coupled to the forward member of the compressor mid-frame.

(126) As with the embodiments described above, the hinged cowl assembly may include a first member and a second member, with the first member and the second member together extending substantially 360° when coupled together (similar to the embodiment depicted in FIG. **14**). Further, the first member and the second member may together define a hinged connection (i.e., any mechanical connection that allows for the first member to pivot relative to the second member, such as a pinned connection) and a releasable mechanical connection (i.e., any mechanical connection that allows for a release without damaging the connection during a normal course, such as a bolted connection, a ratcheted connection, a latched connection, or the like).

(127) It will be appreciated that inclusion of an inner thrust reverser support having a forward interface coupled to a forward member of a compressor mid-frame may allow for the inner thrust reverser support to be moved forward along an axial direction. Such may generally allow for more desirable aerodynamic lines of an outer casing encompassing turbomachinery of a turbomachine of the gas turbine engine, which may allow for a shorter and lighter gas turbine engine. In particular, when incorporated into a gas turbine engine including a reduction gearbox, such may allow for aerodynamic lines of the outer casing to more optimally define an outlet nozzle for a bypass passage in a shorter axial footprint, given a potential reduction in turbine stage enabled by inclusion of the reduction gearbox, allowing for the shorter and lighter gas turbine engine.

(128) Further aspects are provided by the subject matter of the following clauses:

(129) A gas turbine engine comprising: a fan assembly comprising a fan; and a turbomachine drivingly coupled to the fan and comprising a compressor section, a combustion section, and a turbine section arranged in serial flow order and defining in part a working gas flowpath, the gas turbine engine defining a bypass passage over the turbomachine; the turbomachine further comprising a heat exchanger and defining an annular cooling passage extending between an inlet and an outlet, the inlet in airflow communication with the working gas flowpath at a location upstream of the compressor section and the outlet in airflow communication with the bypass passage, the heat exchanger in thermal communication with an airflow through the cooling passage.

(130) The gas turbine engine of any preceding clause, wherein the compressor section comprises a

low pressure compressor and a high pressure compressor, and wherein the inlet is in airflow communication with the working gas flowpath at a location upstream of the low pressure compressor.

(131) The gas turbine engine of any preceding clause, wherein the low pressure compressor is located downstream of the fan and is wherein no intermediate stages of compression are located between the fan and the low pressure compressor.

(132) The gas turbine engine of any preceding clause, wherein the fan is a single stage fan.

(133) The gas turbine engine of any preceding clause, further comprising: an outer nacelle surrounding the fan and at least a portion of the turbomachine, wherein the bypass passage is defined between the turbomachine and the outer nacelle.

(134) The gas turbine engine of any preceding clause, wherein the turbomachine defines a turbomachine inlet to the working gas flowpath, wherein the turbomachine inlet is located immediately downstream of the fan, and wherein the fan is a single stage fan.

(135) The gas turbine engine of any preceding clause, wherein the gas turbine engine defines an axial direction, and wherein the outlet is aligned with the compressor section along the axial direction.

(136) The gas turbine engine of any preceding clause, wherein the gas turbine engine defines a circumferential direction, and wherein the heat exchanger is a first heat exchanger of a plurality of heat exchangers arranged along the circumferential direction within the annular cooling passage.

(137) The gas turbine engine of any preceding clause, wherein the turbomachine comprises a compressor mid-frame, and wherein the outlet is in airflow communication with the bypass passage at a location forward of the compressor mid-frame.

(138) The gas turbine engine of any preceding clause, wherein the gas turbine engine defines an axial direction, wherein the turbomachine comprises a compressor forward frame, and wherein the inlet is aligned with the compressor forward frame along the axial direction.

(139) The gas turbine engine of any preceding clause, wherein the turbomachine includes a means for urging the airflow through the cooling passage.

(140) The gas turbine engine of any preceding clause, wherein the turbomachine comprises an inlet scoop extending into the working gas flowpath to divert an airflow through the working gas flowpath and into the inlet of the cooling passage.

(141) The gas turbine engine of any preceding clause, wherein the turbomachine comprises a hood extending over the outlet of the cooling passage, wherein the hood extends into the bypass passage to reduce a static pressure at the outlet of the cooling passage.

(142) The gas turbine engine of any preceding clause, wherein the turbomachine comprises an ejector positioned in airflow communication with the cooling passage, wherein the ejector is in airflow communication with a high pressure air source.

(143) The gas turbine engine of any preceding clause, wherein the turbomachine comprises a variable bleed assembly, and wherein the high pressure air source is the variable bleed assembly.

(144) The gas turbine engine of any preceding clause, wherein during operating of the gas turbine engine at a first operating condition, the cooling passage is configured to receive between 2% and 20% of a total airflow through the working gas flowpath at a location upstream of the inlet.

(145) The gas turbine engine of any preceding clause, wherein the first operating condition is a takeoff operating condition.

(146) The gas turbine engine of any preceding clause, wherein during operating of the gas turbine engine at a first operating condition, the cooling passage is configured to receive between 4% and 12% of a total airflow through the working gas flowpath at a location upstream of the inlet.

(147) The gas turbine engine of any preceding clause, wherein the gas turbine engine is a ducted turbofan engine.

(148) The gas turbine engine of any preceding clause, further comprising: a reduction gearbox, wherein the turbomachine is drivingly coupled to the fan through the reduction gearbox.

(149) A gas turbine engine comprising: a fan assembly comprising a fan; a turbomachine drivingly coupled to the fan and comprising a compressor section, a combustion section, and a turbine section arranged in serial flow order and defining in part a working gas flowpath, the gas turbine engine defining a bypass passage over the turbomachine, the turbomachine defining an annular cooling passage extending between a CP inlet and a CP outlet, the CP inlet in airflow communication with the working gas flowpath and the CP outlet in airflow communication with the bypass passage; and a variable bleed assembly comprising a variable bleed duct extending between a VB inlet and a VB outlet, the VB inlet in airflow communication with the working gas flowpath at a location downstream of the CP inlet and the VB outlet in airflow communication with the annular cooling passage for urging an airflow through the cooling passage.

(150) The gas turbine engine of any preceding clause, wherein the compressor section comprises a compressor, wherein the CP inlet is in airflow communication with the working gas flowpath at a location upstream of the compressor, and wherein the VB inlet is in airflow communication with the working gas flowpath at a location downstream of the compressor.

(151) The gas turbine engine of any preceding clause, wherein the compressor is a low pressure compressor.

(152) The gas turbine engine of any preceding clause, wherein the compressor section further comprises a high pressure compressor, wherein the VB inlet is in airflow communication with the working gas flowpath at a location upstream of the high pressure compressor.

(153) The gas turbine engine of any preceding clause, wherein the variable bleed assembly comprises a variable bleed valve for varying an amount of airflow through the variable bleed duct.

(154) The gas turbine engine of any preceding clause, further comprising: a controller operably coupled to the variable bleed valve, wherein the controller is configured to actuate the variable bleed assembly to increase the amount of airflow through the variable bleed duct in response to an operating condition of the gas turbine engine to increase an amount of airflow through the annular cooling passage.

(155) The gas turbine engine of any preceding clause, wherein the VB outlet forms at least in part an ejector.

(156) The gas turbine engine of any preceding clause, wherein substantially all of an airflow through the variable bleed duct is provided through the VB outlet to the cooling passage.

(157) The gas turbine engine of any preceding clause, wherein the VB outlet is a first VB outlet, and wherein the variable bleed duct further comprises a second VB outlet, wherein the second VB outlet is in direct airflow communication with the bypass passage.

(158) The gas turbine engine of any preceding clause, wherein the turbomachine comprises a heat exchanger in thermal communication with the airflow through the cooling passage.

(159) The gas turbine engine of any preceding clause, wherein the VB outlet is in airflow communication with the cooling passage at a location downstream of the heat exchanger.

(160) The gas turbine engine of any preceding clause, wherein the gas turbine engine defines a circumferential direction, and wherein the heat exchanger is a first heat exchanger of a plurality of heat exchangers arranged along the circumferential direction within the annular cooling passage.

(161) A method of operating a gas turbine engine comprising a fan assembly and a turbomachine drivingly coupled to a fan of the fan assembly, the method comprising: receiving data indicative of an operating condition of the gas turbine engine; and varying an amount of variable bleed airflow through a variable bleed duct provided to an annular cooling passage in response to the received data, the annular cooling passage extending between a CP inlet in airflow communication with a working gas flowpath of the turbomachine and a CP outlet in airflow communication with a bypass passage of the gas turbine engine.

(162) The method of any preceding clause, wherein the operating condition is a low fan power operating condition, and wherein varying the amount of variable bleed airflow through the variable bleed duct provided to the annular cooling passage comprises increasing the amount of variable

bleed airflow through the variable bleed duct provided to the annular cooling passage.

(163) The method of any preceding clause, wherein the low fan power operating condition is a ground idle operating condition or a flight idle descent operating condition.

(164) The method of any preceding clause, wherein the operating condition is indicative of an ambient temperature.

(165) The method of any preceding clause, wherein the operating condition is indicative of the ambient temperature being greater than a threshold, and wherein varying the amount of variable bleed airflow through the variable bleed duct provided to the annular cooling passage comprises increasing the amount of variable bleed airflow through the variable bleed duct provided to the annular cooling passage.

(166) The method of any preceding clause, wherein the variable bleed assembly comprises a variable bleed valve for varying an amount of airflow through the variable bleed duct.

(167) The method of any preceding clause, wherein the turbomachine comprises a heat exchanger in thermal communication with an airflow through the cooling passage.

(168) The method of any preceding clause, wherein the VB outlet is in airflow communication with the cooling passage at a location downstream of the heat exchanger.

(169) A gas turbine engine comprising: a turbomachine, the gas turbine engine defining a bypass passage over the turbomachine, the turbomachine comprising: a compressor section having a first compressor and a second compressor and defining in part a working gas flowpath; and a compressor mid-frame extending through the working gas flowpath at a location between the first and second compressors, the compressor mid-frame comprising a forward member and an aft member; and a thrust reverser assembly comprising an inner thrust reverser support, the inner thrust reverser support comprising a forward interface coupled to the forward member of the compressor mid-frame.

(170) The gas turbine engine of any preceding clause, wherein the inner thrust reverser support is annular and extends 360° around the turbomachine.

(171) The gas turbine engine of any preceding clause, wherein the inner thrust reverser support is a two piece assembly.

(172) The gas turbine engine of any preceding clause, wherein the forward interface comprises a radial member extending inwardly along the radial direction, wherein the forward member defines a circumferential groove, and wherein the radial member of the forward interface is positioned within the circumferential groove to couple the inner thrust reverser support to the compressor mid-frame.

(173) The gas turbine engine of any preceding clause, wherein the gas turbine engine defines a circumferential direction, and wherein the inner thrust reverser support comprises a plurality of thrust reverser link attachments arranged along the circumferential direction of the gas turbine engine.

(174) The gas turbine engine of any preceding clause, further comprising: a fan assembly comprising a fan, wherein the turbomachine is drivingly coupled to the fan; and an outer nacelle surrounding the fan and at least a portion of the turbomachine, wherein the bypass passage is defined between the turbomachine and the outer nacelle; wherein the thrust reverser assembly further comprises a cascade assembly having a plurality of drag links, wherein the drag links are attachable to the plurality of thrust reverser link attachments of the inner thrust reverser support.

(175) The gas turbine engine of any preceding clause, wherein the turbomachine further comprises a variable bleed assembly comprising a variable bleed duct extending between a VB inlet and a VB outlet, the VB inlet in airflow communication with the working gas flowpath at a location aligned with the compressor mid-frame.

(176) The gas turbine engine of any preceding clause, wherein the VB outlet is in airflow communication with the bypass passage at a location aft of the forward member of the compressor mid-frame.

(177) The gas turbine engine of any preceding clause, wherein the VB outlet is in airflow communication with the bypass passage at a location forward of the aft member of the compressor mid-frame.

(178) The gas turbine engine of any preceding clause, wherein the thrust reverser assembly comprises a seal positioned between the compressor mid-frame and the inner thrust reverser support.

(179) The gas turbine engine of any preceding clause, wherein the VB outlet is in airflow communication with the bypass passage at a location forward of the forward interface of the thrust reverser support.

(180) The gas turbine engine of any preceding clause, wherein the turbomachine further comprises a variable bleed assembly comprising a variable bleed duct, wherein the variable bleed duct of the variable bleed assembly extends forward of the forward member of the compressor mid-frame.

(181) A gas turbine engine comprising: a turbomachine, the gas turbine engine defining a bypass passage over the turbomachine, the turbomachine comprising: a compressor section having a first compressor and a second compressor and defining in part a working gas flowpath; a compressor mid-frame extending through the working gas flowpath at a location between the first and second compressors, the compressor mid-frame comprising a forward member and an aft member; and a variable bleed assembly comprising a variable bleed duct extending between a VB inlet and an VB outlet, the VB inlet in airflow communication with the working gas flowpath at a location aligned with the compressor mid-frame, wherein the VB outlet is in airflow communication with the bypass passage at a location forward of the forward member of the compressor mid-frame, the variable bleed duct of the variable bleed assembly extending forward of the forward member of the compressor mid-frame to the VB outlet.

(182) The gas turbine engine of any preceding clause, further comprising: a thrust reverser assembly comprising an inner thrust reverser support, the inner thrust reverser support comprising a forward interface coupled to the forward member of the compressor mid-frame.

(183) The gas turbine engine of any preceding clause, wherein the VB outlet is in airflow communication with the bypass passage at a location forward of the forward interface of the inner thrust reverser support.

(184) The gas turbine engine of any preceding clause, wherein the forward interface comprises a radial member extending inwardly along a radial direction of the gas turbine engine, wherein the forward member defines a circumferential groove, and wherein the radial member of the forward interface is positioned within the circumferential groove to couple the inner thrust reverser support to the compressor mid-frame.

(185) The gas turbine engine of any preceding clause, wherein the gas turbine engine defines a circumferential direction, and wherein the inner thrust reverser support comprises a plurality of thrust reverser link attachments arranged along the circumferential direction of the gas turbine engine.

(186) The gas turbine engine of any preceding clause, wherein the VB outlet is in airflow communication with the bypass passage at a location aft of the forward member of the compressor mid-frame.

(187) The gas turbine engine of any preceding clause, wherein the VB outlet is in airflow communication with the bypass passage at a location forward of the aft member of the compressor mid-frame.

(188) The gas turbine engine of any preceding clause, further comprising: a thrust reverser assembly comprising an inner thrust reverser support, the inner thrust reverser support comprising a forward interface coupled to the forward member of the compressor mid-frame, and wherein the thrust reverser assembly comprises an aerodynamic seal positioned between the compressor mid-frame and the inner thrust reverser support.

(189) A gas turbine engine comprising: a turbomachine, the gas turbine engine defining a bypass

passage over the turbomachine, the turbomachine comprising: a compressor section having a first compressor and a second compressor and defining in part a working gas flowpath; and a compressor mid-frame extending through the working gas flowpath at a location between the first and second compressors, the compressor mid-frame comprising a forward member and an aft member; and a hinged cowl assembly extending at least partially around the compressor section of the turbomachine, the hinged cowl assembly comprising a forward interface coupled to the forward member of the compressor mid-frame.

(190) The gas turbine engine of any preceding clause, wherein hinged cowl assembly comprises a first member and a second member, wherein first member and the second member together extend substantially 360° when coupled together.

(191) The gas turbine engine of any preceding clause, wherein the first member and the second member together define a hinged connection and a releasable mechanical connection.

(192) The gas turbine engine of any preceding clause, wherein the hinged cowl assembly is an inner thrust reverser support of a thrust reverser assembly of the gas turbine engine.

(193) The gas turbine engine of any preceding clause, wherein the forward interface comprises a radial member extending inwardly along the radial direction, wherein the forward member defines a circumferential groove, and wherein the radial member of the forward interface is positioned within the circumferential groove to couple the hinged cowl assembly to the compressor mid-frame.

(194) This written description uses examples to disclose the present disclosure, including the best mode, and also to enable any person skilled in the art to practice the disclosure, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the disclosure is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they include structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

Claims

1. A gas turbine engine comprising: a fan assembly comprising a fan at a forward end of the gas turbine engine, the fan being a first stage of compression for the gas turbine engine; and a turbomachine drivingly coupled to the fan and comprising a compressor section, a combustion section, and a turbine section arranged in serial flow order and defining in part a working gas flowpath, the gas turbine engine defining a bypass passage over the turbomachine; the turbomachine further comprising a heat exchanger and defining an annular cooling passage extending between an inlet and an outlet, the inlet in airflow communication with the working gas flowpath at a location upstream of the compressor section and the outlet in airflow communication with the bypass passage, the heat exchanger in thermal communication with an airflow through the annular cooling passage, wherein the compressor section is located downstream of the fan, and wherein no intermediate stages of compression are located between the fan and the compressor section.
2. The gas turbine engine of claim 1, wherein the compressor section comprises a low pressure compressor and a high pressure compressor, and wherein the inlet is in airflow communication with the working gas flowpath at a location upstream of the low pressure compressor.
3. The gas turbine engine of claim 2, wherein the fan is a single stage fan.
4. The gas turbine engine of claim 1, further comprising: an outer nacelle surrounding the fan and at least a portion of the turbomachine, wherein the bypass passage is defined between the turbomachine and the outer nacelle.
5. The gas turbine engine of claim 1, wherein the turbomachine defines a turbomachine inlet to the

working gas flowpath, wherein the turbomachine inlet is located immediately downstream of the fan, and wherein the fan is a single stage fan.

6. The gas turbine engine of claim 1, wherein the gas turbine engine defines an axial direction, and wherein the outlet is aligned with the compressor section along the axial direction.
 7. The gas turbine engine of claim 1, wherein the gas turbine engine defines a circumferential direction, and wherein the heat exchanger is a first heat exchanger of a plurality of heat exchangers arranged along the circumferential direction within the annular cooling passage.
 8. The gas turbine engine of claim 1, wherein the turbomachine comprises a compressor mid-frame, and wherein the outlet is in airflow communication with the bypass passage at a location forward of the compressor mid-frame.
 9. The gas turbine engine of claim 8, wherein the gas turbine engine defines an axial direction, wherein the turbomachine comprises a compressor forward frame, and wherein the inlet is aligned with the compressor forward frame along the axial direction.
 10. The gas turbine engine of claim 1, wherein the turbomachine includes a means for urging the airflow through the annular cooling passage.
 11. The gas turbine engine of claim 1, wherein the turbomachine comprises an inlet scoop extending into the working gas flowpath to divert an airflow through the working gas flowpath and into the inlet of the annular cooling passage.
 12. The gas turbine engine of claim 1, wherein the turbomachine comprises a hood extending over the outlet of the annular cooling passage, wherein the hood extends into the bypass passage to reduce a static pressure at the outlet of the annular cooling passage.
 13. The gas turbine engine of claim 1, wherein the turbomachine comprises an ejector positioned in airflow communication with the cooling passage, wherein the ejector is in airflow communication with a high pressure air source.
 14. The gas turbine engine of claim 13, wherein the turbomachine comprises a variable bleed assembly, and wherein the high pressure air source is the variable bleed assembly.
 15. The gas turbine engine of claim 1, wherein during operating of the gas turbine engine at a first operating condition, the annular cooling passage is configured to receive between 2% and 20% of a total airflow through the working gas flowpath at a location upstream of the inlet.
 16. The gas turbine engine of claim 15, wherein the first operating condition is a takeoff operating condition.
 17. The gas turbine engine of claim 1, wherein during operating of the gas turbine engine at a first operating condition, the annular cooling passage is configured to receive between 4% and 12% of a total airflow through the working gas flowpath at a location upstream of the inlet.
 18. The gas turbine engine of claim 1, wherein the gas turbine engine is a ducted turbofan engine.
 19. The gas turbine engine of claim 1, further comprising: a reduction gearbox, wherein the turbomachine is drivingly coupled to the fan through the reduction gearbox.
-