

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12416451
B2
September 16, 2025
Lin; Yu-Ming et al.

Multi-loop cycling heat dissipation module

Abstract

A multi-loop cycling heat dissipation module including a first tank, a first pipe, a second tank, and a second pipe is provided. The first pipe is connected to the first tank to form a first loop, a first working fluid fills the first loop to transfer heat via phase transformation, and a first high-temperature section and a first low-temperature section are formed on the first pipe. The second pipe is connected to the second tank to form a second loop, a second working fluid fills the second loop to transfer heat via phase transformation, and a second high-temperature section and a second low-temperature section are formed on the second pipe. The first high-temperature section is in thermal contact with the second low-temperature section, and the first low-temperature section is in thermal contact with the second high-temperature section.

Inventors: Lin; Yu-Ming (New Taipei, TW), Liao; Wen-Neng (New Taipei, TW), Hsieh; Cheng-Wen (New Taipei, TW), Wang; Chun-Chieh (New Taipei, TW), Chen; Tsung-Ting (New Taipei, TW), Ho; Chi-Tai (New Taipei, TW), Chen; Kuan-Lin (New Taipei, TW), Ke; Jau-Han (New Taipei, TW)

Applicant: Acer Incorporated (New Taipei, TW)

Family ID: 1000008818394

Assignee: Acer Incorporated (New Taipei, TW)

Appl. No.: 17/711069

Filed: April 01, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220325962 A1	Oct. 13, 2022

Foreign Application Priority Data

TW	110112549	Apr. 07, 2021
----	-----------	---------------

Publication Classification

Int. Cl.: F28D15/02 (20060101); F28D15/04 (20060101)

U.S. Cl.:

CPC F28D15/0266 (20130101); F28D15/0275 (20130101); F28D15/046 (20130101);

Field of Classification Search

CPC: F28D (15/0266); F28D (15/0275); F28D (15/046)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2012/0024499	12/2011	Chang	165/104.34	F28F 13/06
2019/0017749	12/2018	Kurashima	N/A	N/A
2020/0064077	12/2019	Machida	N/A	F28D 15/0233

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
108172558	12/2017	CN	N/A
M534957	12/2016	TW	N/A

Primary Examiner: Atkisson; Jianying C

Assistant Examiner: Samiri; Khaled Ahmed Ali Al

Attorney, Agent or Firm: JCIPRNET

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims the priority benefit of Taiwan application serial no. 110112549, filed on Apr. 7, 2021. The entirety of the above-mentioned patent application is hereby incorporated by reference herein and made a part of this specification.

BACKGROUND

Technical Field

(2) The disclosure relates to a heat dissipation module, and particularly relates to a multi-loop cycling heat dissipation module.

Description of Related Art

(3) Along with advancement of science and technology, portable electronic apparatuses, such as notebook computers, tablet PCs, or smart phones, are developed toward a trend of lightness and thinness. The light and thin appearances have made these electronic apparatuses be ideal for users to carry and operate. Furthermore, in order to improve processing efficiency of tablet PCs, performance of central processing units of motherboards is improved as well. Nevertheless, such improvement often leads to generation of a large amount of heat and thereby causes crashes of

circuits or electronic devices of an electronic apparatus as affected by overheating, and an inconvenient using experience is provided as a result.

(4) Generally, the heat dissipation modules arranged in the electronic apparatuses include air-cooled heat dissipation modules and water-cooled heat dissipation modules. The water-cooled heat dissipation modules are more efficient. However, under the design and development trend of the aforementioned portable electronic apparatuses toward lightness, thinness, shortness, and compactness, how to arrange the corresponding heat dissipation module in an apparatus body with limited space while maintaining its heat dissipation efficiency is an important issue.

SUMMARY

(5) The disclosure is directed to a multi-loop cycling heat dissipation module providing improved overall heat dissipation capacity.

(6) The disclosure provides a multi-loop cycling heat dissipation module including a first tank, a first pipe, a second tank, and a second pipe. The first pipe is connected to the first tank to form a first loop. A first working fluid fills the first loop to transfer heat via phase transformation, and a first high-temperature section and a first low-temperature section are formed on the first pipe. The second pipe is connected to the second tank to form a second loop. A second working fluid fills the second loop to transfer heat via phase transformation, and a second high-temperature section and a second low-temperature section are formed on the second pipe. The first high-temperature section is in thermal contact with the second low-temperature section, and the first low-temperature section is in thermal contact with the second high-temperature section.

(7) Based on the above description, the heat dissipation module is formed by a multi-loop cycling arrangement and is filled with corresponding working fluids, so that these loops are independent single loops. More importantly, in the independent loops, the heat dissipation module of the disclosure further combines the high-temperature sections and the low-temperature sections of the pipes by means of thermal contact. Accordingly, the high-temperature section of one loop may further transfer heat to the low-temperature section of another loop, a temperature equalization effect is thereby provided to the entire heat dissipation module, and the overall heat dissipation capacity of the heat dissipation module is effectively improved. In other words, by slowing down a temperature dropping degree of a single loop and providing an additional heat dissipation path, the overall heat dissipation performance of the heat dissipation module is improved accordingly, such that the heat generated by a heat source of an electronic apparatus is quickly transferred to an external environment, and heat is prevented from accumulating on a local part of the electronic apparatus.

(8) To make the aforementioned more comprehensible, several embodiments accompanied with drawings are described in detail as follows.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawings are included to provide a further understanding of the disclosure, and are incorporated in and constitute a part of this specification. The drawings illustrate embodiments of the disclosure and, together with the description, serve to explain the principles of the disclosure.

(2) FIG. 1 is a schematic diagram of a multi-loop cycling heat dissipation module according to an embodiment of the disclosure.

(3) FIG. 2 is a schematic diagram of an internal structural of a tank in the heat dissipation module of FIG. 1.

(4) FIG. 3 is a schematic diagram of a multi-loop cycling heat dissipation module according to another embodiment of the disclosure.

(5) FIG. 4 is a schematic diagram of a multi-loop cycling heat dissipation module according to another embodiment of the disclosure.

DESCRIPTION OF THE EMBODIMENTS

(6) FIG. 1 is a schematic diagram of a multi-loop cycling heat dissipation module according to an embodiment of the disclosure. Referring to FIG. 1, arrows shown next to loops act as a simple illustration of working fluids filling the loops. In this embodiment, a multi-loop cycling heat dissipation module **100** includes a first tank **110**, a first pipe **120**, a second tank **130**, and a second pipe **140**. The first pipe **120** is connected to the first tank **110** to form a first loop **P1**. A first working fluid **F1** fills the first loop **P1** to transfer heat via phase transformation. A first high-temperature section **H1** and a first low-temperature section **L1** are formed on the first pipe **120**. The second pipe **140** is connected to the second tank **130** to form a second loop **P2**. A second working fluid **F2** fills the second loop **P2** to transfer heat via phase transformation. A second high-temperature section **H2** and a second low-temperature section **L2** are formed on the second pipe **140**. The first high-temperature section **H1** is in thermal contact with the second low-temperature section **L2**, and the first low-temperature section **L1** is in thermal contact with the second high-temperature section **H2**.

(7) Further, the multi-loop cycling heat dissipation module **100** is suitable to be disposed in an electronic apparatus (e.g., a notebook computer or a tablet computer) to dissipate heat of a heat source **400** (e.g., a central processing unit or a display chip). The first tank **110** and the second tank **130** of this embodiment are in thermal contact with the heat source **400** to absorb heat generated by the heat source **400** and cause phase transformation (transition from a liquid phase to a vapor phase) of the first working fluid **F1** and the second working fluid **F2** respectively in the first tank **110** and the second tank **130**. In this way, the first working fluid **F1** and the second working fluid **F2** in the vapor phase respectively flow out of the first tank **110** and the second tank **130**, gradually dissipate heat and are transformed into the liquid phase during a travelling process in the first pipe **120** and the second pipe **140**, and accordingly flow back to the first tank **110** and the second tank **130** respectively to form a phase transformation cycle. As such, either the first loop **P1** or the second loop **P2** may provide the heat source **400** with a heat dissipation effect. Regarding the first loop **P1**, the first working fluid **F1** located in the first high-temperature section **H1** is in the vapor phase, the first working fluid **F1** located in the first low-temperature section **L1** is in the liquid phase, and a liquid and vapor coexisting state exists therebetween. Regarding the second circuit **P2**, the second working fluid **F2** in the second high-temperature section **H2** is in the vapor phase, the second working fluid **F2** in the second low-temperature section **L2** is in the liquid phase, and the liquid and vapor coexisting state exists therebetween.

(8) It should be noted that if the first loop **P1** and the second loop **P2** are considered separately, the temperature of the first low-temperature section **L1** and the temperature of the second low-temperature section **L2** are substantially close to an ambient temperature. In the case of a small temperature difference, an overall heat dissipation effect of such position is significantly reduced. In other words, if only the first loop **P1** or only the second loop **P2** is provided, overall heat dissipation performance may only depend on the phase transformation of the first working fluid **F1** in the first pipe **120** or the phase transformation of the second working fluid **F2** in the second pipe **140**, a performance bottleneck is thus generated in the current loop-type cycling heat dissipation module.

(9) In view of the above reason, this embodiment further combines the first loop **P1** and the second loop **P2** that are different from each other to form a thermal contact zone in the first high-temperature section **H1** and the second low-temperature section **L2** and form another thermal contact zone in the second high-temperature section **H2** and the first low-temperature section **L1**. In this way, heat exchange may be performed between the first high-temperature section **H1** and the second low-temperature section **L2**, and heat exchange may also be performed between the second high-temperature section **H2** and the first low-temperature section **L1**. By combining multiple

independent loops by the aforementioned means, a temperature equalization effect is provided to the entire multi-loop cycling heat dissipation module **100**. A temperature drop of each loop is slowed down, and an additional heat dissipation path is provided to the first high-temperature section **H1** and the second high-temperature section **H2**. As such a temperature difference between the multi-loop cycling heat dissipation module **100** and the external environment is produced (equivalent to increasing temperature difference regions between the multi-loop cycling heat dissipation module **100** and the external environment), so that the multi-loop cycling heat dissipation module **100** may easily dissipate the heat generated by the heat source **400** to the external environment.

(10) In this embodiment, a flow direction of the first working fluid **F1** in the first loop **P1** and a flow direction of the second working fluid **F2** in the second loop **P2** are opposite to each other. The first loop **P1** and the second loop **P2** are independent of each other and present inner and outer closed contours, so that the high- and low-temperature sections of the different loops may correspond to each other. Furthermore, the multi-loop cycling heat dissipation module **100** further includes a conduction member one **150** and a conduction member two **160**. The conduction member one **150** is connected between the first high-temperature section **H1** and the second low-temperature section **L2** to transfer the heat of the first high-temperature section **H1** to the second low-temperature section **L2**. The conduction member two **160** is connected between the second high-temperature section **H2** and the first low-temperature section **L1** to transfer the heat of the second high-temperature section **H2** to the first low-temperature section **L1**.

(11) Herein, the conduction member one **150** and the conduction member two **160** are, for example, heat pipes or components with thermal conductivity. For example, when the multi-loop cycling heat dissipation module **100** is applied to a notebook computer, the conduction member one **150** and the conduction member two **160** may be metal structures of an apparatus body or metal back plates or metal brackets disposed on the device body to facilitate the formation of the thermal contact zones of the aforementioned high- and low-temperature sections. Certainly, in other embodiments that are not shown, the first high-temperature section **H1** may also directly abut against the second low-temperature section **L2** in structure, and the second high-temperature section **H2** may directly abut against the first low-temperature section **L1** in structure to achieve direct heat transfer. Herein, the mutual thermal contact of the high- and low-temperature sections is not limited by the disclosure.

(12) In addition, the first tank **110** and the second tank **130** of this embodiment are an integral structure, i.e., belong to different chambers in a same structure member, and the different chambers are independent of each other and do not communicate with each other.

(13) FIG. 2 is a schematic diagram of an internal structural of a tank in the heat dissipation module of FIG. 1. Taking the first tank **110** as an example herein, the second tank **130** also has the same internal structure, so that description thereof is omitted. In this embodiment, the first tank **110** has a chamber **111** and a plurality of flow guiding members **112** arranged in the chamber **111**. The chamber **111** has an inlet **E1** and an outlet **E2**, and the flow guiding members **112** present a tapered profile from the inlet **E1** to the outlet **E2**. Alternatively, the flow guiding members **112** form a plurality of flow channels **113** tapered from the inlet **E1** to the outlet **E2** in the chamber **111**, so as to correspondingly control the first working fluid **F1** and the second working fluid **F2** to flow from the inlet **E1** to the outlet **E2**. In other words, the arrangement of the flow guiding members **112** in the chamber **111** may affect a flow direction of the working fluid (taking the first working fluid **F1** as an example) in the loop. Therefore, by adjusting the first tank **110** and the second tank **130** in the disclosure, the first loop **P1** and the second loop **P2** are formed the arrangement state shown in FIG. 1, so as to achieve the corresponding effect required by the high- and low-temperature sections.

(14) FIG. 3 is a schematic diagram of a multi-loop cycling heat dissipation module according to another embodiment of the disclosure. Referring to FIG. 3, in this embodiment, a multi-loop cycling heat dissipation module **200** includes a first tank **210**, a first pipe **220**, a second tank **230**, a

second pipe **240**, a first tank **250**, and a third pipe **260**. The first tank **210** is connected to the first pipe **220** to form a first loop **P11**, the second tank **230** is connected to the second pipe **240** to form a second loop **P21**, and the third tank **250** is connected to the third pipe **260** to form a third loop **P31**. A first working fluid **F11** fills the first loop **P11**, a second working fluid **F21** fills the second loop **P21**, and a third working fluid **F31** fills the third loop **P31**.

(15) With the same logic as the previous embodiments, in this embodiment, different independent loops are combined, and thermal contact is provided between the high- and low-temperature sections to facilitate heat transfer. Accordingly, a first high-temperature section **H11** of the first pipe **220** is in thermal contact with a third low-temperature section **L31** of the third pipe **260**, a first low-temperature section **L11** of the first pipe **220** is in thermal contact with a second high-temperature section **H21** of the second pipe **240**, and a third high-temperature section **H31** of the third pipe **260** is in thermal contact with a second low-temperature section **L21** of the second pipe **240**. In other words, as shown in FIG. 3, the first loop **P11**, the second loop **P21**, and the third loop **P31** form three thermal contact zones **271-273**, and these thermal contact zones **271-273** are the same as the thermal contact zones described in the above embodiments. Connection may be made through direct structural contact or through a thermal contact member to achieve the effect of transferring heat from the high-temperature section to the low-temperature section.

(16) The first tank **210**, the second tank **230**, and the third tank **250** are an integral structure. A flow direction of the first working fluid **F11** in the first loop **P11** and a flow direction of the second working fluid **F21** in the second loop **P21** are opposite to each other, and the flow direction of the first working fluid **F11** in the first loop **P11** and a flow direction of the third working fluid **F31** in the third loop **P31** are opposite to each other. As such, the second loop **P21** and the third loop **P31** are independent of and separated from each other and are both surrounded by the first loop **P11**.

(17) FIG. 4 is a schematic diagram of a multi-loop cycling heat dissipation module according to another embodiment of the disclosure. A difference between the aforementioned embodiments and this embodiment is that in a multi-loop cycling heat dissipation module **300** of the embodiment, a first tank **310** and a second tank **330** are structures separated from each other, and a first pipe **320** and a second pipe **340** are also separated from each other and paralleled to each other at the same time, and flow directions of the working fluids in the different loops are the same with each other. In other words, in this embodiment, the first tank **310**, the first pipe **320**, and the working fluid filling therein are used to dissipate heat of a heat source **410**. The second tank **330**, the second pipe **340**, and the working fluid filling therein are used to dissipate heat of a heat source **420**.

Meanwhile, the first tank **310** and the second tank **330** are further connected by a conduction member three **350** to achieve a heat transfer effect therebetween. More importantly, the first pipe **320** and the second pipe **340** also have thermal contact zones **360** and **370** for high- and low-temperatures sections. In brief, the independent loops shown in the multi-loop cycling heat dissipation module **300** of the embodiment may simultaneously achieve heat exchange through the conduction member three **350** and the thermal contact zones **360** and **370**. The aforementioned temperature equalization effect and overall heat dissipation capacity are thereby achieved.

(18) It should also be noted that in the tanks, the flow guiding members **112** shown in FIG. 2 may be applied in all embodiments shown in FIG. 1, FIG. 3, and FIG. 4 to make the flow directions of the working fluids flowing in the loops meet the needs.

(19) In view of the foregoing, the heat dissipation module of the disclosure is formed by multi-loop cycling arrangement and is filled with corresponding working fluids so that these loops are independent single loops. More importantly, in the independent loops, the heat dissipation module of the disclosure further combines the high-temperature sections and the low-temperature sections of the pipes by means of thermal contact. Accordingly, the high-temperature section of one loop may further transfer heat to the low-temperature section of another loop. In this way, an additional heat dissipation path is provided, and the temperature equalization effect is also provided to the entire heat dissipation module, so that the overall heat dissipation capacity of the heat dissipation

module is effectively improved. In other words, by slowing down the temperature dropping degree of a single loop and providing the additional heat dissipation path, the overall heat dissipation performance of the heat dissipation module is improved accordingly, the heat generated by the heat source of the electronic apparatus is quickly transferred to the external environment, and heat is prevented from accumulating on a local part of the electronic apparatus.

(20) It will be apparent to those skilled in the art that various modifications and variations can be made to the disclosed embodiments without departing from the scope or spirit of the disclosure. In view of the foregoing, it is intended that the disclosure covers modifications and variations provided that they fall within the scope of the following claims and their equivalents.

Claims

1. A multi-loop cycling heat dissipation module, comprising: a first tank; a first pipe, connected to the first tank to form a first loop, wherein a first working fluid fills the first loop to transfer heat via phase transformation, and a first high-temperature section and a first low-temperature section are formed on the first pipe; a second tank; a second pipe, connected to the second tank to form a second loop, wherein a second working fluid fills the second loop to transfer heat via phase transformation, and a second high-temperature section and a second low-temperature section are formed on the second pipe; a conduction member, connected between the first high-temperature section and the second low-temperature section to transfer heat of the first high-temperature section to the second low-temperature section; and another conduction member, connected between the second high-temperature section and the first low-temperature section to transfer heat of the second high-temperature section to the first low-temperature section, wherein the first high-temperature section is in thermal contact with the second low-temperature section, and the first low-temperature section is in thermal contact with the second high-temperature section, wherein the first high-temperature section abuts against the second low-temperature section in structure, and the second high-temperature section abuts against the first low-temperature section in structure, wherein each of the first tank and the second tank respectively has a chamber and a plurality of flow guiding members arranged in each chamber, each chamber has an inlet and an outlet, and the flow guiding members are protruded sections in each of each chamber that form flow channels with tapered profile from the inlet to the outlet, so as to correspondingly control the first working fluid and the second working fluid to flow from the inlet to the outlet, wherein the protruded sections are arranged laterally and next to each other at middle and outer sides and therebetween, and each extends from the inlet toward the outlet, starting ends of the protruded sections located at middle and outer sides of the chamber are closer to the inlet than starting ends of the protruded sections located therebetween, terminal ends of the protruded sections come together to be adjacent with each other, each of the protruded sections has a thickness increasing and then decreasing on a direction from the inlet to the outlet, and a dimension of an entrance of each flow channel is greater than a dimension of an exit of each flow channel so as to speed up the first working fluid in the first tank and the second working fluid in the second tank.
 2. The multi-loop cycling heat dissipation module according to claim 1, wherein a flow direction of the first working fluid in the first loop and a flow direction of the second working fluid in the second loop are opposite to each other.
 3. The multi-loop cycling heat dissipation module according to claim 1, wherein the first loop and the second loop are independent of each other and the first loop and second loop each presents a closed contour where the first loop is an inner loop and the second loop is an outer loop.
 4. The multi-loop cycling heat dissipation module according to claim 1, wherein the first tank and the second tank are an integral structure.
-