

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416862
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Wang; Po-Han et al.

Apparatus, system and method

Abstract

An apparatus and a method for effectively exhausting evaporated material are provided. In an embodiment the apparatus includes a hot plate and an exhaust hood assembly suspended over the hot plate. The exhaust hood assembly includes a trench plate, a cover plate over the trench plate and a single exhaust pipe header over and attached to a single exhaust opening of the cover plate. During operation, the exhaust hood assembly reduces the amount of condensation and also collects any remaining condensation in order to help prevent condensation from impacting further manufacturing steps.

Inventors: Wang; Po-Han (Hsinchu, TW), Hu; Yu-Hsiang (Hsinchu, TW), Kuo; Hung-Jui (Hsinchu, TW), Yu; Chen-Hua (Hsinchu, TW)

Applicant: Taiwan Semiconductor Manufacturing Co., Ltd. (Hsinchu, TW)

Family ID: 1000008818339

Assignee: Taiwan Semiconductor Manufacturing Company, Ltd. (Hsinchu, TW)

Appl. No.: 18/447104

Filed: August 09, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230384682 A1	Nov. 30, 2023

Related U.S. Application Data

division parent-doc US 16806468 20200302 US 12242197 child-doc US 18447104
us-provisional-application US 62869515 20190701

Publication Classification

Int. Cl.: G03F7/38 (20060101); G03F7/00 (20060101); H01L21/027 (20060101)

U.S. Cl.:

CPC G03F7/38 (20130101); G03F7/70908 (20130101); H01L21/0273 (20130101);

Field of Classification Search

CPC: G03F (7/38); G03F (7/70908); G03F (7/70916)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2002/0064380	12/2001	Reiker	N/A	N/A
2005/0195480	12/2004	Brown et al.	N/A	N/A
2009/0095221	12/2008	Tam et al.	N/A	N/A
2009/0181226	12/2008	Ning et al.	N/A	N/A
2010/0025856	12/2009	Kawamura	257/773	H01L 21/02304
2010/0255428	12/2009	Chen et al.	N/A	N/A
2012/0000490	12/2011	Chung	134/22.12	C23C 16/45576
2012/0161405	12/2011	Mohn et al.	N/A	N/A
2017/0101713	12/2016	Wang et al.	N/A	N/A

Primary Examiner: Chacko-Davis; Daborah

Attorney, Agent or Firm: Slater Matsil, LLP

Background/Summary

PRIORITY CLAIM (1) This application is a divisional of U.S. patent application Ser. No. 16/806,468, filed on Mar. 2, 2020, entitled “Apparatus, System and Method,” which claims the benefit of U.S. Provisional Application No. 62/869,515, filed on Jul. 1, 2019, which applications are hereby incorporated herein by reference.

BACKGROUND

- (1) Integrated circuits comprising semiconductor devices are used in a variety of electronic applications, such as, for example, personal computers, cell phones, digital cameras, and other electronic equipment. Semiconductor devices are typically fabricated by sequentially depositing insulating or dielectric layers, conductive layers, and semiconductor layers of material over a semiconductor substrate, and patterning the various material layers using lithography to form circuit components and elements thereon. A series of chemical and physical processes may be performed during the fabrication process flow, using equipment with processing chambers that are often maintained at low pressure or partial vacuum.
- (2) The integrated circuit industry continues to improve the integration density of various electronic components (e.g., transistors, diodes, resistors, capacitors, etc.) by continual reduction in minimum

feature size, which allows more components to be integrated into a given area, thereby lowering the cost of integrated circuits. Maintaining continual reduction in manufacturing cost requires a high efficiency integrated circuit fabrication facility and infrastructure that may give rise to additional problems that should be addressed.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Aspects of the present disclosure are best understood from the following detailed description when read with the accompanying figures. It is noted that, in accordance with the standard practice in the industry, various features are not drawn to scale. In fact, the dimensions of the various features may be arbitrarily increased or reduced for clarity of discussion.

(2) FIG. 1 illustrates a photoresist track system in accordance with an embodiment;

(3) FIG. 2A-2B illustrates an application of a photoresist in accordance with an embodiment;

(4) FIGS. 3A-3H illustrate various views of a pre-bake station used during a pre-bake process, and various views of some components of the pre-bake station, in accordance with an embodiment;

(5) FIG. 4 illustrates an exposure process of the photoresist in accordance with an embodiment;

(6) FIG. 5 illustrates a post-exposure baking process in accordance with an embodiment;

(7) FIGS. 6A-6C illustrate a development process of the photoresist in accordance with an embodiment;

(8) FIG. 7 illustrates a hard bake process in accordance with an embodiment;

(9) FIGS. 8A-8C illustrate cross-sectional views of the trench plate of FIG. 3C taken through the cut-line C-C' in accordance with some other embodiments; and

(10) FIGS. 9A-9B illustrate top-down views of trench plates in accordance with still some other embodiments.

DETAILED DESCRIPTION

(11) The following disclosure provides many different embodiments, or examples, for implementing different features of the invention. Specific examples of components and arrangements are described below to simplify the present disclosure. These are, of course, merely examples and are not intended to be limiting. For example, the formation of a first feature over or on a second feature in the description that follows may include embodiments in which the first and second features are formed in direct contact, and may also include embodiments in which additional features may be formed between the first and second features, such that the first and second features may not be in direct contact. In addition, the present disclosure may repeat reference numerals and/or letters in the various examples. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship between the various embodiments and/or configurations discussed.

(12) Further, spatially relative terms, such as “beneath,” “below,” “lower,” “above,” “upper” and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. The spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. The apparatus may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein may likewise be interpreted accordingly.

(13) Embodiments will be described with respect to a specific context, namely a wafer baking station utilized in the manufacturing of semiconductor devices. The wafer baking station described herein may be any semiconductor wafer baking apparatus such as a pre-development bake station (e.g., pre-bake station), a post-development station (e.g., post-bake station), a hard bake station, a diffusion bake station, or the like. Features of one embodiment may also be applied and suitably

incorporated as features of other embodiments described herein. Other embodiments may also be applied, however, to other manufacturing apparatuses.

(14) With reference now to FIG. 1, there is shown a photoresist track system **100** with a first loadlock chamber **102**, a coating station **101**, a pre-bake station **103**, an exposure station **105**, a post-bake station **107**, a developer station **109**, an optional hard bake station **111**, a plurality of the transfer stations **104**, and a second loadlock chamber **114**. In an embodiment, the photoresist track system **100** is a track system for processing a substrate **201** (not illustrated in FIG. 1 but illustrated and discussed below with respect to FIG. 2B), and is a self-enclosed, fully contained system into which the substrate **201** may be initially placed. Once within the photoresist track system **100**, the substrate **201** may be moved from station to station and processed without breaking the interior environment, thereby isolating the substrate **201** from the ambient environment that may contaminate or otherwise interfere with the processing of the substrate **201**.

(15) In an embodiment, the photoresist track system **100** receives the substrate **201** into the photoresist track system **100** through, e.g., the first loadlock chamber **102**. The first loadlock chamber **102** opens to the exterior atmosphere and receives the substrate **201**. Once the substrate **201** is located within the first loadlock chamber **102**, the first loadlock chamber **102** can close, isolating the substrate **201** from the exterior atmosphere. Once isolated, the first loadlock chamber **102** can then have the remaining exterior atmosphere evacuated in preparation for moving the substrate **201** into the remainder of the photoresist track system **100** through, e.g., a transfer station **104**.

(16) The transfer station **104** may be one or more robotic arms (not individually illustrated in FIG. 1) that can grip, move, and transfer the substrate **201** from the first loadlock chamber **102** to, e.g., the coating station **101**. In an embodiment, the robotic arms may extend into the first loadlock chamber **102**, grip the substrate **201**, and transfer the substrate **201** into the transfer station **104**. Once inside, the transfer station **104** may have doors that close to isolate the transfer station **104** from the first loadlock chamber **102** so that the first loadlock chamber **102** may again be opened to the exterior atmosphere without contaminating the remainder of the photoresist track system **100**. Once isolated from the first loadlock chamber **102**, the transfer station **104** may open to the next station, e.g., the coating station **101**, and the robotic arms, still holding the substrate **201**, may extend into the next station and place the substrate **201** for further processing.

(17) In an embodiment, and as illustrated in FIG. 1, the transfer station **104** between the first loadlock chamber **102** and the coating station **101** transfers the substrate **201** directly from the first loadlock chamber **102** into the coating station **101**. However, other processing stations (e.g., process chambers) may be located between the first loadlock chamber **102** and the coating station **101**. For example, cleaning stations, temperature control stations, or any other type of station which may be used to prepare the substrate **201** to receive a photoresist **211** (not illustrated in FIG. 1 but illustrated and discussed below with respect to FIG. 2B) may also be included. Any suitable type or number of stations may be used, and all such stations are fully intended to be included within the scope of the embodiments.

(18) Additionally, FIG. 1 illustrates a plurality of separate transfer stations **104** respectively between each of the processing stations (e.g., between the first loadlock chamber **102** and the coating station **101**, between the coating station **101** and the exposure station **105**, etc.). However, this is intended to be illustrative and is not intended to be limiting upon the embodiments. The precise number of transfer stations will depend at least in part upon the overall structural layout of the various processing stations. For example, if the processing stations are arranged in a linear fashion (as illustrated in FIG. 1), then there may be individual transfer stations between each process station of the photoresist track system **100**. However, in other embodiments in which the various processing stations or groups of processing stations are arranged, e.g., in one or more circles, then a single transfer station may be utilized to move the substrates being processed (e.g., substrate **201**) into and out of the various process chambers. All such arrangements are fully

intended to be included within the scope of the embodiments.

(19) FIG. 2A illustrates a top view of one embodiment of the coating station **101** into which the transfer station **104** places the substrate **201**, and FIG. 2B illustrating a cross-sectional view of the substrate **201** after being processed within the coating station **101**. In an embodiment, the coating station **101** is a spin-on station and comprises a rotating chuck **202**, a dispensing arm **204**, and a track **206**. The rotating chuck **202** receives the substrate **201** from the transfer station **104** and holds the substrate **201** during processing.

(20) The dispensing arm **204** has a nozzle **208** in order to dispense photoresist **211** onto the substrate **201**. In an embodiment, the dispensing arm **204** may be moveable relative to the rotating chuck **202** so that the dispensing arm **204** can move over the substrate **201** (illustrated in FIG. 2A by the arrow and dispensing arm illustrated in dashed lines) in order to evenly dispense the photoresist **211**. The dispensing arm **204** may move back and forth with the help of the track **206**, which provides a fixed reference to assist the dispensing arm **204** in its movement.

(21) During operation, the rotating chuck **202**, holding the substrate **201**, can rotate at a speed of about 300 rpms to about 7000 rpms, although any suitable speed may be utilized. While the rotating chuck **202** is rotating, the dispensing arm **204** may move over the substrate **201** and begin dispensing the photoresist **211** onto the substrate **201** through the nozzle **208**. The rotation of the substrate **201** helps the photoresist **211** spread evenly across the substrate **201**, such as to a thickness of between about 10 nm and about 300 nm, such as about 150 nm.

(22) However, the spin-on configuration illustrated in FIG. 2A and described above is intended to be illustrative only and is not intended to limit the embodiments. Rather, any suitable configuration for the coating station **101** that may be used to apply the photoresist **211**, such as a dip coating configuration, an air-knife coating configuration, a curtain coating configuration, a wire-bar coating configuration, a gravure coating configuration, a lamination configuration, an extrusion coating configuration, combinations of these, or the like, may also be utilized. All such suitable configurations for the coating station **101** are fully intended to be included within the scope of the embodiments.

(23) FIG. 2B illustrates a semiconductor device **200** with the substrate **201** after the dispensing of the photoresist **211**. Also illustrated as being formed on the substrate **201** (prior to the application of the photoresist **211**) are active devices **203** on the substrate **201**, an interlayer dielectric (ILD) layer (e.g., the ILD layer **205**) over the active devices **203**, metallization layers **207** over the ILD layer **205**, and a layer to be patterned **209** over the ILD layer **205**. The substrate **201** may comprise bulk silicon, doped or undoped, or an active layer of a silicon-on-insulator (SOI) substrate. Generally, an SOI substrate comprises a layer of a semiconductor material such as silicon, germanium, silicon germanium, SOI, silicon germanium on insulator (SGOI), or combinations thereof. Other substrates that may be used include multi-layered substrates, gradient substrates, or hybrid orientation substrates.

(24) The active devices **203** are represented in FIG. 2B as a single transistor for illustration purpose. However, a wide variety of active devices such as capacitors, resistors, inductors and the like may be used to generate the desired structural and functional requirements of the design for the semiconductor device **200**. The active devices **203** may be formed using any suitable methods either within or else on the surface of the substrate **201**.

(25) The ILD layer **205** may comprise a material such as boron phosphorous silicate glass (BPSG), although any suitable dielectrics may be used for either layer. The ILD layer **205** may be formed using a process such as PECVD, although other processes, such as LPCVD, may also be used. The ILD layer **205** may be formed to a thickness of between about 100 Å and about 3,000 Å.

(26) The metallization layers **207** are formed over the substrate **201**, the active devices **203**, and the ILD layer **205**, and are designed to connect the active devices **203** to form functional circuitry. While illustrated in FIG. 2B as a single layer, the metallization layers **207** may be formed of alternating layers of dielectric and conductive material, and may be formed through any suitable

process (such as deposition, damascene, dual damascene, etc.). In an embodiment, there may be four to twelve layers of metallization separated from the substrate **201** by the ILD layer **205**, but the precise number of metallization layers **207** is dependent upon the design of the semiconductor device **200**.

(27) The layer to be patterned **209** or otherwise processed using the photoresist **211** is formed over the metallization layers **207**. The layer to be patterned **209** may be an upper layer of the metallization layers **207**, a dielectric layer (such as a passivation layer) formed over the metallization layers **207**, or may even be the substrate **201** itself. In an embodiment, in which the layer to be patterned **209** is a metallization layer, the layer to be patterned **209** may be formed of a conductive material using processes similar to the processes used for the metallization layers (e.g., damascene, dual damascene, deposition, etc.). Also, if the layer to be patterned **209** is a dielectric layer, it may be formed of a dielectric material using processes such as deposition, oxidation, or the like.

(28) However, while materials, processes, and other details are described in the embodiments, they are merely intended to be illustrative of embodiments, and are not intended to be limiting in any fashion. Rather, any suitable layer made of any suitable material, by any suitable process, and any suitable thickness, may also be used. All such layers are fully intended to be included within the scope of the embodiments.

(29) The photoresist **211** is applied to the layer to be patterned **209**. In an embodiment the photoresist **211** includes a polymer resin along with one or more photoactive compounds (PACs) in a solvent. Additionally, if desired, other additives, such as cross-linking additives, surfactants, etc. may also be included within the solvent and the photoresist **211**. Any suitable composition may be utilized.

(30) FIGS. 3A-3H illustrate various views of the pre-bake station **103** and various views of some components of the pre-bake station **103** with respect to different cut-lines, according to some embodiments. In particular, FIG. 3A illustrates a cross-sectional view of the pre-bake station **103** through a first cut-line A-A', FIG. 3B illustrates a top view of a hot plate **301** of the pre-bake station **103**, and FIG. 3C illustrates a top view of a trench plate **320** (e.g., a first cover plate, a vented cover disk, or the like) of the pre-bake station **103**, respectively. FIGS. 3D-3E illustrate cross-sectional views of the pre-bake station **103** through a second cut-line B-B' and through a third cut-line C-C', respectively. FIGS. 3F-3G illustrate a bottom view of a cover plate **340** (e.g., a second cover plate, an exhaust cover disk, or the like) of the pre-bake station **103** and a magnified view of a portion of the bottom view of the cover plate **340**, respectively. FIG. 3H illustrates an exploded view of an exhaust hood assembly **380** of the pre-bake station **103**.

(31) FIG. 3A illustrates the pre-bake station **103** into which the substrate **201** with the photoresist **211** (not specifically illustrated in FIG. 3A) thereon, may be moved (through the transfer station **104**) once the photoresist **211** has been applied to the substrate **201**. According to some embodiments, the robotic arm of the transfer station **104** places the substrate **201** on the hot plate **301** of the pre-bake station **103** in preparation for further processing. The hot plate **301** raises the temperature of the substrate **201** and photoresist **211** in order to cure and dry the photoresist **211** prior to exposure to finish the application of the photoresist **211**.

(32) The pre-bake station **103** may be connected, for example, to intake pipes (not shown) in order to introduce air into the pre-bake station **103**. The pre-bake station **103** may also be connected, for example, to one or more exhaust pipes (not shown) and one or more dampers (not shown) to assist in the evacuation and to vary a flow rate of volatile by-products of the pre-bake process **300**, such as components of the evaporated solvent (illustrated by the directional arrows in FIG. 3A), from the pre-bake station **103**.

(33) The curing and drying of the photoresist **211** removes the solvent components while leaving behind the polymer resin, the PACs, cross-linking agents, and other chosen additives. In an embodiment, a pre-bake process **300** may be performed at a temperature suitable to evaporate the

solvent(s), such as between about 40° C. and 150° C., although the precise temperature depends at least in part upon the materials chosen for the photoresist **211**. The pre-bake process **300** is performed for a time sufficient to cure and dry the photoresist **211**, such as between about 10 seconds to about 10 minutes, such as about 90 seconds. As the solvent evaporates during the pre-bake process **300**, the vapor of the evaporated solvent rises (as illustrated in FIG. 3A by the directional arrows) and ultimately escapes through the trench plate **320** and through the exhaust hood assembly **380**.

(34) However, as the vapors of the evaporated solvent rise, there is a possibility that the vapors will cool down so much that the vapors will condense before the vapors exhaust from the pre-bake station **103**. In some cases, these condensed vapors, now becoming liquid again, can either drop onto the wafer currently being processed, drop onto the next semiconductor wafer in the process, or else interfere with the exhaust flow. By falling back down to the substrate **201** (or subsequent substrates), the condensed liquid can interfere with the desired evaporation and drying process. Such interference can interfere with subsequent processes, thereby causing undesired defects within the manufactured device(s).

(35) To help alleviate or prevent these defects, the exhaust hood assembly can be designed to both minimize the amount of condensation and the undesired effects due to the condensation. In an embodiment, the exhaust hood assembly **380** secures and suspends the trench plate **320** over the substrate **201** during baking processes (e.g., the pre-bake process **300**). According to some embodiments, the exhaust hood assembly **380** comprises a retaining ring **330**, the trench plate **320**, a cover plate **340**, an exhaust pipe header **350**, and an exhaust hood heater **360**.

(36) The retaining ring **330** secures the trench plate **320** to the cover plate **340**. According to some embodiments, the trench plate **320** is secured by the retaining ring **330** to the cover plate **340** using fasteners (e.g., screws, threaded bolts, and the like). However, any suitable fasteners and/or any suitable way to secure the trench plate **320** between the retaining ring **330** and the cover plate **340** (e.g., clamping, snap-fitting, and the like) may also be used.

(37) In an embodiment, the trench plate **320** comprises ridges **321**, trenches **325** and vent holes **323**. According to embodiments, the vent holes **323** are located in the ridges **321** and extend through the ridges **321** and the trench plate **320** from the top of the ridges **321** to the bottom surface of the trench plate **320** opposite the top surfaces of the ridges **321**. In some embodiments, the bottom surface of the trench plate **320** is substantially planar (within the range of manufacturing deviation); however, any suitable shape may be used. During baking processes (e.g., the pre-bake process **300**), as vapor forms and rises from the evaporated solvent, the vapor escapes through the vent holes **323** of the trench plate **320** and makes its way up towards the cover plate **340**.

(38) The cover plate **340** serves as a lid covering the trench plate **320** with inner sidewalls of the cover plate **340**, forming a first angle $\theta 1$ with the upper surface of the trench plate **320**. According to some embodiments, the first angle $\theta 1$ is between about 30° and about 90°, such as about 90°. However, any suitable angle may be used. The cover plate **340** further comprises grooves **343** and an opening **317**. During baking processes (e.g., the pre-bake process **300**), the inner sidewalls of the cover plate **340** and the grooves **343** located in the inner sidewalls of the cover plate **340** aid in directing the vapor escaping through vent holes **323** of the trench plate **320** to the opening **317** in the cover plate **340** where the exhaust pipe header **350** is attached. According to some embodiments, the opening **317** in the cover plate **340** comprises a first diameter DIA1 of between about 20 mm and about 40 mm, such as about 30 mm, and the exhaust pipe header **350** is sized to fit the opening **317** of the cover plate **340**. However, any suitable dimensions may be used for the opening **317** of the cover plate **340** and the exhaust pipe header **350**.

(39) According to embodiments, the exhaust hood assembly **380** comprises a single pipe for the exhaust pipe header **350** attached to the opening **317** in the cover plate **340**. The opening **317** and the exhaust pipe header **350** are of sufficient size to maintain a flow level and exhaust efficiency for evacuating vapor from the exhaust hood assembly **380** during bake processes. In an embodiment

the flow level may be between about 20 Pa and about 500 Pa, such as about 300 Pa. However, any suitable flow level may be utilized.

(40) In an embodiment the exhaust pipe header **350** may be integrally formed with the cover plate **340** or may be attached to the cover plate **340**. According to some embodiments, the exhaust pipe header **350** comprises the same diameter or substantially the same diameter as the first diameter **DIA1** and is between about 20 mm and about 40 mm, such as about 30 mm. However, any suitable diameter may be utilized.

(41) The design of the cover plate **340** and the exhaust pipe header **350** with a large opening may further facilitate the exhaust flow, because the flow level may be maintained at a high level in order to remove the vapors from the exhaust hood assembly **380** as quickly as possible. With such a quick removal, it significantly reduces the time for the vapors to cool down before exhausted, thereby reducing the possibility of the vapors condensing. As such, with less condensation, fewer defects from condensing liquids can be achieved in the final manufactured product. In addition, due to the large opening, the condensed vapors at the pipe may not block the opening. For example, because the vapors escape rapidly through the single large opening of the exhaust pipe header **350**, less vapor accumulates at the surface of the cover plate **340** as compared to a design having a plurality of exhaust headers with relatively small openings and a restrictive exhaust flow.

(42) Additionally, in an effort to help increase the exhaust flow rate of the vapors out of the exhaust hood assembly before the vapors can condense, in some embodiments, the surfaces of the cover plate **340**, the exhaust pipe header **350**, and the trench plate **320** can be coated with a layer of nonstick coating to help reduce the friction and allow the vapors to flow faster out of the exhaust pipe header **350**. In an embodiment, the nonstick coating may comprise a non-stick material with a low coefficient of friction as well as hydrophobic properties such as polytetrafluoroethylene (PTFE), fluorinated ethylene propylene (FEP), perfluoroalkoxy (PFA), other fluorocarbons, combinations of these, or the like. However, any suitable material may be utilized.

(43) The low coefficient of friction and hydrophobic properties of the nonstick coating, during bake processes, help reduce the amount of solvent vapor that condenses and wets these surfaces when the chemical solvent vapor comes in contact the cover plate **340**, the exhaust pipe header **350**, and the trench plate **320**. As such, the nonstick coating aids in the evacuation of the vapor through the vent holes **323** of the trench plate **320** and through the exhaust hood assembly **380**, which provides greater exhaust efficiency during bake processes. During the baking process or even after the bake processes, and when the exhaust hood assembly **380** begins to cool down, the amount of a residue of the evaporated solvent that forms on these inner surfaces is minimized. As such, damages caused by residue falling onto the substrate **201** during processing or falling onto subsequently processed workpieces during subsequent bake processes are also minimized or are altogether eliminated.

(44) FIG. 3A further illustrates the exhaust hood heater **360** being fixed to an outer surface of the cover plate **340**. In some embodiments, the exhaust hood heater **360** may be a resistive heating element, and may comprise one or more layers of suitable resistive materials, such as mica, quartz, polyimide, silicone rubber, semiconductor heater materials, metallic alloys, ceramic materials, ceramic metals, a combination thereof, or the like. During bake processes (e.g., the pre-bake process **300**), the exhaust hood heater **360** heats the cover plate **340** and the exhaust pipe header **350** to suitable temperatures in order to allow the evaporated solvent escape through the trench plate **320** as a vapor. According to some embodiments, the exhaust hood heater **360** heats the cover plate **340** and the exhaust pipe header **350** to a bake temperature of between about 40° C. and 150° C., although the precise temperature depends upon the thermal characteristics of the materials chosen for the photoresist **211**. As such, during bake processes, the exhaust hood heater **360** further aids in the evacuation of the vapor from the exhaust hood assembly **380**, which increases an exhaust efficiency of the pre-bake station **103** and further minimizes the amount of residue that forms from the evaporated solvent on the inner surfaces of the cover plate **340** and the exhaust pipe header **350**.

(45) FIG. 3A also illustrates trenches **325**, which are utilized to further reduce the possibility of the condensed vapors (if any) from reaching the substrate **201**. In an embodiment, the trenches **325** are utilized to help capture the condensed vapors therein (instead of simply letting the condensed vapors flow into the vent holes **323**). In an embodiment, the trenches **325** comprise substantially (within the range of manufacturing deviation) flat bottoms and angled sidewalls. According to some embodiments, the trenches **325** have a first width $W1$ of between about 1 mm and about 60 mm, such as about 30 mm, a first depth $D1$ of between about 1 mm and about 20 mm, such as about 5 mm, and angled sidewalls having second angles $\theta2$ of between about 45° and about 90° , such as about 90° . However, any suitable widths, any suitable depths and any suitable angles may be used for the trenches **325**.

(46) FIG. 3A further illustrates residue **390** from the evaporated solvent that forms on the inner surfaces of the cover plate **340** and the exhaust pipe header **350** either during the bake processes or after the bake processes are completed, and temperatures within the pre-bake station **103** begin to cool down. As the residue **390** condenses and falls towards the trench plate **320**, the residue **390** is collected on the upper surfaces of the trench plate **320**. With the trenches **325** separating the vent holes **323**, any residue **390** that is condensed but not directly over the vent holes **323** will not flow into/through the vent holes **323**; instead, it will be collected within the trenches **325** of the trench plate **320**. As such, this prevents the residue **390** from flowing through the vent holes **323** dripping onto the substrate **201**, and causing damage to the substrate **201**.

(47) FIG. 3B illustrates a top view of the hot plate **301**, according to an embodiment. In some embodiments, heating elements **305** such as resistive heating elements may be located within the hot plate **301**. The heating elements **305** raise the temperature of the hot plate **301** during the bake processes. FIG. 3B further illustrates the cutline A-A' through the hot plate **301** relative to the cut lines A-A' illustrated in FIGS. 3A and 3C.

(48) With reference now to FIG. 3C, this figure illustrates a top view of the trench plate **320** in an embodiment. According to some embodiments, the trench plate **320** is integrally formed as a single structure with the trenches **325** being separated from one another by the ridges **321**. According to some embodiments, the trench plate **320** (e.g., vented cover disk) is annular in shape (e.g., a circular plate, a disk, or the like) having a second diameter $DIA2$ of between about 180 mm and about 320 mm. However, any suitable shape and any suitable diameter may be used for the trench plate **320**. According to some embodiments, the vent holes **323** are aligned radially along centerlines. In some embodiments, the vent holes **323** have the same size diameters. According to some embodiments, the diameters of the vent holes **323** are between about 1 mm and about 20 mm. However, any suitable diameters may be utilized.

(49) In other embodiments, the vent holes **323** may have diameters of different sizes. For example, as illustrated in FIG. 3C, the diameters of vent holes **323** that are radially aligned may increase in size as they are located further distances from a center of the trench plate **320**. For example, the diameters of the vent holes **323** may increase between about 10 mm and about 50 mm, such as about 30 mm at each step away from the center. However, any suitable increase or decrease may be utilized.

(50) FIG. 3C further illustrates that, according to some embodiments, through holes **329** are located along an outer edge of the trench plate **320** and extend through the trench plate **320**. The trench plate **320** may have any suitable number (e.g., twelve) of through holes **329**. In some embodiments, fasteners (e.g., screws, threaded bolts, and the like) are used to extend through the through holes **329** of the trench plate **320** to connect the retaining ring **330** to the cover plate **340** with the trench plate **320** secured there between. The through holes **329** may be any suitable type (e.g., threaded, non-threaded, lined, elongated slots, and the like), any suitable shape, and any suitable size of through holes.

(51) FIG. 3C still further illustrates the first, second, and third cut-lines A-A', B-B' and C-C', respectively, which correlate to the cross-sectional views of the pre-bake station **103** in FIGS. 3A,

3D and 3E, respectively. The first cutline A-A' is taken through a centerline of an aligned series of the vent holes **323** in two of the ridges **321** extending radially in opposite directions from one another. The second cutline B-B' is taken through a centerline of three trenches **325** of the trench plate **320**. One of the three trenches **325** is located in a center region of the trench plate **320** and separates the other two of the three trenches **325**, and the other two of the three trenches **325** extend radially in opposite directions from one another. The third cutline C-C' is annularly shaped taken through a centerline of six of the vent holes **323** of six different ones of the ridges **321** separated by five different ones of the trenches **325** of the trench plate **320**, the six of the vent holes **323** being disposed a same radial distance from the center of the trench plate **320**.

(52) According to some embodiments, the trenches **325** comprise a plurality of outer trenches extending from an outer portion of the trench plate **320** towards an inner portion of the trench plate **320** and radially surrounding a center trench disposed at a center of the trench plate **320**. According to some embodiments, the center trench may have a first width W1 of between about 1 mm and about 60 mm, such as about 30 mm and the outer trenches may have a second width W2 of between about 10 mm and about 60 mm, such as about 50 mm. However, any suitable widths may be utilized. According to some embodiments, the outer trenches **325** may be separated from the inner trench **325** by a distance DIS1 of between about 1 mm and about 20 mm, such as about 5 mm. However, any suitable distances may be utilized.

(53) FIG. 3D illustrates the cross-sectional view of the pre-bake station **103** through the second cutline B-B' including three of the trenches **325** and four of the ridges **321** being integrally formed within the trench plate **320**. In the cross-sectional view of FIG. 3D, none of the vent holes **323** are shown, because the second cutline B-B' does not intersect any of the vent holes **323** which correlates to the second cutline B-B' illustrated in FIG. 3C. However, FIG. 3D does illustrate the through holes **329** located in the outer ring of the trench plate **320** because the second cutline B-B' intersects two of the through holes **329** which correlates to the second cutline B-B' illustrated in FIG. 3C.

(54) FIG. 3E illustrates the cross-sectional view of the pre-bake station **103** through the annular shaped third cutline C-C' taken through six of the vent holes **323** located in six different ones of the ridges **321** separated by five different ones of the trenches **325** of the trench plate **320**. In the cross-sectional view of FIG. 3E, the trench plate **320** appears to be separated from the cover plate **340** because the third cutline C-C' is taken through the pre-bake station **103** at points located at the same radial distance from the center of the pre-bake station **103**. As such, the third cutline C-C' does not intersect any points along the outermost one of the ridges **321** of the trench plate **320** at which the cover plate **340** meets the trench plate **320** which correlates to the third cutline C-C' illustrated in FIG. 3C. Furthermore, in FIG. 3E, the cover plate **340** and the exhaust hood heater **360** do not appear to be angled at the first angle θ_1 as illustrated in FIG. 3A, because the cross-section through the annular shape of the third cutline C-C' intersects points along the cover plate **340** and intersects points along the exhaust hood heater **360** at same respective distances above the substrate **201** which correlates to the third cutline C-C' illustrated in FIG. 3C.

(55) FIGS. 3F-3G illustrate a bottom view of the cover plate **340** of the pre-bake station **103** and a magnified bottom view of the exhaust pipe header **350** of the cover plate **340**, respectively. According to some embodiments, the cover plate **340** may have an outer dimension that is shaped and sized to match the outer dimension and shape of the trench plate **320**. As such, the cover plate **340** fits over the trench plate **320** with outer edges of the cover plate **340** being aligned with the outer edges of the trench plate **320**. In some embodiments, the cover plate **340** is annularly shaped with a third diameter DIA3 of between about 180 mm and about 320 mm. According to some embodiments, a surface of the cover plate **340** facing the trench plate **320**, as illustrated in FIG. 3A, may have a slight concave shape with an acute angle for the first angle θ_1 . However, any suitable shapes, diameters, and angles may be used for the cover plate **340**.

(56) FIG. 3F further illustrates the cover plate **340** comprising the grooves **343** on the inner surface

of the cover plate **340** facing the trench plate **320**. In some embodiments, the grooves **343** form a radial pattern extending outward from an opening **317** through the cover plate **340** and the radial pattern of the grooves **343** is aligned with the radial pattern of the vent holes **323** of the trench plate **320**. In such embodiments, each of the grooves **343** is aligned with respective ones of the vent holes **323** of the trench plate **320**. In some embodiments, the grooves **343** may help guide evaporated vapors flowing from the vent holes **323** of the trench plate **320** to the opening **317** during baking processes (e.g., the pre-bake process **300**). According to some embodiments, the opening **317** of the cover plate **340** has the first diameter DIM, as illustrated in the magnified bottom view of FIG. 3G. However, any suitable dimensions of the opening **317** through the cover plate **340** may be used.

(57) FIG. 3H illustrates an exploded view of the components of the exhaust hood assembly **380** of the pre-bake station **103**, according to some embodiments. The exhaust hood assembly **380** comprises fasteners **331** (e.g., threaded bolts), the retaining ring **330**, the trench plate **320** over the retaining ring **330**, the cover plate **340** over the trench plate **320**, the exhaust hood heater **360** over the cover plate **340**, and the exhaust pipe header **350** over the exhaust hood heater **360**. In particular, FIG. 3H illustrates that the components of the exhaust hood assembly **380** are aligned such that through holes **329** of the components receive the fasteners **331** (e.g., threaded bolts) securing the components of the exhaust hood assembly **380** to one another. FIG. 3H further illustrates that the radial pattern of the grooves **343** in the cover plate **340** are aligned with the radial pattern of the vent holes **323** of the trench plate **320**.

(58) In some embodiments, the exhaust hood heater **360** comprises a stack of heating elements having an annular shape and a diameter substantially the same as the cover plate **340**, the exhaust hood heater **360** conforming to an upper surface of the cover plate **340**. The exhaust hood heater **360** comprises an opening **317** extending through the stack of heating elements at a center of the exhaust hood heater **360**. In some embodiments, a vertical portion of the exhaust pipe header **350** extends through the opening **317** of the exhaust hood heater **360** and attaches to the opening **317** of the cover plate **340**.

(59) FIG. 4 illustrates an embodiment of an imaging device **400** of the exposure station **105** into which the substrate **201** and the photoresist **211** may be transferred (e.g., by a transfer station **104**) after the curing and drying of the photoresist **211** in the pre-bake station **103**. The exposure station **105** will expose the photoresist **211** to form one or more exposed regions **401** and one or more unexposed regions **403** within the photoresist **211**. In an embodiment the exposure may be initiated by placing the semiconductor device **200** and the photoresist **211**, once cured and dried, into the imaging device **400** for exposure. The imaging device **400** may comprise a support plate **405**, an energy source **407**, a patterned mask **409** arranged between the support plate **405** and the energy source **407**, and optics **413**. In an embodiment the support plate **405** is a surface to which the semiconductor device **200** and the photoresist **211** may be placed or attached to and which provides support and control to the substrate **201** during exposure of the photoresist **211**. Additionally, the support plate **405** may be movable along one or more axes, as well as providing any desired heating or cooling to the substrate **201** and photoresist **211** in order to prevent temperature gradients from affecting the exposure process.

(60) In an embodiment the energy source **407** supplies energy **411** such as light to the photoresist **211** in order to induce a reaction of the PACs, which in turn reacts with the polymer resin to chemically alter those portions of the photoresist **211** to which the energy **411** impinges. In an embodiment the energy **411** may be electromagnetic radiation, such as g-rays (with a wavelength of about 436 nm), i-rays (with a wavelength of about 365 nm), ultraviolet radiation, far ultraviolet radiation, x-rays, electron beams, or the like. The energy source **407** may be a source of the electromagnetic radiation, and may be a KrF excimer laser light (with a wavelength of 248 nm), an ArF excimer laser light (with a wavelength of 193 nm), a F2 excimer laser light (with a wavelength of 157 nm), or the like, although any other suitable source of energy **411**, such as mercury vapor

lamps, xenon lamps, carbon arc lamps or the like, may also be utilized.

(61) The patterned mask **409** is located between the energy source **407** and the photoresist **211** in order to block portions of the energy **411** to form a patterned energy **415** prior to the energy **411** actually impinging upon the photoresist **211**. In an embodiment the patterned mask **409** may comprise a series of layers (e.g., substrate, absorbance layers, anti-reflective coating layers, shielding layers, etc.) to reflect, absorb, or otherwise block portions of the energy **411** from reaching those portions of the photoresist **211** which are not desired to be illuminated. The desired pattern may be formed in the patterned mask **409** by forming openings through the patterned mask **409** in the desired shape of illumination.

(62) Optics **413** may be used to concentrate, expand, reflect, or otherwise control the energy **411** as it leaves the energy source **407**, is patterned by the patterned mask **409**, and is directed towards the photoresist **211**. In an embodiment the optics **413** comprise one or more lenses, mirrors, filters, combinations of these, or the like to control the energy **411** along its path. Additionally, while the optics **413** are illustrated in FIG. 4 as being between the patterned mask **409** and the photoresist **211**, elements of the optics **413** (e.g., individual lenses, mirrors, etc.) may also be located at any location between the energy source **407** (where the energy **411** is generated) and the photoresist **211**.

(63) In an embodiment the semiconductor device **200** with the photoresist **211** is placed on the support plate **405**. Once the pattern has been aligned to the semiconductor device **200**, the energy source **407** generates the desired energy **411** (e.g., light) which passes through the patterned mask **409** and the optics **413** on its way to the photoresist **211**. The patterned energy **415** impinging upon portions of the photoresist **211** induces a reaction of the PACs within the photoresist **211**. The chemical reaction products of the PACs' absorption of the patterned energy **415** (e.g., acids/bases/free radicals) then reacts with the polymer resin, chemically altering the photoresist **211** in those portions that were illuminated through the patterned mask **409**.

(64) In a specific example in which the patterned energy **415** is a 193 nm wavelength of light, the PAC is a photoacid generator, and the polymer resin comprises a group to be decomposed which is a carboxylic acid group on the hydrocarbon structure and a cross linking agent is used, the patterned energy **415** will impinge upon the photoacid generator and the photoacid generator will absorb the impinging patterned energy **415**. This absorption initiates the photoacid generator to generate a proton (e.g., an H⁺ atom) within the photoresist **211**. When the proton impacts the carboxylic acid group on the hydrocarbon structure, the proton will react with the carboxylic acid group, chemically altering the carboxylic acid group and altering the properties of the polymer resin in general. The carboxylic acid group will then react with the cross-linking agent to cross-link with other polymer resins within the photoresist **211**.

(65) Optionally, the exposure of the photoresist **211** may occur using an immersion lithography technique. In such a technique an immersion medium (not individually illustrated in FIG. 4) may be placed between the imaging device **400** (and particularly between a final lens of the optics **413**) and the photoresist **211**. With this immersion medium in place, the photoresist **211** may be patterned with the patterned energy **415** passing through the immersion medium.

(66) In this embodiment, a protective layer (also not individually illustrated in FIG. 4) may be formed over the photoresist **211** in order to prevent the immersion medium from coming into direct contact with the photoresist **211** and leaching or otherwise adversely affecting the photoresist **211**. In an embodiment the protective layer is insoluble within the immersion medium such that the immersion medium will not dissolve it and is immiscible in the photoresist **211** such that the protective layer will not adversely affect the photoresist **211**. Additionally, the protective layer is transparent so that the patterned energy **415** may pass through the protective layer without hindrance.

(67) In an embodiment the protective layer comprises a protective layer resin within a protective layer solvent which should be removed. The material used for the protective layer solvent is, at

least in part, dependent upon the components chosen for the photoresist **211**, as the protective layer solvent should not dissolve the materials of the photoresist **211** so as to avoid degradation of the photoresist **211** during application and use of the protective layer. In an embodiment the protective layer solvent includes alcohol solvents, fluorinated solvents, and hydrocarbon solvents.

(68) The protective layer resin may, similar to the photoresist **211**, comprise a polymer with a protective layer repeating unit. In an embodiment the protective layer repeating unit may be an acrylic resin with a repeating hydrocarbon structure having a carboxyl group, an alicyclic structure, an alkyl group having one to five carbon atoms, a phenol group, or a fluorine atom-containing group. However, any suitable protective layer resin may also be utilized.

(69) Prior to application of the protective layer onto the photoresist **211**, the protective layer resin and any other desired additives are first added to the protective layer solvent to form a protective layer composition. The protective layer solvent is then mixed to ensure that the protective layer composition has a consistent concentration throughout the protective layer composition.

(70) Once the protective layer composition is ready for application, the substrate **201** with the photoresist **211** may be returned to the coating station **101** or may be transferred to another suitable station by the transfer station **104** for application of the protective layer composition over the photoresist **211**. In an embodiment the application of the protective layer composition may be performed using a process such as a spin-on coating process, a dip coating method, an air-knife coating method, a curtain coating method, a wire-bar coating method, a gravure coating method, a lamination method, an extrusion coating method, combinations of these, or the like. In an embodiment the protective layer composition may be applied such that it has a thickness over the surface of the photoresist **211** of about 100 nm.

(71) After the protective layer composition has been applied to the photoresist **211**, a protective layer pre-bake may be performed in order to remove the protective layer solvent. As such, the transfer station **104** may return the semiconductor device **200** with the protective layer over the photoresist **211** to the pre-bake station **103** to perform the protective layer pre-bake before further processing. In an embodiment, the protective layer pre-bake may be performed at a temperature suitable to evaporate the protective layer solvent, such as between about 40° C. and 150° C., although the precise temperature depends upon the materials chosen for the protective layer composition. The protective layer pre-bake is performed for a time sufficient to cure and dry the protective layer composition, such as between about 10 seconds to about 5 minutes, such as about 90 seconds.

(72) Once the protective layer pre-bake has been performed, the semiconductor device **200** with the photoresist **211** and the protective layer are transferred from the pre-bake station **103** and placed on the support plate **405** of the exposure station **105**, and the immersion medium may be placed between the protective layer and the optics **413**. In an embodiment the immersion medium is a liquid having a refractive index greater than that of the surrounding atmosphere, such as having a refractive index greater than 1. Examples of the immersion medium may include water, oil, glycerine, glycerol, cycloalkanols, or the like, although any suitable medium may also be utilized.

(73) The placement of the immersion medium between the protective layer and the optics **413** may be done using, e.g., an air knife configuration of the exposure station **105**, whereby fresh immersion medium is applied to a region between the protective layer and the optics **413** and controlled using pressurized gas directed towards the protective layer to form a barrier and keep the immersion medium from spreading. In this embodiment the immersion medium may be applied, used, and removed from the protective layer for recycling so that there is fresh immersion medium used for the actual imaging process.

(74) However, the air knife configuration for the exposure station **105** described above is not the only configuration which may be used to expose the photoresist **211** using an immersion method. Any other suitable configuration using an immersion medium, such as immersing the entirety of the substrate **201** along with the photoresist **211** and the protective layer or using solid barriers

instead of gaseous barriers may also be utilized. Any suitable method for exposing the photoresist **211** through the immersion medium may be used, and all are fully intended to be included within the scope of the embodiments.

(75) FIG. 5 illustrates a post-bake process of the semiconductor device, after the photoresist **211** has been exposed to the patterned energy **415** in the exposure station **105**. The semiconductor device **200** with the photoresist **211** may be moved via the transfer station **104** from the exposure station **105** to the post-bake station **107**. In some embodiments, the post-bake station **107** may be separate from but similar to the pre-bake station **103** illustrated in FIG. 3A. In other embodiments, the transfer station **104** may transfer the semiconductor device **200** with the photoresist **211** from the exposure station **105** to the pre-bake station **103** to perform the post-bake process. However, any suitable type of heating station such as a furnace or steam-heating station may also be utilized.

(76) Once in the post-bake station **107**, a first post-exposure bake (PEB) (e.g., PEB **501** represented in FIG. 5 by the wavy lines) may be used in order to assist in the generating, dispersing, and reacting of the acid/base/free radical generated from the impingement of the energy **411** upon the PACs during the exposure in the exposure station **105**. Such assistance helps to create or enhance chemical reactions which generate chemical differences and different polarities between the one or more exposed regions **401** and the one or more unexposed regions **403** within the photoresist **211**. These chemical differences also cause differences in the solubility between the one or more exposed regions **401** and the one or more unexposed regions **403**. In an embodiment the semiconductor device **200** with the photoresist **211** may be placed on the hot plate **301** and the temperature of the photoresist **211** may be increased to between about 50° C. and about 160° C. for a period of between about 40 seconds and about 120 seconds.

(77) Returning now to FIG. 1, the photoresist track system **100** comprises a developer station **109** which can be used, if desired, to develop the photoresist **211** with a positive tone developer or a negative tone developer and which comprises equipment and chemicals which are specific to the development process. In an embodiment the developer station **109** may be connected to the post-bake station **107** through, e.g., the transfer station **104** so that the semiconductor device **200** and photoresist **211** may be transferred to the developer station **109** shortly after the PEB **501** without breaking the interior environment of the photoresist track system **100**.

(78) FIGS. 6A-6B illustrate a top view and a representative cross-sectional view of an embodiment of the developer station **109** in which the developer station **109** uses a spin-on method to apply the developer. In an embodiment the developer station **109** comprises a rotating developer chuck **603** attached to a rotating spindle **605**. A developer dispensing arm **607** with a developer nozzle **608** (on a developer track **606**) is operably connected to a developer storage tank **609** so that the developer storage tank **609** provides a fresh supply of the developer **611** to the developer dispensing arm **607**.

(79) In an embodiment the substrate **201** is placed onto the rotating developer chuck **603** and is held in place using, e.g., a vacuum pressure suctioning the substrate **201** to the rotating developer chuck **603**. The rotating spindle **605** is attached to the rotating developer chuck **603** and is engaged, thereby rotating the rotating developer chuck **603**, the substrate **201** with the photoresist **211**, at a speed of between about 500 rpm and about 3500 rpm. Once the photoresist **211** is rotating at the desired speed, the developer dispensing arm **607** moves over the rotating photoresist **211** and begins to dispense the developer **611** out of the developer nozzle **608** and onto the photoresist **211** at a rate of between about 0.5 cc/sec and about 20 cc/sec, at a temperature of between about 10° C. and about 50° C., such as about 50° C., for a period of time between about 10 second and about 60 minutes, such as about 30 minutes.

(80) In an embodiment the developer dispensing arm **607** dispenses a developer **611** (e.g., a negative tone developer), such as an organic solvent or critical fluid to remove those portions of the photoresist **211** which were not exposed to the energy **411** during the exposure process and, as such, retain their original solubility. Specific examples of materials that may be utilized include hydrocarbon solvents, alcohol solvents, ether solvents, ester solvents, critical fluids, combinations

of these, or the like.

(81) In an embodiment in which immersion lithography is utilized to expose the photoresist **211** and the protective layer utilized to protect the photoresist **211** from the immersion medium, the developer **611** may be chosen to remove not only those portions of the photoresist **211** that are desired to be removed, but may also be chosen to remove the protective layer in the same development step. Also, the protective layer may be removed in a separate process, such as by a separate solvent from the developer **611** or even an etching process to remove the protective layer from the photoresist **211** prior to development.

(82) However, while the spin-on method and configuration described herein for the developer station **109** is one suitable method for developing the photoresist **211** in the developer station log, it is intended to be illustrative and is not intended to limit the embodiment. Rather, the developer station **109** may comprise any mechanism and chemicals in any configuration for any type of development process, include a dip process configuration, a puddle process configuration, combinations of these, or the like. All such development processes and configuration for the developer station **109** are fully intended to be included within the scope of the embodiments.

(83) Furthermore, in an embodiment all of the mechanics and other structures that make up the developer station **109** (e.g., the rotating developer chuck **603**, the rotating spindle **605**, the developer dispensing arm **607**, etc.) are housed within an exterior housing **601**, which provides support and protection to the internal components of the developer station **109**. In an embodiment the exterior housing **601** encloses the developer station **109** and is accessible through the transfer station **104** of the photoresist track system **100**. Additionally, any utilities, such as electricity or fresh raw materials (e.g., fresh developer or fresh rinse water), may come in, if desired, through the exterior housing **601**.

(84) FIG. **6C** illustrates a cross-sectional view of the application of the developer **611** onto the photoresist **211**. In an embodiment the developer **611** will dissolve the unexposed regions **403** of the photoresist **211** that were not exposed to the patterned energy **415**. This dissolving will leave behind the one or more exposed regions **401** of the photoresist **211** that had been exposed to the patterned energy **415**, thereby transferring the pattern of the patterned energy **415** to the photoresist **211**. Once finished, the developer **611** may be removed by stopping the dispensing of the developer **611** while keeping the substrate **201** spinning to remove the developer **611** and performing an optional rinse with, e.g., deionized water.

(85) Returning now to FIG. **1**, after the photoresist **211** has been developed in the developer station **109**, the substrate **201** and the photoresist **211** may be transferred by the transfer station **104** into the optional hard bake station **111** for further processing. Once the substrate **201** and the photoresist **211** are in position, the optional hard bake station **111** may optionally be used to perform a hard-bake process to help polymerize and stabilize the photoresist **211** after the development process, and also aids in improving the adhesion of the photoresist **211** to the layer to be patterned **209**. In some embodiments the optional hard bake station **111** may be separate from but similar to the pre-bake station **103** including the hot plate **301** (see, e.g., FIG. **3A**) and exhaust hood assembly **380**. In other embodiments, the transfer station **104** may transfer the substrate **201** from the developer station **109** to the pre-bake station **103** to perform the hard-bake process. However, any suitable type of heating station such as a furnace or steam-heating station may also be utilized.

(86) Turning to FIG. **7**, once the substrate with the photoresist **211** is in the optional hard bake station **111**, a hard bake process **701** (represented in FIG. **7** by the wavy lines) may be performed on the substrate **201** with the photoresist **211**. During the hard bake process **701**, the hot plate **301** and the heating elements **305** are engaged to raise the temperature of the photoresist **211** to a process temperature of between about 70° C. to about 130° C. The photoresist may be kept at this process temperature for a time period of between about 1 minute and about 3 minutes.

(87) Once the hard bake has been performed on the photoresist **211**, and any other processes such as rinsing or drying that may be desired, the substrate **201** with the photoresist **211** is ready for

further processing and may be removed from the photoresist track system **100** through the second loadlock chamber **114**. Similar to the first loadlock chamber **102**, the second loadlock chamber **114** allows the substrate **201** to be removed from the photoresist track system **100** without exposing the interior stations to the exterior atmosphere.

(88) FIGS. **8A-8C** illustrate cross-sectional views of several different profiles of the trench plate **320**, according to some other embodiments. Although specific shapes and dimensions are illustrated in FIGS. **8A-8C** for the different profiles of the trench plate **320**, these shapes and dimensions are intended to be illustrative and are not intended to limit the embodiments.

(89) FIG. **8A** illustrates the trench plate **320** comprising a second profile **825A** having trenches **325** with substantially (within the range of manufacturing deviation) flat bottoms and substantially (within the range of manufacturing deviation) vertical sidewalls. According to some embodiments, the second profile **825A** comprises trenches **325** having a third width **W3** of between about 1 mm and about 60 mm, such as about 30 mm and a second depth **D2** of between about 1 mm and about 20 mm, such as about 5 mm. However, any suitable widths and any suitable depths may be used for the trenches **325** of the second profile **825A**.

(90) FIG. **8B** illustrates the trench plate **320** comprising a third profile **825B** having trenches **325** with rounded bottoms and rounded sidewalls. According to some embodiments, the third profile **825B** comprises trenches **325** having a fourth width **W4** of between about 1 mm and about 60 mm, such as about 30 mm, a third depth **D3** of between about 1 mm and about 20 mm, such as about 5 mm, and having a first radius **R1** of the rounded bottoms and rounded sidewalls of between about 1 mm and about 20 mm, such as about 5 mm. However, any suitable widths, any suitable depths, and any suitable radiuses may be used for the trenches **325** of the third profile **825B**.

(91) FIG. **8C** illustrates the trench plate **320** comprising a fourth profile **825C** having trenches **325** with pointed bottoms and angled sidewalls. According to some embodiments, the fourth profile **825C** comprises trenches **325** having a fifth width **W5** of between about 1 mm and about 60 mm, such as about 30 mm, a fourth depth **D4** of between about 1 mm and about 20 mm, such as about 5 mm, and angled sidewalls having third angles $\theta 3$ of between about 120° and about 170° , such as about 135° . However, any suitable widths, any suitable depths and any suitable angles may be used for the trenches **325** of the fourth profile **825C**.

(92) FIGS. **9A-9B** illustrate top views of several different configurations of the trench plate **320**, according to some embodiments different from the embodiment illustrated in FIG. **3C**. Although specific shapes and dimensions are illustrated in FIGS. **9A-9B** for the different configurations of the trench plate **320**, these shapes and dimensions are intended to be illustrative and are not intended to limit the embodiments.

(93) FIG. **9A** illustrates the trench plate **320**, according to another embodiment, comprising a series of raised concentric circles **940** instead of the ridges **321** of FIG. **3C** and trenches **325** arranged alternately between the series of raised concentric circles **940**. The series of raised concentric circles **940** comprise vent holes **323** arranged in a radial pattern across the series of raised concentric circles **940** and comprise through holes **329** arranged within an outermost ridge of the series of raised concentric circles **940**. However, any suitable number of concentric circles and any suitable arrangement of vent holes **323** within the series of raised concentric circles **940** may be used.

(94) FIG. **9B** illustrates the trench plate **320**, according to yet another embodiment, comprising a plurality of columns **950** instead of the ridges **321** of FIG. **3C**. The plurality of columns **950** are disposed in a radial pattern with areas between columns forming a plurality of the trenches **325** that are integrally connected. The plurality of columns **950** comprise vent holes **323** arranged within the corresponding ones of the radial pattern of columns **950** and comprise through holes **329** arranged within an outermost circular ridge along a perimeter of the trench plate **320**. However, any suitable number and any suitable shape of the plurality of columns **950** and any suitable arrangement of vent holes **323** within the ridges **321** may also be used.

(95) While the different profiles and configurations of the trench plate **320** are illustrated in FIGS. **8A-8D** and **9A-9B** with specific shapes and specific dimensions suitable for the trench plate **320**, these are intended to be illustrative and are not intended to limit the embodiments. Rather, the profiles and configurations of the trenches **325** of the trench plate **320** may comprise any suitable shapes, any suitable sizes, any suitable dimensions, and in any suitable configuration for collecting the residue **390** within the trenches **325** and preventing the residue from dripping onto the semiconductor device **200** during bake processes. All such profiles and configurations for the trenches **325** of the trench plate **320** are fully intended to be included within the scope of the embodiments.

(96) By providing nonstick coatings on inner surfaces of the cover plate **340** and the exhaust pipe header **350** of the exhaust hood assembly **380**, the solvent vapor condensing into the residue **390** is prevented or minimized from wetting the inner surfaces of the cover plate **340** and the exhaust pipe header **350** which aids in the evacuation of the chemical solvent vapor from the exhaust hood assembly **380** during baking processes. Furthermore, by collecting and trapping any residue **390** within trenches **325** of the trench plate **320**, it is possible to prevent the residue **390** from dropping onto the substrate **201** and causing defects on the substrate **201**.

(97) As such, the exhaust hood assembly **380** efficiently evacuates solvent vapor during bake processes (e.g., the pre-bake process **300**), minimizes the chemical solvent vapor from condensing into a residue and wetting inner surfaces of the exhaust hood assembly, and prevents any residue that has formed from dripping onto and causing damage to a wafer. As such, high exhaust efficiency, improved reliability, increased yield, and ultimately reduced manufacturing time and costs are achieved by the apparatus and bake process methods, as described herein.

(98) In accordance with an embodiment, a semiconductor manufacturing apparatus includes: a trench plate comprising a first surface and a second surface opposite the first surface, wherein the trench plate comprises a first trench extending partially through the trench plate from the first surface, wherein the trench plate also comprises a first opening extending fully through the trench plate from the first surface to the second surface, and a second opening extending fully through the trench plate from the first surface to the second surface, the first trench being located between the first opening and the second opening. In accordance with an embodiment the first surface comprises polytetrafluoroethylene. In accordance with an embodiment the first trench is located within a center of the trench plate. In accordance with an embodiment the trench plate further comprises a second trench separated from the first trench by a first distance between about 1 mm and about 20 mm. In accordance with an embodiment the first trench has a width which increases in size as the first trench extends towards an outer perimeter of the trench plate. In accordance with an embodiment the first trench comprises angled sidewalls. In accordance with an embodiment the semiconductor manufacturing apparatus further includes attachment holes located along a perimeter of the trench plate.

(99) In accordance with another embodiment, a semiconductor manufacturing apparatus includes: a trench plate, wherein the trench plate comprises ridges, a trench disposed between the ridges, and a vent hole extending through the ridges and from a first side of the trench plate to a second side of the trench plate; and a cover plate over and attached to the trench plate. In accordance with an embodiment, the semiconductor manufacturing apparatus further includes a single pipe header attached to the cover plate, wherein the single pipe header is the lone pipe header attached to the cover plate. In an embodiment the single pipe header has a diameter of between about 20 mm and about 40 mm. In an embodiment, surfaces of the trench plate and the cover plate comprise a polytetrafluoroethylene coating. In an embodiment the trench comprises angled sidewalls and a substantially flat bottom surface. In an embodiment the trench comprises a substantially flat bottom surface and sidewalls extending in a direction substantially vertical to the substantially flat bottom surface. In an embodiment the trench has a concave profile.

(100) In accordance with yet another embodiment, a method includes: placing a semiconductor

wafer with a material disposed thereon within a bake station; and heating the semiconductor wafer with the material disposed thereon, thereby forming an evaporated portion of the material, wherein a first portion of the evaporated portion passes through vent holes of a trench plate and through a cover plate above the trench plate, and wherein a second portion of the evaporated portion passes through the vent holes of the trench plate, condenses, and enters trenches within the trench plate after condensing. In an embodiment the trench plate comprises polytetrafluoroethylene. In an embodiment all of the evaporated portion that does not condense passes through a single opening in the cover plate. In an embodiment the single opening has a diameter of between about 20 mm and about 30 mm. In an embodiment the material is a photoresist. In an embodiment the cover plate has a second trench and the first portion of the evaporated portion enters the second trench.

(101) The foregoing outlines features of several embodiments so that those skilled in the art may better understand the aspects of the present disclosure. Those skilled in the art should appreciate that they may readily use the present disclosure as a basis for designing or modifying other processes and structures for carrying out the same purposes and/or achieving the same advantages of the embodiments introduced herein. Those skilled in the art should also realize that such equivalent constructions do not depart from the spirit and scope of the present disclosure, and that they may make various changes, substitutions, and alterations herein without departing from the spirit and scope of the present disclosure.

Claims

1. A semiconductor manufacturing apparatus comprising: a hot plate with a semiconductor wafer holding region; at least one heater within the hot plate; a trench plate over the hot plate, wherein the trench plate comprises a first trench extending partially through the trench plate from a first surface, wherein the trench plate also comprises a first opening extending fully through the trench plate from the first surface to a second surface, and a second opening extending fully through the trench plate from the first surface to the second surface, the first trench being located between the first opening and the second opening; and a cover plate over the trench plate, wherein the cover plate and the trench plate at least partially enclose a first region, and wherein an exhaust opening extends through the cover plate to the first region.
2. The semiconductor manufacturing apparatus of claim 1, wherein the trench plate comprises polytetrafluoroethylene.
3. The semiconductor manufacturing apparatus of claim 1, wherein the cover plate has a single opening over the trench plate.
4. The semiconductor manufacturing apparatus of claim 3, wherein the single opening has a diameter of between about 20 mm and about 30 mm.
5. The semiconductor manufacturing apparatus of claim 3, further comprising: a semiconductor wafer on the semiconductor wafer holding region; and a photoresist overlying the semiconductor wafer.
6. The semiconductor manufacturing apparatus of claim 3, further comprising a single pipe header attached to the single opening in the cover plate, wherein the single pipe header is the lone pipe header attached to the cover plate.
7. The semiconductor manufacturing apparatus of claim 1, wherein the cover plate has a second trench.
8. A semiconductor manufacturing apparatus comprising: a hot plate with a semiconductor wafer holding region; a semiconductor wafer on the semiconductor wafer holding region; at least one heater within the hot plate; a trench plate over the hot plate, wherein the trench plate comprises a first trench extending partially through the trench plate from a first surface, wherein the trench plate also comprises a first opening extending fully through the trench plate from the first surface to a second surface, and a second opening extending fully through the trench plate from the first surface

to the second surface, the first trench being located between the first opening and the second opening, the first opening and the second opening being laterally removed from the first trench; and a cover plate over the trench plate.

9. The semiconductor manufacturing apparatus of claim 8, wherein the trench plate comprises polytetrafluoroethylene.

10. The semiconductor manufacturing apparatus of claim 8, wherein there is a single opening in the cover plate.

11. The semiconductor manufacturing apparatus of claim 10, wherein the single opening has a diameter of between about 20 mm and about 30 mm.

12. The semiconductor manufacturing apparatus of claim 8, wherein the cover plate has a second trench.

13. The semiconductor manufacturing apparatus of claim 12, wherein the first trench and the second trench are part of a plurality of trenches, the plurality of trenches being arranged around a central point of the cover plate.

14. A semiconductor manufacturing apparatus comprising: a hot plate; a semiconductor wafer on the hot plate; at least one heater within the hot plate; a trench plate over the hot plate, wherein the trench plate comprises a first trench extending partially through the trench plate from a first surface, wherein the trench plate also comprises a first opening extending fully through the trench plate from the first surface to a second surface, and a second opening extending fully through the trench plate from the first surface to the second surface, the first trench being located between the first opening and the second opening; and a cover plate over the trench plate, wherein the cover plate and the trench plate at least partially enclose a first region, and wherein an exhaust opening extends through the cover plate to the first region.

15. The semiconductor manufacturing apparatus of claim 14, wherein the trench plate comprises polytetrafluoroethylene.

16. The semiconductor manufacturing apparatus of claim 14, wherein the cover plate has a single opening over the trench plate.

17. The semiconductor manufacturing apparatus of claim 16, wherein the single opening has a diameter of between about 20 mm and about 30 mm.

18. The semiconductor manufacturing apparatus of claim 16, further comprising: a semiconductor wafer holding region within the hot plate and adjacent to the semiconductor wafer; and a photoresist overlying the semiconductor wafer.

19. The semiconductor manufacturing apparatus of claim 16, further comprising a single pipe header attached to the single opening in the cover plate, wherein the single pipe header is the lone pipe header attached to the cover plate.

20. The semiconductor manufacturing apparatus of claim 14, wherein the cover plate has a second trench.
