

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12418774

Kind Code

B2

Date of Patent

September 16, 2025

Inventor(s)

Baker; Rhodes B. et al.

Gesture-based load control via wearable devices

Abstract

A load control system may include control-target devices for controlling an amount of power provided to an electrical load. The control-target devices may be capable of controlling the amount of power provided to the electrical load based on control instructions. The control-target devices and/or the control-instructions may be determined based on a gesture performed by a user. The user may wear a wearable control device capable of measuring movements performed by the user and transmit digital messages that may be used to control an electrical load. The wearable control device may identify gestures performed by the user for controlling a control-target device and/or provide control instructions to the control-target device based on the identified gestures. A gesture may be associated with a scene that includes a configuration of one or more control devices in a load control system.

Inventors: Baker; Rhodes B. (Bethlehem, PA), Clymer; Erica L. (Northampton, PA), Knode; Galen Edgar (Macungie, PA), Kumar; Sanjeev (Harleysville, PA), Nill; John (Emmaus, PA), Twaddell; Daniel L. (Bethlehem, PA), Zizza; Michael J. (Bethlehem, PA)

Applicant: Lutron Technology Company LLC (Coopersburg, PA)

Family ID: 1000008818464

Assignee: Lutron Technology Company LLC (Coopersburg, PA)

Appl. No.: 18/485608

Filed: October 12, 2023

Prior Publication Data

Document Identifier

Publication Date

US 20240040338 A1

Feb. 01, 2024

Related U.S. Application Data

continuation parent-doc US 17385015 20210726 US 11818627 child-doc US 18485608
continuation parent-doc US 16671464 20191101 US 11076265 20210727 child-doc US 17385015
continuation parent-doc US 15011263 20160129 US 10484827 20191119 child-doc US 16671464
us-provisional-application US 62110277 20150130

Publication Classification

Int. Cl.: **H04W4/029** (20180101); **G05D23/19** (20060101)

U.S. Cl.:

CPC **H04W4/029** (20180201); **G05D23/1905** (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7925384	12/2010	Huizenga et al.	N/A	N/A
7940167	12/2010	Steiner et al.	N/A	N/A
8009042	12/2010	Steiner et al.	N/A	N/A
8199010	12/2011	Sloan et al.	N/A	N/A
8228184	12/2011	Blakeley et al.	N/A	N/A
8570221	12/2012	Bao et al.	N/A	N/A
8659230	12/2013	Nanahara et al.	N/A	N/A
8933876	12/2014	Galor et al.	N/A	N/A
9201499	12/2014	Chang et al.	N/A	N/A
9232610	12/2015	Gritti	N/A	N/A
9345115	12/2015	Mohan	N/A	N/A
2010/0245588	12/2009	Waehner et al.	N/A	N/A
2012/0268374	12/2011	Heald	N/A	N/A
2013/0154951	12/2012	Laibowitz et al.	N/A	N/A
2013/0234625	12/2012	Kondo et al.	N/A	N/A
2014/0031987	12/2013	Ericsson et al.	N/A	N/A
2014/0235269	12/2013	Ericsson et al.	N/A	N/A
2014/0267008	12/2013	Jain et al.	N/A	N/A
2014/0317577	12/2013	Chen et al.	N/A	N/A
2015/0026647	12/2014	Park et al.	N/A	N/A
2015/0102984	12/2014	Wong et al.	N/A	N/A
2015/0106770	12/2014	Shah	715/863	G06F 3/017
2015/0189068	12/2014	Mohan et al.	N/A	N/A
2015/0193111	12/2014	Kauffmann et al.	N/A	N/A
2015/0279051	12/2014	Kovesi et al.	N/A	N/A
2015/0346834	12/2014	Martinez et al.	N/A	N/A
2016/0028264	12/2015	Bernhard et al.	N/A	N/A

2016/0041618	12/2015	Poupyrev et al.	N/A	N/A
2016/0054023	12/2015	Baker et al.	N/A	N/A
2016/0056629	12/2015	Baker et al.	N/A	N/A
2016/0124579	12/2015	Tokutake	345/156	G06F 3/0481
2016/0266653	12/2015	Liu et al.	N/A	N/A
2016/0299570	12/2015	Davydov	N/A	N/A
2017/0277267	12/2016	Liu et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102833910	12/2011	CN	N/A

OTHER PUBLICATIONS

Estel et al., Feasibility of Bluetooth iBeacons for Indoor Localization, 2015, 12 pages. cited by applicant

Bourgeois, Mike, "Gesture Like Light Control with Kinect", Available at: <https://www.youtube.com/watch?v=x99gHQKVcg>, retrieved on Jul. 8, 2013, Transcript of Video, May 15, 2011, 2 pages. cited by applicant

Bourgeois, Mike, "Gesture Like Light Control with Kinect", Available at: <https://www.youtube.com/watch?v=x99gHQKVcg>, retrieved on Jul. 8, 2013, Video, May 15, 2011. cited by applicant

Primary Examiner: Moore; Whitney

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/385,015, filed Jul. 26, 2021; which is a continuation of U.S. patent application Ser. No. 16/671,464, filed Nov. 1, 2019, now U.S. Pat. No. 11,076,265 issued Jul. 27, 2021; which is a continuation of U.S. patent application Ser. No. 15/011,263, filed Jan. 29, 2016, now U.S. Pat. No. 10,484,827 issued Nov. 19, 2019; which claims the benefit of U.S. Provisional Patent Application No. 62/110,277, filed Jan. 30, 2015, the entire disclosure of which is incorporated by reference herein.

BACKGROUND

(1) A user environment, such as a residence or an office building for example, may be configured using various types of load control systems. Load control systems may include lighting systems; motorized window treatment systems; heating, ventilation, and air-conditioning (HVAC) systems; and/or the like. Most load control systems require the use of various devices for performing load control. Such load control systems may be embodied in a two-part load control system that includes a control-target device for directly controlling the electrical load and a control-source device, such as a remote control, for indirectly controlling the electrical load by sending instructions to the control-target device. Using such load control systems, a user may indirectly control an electrical load using a control-source device.

(2) FIG. 1 illustrates an example of a prior art load control environment **102**. As shown in FIG. 1, the load control environment **102** may include control-source devices and control-target devices. The control-target devices may include a lighting control device **104** (e.g., a dimmer switch, a ballast, or a light-emitting diode (LED) driver) for directly controlling an amount of power provided to lighting load **106**, a motorized window treatment **112** for controlling the position of a

covering material **114**, a thermostat **120** for controlling an HVAC system, and a plug-in control device **122** (e.g., alternating current (AC) plug-in control device) for controlling the amount of power provided to a floor lamp **124**, a table lamp, or the electrical load of another device that is plugged in to the plug-in control device **122**. The control-source devices in the load control environment **102** may include a remote control device **116**, a daylight sensor **108**, an occupancy sensor **110**, and/or a window sensor **126**.

(3) The control-source devices may communicate control instructions for controlling an electrical load to a control-target device via digital messages that may be transmitted via a wired or wireless communication, e.g., via radio-frequency (RF) signals. The remote control device **116** may transmit a digital message that indicates load control instructions based on the actuation of one or more buttons for controlling an electrical load. The daylight sensor **108** may transmit a digital message that indicates load control instructions based on a level of daylight sensed in the load control environment **102**. The occupancy sensor **110** may transmit a digital message that indicates load control instructions based on an occupancy or vacancy condition sensed in the load control environment **102**. The window sensor **126** may transmit a digital message that indicates load control instructions based on a level of daylight intensity sensed from outside of the load control environment **102**.

(4) The control-source devices in the load control system depicted in FIG. **1** may provide convenient ways for a user **118** to control an electrical load. These load control systems, however, require the user **118** to keep track of the location of one or more devices for controlling the system. A user's control may also be limited due to a predefined interface or the limited instructions provided by the control device.

(5) Gesture recognition is a developing technology, which is being considered for use in load control systems to enable a convenient form of load control. Gesture recognition may be used to enable the user **118** to send instructions to a control-target device without the use of a remote control or a similar control-source device. In order to perform gesture-based load control, additional equipment, such as a camera for capturing images of a user, may need to be installed in the load control environment **102**. There may be advantages to providing gesture control for an electrical load using other devices.

SUMMARY

(6) A load control system may include one or more control devices for controlling an amount of power provided to an electrical load. A control device may be a central control device, a wearable control device, and/or a wireless communication device (e.g., a smartphone, tablet, laptop, etc.). A control device may be a control-source device and/or a control-target device. The control device may detect gestures performed by a user. For example, the control device may detect a gesture (e.g., data indicative of a gesture) performed by a user wearing a wearable control device for controlling a control-source and/or control-target device. Data indicative of a gesture may include the name and/or a label representing the gesture, and/or the data indicative of the gesture may include information (e.g., digital information) representing the position, direction, orientation, and/or speed of the wearable control device while the user is performing the gesture.

(7) The control-source devices may transmit digital messages to the control-target devices for controlling the electrical load. As disclosed herein, control-target devices may be capable of controlling the electrical load (e.g., controlling the amount of power provided to the electrical load) based on control instructions received from a wearable control device or other control device. The control instructions may include load control instructions or another indication that causes the control-target device to determine load control instructions for controlling the electrical load. The control instructions may be determined based on the data indicative of the gesture performed by the user via the wearable control device.

(8) The wearable control device may detect gestures performed by a user for controlling a control-target device. The wearable control device may determine control-target devices and/or control

instructions based on the gestures and may provide control instructions to identified control-target devices based on the identified gestures. The wearable control device may transmit digital messages that indicate the gestures performed by the user or other data indicative of the gesture to other devices for determining control-target devices and/or control instructions based on the gestures. For example, the wearable control device may transmit digital messages that indicate the gestures performed by the user to a wireless communication device and/or a central control device.

(9) The gestures may be identified based on a change in orientation of the wearable control device and/or a change in position of the wearable control device. To determine control-target devices and/or control instructions, the gestures may be compared against gestures that are stored in memory and associated with control-target devices and/or control instructions. A user may identify a control-target device to be controlled by performing an associated gesture. For example, the user may indicate a ballast to be controlled by pointing to the ballast or the ballast's lighting fixture. The user may also, or alternatively, identify a control-target device by selecting the control-target device on a visual display of the wearable control device and/or a wireless communication device (e.g., a smartphone, a tablet, a laptop, etc.). When the control-target device has been determined, the user may identify the control instructions for controlling the control-target device by performing an associated gesture. For example, the user may raise an arm to send instructions to the identified ballast to increase the power provided to the lighting fixture.

(10) A gesture may be associated with a scene (e.g., a preset) that includes a predefined configuration of one or more control devices in a load control system. To configure the control devices according to the scene, the user may perform the associated gesture. The gesture may indicate the control devices for being controlled and/or the control instructions for being sent to each control device.

(11) The user may engage the wearable control device, or another device in the load control system, for enabling load control based on gestures performed by the user. The devices may be engaged by the user performing an engage gesture, actuating a button on the wearable control device, or actuating a button on the wireless communication device. The user may disengage the wearable control device, or another device in the load control system, for disabling load control based on gestures performed by the user. The disengage gesture may cause the wearable control device to be unable to identify control instructions and/or control a control-target device until the user re-engages the wearable control device, or another device in the load control system, for transmitting control instructions.

(12) The user may program the wearable control device, a wireless communication device, and/or a central control device to identify a gesture. The user may perform a programming gesture that may be identified by the wearable control device or the central control device to trigger a programming mode. When the programming mode is activated, the user may program the wearable control device, a wireless communication device, and/or the central control device to identify a gesture. The user may perform a gesture and associate that gesture with a control-target device and/or control instructions. The wearable control device, the wireless communication device, and/or the central control device may store the association such that the gesture may be identified for load control or control of the wearable control device.

(13) The central control device may learn to automate control of the load control system based on repeated gestures performed by the user in a location. The central control device may store gestures performed by a user that cause a change in the status of an electrical load or a control-target device. When the central control device identifies that the user has performed the gesture in the same location a predetermined number of times (e.g., at least three times) for changing the status of the electrical load or the control-target device, the central control device may automate the control of the when the user is within the location. The central control device may receive feedback of whether the user likes the automated control and may modify the automated control based on the feedback.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 depicts an example prior art environment for controlling an electrical load.
- (2) FIG. 2 depicts an example environment for controlling devices using gesture control.
- (3) FIG. 3 is a simplified flow diagram depicting an example method for performing gesture-based control of one or more control-target devices.
- (4) FIG. 4 is a simplified flow diagram depicting another example method for performing gesture-based control of one or more control-target devices.
- (5) FIGS. 5A-5E depict example gestures that may be performed for controlling control-target devices.
- (6) FIG. 6 is a simplified flow diagram depicting an example method for associating a gesture with control-target devices and/or control instructions.
- (7) FIG. 7 is a block diagram depicting an example of a wearable control device.
- (8) FIG. 8 is a block diagram depicting an example of a central control device.
- (9) FIG. 9 is a block diagram depicting an example of a control-target device.
- (10) FIG. 10 is a block diagram depicting an example of a wireless communication device.

DETAILED DESCRIPTION

(11) FIG. 2 depicts an example load control environment **202** (e.g., a room in an office building or residence) for controlling devices using wearable control devices. As shown in FIG. 2, the load control environment **202** may be installed with one or more control devices for controlling the electrical loads within the load control environment **202** to control one or more characteristics of the load control environment (e.g., the amount of artificial and/or natural daylight in the room, the temperature in the room, the status of an electrical device, etc.). The control device may detect gestures performed by a user **222**. For example, the control device may detect a gesture (e.g., data indicative of a gesture) performed by the user **222** wearing a wearable control device **228** for controlling a control-target device. The data indicative of the gesture may include the name and/or a label representing the gesture, and/or the data indicative of the gesture may include information (e.g., digital information) representing the position, direction, orientation, and/or speed of the wearable control device **228** while the user **222** is performing the gesture.

(12) Control devices may be implemented to enable control of an electrical load based on gestures performed by a user. For example, control devices may be implemented to enable control of an electrical load based on data indicative of gestures performed by a user. Each control device may be a control-source device capable of transmitting digital messages, e.g., wirelessly or via a wired communication, for controlling the amount of power provided to an electrical load. A control device may be a control-target device capable of receiving the digital messages and directly controlling the electrical load (e.g., directly controlling an amount of power provided to the electrical load) based on the information in the digital messages. A control device may be a control-source device and a control-target device. Example control devices may include a lighting control device **204** (e.g., a dimmer switch, a switching device, a ballast, or an LED driver) for controlling the amount of power provided to a lamp **206**; a motorized window treatment **216** for controlling the position of a covering material **218** via an electrical motor; a temperature control device **220** (e.g., thermostat) for controlling a heating, ventilation, and air-conditioning (HVAC) system; and/or a plug-in control device **224** for controlling the amount of power provided to an electrical load connected to the plug-in control device **224** (e.g., a floor lamp **226** or a table lamp).

(13) Each of the control devices may control one or more characteristics of the load control environment **202** (e.g., by controlling the amount of power provided to an electrical load) based on received digital messages. A wearable control device **228** may be a control device capable of transmitting digital messages for controlling one or more characteristics of the load control

environment **202**. The wearable control device **228** may be a device capable of being worn by the user **222** and may act as a control-source device for communicating digital messages for controlling one or more electrical loads of the load control environment **202**. The wearable control device **228** may detect one or more gestures performed by the user for controlling one or more electrical loads. Gestures may be identified measurements performed by the wearable control device **228** when the user **222** performs movements. As shown in FIG. 2, the wearable control device **228** may be an armband (e.g., a smart watch, such as a SAMSUNG® GALAXY GEAR™ watch or an APPLE® watch, a FITBIT® armband, or other device capable of being worn on the arm of the user **222**). In other examples (not shown in FIG. 2), the wearable control device **228** may include a ring, glasses (e.g., GOOGLE® GLASS™), a headset (e.g., BLUETOOTH® headset), clothing (e.g., shirts, gloves, etc.), or other wearable control device capable of detecting gestures performed by the user **222**.

(14) The wearable control device **228** may detect gestures performed by the user **222** and may transmit digital messages to one or more control devices (e.g., central control devices, wearable control devices, wireless communication devices, control-source devices, and/or control-target devices). The wearable control device **228** may detect the gestures performed by the user **222** and the gestures may be used to determine one or more control-target devices and/or load control instructions for controlling an electrical load via the one or more control-target devices. For example, the control-target devices and/or load control instructions may be determined at the wearable control device **228** based on the gesture performed by the user **222**. In another example, the wearable control device **228** may transmit a digital message that indicates the gesture performed by the user, which may be used by another device to determine the control-target devices and/or load control instructions. The control-target devices and/or load control instructions may be included in the digital messages transmitted directly from the wearable control device **228** to the control-target devices. The wearable control device **228** may communicate with the control-target devices via wired or wireless communications, e.g., via radio-frequency (RF) signals.

(15) The wearable control device **228** may send digital messages to and/or receive digital messages from one or more intermediate devices capable of communicating with the wearable control device **228** and other control devices in the load control environment **202**. For example, the wearable control device **228** may communicate with a central control device **230** and/or a wireless communication device **232** (e.g., a cellular phone, a tablet, a laptop, or other computing device capable of performing communications on a wireless network). The central control device **230** and/or a wireless communication device **232** may be control devices capable of receiving digital messages from the wearable control device **228** and/or transmitting digital messages to one or more control-target devices for controlling an electrical load. The central control device **230** may be a local computing device located in the load control environment or a remote computing device. The central control device **230** and the wireless communication device **232** may communicate with one another (e.g., via a wireless communication network, such as a cellular network, WI-FI® network, etc.). For example, the wearable control device **228** may communicate digital messages to the central control device **230** via the wireless communication device **232**. The wearable control device **228** may include one or more communication circuits capable of communicating with the central control device **230** and/or the wireless communication device **232**. The communication circuits may be capable of communicating via one or more communication protocols. For example the communication circuits may be capable of communicating with the central control device **230** and/or the wireless communication device **232** via wireless signals (e.g., RF signals), such as WI-FI® signals; WIMAX® signals; BLUETOOTH® signals; near field communication (NFC) signals; proprietary communication signals, such as CLEAR CONNECT™; ZIGBEE® signals, Z-WAVE signals, and/or the like. Each communication circuit may be capable of communicating on different protocols and/or frequencies. For example, different communication circuits may enable the wireless communication device **232** to communicate with the wearable control device **228** via one

protocol or frequency, and with the central control device **230** or control-target devices via another protocol or frequency.

(16) A control device may be a central control device, such as central control device **230**. The central control device **230** may be configured to monitor the status of electrical loads and/or control-target devices. The central control device **230** may receive digital messages from control-target devices capable of two-way communication. The communications may be transmitted from the control-target devices via wired and/or wireless signals. In order to perform wireless communications, the control-target devices may include a communication circuit (e.g., transmitter or transceiver) capable of performing RF communications.

(17) The digital messages may also be sent to the central control device **230** in response to a status request message from the central control device **230**, a status request message from the wireless communication device **232** or the wearable control device **228**, a change in the status of the control-target device (e.g., turning on a lamp **206**, **226**, changing the dimming intensity of the lamp **206**, **226**, changing the level of the covering material **218**, changing the temperature on the temperature control device **220**), based on the location of the user **222** (e.g., when the user **222** enters the load control environment **202**, when the user **222** comes within a predefined distance of a control-target device, etc.) and/or after a predetermined period of time (e.g., an hour, a day, etc.) has elapsed. The status request messages may be triggered at the central control device **230** based on a digital message received from the wireless communication device **232** or the wearable control device **228**. The digital messages that report the status of the control-target devices may indicate whether power is being provided to an electrical load (e.g., lamps **206**, **226**) and/or the current status of the electrical load (e.g., whether the lamps **206**, **226** is on or off, the dimming intensity of the lamp **206**, **226**, the position of the covering material **218**, the temperature at which the HVAC system is being controlled by the temperature control device **220**, etc.).

(18) The wearable control device **228** may perform an association procedure with other devices in the load control system (e.g., control devices, the central control device **230**, the wireless communication device **232**, etc.). The wearable control device **228** may enter an association mode for transmitting digital messages for associating with one or more other devices. The wearable control device **228** may enter the association mode upon actuation of one or more buttons on the wearable control device **228** and/or performance of an association gesture. The other devices in the load control system (e.g., control devices, the central control device **230**, the wireless communication device **232**, etc.) may also enter an association mode for being associated with the wearable control device **228** or otherwise recognize association messages transmitted from the wearable control device **228**. The other devices in the load control system may enter an association mode upon a user actuation of one or more buttons on the devices. During the association procedure, the wearable control device **228** may transmit digital messages that include a unique identifier (e.g., a serial number) of the wearable control device **228**. The digital messages may be received by other devices in the load control system and the devices may store the unique identifier of the wearable control device **228**, such that subsequent digital messages received from the wearable control device **228** may be identified.

(19) The wearable control device **228** may transmit digital messages that include the unique identifier of the wearable control device (e.g., a serial number) for controlling an electrical load. The devices that are associated with the wearable control device **228** may respond to the digital messages when they identify the serial number of the wearable control device **228**. For example, a control-target device may execute load control instructions indicated in a digital message from the wearable control device **228** to control an electrical load. The wearable control device **228** may transmit digital messages via broadcast messages or directly to control-target devices.

(20) The digital messages from the wearable control device **228** may include information that may identify one or more control-target devices. For example, the digital messages from the wearable control device **228** may include a unique identifier of one or more control-target devices, a type of

control-target device (e.g., lighting control devices, motorized window treatments, etc.), and/or a zone or location of the control-target devices. The wireless communication device **232** and/or the central control device **230** may receive the digital messages from the wearable control device **228** and may communicate digital messages to the identified control-target devices for controlling an electrical load. The wireless communication device **232** and/or the central control device **230** may be used to determine the control-target devices and/or the load control instructions for controlling the electrical loads based on the gestures indicated by the wearable control device **228**. The wireless communication device **232** and/or the central control device **230** may determine the load control instructions locally or may forward the indicated gestures to a remote computing device that may determine and return the control-target devices and/or the load control instructions for being transmitted to the control-target devices.

(21) The gesture performed by the user **222** may be identified by the wearable control device **228** and may be compared (e.g., at the wearable control device **228**, the wireless communication device **232**, the central control device **230**, or another device) to movements associated with one or more load control instructions and/or control-target devices. The association of gestures to the load control instructions and/or control-target devices may be stored in a datastore (e.g., database). The datastore may be stored in memory at the wearable control device **228**, the wireless communication device **232**, and/or the central control device **230**.

(22) The wearable control device **228** may include a gyroscope and/or an accelerometer for identifying the gestures performed by the user **222**. The gyroscope may identify an orientation of the wearable control device **228**. The accelerometer may identify an acceleration of the wearable control device **228**. The accelerometer may be used to detect magnitude and direction of the acceleration of the wearable control device **228**, such as in the form of a vector, an orientation of the wearable control device **228**, and/or vibrations of the wearable control device **228**.

(23) The wearable control device **228** may be an armband, ring, glasses, a headset, clothing (e.g., shirts, gloves, etc.), or other wearable control device capable of detecting gestures performed by the user **222**. The wearable control device **228** may detect a change in orientation, direction, and/or speed. The wearable control device **228** may include multiple sensors for detecting gestures performed by a user. For example, the wearable control device **228** may be a shirt or gloves that may include a sensor for detecting different gestures performed by different arms, hands, and/or fingers of the user **222**.

(24) The orientation of the wearable control device **228** may be used to identify a control-target device and/or load control instructions for controlling an electrical load via the control-target device. The wearable control device **228** may be an armband capable of detecting the user **222** rotating an arm or wrist. For example, the user **222** may rotate an arm or wrist to mimic the movement of turning a knob (e.g., a doorknob) or the movement of a lighting control device **204** (e.g., a dimmer switch). The wearable control device **228** may detect the rotation of the arm of the user **222** or the wrist of the user **222** and/or an amount of the rotation, which may indicate an amount of change to a dimming level of a lighting load. The wearable control device **228** may sense sudden movements by the user **222**, such as a twitch left or right, to control a control-target device. The wearable control device **228** may detect when the user **222** changes the orientation of the wearable control device **228** by a predetermined distance. For example, the wearable control device may identify when the user **222** rotates the wearable control device **228** a predetermined distance. A change in the orientation of the wearable control device **228** by a predetermined distance may identify a control-target device and/or load control instructions. The wearable control device **228** may detect when the user **222** changes the orientation of the wearable control device **228** at a predetermined speed. For example, the wearable control device may identify when the user **222** rotates the wearable control device **228** a predetermined speed. A change in the orientation of the wearable control device **228** at a predetermined speed may identify a control-target device and/or load control instructions. The orientation of the wearable control device **228** may be

changed a number of times to identify different control-target devices and/or control instructions.

(25) The orientation of the wearable control device **228** may be used to control an intensity (e.g., a dimming intensity) of the lamps **206**, **226**, a position of the covering material **218**, and/or a temperature of the load control environment (e.g., as measured by the temperature control device **220**). The orientation of the wearable control device **228** may be used to turn an electrical load on or off. The orientation of the wearable control device **228** may be changed a number of times to identify different zones and/or scenes (e.g., presets) for setting control devices to a predetermined level. A preset may be a predefined group of one or more load control devices (e.g., control-target devices) and control instructions that identify a predetermined level for the electrical load (e.g., dimming level for lighting load, shade position for electrical shades, set point temperature for HVAC system, etc.). A scene may be a predefined configuration of one or more control devices in the load control environment **202** (e.g., a movie scene, a bedtime scene, a home or away scene, etc.). For example, in a movie scene or a bedtime scene, the covering material **218** may be closed and/or the intensities of the lamps **206**, **226** may be adjusted to a low dimming level (e.g., 5%) or turned off. In the bedtime scene, the temperature control device **220** may also increase or decrease the temperature to a predetermined level (e.g., depending on the time of year). An away scene may control one or more control devices for when the user is away from the load control environment. For example, in the away scene, the lamps **206**, **226** may be turned off and the temperature of the temperature control device **220** may be increased or decreased (e.g., depending on the time of year). A home scene may control one or more control devices for when the user is occupying the load control environment. For example, in the home scene, the lamps **206**, **226** may be turned on and the temperature of the temperature control device **220** may be increased or decreased (e.g., depending on the time of year). The user **222** may shake the wearable control device **228** to reset the orientation of the wearable control device or initialize the wearable control device **228** (e.g., set the orientation and/or other parameters for measuring gestures to zero).

(26) The scene configuration may be preconfigured based on user input. One or more control devices may be associated with each scene and may be sent control instructions for controlling an electrical load according to a predetermined configuration. For an away scene, for example, the intensities of the lamps **206**, **226** may be dimmed to a predetermined level or the lamps **206**, **226** may be turned off, the motorized window treatment **216** may adjust the position of the covering material **218**, and/or the temperature of the temperature control device **220** may be increased (e.g., in the summer) or decreased (e.g., in the winter) to reduce power consumption while the user is away. For example, the motorized window treatment **216** may lower the position of the covering material **218** as part of the away scene while the user is away.

(27) The orientation of the wearable control device **228** may be used to determine an angle of the arm of the user **222** when raised or lowered (e.g., from an initial starting point of zero). The different angles at which the user **222** positions an arm may indicate different control-target devices and/or control instructions. For example, the user **222** may position an arm at different angles to identify different zones or scenes for performing load control. The distance the user **222** raises or lowers an arm may also, or alternatively, be used to indicate different control-target devices and/or control instructions.

(28) If the wearable control device **228** is a ring, the ring may determine a position of a finger of the user **222**. For example, the position of the thumb of the user may be used to indicate different control-target devices and/or control instructions. The position of the thumb relative to other fingers on the hand of the user **222** may be identified. The different positions of the user's finger may indicate different scenes (e.g., presets) for controlling one or more control-target devices. The orientation of the ring may also be used to control an electrical load. For example, a dimming level for the lamp **206**, **226** or a level of the covering material **218** for the motorized window treatment **216** may be adjusted by changing the orientation of the ring (e.g., rotating the ring on the finger of the user **222**).

(29) The user **222** may identify the control-target device to which the load control instructions may be sent by performing a gesture or otherwise identifying the control-target device. For example, the user **222** may identify a control-target device by pointing in the direction of the control-target device (e.g., using an armband, shirt, ring, or other wearable device capable of identifying a vector pointing in the direction of a control device) or facing the control-target device (e.g., using an armband, shirt, glasses, or other wearable device capable of identifying a direction the user **222** is facing). The wearable control device **228** may identify a vector in the direction of a control-target device and the direction of the vector may be compared (e.g., at the wearable control device **228**, the wireless communication device **232**, the central control device **230**, or another computing device) against a mapping of the load control environment **202** or the known location of a control-target device to identify one or more control-target devices. In another example, each control-target device, or type of control-target devices for executing load control instructions, may be identified with a specific gesture performed by the user **222**. The wearable control device **228** may identify the gesture performed by the user and may determine the control-target device, or communicate the gesture to another device (e.g., the wireless communication device **232** or the central control device **230**) for determining the control-target device based on the gesture.

(30) The control-target devices may be identified by zone. A user may perform a gesture that identifies a zone that includes one or more control-target devices. The wearable control device **228** may identify a vector in the direction of a zone and the direction of the vector may be compared (e.g., at the wearable control device **228**, the wireless communication device **232**, the central control device **230**, or another computing device) against a mapping of the load control environment **202** or the known location of a zone to identify one or more control-target devices in the zone.

(31) The control-target device may be identified using another device. For example, the user **222** may select one or more control-target devices or zones on the wireless communication device **232**. The user **222** may perform a gesture for controlling the identified control-target device. For example, the user **222** may select the lamp **206** and/or lighting control device **204** on the wireless communication device **232** and may raise the arm on which the wearable control device **228** is being worn to increase the intensity of the lamp **206**.

(32) The user **222** may perform a gesture to identify the control-target device that the user **222** would like to control and perform another gesture to send load control instructions for controlling the identified control-target device. For example, the user **222** may point an arm in the direction of the lighting control device **204** and/or the lamp **206** to indicate the lighting control device **204** as the control-target device that the user **222** would like to control and the user **222** may raise an arm to increase the intensity of the lamp **206**. The intensity of the lamp **206** may be increased by a predetermined amount, such as twenty percent, for each time the user **222** raises the arm or the amount of increase may correspond to the distance the user **222**'s arm travels from a starting point to an ending point. In another example, the dimming intensity may be increased for each period of time, e.g., each second, the user **222** holds the gesture.

(33) The gesture performed by the user may identify the control-target devices that the user **222** would like to control and indicate the control instructions to be sent to the control-target devices. For example, the wearable control device **228** may identify a gesture performed by the user **222** that identifies the lighting control device **204**, the plug-in control device **224**, and the motorized window treatment **216** and send control instructions to each of the control-target devices **204**, **224**, **216** for controlling the corresponding electrical load. The user **222** may lower an arm to instruct the lighting control device **204** to decrease the intensity of the lamp **206**, instruct the plug-in control device **224** to decrease the intensity of the floor lamp **226**, and/or instruct the motorized window treatment **216** to lower the covering material **218**. The gesture may correspond to a scene that causes each of the control-target devices **204**, **224**, **246** to be set to a predetermined level. In another example, the dimming level of the lighting control device **204** and the plug-in control

device **224** may be decreased by a predetermined amount (e.g., twenty percent), and the position of the covering material **218** may be lowered by a predetermined amount (e.g., twenty percent), when the user **222** lowers the arm. The amount of change may alternatively correspond to the distance the arm of the user **222** travels from a starting point to an ending point. In another example, the intensity of the lamp **206, 226** may be decreased and the position of the covering material **218** may be lowered for each period of time, e.g., each second, the user **222** holds the gesture.

(34) The wearable control device **228** may sense one or more parameters (e.g., biometric data) that define the physical condition (e.g., behavior, movement, comfort, and/or health) of the user **222**. For example, the wearable control device **228** may detect the heart rate of the user **222**. The heart rate information of the user **222** may be detected in the fingers (e.g., using sensors in a ring or gloves) or the wrist (e.g., using sensors in an armband or shirt) of the user **222**. The heart rate information of the user **222** may be used to perform load control in the load control environment **202**. For example, the heart rate information may be used to automatically sense when user is sleeping and may control the electrical load of one or more control-target devices (e.g., setting a bedtime scene to turn off the lamp **206, 226**, increase or decrease the temperature on the temperature control device **220**, lower the covering material **218**, turn off a television that may be plugged in to the plug-in control device **224**, etc.). The heart rate information may be used to automatically sense when user wakes up, sits up in a bed **208**, or gets out of the bed **208** and may control the electrical load of one or more control-target devices (e.g., setting a wakeup scene to turn on the lamp **206, 226** and set to a predetermined dimming level, increase or decrease the temperature on the temperature control device **220**, raise the covering material **218** to a predetermined level, etc.). When the heart rate information indicates that the user **222** is below a predetermined threshold and/or the time of day is after a predetermined time, the user **222** may automatically be determined to be asleep. When the heart rate information indicates that the user **222** is above a predetermined threshold and/or the time of day is after a predetermined time, the user **222** may automatically be determined to be awake.

(35) The predetermined heart rate threshold may be different among different users. The predetermined heart rate threshold for determining whether the user **222** is asleep may be based on the user **222**'s average heart rate during daytime hours (e.g., a predetermined number of daytime hours). As the heart rate of the user **222** may rise above the predetermined heart rate threshold while the user is asleep, the user **222** may be assumed to be asleep between predetermined hours once the heart rate of the user **222** falls below the predetermined threshold. For example, the user **222** may be determined (e.g., by the wireless communication device **232**, the system control device **230**, or other device) to be asleep when the heart rate of the user **222** drops below a predetermined threshold after 9:00 PM and the user **222** may be determined (e.g., by the wireless communication device **232**, the central control device **230**, or other device) to be asleep until the heart rate of the user **222** rises above a predetermined threshold after 6:00 AM.

(36) One or more control devices may be used to wake up the user **222** at a predetermined time. For example, a wakeup scene may be used to wake up the user **222** at a predetermined time in the morning. The wakeup scene may turn on the lamp **206, 226** to a predetermined dimming intensity and/or raise the covering material **218** to a predetermined level. The wakeup scene may also, or alternatively, turn on a television or music to a predetermined volume level (e.g., using the plug-in control device **224** or the wireless communication device **232**).

(37) The wearable control device **228** may identify the user **222**. For example, the unique identifier (e.g., serial number) of the wearable control device **228** may be associated with one or more users and the association may be stored (e.g., in a database) at the control devices, the wireless communication device **232**, and/or the central control device **230**. When the wearable control device **228** is shared by multiple users, the wearable control device **228** may transmit a different user identifier for each user. The wearable control device **228** may identify the user **222** based on a user identification action, such as an actuation of one or more buttons on the wearable control

device **228** and/or one or more gestures performed by the user **222**. The wearable control device may also include a biometric sensor (e.g., fingerprint scanner, eye scanner, etc.) for identifying the user **222**. After the user **222** is identified, the wearable control device **228** may transmit digital messages that also identify the user **222**.

(38) The unique identifier transmitted by the wearable control device **228** may be recognized (e.g., by the central control device **230**) for enabling control of various control devices in the load control environment **202**. The unique identifier may be used to access a gesture datastore (e.g., database) associated with the unique identifier. The gesture datastore may include an indication of identified gestures and associated control-target devices and/or control instructions. The wearable control device **228** may send the unique identifier to the central control device **230** and the central control device **230** may permit access to the gesture datastore (e.g., stored locally or at a remote location) for control of the electrical loads in the load control environment **202**. The user identifier may be recognized (e.g., by other central control devices) at other locations (e.g., at a residence, office, hotel, other rooms or floors in the same building, etc.) for enabling control of various control devices at different locations by the user **222** using the same gestures or other commands used in the load control environment **202**. The user **222** may use the same gestures or other commands to control the same types of control devices. For example, the user **222** may use the same gestures to control lighting control devices in different locations.

(39) The wearable control device **228** may receive and identify audio commands for controlling control-target devices. A microphone in the wearable control device **228** may record audio or capture a live audio stream. The audio commands may also be received by another device, such as the wireless communication device **232**, for example. The audio commands may be paired with gestures to determine a control device and/or control instructions for controlling the control device. For example, the user **222** may point to the lighting control device **204** or the lamp **206** and say “turn on” to command the lighting control device **204** to turn on the lamp **206**. The audio commands may also be used to identify the device. The user **222** may say “kitchen lights” to identify the lamps in the kitchen and may raise an arm to increase the dimming level of the identified kitchen lamps. The voice command may identify a location, zone, and/or lighting load for being controlled by the wearable control device **228**. The audio commands may also be stored in the gesture datastore and may be accessed at different locations.

(40) The user **222** may engage the wearable control device **228** for identifying commands for transmitting digital messages to control an electrical load. The wearable control device **228** may be engaged by actuating a button on the wearable control device, actuating a button on the wireless communication device **232**, reciting a voice command that is recognizable to the wearable control device **228**, and/or performing an engage gesture. The user **222** may engage the wearable control device **228** by shaking the wearable control device or performing another distinctive movement that is recognizable by the wearable control device **228**. The engaged wearable control device **228** may enter a mode for identifying gestures performed by the user **222** for controlling an electrical load.

(41) The wearable control device **228** may indicate to the user **222** that the wearable control device **228** is engaged. For example, the wearable control device **228** may flash an indicator light after the wearable control device **228** is engaged. The wearable control device **228** may indicate that it is engaged by sending instructions to a control device. For example, the wearable control device **228** may instruct the lighting control device **204** to flash the lamp **206**, instruct the motorized window treatment **216** to adjust the covering material **218** (e.g., jog the covering material **218** up or down by a predetermined amount, wiggle the covering material **218**, or tilt slats of the covering material **218**), and/or instruct the plug-in control device **224** to flash the floor lamp **226** or turn on or off another device that is plugged in to the plug-in control device **224**.

(42) The engaged wearable control device **228** may identify one or more gestures performed by the user **222**. The period of time for which the wearable control device **228** is engaged may be a pre-

determined period of time or until the user **222** disengages the wearable control device **228**. The user **222** may re-engage the wearable control device **228** after each identified gesture or the user **222** may perform consecutive gestures for a period of time without re-engaging the wearable control device **228**. The user **222** may disengage the wearable control device **228** by performing a disengage gesture that may cause the wearable control device **228** to be unable to control a control device until the user **222** re-engages the wearable control device **228**.

(43) The wearable control device **228** may be used to identify the location (e.g., room, floor, building, or other space) of the user **222**. The wearable control device **228** may include a communication circuit capable of communicating via NFC signals. The load control environment **202** may include an NFC device **210** capable of detecting the NFC signals transmitted by the wearable control device **228**. For example, the NFC device **210** may comprise a passive NFC tag, such as a radio-frequency identification (RFID) tag, or may comprise an active NFC device (e.g., an NFC sensor). The user **222** may move the wearable control device **228** in close proximity to the NFC device **210**, for example, by touching the wearable control device **228** to the NFC device **210** or by waving the wearable control device **228** close to the NFC device **210**, to enable load control in the load control environment **202** using the wearable control device **228**. The wearable control device **228** may receive a unique identifier from the NFC device **210**, and may transmit the unique identifier to the central control device **230** to indicate that the user **222** is located in the load control environment **202**. In addition, the NFC device **210** may receive a unique identifier from the wearable control device **228** and may communicate the unique identifier to the central control device **230** to indicate that the user **222** is located in the load control environment **202**. The central control device **230** may listen for digital messages from the wearable control device **228** upon receiving the unique identifier.

(44) The location of the user **222** may be paired with a gesture to perform load control. For example, the user **222** may wave the wearable control device **228** in an upward direction in front of the NFC device **210** to turn on or increase the dimming intensity of the lamps **206**, **226** in the load control environment **202**. The user **222** may wave the wearable control device **228** in an upward direction to also, or alternatively, increase the level of the covering material **218** and/or increase the temperature of the temperature control device **220**. The user **222** may wave the wearable control device **228** in a downward direction in front of the NFC device **210** to turn off or decrease the dimming intensity of the lighting loads **206**, **226**, decrease the level of the covering material **218**, and/or decrease the temperature of the temperature control device **220**. The user **222** may wave the wearable control device **228** in a certain direction in front of the NFC sensor to engage a scene (e.g., movie scene, bedtime scene, etc.) in the load control environment.

(45) The control-target devices of the load control environment **202** may include NFC communication circuits capable of detecting the NFC signals transmitted by the wearable control device **228**. The wearable control device **228** may touch or be waved in front of a control-target device to activate the control-target device for being controlled by the wearable control device **228**. Within a period of time from the activation of the control-target device, the user **222** may perform a recognized gesture for controlling the activated control-target device. The wearable control device **228** touching or being waved in front of a control-target device may also be used to identify the location of the user within the load control environment **202**. The user **222** may use the wearable control device **228** to control devices within a zone or predetermined distance from the NFC device **210** (or control-target device having an NFC communication circuit) that was activated by the user **222**.

(46) The wearable control device **228** may have a global positioning system (GPS) circuit and may thus be GPS enabled. The location of the wearable control device **228** may be determined from the GPS circuit. The location determined by the GPS circuit of the wearable control device **228** may indicate the location of the user **222**. The location determined by the GPS circuit of the wearable control device **228** may be communicated to the wireless communication device **232** and/or the

central control device **230**. When the user **222** is determined (e.g., by the wearable control device **228**, the wireless communication device **232**, and/or the central control device **230**) to be within a predetermined location (e.g., room, portion of a room, floor, portion of a floor, group of floors, building, etc.), the wearable control device **228** may be used to transmit control instructions to control-target devices in the location. The location determined by the GPS circuit of the wearable control device **228** may also, or alternatively, be used to determine whether the user **222** is within a predefined distance of one or more control-target devices. The predetermined location may be a distance (e.g., three feet) from the control-target device. When the user **222** is determined (e.g., by the wearable control device **228**, the wireless communication device **232**, and/or the central control device **230**) to be within the predetermined distance of a control-target device, or an area comprising an electrical load controlled by the control-target device, the wearable control device **228** may be used to transmit control instructions to the control-target device. For example, when the user **222** is approaching the load control environment **202** (e.g., which may be a home, business, or space within the home or business, such as a room or portion of a room within the home or business), and the user **222** reaches a predetermined distance from the load control environment **202**, one or more control-target devices may be controlled or set to a preconfigured setting or scene (e.g., preset). Similarly, when the user **222** is leaving the load control environment **202**, and the user **222** reaches a predetermined distance from the load control environment **202**, one or more control-target devices may be controlled or set to a preconfigured setting or scene (e.g., preset).

(47) The wearable control device **228** may associate (e.g., pair) with a device (e.g., the wireless communication device **232**, such as a smartphone, tablet, laptop, etc.). For example, the wearable control device **228** may pair with a wireless communication device **232** positioned on, or near, the user **222**. The wearable control device **228** may include a communication circuit capable of pairing with the wireless communication device **232** and/or wirelessly communicating with the wireless communication device **232**. The wearable control device **228** may pair with a wireless communication device **232** for determining the location of the user **222**. The wireless communication device **232** may provide a reference point. For example, the wireless communication device **232** may provide a reference point to assist in determining the location and/or movement of the wearable control device **228**.

(48) The wireless communication device **232** may be GPS enabled and may be used to indicate the location of the user **222** and/or the location of the wearable control device **228** (e.g., the location of the wearable control device **228** with respect to the wireless communication device **232**). For example, the direction the user **222** is moving and/or the direction the wearable control device **228** is moving may be determined based on the wireless communication device **232**. The wireless communication device **232** and/or the wearable control device **228** may measure a signal strength received (e.g., a received signal strength indicator (RSSI)) and/or a signal strength transmitted from one device and another device. For example, the wearable control device **228** may determine that it is being moved away from and/or moved toward the wireless communication device **232** because a signal (e.g., an NFC signal, BLUETOOTH signal, WI-FI® signal, cellular signal, etc.) between the wearable control device **228** and wireless communication device **232** becomes less strong and/or stronger, respectively. The direction the wireless communication device **232** is moving may be determined based on the direction of the GPS coordinates of the wireless communication device **232** and/or the strength of a wireless communication signal (e.g., an NFC signal, BLUETOOTH signal, WI-FI® signal, cellular signal, etc.) of the wireless communication device **232**.

(49) The central control device **230** may learn from gestures performed by the user **222** and determine the location of the user **222** to perform control of various control-target devices in the user's location. The central control device **230** may record the gestures of the user **222** and an identified location of the gesture in the gesture datastore. The wearable control device **228** and/or the central control device **230** may enter a programming mode for recording the gestures performed

by the user **222**. The programming mode may be entered by performing a programming gesture using the wearable control device **228**, actuating one or more buttons on the wearable control device **228**, and/or actuating one or more buttons on the wireless communication device **232**.

(50) The user **222** may define the control parameters for a learned gesture. The control parameters may be entered via the wireless communication device **232** and/or the wearable control device **228**. For example, the user **222** may define the boundaries of the location in which the gesture may be applied, the control-target devices to which the gesture is associated, and/or the control instructions for being sent to the control-target devices. While the control parameters may be entered by the user **222** via the wireless communication device **232** or the wearable control device **228**, the control parameters may be sent to the central control device **230** for being stored in the gesture datastore.

(51) The location in which the gesture may be applied may be defined in terms of distance from one or more control-target devices, an area in which one or more control-target devices are located, or the distance from an area in which the control-target devices are located. The identity of the control-target devices to which the gesture may be defined by a user selection of the control-target devices on the wireless communication device **232** or the wearable control device **228**. The identity of the control-target devices to which the gesture may be applied may be defined by performing a gesture on the wearable control device **228** that identifies the control-target devices. For example, the control-target devices may be identified based on a vector that is pointed from the wearable control device **228** to the control-target device. The vector may be identified by the wearable control device **228** and transmitted to the central control device **230** for identifying the control-target devices indicated by the vector. The control instructions for being sent to the control-target devices may be defined by a user selection on the wireless communication device **232** or the wearable control device **228**. For example, the user **222** may record a gesture for controlling the lighting control device **204** and may associate the gesture with control instructions for turning on the lamp **206**, increasing the amount of power provided to the lamp **206** a predetermined amount, decreasing the amount of power provided to the lamp **206** a predetermined amount, or setting the intensity of the lamp **206** to a predetermined level. In another example, the user **222** may record a gesture for controlling the motorized window treatment **216** and may associate the gesture with control instructions for raising the covering material **218** by a predetermined amount, lowering the covering material by a predetermined amount, or setting the position of the covering material **218** to a predetermined level. The recorded gesture may be associated with similar control instructions for controlling the temperature control device **220**, the plug-in control device **224**, or another control-target device.

(52) The central control device **230** may learn to automatically control one or more control-target devices in the load control environment **202** based on gestures performed by the user **222**. The central control device **230** may identify when the user **222** repeatedly performs (e.g., more than a predetermined number of times) a gesture in a location for controlling one or more identified control-target devices. The gesture may be a preprogrammed gesture that is associated with load control instructions for controlling an electrical load, such as the user **222** raising an arm to increase the dimming intensity of the lamp **206** when the user **222** enters the load control environment **202**. The gesture may also, or alternatively, be a natural gesture performed by the user **222** to control an electrical load, such as the user **222** actuating a raise button on a wall-mounted dimmer (not shown) to increase the intensity level of the lamp **206** when the user **222** enters the load control environment **202**.

(53) The central control device **230** may store gestures performed by the user **222** temporarily to determine whether to associate the gesture with a control-target device and/or control instructions. The central control device **230** may also store the location of the user **222** when the user **222** performed the gesture and/or the time at which the gesture was performed. The central control device **230** may determine whether the status of an electrical load or a control-target device has changed within a predetermined period of time from the user performing the gesture. The central

control device **230** may automatically send load control instructions for controlling one or more electrical loads based on one or more gestures performed by the user **222** a predetermined number of times, the time the one or more gestures were performed, the location at which the one or more gestures were performed, and/or the change in status of one or more electrical loads after the one or more gestures were performed by the user **222**.

(54) The central control device **230** may determine to associate the gesture with a control-target device and/or control instructions when the central control device **230** identifies the gesture being performed repeatedly (e.g., more than a predetermined number of times) in the same location and/or at the same time of day or week. In an example, the central control device **230** may identify that the user **222** performs the same gesture a predetermined number of times when the user **222** enters the load control environment **202**. The central control device **230** may detect that the status of the lamp **206** is changed to turn on after the user **222** performs the gesture. The gesture performed by the user **222** may be a gesture that is associated with load control instructions for turning on the lamp **206**, or the user **222** flipping a switch to turn on the lamp **206**, for example. After the central control device **230** identifies that the gesture is performed the predetermined number of times, the central control device **230** may associate the gesture in the gesture datastore with the lighting control device **204** and control instructions for turning on the lamp **206**, such that the lamp **206** may be automatically turned on when the user **222** enters the load control environment **202**. The central control device **230** may similarly automate the control of other control-target devices in the load control environment **202**.

(55) The user **222** may indicate whether the user **222** likes or dislikes the automated control of the control-target devices in the load control environment **202**. The user **222** may indicate whether the user **222** likes or dislikes the automated control of the control-target devices by actuating one or more buttons on the wireless communication device **232** and/or the wearable control device **228**. The user **222** may indicate whether the user **222** likes or dislikes the automated control of the control-target devices by performing one or more gestures that are identifiable by the wearable control device **228**. The actuation of the one or more buttons or the performance of one or more gestures by the user **222** may cause transmission of a digital message to the central control device **230** that includes feedback that indicates whether the user **222** likes or dislikes the automated control of the control-target devices.

(56) The central control device **230** may expect to receive the feedback indicating whether the user **222** likes or dislikes the automated control of the control-target devices within a predetermined period of time after the automated control is implemented. If the user **222** does not provide the feedback within the predetermined period of time, the central control device **230** may assume the user **222** likes the automated control.

(57) The central control device **230** may have different learning strengths for learning gestures performed by the user **222**. For example, the user **222** may be configured to set the central control device (e.g., via the wireless communication device **232** and/or the wearable control device **228**) to different levels of learning strength. The levels of learning strength may range from weaker to stronger learning strength. As the levels increase in strength of learning, the number of gestures that may be stored within a period of time and/or the length of time for which gestures are stored may be increased. The greater number of gestures being stored and/or the greater length of time for which gestures are stored may enable more gestures to be performed by the user **222** and identified as being performed a predetermined number of times.

(58) The central control device **230** may recommend changes to the load control instructions associated with a gesture based on additional gestures identified by the central control device **230** and/or a change in status of an electrical load or a control-target device. For example, the user **222** may perform a gesture associated with control instructions for turning on the lamp **206**. The central control device **230** may identify that the user **222** changes the dimming level after the lamp **206** is turned on. The change in dimming level may be detected by identifying a gesture associated with

control instructions for changing the dimming level or a gesture by the user **222** to increase the dimming level on a wall-mounted dimmer switch. The central control device **230** may also, or alternatively, detect a change in the status of the dimming level of the lamp **206**. The central control device **230** may recommend, via a display on the wearable control device or the wireless communication device **232**, a change in the load control instructions associated with the gesture performed by the user **222** to turn on the lamp **206**. The central control device **230** may recommend the gesture performed by the user **222** be associated with turning on the lamp **206** to the adjusted dimming level detected by the central control device **230**, for example. The suggested change may similarly be identified for controlling one or more other control-target devices. The change may be selected after detecting gestures performed by the user **222** a predetermined number of times.

(59) When the central control device **230** detects a change in the status of an electrical load or control-target device (e.g., a single time or a predetermined number of times) and that there is not a gesture associated with control instructions for performing the detected change, the central control device **230** may ask the user **222** (e.g., via a display on the wearable control device **228** or the wireless communication device) whether the user **222** would like to record a gesture for performing the detected change. For example, when the central control device **230** detects a change in the status of an electrical load or control-target device and that there is not a gesture associated with control instructions for performing the detected change, the user **222** may perform a gesture and associate the gesture with control instructions for performing the detected change. The central control device **230** may be configured to associate a natural gesture with the control instructions, may be configured to associate a unique gesture with the control instructions, and/or may be configured to associate a previously associated gesture with the control instructions.

(60) A natural gesture may be a gesture that the user **222** may perform naturally. A natural gesture may be a gesture performed naturally by the user **222** when changing the status of the electrical load. For example, the user **222** may perform the natural gesture of rotating, raising, or lowering an intensity adjustment actuator of a dimmer to control a dimming intensity of the lamp **206**, and this natural gesture of rotating the user's wrist, or raising or lowering an arm, may be associated with lighting control device **204** to adjust the dimming intensity of the lamp **206**. The central control device **230** may ask the user **222**, after performing a natural gesture, whether to assign the gesture to a control instruction and/or an electrical load. The central control device **230** may learn (e.g., automatically learn) the natural gesture and associate the gesture with a control instruction and/or electrical load. For example, the central control device **230** may learn that each time that the user **222** sits on a couch and points a television remote control at a television, the user **222** also lowers the intensity of one or more lamps **206** in the room. The central control device **230** may learn this gesture of the user **222**, and the central control device **230** may associate the user **222** pointing the television remote control at the television with lowering the intensity of one or more lamps **206** in the room.

(61) The central control device **230** may be configured to control (e.g., automatically control) the electrical loads in response to detecting a preprogrammed natural gesture. For example, the central control device **230** may be configured to determine that the user **222** is moving quickly (e.g., by determining that the user's arms are swinging while moving) and may automatically turn lamp **206** on to full intensity. The central control device **230** may be configured to determine that a user has fallen asleep (e.g., by detecting a lack of movement of the user **222**) and may automatically dim and/or turn off lamp **206**. The central control device **230** may be configured to determine that the user **222** is exercising and/or performing a particular activity. The central control device **230** may control the electrical load to a desired level, based on the exercise and/or the activity. For example, the central control device **230** may be configured to determine an activity mode (e.g., a warm up mode, active mode, cool down mode, rest mode, etc.) associated with the exercise and/or activity and the central control device **230** may be configured to control the electric load accordingly (e.g., may set the lamp **206** to a desired level, based on the activity mode).

(62) A unique gesture may be a gesture that the user **222** does not perform naturally. A unique gesture may be a gesture that a user does not typically perform, such that the unique gesture may not be confused with a natural gesture and/or a previously associated gesture. For example, a unique gesture may include having the user **222** hold an arm at a right angle. The gesture of holding an arm at a right angle may not be a natural gesture, and/or the gesture of holding an arm at a right angle may not be a previously associated gesture. Because the unique gesture may not be a natural gesture and/or a previously associated gesture, the unique gesture may not be confused with natural gestures and/or previously associated gestures. A unique gesture may be used for ordinary changes to an electric load (e.g., dimming a light) and/or a unique gesture may be used for extreme changes to an electric load (e.g., actuating an emergency system, such as a fire alarm, a sprinkler system, etc.).

(63) Though functionality may be described herein as being performed by a certain device, other devices may be similarly configured, alone or in combination with other devices, to perform such functionality. For example, though one control device, such as the central control device **230**, the wearable control device **228**, the wireless communication device **232**, or a control-target device may be described as performing certain functionality, one or more other control devices (e.g., the central control device **230**, the wearable control device **228**, the wireless communication device **232**, or a control-target device) may be configured to perform similar functionality.

(64) FIG. **3** is a simplified flow diagram depicting an example method **300** for performing gesture-based control of one or more control devices using a wearable control device. One or more portions of the method **300** may be performed by a wearable control device, a central control device, a wireless communication device, a control-target device, or any combination thereof (e.g., the wearable control device **228**, the central control device **230**, and/or the wireless communication device **232** shown in FIG. **2**). The method **300** may begin at **302**. At **304**, a user may be identified using the wearable control device. For example, the wearable control device may transmit digital messages to the central control device and/or the wireless communication device that include a unique identifier. The digital messages including the unique identifier may be triggered by actuation of one or more buttons, one or more gestures performed by the user, and/or a determination of the location of the user (e.g., via near field communication with an NFC device and/or via a GPS circuit).

(65) The user may perform a gesture to control one or more electrical loads in a load control environment. The gesture performed by the user may be identified at **306** by the wearable control device. For example, the wearable control device may send a digital message to the wireless communication device or the central control device that indicates the identified gesture. At **308**, a determination may be made as to whether the gesture indicates a scene. For example, the wireless communication device or the central control device, upon receiving a digital message indicating a gesture from the wearable wireless device, may determine whether the gesture indicates a scene at **308**. The gesture identified by the wearable control device may be compared with one or more preconfigured gestures, at **308**, to determine whether the gesture is associated with a preprogrammed scene configuration for the load control environment in a datastore. If the gesture is associated with a preprogrammed scene at **308**, control instructions for controlling the appropriate control-target devices may be determined at **310**. For example, the wireless communication device or the central control device may identify the control-target devices for being controlled in the scene, as well as the control instructions for controlling the control-target devices at **310**. A unique identifier of the control-target devices and the control instructions associated with the scene may be retrieved from storage at the wireless communication device or the central control device. If, at **308**, the gesture does not indicate a scene, the method **300** may determine whether other information being indicated by the gesture.

(66) At **312**, a determination may be made as to whether the gesture indicates control instructions. For example, the wireless communication device or the central control device may determine

whether the gesture indicates control instructions at **312**. The gesture identified by the wearable control device may be compared with one or more preconfigured gestures, at **312**, to determine whether the gesture is associated with control instructions in the datastore. If the gesture identifies control instructions at **312**, the control instructions may be stored, at **314**, for being sent in a digital message to one or more identified control-target devices. At **316**, a determination may be made as to whether the control-target device has been identified other than by the gesture identified at **306**. For example, the wireless communication device or the central control device may determine, at **316**, whether the control-target device has been identified other than by the gesture identified at **306**. For example, the user may have identified the control-target device via another gesture previously performed by the user or by actuating one or more buttons on the wireless communication device. If the control-target device is identified other than by the gesture performed at **306**, the identity of the control-target device to which a digital message will be sent may be stored at **322**. For example, the wireless communication device or the central control device may store the identity of the control-target device for being sent in a digital message at **322**. The identity of the control-target device may not be stored again at **322** if the identity of the control-target device has already been stored for being sent in a digital message (e.g., if the identity of the control-target device was already stored as a result of previously identified gesture or actuation on the wireless communication device).

(67) If, at **312**, it is determined that the identified gesture does not indicate control instructions or, at **316**, the control-target device has not been identified other than by the gesture, a determination may be made as to whether the gesture identified at **306** indicates the identity of one or more control-target devices at **318**. For example, the wireless communication device or the central control device may determine, at **318**, whether the gesture identified at **306** indicates the identity of one or more control-target devices. The gesture identified by the wearable control device may be compared with one or more preconfigured gestures, at **318**, to determine whether the gesture is associated with one or more control-target devices in the datastore. The identified gesture may be associated with the unique identifier of one or more control-target devices, a device type, and/or a zone or location of control-target devices. If the identified gesture is associated with a device type, a zone, and/or a location of the control-target devices for being controlled, the wireless communication device or the central control device may determine the unique identifiers of the control-target devices in the control system having the identified device type, within the identified zone, and/or within the identified location. The gesture may also, or alternatively, indicate a vector (e.g., indicated by the direction of the user's arm or the direction that a user is facing or looking) that points in a direction of one or more control devices in the load control environment. The vector may be compared with a map of the load control environment to determine the identity of the one or more control devices indicated by the vector. The identity of the control-target devices may be stored at **322** for sending digital messages to the identified control-target devices.

(68) If the gesture identified at **306** does not indicate a scene at **308**, control instructions at **312**, or a control-target device at **318**, a determination may be made (e.g., by the wearable control device, the wireless communication device, and/or the central control device), at **320**, whether a predetermined threshold for identifying gestures performed by the user has elapsed. The predetermined threshold may be a period of time (e.g., a period of time without having an identified gesture at **306**, a lack of movement identified by the wearable control device for the period of time, etc.), a number of identified gestures, or another predetermined threshold for stopping the identification of gestures at **306**. If the predetermined threshold has lapsed at **320**, the method **300** may end at **328**. If the predetermined threshold has not lapsed at **320**, the method **300** may return to **306** to identify another gesture performed by the user or otherwise determine the control-target devices to which digital messages may be transmitted.

(69) When the control-target devices and the control instructions have been identified, appropriate digital messages may be generated at **324**. For example, the wireless communication device or the

central control device, at **324**, may generate digital messages that include the control instructions for transmitting to the control-target devices. The digital messages may include the unique identifier of the control-target devices; or the digital messages may include an indirect identifier, such as a device type, a zone, or a location of the control-target device, and the control-target device may determine whether to execute the control instructions based on the indirect identifier. The digital messages may be sent at **326**. After sending the digital messages at **326**, a determination may be made (e.g., by the wearable control device, the wireless communication device, and/or the central control device), at **320**, whether a predetermined threshold for identifying gestures performed by the user has elapsed. If the predetermined threshold has lapsed at **320**, the method **300** may end at **328**. If the predetermined threshold has not lapsed at **320**, the method **300** may return to **306** to identify another gesture performed by the user. While one or more portions of the method **300** may be described as being performed by a wearable control device, a central control device, or a wireless communication device, the method **300** may be performed using any number of devices.

(70) FIG. **4** is a simplified flow diagram depicting an example method **400** for engaging and disengaging a wearable control device for identifying gestures for controlling an electrical load. The method **400** may be performed by a wearable control device, a central control device, a wireless communication device, a control-target device, or any combination thereof (e.g., the wearable control device **228**, the central control device **230**, and/or the wireless communication device **232** shown in FIG. **2**). The method **400** may begin at **402**. At **404**, a determination may be made as to whether the wearable control device is engaged. For example, the wearable control device **228**, the central control device **230**, and/or the wireless communication device **232** may determine whether the wearable control device is engaged at **404**. The wearable control device may detect an engage command from a user and may be engaged for identifying gestures for controlling an electrical load. The wearable control device may transmit a digital message to the central control device and/or the wireless communication device that indicates that the wearable control device is engaged. The digital message may also engage the central control device and/or the wireless communication device for receiving digital messages from the wearable control device for controlling an electrical load.

(71) The wearable control device may be engaged by actuation of one or more buttons on the wearable control device, actuation of one or more buttons on the wireless communication device, and/or an engage gesture performed via the wearable control device. The engage gesture may be identified after being performed for an established period of time, such as a three second period of time for example. The engage gesture may include one or more gestures (e.g., a sequence of gestures) that may be unlikely to be performed by a user by mistake. For example, the user may perform a movement that is unlikely to be performed by a user when the user is not engaging the wearable control device. In another example, the engage gesture may be performed for a longer period of time (e.g., 10-20 seconds) than other gestures for controlling an electrical load or that may be likely to be performed naturally by the user.

(72) The wearable control device may identify the user's arm being raised for a predetermined period of time to engage the wearable control device. In another example, the wearable control device may be engaged by changing the orientation of the wearable control device (e.g., shaking the wearable control device) a predetermined number of times within a period of time. When the wearable control device is a watch, or other armband, the wearable control device may be engaged by raising the wearable control device upward and toward the user, as if to check the time or look at a display on the armband. Such a gesture may be detected by identifying the user raising the wearable control device, bringing the wearable control device toward the user, and changing the orientation of the wearable control device.

(73) If the engage gesture is not identified at **404**, the method **400** may end at **414**. If the engage gesture is identified at **404**, the method **400** may continue to identify a gesture for controlling an

electrical load at **406**. The identification of the engage gesture at **404** may enable the wearable control device to identify the gesture at **406** and/or send digital messages for controlling an electrical load. Without identifying the engage gesture, the wearable control device may be unable to identify other gestures for load control. At **408**, control-target devices and/or the control instructions associated with an identified gesture may be determined. The control-target devices and the control instructions may be a part of a scene indicated by the gesture. The control-target devices may be identified with separate gestures or otherwise identified from the gestures that identify the control instructions. The control instructions may be sent to the identified control-target device at **410** for controlling an electrical load.

(74) At **412**, a determination may be made as to whether device the wearable control device is disengaged. For example, the wearable control device **228**, the central control device **230**, and/or the wireless communication device **232** may determine whether the wearable control device is disengaged at **412**. The wearable control device may detect a disengage command from a user and may be disengaged from identifying gestures for controlling an electrical load. The wearable control device may transmit a digital message to the central control device and/or the wireless communication device that indicates that the wearable control device is disengaged. The digital message may also disengage the central control device and/or the wireless communication device for receiving digital messages from the wearable control device for controlling an electrical load.

(75) The wearable control device may be disengaged by actuation of one or more buttons on the wearable control device, actuation of one or more buttons on the wireless communication device, and/or a disengage gesture performed via the wearable control device. The disengage gesture may be identified after being performed for an established period of time, such as a three second period of time for example. The disengage gesture may include one or more gestures (e.g., a sequence of gestures) that may be unlikely to be performed by a user by mistake. For example, the user may perform a movement that is unlikely to be performed by a user when the user is not disengaging the wearable control device. In another example, the disengage gesture may be performed for a longer period of time (e.g., 10-20 seconds) than other gestures for controlling an electrical load or that may be likely to be performed naturally by the user. The engage and disengage gesture may be the same or different gestures.

(76) The wearable control device may identify the user's arm being lowered for a predetermined period of time to disengage the wearable control device. In another example, the wearable control device may be disengaged by changing the orientation of the wearable control device (e.g., shaking the wearable control device) a predetermined number of times within a period of time. The disengage gesture may cause the wearable control device to be unable to identify a gesture for load control until the engage gesture is identified. If the disengage gesture is identified at **412**, the method may end at **414**. If the disengage gesture is not identified at **412**, the method **400** may continue to identify load control gestures at **406**. While one or more portions of the method **400** may be described as being performed by a wearable control device, a central control device, or a wireless communication device, the method **400** may be performed using any number of devices.

(77) FIGS. 5A-5E depict example gestures that may be identified for indicating a control-target device and/or control instructions for controlling an electrical load. As shown in FIGS. 5A and 5B, a wearable control device **504** may identify a user **500** raising an arm **502** (e.g., FIG. 5A) or lowering an arm **502** (e.g., FIG. 5B). The user **500** raising the arm **502** may be associated with load control instructions and/or a control device. For example, when the wearable control device **504** identifies the user **500** raising the arm **502**, a digital message may be transmitted to a control-target device instructing the control-target device to increase an amount of power provided to the electrical load (e.g., turn on a lamp, increase the dimming level of the lamp, etc.). When the wearable control device **504** identifies the user **500** raising the arm **502**, digital messages may also, or alternatively, be transmitted to a motorized window treatment for raising a covering material, a temperature control device for increasing the temperature in a room, and/or another control-target

device for performing another associated instruction.

(78) The user **500** lowering the arm **502** may be associated with load control instructions and/or a control device. For example, when the wearable control device **504** identifies the user **500** lowering the arm **502**, a digital message may be transmitted to a control-target device instructing the control-target device to decrease an amount of power provided to the electrical load (e.g., turn off a lamp, decrease the dimming level of the lamp, etc.). When the wearable control device **504** identifies the user lowering the arm **502**, digital messages may also, or alternatively, be transmitted to a motorized window treatment for lowering a covering material, a temperature control device for decreasing the temperature in a room, and/or another control-target device for performing another associated instruction.

(79) As shown in FIGS. 5C and 5D, a gesture may be identified when the user **500** moves more than one part of the body. As shown in FIG. 5C, a first wearable control device **504** may identify the user **500** raising a left arm **502** and a second wearable control device **506** may identify the user raising a right arm **508**. As shown in FIG. 5D, the first wearable control device **504** may identify the user **500** lowering the left arm **502** and the second wearable control device **506** may identify the user lowering the right arm **508**. The gesture identified by the user raising or lowering the arms **502**, **508** may correspond to a single set of control instructions and/or a control-target device for transmitting digital messages that include the control instructions. In another example, different functions may be performed by the user **500** performing a gesture with each arm **502**, **504**. The user raising or lowering the left arm **502** may identify a control-target device and the user **500** raising or lowering the right arm **508** may identify load control instructions for controlling the control-target device (or vice versa).

(80) When multiple wearable control devices **504**, **506** are used to detect user gestures, the wearable control devices **504**, **506** may be in communication with one another. For example, the first wearable control device **504** may be a watch capable of wirelessly communicating with the second wearable control device **506**, which may be another type of armband. While multiple wearable control devices **504**, **506** are illustrated in FIGS. 5C and 5D for identifying when the user **500** moves more than one part of the body, multiple body movements may be detected using a single gesture control device (e.g., a shirt having sensors to detect different body movements).

(81) The speed at which a gesture is performed may be identified by tracking the speed of the wearable control device **504**, **506**. The speed at which a gesture is performed may be used to indicate a control device or control instructions. The speed at which a gesture is performed may be used to indicate a speed at which an electrical load controlled by the control device may be controlled. For example, the speed at which the wearable control device **504**, **506** is raised or lowered may indicate a respective speed for raising or lowering the position of the covering material controlled by the motorized window treatment or for increasing or decreasing the dimming level of a lamp.

(82) The speed indicated in the control instructions may be based on the speed at which the wearable control device **504**, **506** moves, taking into consideration the operation speed of the device being controlled. The speed indicated in the control instructions may be the same speed at which the wearable control device **504**, **506** moves or otherwise determined from the speed at which the wearable control device **504**, **506** moves. For example, the speed at which the wearable control device **504**, **506** moves may be a percentage of the speed indicated in the control instructions or the speed indicated in the control instructions may be a percentage of the speed at which the wearable control device **504**, **506** moves.

(83) The distance over which a gesture is performed may be identified. The distance may be identified by tracking the distance over which the wearable control device **504**, **506** moves. The distance over which a gesture is performed may be used to indicate a control device or control instructions. The distance over which a gesture is performed may be used to indicate a distance or range over which a device controlled by the control-target device may be instructed to change. For

example, the distance that the wearable control device **504, 506** is raised or lowered may be identified and the control instructions sent to an identified motorized window treatment may indicate a distance for raising the position of the covering material controlled by the motorized window treatment. In another example, the distance over which the wearable control device **504, 506** is raised or lowered may be identified and the control instructions sent to an identified lighting control device may indicate a range for increasing or decreasing the dimming level of a lamp controlled by lighting control device. The distance indicated in the control instructions may be otherwise determined from the distance over which the wearable control device **504, 506** may move. For example, the distance over which the wearable control device **504, 506** moves may be a percentage of the distance indicated in the control instructions or the distance indicated in the control instructions may be a percentage of the distance over which the wearable control device **504, 506** moves.

(84) One or more of the gestures in FIGS. 5A-5D may be used to engage the wearable control device **504, 506**, disengage the wearable control device **504, 506**, or send a digital message for controlling an electrical load. The digital messages may be sent to one or more control-target devices to control the devices according to an established scene. Other gestures may also be used to transmit digital messages for controlling one or more electric loads (e.g., according to an established scene). For example, the user **500** may perform a goodbye wave when leaving a load control environment (e.g., such as a home or office) to transmit digital messages for controlling one or more electric loads according to an away scene. The goodbye wave may be a wave of either arm **502, 508** from side to side (e.g., left and right). The user **500** may perform another gesture when arriving at the load control environment (e.g., such as the home or office) to transmit digital messages for controlling one or more electric loads according to a home scene. For example, the user may perform the same wave as the goodbye wave or may perform a hello wave by moving either arm **502, 508** up and down, instead of side to side. The location of the user **500** may be paired with the wave to determine whether the user is leaving or arriving.

(85) FIG. 5E shows an example of a sleep gesture for entering a bedtime scene. The sleep gesture may be identified by the location of one or both of the arms **502, 508** of the user **500**. For example, after one of the wearable control devices **504, 506** measures the angle of the respective arm **502, 508**, the angle of the arm **502, 508** may be compared against the predefined angle for activating the bedtime mode. When the user has multiple wearable control devices **504, 506**, the proximity between the devices **504, 506** may be used to select the bedtime scene. For example, the proximity between the devices **504, 506** may be determined based on the signal strength of communications between the devices. When the wearable control devices **504, 506** are within a predetermined proximity, the bedtime mode may be activated.

(86) A wakeup scene may be implemented when the user **500** wakes up or in order to help wake up the user **500**. For example, the wakeup scene to turn on one or more lamps and set the lamps to a predetermined dimming level, increase or decrease the temperature on the temperature in a load control environment, and/or raise the covering material of a motorized window treatment to a predetermined level. The wakeup scene may also, or alternatively, turn on music (e.g., on a wireless communication device or other music device) or turn on a television at a predetermined volume level. The user **500** may perform a snooze gesture to implement the wakeup scene or delay the wakeup scene by a predetermined period of time. The snooze gesture may be identified by the user **500** moving one of the arms **502, 508** up and down, as if to hit a snooze button on a clock for example.

(87) A movie scene may be activated with the user **500** points the wearable control device **504, 506** at the location of the television and/or gestures to turn on the television using a remote control. The location of the television may be identified by a vector that points in the direction of the television from the wearable control device **504, 506** when the user **500** extends an arm **502, 508**. The movement of the user **500**'s thumb may be detected if the user **500** is wearing a ring based on the

movement of the ring up and down to indicate a user selection of a button on a remote control. The movement of the user **500**'s thumb may be similarly detected by the wearable control device **504**, **506**, as the armband may detect movement of the thumb of the user **500** up and down.

(88) FIG. **6** is a simplified flow diagram depicting an example method **600** for associating a gesture with a control-target device and/or control instructions. The method **600** may be performed by a wearable control device, a central control device, a wireless communication device, a control-target device, or any combination thereof (e.g., the wearable control device **228**, the central control device **230**, and/or the wireless communication device **232** shown in FIG. **2**). The method **600** may begin at **602**. A programming mode may be entered, at **604**, by the wearable control device and/or the central control device. The programming mode may be entered upon the identification of a programming gesture and/or actuation of one or more buttons on the wearable control device. The programming mode may also, or alternatively, be entered upon actuation of one or more buttons on the wireless communication device. Identification of the programming gesture may enable the central control device, the wireless communication device, and/or the wearable control device to store programming instructions for controlling an electrical load. For example, the programming gesture may enable association of one or more gestures with a control-target device and/or control instructions in the gesture datastore. The programming gesture may include one or more gestures (e.g., a sequence of gestures) that may be unlikely to be performed by a user by mistake. For example, the user may perform a movement that is unlikely to be performed by a user when the user is not programming the wearable control device. The programming gesture may be performed for a longer period of time (e.g., 10-20 seconds) than other gestures may be performed, such as gestures that may be recognized by the wearable control device for load control or that may be likely to be performed naturally by the user.

(89) At **606**, a control-target device may be identified for being associated with a gesture. The control-target device may be identified by a gesture. For example, the user may point the wearable control device in the direction of the control-target device to be controlled. A vector from the wearable control device may be compared against a map of the room (e.g., at the central control device) to determine the control-target device selected by the user. When the wearable control device is an armband, the user may change the orientation of the user's wrist a number of times to select different control-target devices, different types of control-target devices in a location (e.g., living room lights, kitchen lights, etc.) or different locations. One or more control-target devices may be associated with each change in orientation. The user may also, or alternatively, perform a gesture that is currently associated with a control-target device to change the gesture that is currently associated with the control-target device to another gesture. The control-target device may also, or alternatively, be selected by an actuation on the wireless communication device, actuation of a button on the wearable control device, or by the user speaking the name of the control-target device or electrical load to be controlled. The name of the control-target device or electrical load may be recorded by the wireless communication device and/or the wearable control device and sent to the central control device for identification. One or more control devices may be identified at **606**.

(90) Control instructions may be identified at **608** for being associated with a gesture for performing load control. The control instructions may be identified by a gesture. For example, the user may perform a gesture that is currently associated with control instructions for controlling a control target device in order to change the gesture that is currently associated with the control instructions to another gesture. The gesture that identifies the control instructions may be the same gesture that identifies the control-target device (e.g., gesture associated with a scene). The control instructions may also, or alternatively, be selected by an actuation on the wireless communication device, actuation of a button on the wearable control device, or by the user speaking the control instructions for how to control the identified control-target device. One or more sets of control instructions may be identified at **608**.

(91) The user may associate a gesture, at **610**, with the identified control-target device and/or the identified control instructions. The gesture may be recorded by the wearable control device for being associated with the identified control-target device and/or the identified control instructions. The recorded gesture may be associated with the identified control-target device and/or the identified control instructions and stored at the wearable control device. The recorded gesture may also, or alternatively, be sent to the central control device and/or the wireless communication device for being associated with the identified control-target device and/or the identified control instructions. The association may be stored in the gesture datastore for controlling one or more control-target devices using the identified gesture.

(92) The gesture may also, or alternatively, be selected by an actuation on the wearable control device or the wireless communication device. For example, the central control device may recognize that a number of users are controlling the identified control-target device using a certain gesture. The central control device may send a digital message to the wearable control device or the wireless communication device to suggest to the user the gesture to associate with the identified control-target device and/or identified control instructions based on the gesture being used by other users. The user may select the suggested gesture for being applied to the user's control of the identified control-target device. The user may also apply the suggested gesture to other users' control of the identified control-target device. For example, where the user is a building administrator, the user may program the gestures for controlling the identified control-target devices based on the more popular gestures being used in the building, or a portion of the building. The method **600** may end at **612**.

(93) FIG. 7 is a block diagram depicting an example wearable control device **700** for performing load control (e.g., the wearable control device **228** shown in FIG. 2 or the wearable control devices **504**, **506** shown in FIGS. 5A-5E). As shown in FIG. 7, the wearable control device **700** may include a control circuit **704** for controlling the functionality of the wearable control device **700**. The control circuit **704** may include one or more general purpose processors, special purpose processors, conventional processors, digital signal processors (DSPs), microprocessors, integrated circuits, a programmable logic device (PLD), application specific integrated circuits (ASICs), or the like. The control circuit **704** may perform signal coding, data processing, power control, input/output processing, or any other functionality that enables the wearable control device **700** to perform as described herein.

(94) The control circuit **704** may store information in and/or retrieve information from the memory **706**. The memory **706** may include a non-removable memory and/or a removable memory. The non-removable memory may include random-access memory (RAM), read-only memory (ROM), a hard disk, or any other type of non-removable memory storage. The removable memory may include a subscriber identity module (SIM) card, a memory stick, a memory card, or any other type of removable memory.

(95) The wearable control device **700** may communicate with other devices via a communication circuit **702**. The wearable control device **700** may include one or more communication circuits **702** for communicating with different devices on different protocols and/or frequencies. For example, the communication circuits **702** may include a communication circuit configured to communicate with a central control device on a protocol or frequency and another communication circuit configured to communicate with a wireless communication device on another protocol or frequency.

(96) The communication circuits **702** may be capable of performing wired and/or wireless communications. The communication circuits **702** may include a transmitter, receiver, and/or a transceiver. For example, the communication circuits **702** may include an RF transceiver for transmitting and receiving RF signals via an antenna or other communications module capable of performing wireless communications. The communication circuits **702** may be in communication with the control circuit **704**. The communication circuits **702** may be capable of performing

communications via different communication channels (e.g., communication protocols, communication frequencies, etc.). For example, the communication circuits **702** may be capable of communicating via WI-FI®, WIMAX®, BLUETOOTH®, near field communication (NFC), a proprietary communication protocol, such as CLEAR CONNECT™, ZIGBEE®, Z-WAVE, or the like. The communication circuits **702** may comprise an RF transmitter for transmitting RF signals, an RF receiver for receiving RF signals, an IR transmitter for transmitting IR signals, or an IR receiver for receiving IR signals.

(97) The control circuit **704** may be in communication with an indicator light **712**. The indicator light **712** may turn on and/or off to provide indications to a user, such as whether the wearable control device **700** is on or off, whether a gesture has been identified, whether the wearable control device **700** has been enabled or disabled, whether the wearable control device **700** is in a programming mode, or the like. The control circuit **704** may receive audio data via one or more microphones (not shown) for capturing audio and may store the audio data in memory **706**.

(98) The control circuit **704** may be in communication with a display **710** (e.g., a visual display, such as an LED display) for providing information to a user. The display **710** and the control circuit **704** may be in two-way communication, as the display **704** may include a touch screen module capable of receiving information from a user and providing such information to the control circuit **704**.

(99) The wearable control device **700** may include another input source **708** from which user inputs may be received at the control circuit **704**. The input source **708** may include a keyboard or other buttons from which user inputs may be received. The input source **708** may include a biometric sensor. The biometric sensor may include, for example, a fingerprint scanner, an eye scanner, and a heart rate monitor capable of identifying heart rate information for a user. The input source may include a camera from which images may be received at the control circuit **704**.

(100) The wearable control device **700** may include one or more position determining circuits **714**. The position determining circuit **714** may be capable of determining the position and/or movement of the wearable control device **700**. Position determining circuit **714** may include a global positioning system (GPS) circuit, a gyroscope, and/or an accelerometer. The GPS circuit may be capable of receiving GPS information. The control circuit **704** may be capable of determining the GPS coordinates of the wearable control device **700** based on the GPS information received via the GPS circuit. The gyroscope may identify an orientation of the wearable control device **700**. For example, the control circuit **704** may be capable of determining the orientation of the wearable control device **700** based on the orientation information received via the gyroscope. The accelerometer may identify an acceleration of the wearable control device **700**. The accelerometer may be used (e.g., used by the control circuit **704**) to detect magnitude and/or direction of the acceleration of the wearable control device **700**, such as in the form of a vector, an orientation of the wearable control device **700**, and/or vibrations of the wearable control device **700**.

(101) Each of the modules of the wearable control device **700** may be powered by a power source **716**. The power source **716** may include, for example, DC power source, such as a battery. The power source **716** may generate a supply voltage V_{sub_CC} for powering the modules of the wearable control device **700**.

(102) FIG. **8** is a block diagram depicting an example central control device **800** (e.g., the central control device **230** shown in FIG. **2**). As shown in FIG. **8**, the central control device **800** may include a control circuit **804** for controlling the functionality of the central control device **800**. The control circuit **804** may include one or more general purpose processors, special purpose processors, conventional processors, digital signal processors (DSPs), microprocessors, integrated circuits, a programmable logic device (PLD), application specific integrated circuits (ASICs), or the like. The control circuit **804** may perform signal coding, data processing, image processing, power control, input/output processing, or any other functionality that enables the central control device **800** to perform as described herein.

(103) The control circuit **804** may store information in and/or retrieve information from the memory **802**. The memory **802** may include a non-removable memory and/or a removable memory. The non-removable memory may include random-access memory (RAM), read-only memory (ROM), a hard disk, or any other type of non-removable memory storage. The removable memory may include a subscriber identity module (SIM) card, a memory stick, a memory card, or any other type of removable memory.

(104) The central control device **800** may communicate with other devices via a communication circuit **806**. The central control device **800** may include one or more communication circuits. For example, one communication circuit may communicate with a wearable control device and one communication circuit may communicate with a wireless communication device. The communication circuit **806** may be capable of performing wired and/or wireless communications. The communication circuit **806** may include a transmitter, a receiver, and/or a transceiver. For example, the communication circuit **806** may include an RF transceiver for transmitting and receiving RF signals via an antenna, or other communications module capable of performing wireless communications. The communication circuit **806** may be in communication with controller **804**. The communication circuit **806** may be capable of performing communications via different communication channels. For example, the communication circuit **904** may be capable of communicating via WI-FI®, WIMAX®, BLUETOOTH®, near field communication (NFC), a proprietary communication protocol, such as CLEAR CONNECT™, ZIGBEE®, Z-WAVE, or the like.

(105) Each of the modules of the central control device **800** may be powered by a power source **808**. The power source **808** may include, for example, an AC power source or a DC power source, such as a battery. The power source **808** may generate a supply voltage $V_{sub.CC}$ for powering the modules of the central control device **800**.

(106) FIG. **9** is a block diagram depicting an example control-target device **900**. The control-target device **900** may include a dimmer switch, an electronic switch, an electronic ballast for controlling fluorescent lamps, a light-emitting diode (LED) driver for controlling LED light sources, a plug-in control device (e.g., a switching device), a thermostat, a motorized window treatment, or other control-target device for controlling an electrical load **914**. The control-target device **900** may include a control circuit **902** for controlling the functionality of the control-target device **900**. The control circuit **902** may include one or more general purpose processors, special purpose processors, conventional processors, digital signal processors (DSPs), microprocessors, integrated circuits, a programmable logic device (PLD), application specific integrated circuits (ASICs), or the like. The control circuit **902** may perform signal coding, data processing, image processing, power control, input/output processing, or any other functionality that enables the control-target device **900** to perform as described herein.

(107) The control-target device **900** may communicate with other devices via the communication circuit **904**. The communication circuit **904** may be in communication with controller **902**. The communication circuit **904** maybe capable of performing wired and/or wireless communications. The communication circuit **904** may include an RF transceiver for transmitting and receiving RF signals via an antenna, or other communications module capable of performing wired and/or wireless communications. For example, the communication circuit **904** may be capable of communicating via WI-FI®, WIMAX®, BLUETOOTH®, near field communication (NFC), a proprietary communication protocol, such as CLEAR CONNECT™, ZIGBEE®, Z-WAVE, or the like.

(108) The control circuit **902** may store information in and/or retrieve information from the memory **906**. The memory **906** may include a non-removable memory and/or a removable memory. A load control circuit **908** may receive instructions from the control circuit **902** and may control the electrical load **914** (e.g., by controlling the amount of power provided to the load) based on the received instructions. The load control circuit **908** may receive power via a hot connection **910** and

a neutral connection **912**. While the control-target device **900** includes four terminals as shown in FIG. **9**, the control-target device **900** may include one load terminal connected to the electrical load **914**, which may be connected in series between the control-target device **900** and a neutral of the AC power source supplying power to the hot connection **910** and the neutral connection **912**. In other words, the control-target device **900** may be a “three-wire” device. The control-target device **900** may have one connection to the AC power source (e.g., hot connection **910**) and may not comprise a connection to the neutral of the AC power source (e.g., may not comprise neutral connection **912**). In other words, the control-target device **900** may be a “two-wire” device. The electrical load **914** may include any type of electrical load.

(109) FIG. **10** is a block diagram illustrating an example wireless communication device **1000** (e.g., the wireless communication device **232** shown in FIG. **2**). The wireless communication device **1000** may include a control circuit **1002** for controlling the functionality of the wireless communication device **1000**. The control circuit **1002** may include one or more general purpose processors, special purpose processors, conventional processors, digital signal processors (DSPs), microprocessors, integrated circuits, a programmable logic device (PLD), application specific integrated circuits (ASICs), or the like. The control circuit **1002** may perform signal coding, data processing, power control, input/output processing, or any other functionality that enables the wireless communication device **1000** to perform as described herein.

(110) The control circuit **1002** may store information in and/or retrieve information from a memory **1006**. The memory **1006** may include a non-removable memory and/or a removable memory. The non-removable memory may include random-access memory (RAM), read-only memory (ROM), a hard disk, or any other type of non-removable memory storage. The removable memory may include a subscriber identity module (SIM) card, a memory stick, a memory card, or any other type of removable memory.

(111) The wireless communication device **1000** may include one or more communication circuits **1010** for transmitting and/or receiving information from other devices. For example, the communication circuits **1010** may include a communication circuit configured to communicate with a central control device on a protocol or frequency and another communication circuit configured to communicate with a wireless communication device on another protocol or frequency. The communication circuits **1010** may perform wireless or wired communications. Communication circuits **1010** may be in communication with control circuit **1002** for transmitting and/or receiving information. The communication circuits **1010** may include a transmitter, receiver, and/or a transceiver. For example, the communication circuits **1010** may include an RF transceiver for transmitting and receiving RF signals via an antenna, or other communications module capable of performing wired and/or wireless communications. For example, the communication circuits **1010** may be capable of communicating via WI-FI®, WIMAX®, BLUETOOTH®, cellular communication, near field communication (NFC), a proprietary communication protocol, such as CLEAR CONNECT™, ZIGBEE®, Z-WAVE, or the like.

(112) The control circuit **1002** may be in communication with a display **1008** (e.g., a visual display, such as an LED display) for providing information to a user. The display **1008** and the control circuit **1002** may be in two-way communication, as the display **1008** may include a touch screen module capable of receiving information from a user and providing such information to the control circuit **1002**. The wireless communication device **1000** may include another input source **1004**, such as a keyboard or other buttons, from which user inputs may be received at the control circuit **1002**.

(113) The wireless communication device **1000** may include one or more position determining circuits **1014**. The position determining circuit **1014** may be capable of determining the position and/or movement of the wireless communication device **1000**. Position determining circuit **1014** may include a global positioning system (GPS) circuit, a gyroscope, and/or an accelerometer. The GPS circuit may be capable of receiving GPS information. The control circuit **1002** may be capable

of determining the GPS coordinates of the wireless communication device **1000** based on the GPS information received via the GPS circuit. The gyroscope may identify an orientation of the wireless communication device **1000**. For example, the control circuit **1002** may be capable of determining the orientation of the wireless communication device **1000** based on the orientation information received via the gyroscope. The accelerometer may identify an acceleration of the wireless communication device **1000**. The accelerometer may be used (e.g., used by the control circuit **1002**) to detect magnitude and/or direction of the acceleration of the wireless communication device **1000**, such as in the form of a vector, an orientation of the wireless communication device **1000**, and/or vibrations of the wireless communication device **1000**.

(114) Each of the modules of the wireless communication device **1000** may be powered by a power source **1012**. The power source **1012** may include an AC power supply or DC power supply, for example. The power source **1012** may generate a supply voltage V.sub.CC for powering the modules within the wireless communication device **1000**.

(115) Although features and elements are described above in particular combinations, each feature or element can be used alone or in any combination with the other features and elements. The methods described herein may be implemented in a computer program, software, or firmware incorporated in a computer-readable medium for execution by a computer or processor. Examples of computer-readable media include electronic signals (transmitted over wired or wireless connections) and computer-readable storage media. Examples of computer-readable storage media include, but are not limited to, a read only memory (ROM), a random access memory (RAM), removable disks, and optical media such as CD-ROM disks, and digital versatile disks (DVDs).

Claims

1. An electrical load controller, comprising: first communications interface circuitry; second communications interface circuitry; electrical load device control circuitry communicatively coupled to the first communications interface circuitry and to the second communications interface circuitry, the electrical load device control circuitry to: receive, from a wearable device via the first communications interface circuitry and using a first communication protocol, a first input that includes data representative of a gesture provided by a user of the wearable device; receive, via the first communications interface circuitry, a second input provided by the user of the wearable device; responsive to the receipt of the first input and the second input: using either of the first input or the second input, identify a plurality of electric load devices communicatively coupled to the electrical load controller via the second communication interface circuitry; wherein the plurality of electric load devices include: one or more control-source devices and one or more control-target devices; using the remaining one of either the first input or the second input, identify one or more instructions associated with at least one of the identified plurality of electric load devices; generate one or more commands that include at least one of the one or more instructions; cause a communication, via the second communications interface circuitry using a second communication protocol different than the first communication protocol, of the generated one or more commands to the at least one of the identified plurality of electric load devices.
2. The electrical load controller of claim 1 wherein the second input comprises data representative of a second gesture provided by the user of the wearable device, the second gesture distinct from the first gesture provided by the user of the wearable device.
3. The electrical load controller of claim 1 wherein the second input comprises data representative of a tactile input provided by the user of the wearable device.
4. The electrical load controller of claim 1 wherein the second input comprises data representative of an audio input provided by the user of the wearable device.
5. The electrical load controller of claim 1 wherein the gesture data includes the data indicative of the at least one of the identified plurality of electric load devices and the second input includes data

indicative of the one or more instructions.

6. The electrical load controller of claim 1 wherein the second input includes data indicative of the at least one of the identified plurality of electric load devices and the gesture data includes the data indicative of one or more instructions.

7. The electrical load controller of claim 1 wherein to identify the plurality of electric load devices and to identify the one or more instructions associated with the at least one of the identified plurality of electric load devices, the control circuitry to perform one or more lookup operations using a datastore at least partially resident in the wearable device.

8. The electrical load controller of claim 1 wherein to identify the plurality of electric load devices and to identify the one or more instructions associated with the at least one of the identified plurality of electric load devices, the control circuitry to perform one or more lookup operations using a datastore at least partially resident in a communicatively coupled network device.

9. An electrical load control method, comprising: receiving, by electrical load device control circuitry from a wearable device via first communication interface circuitry using a first communication protocol, a first input that includes data representative of a gesture provided by a user of the wearable device; receiving, by the electrical load device control circuitry via the first communication interface circuitry, a second input provided by the user of the wearable device; responsive to the receipt of the first input and the second input: identifying, by the electrical load device control circuitry, a plurality of electric load devices using either of the first input or the second input; identifying, by the electrical load device control circuitry, one or more instructions associated with at least one of the identified plurality of electric load devices using the remaining one of either the first input or the second input, wherein the plurality of electric load devices include: one or more control-source devices and one or more control-target devices; generating, by the electrical load device control circuitry, one or more commands that include at least one of the one or more instructions; causing, by the electrical load device control circuitry via second communication interface circuitry using a second communication protocol, a communication of the generated one or more commands to the at least one of the identified plurality of electric load devices.

10. The electrical load control method of claim 9 wherein receiving, via the first communication interface circuitry, the second input provided by the user of the wearable device further comprises: receiving, by the electrical load device control circuitry via the first communication interface circuitry, data representative of a second gesture provided by the user of the wearable device, wherein the second gesture differs from the first gesture provided by the user of the wearable device.

11. The electrical load control method of claim 9 wherein receiving, via the first communication interface circuitry, the second input provided by the user of the wearable device further comprises: receiving, by the electrical load device control circuitry via the first communication interface circuitry, data representative of a tactile input provided by the user of the wearable device.

12. The electrical load control method of claim 9 wherein receiving, via the first communication interface circuitry, the second input provided by the user of the wearable device further comprises: receiving, by the electrical load device control circuitry via the first communication interface circuitry, data representative of an audio input provided by the user of the wearable device.

13. The electrical load control method of claim 9: wherein receiving, via the first communication interface circuitry, the first input that includes the data representative of the gesture provided by the user of the wearable device further comprises: receiving, by the electrical load device control circuitry via the first communication interface circuitry, gesture data that includes data indicative of the plurality of electric load devices; and wherein receiving, via the first communication interface circuitry, the second input provided by the user of the wearable device further comprises: receiving, by the electrical load device control circuitry via the first communication interface circuitry, data indicative of the one or more instructions associated with the at least one of the identified plurality

of electric load devices.

14. The electrical load control method of claim 9: wherein receiving, via the first communication interface circuitry, the second input provided by the user of the wearable device further comprises: receiving, by the electrical load device control circuitry via the first communication interface circuitry, data indicative of the plurality of electric load devices; and wherein receiving, via the first communication interface circuitry, the first input that includes the data representative of the gesture provided by the user of the wearable device further comprises: receiving, by the electrical load device control circuitry via the first communication interface circuitry, gesture data includes the data indicative of one or more instructions associated with the at least one of the identified plurality of electric load devices.

15. The electrical load control method of claim 9 wherein identifying the plurality of electric load devices and identifying the one or more instructions associated with the at least one of the identified plurality of electric load devices further comprises: performing, by the electrical load device control circuitry, one or more lookup operations using a datastore at least partially resident in the wearable device.

16. The electrical load control method of claim 9 wherein identifying the plurality of electric load devices and identifying the one or more instructions associated with the at least one of the identified plurality of electric load devices further comprises: performing, by the electrical load device control circuitry, one or more lookup operations using a datastore at least partially resident in a communicatively coupled network device.

17. A non-transitory, machine-readable, storage device that includes instructions that, when executed by electrical load device control circuitry, causes the electrical load device control circuitry to: receive, from a wearable device via first communication interface circuitry using a first communication protocol, a first input that includes data representative of a gesture provided by a user of the wearable device; receive from a wearable device via first communication interface circuitry, a second input provided by the user of the wearable device; responsive to the receipt of the first input and the second input: identify a plurality of electric load devices using either of the first input or the second input, wherein the plurality of electric load devices include: one or more control-source devices and one or more control-target devices; identify one or more instructions associated with at least one of the identified plurality of electric load devices using the remaining one of either the first input or the second input; generate one or more commands that include at least one of the one or more instructions; cause a communication via second communication interface circuitry using a second communication protocol of the generated one or more commands to the at least one of the identified plurality of electric load devices.

18. The non-transitory, machine-readable, storage device of claim 17 wherein the instructions that cause the electrical load device control circuitry to receive, via the first communication interface circuitry, the second input provided by the user of the wearable device further cause the electrical load device control circuitry to: receive, via the first communication interface circuitry, a second input that includes data representative of a second gesture provided by the user of the wearable device, wherein the second gesture differs from the first gesture provided by the user of the wearable device.

19. The non-transitory, machine-readable, storage device of claim 17 wherein the instructions that cause the electrical load device control circuitry to receive, via the first communication interface circuitry, the second input provided by the user of the wearable device further cause the electrical load device control circuitry to: receive, via the first communication interface circuitry, a second input that includes data representative of a tactile input provided by the user of the wearable device.

20. The non-transitory, machine-readable, storage device of claim 17 wherein the instructions that cause the electrical load device control circuitry to receive, via the first communication interface circuitry, the second input provided by the user of the wearable device further cause the electrical load device control circuitry to: receive, via the first communication interface circuitry, a second

input that includes data representative of an audio input provided by the user of the wearable device.

21. The non-transitory, machine-readable, storage device of claim 17: wherein the instructions that cause the electrical load device control circuitry to receive, via the first communication interface circuitry, the first input that includes the data representative of the gesture provided by the user of the wearable device further cause the electrical load device control circuitry to: receive, as the first input, gesture data that includes data indicative of the plurality of electric load devices; and wherein the instructions that cause the electrical load device control circuitry to receive the second input provided by the user of the wearable device further cause the electrical load device control circuitry to: receive, as the second input, data indicative of the one or more instructions associated with the at least one of the identified plurality of electric load devices.

22. The non-transitory, machine-readable, storage device of claim 17: wherein the instructions that cause the electrical load device control circuitry to receive, via the first communication interface circuitry, the second input provided by the user of the wearable device further cause the electrical load device control circuitry to: receive, as the second input, data indicative of the plurality of electric load devices; and wherein the instructions that cause the electrical load device control circuitry to receive, via the first communication interface circuitry, the first input that includes the data representative of the gesture provided by the user of the wearable device further cause the electrical load device control circuitry to: receive, as the first input, gesture data includes the data indicative of one or more instructions associated with the at least one of the identified plurality of electric load devices.

23. The non-transitory, machine-readable, storage device of claim 17 wherein the instructions that cause the electrical load device control circuitry to identify the plurality of electric load devices and to identify the one or more instructions associated with the identified plurality of electric load devices further cause the electrical load device control circuitry to: perform one or more lookup operations using a datastore at least partially resident in the wearable device.

24. The non-transitory, machine-readable, storage device of claim 17 wherein the instructions that cause the electrical load device control circuitry to identify the plurality of electric load devices and to identify the one or more instructions associated with the identified plurality of electric load devices further cause the electrical load device control circuitry to: perform one or more lookup operations using a datastore at least partially resident in a network device communicatively coupled to the wearable device.
