

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250281286

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Becerra; Matthew Michael et al.

MOTORIZED IMPLANT DELIVERY SYSTEM

Abstract

Systems, apparatuses, and methods disclosed herein are provided for a motorized implant delivery system. The delivery system may utilize a processor for control of at least one motor for actuating a delivery apparatus. The delivery system may include sensors configured sense one or more of a condition of the patient's body or a condition of the delivery apparatus. The processor may process the signals provided by the sensors, which may comprise feedback signals to the processor.

Inventors: Becerra; Matthew Michael (Lake Forest, CA), Landon; David Robert (Huntington Beach, CA)

Applicant: EDWARDS LIFESCIENCES CORPORATION (Irvine, CA)

Family ID: 1000008619389

Appl. No.: 19/177436

Filed: April 11, 2025

Related U.S. Application Data

parent US continuation 17156370 20210122 parent-grant-document US 12295839 child US 19177436

parent US continuation PCT/US2020/029138 20200421 PENDING child US 17156370
us-provisional-application US 62837641 20190423

Publication Classification

Int. Cl.: A61F2/24 (20060101); A61B90/00 (20160101); A61F2/95 (20130101); G16H10/60 (20180101); G16H40/63 (20180101)

U.S. Cl.:

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 17/156,370, filed Jan. 22, 2021, and titled “Motorized Implant Delivery System,” which is a continuation of International Application No. PCT/US2020/029138, filed Apr. 21, 2020, which designates the United States and was published in English by the International Bureau on Oct. 29, 2020 as WO 2020/219459, which claims priority to U.S. Provisional App. No. 62/837,641, filed Apr. 23, 2019, the entirety of each of which being hereby incorporated by reference.

BACKGROUND

Field

[0002] Various embodiments disclosed herein relate generally to delivery systems for implants. Some embodiments relate to delivery systems and implants for replacing diseased heart valves.

Background

[0003] The four human heart valves are the aortic valve, mitral valve, tricuspid valve and pulmonary valve. These heart valves function essentially as one-way valves operating in synchronization with the pumping heart to ensure that blood flows downstream, while blocking blood from flowing upstream. Diseased heart valves exhibit impairments such as narrowing of the valve or regurgitation, which inhibit the valves' ability to control blood flow. Such impairments reduce the heart's blood-pumping efficiency and can be a debilitating and life-threatening condition. For example, valve insufficiency can lead to conditions such as heart hypertrophy and dilation of the ventricle. Thus, extensive efforts have been made to develop methods and apparatuses to repair or replace impaired heart valves.

[0004] Prosthetic implants exist to correct problems associated with impaired heart valves. For example, mechanical and tissue-based heart valve prostheses can be used to replace impaired native heart valves. More recently, substantial effort has been dedicated to developing replacement heart valves, particularly tissue-based replacement heart valves that can be delivered with less trauma to the patient than through open heart surgery. Replacement valves are being designed to be delivered through minimally invasive procedures and even percutaneous procedures. Such replacement valves often include a tissue-based valve body that is connected to an expandable frame that is then delivered to the native valve's annulus.

[0005] Development of prosthetic implants including but not limited to replacement heart valves and other types of implants that may be utilized for heart valve repair can be compacted for delivery and then controllably expanded for controlled placement has proven to be particularly challenging. An additional challenge relates to the ability of such prostheses to be secured relative to intraluminal tissue, e.g., tissue within any body lumen or cavity, in an atraumatic manner.

[0006] Delivering an implant to a desired location in the human body, for example delivering a replacement heart valve or other form of implant for heart valve repair via a catheter-based procedure, can also be challenging. Obtaining access to perform procedures in the heart or in other anatomical locations may require delivery of devices percutaneously through tortuous vasculature or through open or semi-open surgical procedures. The ability to control the deployment of the implant at the desired location can also be challenging.

SUMMARY

[0007] Embodiments of the present disclosure are directed to a motorized implant delivery system.

Such a system may be used to deliver and/or controllably deploy an implant, such as but not limited to a replacement heart valve or an implant for repair of a heart valve, to a desired location within the body. In some embodiments, a replacement heart valve and methods for delivering a replacement heart valve to a native heart valve or repairing a heart valve, such as a mitral valve, are provided.

[0008] The delivery system may utilize a processor for control of at least one motor for actuating a delivery apparatus. The delivery system may include sensors configured to sense one or more of a condition of the patient's body or a condition of the delivery apparatus. The processor may process the signals provided by the sensors, which may take the form of feedback signals to the processor. The sensors may be located on a catheter. The sensors may also take the form of imaging devices that provide information regarding the patient's anatomy and/or the location of the catheter and implant in the patient's body.

[0009] Embodiments of the present disclosure include a delivery system for delivering an implant to a location within a patient's body. The system may include a delivery apparatus configured to deliver the implant to the location within the patient's body. The system may include at least one motor configured to actuate at least a portion of the delivery apparatus. The system may include a processor configured to operate the at least one motor to actuate at least the portion of the delivery apparatus.

[0010] Embodiments of the present disclosure include a delivery system for delivering an implant to a location within a patient's body. The system may include a delivery apparatus configured to deliver the implant to the location within the patient's body. The system may include one or more sensors coupled to the delivery apparatus and configured to sense one or more of a condition of the patient's body or a condition of the delivery apparatus. The system may include a processor configured to provide an output based on the one or more of a condition of the patient's body or a condition of the delivery apparatus sensed by the one or more sensors.

[0011] Embodiments of the present disclosure include a delivery system for delivering an implant to a location within a patient's body. The system may include an elongate shaft configured to pass within the patient's body. The elongate shaft may include an outer sheath having an outer lumen and a proximal end and a distal end, at least a portion of the outer sheath surrounding an implant retention area configured to retain the implant. The elongate shaft may include a rail shaft located within the outer lumen and having a proximal end and a distal end, the rail shaft configured to be steerable. The elongate shaft may include an inner shaft located within the outer lumen and having a proximal end and a distal end. The elongate shaft may include an inner retention member coupled to the inner shaft and configured to be releasably coupled to the implant, wherein the outer sheath and inner shaft are configured to move together relative to the rail shaft while the implant remains in the implant retention area, and wherein the outer sheath is configured to retract relative to the inner shaft in order to at least partially deploy the implant. The system may include at least one motor configured to actuate at least a portion of the elongate shaft.

[0012] Embodiments of the present disclosure include methods of using the systems. For example, a method may include extending a delivery apparatus within a portion of a patient's body to deliver an implant to a body location, wherein at least a portion of the delivery apparatus is actuated by at least one motor operated by a processor.

[0013] Another method may include extending a delivery apparatus within a portion of a patient's body to deliver an implant to a body location, the delivery apparatus including one or more sensors coupled to the delivery apparatus and configured to sense one or more of a condition of the patient's body or a condition of the delivery apparatus. The method may include providing, with a processor, an output based on the one or more of a condition of the patient's body or a condition of the delivery apparatus sensed by the one or more sensors.

[0014] Embodiments of the present disclosure include a delivery system for delivering an implant to a location within a patient's body. The system may include an elongate shaft having a proximal

end and a distal end. The elongate shaft may include an implant retention area configured to retain the implant, a capsule configured to surround the implant retention area, and at least one electromagnet configured to attract or repel a portion of the capsule to vary a size of the capsule. [0015] Another method may include deploying an elongate shaft to a location within a patient's body, the elongate shaft including a capsule surrounding an implant retention area retaining an implant for implantation within the patient's body. The method may include utilizing at least one electromagnet to attract or repel a portion of the capsule to vary a size of the capsule within the patient's body.

[0016] Embodiments of the present disclosure include a delivery system for delivering an implant to a location within a patient's body. The system may include an elongate shaft having a proximal end and a distal end. The elongate shaft may include an implant retention area configured to retain the implant and an electrically detachable coupler configured to couple to the implant and to detach from at least a portion of the implant.

[0017] Another method may include extending a delivery apparatus within a portion of a patient's body to deliver an implant to a body location. The method may include detaching at least a portion of the implant from an electrically detachable coupler within the patient's body.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0018] FIG. 1 shows an embodiment of a delivery system.

[0019] FIG. 2A shows a partial cross-sectional view of the distal end of the delivery system of FIG. 1 loaded with the implant of FIG. 3A.

[0020] FIG. 2B shows a partial cross-sectional view of the distal end of the delivery system of FIG. 1 without the implant of FIG. 3A.

[0021] FIG. 2C shows a partial cross-sectional view of the distal end of the delivery system of FIG. 1 with certain shaft assemblies translated along the rail assembly.

[0022] FIG. 3A shows a side view of an embodiment of an implant in the form of a valve prosthesis that may be delivered using the delivery systems described herein.

[0023] FIG. 3B shows a side perspective view of an embodiment of an aortic valve prosthesis that may be delivered using the delivery systems described herein.

[0024] FIG. 4 shows a perspective view of the distal end of the delivery system of FIG. 1.

[0025] FIG. 5 show components of the delivery system of FIG. 4 with the outer sheath assembly moved proximally and out of view.

[0026] FIG. 6A show components of the delivery system of FIG. 5 with the mid shaft assembly moved proximally and out of view.

[0027] FIG. 6B illustrates a cross-section of the rail assembly.

[0028] FIG. 7 show components of the delivery system of FIG. 6A with the rail assembly moved proximally and out of view.

[0029] FIG. 8 show components of the delivery system of FIG. 7 with the inner assembly moved proximally and out of view.

[0030] FIG. 9 illustrates an embodiment of a rail assembly.

[0031] FIG. 10 illustrates a cross sectional view of an embodiment of a delivery system handle and controller.

[0032] FIG. 11 illustrates a front plan view of an embodiment of an adaptor.

[0033] FIG. 12 illustrates a side perspective view of an embodiment of an adaptor and drive rods.

[0034] FIG. 13 illustrates a perspective view of the handle shown in FIG. 1.

[0035] FIG. 14 illustrates a perspective view of a proximal portion of the handle shown in FIG. 1.

[0036] FIG. 15 illustrates a partial cross section view of an embodiment of a portion of a handle.

[0037] FIG. **16** illustrates a partial cross section view of an embodiment of a portion of a handle.

[0038] FIG. **17** illustrates a side perspective view of insertion of a delivery apparatus into a patient's body.

[0039] FIG. **18** illustrates a cross section view of the delivery system handle and controller shown in FIG. **10**.

[0040] FIG. **19** illustrates a cross section view of a rail assembly.

[0041] FIG. **20** illustrates a cross section view of a rail assembly viewed at an angle of ninety degrees from the view shown in FIG. **19**.

[0042] FIG. **21** illustrates a perspective view of an embodiment of a distal end of an elongate sheath.

[0043] FIG. **22** illustrates a perspective view of an embodiment of a distal end of an elongate sheath.

[0044] FIG. **23** illustrates a cross sectional view of a capsule of the elongate sheath shown in FIG. **22**.

[0045] FIG. **24** illustrates a side schematic view of the elongate sheath shown in FIG. **22** deploying an implant to a mitral heart valve.

[0046] FIG. **25** illustrates a schematic view of a delivery system entering a patient's body.

[0047] FIG. **26** illustrates a schematic view of an implant deployed to a patient's mitral valve.

[0048] FIG. **27** illustrates a schematic view of an implant deployed to a patient's mitral valve.

[0049] FIG. **28** illustrates a perspective view of a distal end of an elongate sheath deploying an implant.

[0050] FIG. **29** illustrates a perspective view of a distal end of an elongate sheath deploying an implant.

[0051] FIG. **30** illustrates a perspective view of a distal end of an elongate sheath deploying an implant.

[0052] FIG. **31** illustrates a schematic view of a delivery system positioned within a right atrium of a patient's heart.

[0053] FIG. **32** illustrates a schematic view of the delivery system shown in FIG. **31** positioned within a right atrium of a patient's heart.

[0054] FIG. **33** illustrates a schematic view of a prosthetic tricuspid valve implanted in a native tricuspid valve.

[0055] FIG. **34** illustrates a schematic view of a delivery system extending through an aortic arch of a patient's heart.

[0056] FIG. **35** illustrates a schematic view of the delivery system shown in FIG. **34** extending through an aortic arch of a patient's heart.

[0057] FIG. **36** illustrates a schematic view of a prosthetic aortic valve implanted in a native aortic valve.

[0058] FIG. **37** illustrates a perspective view of an embodiment of a control device and an output device.

[0059] FIG. **38** illustrates a perspective view of an embodiment of a control device and an output device.

[0060] FIG. **39** illustrates a flow chart of a method according to an embodiment of the disclosure.

[0061] FIG. **40** illustrates a flow chart of a method according to an embodiment of the disclosure.

[0062] FIG. **41** illustrates a cross section view of an embodiment of a delivery system handle.

[0063] FIG. **42** illustrates a perspective view of an embodiment of an implant.

[0064] FIG. **43** illustrates a perspective view of an embodiment of an implant.

[0065] FIG. **44** illustrates a top view of the implant shown in FIG. **43**.

[0066] FIG. **45** illustrates a perspective view of a capsule of a delivery system.

[0067] FIG. **46** illustrates a perspective view of the capsule of the delivery system shown in FIG. **45**.

[0068] FIG. **47** illustrates a perspective view of a capsule of a delivery system.

[0069] FIG. **48** illustrates a perspective view of the capsule of the delivery system shown in FIG. **47**.

[0070] FIG. **49** illustrates a schematic view of a delivery system entering a patient's body.

[0071] FIG. **50** illustrates a schematic cross-sectional view of an implant retention area of an elongate shaft of a delivery system.

[0072] FIG. **51** illustrates an enlarged view of a coupling between an electrolytically detachable coupler and an implant.

[0073] FIG. **52** illustrates a schematic cross-sectional view of the implant retention area shown in FIG. **50**.

[0074] FIG. **53** illustrates a schematic cross-sectional view of the implant retention area shown in FIG. **50**.

[0075] FIG. **54** illustrates a schematic cross-sectional view of an implant retention area of a delivery system.

[0076] FIG. **55** illustrates a schematic cross-sectional view of an implant retention area of a delivery system.

[0077] FIG. **56** illustrates a schematic cross-sectional view of an implant retention area of a delivery system.

[0078] FIG. **57** illustrates an enlarged view of a coupling between an electrically detachable coupler and an implant.

[0079] FIG. **58** illustrates a schematic cross-sectional view of an implant retention area of a delivery system.

[0080] FIG. **59** illustrates a schematic cross-sectional view of the implant retention area shown in FIG. **58**.

DETAILED DESCRIPTION

[0081] The present specification and drawings provide aspects and features of the disclosure in the context of several embodiments of delivery systems and methods. The delivery systems and methods are preferably used for improving accuracy and ease of use during implantation of a medical device in a human body. Current medical device implantations are often performed using minimally invasive procedures, which typically involve flexible elongate catheters that are advanced through a patient's vasculature to a treatment site. Because there is no direct line of sight at the treatment site, the clinician must rely on fluoroscopy and other imaging, which can be challenging. Furthermore, the clinician is often required to manipulate buttons and knobs on a delivery system handle during the treatment procedure, which can further distract the clinician. Therefore, enhanced delivery systems that utilize sensors, motors and/or artificial intelligence have the potential to greatly enhance the quality and consistency of the outcome.

[0082] Embodiments of the delivery systems and methods described herein are configured for use in the vasculature of a patient, such as for replacement of natural heart valves in a patient or repair of the heart valves. These embodiments may be discussed in connection with replacing or repairing specific valves such as the patient's aortic, tricuspid, mitral, or pulmonary valve. However, it is to be understood that the features and concepts discussed herein can be applied to devices other than heart valve implants. For example, the delivery systems and methods can be applied to medical implants, for example other types of expandable prostheses, for use elsewhere in the body, such as within an artery, a vein, or other body cavities or locations. In addition, specific features of a valve, delivery system, method, etc. should not be taken as limiting, and features of any one embodiment discussed herein can be combined with features of other embodiments as desired and when appropriate. While certain of the embodiments described herein are described in connection with a transfemoral/transseptal delivery approach, the embodiments disclosed herein are also well-suited for other delivery approaches such as, for example, transapical, transatrial, or transjugular approaches. Moreover, the features described in connection with certain embodiments can be

incorporated with other embodiments, including those that are described in connection with different delivery approaches.

[0083] FIG. 1 illustrates an embodiment of a delivery system **10** according to an embodiment of the present disclosure. The delivery system **10** may be used to deploy an implant, such as a prosthetic replacement heart valve, to a location within a patient's body. In some embodiments, the delivery system **10** may provide multiple planes (e.g., two planes) of deflection for assisting with navigation through a patient's vascular and for enhanced precision during delivery of the implant.

Replacement heart valves may be delivered to a patient's mitral (or tricuspid) valve annulus or other heart valve location (such as the aortic or pulmonary valve) in various manners, such as by open surgery, minimally-invasive surgery, and percutaneous or transcatheter delivery through the patient's vasculature. While the delivery system **10** may be described in certain embodiments in connection with a percutaneous delivery approach, and more specifically a transfemoral delivery approach, it should be understood that features of delivery system **10** can be applied to other delivery systems, including delivery systems for a transapical, transatrial, or transjugular delivery approach.

[0084] The delivery system **10** may be used to deploy an implant, such as a replacement heart valve that may be described elsewhere in this specification, within the body. The delivery system **10** may receive and/or cover portions of the implant such as a first end **301** and second end **303** of the implant **70**, or prosthesis, illustrated in FIG. 3A. For example, the delivery system **10** may be used to deliver an expandable implant **70**, where the implant **70** includes the first end **301** and the second end **303**, and wherein the second end **303** is configured to be deployed or expanded before the first end **301**.

[0085] FIG. 2A further shows an example of the implant **70** that can be inserted into a portion of the delivery system **10**, specifically into an implant retention area **16**. For ease of understanding, in FIG. 2A, the implant is shown with only the bare metal frame illustrated. The implant **70**, or prosthesis, can take any number of different forms. One example of a frame for an implant is shown in FIG. 3A; however, other frame configurations may be utilized in other embodiments. The implant **70** may include one or more sets of anchors, such as distal (or ventricular) anchors **80** (marked in FIG. 3A), which are coupled to a distal end portion of the implant and extend in a generally proximal direction when the implant frame is in an expanded configuration. When the implant is used for mitral or tricuspid valve replacement, the distal anchors may be shaped to capture native leaflets between the anchors and the tubular main body of the implant. The implant may also include proximal (or atrial) anchors **82** for placement on an atrial side of an annulus, thereby further enhancing stability. The atrial anchors may extend radially and/or distally when the implant frame is in an expanded configuration. The implant may further include struts **72** on an atrial end, which may include tabs **74** at the first end **301** (marked in FIG. 3A). The tabs may provide an enlarged tip, such as a mushroom shape, sized for placement in a corresponding retention region, such as a slot or recess, along a distal end of a delivery system, thereby ensuring secure coupling of the implant to the delivery system.

[0086] In some embodiments, the delivery system **10** may be used in conjunction with a replacement aortic valve, such as shown in FIG. 3B. In some embodiments the delivery system **10** can be modified to support and deliver the replacement aortic valve. However, the procedures and structures discussed below can similarly be used for a replacing the function of a mitral, tricuspid, pulmonary or aortic valve, as well as other valves, such as a venous valve in the human body. The principles, procedures and structures of the disclosed embodiments are also fully applicable to other implants, which may be used for other medical treatments (unrelated to heart valves).

[0087] Referring again to FIG. 1, the delivery system **10** may be configured to deliver the implant to a location within the patient's body. The delivery system **10** may include an elongate shaft **12** that may comprise a shaft assembly and is configured to retain the implant. The elongate shaft **12** may include a proximal end **11** and a distal end **13**, wherein a housing in the form of a handle **14** is

coupled to the proximal end of the elongate shaft **12**. The elongate shaft **12** may be used to hold the implant for advancement of the same through the vasculature to a treatment location. The elongate shaft **12** may further comprise a relatively rigid live-on (or integrated) sheath **51** surrounding an interior portion of the shaft **12** that may reduce unwanted motion of the interior portion of the shaft **12**. The live-on sheath **51** can be attached at a proximal end of the shaft **12** proximal to the handle **14**, for example at a sheath hub.

[0088] Referring to FIGS. 2A and 2B, the elongate shaft **12** may include an implant retention area **16** (shown in FIGS. 2A-B with FIG. 2A showing the implant **70** and FIG. 2B with the implant **70** removed) at its distal end that can be used for this purpose. In some embodiments, the elongate shaft **12** can hold an expandable implant in a compressed state at implant retention area **16** for advancement of the implant **70** within the body. The shaft **12** may then be used to allow controlled expansion of the implant **70** at the treatment location. In some embodiments, the shaft **12** may be used to allow for sequential controlled expansion of the implant **70**, as discussed in more detail below. The implant retention area **16** is shown in FIGS. 2A-2B at the distal end of the delivery system **10** but may be in other positions. In some embodiments, the implant **70** may be rotated in the implant retention area **16**, such as through the rotation of the inner shaft assembly **18** discussed herein.

[0089] As shown in the cross-sectional view of FIGS. 2A-2B, the distal end of the delivery system **10** can include one or more assemblies such as an outer sheath assembly **22**, a mid shaft assembly **21**, a rail assembly **20**, an inner shaft assembly **18**, and a nose cone assembly **31** as will be described in more detail below. In some embodiments, the delivery system **10** may not have all the assemblies disclosed herein. For example, in some embodiments a full mid shaft assembly may not be incorporated into the delivery system **10**. In some embodiments, the assemblies may be in a different radial order than is discussed.

[0090] Embodiments of the disclosed delivery system **10** may utilize an inner steerable rail in the rail assembly **20** for steering/deflecting the distal end of the elongate shaft **12**, thereby allowing the implant to be more easily and accurately positioned in a patient's body. As discussed in detail below, the steerable rail can be, for example, a rail shaft that extends through the elongate shaft **12** from the handle **14** generally to the distal end of the elongate shaft **12**. In some embodiments, the steerable rail has a distal end that ends proximal to the implant retention area **16**. A user can manipulate the bending of the distal end of the rail, thereby bending the rail in a desired direction. In preferred embodiments, the rail has more than one bend along its length, thereby providing multiple planes of deflection. The rail preferably deflects the elongate shaft **12** in at least two planes. As the rail is bent, it presses against the other assemblies to bend them as well, and thus the other assemblies of the elongate shaft **12** can be configured to steer along with the rail as a cooperating single unit, thus providing full steerability along the distal end of the elongate shaft **12**.

[0091] Once the rail is steered into a desired location in a patient's body, the implant **70** can be advanced along or relative to the rail through the movement of the other sheaths/shafts relative to the rail and released into the body. For example, the rail can be bent into a desired position within the body, such as to direct the implant **70** towards the native mitral valve or other valve for implantation (e.g., aortic, tricuspid, pulmonary, etc.). The other assemblies (e.g., the outer sheath assembly **22**, the mid shaft assembly **21**, the inner assembly **18**, and the nose cone assembly **31**) can passively follow the bends of the rail. Further, the other assemblies (e.g., the outer sheath assembly **22**, the mid shaft assembly **21**, the inner assembly **18**, and the nose cone assembly **31**) can be advanced together (e.g., relatively together, sequentially, simultaneously, almost simultaneously, at the same time, closely at the same time) relative to the rail while maintaining the implant **70** in the compressed position without releasing or expanding the implant **70** (e.g., within the implant retention area **16**). The other assemblies (e.g., the outer sheath assembly **22**, the mid shaft assembly **21**, the inner assembly **18**, and the nose cone assembly **31**) can be advanced distally or proximally together relative to the rail. In some embodiments, only the outer sheath assembly

22, mid shaft assembly 21, and inner assembly 18 are advanced together over the rail. Thus, the nose cone assembly 31 may remain in the same position. The assemblies can be individually, sequentially, or simultaneously, translated relative to the inner assembly 18 in order to release the implant 70 from the implant retention area 16.

[0092] FIG. 2C illustrates the sheath assemblies, specifically the outer sheath assembly 22, the mid shaft assembly 21, the inner shaft assembly 18, and the nose cone assembly 31 having translated distally together along the rail assembly 20. In some embodiments, the outer sheath assembly 22, the mid shaft assembly 21, the inner shaft assembly 18, and the nose cone assembly 31 translate together (e.g., relatively together, sequentially with one actuator, simultaneously, almost simultaneously, at the same time, closely at the same time). This distal translation can occur while the implant 70 remains in a compressed configuration within the implant retention area 16.

[0093] As shown in FIGS. 2A-2C and as further shown in FIGS. 4-8, starting with the outermost assembly, the delivery system may include an outer sheath assembly 22 forming a radially outer covering, or sheath, to surround an implant retention area 16 and prevent the implant from radially expanding. Specifically, the outer sheath assembly 22 may prevent radial expansion of the distal end of the implant from radially expanding. Moving radially inward and referring to FIG. 5, the mid shaft assembly 21 may be composed of a mid shaft hypotube 43 with its distal end attached to an outer retention member 42 or outer retention ring for radially retaining a portion of the implant in a compacted configuration, such as a proximal end of the implant 70. The mid shaft assembly 21 may be located within a lumen of the outer sheath assembly 22. Moving further inwards, and referring to FIG. 6A, the rail assembly 20 may be configured for steerability, as mentioned above and further described below. The rail assembly 20 may be located within a lumen of the mid shaft assembly 21. Moving further inwards and referring to FIG. 7, the inner shaft assembly 18 may be composed of an inner shaft with its distal end attached to inner retention member or inner retention ring 40 (such as a PEEK ring) for axially retaining the prosthesis, for example the proximal end of the prosthesis. The inner shaft assembly 18 may be located within a lumen of the rail assembly 20. Further, and referring to FIG. 8, the most radially-inward assembly may be the nose cone assembly 31 which includes the nose cone shaft 27 having its distal end connected to the nose cone 28. The nose cone 28 can have a tapered tip. The nose cone assembly 31 is preferably located within a lumen of the inner shaft assembly 18. The nose cone assembly 31 may include a lumen for a guide wire to pass therethrough.

[0094] The elongate shaft 12 and its assemblies, more specifically the nose cone assembly 31, inner assembly 18, rail assembly 20, mid shaft assembly 21, and outer sheath assembly 22, can be collectively configured to deliver an implant 70 positioned within the implant retention area 16 (shown in FIG. 2A) to a treatment location. One or more of the assemblies may then be moved to allow the implant 70 to be released at the treatment location. For example, one or more of the assemblies may be movable with respect to one or more of the other assemblies. The handle 14 may include one or more motors, or other components, that may be used to actuate the various assemblies. The implant 70 may be controllably loaded onto the delivery system 10 and then later deployed within the body. Further, the handle 14 can provide steering to the rail assembly 20, providing for bending/flexing/steering of the distal end of the elongate shaft 12.

[0095] Referring to FIGS. 2A-2C, the inner retention member 40, the outer retention member 42, and the outer sheath assembly 22 can cooperate to hold the implant 70 in a compacted configuration. In FIG. 2A, the inner retention member 40 is shown engaging struts 72 (marked in FIG. 3A) at the proximal end 301 of the implant 70. For example, slots located between radially extending teeth on the inner retention member 40 can receive and engage the struts 72 which may end in mushroom-shaped tabs 74 on the proximal end of the implant 70 (marked in FIG. 3A). The mid shaft assembly 21 can be positioned over the inner retention member 40 so that the first end 301 of the implant 70 (marked in FIG. 3A) is trapped between the inner retention member 40 and the outer retention member 42, thereby securely attaching it to the delivery system 10 between the

mid shaft assembly **21** and the inner retention member **40**. The outer sheath assembly **22** can be positioned to cover the second end **303** of the implant **70** (marked in FIG. 3A).

[0096] The outer retention member **42** may be attached to a distal end of the mid shaft hypotube **43** which can in turn be attached to a proximal tube **44** at a proximal end (marked in FIG. 5), which in turn can be attached at a proximal end to the handle **14**. The outer retention member **42** can provide further stability to the implant **70** when in the compressed position. The outer retention member **42** can be positioned over the inner retention member **40** so that the proximal end of the implant **70** is trapped therebetween, securely attaching it to the delivery system **10**. The outer retention member **42** can encircle a portion of the implant **70**, preferably the first end **301**, thus preventing the implant **70** from fully expanding. Further, the mid shaft assembly **21** can be translated proximally with respect to the inner assembly **18** into the outer sheath assembly **22**, thus exposing a first end **301** of the implant **70** held within the outer retention member **42**. In this way the outer retention member **42** can be used to help secure an implant **70** to or release it from the delivery system **10**. The outer retention member **42** may have a cylindrical or elongate tubular shape and may be referred to as an outer retention ring, though the particular shape is not limiting.

[0097] As shown in FIG. 2A, the distal anchors **80** (marked in FIG. 3A) extend in a generally distal direction (as illustrated, axially away from the main body of the implant frame and away from the handle of the delivery system) when the implant is compressed for delivery. The distal anchors **80** can be restrained in this delivered configuration by the outer sheath assembly **22**. Accordingly, when the outer sheath **22** is withdrawn proximally, the distal anchors **80** can flip positions (e.g., bend approximately 180 degrees) to a deployed configuration (e.g., pointing generally proximally). The flipping of the distal anchors occurs due to a bias or shape-memory preset, which causes the anchors to flip in the absence of external forces. FIG. 2A also shows the proximal anchors (see **82** in FIG. 3A) extending distally in their delivered configuration within the outer sheath assembly **22**. In other embodiments, the distal anchors **80** can extend generally proximally while in the delivered configuration and compressed against the body of the implant frame, thereby eliminating the need to flip during deployment.

[0098] The delivery system **10** may be provided to users with an implant **70** preinstalled. In other embodiments, the implant **70** can be loaded onto the delivery system **10** shortly before use, such as by a physician or nurse.

[0099] FIGS. 4-8 illustrate further views of delivery system **10** with different assemblies translated proximally and described in detail.

[0100] Starting with the outermost assembly shown in FIG. 4, the outer sheath assembly **22** can include an outer proximal shaft **102** directly attached to the handle **14** at its proximal end and an outer hypotube **104** attached at its distal end. A capsule **106** can then be attached generally at the distal end of the outer hypotube **104**. In some embodiments, the capsule **106** can be 28 French or less in size. These components of the outer sheath assembly **22** can form a lumen for the other subassemblies to pass through.

[0101] A capsule **106** can be located at a distal end of the outer proximal shaft **102**. The capsule **106** can be a tube formed of a plastic or metal material. In some embodiments, the capsule **106** is formed of ePTFE or PTFE. In some embodiments, this capsule **106** is relatively thick to prevent tearing and to help maintain a self-expanding implant in a compacted configuration. In some embodiments the material of the capsule **106** is the same material as the coating on the outer hypotube **104**. As shown, the capsule **106** can have a diameter larger than the outer hypotube **104**, though in some embodiments the capsule **106** may have a similar diameter as the hypotube **104**. In some embodiments, the capsule **106** may include a larger diameter distal portion and a smaller diameter proximal portion. In some embodiments, there may be a step or a taper between the two portions. The capsule **106** can be configured to retain the implant **70** in the compressed position within the capsule **106**. Further construction details of the capsule **106** are discussed below.

[0102] The outer sheath assembly **22** is configured to be individually slidable with respect to the

other assemblies. Further, the outer sheath assembly **22** can slide distally and proximally relative to the rail assembly **20** together with the mid shaft assembly **21**, inner assembly **18**, and nose cone assembly **31**.

[0103] Moving radially inwardly, the next assembly is the mid shaft assembly **21**. FIG. 5 shows a similar view as FIG. 4, but with the outer sheath assembly **22** removed, thereby exposing the mid shaft assembly **21**.

[0104] The mid shaft assembly **21** can include a mid shaft hypotube **43** generally attached at its proximal end to a mid shaft proximal tube **44**, which in turn can be attached at its proximal end to the handle **14**, and an outer retention ring **42** located at the distal end of the mid shaft hypotube **43**. Thus, the outer retention ring **42** can be attached generally at the distal end of the mid shaft hypotube **43**. These components of the mid shaft assembly **21** can form a lumen for other subassemblies to pass through.

[0105] The outer retention member **42** can be configured as a prosthesis retention mechanism that can be used to engage with the implant **70**, as discussed with respect to FIG. 2A. For example, the outer retention member **42** may be a ring or covering that is configured to radially cover the struts **72** on the implant **70** (marked in FIG. 3A). The outer retention member **42** can also be considered to be part of the implant retention area **16**, and may be at the proximal end of the implant retention area **16**. With struts or other parts of an implant **70** engaged with the inner retention member **40**, the outer retention member **42** can cover both the implant **70** and the inner retention member **40** to secure the implant **70** on the delivery system **10**. Thus, the implant **70** can be sandwiched between the inner retention member **40** of the inner shaft assembly **18** and the outer retention member **42** of the mid shaft assembly **21**.

[0106] The mid shaft assembly **21** is disposed so as to be individually slidable with respect to the other assemblies. Further, the mid shaft assembly **21** can slide distally and proximally relative to the rail assembly **20** together with the outer sheath assembly **22**, mid inner assembly **18**, and nose cone assembly **31**.

[0107] Next, radially inwardly of the mid shaft assembly **21** is the rail assembly **20**. FIG. 6A shows approximately the same view as FIG. 5, but with the mid shaft assembly **21** removed, thereby exposing the rail assembly **20**. FIG. 6B further shows a cross-section of the rail assembly **20** to view the pull wires. The rail assembly **20** can include a rail shaft **132** (or rail) generally attached at its proximal end to the handle **14**. The rail shaft **132** may be made up of a rail proximal shaft **134** directly attached to the handle at a proximal end and a rail hypotube **136** attached to the distal end of the rail proximal shaft **134**. The rail hypotube **136** may further include an atraumatic rail tip at its distal end. Further, the distal end of the rail hypotube **136** can abut a proximal end of the inner retention member **40**, as shown in FIG. 6A. In some embodiments, the distal end of the rail hypotube **136** can be spaced away from the inner retention member **40**. These components of the rail shaft assembly **20** can form a lumen for the other subassemblies to pass through.

[0108] As shown in FIG. 6B, attached to an inner surface of the rail hypotube **136** are one or more pull wires which can be used apply forces to the rail hypotube **136** and steer the rail assembly **20**. The pull wires can extend distally from the handle **14** to the rail hypotube **136**. In some embodiments, pull wires can be attached at different longitudinal locations on the rail hypotube **136**, thus providing for multiple bending locations in the rail hypotube **136**, allowing for multidimensional steering. The rail hypotube **136** may allow for deflection of the elongate shaft **20** in at least two planes.

[0109] In some embodiments, a distal pull wire **138** can extend to a distal section of the rail hypotube **136** and two proximal pull wires **140** can extend to a proximal section of the rail hypotube **136**, however, other numbers of pull wires can be used, and the particular amount of pull wires is not limiting. For example, two pull wires can extend to a distal location and a single pull wire can extend to a proximal location. In some embodiments, ring-like structures attached inside the rail hypotube **136**, known as pull wire connectors, can be used as attachment locations for the

pull wires, such as proximal ring **137** and distal ring **135**. In some embodiments, the rail assembly **20** can include a distal pull wire connector in the form of distal ring **135** and a proximal pull wire connector in the form of proximal ring **137**. In some embodiments, the pull wires can directly connect to an inner surface of the rail hypotube **136**.

[0110] The distal pull wire **138** can be connected (either on its own or through a connector such as distal ring **135**) generally at the distal end of the rail hypotube **136**. The proximal pull wires **140** can connect (either on its own or through a connector such as proximal ring **137**) at a location approximately one quarter, one third, or one half of the length up the rail hypotube **136** from the proximal end. In some embodiments, the distal pull wire **138** can pass through a small diameter pull wire lumen **139** (e.g., tube, hypotube, cylinder) attached on the inside of the rail hypotube **136**. This can prevent the wires **138** from pulling on the rail hypotube **136** at a location proximal to the distal connection. Further, the lumen **139** can act as compression coils to strengthen the proximal portion of the rail hypotube **136** and prevent unwanted bending. Thus, in some embodiments the lumen **139** is only located on the proximal half of the rail hypotube **136**. In some embodiments, multiple lumens **139**, such as spaced longitudinally apart or adjacent, can be used per distal pull wire **138**. In some embodiments, a single lumen **139** is used per distal pull wire **138**. In some embodiments, the lumen **139** can extend into the distal half of the rail hypotube **136**. In some embodiments, the lumen **139** is attached on an outer surface of the rail hypotube **136**. In some embodiments, the lumen **139** is not used.

[0111] For the pair of proximal pull wires **140**, the wires can be spaced approximately 180 degrees from one another to allow for steering in both directions. Similarly, if a pair of distal pull wires **138** is used, the wires can be spaced approximately 180 degrees from one another to allow for steering in both directions. In some embodiments, the pair of distal pull wires **138** and the pair of proximal pull wires **140** can be spaced approximately 90 degrees from each other. In some embodiments, the pair of distal pull wires **138** and the pair of proximal pull wires **140** can be spaced approximately 0 degrees from each other. However, other locations for the pull wires can be used as well and the illustrated location of the pull wires is not limiting. In some embodiments, the distal pull wire **138** can pass through a lumen **139** attached within the lumen of the rail hypotube **136**. This can prevent an axial force on the distal pull wire **138** from creating a bend in a proximal section of the rail hypotube **136**.

[0112] The rail assembly **20** is disposed so as to be slidable over the inner shaft assembly **18** and the nose cone assembly **31**. In some embodiments, the outer sheath assembly **22**, the mid shaft assembly **21**, the inner shaft assembly **18**, and the nose cone assembly **31** can be configured to slide together along or relative to the rail assembly **20**, such as proximally and distally with or without any bending of the rail assembly **20**. In some embodiments, the outer sheath assembly **22**, the mid shaft assembly **21**, the inner shaft assembly **18**, and the nose cone assembly **31** can be configured to retain the implant **70** in a compressed position when they are simultaneously slid along or relative to the rail assembly **20**.

[0113] Moving radially inwards, the next assembly is the inner shaft assembly **18**. FIG. 7 shows approximately the same view as FIG. 6A, but with the rail assembly **20** removed, thereby exposing the inner shaft assembly **18**.

[0114] The inner shaft assembly **18** can include an inner shaft **122** generally attached at its proximal end to the handle **14**, and an inner retention member **40** located at the distal end of the inner shaft **122**. The inner shaft **122** itself can be made up of an inner proximal shaft **129** directly attached to the handle **14** at a proximal end and a distal section **126** attached to the distal end of the inner proximal shaft **129**. Thus, the inner retention member **40** can be attached generally at the distal end of the distal section **126**. These components of the inner shaft assembly **18** can form a lumen for the other subassemblies to pass through.

[0115] The inner retention member **40** may be configured as an implant retention mechanism that can be used to engage with the implant **70**, as discussed with respect to FIG. 2A. For example, the

inner retention member **40** may be a ring and can include a plurality of slots configured to engage with struts **72** on the implant **70** (marked in FIG. **3A**). The inner retention member **40** can also be considered to be part of the implant retention area **16** and may be at the proximal end of the implant retention area **16**. With struts or other parts of an implant **70** engaged with the inner retention member **40**, the outer retention ring **42** can cover both the implant and the inner retention member **40** to secure the prosthesis on the delivery system **10**. Thus, the implant **70** can be sandwiched between the inner retention member **40** of the inner shaft assembly **18** and the outer retention member **42** of the mid shaft assembly **21**.

[0116] The inner shaft assembly **18** is disposed so as to be individually slidable with respect to the other assemblies. Further, the inner assembly **18** can slide distally and proximally relative to the rail assembly **20** together with the outer sheath assembly **22**, mid shaft assembly **21**, and nose cone assembly **31**.

[0117] Moving further inwardly from the inner shaft assembly **18** is the nose cone assembly **31** seen in FIG. **8**. The nose cone assembly may include a nose cone shaft **27**, and in some embodiments, may have a nose cone **28** on its distal end. The nose cone **28** may be made of polyurethane for atraumatic entry and to minimize injury to venous vasculature. The nose cone **28** may also be radiopaque to provide for visibility under fluoroscopy.

[0118] The nose cone shaft **27** may include a lumen sized and configured to slidably accommodate a guide wire so that the delivery system **10** can be advanced over the guide wire through the vasculature. However, embodiments of the system **10** discussed herein may not use a guide wire and thus the nose cone shaft **27** in certain embodiments may be solid. The nose cone shaft **27** may be connected from the nose cone **28** to the handle, or may be formed of different segments such as the other assemblies. Further, the nose cone shaft **27** may be formed of different materials, such as plastic or metal, similar to those described in detail above. In some embodiments, the nose cone shaft **27** includes a guide wire shield **1200** located on a portion of the nose cone shaft **27**.

[0119] The nose cone assembly **31** may be disposed so as to be individually slidable with respect to the other assemblies. Further, the nose cone assembly **31** may slide distally and proximally relative to the rail assembly **20** together with the outer sheath assembly **22**, mid shaft assembly **21**, and inner assembly **18**.

[0120] In some embodiments, one or more spacer sleeves (not shown) can be used between different assemblies of the delivery system **10**. For example, a spacer sleeve can be located concentrically between the mid shaft assembly and the rail assembly **20**, generally between the mid shaft hypotube **43** and rail hypotube **136**. The spacer sleeve can be generally embedded in the hypotube **43** of the mid shaft assembly **21**, such as on an inner surface of the mid shaft assembly **21**. In some embodiments, a spacer sleeve can be located concentrically between the rail assembly **20** and the inner assembly **18**, generally within the rail hypotube **136**. In some embodiments, a spacer sleeve can be used between the outer sheath assembly **22** and the mid shaft assembly **21**. In some embodiments, a spacer sleeve can be used between the inner assembly **18** and the nose cone assembly **31**. In some embodiments, 4, 3, 2, or 1 of the above-mentioned spacer sleeves can be used. The spacer sleeves can be used in any of the above positions.

[0121] As discussed above, the outer sheath assembly **22**, the mid shaft assembly **21**, the inner assembly **18**, and the rail assembly **20** may contain an outer hypotube **104**, a mid shaft hypotube, a distal section **126**, and a rail hypotube **136**, respectively. Each of these hypotubes/sections/shafts can be laser cut to include a number of slots, thereby creating a bending pathway for the delivery system to follow.

[0122] For example, FIG. **9** shows an embodiment of the rail hypotube **136** (distal end towards the right). The rail hypotube **136** can also contain a number of circumferential slots. The rail hypotube **136** can generally be broken into a number of different sections. At the most proximal end is an uncut (or unslotted) hypotube section **231**. Moving distally, the next section is the proximal slotted hypotube section **233**. This section includes a number of circumferential slots cut into the rail

hypotube **136**. Generally, two slots are cut around each circumferential location forming almost half of the circumference. Accordingly, two backbones are formed between the slots extending up the length of the hypotube **136**. This is the section that can be guided by the proximal pull wires **140**. Moving further distally is the location **237** where the proximal pull wires **140** connect, and thus slots can be avoided. Thus section is just distal of the proximally slotted section.

[0123] Distally following the proximal pull wire connection area is the distal slotted hypotube section **235**. This section is similar to the proximal slotted hypotube section **233**, but has significantly more slots cut out in an equivalent length. Thus, the distally slotted hypotube section **235** provides easier bending than the proximally slotted hypotube section **233**. In some embodiments, the proximal slotted section **233** can be configured to experience a bend of approximately 90 degrees with a half inch radius whereas the distal slotted section **235** can bend at approximately 180 degrees within a half inch. Further, as shown in FIG. **9**, the spines of the distally slotted hypotube section **235** are offset from the spines of the proximally slotted hypotube section **233**. Accordingly, the two sections will achieve different bend patterns, allowing for three-dimensional steering of the rail assembly **20**. In some embodiments, the spines can be offset 30, 45, or 90 degrees, though the particular offset is not limiting. In some embodiments, the proximally slotted hypotube section **233** can include compression coils. This allows for the proximally slotted hypotube section **233** to retain rigidity for specific bending of the distally slotted hypotube section **235**.

[0124] At the distalmost end of the distal slotted hypotube section **235** is the distal pull wire connection area **241** which is again a non-slotted section of the rail hypotube **136**.

[0125] Referring again to FIG. **1**, the elongate shaft **12** and housing in the form of a handle **14** may form a delivery apparatus that is configured to deliver the implant **70** to a location within a patient's body. The delivery system **10** may include at least one motor that is configured to actuate at least a portion of the delivery apparatus. The actuation of at least a portion of the delivery apparatus may include deflection of a portion of the delivery apparatus (including the elongate shaft) or other movement of the delivery apparatus and may include actuation of an operation of the delivery apparatus. The operation may include deployment (whether full or partial) of the implant **70** to the body location, among other operations of the delivery apparatus. The motor may comprise a motor **500** as shown in FIG. **10** or may comprise a plurality of motors **502** shown in FIG. **41** (i.e., at least one motor), among other forms of motors.

[0126] As shown in FIG. **1**, the housing in the form of the handle **14** may be positioned at the proximal end **11** of the elongate shaft **12**. The proximal end **11** of the elongate shaft **12** may be coupled to the handle **14**. The handle **14** may include a control device **504** configured to control the at least one motor. The control device **504** as shown in FIG. **1** may include a plurality of buttons; however, in other embodiments other forms of control devices may be utilized. The control device **504** may be positioned on the handle **14** as shown in FIG. **1** or may be located remotely.

[0127] FIG. **10** illustrates a cross section of the handle **14** including the motor **500** and an actuation mechanism **506** that may be utilized to actuate at least a portion of the delivery apparatus. In various embodiments, the motor and actuation mechanism may be used to actuate pull wires during advancement through the vasculature. The motor and actuation mechanism may be used to actuate to actuate shafts/sheaths for deploying and releasing the implant at the treatment site. The body of the handle **14** may include multiple parts, including a distal portion **508** and a proximal portion **510**. The distal portion **508** as shown in FIG. **10** may be configured to retain the actuation mechanism **506** and the proximal portion **510** may be configured to retain the motor **500**. In other embodiments, other components may be positioned in respective distal **508** and proximal portions **510**, and in certain embodiments the handle **14** may include a single body. In the embodiment shown in FIG. **10**, the distal portion **508** and proximal portion **510** may be configured to couple together via a coupler **512**, **514** (marked in FIGS. **13** and **14**), and may be separable from each other in certain embodiments.

[0128] The actuation mechanism **506** may take the form as shown in FIG. **10** and may include a plurality of adaptors **516a-g** configured to engage with a plurality of drive rods **518a-g** (drive rods **518f-g** are marked in FIG. **12**). Each adaptor **516a-g** may comprise a plate or other body including a plurality of apertures. FIG. **11** illustrates a front plan view of the adaptor **516a**. The adaptor **516a** as shown in FIG. **11** may include apertures **520a-g** and **522**. The apertures **520a-g** may each be configured to allow a respective drive rod **518a-g** to pass therethrough (as represented in FIG. **12**). The apertures **520b-g** may each be configured to be smooth bearing surfaces, that do not engage the respective drive rods **518b-g**. The aperture **520a**, however, may be configured with a threaded surface or other surface that engages the drive rod **518a**. For example, the drive rod **518a** may include a gear threading and the aperture **520a** may include a threading that matches the gear threading. Such a configuration allows the drive rod **518a** to actuate the adaptor **516a** in two directions (distal and proximal) based on the direction that the drive rod **518a** is rotating. In other embodiments, other forms of engagement may be utilized.

[0129] The central aperture **522** may allow other components of the actuation mechanism **506** such as assembly connectors to pass through the central aperture to couple to the remaining respective adaptors **516a-g**.

[0130] FIG. **12** illustrates a perspective view of adaptor **516a** with representative drive rods **518a-g** extending through the apertures **520a-g**.

[0131] The other adaptors **516b-g** may be configured similarly as the adaptor **516a**, however, each respective adaptor **516b-g** may have an aperture that is configured to engage the respective drive rods **518b-g**, with the remaining apertures comprising smooth bearing surfaces. For example, for adaptor **516b**, the equivalent aperture to aperture **520b** may be configured to engage drive rod **518b** while the remaining equivalent apertures to apertures **520a, c-g** may comprise smooth bearing surfaces. Adaptors **516c-g** have similar respective apertures configured to engaged respective drive rods **518c-g**. In this manner, a single drive rod **518a-g** may be configured to actuate a respective dedicated adaptor **516a-g**. The remaining drive rods may pass through the remaining adaptors without engaging the adaptor.

[0132] Referring again to FIG. **10**, the adaptors **516a-g** may be configured to slide within the interior cavity of the housing comprising the handle **14**. The outer surfaces of the adaptors **516a-g** for example, may be positioned on a track within the handle **14** or otherwise configured to slide or move within the handle **14**.

[0133] The drive rods **518a-g** may extend longitudinally along the interior of the handle **14** and may be configured to engage a respective adaptor **516a-g**. For example, FIG. **10** illustrates the adaptor **516a** engaged by drive rod **518a** and the adaptor **516g** engaged by drive rod **518e** (in a configuration in which adaptor **516g** was configured to be engaged by drive rod **518e**, other configurations, e.g., the adaptor **516g** being engaged by drive rod **518g**, may be utilized). Proximal ends of the drive rods **518a-g** may be configured to engage and be actuated by motor **500**.

[0134] The adaptors **516a-g** may be coupled to assembly connectors that couple to respective portions of the assemblies (the outer sheath assembly **22**, the mid shaft assembly **21**, the rail assembly **20**, the inner assembly **18**, and the nose cone assembly **31**) including the pull wire assemblies **138, 140**. In certain embodiments, the adaptors **516a-g** may couple to particular components comprising each of the assemblies, for example, the adaptor **516a** may couple directly to the nose cone shaft **27** in certain embodiments. The coupling of the adaptors **516a-g** to the assembly connectors may be such that the adaptor **516a** couples to an assembly connector **521** for the outer sheath assembly **22**. The adaptor **516b** may couple to an assembly connector **523** for the mid shaft assembly **21**. The adaptor **516c** may couple to an assembly connector **524** for the rail assembly **20**. The adaptor **516d** may couple to an assembly connector for the distal pull wires **138** or may couple to the distal pull wires **138** directly. The adaptor **516e** may couple to an assembly connector for the proximal pull wires **140** or may couple to the proximal pull wires **140** directly. The adaptor **516f** may couple to an assembly connector **526** for the inner assembly **18**. The adaptor

516g may couple to an assembly connector **528** for the nose cone assembly **31**. The assembly connectors **521**, **523**, **524**, **526**, **528** may comprise sheaths that extend concentrically over each other, or may comprise rods, wires, or other forms of connectors. The assembly connectors **521**, **523**, **524**, **526**, **528** may be configured to pass through the central aperture of the respective adaptors **516a-g** (for example aperture **522** shown in FIG. **11**).

[0135] The assembly connectors **521**, **523**, **524**, **526**, **528** may have a proximal portion coupled to the respective adaptor **516a, b, c, f, g** and a distal portion coupled to a portion of the respective assembly in order to actuate the respective assembly. For example, the assembly connector **521** may couple to the outer sheath assembly **22** such that movement of the assembly connector **521** moves the outer covering, or sheath of the outer sheath assembly **22** to expose the implant **70** in the capsule **106**. The assembly connector **523** may couple to the mid shaft assembly **21** such that movement of the assembly connector **523** moves the outer retention member **42**. The assembly connector **524** may couple to the rail assembly **20** such that movement of the assembly connector **524** moves the rail assembly **20**. The movement of the adaptors **516d** and **516e** may move the respective pull wires **138**, **140**. The assembly connector **526** may couple to the inner assembly **18** such that movement of the assembly connector **526** moves the inner retention member **40**. The assembly connector **528** may couple to the nose cone assembly **31** such that movement of the assembly connector **528** moves the nose cone **28**. The respective drive rod **518a-g** may thus be actuated by the motor **500** to selectively move a respective adaptor **516a-g** and accordingly a respective portion of the assemblies (the outer sheath assembly **22**, the mid shaft assembly **21**, the rail assembly **20**, the inner assembly **18**, and the nose cone assembly **31**).

[0136] The motion of the assemblies (the outer sheath assembly **22**, the mid shaft assembly **21**, the rail assembly **20**, the inner assembly **18**, and the nose cone assembly **31**) may be a translation of the respective assemblies, which may include the pull wires **138**, **140**, to produce the desired movement (e.g., deflection) or operation (e.g., deployment of the implant). For example, the motor **500** may be configured to translate a rail shaft of the rail assembly **20** relative to an inner sheath of the inner assembly **18** and the outer sheath of the outer sheath assembly **22**. The motor **500** may be configured to translate the outer sheath of the outer sheath assembly **22** relative to the inner sheath of the inner assembly **18** in certain embodiments. The motor **500** may be configured to translate any of the assemblies relative to each other to produce a desired result. The motor **500** may be configured to steer the rail assembly **20**, for example, by actuating the pull wires **138**, **140**. Other movements may include actuating a depth of the elongate shaft **12**, and actuating an operation of the elongate shaft **12**, for example a full or partial deployment of the implant **70**.

[0137] In other embodiments, the actuation of the delivery apparatus with the motor **500** may occur in a different manner than shown in FIG. **10**. In one embodiment the configuration of the actuation mechanism **506** may differ from the configuration shown in FIG. **10**.

[0138] The delivery system **10** may include a controller **530** that is configured to control operation of the motor **500** and thus control actuation of the portion of the delivery apparatus. The controller **530** as shown in FIG. **10** may include an input device and an output device (marked as item **532**). The controller **530** may include a memory **534** and a processor **536**. The controller may include a power source **538**.

[0139] The input device and output device **532** may have a plurality of configurations, including electrical ports or terminals that are configured to transmit electrical signals. The input device may be configured to receive signals from the motor **500** as well as from sensors positioned on the delivery system **10**. The output device may be configured to transmit signals to the motor **500** or other components of the system **10** which may be received from the processor **536** or other components of the system **10**. In certain embodiments, the input device and output device **532** may comprise wireless transmission devices, such as a Wi-Fi or Bluetooth device or other device configured for wireless communication. In an embodiment in which the controller **530** is positioned remotely from the delivery apparatus, the input device and output device **532** may be

configured to transmit and receive information via the Internet or other form of communication medium. In other embodiments, other forms of input devices and output devices may be utilized. [0140] The memory **534** may be configured to store programs for operation by the processor **536** as well as other data desired to be stored in the controller **530**. The memory **534** may be configured to store and log data, such as regarding the patient and the operation of the delivery apparatus and the motor **500** during a procedure, thereby allowing the system to learn from past events. The learning aspect may be based on an algorithm capable of identifying procedures that have produced positive outcomes in the past, thereby allowing the system to continually refine the procedure to enhance the probability of a successful outcome. Preferably, data could be pooled from different patients, different clinicians and/or different hospitals. The compilation of data could be used to increase precision and improve outcomes in future procedures. This could be achieved, for example, by comparing characteristics of a new patient with patients who have been treated in the past. Data from procedures on past patients with similar anatomies and/or other parameters, such as the patient's gender, age, and health, would be particularly useful. Other parameters could be incorporated into the algorithm, such as the clinician's skill level and amount of experience and/or the facilities available at the hospital. The data may be used in a machine learning algorithm utilizing data from past implantation procedures or from characteristics of the patient.

[0141] The memory **534** may comprise various forms of memory including a hard disk, solid state memory, various forms of RAM or ROM, or other forms of memory. In one embodiment, the memory **534** may be configured to be removable from the controller **530** for storage and/or data analysis. Separate memory **534** may be installed into the controller **530** or swapped into or out of the controller **530** as desired for a particular operation.

[0142] The processor **536** may be configured to perform processes disclosed herein and may be configured to provide signals to components of the system **10** for example, the motor **500** to perform desired processes. The processor **536** may be configured to operate the motor **500**, or at least one motor **500**, to actuate at least a portion of the delivery apparatus. The processor **536** may be configured to operate at least one motor **500** to move a portion of the delivery apparatus (e.g., deflect or control a depth of the elongate shaft **12**), or perform an operation of the delivery apparatus, which may include deploying the implant **70** from the delivery apparatus. The processor **536** may be configured to execute processes stored in the memory **534**. The processor **536** may be configured to receive signals from components of the system **10** such as a control device (for example control device **504**) or sensors of the system **10**. The processor **536** may be configured to process and perform operations based on those signals. The processor **536** may comprise a microprocessor, or other form of processor as desired. In one embodiment, the processor **536** may comprise a plurality of processors, and in one embodiment may be distributed in a cloud computing environment or the like.

[0143] The power source **538** may be configured to provide power to the components of the controller **530** and may be configured to provide power to the motor **500** or other components of the system **10**. The power source **538** may comprise one or more batteries according to certain embodiments, which may be rechargeable and detachable from the controller **530** or other components of the system **10** as desired. In one embodiment, the power source **538** may comprise a power plug, such as an AC plug, and may include a power regulator for converting the AC power to a power usable by the system **10**. Other forms of power sources **538** (e.g., super capacitors, solar cells, among others) may be used in other embodiments as desired.

[0144] The components of the controller **530** may be positioned together as shown in FIG. **10** or may be distributed as desired. The components of the controller **530** may be positioned in a separate housing, or control box, and may be coupled to the delivery apparatus with a cable or the like. FIG. **10** illustrates a cabled connection of the controller **530** to the delivery apparatus. In other embodiments, wireless communication may be possible between one or more components of the controller **530** and the delivery apparatus. In other embodiments, components of the controller **530**

may be positioned within the housing of the delivery apparatus, for example, in a configuration shown in FIG. 41.

[0145] Power and signal connectors **540** may extend between the controller **530** and the delivery apparatus. For example, a signal connector **540** is shown extending along a portion of the handle **14** and may couple between the distal portion **508** of the handle **14** and the proximal portion **510** at the electrical coupler **542**. Power connectors **540** may extend to the motor **500** from the power source **538** of the controller **530**.

[0146] FIG. 13 illustrates a perspective view of the distal portion **508** of the handle **14**. The distal portion **508** of the handle **14** may be configured to separate from the proximal portion **510** (shown in FIG. 14). Such a configuration may allow a particular portion of the handle **14** of the delivery apparatus to be utilized in delivery of an implant, and then separated from another portion (e.g., proximal portion **510**) of the handle **14** such that sterilization or discard of the distal portion **508** may occur. This process may separate electrical components of the system **10**, which may include the motor **500** positioned within the proximal portion **510**, or may include the controller **530**, from components that are inserted into or contact portions of the patient's body. This may enhance reusability of the system **10** and reduce the overall complexity associated with sterilizing the system **10**. As shown in FIG. 13, proximal portions of the drive rods **518a-g** may extend proximally from the distal portion **508** of the handle **14**, for coupling to respective apertures **544a-g** in the proximal portion **510** of the handle **14**. The proximal portions of the drive rods **518a-g** may couple to the respective apertures **544a-g** to allow the motor **500** to engage the drive rods **518a-g**. The electrical coupler **542** and coupler **512** are also shown protruding from the distal portion **508** of the handle **14**.

[0147] FIG. 14 illustrates a perspective view of the proximal portion **510** of the handle **14**. The proximal portion **510** may include a cable **546** or other connector that couples the proximal portion **510** to the controller **530**, which may be contained in a control box or the like.

[0148] Referring again to FIG. 13, the control device **504** is shown on the distal portion **508** of the handle **14** as including a plurality of buttons. The control device **504** may be configured to receive an input from a user to operate the motor **500** and thus actuate a portion of the delivery apparatus. The control device **504** may be configured to send a signal directly to the motor **500** or may be sent to the processor **536** of the controller **530** for processing. The control device **504** may be configured to control deflection and movement of the delivery apparatus. The control device **504** may be configured to control an operation of the delivery apparatus such as deployment of the implant **70**. The control device **504** may have a variety of forms, and as shown in FIG. 13 may have portions designated to control certain movements or operations of the delivery apparatus.

[0149] The control device **504** of FIG. 13 may include buttons **548** that control the rail assembly **20** and particularly the direction of deflection of the rail assembly **20**, which may be in multiple planes. The buttons **548** may be configured to control steering of the rail assembly **20**. The user may press the desired button **548** to cause the motor to actuate the delivery apparatus to deflect in the desired direction. The control device **504** of FIG. 13 may include buttons **550** that control the depth of the elongate shaft **12**, for example, by sliding the assemblies including the outer sheath assembly **22**, the mid shaft assembly **21**, the inner assembly **18**, and the nose cone assembly **31**, relative to the rail assembly **20**. The buttons **550** may allow the user to increase or decrease the depth. The control device **504** of FIG. 13 may include buttons **552** that actuate deployment of the implant **70**. For example, the buttons **552** may cause the motor to actuate the delivery apparatus to retract the outer sheath assembly **22** and the mid shaft assembly **21** to deploy the implant **70**. The control device **504** of FIG. 13 may include buttons **554** that actuate movement of the nose cone assembly **31**, to advance or retract the nose cone **28**. Various configurations of control may be utilized to deflect the delivery apparatus or to perform operations of the delivery apparatus. The control signals from the control device **504** may be sent directly to the motor **500** for operation or may be sent to the processor **536** for the processor **536** to operate the motor **500** to actuate at least a

portion of the delivery apparatus. The configuration of the control device **504** may be varied in other embodiments.

[0150] FIG. **15**, for example, illustrates a cross sectional portion of a part of the handle **14** in which a control device **556** comprises one or more of a touch pad **558** and a touch screen **560** on the handle **14**. The touch pad **558** may be configured for the user to provide directional control for the delivery apparatus via the rail assembly **20**. The touch screen **560** may be configured for the user to provide other controls to the delivery apparatus, including depth control, deployment of the implant **70**, or movement of one or more of the assemblies of the delivery apparatus. The touch pad or touch screen may include tactile, light, or audible feedback for assisting the user.

[0151] FIG. **16**, for example, illustrates a cross sectional portion of a part of the handle **14** in which a control device **562** comprises a joystick **564** and one or more buttons **566**. The joystick **564** may be configured for the user to provide directional control for the delivery apparatus via the rail assembly **20**. The one or more buttons **566** may be configured for the user to provide other controls to the delivery apparatus, including depth control, deployment of the implant **70**, or movement of one or more of the assemblies of the delivery apparatus.

[0152] Through use of a device such as a touch pad **558** or a joystick **564** to control the rail assembly **20**, the user may be able to move the rail assembly **20** in combinations of directions simultaneously. This is an improvement over prior methods, which primarily use mechanical knobs or the like, wherein the user is only able to move the rail assembly **20** in a single plane at a single time. With the use of a motor **500** to actuate the rail assembly **20**, the rail assembly **20** may move in multiple planes simultaneously. The simultaneous control may be provided by a corresponding signal from the control device to the motor **500**. In one embodiment, the simultaneous control may be provided by the processor **536** to the motor **500**. For example, a user (e.g., a clinician) may provide an input for a particular direction of movement via the joystick **564** that is sent to the processor **536**. The processor **536** may process the input to control the motor **500** to move the elongate shaft **12** in that direction. The processor **536** may control the motor **500** to move in various directions, for example the motor **500** may move the pull wires **138**, **140** simultaneously or in sequence to produce movement in a variety of directions. The processor **536** may be configured to operate the motor **500** to deflect the elongate shaft **12** in at least two planes, among a variety of other directions. The control device used to provide an input to the processor **536** or motor **500** may include buttons, joysticks, touchpads, touch screens, knobs, or motion sensing devices, among other forms of input. An example of a motion sensing device is shown in FIGS. **37** and **38**, in which the control device **588** may be configured to sense motion (e.g., tilt or spatial displacement) of the control device **588** to provide an input to the processor **536** or motor **500**.

[0153] Referring again to FIG. **15**, the system **10** may include an output device that may have various forms. The output device may be configured to provide an output to a user that may indicate a condition of the delivery apparatus or of the patient. The output device may be configured to provide an indicator of a condition of the delivery apparatus or of the patient. For example, as shown in FIG. **15**, an output device may include lights **568** that may illuminate to indicate a condition of the delivery apparatus or of the patient. The lights **568** may illuminate to indicate the delivery apparatus has contacted or approached a surface of the patient's body (a condition of the delivery apparatus), or may illuminate to indicate a certain condition of the patient's body, such as a correct or incorrect pressure being sensed in the patient's body. Other forms of output devices may be utilized, including a haptic device **570**, such as a vibrating actuator, which may indicate the condition of the delivery apparatus or of the patient. An output device may include the display screen of the touch screen **560** shown in FIG. **15**. An output device may include a display screen **584** as shown in FIG. **37**. An output device may include one or more of a display screen, a light, a speaker, or a haptic device, among other forms of output devices. Various forms of output devices may be utilized as desired. An indicator produced on the output device may include one or more of an image, data, a sound, a light, or a haptic signal. The output device may be

configured to provide an indicator based on an output provided by the processor **536**.

[0154] The actuation of the delivery apparatus may include deflection of a portion of the delivery apparatus and performing an operation of the delivery apparatus. The actuation of the delivery apparatus by at least one motor may include a translation of the elongate shaft **12** and may include a translation of a housing at a proximal end of the elongate shaft **12**. Axial translation of the delivery apparatus may be provided. FIG. **17**, for example, illustrates a side perspective view of a delivery apparatus including an elongate shaft **572** and a housing **574**. The delivery apparatus is being passed transfemorally into a patient's body **576**. The elongate shaft **572** may be configured similarly as the elongate shaft **12**. The housing **574** may be configured similarly as the housing forming the handle **14**, however the housing **574** may not comprise a handle for grip by a user. Rather the housing **574** may include a motor or may be configured to move along a motor driven rail **577** or other assembly that actuates axial movement of the delivery apparatus into the patient's body. The axial movement of the delivery apparatus may be controlled by a control device, which may be positioned proximate the housing **574** or may be located remote from the housing **574**. The control device may be configured to perform other control of the delivery apparatus, including deflection of a portion of the delivery apparatus and performing a process of the delivery apparatus, as discussed herein. In this manner, a user need not hold the housing **574** and may proceed with the implant delivery procedure without contacting the delivery apparatus or without being present for the implant delivery procedure. A processor **536** may provide the control of the motor of the motor driven rail **577** and any other motor used to actuate the delivery apparatus, as discussed herein.

[0155] The motor **500** may be configured to actuate the delivery apparatus by selectively moving one or more of the outer sheath assembly **22**, the mid shaft assembly **21**, the inner assembly **18**, the rail assembly **20**, the assembly including the distal pull wires **138**, the assembly including the proximal pull wires **140**, and the nose cone assembly **31**. As discussed with respect to FIG. **10**, the motor **500** may be configured to selectively move such components based on the configuration of the actuation mechanism **506**. As an example of the selective actuation of the motor **500**, an example of depth control is provided. The depth of the elongate shaft **12** of the delivery apparatus may be set by moving the outer sheath assembly **22**, the mid shaft assembly **21**, the inner assembly **18**, and the nose cone assembly **31**, relative to the rail assembly **20**. Such a movement allows the outer sheath assembly **22**, the mid shaft assembly **21**, the inner assembly **18**, and the nose cone assembly **31** to slide relative to the rail assembly **20**, which may be deflected at an angle. The deflection of the rail assembly **20** allows the outer sheath assembly **22**, the mid shaft assembly **21**, the inner assembly **18**, and the nose cone assembly **31** to slide along the rail assembly **20** at this angle and accordingly have depth in a direction towards a mitral or tricuspid annulus or the like, including another annulus or body location. As such, the relative movement of the outer sheath assembly **22**, the mid shaft assembly **21**, the inner assembly **18**, and the nose cone assembly **31** to the rail assembly **20** produces the depth. As shown in FIG. **18**, the motor **500** may be configured to actuate such depth by simultaneously actuating drive rods **518c**, **518d**, and **518e** to move adaptors **516c**, **516d**, and **516e**. The adaptors **516c**, **516d**, and **516e** may move proximally, thus causing the rail assembly **20** and pull wires **138**, **140** to move proximally as well relative to the outer sheath assembly **22**, the mid shaft assembly **21**, the inner assembly **18**, and the nose cone assembly **31** to thus result in depth of the elongate shaft **12**. The motor **500** may thus be configured to simultaneously actuate various portions of the elongate shaft **12** to produce a desired result. The motor **500** may move the assemblies including the pull wires **138**, **140** with the rail assembly **20** to maintain tension in the pull wires **138**, **140**. Although shown as an operation to produce depth, the motor **500** may be configured to produce other combinations of movement. For example, as discussed previously, a deflection of the rail assembly **20** in multiple planes may be provided. The motor **500** may be configured to actuate both the distal pull wire **138** and the proximal pull wire **140** simultaneously or in a sequence to produce the desired movement of the rail assembly **20**.

[0156] The motor **500** accordingly may be configured to move one of the assemblies (outer sheath

assembly **22**, the mid shaft assembly **21**, the inner assembly **18**, the rail assembly **20**, the assembly including the distal pull wires **138**, the assembly including the proximal pull wires **140**, and the nose cone assembly **31**), each extending along a length of the elongate shaft, relative to another one of the assemblies. The assembly may be moved relative to another assembly that is positioned within a lumen of the assembly (e.g., the rail assembly **20** may be positioned within a lumen of the outer sheath assembly **22**). Various assemblies may be moved simultaneously (e.g., rail assembly **20** may be moved simultaneously with the assembly including the distal pull wires **138**, and the assembly including the distal pull wires **138** may be moved simultaneously with the assembly including the proximal pull wires **140**). The processor **536** may be configured to control the motor **500** to provide the movements disclosed herein.

[0157] In one embodiment, the motor **500** may be configured to compensate for movement of a portion of the elongate shaft **12** based on movement of another portion of the elongate shaft **12**. For example, as portions of the elongate shaft **12** are moved, the position of another portion of the elongate shaft **12** may be undesirably moved as well. The motor **500** may be configured to compensate for the undesired movement. FIG. **19**, for example, illustrates a side cross sectional view of a portion of the rail assembly **20**. The distal pull wire **138** has been pulled proximally, causing a distal portion of the rail assembly **20** to deflect in a direction as shown in FIG. **19**. Upon the proximal pull wire **140** then being pulled to deflect a proximal portion of the rail assembly **20**, the distal pull wire **138** may be consequently pulled due to the deflection of the proximal portion of the rail assembly **20**. FIG. **20**, for example, shows a side cross sectional view of the rail assembly **20** viewed at a ninety-degree angle from shown in FIG. **19** (rotated about the axial dimension of the rail assembly **20**). The deflected distal portion of the rail apparatus **20** is facing into the page in FIG. **20**. Upon the proximal pull wire **140** being pulled to deflect the proximal portion of the rail apparatus **20**, the distal portion of the rail apparatus **20** has consequently deflected as represented in dashed lines in FIG. **20**. Under prior methods using mechanical knobs or the like to control the rail apparatus **20**, the shortening of the distal end of the rail apparatus **20** would be corrected by operating multiple mechanical knobs move the distal pull wire **138**. Here, however, the motor **500** may be configured to automatically compensate for movement of one or more of the pull wires **138**, **140** to reduce the shortening of the distal portion of the rail assembly **20**. In embodiments, the motor **500** may be configured to compensate for shortening or elongation of any portion of the elongate shaft **12**, including portions of the outer sheath assembly **22**, the mid shaft assembly **21**, the inner assembly **18**, and the nose cone assembly **31**. For example, the motor **500** may be configured to translate a portion of the elongate shaft **12** other than the rail assembly **20** to compensate for deflection of the rail assembly **20**.

[0158] The motor **500** may be configured to perform the operations discussed with respect to FIGS. **18-20** based on the input from the control device (for example control device **504**) or based on the wiring of the motor **500** or a combination of both. For example, if the control device **504** is utilized to request simultaneous movement of two assemblies of the elongate shaft **12**, then a signal may be provided to the motor **500** to operate the respective drive rods corresponding to those assemblies. If the control device **504** is utilized to request movement of portion of the elongate shaft **12** that requires compensation, then the motor **500** may be wired to automatically perform such compensation. For example, the motor **500** may be wired to compensate for movement of certain assemblies based on movements of other assemblies.

[0159] In certain embodiments, the processor **536** may be utilized to automatically move the assemblies or other portions of the elongate shaft **12** to perform the operations discussed with regards to FIGS. **18-20**. For example, if a request is made to increase the depth of the elongate shaft **12** or deploy the implant **70**, then the processor **536** may be configured to operate a program (which may be stored in memory **534**) to control the motor **500** to move the corresponding assemblies or other portions of the elongate shaft **12**. If a request is made that requires compensation, then the processor **536** may be configured to operate a program (which may be stored in memory **534**) to

control the motor **500** to move the corresponding assemblies or other portions of the elongate shaft **12** to automatically perform such compensation. The processor **536** may be configured to operate the motor to move one of the assemblies to compensate for a motion of another of the assemblies. Particular movements and combinations of movements of the assemblies or other portion of the elongate shaft **12** may be programmed into the memory **534** and operated by the processor **536**. As discussed above, the programmed movements may be based on data “learned” from previous procedures such as, for example, learned from previous procedures performed on patients with similar anatomies and/or other characteristics. The movements may be based on a machine learning algorithm utilizing data from past implantation procedures or from characteristics of the patient. Therefore, procedural steps performed successfully on patients with similar anatomies could be duplicated, thereby increasing the probability of a successful procedure on the current patient. The processor **536** may be configured to automatically operate the motor **500** to actuate a portion of the delivery apparatus in a desired manner.

[0160] The system **10** may include sensors that are configured to sense a condition of the delivery apparatus and may include sensors that are configured to sense a condition of the patient.

[0161] In certain embodiments, a sensor may be utilized to sense a condition of the delivery apparatus. The sensor may comprise a position sensor that may be utilized to determine the movement and/or position of one or more of the assemblies. For example, the position sensor may be configured to sense the amount that the motor **500** has moved the assembly to track the position and movement of the assembly. The motor **500** may be wired to track movement of the various assemblies and perform a desired movement (e.g., simultaneous movement of assemblies, or compensatory movement of one or more assemblies) based on the signal from the position sensor. In one embodiment, the signal from the position sensor may be provided to the processor **536** for the processor **536** to perform a desired movement. The signal from the position sensor may be a feedback signal to the processor **536**. For example, the position sensor may sense that a portion of the elongate shaft **12** is moving in response to movement of another portion of the elongate shaft **12**, and the processor **536** may operate the motor **500** to produce compensatory movement based on this signal. An indicator indicating a position of the delivery apparatus may be provided on an output device, as discussed herein. The indicator may be provided based on the position sensed by the position sensor.

[0162] A sensor may be utilized to sense a condition of the delivery apparatus in the form of a motor torque sensor. The sensor may be utilized to determine the amount of torque exerted by the motor **500**. The motor torque sensor, for example, may be a current draw sensor able to sense the amount of current drawn by the motor **500**. If the amount of torque exceeds a certain amount, the motor **500** may be configured to automatically shut off or reverse its operation or reduce torque. In one embodiment, the signal from the motor torque sensor may be provided to the processor **536** for the processor **536** to perform a desired movement. The signal from the motor torque sensor may be a feedback signal to the processor **536**. For example, the processor **536** may operate the motor **500** to automatically shut off or reverse its operation or reduce torque based on this signal. An indicator indicating a torque of a motor of the delivery apparatus may be provided on an output device, as discussed herein. The indicator may be provided based on the torque sensed by the motor torque sensor.

[0163] Referring to FIG. **21**, sensors configured to sense a condition of the patient may be utilized. Such sensors may be positioned as desired on the delivery apparatus. Sensors configured to sense a condition of the patient may include ambient pressure sensors **578**. Such pressure sensors **578** may be configured to sense a pressure, such as a fluid pressure, within the patient's body. The pressure sensors **578** may be utilized during and following delivery of the implant **70**, to determine whether the deployed implant **70** is operating as desired following implantation, or to generally monitor a condition of the patient before and following implantation. In the embodiment shown in FIG. **21**, a pressure sensor **578** may be positioned on the nose cone **28** and a pressure sensor may be

positioned on the capsule **106** among other locations. With this particular configuration of pressure sensors **578**, one pressure sensor may be positioned in the left ventricle during implantation of the implant **70**, and one pressure sensor may be positioned in the left atrium during implantation. Thus, following implantation, the pressure gradient across the mitral valve can be determined. A signal from the pressure sensors **578** may be provided to an output device (such as output devices **568**, **570**, or other output device) for indication to the user. In one embodiment, the pressure sensed by the pressure sensors **578** may be utilized as feedback to the system **10**, such as the processor **536**, to actuate the delivery apparatus. For example, if an incorrect pressure is read, the processor **536** may actuate the delivery apparatus to redeploy the implant or perform another operation. In other embodiments, other positions of pressure sensors **578** and other pressure readings may be provided.

[0164] In one embodiment, a sensor configured to sense a condition of the delivery apparatus may include sensors configured to sense a spatial relationship between the delivery apparatus and a surface of the patient's body. Such a sensor may be positioned on the delivery apparatus. Such a sensor may include a contact sensor **580**. A contact sensor **580** may comprise a force transducer or load cell, or other form of contact sensor **580** that is configured to sense a force applied to the delivery apparatus. As shown, a contact sensor **580** may be positioned in a variety of positions on the elongate shaft **12**, including on the nose cone **28** or other locations (such as generally on the outer surface of the elongate shaft **12**). A contact sensor **580** may be configured to provide a signal when the elongate shaft **12** contacts a portion of the patient's body. Such a signal may indicate the possibility of damage to the patient's body due to the elongate shaft **12**. A signal from a contact sensor **580** may be provided to an output device (such as output devices **568**, **570**, or other output device) for indication to the user. In one embodiment, the contact sensed by the contact sensor **580** may be utilized as feedback to the system **10**, such as the processor **536**, to actuate the delivery apparatus. For example, if contact is sensed with a surface, then the processor **536** may actuate the delivery apparatus to move away from the surface or stop operation of the motor **500**. In other embodiments, other positions of contact sensors **580** and other contact sensors may be provided.

[0165] In one embodiment, a sensor configured to sense a condition of the delivery apparatus may include a proximity sensor **582**. The proximity sensor **582** may be configured to sense a spatial relationship between the delivery apparatus and a surface of the patient's body. Such a sensor may be positioned on the delivery apparatus. A proximity sensor **582** may comprise a device for sensing a distance to a portion of the patient's body, including use of ultrasound, or echo signals, or visual identification. As shown, a proximity sensor **582** may be positioned in a variety of positions on the elongate shaft **12**, including on the nose cone **28** or other locations (such as generally on the outer surface of the elongate shaft **12**). The proximity sensor **582** may be configured to provide a signal when the elongate shaft **12** approaches a portion of the patient's body and may provide such a signal to an output device (such as output devices **568**, **570**, or other output device) for indication to the user. In one embodiment, the proximity sensed by the proximity sensor **582** may be utilized as feedback to the system **10**, such as the processor **536**, to actuate the delivery apparatus. For example, if proximity to a surface (e.g., an inner wall of blood vessel) is sensed, the processor **536** may actuate the delivery apparatus to move away from the surface or stop operation of the motor **500**. As such, the delivery system could be advanced through the patient's vasculature without damaging an inner wall of a blood vessel. This "smart catheter" technology could provide a significant improvement over current "blind catheters." For example, this technology could reduce or eliminate the possibility of vascular dissection, which is a significant and life-threatening risk with current delivery systems. Although embodiments have been described for sake of explanation, it will be understood that other positions of proximity sensors **582** and other proximity readings may be provided.

[0166] FIGS. **22-24** illustrate an embodiment of a sensor configured to sense a condition of the patient. The sensor comprises a flow sensor that may sense a fluid flow (e.g., blood flow) within the patient's body. A plurality of sensors **583a-l** (as marked in FIG. **23**) may be positioned on the

delivery apparatus forming a spaced array of sensors **583a-l**. The sensors **583a-l** may be configured to sense a local fluid flow, such that the sensors **583a-l** may sense a fluid flow in a local area in the body that is different from the fluid flow sensed by other sensors **583a-l**. FIG. 22 illustrates a perspective view of the distal end of the elongate shaft **12**, with sensors **583a-c** visible on the capsule **106**. FIG. 23 illustrates a cross sectional view of the capsule **106** showing the spaced array of sensors **583a-l**. The sensors **583a-l** may be positioned on the delivery apparatus to sense fluid flow at a location proximate the deployment location for the implant **70**. Such a location may comprise the capsule **106** or another portion of the delivery apparatus.

[0167] FIG. 24 illustrates an exemplary operation of the sensors **583a-l**. The implant **70** may be deployed in a native mitral or tricuspid valve, with one distal anchor **80a** capturing a leaflet **1108** and another distal anchor **80b** failing to capture a leaflet **1108**. The sensors **583k**, **583l** may sense a flow of blood by the mis-captured leaflet **1108** and may provide a signal accordingly. The sensors **583a-l** may be configured to sense a differential flow between the sensors **583f**, **583g** proximate the captured leaflet **1108** and the sensors **583k**, **583l** proximate the mis-captured leaflet **1108**. The flow sensors **583a-l** may be configured to provide a signal when a flow is sensed and may provide such a signal to an output device (such as output devices **568**, **570**, or other output device) for indication to the user. In one embodiment, the flow sensed by the flow sensors **583a-l** may be utilized as feedback to the system **10**, such as the processor **536**, to actuate the delivery apparatus. For example, if flow is sensed indicated a mis-capture of a leaflet, then the processor **536** may actuate the delivery apparatus to redeploy the implant **70** or perform another operation. In other embodiments, other positions of flow sensors **583a-l** and other flow readings may be provided.

[0168] The sensors that are configured to sense the condition of the delivery apparatus and the sensors that are configured to sense a condition of the patient may be coupled to the delivery apparatus. In certain embodiments, however, the sensors that are configured to sense the condition of the delivery apparatus and the sensors that are configured to sense a condition of the patient may not be coupled to the delivery apparatus and may be external to the patient's body.

[0169] The signals from the sensors that are configured to sense the condition of the delivery apparatus and the sensors that are configured to sense a condition of the patient, may be utilized in a variety of manners. In one embodiment, the signals may be provided as indicators on an output device (such as output devices **568**, **570**, or other output device) for indication to the user. For example, a condition of the delivery apparatus may be indicated to a user in a variety of forms, for example, an output device may include one or more of a display screen, a light, a speaker, or a haptic device, among other forms of output devices. An indicator produced on the output device may include one or more of an image, data, a sound, a light, or a haptic signal. The user may be able to act accordingly based on the indicator. For example, if an indicator indicates that the delivery apparatus has contacted a portion of the patient's body, then the user may act accordingly to move the delivery apparatus away from the body. A condition of the patient's body may similarly be indicated to a user in a variety of forms.

[0170] In embodiments, the signals from the sensors that are configured to sense the condition of the delivery apparatus and the sensors that are configured to sense a condition of the patient may be provided to the processor **536**. The processor **536** may provide a variety of outputs based on the one or more of a condition of the patient's body or a condition of the delivery apparatus sensed by the one or more sensors. One such form of output includes a log of data for an implantation procedure with the delivery apparatus. Such a log of data may be stored in the memory **534**. The data may be stored for later retrieval by a user for analysis or may record a log of actions taken by the delivery apparatus. For example, the position sensor signals may be logged to record the movements of the delivery apparatus, among other forms of sensors signals.

[0171] The processor **536** may provide an output to an output device based on the condition of the patient's body or a condition of the delivery apparatus sensed by the one or more sensors. The output may result in an indicator on an output device (such as output devices **568**, **570**, or other

output device) for indication to the user. For example, a condition of the delivery apparatus may be indicated to a user in a variety of forms, for example, an output device may include one or more of a display screen, a light, a speaker, or a haptic device, among other forms of output devices. The processor **536** may process the signals to produce a desired indicator to a user. For example, the sensors **583a-l** may sense a flow of blood during deployment of the implant **70**, and the processor **536** may process these signals to provide an indicator to a user that leaflet mis-capture has occurred.

[0172] The processor **536** may provide an output that comprises a control of the motor **500** based on the condition of the patient's body or a condition of the delivery apparatus sensed by the one or more sensors. The processor **536** may be configured to operate the motor **500** to actuate the delivery apparatus based on a signal from the sensors. The signal from the sensors may comprise feedback signals that are input to the processor **536** for the processor to control operation of the motor **500**. For example, a signal from a contact sensor **580** or a proximity sensor **582** may be provided to the processor **536** as feedback that the delivery apparatus has contacted or is proximate a surface of the patient's body. The processor **536** accordingly may provide an output that operates the motor **500** to avoid or retract from the surface of the patient's body. A signal from the flow sensors **583a-l** may cause the processor **536** to provide an output to the motor **500** to redeploy the implant **70** or move the portion of the delivery apparatus to recapture the leaflet **1108**. A signal from a position sensor may provide feedback to the processor **536** regarding whether the delivery apparatus is performing the correct movements, and the processor **536** may operate the motor **500** to perform corrective movements if desired (e.g., deflect the elongate shaft **12** if needed). The processor **536** may be programmed to automatically respond and produce outputs based on the condition of the patient's body or a condition of the delivery apparatus sensed by the one or more sensors. The programming for the processor **536** may be stored in the memory **534** and operated by the processor **536**.

[0173] A method of utilizing the system **10** for delivering an implant **70** is represented in FIGS. **25-30**. The method may utilize any of the systems or devices disclosed herein. The delivery system **10** can be used in a method for percutaneous delivery of a replacement mitral valve to treat patients with moderate to severe mitral regurgitation. However, it will be understood that the delivery systems described herein can be used as part of other methods as well, such as implants for repair of valves and delivery of implants to other heart valves and delivery of other implants.

[0174] As shown in FIG. **25**, in one embodiment the method may include extending a delivery apparatus within a portion of the patient's body to deliver an implant to a body location. The delivery system **10** can be placed in the ipsilateral femoral vein **1074** and advanced toward the right atrium **1076**. A transseptal puncture using known techniques can then be performed to obtain access to the left atrium **1078**. The delivery system **10** can then be advanced in to the left atrium **1078** and then to the left ventricle **1080** passing through the atrial septum. FIG. **25** shows the delivery system **10** extending from the ipsilateral femoral vein **1074** to the left atrium **1078**. In embodiments of the disclosure, a guide wire is not necessary to position the delivery system **10** in the proper position, although in other embodiments, one or more guide wires may be used.

[0175] Accordingly, it can be advantageous for a user to be able to steer the delivery system **10** through the complex areas of the heart in order to position a replacement mitral valve in line with the native mitral valve. This task can be performed with or without the use of a guide wire with the above disclosed system. The distal end of the delivery system can be advanced into the left atrium **1078**. The motor **500** may then be operated to actuate the rail assembly **20** to target the distal end of the delivery system **10** to the appropriate area. The motor **500** may be operated by a processor **536** as discussed herein. A user can then continue to pass the bent delivery system **10** through the transseptal puncture and into the left atrium **1078**. The motor **500** may then be operated to create an even greater bend in the rail assembly **20**. In the fully bent configuration, a user can then place the replacement mitral valve in the proper location.

[0176] The rail assembly **20** can be particularly advantageous for entering into the native mitral valve. As discussed above, the rail assembly **20** can form two bends, both of which can be located in the left atrium **1078**. The bends in the rail assembly **20** can position the implant **70**, located in the implant retention area **16**, so that it is coaxial with the native mitral valve. Once the implant **70** is coaxial, the outer sheath assembly **22**, mid shaft assembly **21**, inner assembly **18**, and nose cone assembly **31** can together be advanced (e.g., using the motor **500**) distally relative to the rail assembly **20**. These assemblies advance straight off of the rail assembly **20**, thus advancing them coaxial with the native mitral valve until the implant **70** is to be released while maintaining the implant **70** in the compressed configuration, as discussed below. Thus, the rail assembly **20** provides the ability for a user to lock the angular position in place, so that the user then has to just longitudinally advance the other assemblies over the rail assembly **20** while not needed to make any angular changes, greatly simplifying the procedure. The rail assembly **20** acts as an independent steering assembly, where all the assembly does is provide steerability and no further implant release functionality. Further, the construction of the rail assembly **20** as described above is sufficiently rigid so that when the rail assembly is actuated to its bent shape, movement of the other components, e.g., the outer sheath assembly **22**, mid shaft assembly **21**, inner assembly **18**, and/or nose cone assembly **31**, the rail assembly **20** maintains its shape. Thus, the rail assembly **20** can remain in the desired bent position during the sliding of the other assemblies relative to the rail assembly **20**, and the rail assembly **20** can help direct the other assemblies to the final position. The proximal/distal translation of the other assemblies over the rail assembly **20** allows for ventricular-atrial motion. In addition, once the distal anchors **80** of the implant **70** have been released in the left ventricle **1080**, but prior to full release, the other assemblies can be proximally retracted over the rail assembly **20** to capture any leaflets or chordae.

[0177] Reference is now made to FIG. **26** which illustrates a schematic representation of a portion of an embodiment of a replacement heart valve (implant **70**) positioned within a native mitral valve of a heart **83**. A portion of the native mitral valve is shown schematically and represents typical anatomy, including a left atrium **1078** positioned above an annulus **1106** and a left ventricle **1080** positioned below the annulus **1106**. The left atrium **1078** and left ventricle **1080** communicate with one another through a mitral annulus **1106**. Also shown schematically in FIG. **26** is a native mitral leaflet **1108** having chordae tendineae **1110** that connect a downstream end of the mitral leaflet **1108** to the papillary muscle of the left ventricle **1080**. The portion of the implant **70** disposed upstream of the annulus **1106** (toward the left atrium **1078**) can be referred to as being positioned supra-annularly. The portion generally within the annulus **1106** is referred to as positioned intra-annularly. The portion downstream of the annulus **1106** is referred to as being positioned sub-annularly (toward the left ventricle **1080**).

[0178] As shown in FIG. **26**, the replacement heart valve (e.g., implant **70**) can be positioned so that the mitral annulus **1106** is located between the distal anchors **80** and the proximal anchors **82**. In some situations, the implant **70** can be positioned such that ends or tips of the distal anchors **80** contact the annulus **1106** as shown, for example, in FIG. **26**. In some situations, the implant **70** can be positioned such that ends or tips of the distal anchors **80** do not contact the annulus **1106**. In some situations, the implant **70** can be positioned such that the distal anchors **80** do not extend around the leaflet **1108**.

[0179] As illustrated in FIG. **26**, the replacement heart valve implant **70** can be positioned so that the ends or tips of the distal anchors **80** are on a ventricular side of the mitral annulus **1106** and the ends or tips of the proximal anchors **82** are on an atrial side of the mitral annulus **1106**. The distal anchors **80** can be positioned such that the ends or tips of the distal anchors **80** are on a ventricular side of the native leaflets beyond a location where chordae tendineae **1110** connect to free ends of the native leaflets. The distal anchors **80** may extend between at least some of the chordae tendineae **1110** and, in some situations such as those shown in FIG. **26**, can contact or engage a ventricular side of the annulus **1106**. It is also contemplated that in some situations, the distal

anchors **80** may not contact the annulus **1106**, though the distal anchors **80** may still contact the native leaflet **1108**. In some situations, the distal anchors **80** can contact tissue of the left ventricle **1080** beyond the annulus **1106** and/or a ventricular side of the leaflets.

[0180] During delivery, the distal anchors **80** (along with the frame) can be moved toward the ventricular side of the annulus **1106**, such as by translating the other assemblies (e.g., outer sheath assembly **22**, mid shaft assembly **21**, inner assembly **18**, and nose cone assembly **31**) proximally with respect to the rail assembly **20**, with the distal anchors **80** extending between at least some of the chordae tendineae **1110** to provide tension on the chordae tendineae **1110**. The degree of tension provided on the chordae tendineae **1110** can differ. For example, little to no tension may be present in the chordae tendineae **1110** where the leaflet **1108** is shorter than or similar in size to the distal anchors **80**. A greater degree of tension may be present in the chordae tendineae **1110** where the leaflet **1108** is longer than the distal anchors **80** and, as such, takes on a compacted form and is pulled proximally. An even greater degree of tension may be present in the chordae tendineae **1110** where the leaflets **1108** are even longer relative to the distal anchors **80**. The leaflet **1108** can be sufficiently long such that the distal anchors **80** do not contact the annulus **1106**.

[0181] The proximal anchors **82**, if present, can be positioned such that the ends or tips of the proximal anchors **82** are adjacent the atrial side of the annulus **1106** and/or tissue of the left atrium **1078** beyond the annulus **1106**. In some situations, some or all of the proximal anchors **82** may only occasionally contact or engage atrial side of the annulus **1106** and/or tissue of the left atrium **1078** beyond the annulus **1106**. For example, as illustrated in FIG. 26, the proximal anchors **82** may be spaced from the atrial side of the annulus **1106** and/or tissue of the left atrium **1078** beyond the annulus **1106**. The proximal anchors **82** could provide axial stability for the implant **70**. It is also contemplated that some or all of the proximal anchors **82** may contact the atrial side of the annulus **1106** and/or tissue of the left atrium **1078** beyond the annulus **1106**. FIG. 27 illustrates the implant **70** implanted in the heart. Although the illustrated replacement heart valve includes both proximal and distal anchors, it will be appreciated that proximal and distal anchors are not required in all cases. For example, a replacement heart valve with only distal anchors may be capable of securely maintaining the replacement heart valve in the annulus. This is because the largest forces on the replacement heart valve are directed toward the left atrium during systole. As such, the distal anchors are most important for anchoring the replacement heart valve in the annulus and preventing migration.

[0182] FIGS. 28-30 illustrate the release mechanism of the delivery system **10**. During the initial insertion of the implant **70** and the delivery system **10** into the body, the implant **70** can be located within the system **10**, similar to as shown in FIG. 2A. The distal end **303** of the implant **70**, and specifically the distal anchors **80**, are restrained within the capsule **106** of the outer sheath assembly **22**, thus preventing expansion of the implant **70**. Similar to what is shown in FIG. 2A, the distal anchors **80** can extend distally when positioned in the capsule. The proximal end **301** of the implant **70** is restrained within the capsule **106** and within a portion of the inner retention member **40** and thus is generally constrained between the capsule **106** and the inner retention member **40**.

[0183] The system **10** can first be positioned to a particular location in a patient's body, such as at the native mitral valve, through the use of the steering mechanisms discussed herein or other techniques.

[0184] Once the implant **70** is loaded into the delivery system **10**, a user can thread a guide wire into a patient to the desired location. The guide wire passes through the lumen of the nose cone assembly **31**, and thus the delivery system **10** can be generally advanced through the patient's body following the guide wire. The delivery system **10** can be advanced by the user manually moving the handle **14** in an axial direction. In some embodiments, the delivery system **10** can be placed into a stand while operating the handle **14** controls. In one embodiment, the delivery system may be axially advanced with a motor as shown in FIG. 17.

[0185] Once generally in the heart, the user can begin the steering operation of the rail assembly **20**

using motor **500**. The motor **500** can provide flexing/bending of the rail assembly **20** (either on the distal end or the proximal end), thus bending the distal end of the delivery system **10** in one, two, or more locations into the desired configuration. As discussed above, the user can provide multiple bends in the rail assembly **20** to direct the delivery system **10** towards the mitral valve. In particular, the bends of the rail assembly **20** can direct a distal end of the delivery system **10**, and thus the capsule **106**, along the center axis passing through the native mitral valve. Thus, when the outer sheath assembly **22**, mid shaft assembly **21**, inner assembly **18**, and nose cone assembly **31** are together advanced over the rail assembly **20** with the compressed implant **70**, the capsule **106** proceeds directly in line with the axis for proper release of the implant **70**.

[0186] In a next step, the user can adjust the depth of the elongate shaft **12**. The motor **500** may be utilized for such an operation. As discussed, adjusting the depth advances the inner shaft assembly **18**, mid shaft assembly **21**, outer sheath assembly **22**, and nose cone assembly **31** over/through the rail assembly **20** while the implant **70** remains in the compressed configuration within the implant retention area **16**. Due to the rigidity of, for example, either the inner shaft assembly **18**, the mid shaft assembly **21**, and/or the outer sheath assembly **22**, these assemblies proceed straight forward in the direction aligned by the rail assembly **20**.

[0187] Once in the release position, the motor **500** can operate to individually translate the outer sheath assembly **22** (and thus the capsule **106**) with respect to the other assemblies, such as the inner assembly **18**, in a proximal direction towards the handle **14** as shown in FIG. **28**. By doing so, the distal end **303** of implant **70** is uncovered in the body, allowing for the beginning of expansion. At this point, the distal anchors **80** can flip proximally and the distal end **303** begins to expand radially outwardly. For example, if the system **10** has been delivered to a native mitral valve location through a transseptal approach, the nose cone is positioned in the left ventricle, preferably aligning the implant **70** such that it is generally perpendicular to the plane of the mitral annulus. The distal anchors **80** expand radially outwardly within the left ventricle. The distal anchors **80** can be located above the papillary heads, but below the mitral annulus and mitral leaflets. In some embodiments, the distal anchors **80** may contact and/or extend between the chordae in the left ventricle, as well as contact the leaflets, as they expand radially. In some embodiments, the distal anchors **80** may not contact and/or extend between the chordae or contact the leaflets. Depending on the position of the implant **70**, the distal ends of the distal anchors **80** may be at or below where the chordae connect to the free edge of the native leaflets.

[0188] As shown in the illustrated embodiment, the distal end **303** of the implant **70** is expanded outwardly. It should be noted that the proximal end **301** of the implant **70** can remain covered by the outer retention ring during this step such that the proximal end **301** remains in a radially compacted state. At this time, the system **10** may be withdrawn proximally so that the distal anchors **80** capture and engage the leaflets of the mitral valve or may be moved proximally to reposition the implant **70**. For example, the assemblies may be proximally moved relative to the rail assembly **20**. In some embodiments, the distal anchors **80** may capture the native leaflet and be between the chordae without any further movement of the system **10** after withdrawing the outer sheath assembly **22**.

[0189] During this step, the system **10** may be moved proximally or distally to cause the distal or ventricular anchors **80** to properly capture the native mitral valve leaflets. This can be done by the motor **500** moving the outer sheath assembly **22**, mid shaft assembly **21**, inner assembly **18**, and nose cone assembly **31** with respect to the rail assembly **20**. In particular, the tips of the ventricular anchors **80** may be moved proximally to engage a ventricular side of the native annulus, so that the native leaflets are positioned between the anchors **80** and the body of the implant **70**. When the implant **70** is in its final position, there may or may not be tension on the chordae, though the distal anchors **80** can be located between at least some of the chordae.

[0190] The proximal end **301** of the implant **70** will remain in the outer retention ring **42** after retraction of the capsule **106**. As shown in FIG. **29**, once the distal end **303** of the implant **70** is

fully expanded (or as fully expanded as possible at this point), the outer retention ring **42** can be individually withdrawn proximally with respect to the other assemblies, in particular relative to the inner assembly **18**, to expose the inner retention member **40**, thus beginning the expansion of the proximal end **301** of the implant **70**. For example, in a mitral valve replacement procedure, after the distal or ventricular anchors **80** are positioned between at least some of the chordae tendineae and/or engage the native mitral valve annulus, the proximal end **301** of the implant **70** may be expanded within the left atrium.

[0191] The outer retention ring **42** can be moved proximally such that the proximal end **301** of the implant **70** can radially expand to its fully expanded configuration as shown in FIG. **30**. After expansion and release of the implant **70**, the inner assembly **18**, nose cone assembly **31**, mid shaft assembly **21**, and outer sheath assembly **22** can be simultaneously withdrawn proximally along or relative to the rail assembly **20** back to their original position via the motor **500**. In some embodiments, they are not withdrawn relative to the rail assembly **20** and remain in the extended position. Further, the nose cone **28** can be withdrawn through the center of the expanded implant **70** and into the outer sheath assembly **22** via the motor **500**. The system **10** can then be removed from the patient.

[0192] The methods disclosed herein may utilize the systems and devices disclosed herein. For example, the motor **500** may deflect a portion of the delivery apparatus or deploy the implant to the body location. The operation of the motor **500** may be operated by a processor **536**. A user may provide input to the processor **536** with a control device **504**.

[0193] Further the sensors discussed herein may be utilized in certain embodiments. The delivery apparatus may include one or more sensors coupled to the delivery apparatus and configured to sense one or more of a condition of the patient's body or a condition of the delivery apparatus. The processor **536** may be configured to provide an output based on the one or more of a condition of the patient's body or a condition of the delivery apparatus sensed by the one or more sensors. For example, the processor may cause at least a portion of the delivery apparatus to avoid or retract from a surface of the patient's body based on a condition of the delivery apparatus.

[0194] In embodiments, the delivery system **10** can be used in a method for percutaneous delivery of a replacement tricuspid valve that may be used to treat patients with moderate to severe tricuspid regurgitation. Such a method may utilize any of the systems or devices disclosed herein. Referring to FIG. **31**, for example, the delivery apparatus may be extended within a portion of a patient's body to deliver an implant to a body location. The portion of the patient's body may be the right atrium **1076** and the body location for delivering the implant may be the native tricuspid heart valve **1082**. The delivery apparatus may be extended within a portion of the patient's body in a similar manner as discussed in regard to FIG. **25**, for example, the delivery apparatus can be placed in the ipsilateral femoral vein **1074** (marked in FIG. **25**) and advanced towards the right atrium **1076**. Other entry methods may be utilized as desired.

[0195] The delivery apparatus may be extended within the inferior vena cava **1084** into the right atrium **1076**. As discussed with respect to the mitral valve delivery represented in FIG. **25**, one or more guide wires may or may not be utilized as desired. One or more motors, which may be operated by a processor **536** as discussed herein, may be utilized to extend the delivery apparatus into the right atrium **1076**.

[0196] The delivery apparatus may be steered through the complex areas of the heart in order to position a replacement tricuspid valve in line with the native tricuspid valve. The motor **500** may be operated to actuate the rail assembly **20** to target the distal end of the delivery apparatus to the appropriate area. For example, the motor **500** may be utilized to steer the rail assembly **20** to the desired orientation relative to the tricuspid heart valve **1082**. The motor **500** may be operated by a processor **536** as discussed herein. The rail assembly **20** may form one or more bends such that the distal end of the delivery apparatus is oriented coaxial with the native tricuspid heart valve **1082**.

[0197] FIG. **32**, for example, shows that the delivery apparatus has been deflected within the right

atrium **1076** towards the native tricuspid heart valve **1082**. One or more bends may be formed within the right atrium **1076** and/or the inferior vena cava **1084**. Once the implant **70** is positioned coaxial with the native tricuspid heart valve **1082**, the outer sheath assembly **22**, mid shaft assembly **21**, inner assembly **18**, and nose cone assembly **31** can together be advanced (e.g., using the motor **500**) distally relative to the rail assembly **20** towards the right ventricle **1086**. The depth of the elongate shaft **12** may be varied by the operation of the motor **500** disclosed herein, which may be operated by a processor **536**. The proximal/distal translation of the other assemblies over the rail assembly **20** allows for ventricular-atrial motion.

[0198] The depth of the elongate shaft **12** may be varied until the capsule **106** is positioned in the desired location relative to the native tricuspid heart valve **1082**. The distal end **303** of the implant **70**, and specifically the distal anchors **80**, may be restrained within the capsule **106** of the outer sheath assembly **22**, thus preventing expansion of the implant **70**. Similar to what is shown in FIG. 2A, the distal anchors **80** can extend distally when positioned in the capsule. The proximal end **301** of the implant **70** is restrained within the capsule **106** and within a portion of the inner retention member **40** and thus is generally constrained between the capsule **106** and the inner retention member **40**. The implant **70** may then be deployed to the native tricuspid heart valve **1082** in a similar manner as discussed in regard to FIGS. 28-30. FIG. 33, for example, illustrates the implant **70** deployed to the native tricuspid heart valve **1082**. The distal anchors of the implant **70** extend over the leaflets **1088** of the tricuspid heart valve **1082**, in a similar manner as the distal anchors extend over the leaflets **1108** of the native mitral heart valve as shown in FIG. 26. The delivery apparatus may then be withdrawn from the patient's right atrium **1076**.

[0199] The procedures disclosed with respect to FIGS. 31-33 may utilize the systems and devices disclosed herein. For example, the motor **500** may deflect a portion of the delivery apparatus or deploy the implant to the body location. The operation of the motor **500** may be operated by a processor **536**. A user may provide input to the processor **536** with a control device **504**. The system **10** can be positioned through the use of the steering mechanisms discussed herein or other techniques. The delivery system **10** can be advanced by the user manually moving the handle **14** in an axial direction. In some embodiments, the delivery system **10** can be placed into a stand while operating the handle **14** controls. In one embodiment, the delivery system may be axially advanced with a motor as shown in FIG. 17.

[0200] The delivery apparatus may be utilized in the form shown in FIG. 1, or other forms of delivery apparatuses may be utilized, for example, delivery apparatuses configured for delivery of an implant to the native tricuspid valve.

[0201] Further, the sensors discussed herein may be utilized in certain embodiments. The delivery apparatus may include one or more sensors coupled to the delivery apparatus and configured to sense one or more of a condition of the patient's body or a condition of the delivery apparatus. The processor **536** may be configured to provide an output based on the one or more of a condition of the patient's body or a condition of the delivery apparatus sensed by the one or more sensors. For example, the processor **536** may cause at least a portion of the delivery apparatus to avoid or retract from a surface of the patient's body based on a condition of the delivery apparatus. FIGS. 31 and 32, for example, illustrate sensor signals **802** produced by proximity sensors **582** (as marked in FIG. 21) that may be utilized to navigate within the patient's body. The processor may navigate the delivery apparatus to the desired orientation relative to the native tricuspid valve for deployment of the implant **70**. The processor may actuate the delivery apparatus to align coaxial with the native tricuspid valve and deliver the implant **70** to the native tricuspid valve.

[0202] In embodiments, the delivery system **10** can be used in a method for percutaneous delivery of a replacement aortic valve. Such a method may utilize any of the systems or devices disclosed herein. Further, such a method may utilize a delivery system including a delivery apparatus that is configured for delivery of a prosthetic replacement aortic valve. Such a delivery apparatus may include similar components as the apparatus shown in FIG. 1, for example, the delivery apparatus

may include an elongate shaft **804** including a capsule **806** surrounding an implant retention area for retaining the implant, and may include a nose cone **808** at a distal end of the elongate shaft **804**. The delivery apparatus may include a housing that may be in the form of a handle at the proximal end of the elongate shaft **804**. The delivery apparatus may include a plurality of assemblies, as disclosed with respect to the embodiment of FIG. **1**. The assemblies may be controlled by a motor and may be controlled by a controller including a processor as disclosed herein. As such, the actuation of the delivery apparatus may be controlled by a motor and a processor. The delivery apparatus may be configured to extend around the curve of a patient's aortic arch **1090** and deliver an implant to the aortic valve **1092**. For example, a steering mechanism may be utilized that is configured to steer around the curve of the patient's aortic arch **1090**. The delivery apparatus may further include the sensors and other components disclosed with respect to the apparatus shown in FIG. **1**, as desired.

[0203] Referring to FIG. **34**, for example, the delivery apparatus may be extended within a portion of a patient's body to deliver an implant to a body location. The portion of the patient's body may be the aortic arch **1090** and the body location for delivering the implant may be the native aortic heart valve **1092**. The delivery apparatus may be extended within a portion of the patient's body percutaneously, for example, the delivery apparatus can be placed in a femoral vein and advanced towards the aortic arch **1090**. Other entry methods may be utilized as desired.

[0204] The delivery apparatus may be passed through the aortic arch **1090** and advanced towards the native aortic heart valve **1092**. One or more guide wires may or may not be utilized as desired. One or more motors, which may be operated by a processor **536** as discussed herein, may be utilized to extend the delivery apparatus through the aortic arch **1090**.

[0205] The motor **500** may be operated to actuate the rail assembly **20**, or another steering mechanism of the delivery apparatus, to target the distal end of the delivery apparatus to the appropriate area. For example, the motor **500** may be utilized to steer the rail assembly **20** to the desired orientation relative to the native aortic heart valve **1092**. The motor **500** may be operated by a processor **536** as discussed herein. The rail assembly **20**, or another steering mechanism of the delivery apparatus, for example one or more pull wires, may form one or more bends such that the distal end of the delivery apparatus is oriented coaxial with the native aortic heart valve **1092**.

[0206] FIG. **35**, for example, shows that the delivery apparatus has been deflected within the aortic arch **1090** towards the native aortic heart valve **1092**. A bend may be formed within the aortic arch **1090**. Once the implant is positioned coaxial with the native aortic heart valve **1092**, the capsule **806** may be further advanced to the desired depth relative to the native aortic heart valve **1092**.

[0207] The depth of the capsule **806** may be varied until the capsule **806** is positioned in the desired location relative to the native aortic heart valve **1092**. The implant may be restrained within the capsule **806** of an outer sheath assembly, thus preventing expansion of the implant. The implant may then be deployed by the outer sheath of the capsule **806** being retracted or otherwise moved relative to the implant retention area. The implant may have a variety of forms, including the form of the implant shown in FIG. **3B**. In embodiments, the implant may not be covered by a capsule. For example, the implant may be a balloon expandable or mechanically expandable implant that is not restrained within a capsule, or other form of implant. The implant may be deployed at the desired location.

[0208] FIG. **36** illustrates the implant **810** deployed to the native aortic heart valve **1092**. The delivery apparatus may be withdrawn from the patient's aortic arch **1090**.

[0209] The method disclosed with respect to FIGS. **34** through **36** may utilize the systems and devices disclosed herein. For example, the motor **500** may deflect a portion of the delivery apparatus or deploy the implant to the body location. The operation of the motor **500** may be operated by a processor **536**. A user may provide input to the processor **536** with a control device **504**. The system **10** can be positioned through the use of the steering mechanisms discussed herein or other techniques. The delivery system can be advanced by the user manually moving a handle in

an axial direction. In some embodiments, the delivery system can be placed into a stand while operating the handle controls. In one embodiment, the delivery system may be axially advanced with a motor as shown in FIG. 17.

[0210] Further the sensors discussed herein may be utilized in certain embodiments. The delivery apparatus may include one or more sensors coupled to the delivery apparatus and configured to sense one or more of a condition of the patient's body or a condition of the delivery apparatus. The processor **536** may be configured to provide an output based on the one or more of a condition of the patient's body or a condition of the delivery apparatus sensed by the one or more sensors. For example, the processor may cause at least a portion of the delivery apparatus to avoid or retract from a surface of the patient's body based on a condition of the delivery apparatus. FIGS. **34** and **35**, for example, illustrate sensor signals **812** (e.g., echo signals) produced by proximity sensors **582** (as marked in FIG. **21**) that may be utilized to navigate within the patient's body. A spatial relationship between the delivery apparatus and the surface of the aortic arch may be sensed with sensors. The sensor signals **812** are shown reflecting from the surface of the aortic arch **1090**. The processor may actuate the delivery apparatus to avoid or retract from a surface of the patient's body by deflecting within the aortic arch based on the spatial relationship, and navigate around the aortic arch to the desired orientation relative to the native aortic heart valve **1092** for deployment of the implant **810**. By continually sensing the position of the delivery apparatus relative to the aortic arch and modifying the deflection accordingly, it is thereby possible to navigate through the aortic arch with little or no contact with the vessel wall. As noted above, the sensor feedback from the delivery apparatus may be supplemented by imaging feedback such as from a fluoroscope to provide additional detail. The use of sensor feedback during advancement through a vessel, such as an aortic arch, provides an important improvement because it reduces the likelihood of vascular dissection and/or causing a particle to break free from the vessel wall. In another advantage, the replacement valve may be precisely positioned relative to the native aortic heart valve, which thereby facilitates crossing the native aortic leaflets and accurately deploying the replacement valve within the diseased native valve.

[0211] In other embodiments, other methods of delivering the implant to the native aortic heart valve may be utilized, for example, a transapical, transseptal, or other method may be utilized.

[0212] Other locations for valve implant may include the pulmonary valve, and other valves of a patient's body. Other forms of implants may be delivered to other body locations as desired.

[0213] In embodiments disclosed herein, the implant can be delivered under fluoroscopy so that a user can view certain reference points for proper positioning of the implant. Further, echocardiography can be used for proper positioning of the implant.

[0214] In one embodiment, the proximity sensor **582** may be configured to provide a model of the interior of the patient's body and the spatial relationship of the elongate shaft **12** from surfaces of the patient's body. Such a model may be provided on output devices **584**, **586** shown in FIGS. **37** and **38** as display screens (on a monitor and on a virtual reality or augmented reality display). Such a model may also be provided by other sensors positioned external to the patient's body if desired. Such a model may be a two-dimensional map or three-dimensional map of the patient's body for view by a user, and for use by the processor **536** as feedback to navigate through the patient's body and deliver an implant **70** to the desired location. Such a configuration may be utilized with any embodiment disclosed herein, including delivery of an implant to a native aortic valve.

[0215] FIG. **37** illustrates an embodiment in which operation of the delivery apparatus may occur remotely by a user. The user may utilize a control device **588** such as a joystick or other form of control device to control movement of the delivery apparatus and elongate shaft **12**. The control device **588** may be configured to sense motion of the control device to control the delivery apparatus. The user may view the position of the elongate shaft **12** on an output device **584** in the form of a display screen. The position may be provided in a variety of manners, including external sensing of the position via sensors using fluoroscopy or echocardiography. The position may also

be provided via an image produced by signals from proximity sensors of the elongate shaft **12**. The proximity sensors may be configured to produce an image of the spatial relationship between the elongate shaft **12** and the surfaces of the patient's body. A configuration including a motor for axial movement of the elongate shaft **12**, as shown in FIG. **17**, may be utilized as well for remote control of the procedure. Such a configuration may be utilized with any embodiment disclosed herein, including delivery of an implant to a native aortic valve.

[0216] FIG. **38** illustrates an embodiment in which the output device **586** is in the form of a display screen on a virtual reality or augmented reality display. The display may include a helmet (or other headset that allows for enhanced visualization) for wear by the user, wherein the user is able to move his or her head to alter the perspective of the view provided by the display screen. Similar to the embodiment discussed with respect to FIG. **37**, the position of the elongate shaft **12** and portions of the patient's heart seen in the output device **586** may be provided in a variety of manners, including external sensing of the position via fluoroscopy or echocardiography. The position may also be provided via an image produced by signals from proximity sensors of the elongate shaft **12**. The proximity sensors may be configured to produce an image of the spatial relationship between the elongate shaft **12** and the surfaces of the patient's body. A configuration including a motor for axial movement of the elongate shaft **12**, as shown in FIG. **17**, may be utilized as well for remote control of the procedure. Such a configuration may be utilized with any embodiment disclosed herein, including delivery of an implant to a native aortic valve.

[0217] FIG. **39** illustrates an exemplary method that may utilize devices and systems disclosed herein. The method is exemplary in nature, and features of the method may be removed or added to, and the order of steps may be varied as desired. The features of the method may be combined or substituted with other features of devices, systems, and methods disclosed herein. The features of the method may be utilized in the embodiments disclosed in FIGS. **25-36**.

[0218] The method may include a step **820** of extending a delivery apparatus within a portion of a patient's body to deliver an implant to a body location. The delivery apparatus may be configured similarly as any embodiment of delivery apparatus disclosed herein. The delivery apparatus may be extended within a portion of the patient's body as shown in the embodiments of FIGS. **25-36** or any other manner disclosed herein. The implant may be configured similarly as any implant disclosed herein, and the body location may comprise any location disclosed herein. At least a portion of the delivery apparatus may be actuated by at least one motor operated by a processor.

[0219] The delivery apparatus may be extended within the portion of the patient's body by way of a user (e.g., clinician) advancing the delivery apparatus, such as the elongate shaft of the delivery apparatus within the patient's body. The delivery apparatus may be advanced manually by the user. For example, the user may manually grip a handle of the delivery apparatus or a control mechanism to advance the delivery apparatus. In embodiments, an automated method may be utilized, for example, utilizing a motor driven rail **577**, as shown in FIG. **17**, or other assembly that actuates axial movement of the delivery apparatus into the patient's body. In embodiments, the delivery apparatus may be advanced remotely by the user, for example, utilizing a remote control device **588** as shown in FIGS. **37** and **38**. In other embodiments, other methods may be utilized to extend the delivery apparatus within the portion of the patient's body.

[0220] Referring to step **822**, an input may be provided with a control device. The input may be provided by a user to actuate at least a portion of the delivery apparatus. A control device such as a control devices **504, 556, 562, 588** shown in FIG. **13, 15, 16, 37, or 38**, or another form of control device may be utilized as desired. The input may be provided to control a movement of the delivery apparatus. For example, the user may determine to deflect the delivery apparatus or control a depth of the delivery apparatus to a desired orientation. FIG. **25** illustrates an elongate shaft of a delivery apparatus being deflected to a desired orientation towards a native mitral valve. FIG. **32** illustrates an elongate shaft of a delivery apparatus being deflected to a desired orientation towards a native tricuspid valve. FIG. **35** illustrates an elongate shaft of a delivery apparatus being deflected to a

desired orientation within an aortic arch. A variety of forms of deflections may occur, as well as variations in the depth of the delivery apparatus. The user may further provide an input to perform an operation of the delivery apparatus, for example to deploy the implant either fully or partially. The user may view the position of the delivery apparatus within the patient's body on an output device, such as a display screen **584** as shown in FIG. **37**. The image on the display screen **584** may be produced by sensors external to the patient's body, such as fluoroscopy or echocardiography sensors, and/or may be provided via signals from proximity sensors of the elongate shaft. The user may view of a model of an interior of the patient's body on the output device, as discussed in regard to FIG. **37**.

[0221] In embodiments, the input may be provided remotely by the user, for example, utilizing a remote control device **588** as shown in FIGS. **37** and **38**.

[0222] The input provided by the control device may be utilized to operate the motor and may be provided to the processor **536**. The processor **536** accordingly may be utilized to operate the motor to produce the desired actuation of the delivery apparatus.

[0223] Referring to step **824**, signals may be received from one or more sensors. The signals may be received by the processor **536** and may comprise feedback signals that are provided to the processor **536** from the sensors. The sensors may include any of the sensors disclosed herein, including sensors for sensing a condition of the delivery apparatus or sensing a condition of the patient's body. Such sensors may include the position sensors, motor torque sensors, contact sensors, proximity sensors, pressure sensors, flow sensors, or other forms of sensors disclosed herein. The sensors may operate in manners disclosed herein. The sensor signals may be provided during an implantation procedure and may be provided in real-time to the processor **536** as feedback signals during the procedure. For example, the proximity sensor **582** may provide a signal indicating that the delivery apparatus has contacted or is proximate a surface of the surface of the patient's body. A pressure sensor **578** may provide a signal indicating a pressure, such as a fluid pressure, within the patient's body. Other sensors may be utilized and may operate in manners disclosed herein. In embodiments, the sensors may not be coupled to the delivery apparatus and may be positioned external to the patient's body. The sensors, for example, may be sensors that are utilized in fluoroscopy and/or echocardiography, and may be provided to the processor **536** for the processor to determine the location of the delivery apparatus within the patient's body.

[0224] Referring to step **826**, an output may be provided based on the signals. The processor **536** may provide the output based on the signals. The processor **536** may be configured to provide an output based on the one or more of a condition of the patient's body or the condition of the delivery apparatus sensed by the one or more sensors. The output may have a variety of forms as disclosed herein. For example, the output may comprise a log of data **828**. Such a log of data may be for an implantation procedure with the delivery apparatus and may be stored in the memory **534** and may have a form as disclosed herein. The data may be stored for later retrieval by a user for analysis or may record a log of actions taken by the delivery apparatus. For example, the position sensor signals may be logged to record the movements of the delivery apparatus, among other forms of sensors signals. In embodiments, the log of data may be utilized to allow the system to learn from past events and may be utilized in a machine learning algorithm to allow the system to continually refine the procedure to enhance the probability of success. The log of data may include data from implantation procedures or characteristics of the patient, for use in a machine learning algorithm that may use such data.

[0225] The output may comprise an indicator **830**. The indicator may be produced by the processor **536** in manners disclosed herein and may be provided on an output device. A condition of the delivery apparatus or a condition of the patient's body may be indicated to a user in a variety of forms, for example, an output device may include one or more of a display screen, a light, a speaker, or a haptic device, among other forms of output devices. The user may be able to respond to the indicator. For example, if the indicator indicates that the proximity sensor **582** sensed that the

delivery apparatus has contacted or is proximate a surface of the patient's body, then the user may be able to respond and actuate the delivery apparatus away from the surface. Further, if the indicator indicates that a flow sensor **583** senses an undesired flow within the patient's body during implantation, then the user may be able to respond and redeploy the implant if desired. The indicator may indicate whether the implantation procedure is operating desirably, or may indicate an undesirable operation of the implantation procedure. Other forms of indicators may be provided as disclosed herein, and the user may respond in a desired manner.

[0226] The output may comprise an actuation **832** of at least a portion of the delivery apparatus. The processor **536** may provide an output that comprises a control of the motor **500** based on the signals from the one or more sensors. For example, a signal from a contact sensor **580** or a proximity sensor **582** may be provided to the processor **536** as feedback that the delivery apparatus has contacted or is proximate a surface of the patient's body. The processor **536** accordingly may provide an output that operates the motor **500** based on feedback from the sensors to avoid or retract from the surface of the patient's body. A signal from the flow sensors **583a-l** may cause the processor **536** to provide an output to the motor **500** to redeploy the implant **70** or move the portion of the delivery apparatus to recapture the leaflet **1108**. A signal from a position sensor may provide feedback to the processor **536** regarding whether the delivery apparatus is performing the correct movements, and the processor **536** may operate the motor **500** to perform corrective movements if desired (e.g., deflect the elongate shaft **12** if needed). The processor **536** may be programmed to automatically respond and produce outputs based on the condition of the patient's body or a condition of the delivery apparatus sensed by the one or more sensors. The programming for the processor **536** may be stored in the memory **534** and operated by the processor **536**.

[0227] In embodiments, the processor **536** may be configured to adjust an input that is provided by a user, for example, in step **822**, based on the feedback from the sensors. For example, if the user is providing a control to direct the elongate shaft towards a surface of the patient's body, and the proximity sensor **582** determines that such action brings the elongate shaft within a certain threshold of proximity to the surface, then the processor **536** may determine that the user's input is unsafe and may automatically adjust the input to avoid or retract from the surface of the patient's body. As such, the processor **536** may automatically operate the delivery apparatus to adjust the input provided by a user, which may include overriding the input provided by the user. Similarly, if a flow sensor **583** senses that undesired flow is provided during implantation of a valve, then the processor may automatically operate the delivery apparatus to adjust an input provided by a user to properly implant the valve. The processor **536** may operate based on any sensor signals disclosed herein to adjust the input provided by a user.

[0228] The actuation produced by the processor **536** may be based on a machine learning algorithm utilizing data from past implantation procedures or from characteristics of the patient. The data may be "learned" from previous procedures and, in particular, learned from previous procedures performed on patients with similar anatomies and/or other characteristics. Therefore, procedural steps performed successfully on patients with similar anatomies could be duplicated, thereby increasing the probability of a successful procedure on the current patient. A machine learning algorithm may be utilized by the processor **536** to control actuation of the delivery apparatus, and may be used to adjust the input provided by a user.

[0229] Further, the actuation produced by the processor **536** may be based on a programmed series of movements that are to be performed by the delivery apparatus. Such a program may be pre-programmed into the processor **536** or may be programmed based on a model or map of the patient's anatomy as discussed in regard to FIG. **37**. For example, external sensors may be utilized to determine a model or map of the patient's anatomy and the processor **536** may be programmed with movements to deliver the implant to the desired body location. The programming may also occur during the implantation procedure, for example, based on the feedback from sensors. If the input from the user strays from the desired movements within a certain threshold, then the

processor **536** may be configured to automatically adjust the input to move the delivery apparatus in the desired manner. As such, the processor **536** may be programmed to reduce the possibility of the user performing an undesired procedure during implantation.

[0230] Referring to step **834**, a confirmation of implantation may be provided. Such a confirmation may be provided by the processor **536**, and may be provided based on signals from sensors. For example, a pressure sensor or flow sensor, or other form of sensor, may determine that the implant has been implanted. The processor **536** may be configured to provide such a confirmation of implantation as an indicator on an output device, so that the user is notified that the implant has been implanted. The user may then perform steps to withdraw the delivery apparatus from the patient's body and otherwise complete the implantation procedure.

[0231] In the exemplary method discussed in regard to FIG. **39**, a user (e.g., clinician) may provide input, which may be assisted by use of the components disclosed herein (e.g., the processor, motor, and one or more sensors, among other components). In embodiments, however, an implantation procedure may occur autonomously (i.e., adapts to environment during operation). The processor may perform autonomous control of the delivery apparatus to perform the implantation procedure. A user may provide some input during the procedure, such that the procedure may occur semi-autonomously. As such, a method may occur autonomously or semi-autonomously (or at least semi-autonomously).

[0232] FIG. **40**, for example, illustrates a method of autonomous control of the delivery apparatus. A user may provide some input during the procedure, such that the procedure may occur semi-autonomously or least semi-autonomously. Similar to the method disclosed in regard to FIG. **39**, the method of FIG. **40** is an exemplary method that may utilize devices and systems disclosed herein. Features of the method may be removed or added to, and the order of steps may be varied as desired. The features of the method may be combined or substituted with other features of devices, systems, and methods disclosed herein. The features of the method may be utilized in the embodiments disclosed in FIGS. **25-36**.

[0233] The method may include a step **840** of extending a delivery apparatus within a portion of a patient's body to deliver an implant to a body location. The delivery apparatus may be configured similarly as any embodiment of delivery apparatus disclosed herein. The delivery apparatus may be extended within a portion of the patient's body as shown in the embodiments of FIGS. **25-36** or any other manner disclosed herein. The implant may be configured similarly as any implant disclosed herein, and the body location may comprise any location disclosed herein.

[0234] The delivery apparatus may be extended within the portion of the patient's body by way of a motor advancing the delivery apparatus, such as the elongate shaft of the delivery apparatus within the patient's body. The motor may be controlled by the processor **536**. For example, a motor driven rail **577**, as shown in FIG. **17**, or other assembly that actuates axial movement of the delivery apparatus into the patient's body may be utilized. In other embodiments, other methods may be utilized to extend the delivery apparatus within the portion of the patient's body.

[0235] Referring to step **842**, the processor **536** may operate a program to actuate the delivery apparatus. The processor **536** may be programmed with a sequence of movements to actuate the delivery apparatus to the desired location and for the desired deployment operation. For example, the processor **536** may be configured to determine the desired delivery location and the path and orientation to be followed to reach the desired delivery location based on external sensing of the position via fluoroscopy or echocardiography and/or the position being determined via signals from proximity sensors of the elongate shaft **12**. The programmed sequence of movement may be provided based on the geometry of the path to the desired implant location, and the orientation of the desired implant location. The movement and deployment of the delivery apparatus may be preprogrammed into the processor **536** and may be individualized based on the particular path to the desired location in the patient's body to be followed. In certain embodiments, a machine learning algorithm may be utilized by the processor **536** to control actuation of the delivery

apparatus. For example, the path and orientation also may be supplemented by data from previous procedures on patients with similar characteristics. The processor **536** and programming may be utilized to extend the delivery apparatus within a portion of the patient's body as disclosed in regard to step **840**.

[0236] Referring to step **844**, the processor **536** may continue to follow the program, and may receive signals from one or more sensors. The processor **536** may receive feedback from sensors (as discussed herein) that cause the processor **536** to produce outputs in step **846**. The signals from the sensors may be utilized by the processor **536** in a similar manner as disclosed with respect to step **826** and may produce similar outputs **848**, **850**, **852** as disclosed regarding the outputs **828**, **830**, **832** of FIG. **39**. For example, the processor **536** may be configured to produce a log of data **848** in a similar manner as disclosed regarding the method of FIG. **39**. The processor **536** may be configured to produce an indicator **850** in a similar manner as disclosed regarding the method of FIG. **39**. The indicator **850** may be provided for a user to determine whether to intervene in a procedure. For example, if a user (e.g., a clinician) receives an indicator that the autonomously operated delivery apparatus has contacted a surface or has improperly deployed an implant, then the user may intervene to attempt to correct such actuation.

[0237] The processor **536** may be configured to produce actuation **852** of the delivery apparatus. The actuation **852** may be provided for the processor **536** to correct the path and operation with minimal or no human interaction using feedback from sensors as discussed herein, to complete the procedure. For example, if the position sensor indicates the delivery apparatus is straying from the intended path, the processor **536** may automatically adjust the path. If the proximity sensor indicated the delivery apparatus is approaching a surface, then the processor **536** may automatically adjust the path. The processor **536** may be used to navigate to any desired location for delivery of the implant. Such navigation is shown, for example, in FIGS. **25**, **31**, **32**, **34**, and **35**, among other forms of navigation. Any of the sensors and feedback operations from the sensors disclosed herein may be utilized in such a method. In certain embodiments, a user may provide some input during the procedure to correct the procedure or otherwise provide input to control the procedure.

[0238] Similar to the method discussed in regard to FIG. **39**, the actuation produced by the processor **536** may be based on a machine learning algorithm utilizing data from past implantation procedures or from characteristics of the patient. The actuation may be based on data “learned” from previous procedures and, in particular, learned from previous procedures performed on patients with similar anatomies and/or other characteristics. Therefore, procedural steps performed successfully on patients with similar anatomies could be duplicated, thereby increasing the probability of a successful procedure on the current patient. A machine learning algorithm may be utilized by the processor **536** to control actuation of the delivery apparatus.

[0239] The processor **536** may be configured to operate the motor **500** to produce the desired actuation of the delivery apparatus. The processor **536** may be configured to automatically operate the motor to deflect the delivery apparatus to the desired body location. The processor **536** may be configured to automatically operate the motor to deflect the delivery apparatus in at least two planes. The processor **536** may be configured to automatically deploy the implant **70** to the desired location and complete the delivery procedure. The processor **536** may be configured to complete the delivery procedure in certain embodiments without control or intervention by a user. In step **854**, a confirmation of implantation may be provided in a similar manner as with step **834** in FIG. **39**. The processor **536** may be configured to provide such a confirmation of implantation as an indicator on an output device, so that the user is notified that the implant has been implanted.

[0240] The methods of FIGS. **39** and **40** may be utilized for replacement or repair of a heart valve within a patient's body. The heart valve may comprise one or more of an aortic heart valve, a mitral heart valve, a tricuspid heart valve, or a pulmonary heart valve. Other valves or body locations for implantation may be treated in other embodiments. Variations on the methods of FIGS. **39** and **40** may be provided as desired.

[0241] FIG. **41** illustrates an embodiment of a delivery apparatus configured similarly as the apparatus shown in FIG. **10**, however, multiple motors **502** may be utilized to control actuation of the delivery apparatus. The multiple motors **502**, for example, may each be configured to engage respective adaptors **590**, **592**, **594** configured to actuate portions of the delivery apparatus. The motors **502** may be configured to perform linear movement of the adaptors **590**, **592**, **594** to cause actuation of the delivery apparatus. Further, in the embodiment of FIG. **41**, the processor, memory, and input device and output device of FIG. **41** may be provided on a printed circuit board **596** positioned within the handle. A power source **598** such as a battery pack or other form of power source may also be utilized within the handle. The embodiment of FIG. **41** may comprise a self-contained handle unit including a processor for performing a delivery procedure and receiving feedback from sensors, as well as performing data logging if desired.

[0242] The motors disclosed herein may comprise a variety of forms of motors, including electromagnetic, stepper, hydraulic, piezoelectric, among others.

[0243] Although many of the systems and methods disclosed herein have been discussed with respect to implantation of a prosthetic mitral valve implant, the systems and methods are also applicable to replacement of other heart valves, such as the tricuspid, aortic, and pulmonary valve. It is also understood that the systems and methods may be utilized to deliver a variety of implants, including implants for repair of a heart valve. For example, other types of heart valve implants that may be utilized are shown in FIGS. **42-44**, among other types of implants (e.g., aortic valve implants and other repair implants).

[0244] The delivery apparatuses utilized herein may be configured as the delivery apparatus shown in FIG. **1**, or may have a variety of other configurations. For example, delivery apparatuses may be utilized that are configured to deliver implants to the native aortic valve, and may be configured to pass through the aortic arch. The delivery apparatus may be configured according to the type of implant to be delivered and according to the location of delivery of the implant. Other forms of delivery apparatuses may be utilized as desired.

[0245] The methods and systems disclosed herein may in certain embodiments not be limited to delivery of implants, but may extend to any medical intervention or insertion into a patient's body, which may include performing a medical procedure within the body. The methods and systems disclosed herein may be utilized in general use of a catheter as desired. For example, the handle shown in FIG. **41** and components disclosed therein may comprise a general catheter handle in certain embodiments. Further, the configuration of the delivery apparatus may be modified in other embodiments. For example, for an aortic valve delivery apparatus, the configuration of the implant retention area and other features of the delivery apparatus may be modified.

[0246] FIG. **42** illustrates an alternative embodiment of an implant that may be utilized according to embodiments herein. Reference numbering of FIG. **42** is the same as discussed above with respect to FIG. **3A**.

[0247] With reference next to FIGS. **43-44**, an alternative embodiment of an implant **1600** in an expanded configuration is illustrated. The implant **1600** can include an inner frame **1620**, an outer frame **1640**, a valve body **1660**, and one or more skirts, such as an outer skirt **1680** and an inner skirt **1690**.

[0248] With reference first to the outer frame **1640** illustrated in FIGS. **43-44**, the outer frame **1640** can be attached to the inner frame **1620** using any known fasteners and/or techniques. Although the outer frame **1640** is illustrated as a separate component from the inner frame **1620**, it is to be understood that the frames **1620**, **1640** can be unitarily or monolithically formed.

[0249] As shown in the illustrated embodiment, the outer frame **1640** can include an outer frame body **1642**. The outer frame body **1642** can have an upper region **1642a**, an intermediate region **1642b**, and a lower region **1642c**. At least a portion of the upper region **1642a** of the outer frame body **1642** can be sized and/or shaped to generally match the size and/or shape of an upper region **1622a** of the inner frame **1620**. As shown in the illustrated embodiment, the upper region **1642a** of

the outer frame body **1642** can include one or more struts which generally match the size and/or shape of struts of the inner frame **1620**. This can locally reinforce a portion of the implant **1600** by effectively increasing the wall thickness of the combined struts.

[0250] When in an expanded configuration such as in a fully expanded configuration, the intermediate region **1642b** and the lower region **1642c** can have a diameter which is larger than the diameter of the upper region **1642a**. The upper region **1642a** of the outer frame body **1642** can have a decreasing diameter from a lower end to an upper end such that the upper region **1642a** is inclined or curved radially inwards towards the longitudinal axis of the implant **1600**. Although the outer frame body **1642** has been described and illustrated as being cylindrical or having circular cross-sections, it is to be understood that all or a portion of the outer frame body **1642** can have a non-circular cross-section such as, but not limited to, a D-shape, an oval or an otherwise ovoid cross-sectional shape.

[0251] With continued reference to the outer frame **1600** illustrated in FIG. **43**, the outer frame body **1642** can include a plurality of struts with at least some of the struts forming cells **1646a-c**. Any number of configurations of struts can be used, such as rings of undulating struts shown forming ellipses, ovals, rounded polygons, and teardrops, but also chevrons, diamonds, curves, and various other shapes.

[0252] The upper row of cells **1646a** can have an irregular octagonal shape such as a “heart” shape. This additional space can beneficially allow the outer frame **1640** to retain a smaller profile when crimped. The cell **1646a** can be formed via a combination of struts. As shown in the illustrated embodiment, the upper portion of cells **1646a** can be formed from a set of circumferentially-expandable struts **1648a** having a zig-zag or undulating shape forming a repeating “V” shape. The struts **1648a** can extend radially outwardly from an upper end to a lower end. These struts can generally match the size and/or shape of struts of the inner frame **1620**.

[0253] The middle portion of cells **1646a** can be formed from a set of struts **1648b** extending downwardly from bottom ends of each of the “V” shapes. The struts **1648b** can extend radially outwardly from an upper end to a lower end. The portion of the cells **1646a** extending upwardly from the bottom end of struts **1648b** may be considered to be a substantially non-foreshortening portion of the outer frame **1640**.

[0254] The lower portion of cells **1646a** can be formed from a set of circumferentially-expandable struts **1648c** having a zig-zag or undulating shape forming a repeating “V” shape. As shown in the illustrated embodiment, the struts **1648c** can incorporate a curvature such that the lower end of struts **1648c** extend more parallel with the longitudinal axis than the upper end of the struts **1648c**. One or more of the upper ends or tips of the circumferentially-expandable struts **1648c** can be a “free” apex which is not connected to a strut. For example, as shown in the illustrated embodiment, every other upper end or tip of circumferentially-expandable struts **1648b** is a free apex. However, it is to be understood that other configurations can be used. For example, every upper apex along the upper end can be connected to a strut.

[0255] The middle and/or lower rows of cells **1646b-c** can have a different shape from the cells **1646a** of the first row. The middle row of cells **1646b** and the lower row of cells **1646c** can have a diamond or generally diamond shape. The diamond or generally diamond shape can be formed via a combination of struts.

[0256] The upper portion of cells **1646b** can be formed from the set of circumferentially-expandable struts **1648c** such that cells **1646b** share struts with cells **1646a**. The lower portion of cells **1646b** can be formed from a set of circumferentially-expandable struts **1648d**. As shown in the illustrated embodiment, one or more of the circumferentially-expandable struts **1648d** can extend generally in a downward direction generally parallel to the longitudinal axis of the outer frame **1640**.

[0257] The upper portion of cells **1646c** can be formed from the set of circumferentially-expandable struts **1648d** such that cells **1646c** share struts with cells **1646b**. The lower portion of cells **1646c** can be formed from a set of circumferentially-expandable struts **1648e**. Circumferentially-

expandable struts **1648e** can extend generally in a downward direction.

[0258] As shown in the illustrated embodiment, there can be a row of nine cells **1646a** and a row of eighteen cells **1646b-c**. While each of the cells **1646a-c** are shown as having the same shape as other cells **1646a-c** of the same row, it is to be understood that the shapes of cells **1646a-c** within a row can differ. Moreover, it is to be understood that any number of rows of cells can be used and any number of cells may be contained in the rows.

[0259] As shown in the illustrated embodiment, the outer frame **1600** can include a set of eyelets **1650**. The upper set of eyelets **1650** can extend from an upper region **1642a** of the outer frame body **1642**. As shown, the upper set of eyelets **1650** can extend from an upper portion of cells **1646a**, such as the upper apices of cells **1646a**. The upper set of eyelets **1650** can be used to attach the outer frame **1640** to the inner frame **1620**. For example, in some embodiments, the inner frame **1620** can include one or more eyelets which correspond to the eyelets **1650**. In such embodiments, the inner frame **1620** and outer frame **1640** can be attached together via eyelets **1650** and corresponding eyelets on the inner frame **1620**. For example, the inner frame **1620** and outer frame **1640** can be sutured together through said eyelets or attached via other means, such as mechanical fasteners (e.g., screws, rivets, and the like).

[0260] As shown, the set of eyelets **1650** can include two eyelets extending in series from each “V” shaped strut. This can reduce the likelihood that the outer frame **1640** twists along an axis of the eyelet. However, it is to be understood that some “V” shaped struts may not include an eyelet. Moreover, it is to be understood that a fewer or greater number of eyelets can extend from a “V” shaped strut.

[0261] The outer frame **1640** can include a set of locking tabs **1652** extending from at or proximate an upper end of the upper region **1642a**. As shown, the locking tabs **1652** can extend upwardly from the set of eyelets **1650**. The outer frame **1640** can include twelve locking tabs **1652**, however, it is to be understood that a greater number or lesser number of locking tabs can be used. The locking tabs **1652** can include a longitudinally-extending strut **1652a**. At an upper end of the strut **1652a**, the locking tab **1652** can include an enlarged head **1652b**. As shown, the enlarged head **1652b** can have a semi-circular or semi-elliptical shape forming a “mushroom” shape with the strut **1652a**. The locking tab **1652** can include an eyelet **1652c** which can be positioned through the enlarged head **1652b**. It is to be understood that the locking tab **1652** can include an eyelet at other locations, or can include more than a single eyelet.

[0262] The locking tab **1652** can be advantageously used with multiple types of delivery systems. For example, the shape of the struts **1652a** and the enlarged head **1652b** can be used to secure the outer frame **1640** to a “slot” based delivery system, such as the inner retention member **40** described above. The eyelets **1652c** and/or eyelets **1650** can be used to secure the outer frame **1640** to a “tether” based delivery system such as those which utilize sutures, wires, or fingers to control delivery of the outer frame **1640** and the implant **1600**. This can advantageously facilitate recapture and repositioning of the outer frame **1640** and the implant **1600** in situ.

[0263] The outer frame **1640**, such as the outer frame body **1642** can be used to attach or secure the implant **1600** to a native valve, such as a native mitral valve. For example, the intermediate region **1642b** of the outer frame body **1642** and/or the outer anchoring feature **1644** can be positioned to contact or engage a native valve annulus, tissue beyond the native valve annulus, native leaflets, and/or other tissue at or around the implantation location during one or more phases of the cardiac cycle, such as systole and/or diastole. As another example, the outer frame body **1642** can be sized and positioned relative to the inner frame anchoring feature **1624** such that tissue of the body cavity positioned between the outer frame body **1642** and the inner frame anchoring feature **1624**, such as native valve leaflets and/or a native valve annulus, can be engaged or pinched to further secure the implant **1600** to the tissue. As shown, the inner frame anchoring feature **1624** includes nine anchors; however, it is to be understood that a fewer or greater number of anchors can be used. In some embodiments, the number of individual anchors can be chosen as a multiple of the number of

commissures for the valve body **1660**. For example, for a valve body **1660** have three commissures, the inner frame anchoring feature **1624** can have three individual anchors (1:1 ratio), six individual anchors (2:1 ratio), nine individual anchors (3:1 ratio), twelve individual anchors (4:1 ratio), fifteen individual anchors (5:1 ratio), or any other multiple of three. In some embodiments, the number of individual anchors does not correspond to the number of commissures of the valve body **1660**.

[0264] With continued reference to the prosthesis **1600** illustrated in FIGS. **43-44**, the valve body **1660** is attached to the inner frame **1620** within an interior of the inner frame body **1622**. The valve body **1660** functions as a one-way valve to allow blood flow in a first direction through the valve body **1660** and inhibit blood flow in a second direction through the valve body **1660**.

[0265] The valve body **1660** can include a plurality of valve leaflets **1662**, for example three leaflets **1662**, which are joined at commissures. The valve body **1660** can include one or more intermediate components **1664**. The intermediate components **1664** can be positioned between a portion of, or the entirety of, the leaflets **1662** and the inner frame **1620** such that at least a portion of the leaflets **1642** are coupled to the frame **1620** via the intermediate component **1664**. In this manner, a portion of, or the entirety of, the portion of the valve leaflets **1662** at the commissures and/or an arcuate edge of the valve leaflets **1662** are not directly coupled or attached to the inner frame **1620** and are indirectly coupled or “float” within the inner frame **1620**.

[0266] With reference next to the outer skirt **1680** illustrated in FIG. **43**, the outer skirt **1680** can be attached to the inner frame **1620** and/or outer frame **1640**. As shown, the outer skirt **1680** can be positioned around and secured to a portion of, or the entirety of, the exterior of the outer frame **1640**. The inner skirt **1690** can be attached to the valve body **1660** and the outer skirt **1680**. As shown in FIG. **44**, a first end of the inner skirt **1690** can be coupled to the valve body **1660** along portions of the valve body **1660** which are proximate the inner frame **1620**. A second end of the inner skirt **1690** can be attached to the lower region of the outer skirt **1680**. In so doing, a smooth surface can be formed along under each of the leaflets. This can beneficially enhance hemodynamics by allowing blood to more freely circulate and reducing areas of stagnation.

[0267] Although the implant **1600** has been described as including an inner frame **1620**, an outer frame **1640**, a valve body **1660**, and skirts **1680**, **1690**, it is to be understood that the implant **1600** need not include all components. For example, in some embodiments, the implant **1600** can include the inner frame **1620**, the outer frame **1640**, and the valve body **1660** while omitting the skirt **1680**. Moreover, although the components of the implant **1600** have been described and illustrated as separate components, it is to be understood that one or more components of the implant **1600** can be integrally or monolithically formed. For example, in some embodiments, the inner frame **1620** and the outer frame **1640** can be integrally or monolithically formed as a single component.

[0268] FIGS. **45-48** illustrate embodiments in which at least one electromagnet is utilized that is configured to attract or repel a portion of a capsule of a delivery apparatus to vary a size of the capsule. Referring to FIG. **45**, the capsule **600** may be configured similarly as the capsule **106** or any other capsule disclosed herein. The capsule **600** may surround an implant retention area **602** that may be configured similarly as implant retention area **16** or any other implant retention area disclosed herein. The capsule **600** may be a part of an elongate shaft of a delivery apparatus, which may be configured in a similar manner as disclosed herein. The implant retention area **602** may be configured to retain an implant, which may comprise the implant **70** or another form of implant as disclosed herein.

[0269] At least one electromagnet **604** may be utilized to vary a size of the capsule. As shown in FIG. **45**, a plurality of electromagnets **604** may be utilized, or in other embodiments a single electromagnet **604** may be utilized. The electromagnets **604** may be coupled to and positioned on a first portion **606** of a capsule **600** and may be configured to attract or repel a second portion **608** of the capsule **600**. The first portion **606** as shown in FIG. **45** may comprise a side wall of the capsule **600** that is configured to surround the implant **70** within the implant retention area **602**. The second

portion **608** may similarly comprise a side wall of the capsule **600** that is configured to surround the implant **70**. The side walls may be configured to apply a compressive force to the implant **70** while the implant **70** is retained within the implant retention area **602**. The first portion **606** and second portion **608** may comprise halves of the capsule **600** and may extend along the axial length of the capsule **600**. In other embodiments, other configurations of portions of the capsule **600** may be utilized. Further, other positions of the one or more electromagnets **604** may be utilized. For example, the one or more electromagnets **604** may be positioned on another assembly of the delivery apparatus such as the nose cone assembly **31**, the inner assembly **18**, the mid shaft assembly **21**, among other locations. The electromagnets **604** as shown in FIG. **45** are positioned on the outer sheath assembly **22**, although other positions may be utilized to vary a size of the capsule **600**.

[0270] The portions **606**, **608** may be separated from each other by a gap **610** between the portions **606**, **608**. The gap **610** may be an open gap **610** or may be a filled gap **610** that is filled with material, for example, material that may be compressed if desired. The gap **610** may extend along the axial length of the capsule **600** as shown in FIG. **45** or may have other configurations in other embodiments as desired. The separation between the edges of the portions **606**, **608** provided by the gap **610** may allow the portions **606**, **608** to move relative to each other to increase and decrease the size of the gap **610** and accordingly vary the size of the capsule **600**.

[0271] A biasing body **612** may be utilized that may bias the portions **606**, **608** towards each other or away from each other. The biasing body **612** may be configured to apply a biasing force to the portions **606**, **608**. Such a biasing force may draw the portions **606**, **608** towards each other or away from each other as desired. The biasing force may counteract the direction of the force to be applied by the at least one electromagnet **604**. For example, in an embodiment in which the at least one electromagnet **604** attracts the portions **606**, **608** together, the biasing body **612** may move the portions **606**, **608** away from each other. In an embodiment in which the at least one electromagnet **604** repels the portions **606**, **608**, the biasing body **612** may move the portions **606**, **608** towards each other. The biasing body **612** may comprise an elastic body that is configured to resist a compression or expansion of the body **612**. For example, as the body **612** is compressed, the body **612** may provide a resistive expansion force, and as the body **612** is expanded, the body **612** may provide a resistive compressive force. The body **612** may be positioned within the gap **610** or may be positioned outside of the gap **610** as desired. For example, the body **612** may comprise a sheath placed over the gap **610** or the outer surface of the capsule **600** as desired.

[0272] The one or more electromagnets **604** may be positioned as desired to attract or repel the portion of the capsule **600** to vary the size of the capsule **600**. The one or more electromagnets **604** may be coupled to electrical conduits **614a, b** that may extend along the length of the elongate shaft and may couple to a power source **616** that may be configured similarly as the power source **538** shown in FIG. **10** or any other power source disclosed herein. The power source **616** may be configured to provide electrical energy to the at least one electromagnet **604**. The power source **616** may be configured to pass a current through the electrical conduits **614a, b** and through the one or more electromagnets **604** to actuate the electromagnets **604** and cause the electromagnets **604** to provide an attractive or repulsive force. The power source **616** may be configured to reverse the direction of current to vary from an attractive or repulsive force as desired. The power source **616** may also be able to vary the amount of current through the one or more electromagnets **604** to vary the strength of the attractive or repulsive force.

[0273] The one or more electromagnets **604** may be configured to apply a magnetic force to magnetically responsive materials in the capsule **600** (for example the portion of the capsule **600** that does not include the electromagnets **604** such as the second portion **608** shown in FIG. **45**). The magnetically responsive material may be a metal or other form of magnetically responsive material that may be coupled to the capsule **600** at a desired location. In other embodiments, the electromagnets **604** may be configured to apply a magnetic force to other electromagnets **604** or

magnetic materials.

[0274] The one or more electromagnets **604** may be utilized to vary a radial size of the capsule **600**. The diameter of the implant retention area **602** may vary, and the inner and outer diameter of the capsule **600** may vary as well. The variation in the size of the capsule **600** may allow for a lower profile size of the capsule **600** at a desired time, and a larger profile size of the capsule **600** at another desired time. For example, a lower profile size of the capsule **600** may be desired upon passage through the vasculature of the patient's body. A larger profile size of the capsule **600** may be desired to enhance ease of passage of the implant **70** into and out of the capsule **600** at a desired time. For example, upon entry of the implant **70** into the capsule **600** during a loading procedure, a larger sized implant retention area **602** and capsule **600** may be desired. Further, upon deployment of the implant **70** from the capsule, for example in a procedure as shown in FIGS. **28-30**, a larger sized implant retention area **602** and capsule **600** may be desired. A larger sized implant retention area **602** and capsule **600** may reduce friction upon the implant **70** and capsule **600** upon loading and deployment of the implant **70**. As such, a reduced force may be applied to the capsule **600** upon retraction of the capsule **600** to deploy the implant **70**. The use of the one or more electromagnets **604** may allow a user to selectively vary a size of the capsule **600**.

[0275] The capsule **600** may be biased to have a larger size, with the one or more electromagnets **604** utilized to decrease the size of the capsule **600**. For example, as shown in FIG. **45**, the biasing body **612** may apply a biasing force to the portions **606**, **608** to increase the radial size of the capsule **600**. The one or more electromagnets **604** may then be actuated to attract the portion **606** to the portion **608** thus overcoming the biasing force and closing the gap **610**. The one or more electromagnets **604** may attract the portion **608** to decrease the radial size of the capsule **600**. FIG. **46** illustrates the capsule **600** having a decreased radial size than shown in FIG. **45**. In such an embodiment, the capsule **600** may be advanced to a desired location within the patient's body with the capsule **600** having the decreased radial size. At a desired time for deployment of the implant **70** positioned within the capsule **600**, the one or more electromagnets **604** may be deenergized and the biasing body **612** may press the portions **606**, **608** apart from each other to increase the radial size of the capsule **600**. The implant **70** accordingly may be deployed from the implant retention area **602** with a reduced friction force with the capsule **600**. The one or more electromagnets **604** may be reenergized after deployment of the implant **70** to decrease the radial size of the capsule **600** for withdrawal of the capsule **600** and the delivery apparatus from the patient's body.

[0276] In embodiments, the biasing body **612** may be configured to decrease the radial size of the capsule **600**, with the one or more electromagnets **604** applying a repulsive force to repel a portion of the capsule **600** to increase the radial size of the capsule **600**. In such an embodiment, the one or more electromagnets **604** may be energized at the desired time to overcome the force of the biasing body **612** and increase the radial size of the capsule **600**.

[0277] In embodiments, a biasing body may be excluded. For example, the one or more electromagnets **604** may apply an attractive or repulsive force alternatively to vary a size of the capsule **600**. The one or more electromagnets **604** may be configured to apply an attractive force to keep the capsule **600** in a low profile configuration until the desired time. The one or more electromagnets **604** may be configured to then apply a repulsive force to increase the radial size of the capsule at a desired time. The direction of current through the electrical conduits **614a, b** may be alternated to vary the force between attractive and repulsive. The amount of current may also be controlled to vary the strength of the attractive and repulsive force and set the size of the capsule to a desired size. In embodiments, a biasing body may be excluded and the one or more electromagnets **604** may only be configured to provide an attractive force. An expansion force provided by the implant **70** within the implant retention area **602** may cause the size of the capsule **600** to increase upon the attractive force by the one or more electromagnets **604** being ceased. Other configurations utilizing the one or more electromagnets **604** may be provided.

[0278] FIGS. **47** and **48** illustrate an embodiment in which the capsule may be split into multiple

portions, with one or more electromagnets **604** configured to attract or repel a portion of a capsule of a delivery apparatus to vary a size of the capsule. The capsule **618** may include portions **620**, **622**, **624**, **626** that are separated by gaps and that form side walls of the capsule **618**, similar to the portions **606**, **608**. The position and greater number of gaps, however, may increase the overall size variation of the capsule **618**. Further, the size variation may be more uniform about the capsule **618** due to the symmetrically spaced placement of the portions **620**, **622**, **624**, **626**. The one or more electromagnets **604** may be configured to vary the size of the capsule **618** in a similar manner as discussed in regard to FIGS. **45** and **46**.

[0279] The electromagnets may be utilized with any embodiment of delivery system disclosed herein. The electromagnets may be controlled by a processor, as disclosed herein, which may operate to actuate the electromagnets and thus vary the size of the capsule as desired. Such operation may occur in response to a user's input, via a control device or the like, or the processor may automatically actuate the electromagnets as desired. For example, the processor may actuate the electromagnets in response to a sensor reading (for example one of the sensors as disclosed herein), or in response to a program, indicating that the size of the capsule should be varied. The processor may be configured to automatically vary the size of the capsule and deploy the implant. [0280] The power supply for the electromagnets may be integrated with a controller, for example a controller **530** as shown in FIG. **18**. The electrical conduits for the electromagnets may extend to the controller. The processor may be configured to control the power supply to control the electromagnets.

[0281] A method that may utilize the embodiments of FIGS. **45-48** may include deploying an elongate shaft to a location within a patient's body, the elongate shaft including a capsule surrounding an implant retention area retaining an implant for implantation within the patient's body. The at least one electromagnet may be utilized to attract or repel a portion of the capsule to vary of a size of the capsule within the patient's body. A radial size of the capsule may be increased utilizing the at least one electromagnet. For example, the at least one electromagnet may be energized to repel a portion of the capsule or the at least one electromagnet may be deenergized to allow a biasing body to increase the size of the capsule. The implant may be deployed from the capsule with the capsule having the increased radial size. In addition, the capsule may have its size increased to recapture a portion of the implant. Further, the implant may be inserted into the capsule with the capsule having the increased radial size. The implant may be inserted into the capsule during loading of the implant into the capsule. The size of the capsule may be dynamically adjustable.

[0282] FIGS. **49-59** illustrate embodiments including electrically detachable couplers that are configured to couple to an implant and to detach from at least a portion of the implant. FIGS. **49-55** illustrate embodiments utilizing an electrolytically detachable coupler.

[0283] Referring to FIG. **49**, an electrolytically detachable coupler may utilize an electrical circuit to electrolytically erode the electrolytically detachable coupler. The electrical circuit may include electrical conduits **700a**, **b** that may be coupled to a power supply **702**. The electrical conduits **700a**, **b** may couple to electrical terminals. The blood of the patient and other fluids or materials may be utilized as a conduit for the electrical circuit to electrically couple the electrical terminals. For example, as shown in FIG. **49**, an electrical terminal **704** may be configured to be positioned on a portion of the patient's body. The electrical terminal **704** may be configured as an electrode that is coupled to a patch that is coupled to the patient's body. The patch may be positioned on the patient's skin, and may be near the shoulder or otherwise may be positioned on the chest or elsewhere on the patient. In other embodiments, other forms of electrical terminals may be utilized such as clips or other devices for coupling to the patient's body. The electrical terminal **704** may couple to the electrical conduit **700a** that is coupled to the power supply **702**. The electrical conduit **700b** may be coupled to the power supply **702** and may extend along the elongate shaft of the delivery apparatus to reach the electrical terminal as part of the electrolytically detachable coupler.

The electrolytically detachable coupler may comprise a first portion of an electrical circuit, and the electrical terminal **704** may form a second portion of the electrical circuit. The power supply **702** may electrically couple the first portion of the electrical circuit to the second portion of the electrical circuit and may be configured to pass an electrical current between the first portion and the second portion.

[0284] FIG. **50**, for example, illustrates a schematic side cross sectional view of the implant retention area of an elongate shaft, including an implant **706** positioned therein. The implant **706** may be configured similarly as the implant **70** or another form of implant as disclosed herein. The implant **706** may include distal anchors **708** and proximal anchors **710** and may be a self-expanding implant. The implant **706** as shown in FIG. **50** may be in a compressed state within the implant retention area **712**.

[0285] A capsule **714** may surround the implant **706** within the implant retention area **712** and may be configured similarly as the capsule **106** or any other capsule disclosed herein. The capsule **714** may be formed of an outer sheath **716** and an outer retention ring **718** that may be configured similarly as the respective outer sheath and outer retention ring **42** otherwise disclosed herein. A nose cone shaft **720** may couple to a nose cone **722** that may be configured similarly as the nose cone shaft **27** and nose cone **28** respectively, or any other nose cone shaft or nose cone disclosed herein.

[0286] The delivery apparatus shown in FIG. **50** may include an electrolytically detachable coupler **724a, b** that couples to the implant **706**. The electrolytically detachable coupler **724a, b** may couple to a proximal end of the implant **706** as shown in FIG. **50**. FIG. **51** provides an enlarged view of the point of connection between the electrolytically detachable coupler **724a** and the implant **706** (at which reference number **726a** points to in FIG. **50**). The implant **706** may include a proximal end coupler **726a** that may be positioned in a similar location as the mushroom-shaped tabs **74** shown in FIG. **3A**. As shown in FIG. **51**, the proximal end coupler **726a** may include a cavity or other form of coupler that receives the electrolytically detachable coupler **724a**. The electrolytically detachable coupler **724a** may form a rigid connection with the proximal end coupler **726a**. The electrolytically detachable coupler **724a** may include an exposed electrical terminal **728** that is exposed and in contact with the patient's fluid during deployment of the implant **706**. The exposed electrical terminal **728** may be electrically connected to the electrical conduit **700b**, which may extend along the elongate shaft to the power supply **702** as shown in FIG. **49**. Portions adjacent to the exposed electrical terminal **728** may be electrically insulated, for example an electrically insulated portion **730** may be proximal the exposed electrical terminal **728** and another electrically insulated portion **732** may be positioned distal of the exposed electrical terminal **728**. As such, flow of current from the electrical conduit **700b** may be prevented from reaching the implant **706**. In other embodiments, the implant **706** may be electrically insulated.

[0287] The electrolytically detachable coupler **724a** may be configured such that as current is passed through the electrical conduit **700b** with the power supply **702**, the exposed electrical terminal **728** may be in electrical contact with the patient's fluid (which may be blood during delivery of the implant to a portion of the patient's heart) and may utilize the fluid to complete the electrical circuit with the terminal **704**. The exposed electrical terminal **728** may disintegrate due to electrolytic erosion and may detach from the portion of the implant **706**.

[0288] For example, as shown in FIG. **52**, the capsule **714** may be placed in the desired location within the patient's body and the outer sheath **716** and outer retention ring **718** may be retracted to expose the implant **706**. The implant **706** may begin a process of expansion yet may remain coupled to the electrolytically detachable coupler **724a, b**. Upon the implant **706** being positioned in the desired location, the power supply **702** may be powered to pass a current through the electrical conduits **700a, b**. The electrolytically detachable coupler **724a, b** may disintegrate due to electrolytic erosion and thus detach from the implant **706** as shown in FIG. **53**. The implant **706** may then be left deployed in position within the desired location in the patient's body, for example,

the implant **706** may be left deployed to the patient's heart valve. The delivery apparatus may then be removed from the patient's body as disclosed herein.

[0289] The electrolytically detachable coupler **724a, b** may be disintegrated after assessing implant anchoring and hemodynamic stability. The electrolytically detachable coupler **724a, b** may provide a strong, rigid attachment that may be capable of withstanding forces involved in repositioning and resheathing an implant if desired. Further, the use of an electrolytically detachable coupler **724a, b** may reduce the overall length and size of the deployment mechanism.

[0290] FIG. **54** illustrates a variation of the embodiment shown in FIGS. **50-53**, in which the electrical conduit **700a** may be coupled to an electrical terminal **734** that is positioned on the elongate shaft. For example, as shown in FIG. **54**, the electrical terminal **734** may be positioned on the nose cone shaft **720**, although in other embodiments other locations for the electrical terminal **734** may be utilized. For example, the electrical terminal **734** may be positioned on a portion of an inner assembly, rail assembly, mid shaft assembly, or outer sheath assembly, as desired. The electrical terminal **734** may couple to the electrical conduit **700a** to form a return path for the electrical conduit **700b** that passes to the electrolytically detachable coupler **736a, b**. As such, in such an embodiment, the electrical terminal **704** shown in FIG. **49** does not need to be used, because an electrical terminal **734** on the elongate shaft forms a return path for the electrical circuit. The electrolytically detachable coupler **736a, b** may comprise a first portion of an electrical circuit, and the electrical terminal **734** may be coupled to the elongate shaft and form a second portion of the electrical circuit. Further, as shown in FIG. **54**, the electrolytically detachable coupler **736a, b** may be in the form of tethers that extend to the proximal ends of the implant **706** and couple to the implant **706**. As such, as the outer sheath **716** and outer retention ring **718** are retracted, the implant **706** may deploy to its full expanded size. The electrolytically detachable coupler **736a, b**, however, may remain coupled to the implant **706** until it is desired for the implant **706** to detach from the elongate shaft. The power supply may then be energized to pass current through the electrical conduits to disintegrate the electrolytically detachable coupler **736a, b** due to electrolytic erosion.

[0291] In certain embodiments, the electrolytically detachable coupler may be utilized such that one or more of the outer sheath **716** or the outer retention ring **718** does not need to be utilized. For example, the electrolytically detachable coupler may retain the implant **706** with such force that expansion of the implant **706** is restrained by the electrolytically detachable coupler. FIG. **55**, for example, illustrates an embodiment in which an electrolytically detachable coupler **738** extends over an outer surface of the implant **706**. The electrolytically detachable coupler **738** may comprise a coil that extends over the implant **706** as shown in FIG. **55** or may have a variety of other shapes as desired (e.g. a sheath, longitudinal slats, a mesh, among others). The electrolytically detachable coupler **738**, however, may operate in a similar manner as discussed regarding the other electrolytically detachable couplers disclosed herein, namely, the electrolytically detachable coupler **738** may disintegrate due to electrolytic erosion and may detach from the portion of the implant **706**. The implant **706** may then expand upon disintegration of the electrolytically detachable coupler **738**. A variety of other configurations of electrolytically detachable couplers may be utilized as desired.

[0292] FIGS. **56-57** illustrate an embodiment in which an electrically detachable coupler **740** may be utilized that disintegrates due to heat caused by an electrical current passed through the electrically detachable coupler **740**. For example, electrical conduits, similar to the conduits **700a, 700b**, may be coupled to a power supply **702** and may pass a current through the electrically detachable coupler **740**. The electrically detachable coupler **740** may be made of a material that disintegrates due to the heat energy provided by the passage of current through the electrically detachable coupler **740**, working in a similar manner as a fuse or the like. The electrically detachable coupler **740** may disintegrate at a desired time to detach from the implant **742**. The implant **742** may be configured similarly as the implant **70** or any other implant disclosed herein.

[0293] The electrically detachable coupler **740** may couple to the implant **70** in a manner shown in

the enlarged view of FIG. 57 (at which reference number **744** points to in FIG. 56). The electrically detachable coupler **740** may comprise a loop passing around a coupler **744** on a portion of the implant **742** (for example, a proximal end coupler of the implant **742** as shown in FIG. 57). The loop may couple to the conduits **700a**, **700b**, and as current is passed through the conduits **700a**, **700b** and the loop, the electrically detachable coupler **740** may disintegrate due to heat and may detach from the implant **742**. The conduit **700a** may comprise a first portion of an electrical circuit coupled to a first portion of the electrically detachable coupler **740** and the conduit **700b** may comprise a second portion of an electrical circuit coupled to a second portion of the electrically detachable coupler **740** (with the first and second portions of the electrically detachable coupler **740** comprising parts of the loop). The conduits **700a**, **700b** may both extend along the elongate shaft. Other configurations of couplers **740**, including other locations of coupling, may be utilized as desired.

[0294] FIGS. 58-59 illustrate an embodiment of an electrically detachable coupler **746** including one or more electromagnets **748**. The electromagnets **748** may be configured to magnetically attract a portion of an implant **750**, which may be configured similarly as the implant **70**, yet may include magnetically responsive materials **752** that couple to the electromagnets **748**. The one or more electromagnets **748** may be coupled to electrical conduits that may be configured similarly as the conduits **700a**, **700b** and that extend along the elongate shaft. As shown in FIG. 59, upon deactivation of power to the one or more electromagnets **748**, the electrically detachable coupler **746** may detach from the implant **750**.

[0295] The electrically detachable couplers disclosed herein may be utilized with any embodiment of delivery system disclosed herein. The electrically detachable couplers, for example, may be utilized with a delivery apparatus having an elongate shaft. The elongate shaft may include a rail shaft configured to be steerable and a shaft configured to move relative to the rail shaft. The shaft may be coupled to the electrically detachable coupler. The elongate shaft in embodiments may include an outer sheath having an outer lumen and a proximal end and a distal end, with at least a portion of the outer sheath surrounding the implant retention area, and wherein the shaft is positioned within the outer lumen and the rail shaft is positioned within the outer lumen. The outer sheath may be configured to retract relative to the shaft to uncover at least a portion of the implant. The electrically detachable couplers may be utilized in lieu of, and in the same position as, the inner retention ring **40** as shown in FIGS. 2A-2C for example.

[0296] The electrically detachable couplers may be controlled by a processor, as disclosed herein, which may operate to actuate the electrically detachable couplers and thus detach at least a portion of the implant from the electrically detachable couplers. Such operation may occur in response to a user's input, via a control device or the like, or the processor may automatically actuate the electrically detachable couplers as desired. For example, the processor may actuate the electrically detachable couplers in response to a sensor reading (for example one of the sensors as disclosed herein), or in response to a program, indicating that the electrically detachable couplers are to be actuated. The processor may be configured to automatically actuate the electrically detachable couplers and deploy the implant.

[0297] The power supply for the electrically detachable couplers may be integrated with a controller, for example a controller **530** as shown in FIG. 18. The electrical conduits for the electrically detachable couplers may extend to the controller. The processor may be configured to control the power supply to control the electrically detachable couplers.

[0298] A method that may utilize the embodiments of FIGS. 49-59 may include extending a delivery apparatus within a portion of a patient's body to deliver an implant to a body location. At least a portion of the implant may be detached from an electrically detachable coupler within the patient's body. The implant may be any form of implant disclosed herein, including a prosthetic replacement heart valve, including an expandable prosthetic replacement heart valve. The implant may be a self-expanding prosthetic replacement heart valve, and may be a prosthetic mitral valve.

Other forms of implants (including implants for repair or replacement of a heart valve) may be utilized as desired. The electrically detachable coupler may retain at least a portion of the expandable prosthetic replacement heart valve in a compressed state. The electrically detachable coupler may be coupled to a proximal end of the expandable prosthetic replacement heart valve. Detaching at least the portion of the implant from the electrically detachable coupler may allow the portion of the implant to expand. The implant may be deployed to the body location as disclosed herein.

[0299] From the foregoing description, it will be appreciated that an inventive product and approaches for implant delivery systems are disclosed. While several components, techniques and aspects have been described with a certain degree of particularity, it is manifest that many changes can be made in the specific designs, constructions and methodology herein above described without departing from the spirit and scope of this disclosure.

[0300] Certain features that are described in this disclosure in the context of separate implementations can also be implemented in combination in a single implementation. Conversely, various features that are described in the context of a single implementation can also be implemented in multiple implementations separately or in any suitable subcombination. Moreover, although features may be described above as acting in certain combinations, one or more features from a claimed combination can, in some cases, be excised from the combination, and the combination may be claimed as any subcombination or variation of any subcombination.

[0301] Moreover, while methods may be depicted in the drawings or described in the specification in a particular order, such methods need not be performed in the particular order shown or in sequential order, and that all methods need not be performed, to achieve desirable results. Other methods that are not depicted or described can be incorporated in the example methods and processes. For example, one or more additional methods can be performed before, after, simultaneously, or between any of the described methods. Further, the methods may be rearranged or reordered in other implementations. Also, the separation of various system components in the implementations described above should not be understood as requiring such separation in all implementations, and it should be understood that the described components and systems can generally be integrated together in a single product or packaged into multiple products. Additionally, other implementations are within the scope of this disclosure.

[0302] Conditional language, such as “can,” “could,” “might,” or “may,” unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include or do not include, certain features, elements, and/or steps. Thus, such conditional language is not generally intended to imply that features, elements, and/or steps are in any way required for one or more embodiments.

[0303] Conjunctive language such as the phrase “at least one of X, Y, and Z,” unless specifically stated otherwise, is otherwise understood with the context as used in general to convey that an item, term, etc. may be either X, Y, or Z. Thus, such conjunctive language is not generally intended to imply that certain embodiments require the presence of at least one of X, at least one of Y, and at least one of Z.

[0304] Language of degree used herein, such as the terms “approximately,” “about,” “generally,” and “substantially” as used herein represent a value, amount, or characteristic close to the stated value, amount, or characteristic that still performs a desired function or achieves a desired result. For example, the terms “approximately,” “about,” “generally,” and “substantially” may refer to an amount that is within less than or equal to 10% of, within less than or equal to 5% of, within less than or equal to 1% of, within less than or equal to 0.1% of, and within less than or equal to 0.01% of the stated amount. If the stated amount is 0 (e.g., none, having no), the above recited ranges can be specific ranges, and not within a particular % of the value. For example, within less than or equal to 10 wt./vol. % of, within less than or equal to 5 wt./vol. % of, within less than or equal to 1 wt./vol. % of, within less than or equal to 0.1 wt./vol. % of, and within less than or equal to 0.01

wt./vol. % of the stated amount.

[0305] Some embodiments have been described in connection with the accompanying drawings. The figures are drawn to scale, but such scale should not be limiting, since dimensions and proportions other than what are shown are contemplated and are within the scope of the disclosed inventions. Distances, angles, etc. are merely illustrative and do not necessarily bear an exact relationship to actual dimensions and layout of the devices illustrated. Components can be added, removed, and/or rearranged. Further, the disclosure herein of any particular feature, aspect, method, property, characteristic, quality, attribute, element, or the like in connection with various embodiments can be used in all other embodiments set forth herein. Additionally, it will be recognized that any methods described herein may be practiced using any device suitable for performing the recited steps.

[0306] While a number of embodiments and variations thereof have been described in detail, other modifications and methods of using the same will be apparent to those of skill in the art. Accordingly, it should be understood that various applications, modifications, materials, and substitutions can be made of equivalents without departing from the unique and inventive disclosure herein or the scope of the claims.

Claims

1. A delivery system for delivering a medical device to a native heart valve within a patient's body, the delivery system comprising: a delivery apparatus configured to deliver the medical device to the native heart valve within the patient's body, the delivery apparatus including an elongate shaft configured to retain the medical device; a nose cone positioned distal to the elongate shaft; one or more proximity sensors positioned on the nose cone and configured to sense a lateral distance between the nose cone and an inner wall of the patient's vasculature; at least one motor configured to deflect the elongate shaft within the patient's vasculature; and a processor configured to control the at least one motor to deflect the elongate shaft within the patient's vasculature based on signals from the one or more proximity sensors of the lateral distance between the nose cone and the inner wall of the patient's vasculature while the elongate shaft is continuing to be advanced through the patient's vasculature.
2. The delivery system of claim 1, further comprising one or more pull wires for the at least one motor to operate to deflect the elongate shaft within the patient's vasculature.
3. The delivery system of claim 1, further comprising an output device comprising one or more of a display screen, a light, a speaker, or a haptic device, and wherein the processor is configured to provide an output that is provided as an indicator on the output device, and wherein the indicator indicates a condition of the delivery apparatus or a condition of the patient's body.
4. The delivery system of claim 1, wherein the processor is configured to control the at least one motor to avoid or retract from the inner wall of the patient's vasculature based on the signals.
5. The delivery system of claim 1, wherein the processor is configured to control the at least one motor to deploy the medical device from the elongate shaft to the native heart valve.
6. The delivery system of claim 1, wherein the one or more proximity sensors are configured to sense the lateral distance between the nose cone and the inner wall of the patient's vasculature utilizing ultrasound signals, echo signals, or visual identification.
7. The delivery system of claim 1, further comprising a handle coupled to a proximal end of the elongate shaft, and further comprising a power source positioned within the handle and configured to provide power to the processor and the at least one motor.
8. The delivery system of claim 1, wherein the elongate shaft includes a retractable capsule configured to retain the medical device.
9. The delivery system of claim 8, wherein the processor is configured to control the at least one motor to retract the retractable capsule.

- 10.** The delivery system of claim 1, further comprising the medical device, the medical device including an expandable frame and a tissue-based valve body supported by the expandable frame.
- 11.** A delivery system for delivering a medical device to a native heart valve within a patient's body, the delivery system comprising: a delivery apparatus configured to deliver the medical device to the native heart valve within the patient's body, the delivery apparatus including an elongate shaft configured to retain the medical device; a nose cone positioned distal to the elongate shaft; one or more sensors positioned on the nose cone and configured to sense a spatial relationship between the nose cone and an inner wall of the patient's vasculature; at least one motor configured to deflect the elongate shaft within the patient's vasculature; and a processor configured to control the at least one motor to deflect the elongate shaft within the patient's vasculature based on signals from the one or more sensors of the spatial relationship between the nose cone and the inner wall of the patient's vasculature while the elongate shaft is continuing to be advanced through the patient's vasculature.
- 12.** The delivery system of claim 11, further comprising one or more pull wires for the at least one motor to operate to deflect the elongate shaft within the patient's vasculature.
- 13.** The delivery system of claim 11, wherein the elongate shaft includes a retractable capsule configured to retain the medical device.
- 14.** The delivery system of claim 13, wherein the processor is configured to control the at least one motor to retract the retractable capsule.
- 15.** The delivery system of claim 11, wherein the processor is configured to control the at least one motor to avoid or retract from the inner wall of the patient's vasculature based on the signals.
- 16.** A delivery system for delivering a medical device to a native heart valve within a patient's body, the delivery system comprising: a delivery apparatus configured to deliver the medical device to the native heart valve within the patient's body, the delivery apparatus including an elongate shaft having a retractable capsule configured to retain the medical device; one or more sensors positioned on the retractable capsule and configured to sense a spatial relationship between the retractable capsule and an inner wall of the patient's vasculature; at least one motor configured to deflect the elongate shaft within the patient's vasculature; and a processor configured to control the at least one motor to deflect the elongate shaft within the patient's vasculature based on signals from the one or more sensors of the spatial relationship between the retractable capsule and the inner wall of the patient's vasculature while the elongate shaft is continuing to be advanced through the patient's vasculature.
- 17.** The delivery system of claim 16, further comprising one or more pull wires for the at least one motor to operate to deflect the elongate shaft within the patient's vasculature.
- 18.** The delivery system of claim 16, wherein the one or more sensors comprise proximity sensors.
- 19.** The delivery system of claim 16, wherein the one or more sensors are configured to sense the spatial relationship between the retractable capsule and the inner wall of the patient's vasculature utilizing ultrasound signals, echo signals, or visual identification.
- 20.** The delivery system of claim 16, wherein the processor is configured to control the at least one motor to avoid or retract from the inner wall of the patient's vasculature based on the signals.
-