

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250282131

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

KOHLER; Herbert B. et al.

MULTI-LAYER COMPOSITE ALIGNMENT DEVICE

Abstract

Disclosed is an alignment device capable of making high-speed adjustments to successive top sheets relative to underlying backings as they are conveyed toward an application station for lamination, in order to ensure that each successive top sheet is properly aligned prior to being laminated to its backing. In desirable embodiments, the alignment device can achieve successive angular corrections at a rate of at least 13,000 top sheets per hour.

Inventors: KOHLER; Herbert B. (Uniontown, OH), WICK; Stefan (Oberbuchsiten, CH)

Applicant: KOHLAM, LLC (Uniontown, OH)

Family ID: 1000008619396

Appl. No.: 19/195924

Filed: May 01, 2025

Related U.S. Application Data

parent US continuation 18763092 20240703 parent-grant-document US 12319044 child US 19195924

us-provisional-application US 63626359 20240129

Publication Classification

Int. Cl.: B32B38/18 (20060101); B32B37/18 (20060101); B65H9/16 (20060101)

U.S. Cl.:

CPC B32B38/1833 (20130101); B32B37/18 (20130101); B65H9/166 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/763,092, filed Jul. 3, 2024, which claims the benefit of U.S. Provisional Patent Application No. 63/626,359, filed Jan. 29, 2024, the contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0002] Multi-layer composites (an example of which is shown schematically in FIG. 1) are often used to produce high-end packaging for goods. With reference to FIGS. 1-2 (FIG. 2 depicting a cross-sectional view along the line 2-2 in FIG. 1), an example of a multi-layer composite **100** is shown, and includes a top sheet **102** (or first sheet) disposed on a backing **104** (or second sheet). Notably, in the illustrated embodiment, the dimensions of the top sheet **102** (i.e., length and width) are substantially the same as that of the backing **104**. However, the dimensions of the top sheet **102** may differ with respect to those of the backing **104**.

[0003] The top sheet **102** is adhered to the backing via an adhesive **106** (the thickness of the adhesive **106** being exaggerated in FIG. 2 for illustrative purposes). The top sheet **102** may have high-quality indicia printed thereon (e.g., via flexography, photogravure or offset printing) such that after the top sheet **102** is adhered to the backing **104**, the multi-layer composite **100** can be folded to produce packaging (e.g., a gift box) with the high-quality indicia displayed on its external surface.

[0004] Moving now to FIG. 3, one example of a laminating machine **108** for manufacturing the multi-layer composite **100** is shown schematically. The laminating machine **108** includes first and second conveyors **110**, **112** (e.g., conveyor belts, rollers, etc.) for respectively conveying the top sheet **102** and the backing **104** from respective upstream sources (not shown) towards an application station **114** where the top sheet **102** is adhered to the backing **104**. Of note, a plurality of top sheets **102** are shingled with respect to one another and conveyed in this manner (on the first conveyor **110**) toward the application station **114**. Additionally, a plurality of backings **104** are spaced apart from one another (in the conveyance direction) on the second conveyor **112** and conveyed in this manner towards the application station **114**. The backings **104** may have the adhesive **106** (not shown) applied on a surface thereof prior to reaching the application station **114**. Notably, while FIG. 3 depicts separate backings **104** being conveyed via the second conveyor **112**, it is contemplated that a continuous backing web can be conveyed along the second conveyor **112**, where discrete portions thereof are cut (prior to entering the application station **114**) to form discrete backings, each corresponding to a respective top sheet **102** that is to be applied thereto.

[0005] Prior to adhering each top sheet **102** to the respective backing **104**, the top sheet **102** must be properly aligned relative thereto so that the top sheet **102** and its backing **104** will be affixed in the correct alignment. In the illustrated example, the dimensions of the top sheet **102** and the backing **104** are the same, and thus the desired alignment will require that the top sheet **102** be disposed and oriented in register with the backing **104** so that their adjacent edges are essentially co-extensive. While the backings **104** typically will be uniformly and precisely aligned (usually centered with respect to a center line **116** of the machine **108**) on the second conveyor **112**, that is not usually the case for the respective top sheets **102** advancing along the first conveyor **110**.

[0006] For example, with respect to FIGS. 4A-4C (depicting schematic top views of a top sheet **102** and the associated backing **104**), the top sheet **102** may be: (1) angularly offset with respect to the backing **104** (i.e., FIG. 4A), as initially supplied along the first conveyor **110**; (2) laterally offset with respect to the backing **104** (i.e., FIG. 4B) as initially supplied; and/or longitudinally offset with respect to the backing **104** (i.e., FIG. 4C) as initially supplied. As such, when the top sheet **102** is angularly offset, its own center line may be at an oblique angle relative to the center line **116** of

the machine **108**; and thus to that of the associated backing **104**. Lateral offset refers to the top sheet **102** being laterally displaced, i.e., along a direction perpendicular to the center line **116** of the machine **108** (and thus to the conveyance direction), when the top sheet **102** and the backing **104** are properly angularly aligned. Longitudinal offset refers to the top sheet **102** being either advanced or retarded relative to the associated backing **104** along the conveyance direction when they are properly angularly aligned.

[0007] It is routine for the shingled top sheets **102** riding along the first conveyor **110** toward the application station **114** to be misaligned relative to the respective intended backings **104** riding along the second conveyor toward that station **114**. There is a need for an alignment device that can adjust one or more of the angular, lateral and longitudinal alignment of each top sheet **102** as it advances toward the application station **114**, so that upon arrival at that station **114** it will be properly aligned with respect to the intended backing **104**, angularly, laterally and longitudinally, prior to their being adhered together. When the two have the same shape and dimensions, typically proper alignment will mean that the top sheet **102** will be in register with the backing **104**.

SUMMARY

[0008] In accordance with one aspect of the present invention, an alignment device is provided for aligning a top sheet relative to a corresponding backing. The alignment device includes a driven roller aligned along a roller axis. The driven roller is both translatable and pivotable within predefined limits in a plane comprising the roller axis. The alignment device further includes a first frame that is both translatable and pivotable together with the driven roller.

[0009] In accordance with another aspect of the present invention, a laminating apparatus includes a first conveyance path along which a top sheet is conveyed in use, and a second conveyance path along which a backing is conveyed in use. The laminating apparatus further includes an alignment device for aligning the top sheet relative to the backing. The alignment device includes a driven roller aligned along a roller axis. The driven roller is both translatable and pivotable within predefined limits in a plane comprising the roller axis.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. **1** shows an example multilayer composite used to produce high-end packaging for goods;

[0011] FIG. **2** is a cross section of the multilayer composite shown in FIG. **1**;

[0012] FIG. **3** shows a schematic diagram of an example laminating machine for manufacturing a multi-layer composite;

[0013] FIGS. **4A-4C** depict schematic top views of a top sheet and an associated backing sheet used to make a multi-layer composite as herein disclosed, in different states of misalignment;

[0014] FIG. **5** shows a first embodiment of an alignment device as herein disclosed, fully assembled;

[0015] FIG. **6** shows an exploded view of the alignment device shown in FIG. **5**;

[0016] FIGS. **7** and **8** are top and perspective views, respectively, of a nested frame assembly of the example alignment device of FIG. **5**, having outer and intermediate frames **206**, **202**;

[0017] FIGS. **9** and **10** show a roller assembly associated with an inner frame **204** of a nested frame assembly, wherein in FIG. **9** the roller assembly is separated from the inner frame and in

[0018] FIG. **10** it is attached to the inner frame;

[0019] FIGS. **11** and **12** are perspective and top views, respectively, of a nested frame assembly having outer, intermediate and inner frames **206**, **202** and **204**, as well as the aforementioned roller assembly **208**;

[0020] FIG. **13** shows a schematic diagram of an example laminating machine for manufacturing a

multi-layer composite, wherein an alignment device is installed at or near an end of a first conveyor of the laminating machine, upstream of an application station where top sheets riding along the first conveyor are to be laminated to backings riding along a second conveyor;

[0021] FIGS. **14-17** schematically illustrate example steps of aligning an initially mis-aligned top sheet using an alignment device as herein disclosed;

[0022] FIGS. **18-19** schematically illustrate a second embodiment of an alignment device as herein disclosed;

[0023] FIGS. **20** and **21** show schematic representations of different states of pivotable orientation of the roller assembly **208** in the alignment device shown in FIGS. **18-19**; and

[0024] FIG. **22** illustrates an example rotary guide bearing as can be used in the aforementioned second-embodiment alignment device to facilitate the pivotable movement of the roller assembly as shown in FIGS. **20-21** above.

DESCRIPTION OF EXAMPLE EMBODIMENTS

[0025] In the example misalignments shown in FIGS. **4A-4C**, both the top sheet **102** and the backing **104** are shown as rectangular having linear edges, and having substantially the same dimensions. But this is not required, and it will be appreciated that different-sized and shaped top sheets **102** and backings **104** can be used (including different from one another), the only requirement being that the desired final alignment between top sheet **102** and backing **104** has been determined in advance so that the alignment device described herein can be operated to place each top sheet **102** in proper alignment prior to adhering it to the associated backing **104**.

[0026] With reference to FIGS. **5-6**, illustrated is a first embodiment of an alignment device **200** which can be used to correct misalignment (as described above) between the top sheet **102** and the backing **104**. Notably, this alignment device **200** may be incorporated or retrofitted into a conventional laminating machine **108** such as that shown schematically in FIG. **3** (see FIG. **13**). In the illustrated embodiment, as best seen in FIG. **6** (which is an exploded view) the alignment device **200** has a nested frame assembly, including a first frame **202**, a second frame **204**, and a third frame **206**. Each of these frames **202**, **204**, **206** is shown as rectangular and open at its center to permit another element to reside therein. More specifically, the second frame **204** is received in the central opening of the first frame **202**, which is received in the central opening of the third frame **206**. Accordingly, in the illustrated embodiment the first, second, and third frames **202**, **204**, **206** are intermediate, inner, and outer frames, respectively, of the nested frame assembly in the illustrated embodiment. Additionally, the intermediate, inner, and outer frames **202**, **204**, **206** are coplanar when assembled as-illustrated in FIG. **5**, but this is not required.

[0027] The alignment device **200** further includes a roller assembly **208** attached to the inner frame **204**. The inner frame **204** is movable via a first actuator **210** and/or a second actuator **212** to correct angular misalignment of the top sheet **102** with respect to a corresponding backing **104**, as will be further discussed below. As further shown, a plate **213** is provided and includes an aperture **215**. In use, the alignment device **200** is installed in or to the laminating machine **108** so that the outer frame **202** of the alignment device **200** is fixed with respect to the laminating machine, preferably so that its long axis (e.g. a centerline parallel to its length dimension) is parallel to a cross-machine direction of the laminating machine **108**, and perpendicular to a conveyance direction thereof. Also as-installed, the upper surface of the plate **213** will be substantially co-planar with the upper surface of the first conveyor **110**. In this manner, as that conveyor **110** advances top sheets **102** forward, those sheets are conveyed onto an area above the plate **213**; i.e. over the upper surface of that plate **213**. The aperture **215** in the plate **213** is aligned with the roller assembly **208**, whose roller(s) thus will engage with the underside surface of top sheets **102** as they are advanced above the plate **213**. Engagement of each top sheet **102** by the roller assembly **208** will enable the latter to make adjustments to the alignment of that top sheet **102** as it passes over the plate **213**, by correspondingly adjusting the angle and orientation of the inner frame **204** that carries the roller assembly as hereafter described.

[0028] Moving now to FIGS. 7-8, the intermediate frame **202** is received within the central opening of the outer frame **206** and is movably secured therein via a sliding assembly. In the illustrated example, the sliding assembly includes a pair of rails **214**, each configured to slidably receive a corresponding pair of carriages **216** therein. Notably, the pair of rails **214** are provided on and secured (e.g., via bolts, screws, etc.) to opposing, inner edges of the outer frame **206**, and each pair of carriages **216** is provided on and secured to opposite, outer edges of the intermediate frame **202**. Accordingly, each pair of carriages **216** is configured to be received within and slide along their corresponding rail **214** to permit linear translation of the intermediate frame **202** with respect to the outer frame **206** along a single direction, which will be the cross-machine direction; i.e., perpendicular to the center line **116** (and to the conveyance direction) of the laminating machine **108** when viewed from above.

[0029] Returning to FIG. 6, the outer and intermediate frames **206**, **202** have respective through-holes **218**, **220** formed therein in registry with one another (when assembled). Notably, these through-holes **218**, **220** define a common path configured to receive a shaft **222** of the first actuator **210** (as shown in FIGS. 7-8). When assembled, the first actuator **210** is positioned such that its shaft **222** successively penetrates both the through-holes **218**, **220** starting from outside the outer frame **206**, so that a distal end of the shaft **222** emerges just within the central opening of the intermediate frame **202**. Thereafter, a bracket **224** can be assembled to the distal end of the shaft **222** (opposite the actuator's motor) that has emerged within the central opening of the intermediate frame **202**. As shown, the bracket **224** can be substantially U-shaped, having corresponding (i.e., coaxial) apertures formed in opposing walls thereof extending inward within the central opening of the intermediate frame **202**, which apertures are adapted to receive a hinge-pin as discussed further below. Alternatively, the bracket **224** can be affixed to an interior edge of the intermediate frame **202** in another way; e.g. via adhesive, fasteners, welding, etc. Likewise, the distal end of the shaft of the first actuator **210** can be affixed to the intermediate frame **202** (e.g. to an exterior edge thereof, opposite to the location of the bracket **224**) other than via the bracket **224**, such as via adhesive, other fasteners, welding, etc.

[0030] The first actuator **210** is operable to actuate the intermediate frame **202** in order to translate it along the cross-machine direction (as described above) within the confines of the outer frame **206** within which it is nested. In the illustrated embodiment, the first actuator **210** is a linear actuator that translates the intermediate frame **202** linearly (in the cross-machine direction) with respect to the outer frame **206**, which can be stationary and fixed relative to the laminating machine **108**. However, it is contemplated that other conventional actuators may be used to provide adjustable linear translation of the intermediate frame **202**.

[0031] Moving N on to FIGS. 9-10, the roller assembly **208** includes one or more rollers **226** (which are coaxial in case of two or more) provided on (i.e., fixed to) a common axle **228**, which is rotatable via a motor (not shown). The motor can be integrated and housed within the inner frame **204**, e.g. so that its drive shaft is coupled to, or forms an extension of, the common axle **228** in order to drive that axle. Alternatively, the motor can be located remotely and coupled to the common axle **228** via a suitable gear train and/or belts or chains in order to drive that axle. Accordingly, when the associated motor is activated, the roller(s) **226** is/are driven in rotation via the axle **228**, and at the same speed when there are two or more such rollers. Notably, in the illustrated embodiment, there is a single roller **226** having a radially recessed central region that will not contact the overlying top sheet **102** in-use. However, there may be two (or more) such rollers **226** axially spaced from one another and which are separately manufactured and fixed on the common axle **228**. Alternatively, it is contemplated that the rollers **226** need not be placed on a common axle. For example, rollers **226** may be placed on distinct, preferably co-axial axles that are separately driven by respective motors. Whichever of the foregoing configurations is used, the result will be that each top sheet **102** will be engaged at two distinct locations, spaced from one another in a direction along the length of the axle **228**, preferably colinear with a pivot axis of that

axle (described below). Engaging the top sheet **102** at two distinct, spaced locations can impart better angular-adjustment control over each such sheet **102** as the roller(s) **226** pivot (discussed below). That is, engaging two distinct locations on the top sheet **102**, spaced from one another, to rotate the sheet **102** either clockwise or counter-clockwise, as the case may be, will yield greater rotational control and adjustment resolution than would be achieved if the torque to induce such rotation were to be introduced substantially by a single roller at a single (or center-focused) location. Alternatively, though less preferably, a single uniform-diameter roller **226** can be used to engage the top sheets **102**.

[0032] As further shown, the roller assembly **208** is attached to the inner frame **204** via mounts **230**. Notably, the mounts **230** are located on opposite sides of the roller(s) **226**, respectively, and rotatably support their common axle **228**, or in selected embodiments respective but coaxial axles for distinct rollers. Moreover, a tab **232** protrudes outwards from an outer edge or surface of the inner frame **204** (i.e., at one of its longitudinal ends) and has an aperture formed therein. With reference to FIGS. **11-12**, the bracket **224** (affixed to either the distal end of the shaft **222** of the first linear actuator **210**, or to an interior surface of the intermediate frame **202**) can be pivotally affixed to the tab **232** so that the entire inner frame **204** can pivot relative to a pivot axis **236** defined at the bracket **224**. Specifically, the U-shaped bracket as shown in the illustrated embodiment receives the tab **232** between the opposing walls thereof such that the apertures in the opposing walls of the bracket **224** and the aperture in the tab **232** are aligned. With these apertures aligned (as shown in FIG. **12**), a hinge pin **234** is inserted therein to pivotally link them together and establish a hinged-connection. With the hinge pin **234** in place, the inner frame **204** is pivotable about the pivot axis **236** via activation of the second actuator **212** (shown schematically in FIG. **12**). Because the hinged-connection is provided at a longitudinal end of the inner frame **204**, the pivot axis **236** is laterally offset with respect to the roller assembly **208**.

[0033] The second actuator **212** may be a linear actuator (similar to the first actuator **210**), having a shaft whose distal end is secured to the inner frame **204** remote from the pivot axis **236** so that actuation thereof will induce a pivoting movement of the inner frame **204** relative to the pivot axis **236**. The second actuator **212** can be affixed to the intermediate frame so that it remains fixed relative thereto as the intermediate frame (and correspondingly, the inner frame nested therein) is (are) translated along the cross-machine direction via the first actuator **210**. Notably, the bracket **224** both can be secured to the intermediate frame **202** in order to supply translational movement thereto upon actuation of the first actuator **210**, and also provides the pivot point for the inner frame **204** (and thus the roller assembly **208** therein). In this manner, both the intermediate and inner frames **202**, **204** will translate together as a single sub-assembly upon actuation of the first actuator **210**, with the pivot point for the inner frame **204** also being fixed relative to the intermediate and inner frames **202**, **204** as they translate in the cross-machine direction relative to the outer frame **206**. In this manner, both the intermediate and inner frames **202**, **204** will translate together, whereas the inner frame **204** will be independently pivotable relative to (and within the confines of) the intermediate frame **202**, regardless of the cross-machine-direction position thereof based on the state of the first actuator **210**.

[0034] As noted above, the second actuator **212** may be secured to the intermediate frame **202** in order to translate together therewith (and thus maintain its registration with the inner frame **204**). Alternatively, the second actuator **212** may be secured in a different manner that allows the second actuator **212** to translate together with the inner frame **204** when the first actuator **210** is activated.

[0035] The plate **213** is attached to the inner frame **204** and is oriented such that its aperture **215** is aligned with the rollers **226**, which protrude just through that aperture **215** so that they may engage a top sheet **102** passing over the plate **213**. Because the plate **213** is attached to the inner frame **204**, the plate **213** likewise translates and/or pivots in accordance with movement of the inner frame **204** subject to the operation of both the first and second actuators **210**, **212**. Alternatively, it is contemplated that the plate **213** can be attached to the intermediate frame **202** or the outer frame

206, so long as the aperture **215** is dimensioned as to not impede movement of the roller assembly **208** during translation and/or pivoting movement(s).

[0036] In sum, the nested frame assembly as described above facilitates both linear translation of the roller assembly **208** in a direction transverse to the conveyance direction of the top sheet (i.e., in the cross-machine direction), and pivoting of the same about the pivot axis **236**, both with respect to the stationary outer frame **206**. The degrees of translation and pivotal movement for the roller assembly also are confined to be within predefined limits. For example, in the illustrated embodiment the degree of pivoting of the roller assembly **208** is confined within the central opening of the intermediate frame, relative to its pivot axis **236**. Whereas the degree of translation of the roller assembly **208** is confined within the range that the intermediate frame **202** (and the inner frame **204** nested therein) can translate within the central opening of the outer frame **206**. Notably, both the translation and the pivotal movement of the roller assembly **208** also are confined within a plane that includes the rotational axis of the roller(s) **226** of the roller assembly **208**.

[0037] When the first actuator **210** is activated, the intermediate frame **202** linearly translates within the central opening of the outer frame **206**, with its movement guided and bounded by the slide assembly. As the first actuator **210** is also connected to the inner frame **204** (i.e., via the connection between the bracket **224** and the tab **232**), the inner frame **204** (and thus the roller assembly **208**) simultaneously translates together with the intermediate frame **202** in the cross-machine direction. Moreover, when the second actuator **212** is activated, the inner frame **204** (and thus the roller assembly **208**) is pivoted about the pivot axis **236** within the central opening of the intermediate frame **202**. In other words, the inner frame **204** (and thus the roller assembly **208**) is capable of both linear and pivoting movement, whereas the intermediate frame **202** is only capable of linear movement with respect to the outer frame **206**, which remains stationary.

[0038] A method of using the alignment device **200** to correct an orientation of an incoming top sheet to yield the desired alignment/registration relative to its corresponding backing will now be described. With reference to FIG. **13**, the alignment device **200** is installed at (or near) the end of the first conveyor **110** along the conveyance direction, just upstream from the application station **114**. Preferably the alignment device **200** is located at an inclined portion of the first conveyor **110** that is angled relative to the second conveyor **112** (which is substantially planar) along a convergent path relative to the second conveyor **112**. As schematically shown, at least one nip roller **120** is aligned with the alignment device **200** in order to engage an opposite, upper surface of an incoming top sheet **102** relative to the roller(s) **226** of the underlying roller assembly **208**. In operation, the top sheet **102** proceeds through the nip defined between the nip roller **120** and the roller(s) **226** of the alignment device **200**, in order that the latter will engage and be operative to drive the top sheet **102** to make the adjustments described herein. The nip roller **120** may be actively rotatable by a corresponding motor, or it may be a passive roller.

[0039] As previously mentioned, the incoming backing **104** is typically properly aligned. Preferably, a (longitudinal) center line of the backing **104** is aligned relative to the (longitudinal) center line of the machine (e.g., in a common vertical plane when viewed from above). Accordingly, to effectuate the desired registration between an incoming top sheet **102** and its corresponding backing **104**, the incoming top sheet **102** must be aligned relative to the associated backing **104**. In conventional embodiments wherein the top sheet **102** and backing **104** are laterally symmetrical (e.g., rectangular) and the backing **104** has its center line aligned with the machine center line **116**, then the machine center line **116** can be used as a landmark against which the top sheet **102** itself must also be aligned and centered. In the case of identically dimensioned, rectangular top sheets **102** and backings **104**, it also means that the leading edge of the top sheet **102** must be aligned relative to the leading edge of the backing **104** (e.g., in a common vertical plane when viewed from above) prior to being affixed in the application station **114**.

[0040] The following method description relies on aligning the center line **102a** of each respective top sheet **102** with the center line **116** of the machine as described above to achieve suitable angular

and lateral alignment. This is valid in the case of laterally symmetric (e.g., rectangular) top sheets **102** wherein the underlying backings **104** also are aligned laterally and angularly with the machine center line **116** in a known way. But it is to be recognized that the machine center line **116** is an arbitrary landmark against which to achieve such alignment, and that any suitable landmark can be used to achieve proper alignment so long as the landmark has been pre-calibrated with the lateral and angular alignment of the underlying backing **104** on the second conveyor **112**. Likewise, utilizing the center line **102a** of the top sheets **102** also is arbitrary, and alignment can be made with respect to any predetermined feature of those sheets **102**, so long as it is fixed with respect to the individual sheets and their particular shape/geometry. For example, an irregular-shaped, non-symmetric top sheet might be aligned with respect to a particular known edge whose position and angle is fixed with respect to the top sheet **102**, and thus can be used to align the top sheet **102** as desired relative to a suitable pre-calibrated landmark.

[0041] Referring to FIG. **14** (and to symmetric, rectangular top sheets **102**), an incoming top sheet **102** is oriented, for example, such that its center line **102a** is both angularly and laterally offset relative to the center line **116** of the machine (in the conveyance direction). In other words, the illustrated top sheet **102** is misaligned, and its alignment will need corrected prior to affixing to an underlying backing **104** at the application station **114** downstream. Notably, a sensor is provided upstream of the alignment device **200** (i.e., upstream of the roller assembly **208**) and detects a leading edge of the top sheet **102** at a predetermined location. As will be described below, the sensor is configured to relay detected information to a controller (e.g., a programmable logic controller, not shown) for determining angular and lateral offsets of the center line **102a** of the top sheet **102** relative to the center line **116** of the machine. In the illustrated embodiment, the sensor utilizes a laser plane **240**, which is oriented orthogonal to the conveyance direction. Accordingly, when the leading edge of the traveling top sheet **102** (as it is conveyed by the first conveyor **110**) first intersects the laser plane **240**, the sensor detects the leading edge at an intersection point along the length of the laser plane **240**. Of note, other types of sensors are contemplated. For example, a sensor emitting an array of laser beams, a pair of single-point laser sensors, cameras, etc., may be employed.

[0042] Notably, a distance between the laser plane **240** and the roller assembly **208** is fixed and known (e.g., input by a user or pre-programmed in the controller). Moreover, the conveyance speed of the incoming top sheet **102** and its dimensions are known (e.g., via user input, the sensor, or pre-programmed in the controller). Accordingly, with the above known information, the detected intersection point of the leading edge (corner) of the top sheet **102**, as well as the angle of that leading edge discernible via monitoring the advancement of that edge for a short interval (e.g. measurable in microns or millimeters) just after the initial corner detected intersection, the controller performs the trigonometric calculations in order to ascertain the precise lateral and angular offsets (if any) of the sheet's center line **102a** relative to the center line **116** of the machine. With these offsets known, the controller can activate the first and second actuators **210**, **212** (either successively or concurrently) to adjust the lateral position and the angular orientation of the roller assembly **208** relative to the incoming top sheet **102** to correct those offsets via engagement by the roller(s) **226**, as will now be described.

[0043] With reference to FIGS. **15-16**, which schematically illustrate successive instants in the operation of the alignment device **200**, as the leading edge of the top sheet **102** advances over and engages the roller(s) **226** of the roller assembly **208**, the controller activates the first actuator **210** to linearly translate the roller assembly **208** in the cross-machine direction (as described above) to effectuate correction of the measured lateral offset—in order that said sheet **102** ends up where illustrated in FIG. **16**. In order that such cross-machine translation of the roller(s) **226** merely adjusts the lateral position of the top sheet **102** and does not alter its angular orientation, there must be sufficient engagement between the top sheet **102** and the roller assembly **208** during translation of the roller assembly **208** so translation thereof merely ‘pushes’ the top sheet **102** and does not

rotate it (e.g., such as when pushing against only the corner of a sheet of paper). Therefore, ideally cross-machine translation will not begin until the roller(s) **226** have engaged with the top sheet **102** against two distinct regions of that sheet **102** remote from one another; and preferably adjacent to the respective opposing lateral edges of that sheet **102** opposite the center line **102a**. This is another reason it is desirable to use either a segmented roller **226** having a central recess in order to engage the top sheet **102** at two distinct, spaced apart locations, or alternatively two discrete and spaced rollers **226**. Alternatively, it is contemplated that only a majority of one of the lateral side portions of the top sheet **102** may need engage the roller assembly **208** to hinder altering the sheet's angular offset.

[0044] Now with reference to FIG. **17**, which illustrates an instant immediately following that shown in FIG. **16** during operation, after (as illustrated—though optionally this operation can be carried out concurrent with) the desired correction of the sheet's lateral offset, the controller activates the second actuator **212** to pivot the roller assembly **208** about the pivot axis **236**. With the top sheet **102** continuously moving over the roller assembly **208**, the roller assembly **208** pivots either clockwise or counterclockwise (i.e., clockwise in the illustrated example) to correct the angular offset of the top sheet **102**, so that at the end of the above described operations the top sheet **102** ends up in the orientation and lateral position as shown in FIG. **17**.

[0045] Of note, both the initial lateral and angular offsets of the top sheet **102** (as measured) are considered by the controller when calculating the necessary degrees of adjustment, and then actuating the first and second actuators to effect those adjustments to correct both lateral and angular orientation of the top sheet **102**. This is because adjustment of the lateral position of the top sheet **102** can affect the degree of angular alignment requiring correction to achieve the final desired alignment, and vice versa. So both should be considered and an overall calculation performed in order to determine the appropriate degrees of both angular and lateral adjustment to be effected by the respective actuators, so that when both adjustments are completed the top sheet **102** will have both the proper angular alignment and the proper lateral alignment.

[0046] Moreover, it is to be understood that the roller(s) **226** of the roller assembly is/are rotatably driven (via a motor) throughout the aforementioned adjustment process. To achieve the desired longitudinal alignment for each top sheet, the controller can adjust the speed of the roller(s) **226** as necessary to effectuate alignment of the leading edge of the top sheet **102** relative to the leading edge of the corresponding backing **104** as the latter is advanced along the second conveyor **112**, in order to yield the desired longitudinal alignment/registration therebetween. In other words, the controller can adjust the rotational speed of the roller(s) **226** (which rotate at the same speed) to advance or retard the top sheet **102** along the conveyance direction relative to the corresponding backing **104** to ensure proper registration before adhering them together in the application station **114**.

[0047] As noted, lateral offset of the top sheet **102** can be corrected prior to correcting the sheet's angular offset (e.g., relative to the center line **116** of the machine). However, it is contemplated that correcting the sheet's orientation to achieve desired registration relative to the corresponding backing can be achieved in a different manner. For example, the sheet's angular offset can be corrected prior to correcting the sheet's lateral offset. In such an example, the controller will first activate the second actuator **212** (to pivot the roller assembly **208**), and then activate the first actuator **210** (to linearly translate the roller assembly **208**). In another alternative, the sheet's lateral and angular offsets can be corrected simultaneously by activating the first and second actuators concurrently to both laterally translate and pivot the roller assembly **208**.

[0048] With reference to FIGS. **18-19**, illustrated is a second embodiment of an alignment device **300**. Notably, this alignment device **300** is substantially similar to the alignment device **200** described above. That is, the alignment device **300** includes the nested frame assembly as described above, wherein the intermediate frame **202** is linearly translatable relative to the outer frame **206** via a first actuator **210**, and wherein the inner frame **204** (and thus the roller assembly **208**) is

pivotable relative to the intermediate frame **202** via the second actuator **212**.

[0049] The differences between this alignment device **300** and the prior described alignment device **200** are the interconnection between the inner frame **204** and the intermediate frame **202** and the location of the pivot axis **236** about which the roller assembly **208** pivots. With respect to FIG. **18**, one or more rotary guide bearing(s) **350** (see FIG. **22** for an example of a conventional rotary guide bearing) is/are provided at or near each of the lateral edges (for example one adjacent to each of the four corners) of the inner frame **204**, and located outside of the inner frame **204**. Each rotary guide bearing **350** includes a curved rail **352** attached (directly or indirectly) to the intermediate frame **202**, and a carriage **354** attached to the inner frame **204**. The carriages **354** are movable (i.e., slidable) along their respective rails **352** to effectuate pivoting of the roller assembly **208** (as shown in FIGS. **20-21**). In this embodiment, by fixing the inner frame **204** so that it can be pivoted only insofar as the respective carriages **354** affixed thereto can slide along their respective rails **352**, the pivot axis of the inner frame **204** also can be fixed to correspond to the geometric center thereof, rather than adjacent to or even outside of a lateral end of that frame **204**. More specifically, the rotary guide bearings **350** are located such that the pivot axis **236** is positioned at a center of the roller assembly **208** as seen in the figures. Meanwhile, the second actuator **212** still engages the inner frame **204** adjacent to an end thereof in order to pivot that frame. But with the pivot axis now fixed at the center of the inner frame **204**, activation of the second actuator **212** causes the inner frame **204** (and roller assembly **208**) to pivot relative to their center, rather than to swing relative to an offset axis.

[0050] As mentioned above, the alignment device (i.e., either the first or second described embodiment) preferably is located at an inclined portion of the first conveyor (as shown in FIG. **13**). Using the alignment device **300** of the second embodiment described above, having its corresponding center-pivot configuration, the load of the roller assembly **208** is balanced and symmetric with respect to the axis of rotation (i.e., the pivot axis **236**). As such, the second actuator **212** need not overcome the force of gravity (either additive or subtractive depending on the direction of pivotal adjustment) when actuating pivotal movement of the inner frame **204** and the nested roller assembly **208**—as would be the case for the first embodiment above, wherein the inner frame **204** is effectively cantilevered from an offset pivot axis so that the second actuator **212** effective must lift or lower the frame **204**, and its weight, cantilevered from the offset pivot axis. Rather, in the second embodiment of the device **300** shown in FIGS. **18-19**, as a left half of the inner frame **204** (and roller assembly **208**) is raised relative to the central pivot axis, the right half thereof is lowered relative to gravity. These counter-acting gravitational forces effectively cancel one another out so that the second actuator **212** need not overcome gravitational force acting on the inner frame **204** (and roller assembly **208**) in order to pivot them in response to control inputs.

[0051] This can be highly desirable in the instant applications because the contemplated degrees of required angular adjustment are likely to be quite small—on the order of single-digit degrees—and the speed at which such adjustments will have to be made for successive top sheets **102** advanced along the first conveyor **110** is quite fast; e.g., at or even greater than 13,000 such successive adjustments per hour (i.e. on the order of four or more angular adjustments of successive top sheets **102** per second). Because the second actuator **212** will not have to compensate for (i.e., overcome) the force of gravity on the inner frame **204** and roller assembly **208** as they are pivoted (because gravity will act equally at opposite sides thereof relative to the pivot axis **236**, and will thus be nulled as one end moves upward and the other one down), a substantial component of cyclic inertia against which the second actuator **212** must act is removed. As a result, greater speeds (i.e. lower cycling times), resulting in a larger number of corrections per hour, and thus of line speed, can be achieved. It is contemplated that adjustment resolution also will be materially improved because the degree of force required to make minute adjustments will be reduced when gravity is nulled out of those adjustments. Further still, with the pivot point located at the center of the inner frame **204**, the magnitude of linear actuation required to achieve the same degree of angular adjustment

(assuming similar positioning of the second actuator **212**) will be about half compared to when the pivot point is located adjacent to an edge of the inner frame **204**; because the point where the second actuator **212** engages the inner frame **204** is roughly half the distance from a central pivot axis as in the second disclosed embodiment, as compared to in the first disclosed embodiment. Accordingly, the second actuator **212** not only will face lower loads and lower inertia when making adjustments, but it also will require small-magnitude actuations when making those same, cyclic adjustments compared to the first embodiment. These differences compared to the first embodiment can yield much faster cycling times, as well as less wear and greater reliability on at least the second actuator **212**. Using the disclosed alignment device it is contemplated that line speeds of at least 13,000 top sheets per hour can be achieved, more preferably at least 15,000 top sheets per hour, more preferably still at least 16,000, 17,000, 18,000 or 20,000 top sheets per hour. It is contemplated that the disclosed device will enable line speeds of 13,000 to 18,000 top sheets per hour.

[0052] The invention has been described with reference to example embodiments. Modifications and alterations thereto will be evident to persons of skill in the art upon a reading and understanding this specification.

Claims

1. An alignment device for aligning a top sheet relative to a corresponding backing, the alignment device comprising: a driven roller aligned along a roller axis, said driven roller being both translatable and pivotable within predefined limits in a plane comprising said roller axis; and a first frame that is both translatable and pivotable together with the driven roller.
2. The alignment device of claim 1, further comprising a second frame, wherein the first frame is fixed in translation relative to the second frame.
3. The alignment device of claim 2, wherein the first frame is independently pivotable with respect to the second frame.
4. The alignment device of claim 2, wherein the first frame is disposed within an opening of the second frame.
5. The alignment device of claim 1, further comprising a rail extending parallel to a translation direction in which the driven roller is translatable, and configured to constrain translation of the driven roller in said translation direction.
6. The alignment device of claim 5, further comprising a second frame and a third frame, wherein the first frame is disposed within an opening of the second frame, and wherein the second frame is disposed within an opening of the third frame.
7. The alignment device of claim 6, wherein the rail is disposed between the second frame and the third frame.
8. The alignment device of claim 1, further comprising a first actuator configured to translate the first frame.
9. The alignment device of claim 8, further comprising a second actuator configured to pivot the first frame about a pivot axis.
10. The alignment device of claim 9, wherein the pivot axis is offset from the driven roller.
11. The alignment device of claim 9, wherein the pivot axis is substantially centered with respect to the driven roller.
12. The alignment device of claim 1, wherein said driven roller is translatable along a translation direction that is parallel to said roller axis, and wherein said driven roller is pivotable about a pivot axis that intersects with said roller axis.
13. A laminating apparatus comprising: a first conveyance path along which a top sheet is conveyed in use; a second conveyance path along which a backing is conveyed in use; and an alignment device for aligning the top sheet relative to the backing, the alignment device comprising a driven

roller aligned along a roller axis, said driven roller being both translatable and pivotable within predefined limits in a plane comprising said roller axis.

- 14.** The laminating apparatus of claim 13, wherein the alignment device is disposed upstream from a convergence point where the first and second conveyance paths intersect.
 - 15.** The laminating apparatus of claim 13, further comprising a first conveyor and a second conveyor, wherein the first and second conveyors define the first and second conveyance paths, respectively, and wherein said first conveyor is disposed above said second conveyor and has a convergent portion that follows a convergent path downward to a convergence point where the first and second conveyance paths intersect.
 - 16.** The laminating apparatus of claim 13, further comprising an application station configured to affix said top sheet to said backing.
 - 17.** The laminating apparatus of claim 13, wherein each of the first conveyance path and the second conveyance path is a linear path, and wherein the first and second conveyance paths intersect at a convergence point located downstream from the alignment device.
 - 18.** The laminating apparatus of claim 13, wherein the alignment device further comprises a first frame that is both translatable and pivotable together with the driven roller.
 - 19.** The laminating apparatus of claim 18, wherein the alignment device further comprises a second frame, wherein the first frame is fixed in translation relative to the second frame, and wherein the first frame is independently pivotable with respect to the second frame.
 - 20.** The laminating apparatus of claim 13, wherein the alignment device further comprises a rail extending parallel to a translation direction in which the driven roller is translatable, and configured to constrain translation of the driven roller in said translation direction.
-