

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250282604

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Biasi; John J. et al.

PRODUCT DISPENSING SYSTEM

Abstract

A system for controlling selection and distribution of a product in a product dispensing system. The system includes a user interface for prompting a selection and selecting the product, a machine control processor in communication with the user interface, a power distribution module connected to the machine control processor, and a power supply unit for supplying power to the system through the power distribution module.

Inventors: Biasi; John J. (Lancaster, MA), Beavis; Russell H. (Merrimack, NH), Goulet; Michael J. (Weare, NH), Pribyl; Eric L. (Manchester, NH)

Applicant: DEKA Products Limited Partnership (Manchester, NH)

Family ID: 50476102

Appl. No.: 19/214510

Filed: May 21, 2025

Related U.S. Application Data

parent US continuation 18238822 20230828 parent-grant-document US 12319560 child US 19214510

parent US continuation 17897670 20220829 parent-grant-document US 11738989 child US 18238822

parent US continuation 16791663 20200214 parent-grant-document US 11427462 child US 17897670

parent US continuation 13803434 20130314 parent-grant-document US 10562757 child US 16791663

parent US continuation 12549778 20090828 parent-grant-document US 8087303 child US 13339962

parent US continuation-in-part 13662102 20121026 parent-grant-document US 10859072 child US 13803434

parent US continuation-in-part 13339962 20111229 parent-grant-document US 8516902 child US

13662102

parent US continuation-in-part 12437356 20090507 parent-grant-document US 9146564 child US 12549778

parent US continuation-in-part 12205762 20080905 parent-grant-document US 8322570 child US 12437356

us-provisional-application US 60970501 20070906

us-provisional-application US 60970494 20070906

us-provisional-application US 60970493 20070906

us-provisional-application US 60970495 20070906

us-provisional-application US 60970497 20070906

us-provisional-application US 61054757 20080520

us-provisional-application US 61054629 20080520

us-provisional-application US 61054745 20080520

us-provisional-application US 61054776 20080520

us-provisional-application US 61092396 20080827

us-provisional-application US 61092394 20080827

us-provisional-application US 61092388 20080827

us-provisional-application US 61092404 20080828

us-provisional-application US 61552938 20111028

us-provisional-application US 61560007 20111115

us-provisional-application US 61636298 20120420

Publication Classification

Int. Cl.: **B67D7/22** (20100101); **B67D1/00** (20060101); **B67D1/08** (20060101); **G01F3/10** (20060101); **G01F3/20** (20060101); **G01F23/80** (20220101)

U.S. Cl.:

CPC **B67D7/221** (20130101); **B67D1/0036** (20130101); **B67D1/0892** (20130101); **G01F3/10** (20130101); **G01F3/20** (20130101); **G01F23/804** (20220101); B67D2210/00034 (20130101); B67D2210/0006 (20130101)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] The present application is a Continuation of U.S. application Ser. No. 18/238,822, filed Aug. 28, 2023; [0002] which is a Continuation of U.S. application Ser. No. 17/897,670, filed Aug. 29, 2022, now U.S. Pat. No. 11,738,989, issued Aug. 29, 2023 (AA180); [0003] which is a Continuation of U.S. application Ser. No. 16/791,663, filed Feb. 14, 2020, now U.S. Pat. No. 11,427,462, issued Aug. 30, 2022 (AA180); [0004] which is a Continuation of U.S. application Ser. No. 13/803,434, filed Mar. 14, 2013, now U.S. Pat. No. 10,562,757, issued Feb. 18, 2020 (K34); [0005] which is a Continuation-In-Part of U.S. application Ser. No. 13/662,102, filed Oct. 26, 2012, now U.S. Pat. No. 10,859,072, issued Dec. 8, 2020, (J70); [0006] which claims the benefit of: [0007] U.S. Provisional No. 61/552,938, filed Oct. 28, 2011 (I82); [0008] U.S. Provisional No. 61/560,007, filed Nov. 15, 2011 (J13); and [0009] U.S. Provisional No. 61/636,298, filed Apr. 20, 2012 (J39), all of which are hereby incorporated herein by reference in their entirety.

FIELD OF THE INVENTION

[0010] The present invention relates generally to processing systems and, more particularly, to processing systems that are used to generate products from a plurality of separate ingredients.

BACKGROUND

[0011] Processing systems may combine one or more ingredients to form a product. Unfortunately, such systems are often static in configuration and are only capable of generating a comparatively limited number of products. While such systems may be capable of being reconfigured to generate other products, such reconfiguration may require extensive changes to mechanical/electrical/software systems.

[0012] For example, in order to make a different product, new components may need to be added, such as e.g., new valves, lines, manifolds, and software subroutines. Such extensive modifications may be required due to existing devices/processes within the processing system being non-reconfigurable and having a single dedicated use, thus requiring that additional components be added to accomplish new tasks.

SUMMARY OF THE INVENTION

[0013] In accordance with one aspect of the present invention, a system for controlling selection and distribution of a product in a product dispensing system is disclosed. The system includes a user interface for prompting a selection and selecting the product, a machine control processor in communication with the user interface, a power distribution module connected to the machine control processor, and a power supply unit for supplying power to the system through the power distribution module.

[0014] Some embodiments of this aspect of the present invention may include one or more of the following features. Wherein the machine control processor further includes a microprocessor, and a communication interface. Wherein the machine control processor controls the distribution of the product through control of the power distribution module and a control logic subsystem. Wherein the power distribution module supplies power to the machine control processor through the power supply unit. Wherein the communication between the machine control processor and the user interface is a wireless communication. Wherein the communication between the machine control processor and the user interface is a wired communication.

[0015] In accordance with one aspect of the present invention, a method for controlling selection and distribution of a product from a product dispensing system. The method includes prompting a selection of the product on a user interface, communicating the selection from the user interface to a machine control processor, and dispensing the product under the control of the machine control processor and a product distribution module.

[0016] Some embodiments of this aspect of the present invention may include one or more of the following features. Wherein the machine control processor further includes a microprocessor, and a communication interface. Wherein the selection is communicated to the user interface from a wireless device. Wherein the wireless device selects the product from the user interface using a downloaded application. Wherein the wireless device is a device from the group comprising a smartphone, a desktop computer, a laptop computer, an MP3 player, and a tablet computer. Wherein the selection communication from the user interface to the machine control processor is a wireless communication.

[0017] In accordance with one aspect of the present invention, a system for monitoring flow conditions of fluid flowing from a product container through a solenoid pump is disclosed. The system includes at least one solenoid pump comprising a solenoid coil, which, when energized, produces a stroke of the solenoid pump, at least one product container connected to the at least one solenoid pump wherein the at least one solenoid pump pumps fluid from the at least one product container during each stroke, at least one PWM controller configured to energize the at least one solenoid pump, at least one current sensor for sensing the current flow through the solenoid coil

and producing an output of the sensed current flow, and a control logic subsystem for controlling the flow of fluids through the solenoid pump by commanding the PWM controller and for monitoring the current through the solenoid pump by receiving the output from the current sensor, wherein the control logic subsystem uses the measured current flow through the solenoid coil to determine whether the stroke of the solenoid pump is functional.

[0018] Some embodiments of this aspect of the present invention may include one or more of the following features: wherein the control logic subsystem uses at least the measured current flow through the solenoid coil to determine a Sold-Out condition of the at least one product container. Wherein the control logic subsystem uses the measured current flow through the solenoid coil to determine whether the stroke of the solenoid pump is non-functional. Wherein the control logic subsystem uses the measured current flow through the solenoid coil to determine whether the stroke of the solenoid pump is a Sold-Out Stroke.

[0019] Wherein the control logic subsystem determines a Sold-Out condition of the at least one product container if a threshold number of consecutive Sold-Out Strokes is reached. Wherein the at least one product container further comprising an RFID tag that stores a fuel gauge value representing the amount of fluid remaining in the at least one product container.

[0020] Wherein the control logic subsystem determines a Sold-Out condition of the at least one product container if a given number of consecutive Sold-Out Strokes are determined and the fuel gauge is above a threshold volume.

[0021] In accordance with one aspect of the present invention, a method for monitoring flow of fluid from a product container through a solenoid pump is disclosed. The method includes energizing a solenoid coil of the solenoid pump to produce a stroke of the solenoid pump, pumping fluid from a product container through the solenoid pump during each stroke, sensing the current flow through the solenoid using a current sensor and producing an output of sensed current flow, monitoring the current through the solenoid pump using a control logic subsystem, the control logic subsystem receiving the sensed current flow from the current sensor, and determining whether the stroke of the solenoid pump is functional.

[0022] Some embodiments of this aspect of the present invention may include one or more of the following features: wherein the control logic subsystem determining a Sold-Out condition of the at least one product container using at least the measured current flow through the solenoid coil.

[0023] Wherein the control logic subsystem determining whether the stroke of the solenoid pump is non-functional using the measured current flow through the solenoid coil. Wherein the control logic subsystem determining whether the stroke of the solenoid pump a Sold-Out Stroke using the measured current flow through the solenoid coil.

[0024] Wherein the control logic subsystem determining a Sold-Out condition of the at least one product container if a threshold number of consecutive Sold-Out Strokes is reached. Determining the amount of fluid remaining in the product container using an RFID tag that stores a fuel gauge value representing the amount of fluid remaining in the at least one product container. Wherein the control logic subsystem determining a Sold-Out condition of the product container if a given number of consecutive Sold-Out Strokes are determined and the fuel gauge is above a threshold volume.

[0025] In accordance with one aspect of the present invention, a system for determining a Sold-Out condition of a product container is disclosed. The system includes at least one solenoid pump comprising a solenoid coil, which, when energized, produces a stroke of the pump, at least one product container connected to the at least one solenoid pump wherein the at least one solenoid pump pumps fluid from the at least one product container during each stroke, at least one PWM controller configured to energize the at least one solenoid pump and control the voltage applied to the at least one solenoid pump, at least one current sensor for sensing the current flow through the solenoid coil and producing an output of the sensed current flow, and a control logic subsystem for controlling the flow of fluids through the solenoid pump by commanding the PWM controller and

for monitoring the current through the pump by receiving the output from the current sensor, wherein the control logic subsystem uses at least the measured current flow through the solenoid coil to determine a Sold-Out condition of the at least one product container.

[0026] Some embodiments of this aspect of the present invention may include one or more of the following features: Wherein the control logic subsystem determines if the at least one solenoid pump stroke was a functional stroke based on the output of the current sensor.

[0027] Wherein the control logic subsystem determines if the at least one solenoid pump stroke was a Sold-Out Stroke based on the output of the current sensor. Wherein the control logic subsystem determines a Sold-Out condition of the at least one product container if a threshold number of consecutive Sold-Out Strokes is reached. Wherein the control logic subsystem determines if the at least one solenoid pump stroke was a non-functional stroke based on the output of the current sensor. Wherein the at least one product container further comprising an RFID tag that stores a fuel gauge value representing the amount of fluid remaining in the at least one product container. Wherein the control logic subsystem determines a Sold-Out condition of the system if a given number of consecutive Sold-Out strokes are determined and the fuel gauge is above a threshold volume. Wherein the control logic subsystem varies a high frequency duty cycle of the PWM controller to control the current measured by the current sensor. At least one power supply connected to the at least one solenoid pump via the at least one PWM controller and the at least one current sensor.

[0028] In accordance with one aspect of the present invention, a method for cross reading mitigation in a product dispensing system is disclosed. The method includes scanning a plurality of RFID tag assemblies in the product dispensing system, evaluating the RFID tag assemblies for position within the product dispensing system, if one or more RFID tag assemblies are read in more than one slot, determining the time in slot, comparing the fitment maps, and comparing received signal strength indication values.

[0029] In accordance with one aspect of the present invention, in a first implementation, a flow sensor includes a fluid chamber configured to receive a fluid. A diaphragm assembly is configured to be displaced whenever the fluid within the fluid chamber is displaced. A transducer assembly is configured to monitor the displacement of the diaphragm assembly and generate a signal based, at least in part, upon the quantity of fluid displaced within the fluid chamber.

[0030] Some embodiments of this aspect of the present invention may include one or more of the following features: wherein the transducer assembly comprising a linear variable differential transformer coupled to the diaphragm assembly by a linkage assembly; wherein the transducer assembly comprising a needle/magnet cartridge assembly; wherein the transducer assembly comprising a magnetic coil assembly; wherein the transducer assembly comprising a Hall Effect sensor assembly; wherein the transducer assembly comprising a piezoelectric buzzer element; wherein the transducer assembly comprising a piezoelectric sheet element; wherein the transducer assembly comprising an audio speaker assembly; wherein the transducer assembly comprising an accelerometer assembly; wherein the transducer assembly comprising a microphone assembly; and/or wherein the transducer assembly comprising an optical displacement assembly.

[0031] In accordance with another aspect of the present invention, a method for determining a product container is empty is disclosed. The method includes energizing a pump assembly, pumping a micro-ingredient from a product container, displacing a capacitive plate a displacement distance, measuring the capacitance of a capacitor, calculating the displacement distance from the measured capacitance, and determining whether the product container is empty.

[0032] In accordance with another aspect of the present invention a method for determining a product container is empty is disclosed. The method includes energizing a pump assembly, displacing a diaphragm assembly a displacement distance by pumping a micro-ingredient from a product container, measuring the displacement distance using a transducer assembly, using the transducer assembly generating a signal based, at least in part, upon the quantity of micro-

ingredient pumped from the product container, and determining, using the signal, whether the product container is empty.

[0033] In accordance with another aspect of the present invention, a bracket for a product dispensing system is disclosed. The bracket includes a plurality of tabs and configured to align at least one bar code reader onto the door of the product dispensing system.

[0034] These aspects of the invention are not meant to be exclusive and other features, aspects, and advantages of the present invention will be readily apparent to those of ordinary skill in the art when read in conjunction with the appended claims and accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0035] These and other features and advantages of the present invention will be better understood by reading the following detailed description, taken together with the drawings wherein:

[0036] FIG. 1 is a diagrammatic view of one embodiment of a processing system;

[0037] FIG. 2 is a diagrammatic view of one embodiment of a control logic subsystem included within the processing system of FIG. 1;

[0038] FIG. 3 is a diagrammatic view of one embodiment of a high volume ingredient subsystem included within the processing system of FIG. 1;

[0039] FIG. 4 is a diagrammatic view of one embodiment of a microingredient subsystem included within the processing system of FIG. 1;

[0040] FIG. 5A is a diagrammatic side view of one embodiment of a capacitance-based flow sensor included within the processing system of FIG. 1 (during a non-pumping condition);

[0041] FIG. 5B is a diagrammatic top view of the capacitance-based flow sensor of FIG. 5A;

[0042] FIG. 5C is a diagrammatic view of two capacitive plates included within the capacitance-based flow sensor of FIG. 5A;

[0043] FIG. 5D is a time-dependent graph of the capacitance value of the capacitance based flow sensor of FIG. 5A (during a non-pumping condition, a pumping condition, and an empty condition);

[0044] FIG. 5E is a diagrammatic side view of the capacitance-based flow sensor of FIG. 5A (during a pumping condition);

[0045] FIG. 5F is a diagrammatic side view of the capacitance-based flow sensor of FIG. 5A (during an empty condition);

[0046] FIG. 5G is a diagrammatic side view of an alternative embodiment of the flow sensor of FIG. 5A;

[0047] FIG. 5H is a diagrammatic side view of an alternative embodiment of the flow sensor of FIG. 5A;

[0048] FIG. 6A is a diagrammatic view of a plumbing/control subsystem included within the processing system of FIG. 1;

[0049] FIG. 6B is a diagrammatic view of one embodiment of a gear-based, positive displacement flow measuring device;

[0050] FIGS. 7A and 7B diagrammatically depict an embodiment of a flow control module of FIG. 3;

[0051] FIGS. 8-14C diagrammatically depict various alternative embodiments of a flow control module of FIG. 3;

[0052] FIGS. 15A and 15B diagrammatically depict a portion of a variable line impedance;

[0053] FIG. 15C diagrammatically depicts one embodiment of a variable line impedance;

[0054] FIGS. 16A and 16B diagrammatically depict a gear of a gear-based positive displacement flow measuring device according to one embodiment; and

[0055] FIG. **17** is a diagrammatic view of a user interface subsystem included within the processing system of FIG. **1**.

[0056] FIG. **18** is a flowchart of an FSM process executed by the control logic subsystem of FIG. **1**;

[0057] FIG. **19** is a diagrammatic view of a first state diagram;

[0058] FIG. **20** is a diagrammatic view of a second state diagram;

[0059] FIG. **21** is a flowchart of a virtual machine process executed by the control logic subsystem of FIG. **1**;

[0060] FIG. **22** is a flowchart of a virtual manifold process executed by the control logic subsystem of FIG. **1**;

[0061] FIG. **23** is an isometric view of an RFID system included within the processing system of FIG. **1**;

[0062] FIG. **24** is a diagrammatic view of the RFID system of FIG. **23**;

[0063] FIG. **25** is a diagrammatic view of an RFID antenna assembly included within the RFID system of FIG. **23**;

[0064] FIG. **26** is an isometric view of an antenna loop assembly of the RFID antenna assembly of FIG. **25**;

[0065] FIG. **27** is an isometric view of a housing assembly for housing the processing system of FIG. **1**;

[0066] FIG. **28** is a diagrammatic view of an RFID access antenna assembly included within the processing system of FIG. **1**;

[0067] FIG. **29** is a diagrammatic view of an alternative RFID access antenna assembly included within the processing system of FIG. **1**;

[0068] FIG. **30** is a diagrammatic view of an embodiment of the processing system of FIG. **1**;

[0069] FIG. **31** is a diagrammatic view of the internal assembly of the processing system of FIG. **30**;

[0070] FIG. **32** is a diagrammatic view of the upper cabinet of the processing system of FIG. **30**;

[0071] FIG. **33** is a diagrammatic view of a flow control subsystem of the processing system of FIG. **30**;

[0072] FIG. **34** is a diagrammatic view of a flow control module of the flow control subsystem of FIG. **33**;

[0073] FIG. **35** is a diagrammatic view of the upper cabinet of the processing system of FIG. **30**;

[0074] FIGS. **36A** and **36B** are diagrammatic views of a power module of the processing system of FIG. **35**;

[0075] FIGS. **37A**, **37B**, and **37C** diagrammatically depict a flow control module of the flow control subsystem of FIG. **35**;

[0076] FIG. **38** is a diagrammatic view of the lower cabinet of the processing system of FIG. **30**;

[0077] FIG. **39** is a diagrammatic view of a microingredient tower of the lower cabinet of FIG. **38**;

[0078] FIG. **40** is a diagrammatic view of a microingredient tower of the lower cabinet of FIG. **38**;

[0079] FIG. **41** is a diagrammatic view of a quad product module of the microingredient tower of FIG. **39**;

[0080] FIG. **42** is a diagrammatic view of a quad product module of the microingredient tower of FIG. **39**;

[0081] FIGS. **43A**, **43B**, and **43C** are diagrammatic views of one embodiment of a microingredient container;

[0082] FIG. **44** is a diagrammatic view of another embodiment of a microingredient container;

[0083] FIGS. **45A** and **45B** diagrammatically depict an alternative embodiment of a lower cabinet of the processing system of FIG. **30**;

[0084] FIGS. **46A**, **46B**, **46C**, and **46D** diagrammatically depict one embodiment of a microingredient shelf of the lower cabinet of FIGS. **45A** and **45B**.

[0085] FIGS. **47A**, **47B**, **47C**, **47D**, **47E**, and **47F** diagrammatically depict a quad product module of the microingredient shelf of FIGS. **46A**, **46B**, **46C**, and **46D**;

[0086] FIG. **48** diagrammatically depicts a plumbing assembly of the quad product module of FIGS. **47A**, **47B**, **47C**, **47D**, **47E**, and **47F**;

[0087] FIG. **49A**, **49B**, **49C** diagrammatically depict a large volume microingredient assembly of the lower cabinet of FIGS. **45A** and **45B**;

[0088] FIG. **50** diagrammatically depicts a plumbing assembly of large volume microingredient assembly of FIG. **49A**, **49B**, **49C**;

[0089] FIG. **51** diagrammatically depicts one embodiment of a user interface screen in a user interface bracket;

[0090] FIG. **52** diagrammatically depicts one embodiment of a user interface bracket without a screen;

[0091] FIG. **53** is a detailed side view of the bracket of FIG. **52**;

[0092] FIGS. **54** and **55** diagrammatically depict a membrane pump;

[0093] FIG. **56** is a cross sectional view of one embodiment of a flow control module in a de-energized position;

[0094] FIG. **57** is a cross sectional view of one embodiment of a flow control module with the binary valve in an open position;

[0095] FIG. **58** is a cross sectional view of one embodiment of a flow control module in a partially energized position;

[0096] FIG. **59** is a cross sectional view of one embodiment of a flow control module in a fully energized position;

[0097] FIG. **60** is a cross sectional view of one embodiment of a flow control module with an anemometer sensor;

[0098] FIG. **61** is a cross sectional view of one embodiment of a flow control module with a paddle wheel sensor;

[0099] FIG. **62** is a top cut-away view of one embodiment of the paddle wheel sensor;

[0100] FIG. **63** is an isometric view of one embodiment of a flow control module;

[0101] FIG. **64** is one embodiment of a dither scheduling scheme;

[0102] FIG. **65** is a cross sectional view of one embodiment of a flow control module in a fully energized position with the fluid flow path indicated;

[0103] FIG. **66** is a schematic representation of an exemplary solenoid pump, measurement and control circuitry;

[0104] FIG. **67** is a schematic representation of the pwm controller and current sensing circuit;

[0105] FIGS. **68A**, **68B**, **68C** and **68D** plot the time varying current in a solenoid pump for a different normal, empty and occluded cases according to one embodiment;

[0106] FIGS. **69A**, **69B**, **69C**, **69D**, **69E**, and **69F** diagrammatically depict an alternative quad product module of the microingredient shelf of FIGS. **46A**, **46B**, **46C**, and **46D** according to one embodiment;

[0107] FIG. **70A** is a view of one embodiment of the external communication module according to one embodiment;

[0108] FIG. **70B** is an exploded view of one embodiment of the external communication module according to one embodiment;

[0109] FIGS. **71A**, **71B**, and **71C** are isometric views of one embodiment of the external communication module mounting in the upper door of the processing system according to one embodiment;

[0110] FIG. **72** is a view of one embodiment of the alignment bracket according to one embodiment;

[0111] FIG. **73** is a flow diagram of a method for cross talk mitigation according to one embodiment;

[0112] FIG. **74** is a plot of pulses and Sold-Out Value of a product according to one embodiment;
[0113] FIG. **75** is a plot of pulses and Sold-Out Value and pulses and Estimated Standard Deviation according to one embodiment;
[0114] FIG. **76** is a diagrammatic representation of the leak detection for the flow control module according to one embodiment;
[0115] FIG. **77** is a diagrammatic representation of the leak detection for the flow control module according to one embodiment;
[0116] FIG. **78** is a plot of time and volume showing the leak integrator and leak detected;
[0117] FIG. **79** is a block diagram of a power module;
[0118] FIG. **80** is a diagrammatic view of one embodiment of the power module of FIG. **79**;
[0119] FIG. **81** is a diagrammatic view of one the power module of FIG. **80** in communication with a user interface module according to one embodiment;
[0120] FIG. **82** is a diagrammatic view of one embodiment of a configuration of connections between the power module of FIG. **80** and other subsystems and devices of the processing system, according to one embodiment; and
[0121] FIG. **83** is one embodiment of connections within the configuration of FIG. **82**.
[0122] Like reference symbols in the various drawings indicate like elements.

DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

[0123] Described herein is a product dispensing system. The system includes one or more modular components, also termed “subsystems”. Although exemplary systems are described herein, in various embodiments, the product dispensing system may include one or more of the subsystems described, but the product dispensing system is not limited to only one or more of the subsystems described herein. Thus, in some embodiments, additional subsystems may be used in the product dispensing system.

[0124] The following disclosure will discuss the interaction and cooperation of various electrical components, mechanical components, electro-mechanical components, and software processes (i.e., “subsystems”) that allow for the mixing and processing of various ingredients to form a product. Examples of such products may include but are not limited to: dairy-based products (e.g., milkshakes, floats, malts, frappes); coffee-based products (e.g., coffee, cappuccino, espresso); soda-based products (e.g., floats, soda w/fruit juice); tea-based products (e.g., iced tea, sweet tea, hot tea); water-based products (e.g., spring water, flavored spring water, spring water w/vitamins, high-electrolyte drinks, high-carbohydrate drinks); solid-based products (e.g., trail mix, granola-based products, mixed nuts, cereal products, mixed grain products); medicinal products (e.g., infusible medicants, injectable medicants, ingestible medicants, dialysates); alcohol-based products (e.g., mixed drinks, wine spritzers, soda-based alcoholic drinks, water-based alcoholic drinks, beer with flavor “shots”); industrial products (e.g., solvents, paints, lubricants, stains); and health/beauty aid products (e.g., shampoos, cosmetics, soaps, hair conditioners, skin treatments, topical ointments).

[0125] The products may be produced using one or more “ingredients”. Ingredients may include one or more fluids, powders, solids or gases. The fluids, powders, solids, and/or gases may be reconstituted or diluted within the context of processing and dispensing. The products may be a fluid, solid, powder or gas.

[0126] The various ingredients may be referred to as “macroingredients”, “microingredients”, or “large volume microingredients”. One or more of the ingredients used may be contained within a housing, i.e., part of a product dispensing machine. However, one or more of the ingredients may be stored or produced outside the machine. For example, in some embodiments, water (in various qualities) or other ingredients used in high volume may be stored outside of the machine (for example, in some embodiments, high fructose corn syrup may be stored outside the machine), while other ingredients, for example, ingredients in powder form, concentrated ingredients, nutraceuticals, pharmaceuticals and/or gas cylinders may be stored within the machine itself.

[0127] Various combinations of the above-referenced electrical components, mechanical components, electro-mechanical components, and software processes are discussed below. While combinations are described below that disclose e.g., the production of beverages and medicinal products (e.g., dialysates) using various subsystems, this is not intended to be a limitation of this disclosure, rather, exemplary embodiments of ways in which the subsystems may work together to create/dispense a product. Specifically, the electrical components, mechanical components, electro-mechanical components, and software processes (each of which will be discussed below in greater detail) may be used to produce any of the above-referenced products or any other products similar thereto.

[0128] Referring to FIG. 1, there is shown a generalized view of processing system **10** that is shown to include a plurality of subsystems namely: storage subsystem **12**, control logic subsystem **14**, high volume ingredient subsystem **16**, microingredient subsystem **18**, plumbing/control subsystem **20**, user interface subsystem **22**, and nozzle **24**. Each of the above described subsystems **12**, **14**, **16**, **18**, **20**, **22** will be described below in greater detail.

[0129] During use of processing system **10**, user **26** may select a particular product **28** for dispensing (into container **30**) using user interface subsystem **22**. Via user interface subsystem **22**, user **26** may select one or more options for inclusion within such product. For example, options may include but are not limited to the addition of one or more ingredients. In one exemplary embodiment, the system is a system for dispensing a beverage. In this embodiment, the user may select various flavorings (e.g. including but not limited to lemon flavoring, lime flavoring, chocolate flavoring, and vanilla flavoring) to be added into a beverage; the addition of one or more nutraceuticals (e.g. including but not limited to Vitamin A, Vitamin C, Vitamin D, Vitamin E, Vitamin B6, Vitamin B12, and Zinc) into a beverage; the addition of one or more other beverages (e.g. including but not limited to coffee, milk, lemonade, and iced tea) into a beverage; and the addition of one or more food products (e.g. ice cream, yogurt) into a beverage.

[0130] Once user **26** makes the appropriate selections, via user interface subsystem **22**, user interface subsystem **22** may send the appropriate data signals (via data bus **32**) to control logic subsystem **14**. Control logic subsystem **14** may process these data signals and may retrieve (via data bus **34**) one or more recipes chosen from a plurality of recipes **36** maintained on storage subsystem **12**. The term “recipe” referring to instructions for processing/creating the requested product. Upon retrieving the recipe(s) from storage subsystem **12**, control logic subsystem **14** may process the recipe(s) and provide the appropriate control signals (via data bus **38**) to e.g. high volume ingredient subsystem **16**, microingredient subsystem **18** (and, in some embodiments, large volume microingredients, not shown, which may be included in the description with respect to microingredients with respect to processing. With respect to the subsystems for dispensing these large volume microingredients, in some embodiments, an alternate assembly from the microingredient assembly, may be used to dispense these large volume microingredients), and plumbing/control subsystem **20**, resulting in the production of product **28** (which is dispensed into container **30**).

[0131] Referring also to FIG. 2, a diagrammatic view of control logic subsystem **14** is shown. Control logic subsystem **14** may include microprocessor **100** (e.g., an ARM™ microprocessor produced by Intel Corporation of Santa Clara, California), nonvolatile memory (e.g. read only memory **102**), and volatile memory (e.g. random access memory **104**); each of which may be interconnected via one or more data/system buses **106**, **108**. As discussed above, user interface subsystem **22** may be coupled to control logic subsystem **14** via data bus **32**.

[0132] Control logic subsystem **14** may also include an audio subsystem **110** for providing e.g. an analog audio signal to speaker **112**, which may be incorporated into processing system **10**. Audio subsystem **110** may be coupled to microprocessor **100** via data/system bus **114**.

[0133] Control logic subsystem **14** may execute an operating system, examples of which may include but are not limited to Microsoft Windows CE™, Redhat Linux™, Palm OS™, or a device-

specific (i.e., custom) operating system.

[0134] The instruction sets and subroutines of the above-described operating system, which may be stored on storage subsystem **12**, may be executed by one or more processors (e.g. microprocessor **100**) and one or more memory architectures (e.g. read-only memory **102** and/or random access memory **104**) incorporated into control logic subsystem **14**.

[0135] Storage subsystem **12** may include, for example, a hard disk drive, a solid state drive, an optical drive, a random access memory (RAM), a read-only memory (ROM), a CF (i.e., compact flash) card, an SD (i.e., secure digital) card, a SmartMedia card, a Memory Stick, and a MultiMedia card, for example.

[0136] As discussed above, storage subsystem **12** may be coupled to control logic subsystem **14** via data bus **34**. Control logic subsystem **14** may also include storage controller **116** (shown in phantom) for converting signals provided by microprocessor **100** into a format usable by storage system **12**. Further, storage controller **116** may convert signals provided by storage subsystem **12** into a format usable by microprocessor **100**.

[0137] In some embodiments, an Ethernet connection is also included.

[0138] As discussed above, high-volume ingredient subsystem (also referred to herein as “macroingredients”) **16**, microingredient subsystem **18**, and/or plumbing/control subsystem **20** may be coupled to control logic subsystem **14** via data bus **38**. Control logic subsystem **14** may include bus interface **118** (shown in phantom) for converting signals provided by microprocessor **100** into a format usable by high-volume ingredient subsystem **16**, microingredient subsystem **18**, and/or plumbing/control subsystem **20**. Further, bus interface **118** may convert signals provided by high-volume ingredient subsystem **16**, microingredient subsystem **18** and/or plumbing/control subsystem **20** into a format usable by microprocessor **100**.

[0139] As will be discussed below in greater detail, control logic subsystem **14** may execute one or more control processes **120** (e.g., finite state machine process (FSM process **122**), virtual machine process **124**, and virtual manifold process **126**, for example) that may control the operation of processing system **10**. The instruction sets and subroutines of control processes **120**, which may be stored on storage subsystem **12**, may be executed by one or more processors (e.g. microprocessor **100**) and one or more memory architectures (e.g. read-only memory **102** and/or random access memory **104**) incorporated into control logic subsystem **14**.

[0140] Referring also to FIG. **3**, a diagrammatic view of high-volume ingredient subsystem **16** and plumbing/control subsystem **20** are shown. High-volume ingredient subsystem **16** may include containers for housing consumables that are used at a rapid rate when making beverage **28**. For example, high-volume ingredient subsystem **16** may include carbon dioxide supply **150**, water supply **152**, and high fructose corn syrup supply **154**. The high-volume ingredients, in some embodiments, are located within close proximity to the other subsystems. An example of carbon dioxide supply **150** may include, but is not limited to, a tank (not shown) of compressed, gaseous carbon dioxide. An example of water supply **152** may include but is not limited to a municipal water supply (not shown), a distilled water supply, a filtered water supply, a reverse-osmosis (“RO”) water supply or other desired water supply. An example of high fructose corn syrup supply **154** may include, but is not limited to, one or more tank(s) (not shown) of highly-concentrated, high fructose corn syrup, or one or more bag-in-box packages of high-fructose corn syrup.

[0141] High-volume ingredient subsystem **16** may include a carbonator **156** for generating carbonated water from carbon dioxide gas (provided by carbon dioxide supply **150**) and water (provided by water supply **152**). Carbonated water **158**, water **160** and high fructose corn syrup **162** may be provided to cold plate assembly **163** (for example, in embodiments where a product is being dispensed in which it may be desired to be cooled. In some embodiments, the cold plate assembly is not included as part of the dispensing systems or may be by-passed). Cold plate assembly **163** may be designed to chill carbonated water **158**, water **160**, and high fructose corn syrup **162** down to a desired serving temperature (e.g. 40° F.).

[0142] While a single cold plate **163** is shown to chill carbonated water **158**, water **160**, and high fructose corn syrup **162**, this is for illustrative purposes only and is not intended to be a limitation of disclosure, as other configurations are possible. For example, an individual cold plate may be used to chill each of carbonated water **158**, water **160** and high fructose corn syrup **162**. Once chilled, chilled carbonated water **164**, chilled water **166**, and chilled high fructose corn syrup **168** may be provided to plumbing/control subsystem **20**. And in still other embodiments, a cold plate may not be included. In some embodiments, at least one hot plate may be included.

[0143] Although the plumbing is depicted as having the order shown, in some embodiments, this order is not used. For example, the flow control modules described herein may be configured in a different order, i.e., flow measuring device, binary valve and then variable line impedance.

[0144] For descriptive purposes, the system will be described below with reference to using the system to dispense soft drinks as a product, i.e., the macroingredients/high-volume ingredients described will include high-fructose corn syrup, carbonated water and water. However, in other embodiments of the dispensing system, the macroingredients themselves, and the number of macroingredients, may vary.

[0145] For illustrative purposes, plumbing/control subsystem **20** is shown to include three flow control modules **170**, **172**, **174**. Flow control modules **170**, **172**, **174** may generally control the volume and/or flow rate of high-volume ingredients. Flow control modules **170**, **172**, **174** may each include a flow measuring device (e.g., flow measuring devices **176**, **178**, **180**), which measure the volume of chilled carbonated water **164**, chilled water **166** and chilled high fructose corn syrup **168** (respectively). Flow measuring devices **176**, **178**, **180** may provide feedback signals **182**, **184**, **186** (respectively) to feedback controller systems **188**, **190**, **192** (respectively).

[0146] Feedback controller systems **188**, **190**, **192** (which will be discussed below in greater detail) may compare flow feedback signals **182**, **184**, **186** to the desired flow volume (as defined for each of chilled carbonated water **164**, chilled water **166**, and chilled high fructose corn syrup **168**; respectively). Upon processing flow feedback signals **182**, **184**, **186**, feedback controller systems **188**, **190**, **192** (respectively) may generate flow control signals **194**, **196**, **198** (respectively) that may be provided to variable line impedances **200**, **202**, **204** (respectively). Examples of variable line impedances **200**, **202**, **204** are disclosed and claimed in U.S. Pat. No. 5,755,683 (Attorney Docket B13) and U.S. Patent Publication No.: 2007/0085049 (Attorney Docket E66). Variable line impedances **200**, **202**, **204** may regulate the flow of chilled carbonated water **164**, chilled water **166** and chilled high fructose corn syrup **168** passing through lines **218**, **220**, **222** (respectively), which are provided to nozzle **24** and (subsequently) container **30**. However, additional embodiments of the variable line impedances are described herein.

[0147] Lines **218**, **220**, **222** may additionally include binary valves **212**, **214**, **216** (respectively) for preventing the flow of fluid through lines **218**, **220**, **222** during times when fluid flow is not desired/required (e.g. during shipping, maintenance procedures, and downtime).

[0148] In one embodiment, binary valves **212**, **214**, **216** may include solenoid operated binary valves. However, in other embodiments, the binary valves may be any binary valve known in the art, including, but not limited to a binary valve actuated by any means. Additionally, binary valves **212**, **214**, **216** may be configured to prevent the flow of fluid through lines **218**, **220**, **222** whenever processing system **10** is not dispensing a product. Further, the functionality of binary valves **212**, **214**, **216** may be accomplished via variable line impedances **200**, **202**, **204** by fully closing variable line impedances **200**, **202**, **204**, thus preventing the flow of fluid through lines **218**, **220**, **222**.

[0149] As discussed above, FIG. **3** merely provides an illustrative view of plumbing/control subsystem **20**. Accordingly, the manner in which plumbing/control subsystem **20** is illustrated is not intended to be a limitation of this disclosure, as other configurations are possible. For example, some or all of the functionality of feedback controller systems **182**, **184**, **186** may be incorporated into control logic subsystem **14**. Also, with respect to the flow control modules **170**, **172**, **174**, the sequential configuration of the components are shown in FIG. **3** for illustration purposes only.

Thus, the sequential configuration shown serves merely as an exemplary embodiment. However, in other embodiments, the components may be arranged in a different sequence.

[0150] Referring also to FIG. 4, a diagrammatic top-view of microingredient subsystem **18** and plumbing/control subsystem **20** is shown. Microingredient subsystem **18** may include product module assembly **250**, which may be configured to releasably engage one or more product containers **252**, **254**, **256**, **258**, which may be configured to hold microingredients for use when making product **28**. The microingredients are substrates that are used in making the product. Examples of such micro ingredients/substrates may include but are not limited to a first portion of a soft drink flavoring, a second portion of a soft drink flavoring, coffee flavoring, nutraceuticals, pharmaceuticals, and may be fluids, powders or solids. However for illustrative purposes, the description below refers to microingredients that are fluids. In some embodiments, the microingredients are powders or solids. Where a microingredient is a powder, the system may include an additional subsystem for metering the powder and/or reconstituting the powder (although, as described in examples below, where the microingredient is a powder, the powder may be reconstituted as part of the methods of mixing the product, i.e., the software manifold). Product module assembly **250** may include a plurality of slot assemblies **260**, **262**, **264**, **266** configured to releasably engage plurality of product containers **252**, **254**, **256**, **258**. In this particular example, product module assembly **250** is shown to include four slot assemblies (namely slots **260**, **262**, **264**, **266**) and, therefore, may be referred to as a quad product module assembly. When positioning one or more of product containers **252**, **254**, **256**, **258** within product module assembly **250**, a product container (e.g. product container **254**) may be slid into a slot assembly (e.g. slot assembly **262**) in the direction of arrow **268**. Although as shown herein, in the exemplary embodiment, a “quad product module” assembly is described, in other embodiments, more or less product may be contained within a module assembly. Depending on the product being dispensed by the dispensing system, the numbers of product containers may vary. Thus, the numbers of product contained within any module assembly may be application specific, and may be selected to satisfy any desired characteristic of the system, including, but not limited to, efficiency, necessity and/or function of the system.

[0151] For illustrative purposes, each slot assembly of product module assembly **250** is shown to include a pump assembly. For example, slot assembly **252** is shown to include pump assembly **270**; slot assembly **262** is shown to include pump assembly **272**; slot assembly **264** is shown to include pump assembly **274**; and slot assembly **266** is shown to include pump assembly **276**.

[0152] An inlet port, coupled to each of pump assemblies **270**, **272**, **274**, **276**, may releasably engage a product orifice included within the product container. For example, pump assembly **272** is shown to include inlet port **278** that is configured to releasably engage container orifice **280** included within product container **254**. Inlet port **278** and/or product orifice **280** may include one or more sealing assemblies (not shown), for example, one or more o-rings or a luer fitting, to facilitate a leak-proof seal. The inlet port (e.g., inlet port **278**) coupled to each pump assembly may be constructed of a rigid “pipe-like” material or may be constructed from a flexible “tubing-like” material.

[0153] An example of one or more of pump assemblies **270**, **272**, **274**, **276** may include, but is not limited to, a solenoid piston pump assembly that provides a calibratedly expected volume of fluid each time that one or more of pump assemblies **270**, **272**, **274**, **276** are energized. In one embodiment, such pumps are available from ULKA Costruzioni Elettromeccaniche S.p.A. of Pavia, Italy. For example, each time a pump assembly (e.g. pump assembly **274**) is energized by control logic subsystem **14** via data bus **38**, the pump assembly may provide approximately 30 μ L of the fluid microingredient included within product container **256** (however, the volume of flavoring provided may vary calibratedly). Again, for illustrative purposes only, the microingredients are fluids in this section of the description. The term “calibratedly” refers to volumetric, or other information and/or characteristics, that may be ascertained via calibration of

the pump assembly and/or individual pumps thereof.

[0154] Other examples of pump assemblies **270**, **272**, **274**, **276** and various pumping techniques are described in U.S. Pat. No. 4,808,161 (Attorney Docket A38); U.S. Pat. No. 4,826,482 (Attorney Docket A43); U.S. Pat. No. 4,976,162 (Attorney Docket A52); U.S. Pat. No. 5,088,515 (Attorney Docket A49); and U.S. Pat. No. 5,350,357 (Attorney Docket 147), all of which are incorporated herein by reference in their entireties. In some embodiments, the pump assembly may be a membrane pump as shown in FIGS. **54-55**. In some embodiments, the pump assembly may be any of the pump assemblies and may use any of the pump techniques described in U.S. Pat. No. 5,421,823 (Attorney Docket 158) which is herein incorporated by reference in its entirety.

[0155] The above-cited references describe non-limiting examples of pneumatically actuated membrane-based pumps that may be used to pump fluids. A pump assembly based on a pneumatically actuated membrane may be advantageous, for one or more reasons, including but not limited to, ability to deliver quantities, for example, microliter quantities of fluids of various compositions reliably and precisely over a large number of duty cycles; and/or because the pneumatically actuated pump may require less electrical power because it may use pneumatic power, for example, from a carbon dioxide source. Additionally, a membrane-based pump may not require a dynamic seal, in which the surface moves with respect to the seal. Vibratory pumps such as those manufactured by ULKA generally require the use of dynamic elastomeric seals, which may fail over time for example, after exposure to certain types of fluids and/or wear. In some embodiments, pneumatically-actuated membrane-based pumps may be more reliable, cost effective and easier to calibrate than other pumps. They may also produce less noise, generate less heat and consume less power than other pumps. A non-limiting example of a membrane-based pump is shown in FIG. **54**.

[0156] The various embodiments of the membrane-based pump assembly **2900**, shown in FIGS. **54-55**, include a cavity, which in FIG. **54** is **2942**, which may also be referred to as a pumping chamber, and in FIG. **55** is **2944**, which may also be referred to as a control fluid chamber. The cavity includes a diaphragm **2940** which separates the cavity into the two chambers, the pumping chamber **2942** and the volume chamber **2944**.

[0157] Referring now to FIG. **54**, a diagrammatic depiction of an exemplary membrane-based pump assembly **2900** is shown. In this embodiment, the membrane-based pump assembly **2900** includes membrane or diaphragm **2940**, pumping chamber **2942**, control fluid chamber **2944** (best seen in FIG. **55**), a three-port switching valve **2910** and check valves **2920** and **2930**. In some embodiments, the volume of pumping chamber **2942** may be in the range of approximately microliters to approximately 500 microliters. In an exemplary embodiment, the volume of pumping chamber **2942** may be in the range of approximately 30 microliters to approximately 250 microliters. In other exemplary embodiments, the volume of pumping chamber **2942** may be in the range of approximately 40 microliters to approximately 100 microliters.

[0158] Switching valve **2910** may be operated to place pump control channel **2958** either in fluid communication with switching valve fluid channel **2954**, or switching valve fluid channel **2956**. In a non-limiting embodiment, switching valve **2910** may be an electromagnetically operated solenoid valve, operating on electrical signal inputs via control lines **2912**. In other non-limiting embodiments, switching valve **2910** may be a pneumatic or hydraulic membrane-based valve, operating on pneumatic or hydraulic signal inputs. In yet other embodiments, switching valve **2910** may be a fluidically, pneumatically, mechanically or electromagnetically actuated piston within a cylinder. More generally, any other type of valve may be contemplated for use in pump assembly **2900**, with preference that the valve is capable of switching fluid communication with pump control channel **2958** between switching valve fluid channel **2954** and switching valve fluid channel **2956**.

[0159] In some embodiments, switching valve fluid channel **2954** is ported to a source of positive fluid pressure (which may be pneumatic or hydraulic). The amount of fluid pressure required may

depend on one or more factors, including, but not limited to, the tensile strength and elasticity of diaphragm **2940**, the density and/or viscosity of the fluid being pumped, the degree of solubility of dissolved solids in the fluid, and/or the length and size of the fluid channels and ports within pump assembly **2900**. In various embodiments, the fluid pressure source may be in the range of approximately 15 psi to approximately 250 psi. In an exemplary embodiment, the fluid pressure source may be in the range of approximately 60 psi to approximately 100 psi. In another exemplary embodiment, the fluid pressure source may be in the range of approximately 70 psi to approximately 80 psi. As discussed above, some embodiments of the dispensing system may produce carbonated beverages and thus, may use, as an ingredient, carbonated water. In these embodiments, the gas pressure of CO₂ used to generate carbonated beverages is often approximately 75 psi, the same source of gas pressure may also be regulated lower and used in some embodiments to drive a membrane-based pump for pumping small quantities of fluids in a beverage dispenser.

[0160] In response to the appropriate signal provided via control lines **2912**, valve **2910** may place switching valve fluid channel **2954** into fluid communication with pump control channel **2958**. Positive fluid pressure may thus be transmitted to diaphragm **2940**, which in turn may force fluid in pumping chamber **2942** out through pump outlet channel **2950**. Check valve **2930** ensures that the pumped fluid is prevented from flowing out of pumping chamber **2942** through inlet channel **2952**. [0161] Switching valve **2910** via control lines **2912** may place the pump control channel **2958** into fluid communication with switching valve fluid channel **2956**, which may cause the diaphragm **2940** to reach the wall of the pumping chamber **2942** (as shown in FIG. 54). In an embodiment, switching valve fluid channel **2956** may be ported to a vacuum source, which when placed in fluid communication with pump control channel **2958**, may cause diaphragm **2940** to retract, reducing the volume of pump control chamber **2944**, and increasing the volume of pumping chamber **2942**. Retraction of diaphragm **2940** causes fluid to be pulled into pumping chamber **2942** via pump inlet channel **2952**. Check valve **2920** prevents reverse flow of pumped fluid back into pumping chamber **2942** via outlet channel **2950**.

[0162] In an embodiment, diaphragm **2940** may be constructed of semi-rigid spring-like material, imparting on the diaphragm a tendency to maintain a curved or spheroidal shape, and acting as a cup-shaped diaphragm type spring. For example, diaphragm **2940** may be constructed or stamped at least partially from a thin sheet of metal, the metal that may be used includes but is not limited to high carbon spring steel, nickel-silver, high-nickel alloys, stainless steel, titanium alloys, beryllium copper, and the like. Pump assembly **2900** may be constructed so that the convex surface of diaphragm **2940** faces the pump control chamber **2944** and/or the pump control channel **2958**. Thus, diaphragm **2940** may have a natural tendency to retract after it is pressed against the surface of pumping chamber **2942**. In this circumstance, switching valve fluid channel **2956** may be ported to ambient (atmospheric) pressure, allowing diaphragm **2940** to automatically retract and draw fluid into pumping chamber **2942** via pump inlet channel **2952**. In some embodiments the concave portion of the spring-like diaphragm defines a volume equal to, or substantially/approximately equal to the volume of fluid to be delivered with each pump stroke. This has the advantage of eliminating the need for constructing a pumping chamber having a defined volume, the exact dimensions of which may be difficult and/or expensive to manufacture within acceptable tolerances. In this embodiment, the pump control chamber is shaped to accommodate the convex side of the diaphragm at rest, and the geometry of the opposing surface may be any geometry, i.e., may not be relevant to performance.

[0163] In an embodiment, the volume delivered by a membrane pump may be performed in an 'open-loop' manner, without the provision of a mechanism to sense and verify the delivery of an expected volume of fluid with each stroke of the pump. In another embodiment, the volume of fluid pumped through the pump chamber during a stroke of the membrane may be measured using a Fluid Management System ("FMS") technique, described in greater detail in U.S. Pat. No.

4,808,161 (Attorney Docket A38); U.S. Pat. No. 4,826,482 (Attorney Docket A43); U.S. Pat. No. 4,976,162 (Attorney Docket A52); U.S. Pat. No. 5,088,515 (Attorney Docket A49); and U.S. Pat. No. 5,350,357 (Attorney Docket 147), all of which are hereby incorporated herein by reference in their entireties. Briefly, FMS measurement is used to detect the volume of fluid delivered with each stroke of the membrane-based pump. A small fixed reference air chamber is located outside of the pump assembly, or example in a pneumatic manifold (not shown). A valve isolates the reference chamber and a second pressure sensor. The stroke volume of the pump may be precisely computed by charging the reference chamber with air, measuring the pressure, and then opening the valve to the pumping chamber. The volume of air on the chamber side may be computed based on the fixed volume of the reference chamber and the change in pressure when the reference chamber was connected to the pump chamber. In some embodiments, the volume of fluid pumped through the pump chamber during a stroke of the membrane may be measured using an Acoustic Volume Sensing (“AVS”) technique. Acoustic volume measurement technology is the subject of U.S. Pat. No. 5,575,310 (Attorney Docket B28) and U.S. Pat. No. 5,755,683 (Attorney Docket B13) assigned to DEKA Products Limited Partnership, as well as U.S. Patent Application Publication Nos. US 2007/0228071 A1 (Attorney Docket E70), US 2007/0219496 A1, US 2007/0219480 A1, US 2007/0219597 A1 and WO 2009/088956, all of which are hereby incorporated herein by reference. Fluid volume sensing in the nanoliter range is possible with this embodiment, thus contributing to highly accurate and precise monitoring of the volume pumped. Other alternate techniques for measuring fluid flow may also be used; for example, Doppler-based methods; the use of Hall-effect sensors in combination with a vane or flapper valve; the use of a strain beam (for example, related to a flexible member over a fluid chamber to sense deflection of the flexible member); the use of capacitive sensing with plates; or thermal time of flight methods.

[0164] Product module assembly **250** may be configured to releasably engage bracket assembly **282**. Bracket assembly **282** may be a portion of (and rigidly fixed within) processing system **10**. Although referred to herein as a “bracket assembly”, the assembly may vary in other embodiments. The bracket assembly serves to secure the product module assembly **282** in a desired location. An example of bracket assembly **282** may include but is not limited to a shelf within processing system **10** that is configured to releasably engage product module **250**. For example, product module **250** may include an engagement device (e.g. a clip assembly, a slot assembly, a latch assembly, a pin assembly; not shown) that is configured to releasably engage a complementary device that is incorporated into bracket assembly **282**.

[0165] Plumbing/control subsystem **20** may include manifold assembly **284** that may be rigidly affixed to bracket assembly **282**. Manifold assembly **284** may be configured to include a plurality of inlet ports **286, 288, 290, 292** that are configured to releasably engage a pump orifice (e.g. pump orifices **294, 296, 298, 300**) incorporated into each of pump assemblies **270, 272, 274, 276**. When positioning product module **250** on bracket assembly **282**, product module **250** may be moved in the direction of the arrow **302**, thus allowing for inlet ports **286, 288, 290, 292** to releasably engage pump orifices **294, 296, 298, 300** (respectively). Inlet ports **286, 288, 290, 292** and/or pump orifices **294, 296, 298, 300** may include one or more o-ring or other sealing assemblies as described above (not shown) to facilitate a leak-proof seal. The inlet ports (e.g., inlet ports **286, 288, 290, 292**) included within manifold assembly **284** may be constructed of a rigid “pipe-like” material or may be constructed from a flexible “tubing-like” material.

[0166] Manifold assembly **284** may be configured to engage tubing bundle **304**, which may be plumbed (either directly or indirectly) to nozzle **24**. As discussed above, high-volume ingredient subsystem **16** also provides fluids in the form of, in at least one embodiment, chilled carbonated water **164**, chilled water **166** and/or chilled high fructose corn syrup **168** (either directly or indirectly) to nozzle **24**. Accordingly, as control logic subsystem **14** may regulate (in this particular example) the specific quantities of the various high-volume ingredients e.g. chilled carbonated water **164**, chilled water **166**, chilled high fructose corn syrup **168** and the quantities of the various

micro ingredients (e.g. a first substrate (i.e., flavoring, a second substrate (i.e., a nutraceutical, and a third substrate (i.e., a pharmaceutical), control logic subsystem **14** may accurately control the makeup of product **28**.

[0167] As discussed above, one or more of pump assemblies **270, 272, 274, 276** may be a solenoid piston pump assembly that provides a defined and consistent amount of fluid each time that one or more of pump assemblies **270, 272, 274, 276** are energized by control logic subsystem **14** (via data bus **38**). Further and as discussed above, control logic subsystem **14** may execute one or more control processes **120** that may control the operation of processing system **10**. An example of such a control process may include a drive signal generation process (not shown) for generating a drive signal that may be provided from control logic subsystem **14** to pump assemblies **270, 272, 274, 276** via data bus **38**. One exemplary methodology for generating the above-described drive signal is disclosed in U.S. patent application Ser. No. 11/851,344, entitled SYSTEM AND METHOD FOR GENERATING A DRIVE SIGNAL, which was filed on 6 Sep. 2007, now U.S. Pat. No. 7,905,373 (Attorney Docket F45) the entire disclosure of which is incorporated herein by reference.

[0168] Although FIG. **4** depicts one nozzle **24**, in various other embodiments, more than one nozzle **24** may be included. In some embodiments, more than one container **30** may receive product dispensed from the system, for example, via more than one set of tubing bundles. Thus, in some embodiments, the dispensing system may be configured such that one or more users may request one or more products to be dispensed concurrently.

[0169] Capacitance-based flow sensors **306, 308, 310, 312** may be utilized to sense flow of the above-described microingredients through each of pump assemblies **270, 272, 274, 276**.

[0170] Referring also to FIG. **5A** (side view) and FIG. **5B** (top view), a detailed view of exemplary capacitance-based flow sensor **308** is shown. Capacitance-based flow sensor **308** may include first capacitive plate **310** and second capacitive plate **312**. Second capacitive plate **312** may be configured to be movable with respect to first capacitive plate **310**. For example, first capacitive plate **310** may be rigidly affixed to a structure within processing system **10**. Further, capacitance-based flow sensor **308** may also be rigidly affixed to a structure within processing system **10**. However, second capacitive plate **312** may be configured to be movable with respect to first capacitive plate **310** (and capacitance-based flow sensor **308**) through the use of diaphragm assembly **314**. Diaphragm assembly **314** may be configured to allow for the displacement of second capacitive plate **312** in the direction of arrow **316**. Diaphragm assembly **314** may be constructed of various materials that allow for displacement in the direction of arrow **316**. For example, diaphragm assembly **314** may be constructed out of a stainless steel foil with a PET (i.e., Polyethylene Terephthalate) coating to prevent corrosion of the stainless steel foil. Alternatively, diaphragm assembly **314** may be constructed of a titanium foil. Further still, diaphragm assembly **314** may be constructed of a plastic in which one surface of the plastic diaphragm assembly is metalized to form second capacitive plate **312**. In some embodiments, the plastic may be, but is not limited to, an injection molded plastic or a PET rolled sheet.

[0171] As discussed above, each time a pump assembly (e.g. pump assembly **272**) is energized by control logic subsystem **14** via data bus **38**, the pump assembly may provide a calibrated volume of fluid, for example 30-33 μL , of the appropriate microingredient included within e.g., product container **254**. Accordingly, control logic subsystem **14** may control the flow rate of the microingredients by controlling the rate at which the appropriate pump assembly is energized. An exemplary rate of energizing a pump assembly is between 3 Hz (i.e. three times per second) to 30 Hz (i.e. 30 times per second).

[0172] Accordingly, when pump assembly **272** is energized, a suction is created (within chamber **318** of capacitance-based flow sensor **308**) that effectuates drawing of the appropriate microingredient (e.g. a substrate) from e.g. product container **254**. Therefore, upon pump assembly **272** being energized and creating a suction within chamber **318**, second capacitive plate **312** may be displaced downward (with respect to FIG. **5A**), thus increasing distance “d” (i.e. the distance

between first capacitive plate **310** and second capacitive plate **312**).

[0173] Referring also to FIG. 5C and as is known in the art, the capacitance (C) of a capacitor is determined according to the following equation:

$$[00001]C = \frac{A}{d}$$

[0174] wherein “ ϵ ” is the permittivity of the dielectric material positioned between first capacitive plate **310** and second capacitive plate **312**; “A” is the area of the capacitive plates; and “d” is the distance between first capacitive plate **310** and second capacitive plate **312**. As “d” is positioned in the denominator of the above-described equation, any increase in “d” results in a corresponding decrease in “C” (i.e. the capacitance of the capacitor).

[0175] Continuing with the above-stated example and referring also to FIG. 5D, assume that when pump assembly **272** is not energized, the capacitor formed by first capacitive plate **310** and second capacitive plate **312** has a value of 5.00 pF. Further assume that when pump assembly **272** is energized at time T=1, a suction is created within chamber **316** that is sufficient to displace second capacitive plate **312** downward a distance sufficient to result in a 20% reduction in the capacitance of the capacitor formed by first capacitive plate **310** and second capacitive plate **312**. Accordingly, the new value of the capacitor formed by first capacitive plate **310** and second capacitive plate **312** may be 4.00 pF. An illustrative example of a second capacitive plate **312** being displaced downward during the above-described pumping sequence is shown in FIG. 5E.

[0176] As the appropriate microingredient is drawn from product container **254**, the suction within chamber **318** may be reduced and second capacitive plate **312** may be displaced upward to its original position (as shown in FIG. 5A). As second capacitive plate **312** is displaced upward, the distance between second capacitive plate **312** and first capacitive plate **310** may be reduced back to its initial value. Accordingly, the capacitance of the capacitor formed by first capacitive plate **310** and second capacitive plate **312** may once again be 5.00 pF. When second capacitive plate **312** is moving upward and returning to its initial position, the momentum of second capacitive plate **312** may result in second capacitive plate **312** overshooting its initial position and momentarily being positioned closer to first capacitive plate **310** than during the initial position of the second capacitive plate **312** (as shown in FIG. 5A). Accordingly, the capacitance of the capacitor formed by first capacitive plate **310** and second capacitive plate **312** may momentarily increase above its initial value of 5.00 pF and shortly thereafter stabilize at 5.00 pF.

[0177] The above-described varying of the capacitance value of between (in this example) 5.00 pF and 4.00 pF while pump assembly **272** is repeatedly cycled on and off may continue until e.g. product container **254** is empty. Assume for illustrative purposes that product container **254** is emptied at time T=5. At this point in time, second capacitive plate **312** may not return to its original position (as shown in FIG. 5A). Further, as pump assembly **272** continues to be cycled, second capacitive plate **312** may continue to be drawn downward until second capacitive plate **312** can no longer be displaced (as shown in FIG. 5F). At this point in time, due to the increase in distance “d” over and above that illustrated in FIG. 5A and FIG. 5E, the capacitance value of the capacitor formed by first capacitive plate **310** and second capacitive plate **312** may be minimized to minimum capacitance value **320**. The actual value of minimum capacitance value **320** may vary depending upon the flexibility of diaphragm assembly **314**.

[0178] Accordingly, by monitoring the variations in the capacitance value (e.g., absolute variations or peak-to-peak variations) of the capacitor formed by first capacitive plate **310** and second capacitive plate **312**, the proper operation of e.g. pump assembly **272** may be verified. For example, if the above-described capacitance value cyclically varies between 5.00 pF and 4.00 pF, this variation in capacitance may be indicative of the proper operation of pump assembly **272** and a nonempty product container **254**. However, in the event that the above-described capacitance value does not vary (e.g. remains at 5.00 pF), this may be indicative of a failed pump assembly **272** (e.g., a pump assembly that includes failed mechanical components and/or failed electrical components) or a blocked nozzle **24**.

[0179] Further, in the event that the above-described capacitance value decreases to a point below 4.00 pF (e.g. to minimum capacitance value **320**), this may be indicative of product container **254** being empty. Additionally still, in the event that the peak-to-peak variation is less than expected (e.g., less than the above-described 1.00 pF variation), this may be indicative of a leak between product container **254** and capacitance-based flow sensor **308**.

[0180] To determine the capacitance value of the capacitor formed by first capacitive plate **310** and second capacitive plate **312**, a signal may be provided (via conductors **322**, **324**) to capacitance measurement system **326**. The output of capacitance measurement system **326** may be provided to control logic subsystem **14**. An example of capacitance measurement system **326** may include the CY8C21434-24LFXI PSOC offered by Cypress Semiconductor of San Jose, California, the design and operation of which are described within the “CSD User Module” published by Cypress Semiconductor, which is incorporated herein by reference. Capacitance measurement circuit **326** may be configured to provide compensation for environmental factors (e.g., temperature, humidity, and power supply voltage change).

[0181] Capacitance measurement system **326** may be configured to take capacitance measurements (with respect to the capacitor formed with first capacitive plate **310** and second capacitive plate **312**) over a defined period of time to determine if the above-described variations in capacitance are occurring. For example, capacitance measurement system **326** may be configured to monitor changes in the above-described capacitance value that occur over the time frame of 0.50 seconds. Accordingly and in this particular example, as long as pump assembly **272** is being energized at a minimum rate of 2.00 Hz (i.e., at least once every 0.50 seconds), at least one of the above-described capacitance variations should be sensed by capacitance measurement system **326** during each 0.50 second measurement cycle.

[0182] While flow sensor **308** is described above as being capacitance-based, this is for illustrative purposes only and is not intended to be a limitation of this disclosure, as other configurations are possible and are considered to be within the scope of this disclosure.

[0183] For example and referring also to FIG. 5G, assume for illustrative purposes that flow sensor **308** does not include first capacitive plate **310** and second capacitive plate **312**. Alternatively, flow sensor **308** may include transducer assembly **328** that may be (directly or indirectly) coupled to diaphragm assembly **314**. If directly coupled, transducer assembly **328** may be mounted on/attached to diaphragm assembly **314**. Alternatively, if indirectly coupled, transducer assembly **328** may be coupled to diaphragm assembly **314** with e.g., linkage assembly **330**.

[0184] As discussed above, as fluid is displaced through chamber **318**, diaphragm assembly **314** may be displaced. For example, diaphragm assembly **314** may move in the direction of arrow **316**. Additionally/alternatively, diaphragm assembly **314** may distort (e.g., become slightly concave/convex (as illustrated via phantom diaphragm assemblies **332**, **334**). As is known in the art, whether: (a) diaphragm assembly **314** remains essentially planar while being displaced in the direction of arrow **316**; (b) flexes to become convex diaphragm assembly **332**/concave diaphragm assembly **334** while remaining stationary with respect to arrow **316**; or (c) exhibits a combination of both forms of displacement, may depend upon a plurality of factors (e.g., the rigidity of various portions of diaphragm assembly **314**). Accordingly, by utilizing transducer assembly **328** (in combination with linkage assembly **330** and/or transducer measurement system **336**) to monitor the displacement of all or a portion of diaphragm assembly **314**, the quantity of fluid displaced through chamber **318** may be determined.

[0185] Through the use of various types of transducer assemblies (to be discussed below in greater detail), the quantity of fluid passing through chamber **318** may be determined.

[0186] For example, transducer assembly **328** may include a linear variable differential transformer (LVDT) and may be rigidly affixed to a structure within processing system **10**, which may be coupled to diaphragm assembly **314** via linkage assembly **330**. An illustrative and non-limiting example of such an LVDT is an SE 750 100 produced by Macro Sensors of Pennsauken, New

Jersey. Flow sensor **308** may also be rigidly affixed to a structure within processing system **10**. Accordingly, if diaphragm assembly **314** is displaced (e.g., along arrow **316** or flexed to become convex/concave), the movement of diaphragm assembly **314** may be monitored. Therefore, the quantity of fluid passing through chamber **318** may also be monitored.

[0187] Transducer assembly **328** (i.e., which includes LVDT) may generate a signal that may be processed (e.g., amplified/converted/filtered) by transducer measurement system **336**. This processed signal may then be provided to control logic subsystem **14** and used to ascertain the quantity of fluid passing through chamber **318**.

[0188] Alternatively, transducer assembly **328** may include a needle/magnetic cartridge assembly (e.g., such as a phonograph needle/magnetic cartridge assembly) and may be rigidly affixed to a structure within processing system **10**. An illustrative and non-limiting example of such a needle/magnetic cartridge assembly is a N 16 D produced by Toshiba Corporation of Japan. Transducer assembly **328** may be coupled to diaphragm assembly **314** via linkage assembly **330** (e.g., a rigid rod assembly). The needle of transducer assembly **328** may be configured to contact the surface of linkage assembly **330** (i.e., the rigid rod assembly). Accordingly, as diaphragm assembly **314** is displaced/flexes (as discussed above), linkage assembly **330** (i.e., rigid rod assembly) is also displaced (in the direction of arrow **316**) and may rub against the needle of transducer assembly **328**. Therefore, the combination of transducer assembly **328** (i.e., the needle/magnetic cartridge) and linkage assembly **330** (i.e., the rigid rod assembly) may generate a signal that may be processed (e.g., amplified/converted/filtered) by transducer measurement system **336**. This processed signal may then be provided to control logic subsystem **14** and used to ascertain the quantity of fluid passing through chamber **318**. Alternatively, transducer assembly **328** may include a magnetic coil assembly (e.g., similar to a voice coil of a speaker assembly) and may be rigidly affixed to a structure within processing system **10**. An illustrative and non-limiting example of such a magnetic coil assembly is a 5526-1 produced by API Delevan Inc. of East Aurora, New York. Transducer assembly **328** may be coupled to diaphragm assembly **314** via linkage assembly **330**, which may include an axial magnet assembly. An illustrative and non-limiting example of such an axial magnet assembly is a D16 produced by K & J Magnetics, Inc. of Jamison, Pennsylvania. The axial magnet assembly included within linkage assembly **330** may be configured to slide coaxially within the magnetic coil assembly of transducer assembly **328**. Accordingly, as diaphragm assembly **314** is displaced/flexes (as discussed above), linkage assembly **330** (i.e., the axial magnet assembly) is also displaced (in the direction of arrow **316**). As is known in the art, the movement of an axial magnet assembly within a magnetic coil assembly induces a current within the windings of the magnetic coil assembly. Accordingly, the combination of the magnetic coil assembly (not shown) of transducer assembly **328** and the axial magnet assembly (not shown) of linkage assembly **330** may generate a signal that may be processed (e.g., amplified/converted/filtered) and then provided to control logic subsystem **14** and used to ascertain the quantity of fluid passing through chamber **318**.

[0189] Alternatively, transducer assembly **328** may include a Hall Effect sensor assembly and may be rigidly affixed to a structure within processing system **10**. An illustrative and non-limiting example of such a Hall Effect sensor assembly is a AB0iKUA-T produced by Allegro Microsystems Inc. of Worcester, Massachusetts. Transducer assembly **328** may be coupled to diaphragm assembly **314** via linkage assembly **330**, which may include an axial magnet assembly. An illustrative and non-limiting example of such an axial magnet assembly is a D16 produced by K & J Magnetics, Inc. of Jamison, Pennsylvania. The axial magnet assembly included within linkage assembly **330** may be configured to be positioned proximate the Hall Effect sensor assembly of transducer assembly **328**. Accordingly, as diaphragm assembly **314** is displaced/flexes (as discussed above), linkage assembly **330** (i.e., the axial magnet assembly) is also displaced (in the direction of arrow **316**). As is known in the art, a Hall Effect sensor assembly is an assembly that generates an output voltage signal that varies in response to changes in a magnetic field.

Accordingly, the combination of the Hall Effect sensor assembly (not shown) of transducer assembly **328** and the axial magnet assembly (not shown) of linkage assembly **330** may generate a signal that may be processed (e.g., amplified/converted/filtered) and then provided to control logic subsystem **14** and used to ascertain the quantity of fluid passing through chamber **318**.

[0190] Piezoelectric, as used herein, refers to any material which exhibits a piezoelectric effect. The materials may include, but are not limited to, the following: ceramic, films, metals, crystals.

[0191] Alternatively, transducer assembly **328** may include a piezoelectric buzzer element that may be directly coupled to diaphragm assembly **314**. Accordingly, linkage assembly **330** may not be utilized. An illustrative and non-limiting example of such a piezoelectric buzzer element is a KBS-13DA-12A produced by AVX Corporation of Myrtle Beach, South Carolina. As is known in the art, a piezoelectric buzzer element may generate an electrical output signal that varies depending on the amount of mechanical stress that the piezoelectric buzzer element is exposed to. Accordingly, as diaphragm assembly **314** is displaced/flexes (as discussed above), the piezoelectric buzzer element (included within transducer assembly **328**) may be exposed to mechanical stress and, therefore, may generate a signal that may be processed (e.g., amplified/converted/filtered) by transducer measurement system **336**. This processed signal may then be provided to control logic subsystem **14** and used to ascertain the quantity of fluid passing through chamber **318**.

[0192] Alternatively, transducer assembly **328** may include a piezoelectric sheet element that may be directly coupled to diaphragm assembly **314**. Accordingly, linkage assembly **330** may not be utilized. An illustrative and non-limiting example of such a piezoelectric sheet element is a 0-1002794-0 produced by MSI/Schaevitz of Hampton, Virginia. As is known in the art, a piezoelectric sheet element may generate an electrical output signal that varies depending on the amount of mechanical stress that the piezoelectric sheet element is exposed to. Accordingly, as diaphragm assembly **314** is displaced/flexes (as discussed above), the piezoelectric sheet element (included within transducer assembly **328**) may be exposed to mechanical stress and, therefore, may generate a signal that may be processed (e.g., amplified/converted/filtered) by transducer measurement system **336**. This processed signal may then be provided to control logic subsystem **14** and used to ascertain the quantity of fluid passing through chamber **318**.

[0193] Alternatively, the above-described piezoelectric sheet element (included within transducer assembly **328**) may be positioned proximate and acoustically coupled with diaphragm assembly **314**. The piezoelectric sheet element (included within transducer assembly **328**) may or may not include a weight assembly to enhance the ability of the piezoelectric sheet element to resonate. Accordingly, as diaphragm assembly **314** is displaced/flexes (as discussed above), the piezoelectric sheet element (included within transducer assembly **328**) may be exposed to mechanical stress (due to the acoustic coupling) and, therefore, may generate a signal that may be processed (e.g., amplified/converted/filtered) by transducer measurement system **336**. This processed signal may then be provided to control logic subsystem **14** and used to ascertain the quantity of fluid passing through chamber **318**.

[0194] Alternatively, transducer assembly **328** may include an audio speaker assembly in which the cone of the audio speaker assembly may be directly coupled to diaphragm assembly **314**. Accordingly, linkage assembly **330** may not be utilized. An illustrative and non-limiting example of such an audio speaker assembly is a AS01308MR-2X produced by Projects Unlimited of Dayton, Ohio. As is known in the art, the audio speaker assembly may include a voice coil assembly and a permanent magnet assembly within which the voice coil assembly slides. While a signal is typically applied to the voice coil assembly to generate movement of the speaker cone, if the speaker is manually moved, a current will be induced in the voice coil assembly. Accordingly, as diaphragm assembly **314** is displaced/flexes (as discussed above), the voice coil of the audio speaker assembly (included within transducer assembly **328**) may be displaced with respect to the above-described permanent magnet assembly and, therefore, a signal may be generated that may be processed (e.g., amplified/converted/filtered) by transducer measurement system **336**. This

processed signal may then be provided to control logic subsystem **14** and used to ascertain the quantity of fluid passing through chamber **318**.

[0195] Alternatively, transducer assembly **328** may include an accelerometer assembly that may be directly coupled to diaphragm assembly **314**. Accordingly, linkage assembly **330** may not be utilized. An illustrative and non-limiting example of such an accelerometer assembly is a AD22286-R2 produced by Analog Devices, Inc. of Norwood, Massachusetts. As is known in the art, an accelerometer assembly may generate an electrical output signal that varies depending on the acceleration that the accelerometer assembly is exposed to. Accordingly, as diaphragm assembly **314** is displaced/flexes (as discussed above), the accelerometer assembly (included within transducer assembly **328**) may be exposed to varying levels of acceleration and, therefore, may generate a signal that may be processed (e.g., amplified/converted/filtered) by transducer measurement system **336**. This processed signal may then be provided to control logic subsystem **14** and used to ascertain the quantity of fluid passing through chamber **318**.

[0196] Alternatively, transducer assembly **328** may include a microphone assembly that may be positioned proximate and acoustically coupled with diaphragm assembly **314**. Accordingly, linkage assembly **330** may not be utilized. An illustrative and non-limiting example of such a microphone assembly is a EA-21842 produced by Knowles Acoustics of Itasca, Illinois. Accordingly, as diaphragm assembly **314** is displaced/flexes (as discussed above), the microphone assembly (included within transducer assembly **328**) may be exposed to mechanical stress (due to the acoustic coupling) and, therefore, may generate a signal that may be processed (e.g., amplified/converted/filtered) by transducer measurement system **336**. This processed signal may then be provided to control logic subsystem **14** and used to ascertain the quantity of fluid passing through chamber **318**.

[0197] Alternatively, transducer assembly **328** may include an optical displacement assembly configured to monitor the movement of diaphragm assembly **314**. Accordingly, linkage assembly **330** may not be utilized. An illustrative and non-limiting example of such an optical displacement assembly is a Z4 W-V produced by Advanced Motion Systems, Inc. of Pittsford, New York. Assume for illustrative purposes that the above-described optical displacement assembly includes an optical signal generator that directs an optical signal toward diaphragm assembly **314**, which is reflected off of diaphragm assembly **314** and is sensed by an optical sensor (also included within optical displacement assembly). Accordingly, as diaphragm assembly **314** is displaced/flexes (as discussed above), the optical signal sensed by the above-described optical sensor (included within transducer assembly **328**) may vary. Therefore, a signal may be generated by the optical displacement assembly (included within transducer assembly **328**) that may be processed (e.g., amplified/converted/filtered) by transducer measurement system **336**. This processed signal may then be provided to control logic subsystem **14** and used to ascertain the quantity of fluid passing through chamber **318**.

[0198] While the above-described examples of flow sensor **308** are meant to be illustrative, they are not intended to be exhaustive, as other configurations are possible and are considered to be within the scope of this disclosure. For example, while transducer assembly **328** is shown to be positioned outside of diaphragm assembly **314**, transducer assembly **328** may be positioned within chamber **318**.

[0199] While several of the above-described examples of flow sensor **308** are described as being coupled to diaphragm assembly **314**, this is for illustrative purposes only and is not intended to be a limitation of this disclosure, as other configurations are possible and are considered to be within the scope of this disclosure. For example and referring also to FIG. 5H, flow sensor **308** may include piston assembly **338** that may be biased by spring assembly **340**. Piston assembly **338** may be positioned proximate and configured to bias diaphragm assembly **314**. Accordingly, piston assembly **338** may emulate the movement of diaphragm assembly **314**. Therefore, transducer assembly **328** may be coupled to piston assembly **338** and achieve the results discussed above.

[0200] Further, when flow sensor **308** is configured to include piston assembly **338** and spring assembly **340**, transducer assembly **328** may include an inductance monitoring assembly configured to monitor the inductance of spring assembly **340**. Accordingly, linkage assembly **330** may not be utilized. An illustrative and non-limiting example of such an inductance monitoring assembly is a L/C Meter II B produced by Almost All Digital Electronics of Auburn, Washington. Accordingly, as diaphragm assembly **314** is displaced/flexes (as discussed above), the inductance of spring assembly **340** sensed by the above-described inductance monitoring assembly (included within transducer assembly **328**) may vary i.e., due to the changes in resistance as spring assembly **340** flexes. Therefore, a signal may be generated by the inductance monitoring assembly (included within transducer assembly **328**) that may be processed (e.g., amplified/converted/filtered) by transducer measurement system **336**. This processed signal may then be provided to control logic subsystem **14** and used to ascertain the quantity of fluid passing through chamber **318**.

[0201] Referring also to FIG. **6A**, a diagrammatic view of plumbing/control subsystem **20** is shown. While the plumbing/control subsystem described below concerns the plumbing/control system used to control the quantity of chilled carbonated water **164** being added to product **28**, via flow control module **170**, this is for illustrative purposes only and is not intended to be a limitation of this disclosure, as other configurations are also possible. For example, the plumbing/control subsystem described below may also be used to control e.g., the quantity of chilled water **166** (e.g., via flow control module **172**) and/or chilled high fructose corn syrup **168** (e.g., via flow control module **174**) being added to product **28**.

[0202] As discussed above, plumbing/control subsystem **20** may include feedback controller system **188** that receives flow feedback signal **182** from flow measuring device **176**. Feedback controller system **188** may compare flow feedback signal **182** to the desired flow volume (as defined by control logic subsystem **14** via data bus **38**). Upon processing flow feedback signal **182**, feedback controller system **188** may generate flow control signal **194** that may be provided to variable line impedance **200**.

[0203] Feedback controller system **188** may include trajectory shaping controller **350**, flow regulator **352**, feed forward controller **354**, unit delay **356**, saturation controller **358**, and stepper controller **360**, each of which will be discussed below in greater detail.

[0204] Trajectory shaping controller **350** may be configured to receive a control signal from control logic subsystem **14** via data bus **38**. This control signal may define a trajectory for the manner in which plumbing/control subsystem **20** is supposed to deliver fluid (in the case, chilled carbonated water **164** via flow control module **170**) for use in product **28**. However, the trajectory provided by control logic subsystem **14** may need to be modified prior to being processed by e.g., flow controller **352**. For example, control systems tend to have a difficult time processing control curves that are made up of a plurality of line segments (i.e., that include step changes). For example, flow regulator **352** may have difficulty processing control curve **370**, as it consists of three distinct linear segments, namely segments **372**, **374**, **376**. Accordingly, at the transition points (e.g., transition points **378**, **380**), flow controller **352** specifically (and plumbing/control subsystem **20** generally) would be required to instantaneously change from a first flow rate to a second flow rate. Therefore, trajectory shaping controller **350** may filter control curve **30** to form smoothed control curve **382** that is more easily processed by flow controller **352** specifically (and plumbing/control subsystem **20** generally), as an instantaneous transition from a first flow rate to a second flow rate is no longer required.

[0205] Additionally, trajectory shaping controller **350** may allow for the pre-fill wetting and post-fill rinsing of nozzle **24**. In some embodiments, and/or for some recipes, one or more ingredients may present problems to the nozzle **24** if the ingredient (referred to herein as “dirty ingredient”) contacts the nozzle **24** directly, i.e., in the form in which it is stored. In some embodiments, the nozzle **24** may be pre-fill wetted with a “pre-fill” ingredient, for example, water, so as to prevent the direct contact of these “dirty ingredients” with the nozzle **24**. The nozzle **24** may following, be

post-fill rinsed with a “post-wash ingredient”, for example, water.

[0206] Specifically, in the event that nozzle **24** is pre-fill wetted with, for example, 10 mL of water, and/or post-fill rinsed with, for example, 10 mL of water or any “post-wash” ingredient, once the adding of the dirty ingredient has stopped, trajectory shaping controller **350** may offset the pre-wash ingredient added during the pre-fill wetting and/or post-fill rinsing by providing an additional quantity of dirty ingredient during the fill process. Specifically, as container **30** is being filled with product **28**, the pre-fill rinse water or “pre-wash” may result in product **28** being initially under-concentrated with the dirty ingredient, Trajectory shaping controller **350** may then add dirty ingredient at a higher-than-needed flow rate, resulting in product **28** transitioning from “under-concentrated” to “appropriately concentrated” to “over-concentrated”, or present in a concentration higher than that which is called for by the particular recipe. However, once the appropriate amount of dirty ingredient has been added, the post-fill rinse process may add additional water, or another appropriate “post-wash ingredient”, resulting in product **28** once again becoming “appropriately-concentrated” with the dirty ingredient.

[0207] Flow controller **352** may be configured as a proportional-integral (PI) loop controller. Flow controller **352** may perform the comparison and processing that was generally described above as being performed by feedback controller system **188**. For example, flow controller **352** may be configured to receive feedback signal **182** from flow measuring device **176**. Flow controller **352** may compare flow feedback signal **182** to the desired flow volume (as defined by control logic subsystem **14** and modified by trajectory shaping controller **350**). Upon processing flow feedback signal **182**, flow controller **352** may generate flow control signal **194** that may be provided to variable line impedance **200**.

[0208] Feed forward controller **354** may provide a “best guess” estimate concerning what the initial position of variable line impedance **200** should be. Specifically, assume that at a defined constant pressure, variable line impedance has a flow rate (for chilled carbonated water **164**) of between 0.00 mL/second and 120.00 mL/second. Further, assume that a flow rate of 40 mL/second is desired when filling container **30** with a beverage product **28**. Accordingly, feed forward controller **354** may provide a feed forward signal (on feed forward line **384**) that initially opens variable line impedance **200** to 33.33% of its maximum opening (assuming that variable line impedance **200** operates in a linear fashion).

[0209] When determining the value of the feed forward signal, feed forward controller **354** may utilize a lookup table (not shown) that may be developed empirically and may define the signal to be provided for various initial flow rates. An example of such a lookup table may include, but is not limited to, the following table:

TABLE-US-00001 Flowrate Signal to stepper mL/second controller 0 pulse to 0 degrees 20 pulse to 30 degrees 40 pulse to 60 degrees 60 pulse to 150 degrees 80 pulse to 240 degrees 100 pulse to 270 degrees 120 pulse to 300 degrees

[0210] Again, assuming that a flow rate of 40 mL/second is desired when filling container **30** with beverage product **28**, for example, feed forward controller **354** may utilize the above-described lookup table and may pulse the stepper motor to 60.0 degrees (using feed forward line **384**).

Although in the exemplary embodiment a stepper motor is used, in various other embodiments, any other type of motor may be used including but not limited to a servo motor. Unit delay **356** may form a feedback path through which a previous version of the control signal (provided to variable line impedance **200**) is provided to flow controller **352**.

[0211] Saturation controller **358** may be configured to disable the integral control of feedback controller system **188** (which, as discussed above, may be configured as a PI loop controller) whenever variable line impedance **200** is set to a maximum flow rate (by stepper controller **360**), thus increasing the stability of the system by reducing flow rate overshoots and system oscillations.

[0212] Stepper controller **360** may be configured to convert the signal provided by saturation controller **358** (on line **386**) into a signal usable by variable line impedance **200**. Variable line

impedance **200** may include a stepper motor for adjusting the orifice size (and, therefore, the flow rate) of variable line impedance **200**. Accordingly, control signal **194** may be configured to control the stepper motor included within variable line impedance.

[0213] Referring also to FIG. **6B**, an example of flow measuring devices **176**, **178**, **180** of flow control modules **170**, **172**, **174**, respectively, may include but is not limited to a paddle wheel flow measuring device, a turbine-type flow measuring device, or a positive displacement flow measuring device (e.g., gear-based, positive displacement flow measuring device **388**). Thus, in various embodiments, the flow measuring device may be any device capable of measuring flow, either directly or indirectly. In the exemplary embodiment, a gear-based, positive displacement, flow measuring device **388** is used. In this embodiment, the flow measuring device **388** may include a plurality of meshing gears (e.g., gears **390**, **392**) that e.g., may require that any content passing through gear-based, positive displacement flow measuring device **388** follow one or more defined pathways (e.g., pathways **394**, **396**), resulting in e.g., the counterclockwise rotation of gear **390** and the clockwise rotation of gear **392**. By monitoring the rotation of gears **390**, **392**, a feedback signal (e.g., feedback signal **182**) may be generated and provided to the appropriate flow controller (e.g., flow controller **352**).

[0214] Referring also to FIGS. **7-14**, various illustrative embodiments of a flow control module (e.g., flow control module **170**) are shown. However, as discussed above, the order of the various assemblies may vary in various embodiments, i.e., the assemblies may be arranged in any order desired. For example, in some embodiments the assemblies are arranged in the following order: flow measuring device, binary valve, variable impedance; while in other embodiments, the assemblies are arranged in the following order: flow measuring device, variable impedance, binary valve. In some embodiments, it may be desired to vary the order of the assemblies to either maintain pressure and fluid on the variable impedance or vary the pressure on the variable impedance. In some embodiments, the variable impedance valve may include a lip seal. In these embodiments, it may be desirable to maintain pressure and fluid on the lip seal. This may be accomplished by ordering the assemblies as follows: flow measuring device, variable impedance, and binary valve. The binary valve being downstream from the variable line impedance maintains pressure and liquid on the variable impedance such that the lip seal maintains a desirable seal.

[0215] Referring first to FIGS. **7A** and **7B**, one embodiment of the flow control module **170a** is shown. In some embodiments, the flow control module **170a** may generally include flow meter **176a**, variable line impedance **200a** and binary valve **212a**, and may have a generally linear fluid flow path there-through. Flow meter **176a** may include fluid inlet **400** for receiving a high-volume ingredient from high-volume ingredient subsystem **16**. Fluid inlet **400** may communicate the high-volume ingredient to a gear-based, positive displacement, flow measuring device (e.g., gear-based, positive displacement device **388** generally described above), including a plurality of intermeshing gears (e.g., including gear **390**) disposed within housing **402**. The high-volume ingredient may pass from flow meter **176a** to a binary valve **212a** via fluid passage **404**.

[0216] Binary valve **212a** may include banjo valve **406** actuated by solenoid **408**. Banjo valve **406** may be biased (e.g., by a spring, not shown) to position banjo valve **406** toward a closed position, thereby preventing the flow of the high-volume ingredient through flow control module **170a**. Solenoid coil **408** may be energized (e.g., in response to a control signal from control logic subsystem **14**), to linearly drive plunger **410**, via linkage **412**, to move banjo valve **406** out of scaling engagement with valve seat **414**, thereby opening binary valve **212a** to permitting flow of the high-volume ingredient to variable line impedance **200a**.

[0217] As mentioned above, variable line impedance **200a** may regulate the flow of the high-volume ingredients. Variable line impedance **200a** may include drive motor **416**, which may include, but is not limited to a stepper motor, or a servo motor. Drive motor **416** may be coupled to variable impedance valve **418**, generally. As mentioned above, variable impedance valve **418** may control the flow of the high-volume ingredients, e.g., passing from binary valve **212a** via fluid

passage **420**, and exiting from fluid discharge **422**. Examples of variable impedance valve **418** are disclosed and claimed in U.S. Pat. No. 5,755,683 (Attorney Docket B13) and U.S. Patent Publication No.: 2007/0085049 (Attorney Docket E66), both of which are incorporated by reference in their entireties. While not shown, a gearbox may be coupled between drive motor **416** and variable impedance valve **418**.

[0218] Referring also to FIGS. **8** and **9**, another embodiment of a flow control module (e.g., flow control module **170b**) is shown, generally including flow meter **176b**, binary valve **212b**, and variable line impedance **200b**. Similar to flow control module **170a**, flow control module **170b** may include fluid inlet **400**, which may communicate the high-volume ingredient to flow meter **176b**. Flow meter **176b** may include meshing gears **390**, **392** disposed within cavity **424**, e.g., which may be formed within housing member **402**. Meshing gears **390**, **392** and cavity **424** may define flow pathways about the perimeter of cavity **424**. The high-volume ingredient may pass from flow meter **176b** to binary valve **212b** via fluid passage **404**. As shown, fluid inlet **400** and fluid passage **404** may provide for a 90 degree flow path in to, and out of, flow meter **176b** (i.e., into and out of cavity **424**).

[0219] Binary valve **212b** may include banjo valve **406**, urged into engagement with valve seat **414** (e.g., in response to a biasing force applied by spring **426** via linkage **412**). When solenoid coil **408** is energized, plunger **410** may be retracted toward solenoid coil **408**, thereby moving banjo valve **406** out of sealing engagement with valve seat **414**, thereby allowing the high-volume ingredient to flow to variable line impedance **200b**. In other embodiments, the banjo valve **406** may be downstream from the variable line impedance **200b**.

[0220] Variable line impedance **200b** may generally include a first rigid member (e.g., shaft **428**) having a first surface. Shaft **428** may define a first fluid-path portion with a first terminus at the first surface. The first terminus may include a groove (e.g., groove **430**) defined on the first surface (e.g., of shaft **428**). Groove **430** may taper from a large cross-sectional area to a small cross-sectional area normal to the tangent of the curve of the first surface. However, in other embodiments, the shaft **428** may include a bore (i.e., a straight ball-style hole, see FIG. **15C**) rather than a groove **430**. A second rigid member (e.g., housing **432**) may have a second surface (e.g., inner bore **434**). The second rigid member (e.g., housing **432**) may define a second fluid-path portion with a second terminus at the second surface. The first and second rigid members are capable of being rotated with respect to each other from a fully open position continuously through partially open positions to a closed position. For example, shaft **428** may be rotatably driven relative to housing **432** by drive motor **416** (e.g., which may include, a stepper motor or a servo motor). The first and second surfaces define a space therebetween. An aperture (e.g., opening **436**) in the second rigid member (i.e., housing **432**) may provide fluid communication between the first and second fluid-path portions when the first and second rigid members are in the fully open position or in one of the partially open positions with respect to each other. Fluid flowing between the first and second fluid-path portions flows through the groove (i.e., groove **430**) as well as the aperture (i.e., opening **436**). At least one sealing means (e.g., a gasket, o-ring, or the like, not shown) in some embodiments, may be disposed between the first and second surfaces providing a seal between the first and second rigid members for preventing fluid from leaking out of the space which also prevents fluid leaking from the desired flow path. However, in the exemplary embodiment as shown, this type of sealing means is not used. Rather, in the exemplary embodiments, a lip seal **429** or other sealing means, is used to seal the space.

[0221] Various connection arrangements may be included for fluidly coupling flow control modules **170**, **172**, **174** to high-volume ingredient subsystem **16** and/or downstream components, e.g., nozzle **24**. For example, as shown in FIGS. **8** and **9** with respect to flow control module **170b**, locking plate **438** may be slidably disposed relative to guide feature **440**. A fluid line (not shown) may be at least partially inserted into fluid discharge **422** and locking plate **438** may be slidably translated to lock the fluid line in engagement with fluid discharge. Various gaskets, o-rings, or the

like may be employed to provide a fluid-tight connection between the fluid line and fluid discharge **422**.

[0222] FIGS. **10** through **13** depict various additional embodiments of flow control modules (e.g., flow control modules **170c**, **170d**, **170e**, and **170f**, respectively). Flow control modules **170c**, **170d**, **170c**, **170f** generally differ from previously described flow control modules **170a**, **170b** in terms of fluid connections and relative variable line impedance **200** and binary valve **212** orientations. For example, flow control modules **170d** and **170f**, shown in FIGS. **11** and **13** respectively, may include barbed fluid connections **442** for communicating fluid to/from flow meters **176d** and **176f**.

Similarly, flow control module **170c** may include barbed fluid connection **444** for communicating fluid to/from variable line impedance **200c**. Various additional/alternative fluid connection arrangements may be equally utilized. Similarly, various relative orientations of solenoid **408** and configurations of spring bias for banjo valve **406** may be employed to suit various packaging arrangements and design criteria.

[0223] Referring also to FIGS. **14A-14C**, yet another embodiment of a flow control module is depicted (i.e., flow control module **170g**). Flow control module **170g** may generally include flow meter **176g**, variable line impedance **200g**, and binary valve **212g** (e.g., which may be a solenoid actuated banjo valve, as generally described herein above). Referring to FIG. **14C**, the lip seals **202g** may be seen. Also, FIG. **14C** shows one exemplary embodiment where the flow control module includes a cover which may provide protection to the various flow control module assemblies. Although not depicted in all embodiments shown, each of the embodiments of the flow control module may also include a cover

[0224] It should be noted that while the flow control module (e.g., flow control modules **170**, **172**, **174**) have been described as being configured such that high-volume ingredients flow from high-volume ingredient subsystem **16** to the flow meter (e.g., flow meters **176**, **178**, **180**), then to the variable line impedance (e.g., variable line impedance **200**, **202**, **204**), and finally through the binary valve (e.g., binary valves **212**, **214**, **216**), this should not be construed as a limitation on the present disclosure. For example, as shown and discussed with respect to FIGS. **7** through **14C**, the flow control modules may be configured having a flow path from high-volume ingredient subsystem **16**, to the flow meter (e.g., flow meters **176**, **178**, **180**), then to the binary valve (e.g., binary valve **212**, **214**, **216**), and finally through the variable line impedance (e.g., variable line impedance **200**, **202**, **204**). Various additional/alternative configurations may be equally utilized. Additionally, one or more additional components may be interconnected between one or more of the flow meter, the binary valve, and the variable line impedance.

[0225] Referring to FIGS. **15A** and **15B**, a portion of a variable line impedance (e.g., variable line impedance **200**) is shown including drive motor **416** (e.g., which may be a stepper motor, a servo motor, or the like). Drive motor **416** may coupled to shaft **428**, having groove **430** therein. Referring now to FIG. **15C**, in some embodiments, the shaft **428** includes a bore, and in the exemplary embodiment, as shown in FIG. **15C**, the bore is a ball-shaped bore. As discussed, e.g., with reference to FIGS. **8** and **9**, drive motor **416** may rotate shaft **428** relative to a housing (e.g., housing **432**) to regulate flow through the variable line impedance. Magnet **446** may be coupled to shaft **428** (e.g., maybe at least partially disposed within axial opening in shaft **428**). Magnet **446** may be generally diametrically magnetized, providing south pole **450** and north pole **452**. The rotational position of shaft **428** may be determined, e.g., based upon the magnetic flux imparted by magnet **446** on one or more magnetic flux sensing devices, e.g., sensors **454**, **456** shown in FIG. **9**. Magnetic flux sensing devices may include, but are not limited to, for example, a Hall-Effect sensor, or the like. The magnetic flux sensing device may provide a position feedback signal, e.g., to control logic subsystem **14**.

[0226] Referring again to FIG. **15C**, in some embodiments, the magnet **446** is located on the opposite side as the embodiment shown and described above with respect to FIGS. **8** and **9**. Additionally, in this embodiment, the magnet **446** is held by magnet holder **480**.

[0227] In addition/as an alternative to utilizing magnetic position sensors (e.g., for determining the rotational position of the shaft), the variable line impedance may be determined based upon, at least in part, a motor position, or an optical sensor to detect shaft position.

[0228] Referring next to FIGS. **16A** and **16B**, a gear (e.g., gear **390**) of a gear-based, positive displacement, flow measuring device (e.g., gear-based, positive displacement, flow measuring device **388**) may include one or more magnets (e.g., magnets **458**, **460**) coupled thereto. As discussed above, as a fluid (e.g., a high-volume ingredient) flows through gear-based, positive displacement, flow measuring device **388**, gear **390** (and gear **392**) may rotate. The rate of rotation of gear **390** may be generally proportional to the flow rate of the fluid passing through gear-based, positive displacement, flow measuring device **388**. The rotation (and/or rate of rotation) of gear **390** may be measured using a magnetic flux sensor (e.g., a Hall-Effect sensor, or the like), which may measure the rotational movement of axial magnets **458**, **460** coupled to gear **390**. The magnetic flux sensor, e.g., which may be disposed on printed circuit board **462**, depicted in FIG. **8**, may provide a flow feedback signal (e.g., flow feedback signal **182**) to a flow feedback controller system (e.g., feedback controller system **188**).

Flow Control Module Leak Detect

[0229] In various embodiments, a flow control module may be in an operational state but fluid should not be flowing, i.e., the flow control module is not acting on any pump command. In some embodiments, a system including a method for leak detection may be used to detect fluid flow from the flow control module when fluid should not be flowing.

[0230] In various embodiments of the flow control module leak detect, the leak detect may be activated when the flow control module is not acting on any pump commands, and the banjo valve or other valve controller is idle and the gear meter monitor is idle any post-pour gear meter spin-down time has elapsed. When these conditions are met, the leak detection is activated. In some embodiments, a predetermined lapsed time may be given to the flow control module before the leak detection is activated.

[0231] Referring now also to FIG. **76**, in various embodiments, the leak detection method includes three states: leak test start; leak test initialize and leak test run. In the leak test start the leak detection is idle because one or more of the activation criteria have not been met. In various embodiments, the activation criteria may include one or more of the above-described criteria. In the leak test initialize state the timing guard band, which occurs when the flow control module transitions from an active state to an idle state (i.e. once the activation criteria have been met) is controlled. In the leak test run state, once the timing guard band has elapsed, the leak test method remains in this state until the flow control module is activated.

[0232] Referring now also to FIG. **77**, at a high level, the FCM leak detection method receives and monitors the fluid volume communicated and determined by the gear meter. If that reported volume exceeds a pre-determined, preset threshold, an alert is raised. To accomplish this, a “leaky integrator” algorithm is used which, in some embodiments, includes for each update, the fluid volume measured by the gear meter is added to a running sum—the integrator; and if the integrator exceeds a threshold, a leak is determined. For each update, the integrator is then reduced by a fixed “drain amount”. The running sum does not have a value below zero.

[0233] In various embodiments, three coefficients may be used; these include the Update Period, the Leak Detection Threshold and the Integrator Drain Rate. In various other embodiments, different coefficients may be used or additional or less coefficients may be used.

[0234] In some embodiments, the Update Period defines how often the leak detect is executed. In some embodiments, the leak detect may be executed regularly, for example, executes once every 2 seconds (0.5 Hz). In some embodiments, the Leak Detection Threshold is set and if the integrator exceeds this value, a leak is declared. The Leak Detection Threshold may, in some embodiments, be defined in terms of the maximum flow rate defined in the flow control module calibration data as follows:

[00002] Leak_Detection_Threshold = (0.25 * FCM_Maximum_Flow_Rate) * Update_Period
[0235] In some embodiments, the Integrator Drain Rate is a value in which the integrated gear meter flow is reduced by for each update. This may be beneficial for example because draining the integrator improves the method's noise immunity and allows the algorithm to reset should a leak condition clear. The Integrator Drain Rate is defined in terms of the maximum flow rate defined in the flow control module's calibration data as follows:

[00003] Integrator_Drain_Rate = (0.01 * FCM_Maximum_Flow_Rate) * Update_Period

[0236] In various embodiments, a leak is determined and, in some embodiments, an alert or alarm is generated when the following conditions are met: the Integrator exceeds the Leak Detection Threshold and the alert generation is “armed”. In various embodiments, the alert generation is “armed” when the algorithm is initialized and whenever the integrator is zero. In various embodiments, the alert generation is “disarmed” when an alert is generated. This arming/disarming process keeps the method and system from generating a large number of alerts for a single leak event. The following are examples of when alerts may be generated. These are given only by illustration and example and are not intended to be an exhaustive list. In various embodiments, the method may vary and different conditions may generate alerts/alarms. In various embodiments, additional conditions may generate alerts/alarms.

[0237] As an example, a flow control module leaks steadily until the integrator exceeds the threshold. The flow control module continues to leak. In this example, a single alert may be generated when the integrator first crosses the threshold.

[0238] As another example, a flow control module leaks intermittently until the integrator eventually exceeds the threshold. The integrator then oscillates around the threshold. In this example, a single alert may be generated when the integrator first crosses the threshold. The disarming logic present in some embodiments may prevent subsequent nuisance alerts should the integrator re-cross the threshold.

[0239] As another example, a flow control module leaks steadily until the integrator exceeds the threshold. The flow control module then stops leaking. In this example, an alert may be generated when the integrator first crosses the threshold. When the flow control module stops leaking, the integrator may slowly drain all the way back to zero. Once the integrator drains back to zero, alert generation may be re-armed so that additional alerts may be generated should the flow control module begin to leak again.

[0240] Referring now also to FIG. 77, this graph presents data collected during an example of the leak detection method. In this example, a high fructose corn syrup leak was simulated using a flow control module manual override. The manual override was toggled open-and-closed for a period of time, and then held in its full-open position. Once a leak was declared, the manual override was closed. As shown in FIG. 77, the integrator can be seen to grow until the leak is declared. At that point the integrator is not allowed to grow any more. Once the manual override is closed, the integrator can be seen to drain back to zero at which time the leak state is cleared and the alert is re-armed.

[0241] Referring also to FIG. 17, a diagrammatic view of user interface subsystem 22 is shown. User interface subsystem 22 may include touch screen interface 500 (exemplary embodiments described below with respect to FIGS. 51-53) that allows user 26 to select various options concerning beverage 28. For example, user 26 (via “drink size” column 502) may be able to select the size of beverage 28. Examples of the selectable sizes may include but are not limited to: “12 ounce”; “16 ounce”; “20 ounce”; “24 ounce”; “32 ounce”; and “48 ounce”.

[0242] User 26 may be able to select (via “drink type” column 504) the type of beverage 28. Examples of the selectable types may include but are not limited to: “cola”; “lemon-lime”; “root beer”; “iced tea”; “lemonade”; and “fruit punch”.

[0243] User 26 may also be able to select (via “add-ins” column 506) one or more flavorings/products for inclusion within beverage 28. Examples of the selectable add-ins may

include but are not limited to: “cherry flavor”; “lemon flavor”; “lime flavor”; “chocolate flavor”; “coffee flavor”; and “ice cream”.

[0244] Further, user **26** may be able to select (via “nutraceuticals” column **508**) one or more nutraceuticals for inclusion within beverage **28**. Examples of such nutraceuticals may include but are not limited to: “Vitamin A”; “Vitamin B6”; “Vitamin B12”; “Vitamin C”; “Vitamin D”; and “Zinc”.

[0245] In some embodiments, an additional screen at a level lower than the touch screen may include a “remote control” (not shown) for the screen. The remote control may include buttons indicating up, down, left and right and select, for example. However, in other embodiments, additional buttons may be included.

[0246] Once user **26** has made the appropriate selections, user **26** may select “GO!” button **510** and user interface subsystem **22** may provide the appropriate data signals (via data bus **32**) to control logic subsystem **14**. Once received, control logic subsystem **14** may retrieve the appropriate data from storage subsystem **12** and may provide the appropriate control signals to e.g., high volume ingredient subsystem **16**, microingredient subsystem **18**, and plumbing/control subsystem **20**, which may be processed (in the manner discussed above) to prepare beverage **28**. Alternatively, user **26** may select “Cancel” button **512** and touch screen interface **500** may be reset to a default state (e.g., no buttons selected).

[0247] User interface subsystem **22** may be configured to allow for bidirectional communication with user **26**. For example, user interface subsystem **22** may include informational screen **514** that allows processing system **10** to provide information to user **26**. Examples of the types of information that may be provided to user **26** may include but is not limited to advertisements, information concerning system malfunctions/warnings, and information concerning the cost of various products.

[0248] As discussed above, control logic subsystem **14** may execute one or more control processes **120** that may control the operation of processing system **10**. Accordingly, control logic subsystem **14** may execute a finite state machine process (e.g., FSM process **122**).

[0249] As also discussed above, during use of processing system **10**, user **26** may select a particular beverage **28** for dispensing (into container **30**) using user interface subsystem **22**. Via user interface subsystem **22**, user **26** may select one or more options for inclusion within such beverage. Once user **26** makes the appropriate selections, via user interface subsystem **22**, user interface subsystem **22** may send the appropriate indication to control logic subsystem **14**, indicating the selections and preferences of user **26** (with respect to beverage **28**).

[0250] When making a selection, user **26** may select a multi-portion recipe that is essentially the combination of two separate and distinct recipes that produces a multi-component product. For example, user **26** may select a root beer float, which is a multi-portion recipe that is essentially the combination of two separate and distinct components (i.e. vanilla ice cream and root beer soda). As a further example, user **26** may select a drink that is a combination of cola and coffee. This cola/coffee combination is essentially a combination of two separate and distinct components (i.e. cola soda and coffee).

[0251] Referring also to FIG. **18**, upon receiving **550** the above-described indication, FSM process **122** may process **552** the indication to determine if the product to be produced (e.g., beverage **28**) is a multi-component product.

[0252] If the product to be produced is a multi-component product **554**, FSM process **122** may identify **556** the recipe(s) required to produce each of the components of the multi-component product. The recipe(s) identified may be chosen from plurality of recipes **36** maintained on storage subsystem **12**, shown in FIG. **1**.

[0253] If the product to be produced is not a multi-component product **554**, FSM process **122** may identify **558** a single recipe for producing the product. The single recipe may be chosen from plurality of recipes **36** maintained on storage subsystem **12**. Accordingly, if the indication received

550 and processed **552** was an indication that defined a lemon-lime soda, as this is not a multi-component product, FSM process **122** may identify **558** the single recipe required to produce the lemon-lime soda.

[0254] If the indication concerns a multi-component product **554**, upon identifying **556** the appropriate recipes chosen from plurality of recipes **36** maintained on storage subsystem **12**, FSM process **122** may parse **560** each of the recipes into a plurality of discrete states and define one or more state transitions. FSM process **122** may then define **562** at least one finite state machine (for each recipe) using at least a portion of the plurality of discrete states.

[0255] If the indication does not concern a multi-component product **554**, upon identifying **558** the appropriate recipe chosen from plurality of recipes **36** maintained on storage subsystem **12**, FSM process **122** may parse **564** the recipe into a plurality of discrete states and define one or more state transitions. FSM process **122** may then define **566** at least one finite state machine for the recipe using at least a portion of the plurality of discrete states.

[0256] As is known in the art, a finite state machine (FSM) is a model of behavior composed of a finite number of states, transitions between those states and/or actions. For example and referring also to FIG. **19**, if defining a finite state machine for a physical doorway that can either be fully opened or fully closed, the finite state machine may include two states, namely “opened” state **570** and “closed” state **572**. Additionally, two transitions may be defined that allow for the transition from one state to another state. For example, transition state **574** “opens” the door (thus transitioning from “closed” state **572** to “open” state **570**) and transition state **576** “closes” the door (thus transitioning from “opened” state **570** to “closed” state **572**).

[0257] Referring also to FIG. **20**, a state diagram **600** concerning the manner in which coffee may be brewed is shown. State diagram **600** is shown to include five states, namely: idle state **602**; ready to brew state **604**; brewing state **605**; maintain temperature state **608**; and off state **610**. Additionally, five transition states are shown. For example, transition state **612** (e.g., installing coffee filter, installing coffee grounds, filling coffee machine with water) may transition from idle state **602** to ready to brew state **604**. Transition state **614** (e.g., pressing the brew button) may transition from ready to brew state **604** to brewing state **606**. Transition state **616** (e.g., exhausting the water supply) may transition from brewing state **606** to maintain temperature **608**. Transition state **618** (e.g., turning the power switch off or exceeding a maximum “maintain temperature” time) may transition from maintain temperature state **608** to off state **610**. Transition state **620** (e.g., turning the power switch on) may transition from off state **610** to idle state **602**.

[0258] Accordingly, FSM process **122** may generate one or more finite state machines that correspond to the recipes (or portions thereof) utilized to produce a product. Once the appropriate finite state machines are produced, control logic subsystem **14** may execute the finite state machine(s) and generate the product (e.g., multi-component or single component) requested by e.g., user **26**.

[0259] Accordingly, assume that processing system **10** receives **550** an indication (via user interface subsystem **22**) that user **26** has selected a root beer float. FSM process **122** may process **552** the indication to determine if the root beer float is a multi-component product **554**. As the root beer float is a multi-component product, FSM process **122** may identify **556** the recipes required to produce the root beer float (namely the recipe for root beer soda and the recipe for vanilla ice cream) and parse **560** the recipe for root beer soda and the recipe for vanilla ice cream into a plurality of discrete states and define one or more state transitions. FSM process **122** may then define **562** at least one finite state machine (for each recipe) using at least a portion of the plurality of discrete states. These finite state machines may subsequently be executed by control logic subsystem **14** to produce the root beer float selected by user **26**.

[0260] When executing the state machines corresponding to the recipes, processing system **10** may utilize one or more manifolds (not shown) included within processing system **10**. As used in this disclosure, a manifold is a temporary storage area designed to allow for the execution of one or

more processes. In order to facilitate the movement of ingredients into and out of the manifolds, processing system **10** may include a plurality of valves (controllable by e.g., control logic subsystem **14**) for facilitating the transfer of ingredients between manifolds. Examples of various types of manifolds may include but are not limited to: a mixing manifold, a blending manifold, a grinding manifold, a heating manifold, a cooling manifold, a freezing manifold, a steeping manifold, a nozzle, a pressure manifold, a vacuum manifold, and an agitation manifold.

[0261] For example, when making coffee, a grinding manifold may grind coffee beans. Once the beans are ground, water may be provided to a heating manifold in which water **160** is heated to a predefined temperature (e.g. 212° F.). Once the water is heated, the heated water (as produced by the heating manifold) may be filtered through the ground coffee beans (as produced by the grinding manifold). Additionally and depending on how processing system **10** is configured, processing system **10** may add cream and/or sugar to the coffee produced in another manifold or at nozzle **24**.

[0262] Accordingly, each portion of a multi-portion recipe may be executed in a different manifold included within processing system **10**. Therefore, each component of a multi-component recipe may be produced in a different manifold included within processing system **10**. Continuing with the above-stated example, the first component of the multi-component product (i.e., the root beer soda) may be produced within a mixing manifold included within processing system **10**. Further, the second component of the multi-component product (i.e., the vanilla ice cream) may be produced within a freezing manifold included within processing system **10**.

[0263] As discussed above, control logic subsystem **14** may execute one or more control processes **120** that may control the operation of processing system **10**. Accordingly, control logic subsystem **14** may execute virtual machine process **124**.

[0264] As also discussed above, during use of processing system **10**, user **26** may select a particular beverage **28** for dispensing (into container **30**) using user interface subsystem **22**. Via user interface subsystem **22**, user **26** may select one or more options for inclusion within such beverage. Once user **26** makes the appropriate selections, via user interface subsystem **22**, user interface subsystem **22** may send the appropriate instructions to control logic subsystem **14**.

[0265] When making a selection, user **26** may select a multi-portion recipe that is essentially the combination of two separate and distinct recipes that produces a multi-component product. For example, user **26** may select a root beer float, which is a multi-portion recipe that is essentially the combination of two separate and distinct components (i.e. vanilla ice cream and root beer soda). As a further example, user **26** may select a drink that is a combination of cola and coffee.

[0266] This cola/coffee combination is essentially a combination of two separate and distinct components (i.e. cola soda and coffee).

[0267] Referring also to FIG. **21**, upon receiving **650** the above-described instructions, virtual machine process **124** may process **652** these instructions to determine if the product to be produced (e.g., beverage **28**) is a multi-component product.

[0268] If **654** the product to be produced is a multi-component product, virtual machine process **124** may identify **656** a first recipe for producing a first component of the multi-component product and at least a second recipe for producing at least a second component of the multi-component product. The first and second recipes may be chosen from plurality of recipes **36** maintained on storage subsystem **12**.

[0269] If **654** the product to be produced is not a multi-component product, virtual machine process **124** may identify **658** a single recipe for producing the product. The single recipe may be chosen from plurality of recipes **36** maintained on storage subsystem **12**. Accordingly, if the instructions received **650** were instructions concerning a lemon-lime soda, as this is not a multi-component product, virtual machine process **124** may identify **658** the single recipe required to produce the lemon-lime soda.

[0270] Upon identifying **656**, **658** the recipe(s) from plurality of recipes **36** maintained on storage subsystem **12**, control logic subsystem **14** may execute **660**, **662** the recipe(s) and provide the

appropriate control signals (via data bus **38**) to e.g. high volume ingredient subsystem **16** microingredient subsystem **18** and plumbing/control subsystem **20**, resulting in the production of beverage **28** (which is dispensed into container **30**).

[0271] Accordingly, assume that processing system **10** receives instructions (via user interface subsystem **22**) to create a root beer float. Virtual machine process **124** may process **652** these instructions to determine if **654** the root beer float is a multi-component product. As the root beer float is a multi-component product, virtual machine process **124** may identify **656** the recipes required to produce the root beer float (namely the recipe for root beer soda and the recipe for vanilla ice cream) and execute **660** both recipes to produce root beer soda and vanilla ice cream (respectively). Once these products are produced, processing system **10** may combine the individual products (namely root beer soda and vanilla ice cream) to produce the root beer float requested by user **26**.

[0272] When executing a recipe, processing system **10** may utilize one or more manifolds (not shown) included within processing system **10**. As used in this disclosure, a manifold is a temporary storage area designed to allow for the execution of one or more processes. In order to facilitate the movement of ingredients into and out of the manifolds, processing system **10** may include a plurality of valves (controllable by e.g., control logic subsystem **14**) for facilitating the transfer of ingredients between manifolds. Examples of various types of manifolds may include but are not limited to: a mixing manifold, a blending manifold, a grinding manifold, a heating manifold, a cooling manifold, a freezing manifold, a steeping manifold, a nozzle, a pressure manifold, a vacuum manifold, and an agitation manifold.

[0273] For example, when making coffee, a grinding manifold may grind coffee beans. Once the beans are ground, water may be provided to a heating manifold in which water **160** is heated to a predefined temperature (e.g. 212° F.). Once the water is heated, the heated water (as produced by the heating manifold) may be filtered through the ground coffee beans (as produced by the grinding manifold). Additionally and depending on how processing system **10** is configured, processing system **10** may add cream and/or sugar to the coffee produced in another manifold or at nozzle **24**.

[0274] Accordingly, each portion of a multi-portion recipe may be executed in a different manifold included within processing system **10**. Therefore, each component of a multi-component recipe may be produced in a different manifold included within processing system **10**. Continuing with the above-stated example, the first portion of the multi-portion recipe (i.e., the one or more processes utilized by processing system **10** to make root beer soda) may be executed within a mixing manifold included within processing system **10**. Further, the second portion of the multi-portion recipe (i.e., the one or more processes utilized by processing system to make vanilla ice cream) may be executed within a freezing manifold included within processing system **10**.

[0275] As discussed above, during use of processing system **10**, user **26** may select a particular beverage **28** for dispensing (into container **30**) using user interface subsystem **22**. Via user interface subsystem **22**, user **26** may select one or more options for inclusion within such beverage. Once user **26** makes the appropriate selections, via user interface subsystem **22**, user interface subsystem **22** may send the appropriate data signals (via data bus **32**) to control logic subsystem **14**. Control logic subsystem **14** may process these data signals and may retrieve (via data bus **34**) one or more recipes chosen from plurality of recipes **36** maintained on storage subsystem **12**. Upon retrieving the recipe(s) from storage subsystem **12**, control logic subsystem **14** may process the recipe(s) and provide the appropriate control signals (via data bus **38**) to e.g. high volume ingredient subsystem **16** microingredient subsystem **18** and plumbing/control subsystem **20**, resulting in the production of beverage **28** (which is dispensed into container **30**).

[0276] When user **26** makes their selection, user **26** may select a multi-portion recipe that is essentially the combination of two separate and distinct recipes. For example, user **26** may select a root beer float, which is a multi-portion recipe that is essentially the combination of two separate and distinct recipes (i.e. vanilla ice cream and root beer soda). As a further example, user **26** may

select a drink that is a combination of cola and coffee. This cola/coffee combination is essentially a combination of two separate and distinct recipes (i.e. cola soda and coffee).

[0277] Accordingly, assume that processing system **10** receives instructions (via user interface subsystem **22**) to create a root beer float, knowing that a recipe for a root beer float is a multi-portion recipe, processing system **10** may simply obtain the standalone recipe for root beer soda, obtain the standalone recipe for vanilla ice cream, and execute both recipes to produce root beer soda and vanilla ice cream (respectively). Once these products are produced, processing system may combine the individual products (namely root beer soda and vanilla ice cream) to produce the root beer float requested by user **26**.

[0278] When executing a recipe, processing system **10** may utilize one or more manifolds (not shown) included within processing system **10**. As used in this disclosure, a manifold is a temporary storage area designed to allow for the execution of one or more processes. In order to facilitate the movement of ingredients into and out of the manifolds, processing system **10** may include a plurality of valves (controllable by e.g., control logic subsystem **14**) for facilitating the transfer of ingredients between manifolds. Examples of various types of manifolds may include but are not limited to: a mixing manifold, a blending manifold, a grinding manifold, a heating manifold, a cooling manifold, a freezing manifold, a steeping manifold, a nozzle, a pressure manifold, a vacuum manifold, and an agitation manifold.

[0279] For example, when making coffee, a grinding manifold may grind coffee beans. Once the beans are ground, water may be provided to a heating manifold in which water **160** is heated to a predefined temperature (e.g. 212° F.). Once the water is heated, the heated water (as produced by the heating manifold) may be filtered through the ground coffee beans (as produced by the grinding manifold). Additionally and depending on how processing system **10** is configured, processing system **10** may add cream and/or sugar to the coffee produced in another manifold or at nozzle **24**.

[0280] As discussed above, control logic subsystem **14** may execute one or more control processes **120** that may control the operation of processing system **10**. Accordingly, control logic subsystem **14** may execute virtual manifold process **126**.

[0281] Referring also to FIG. **22**, virtual manifold process **126** may monitor **680** one or more processes occurring during a first portion of a multi-portion recipe being executed on e.g., processing system **10** to obtain data concerning at least of portion of the one or more processes. For example, assume that the multi-portion recipe concerns the making of a root beer float, which (as discussed above) is essentially the combination of two separate and distinct recipes (i.e. root beer soda and vanilla ice cream) that may be chosen from plurality of recipes **36** maintained on storage subsystem **12**. Accordingly, the first portion of the multi-portion recipe may be considered the one or more processes utilized by processing system **10** to make root beer soda. Further, the second portion of the multi-portion recipe may be considered the one or more processes utilized by processing system **10** to make vanilla ice cream.

[0282] Each portion of these multi-portion recipes may be executed in a different manifold included within processing system **10**. For example, the first portion of the multi-portion recipe (i.e., the one or more processes utilized by processing system **10** to make root beer soda) may be executed within a mixing manifold included within processing system **10**. Further, the second portion of the multi-portion recipe (i.e., the one or more processes utilized by processing system to make vanilla ice cream) may be executed within a freezing manifold included within processing system **10**. As discussed above, processing system **10** may include a plurality of manifolds, examples of which may include but are not limited to: mixing manifolds, blending manifolds, grinding manifolds, heating manifolds, cooling manifolds, freezing manifolds, steeping manifolds, nozzles, pressure manifolds, vacuum manifolds, and agitation manifolds.

[0283] Accordingly, virtual manifold process **126** may monitor **680** the processes utilized by processing system **10** to make root beer soda (or may monitor the processes utilized by processing system **10** to make vanilla ice cream) to obtain data concerning these processes.

[0284] Examples of the type of data obtained may include but is not limited to ingredient data and processing data.

[0285] Ingredient data may include but is not limited to a list of ingredients used during the first portion of a multi-portion recipe. For example, if the first portion of a multi-portion recipe concerns making root beer soda, the list of ingredients may include: a defined quantity of root beer flavoring, a defined quantity of carbonated water, a defined quantity of non-carbonated water, and a defined quantity of high fructose corn syrup.

[0286] Processing data may include but is not limited to a sequential list of processes performed on the ingredients. For example, a defined quantity of carbonated water may begin to be introduced into a manifold within processing system **10**. While filling the manifold with carbonated water, the defined quantity of root beer flavoring, the defined quantity of high fructose corn syrup, and the defined quantity of non-carbonated water may also be introduced into the manifold.

[0287] At least a portion of the data obtain may be stored **682** (e.g., either temporarily or permanently). Further, virtual manifold process **126** may enable **684** the availability of this stored data for subsequent use by e.g., one or more processes occurring during a second portion of the multi-portion recipe. When storing **682** the data obtained, virtual manifold process **126** may archive **686** the data obtained in a non-volatile memory system (e.g., storage subsystem **12**) for subsequent diagnostic purposes. Examples of such diagnostic purposes may include enabling a service technician to review ingredient consumption characteristics to establish a purchasing plan for purchasing consumables for processing system **10**. Alternatively/additionally, when storing **682** the data obtained, virtual manifold process **126** may temporarily write **688** the data obtained to a volatile memory system (e.g., random access memory **104**).

[0288] When enabling **684** the availability of the data obtained, virtual manifold process **126** may route **690** the obtained data (or a portion thereof) to one or more processes that are occurring (or will occur) during the second portion of the multi-portion recipe. Continuing with the above-stated example, in which the second portion of the multi-portion recipe concerns the one or more processes utilized by processing system **10** to make vanilla ice cream, virtual manifold process **126** may enable **684** the data obtained (or a portion thereof) to be available to the one or more processes utilized to make vanilla ice cream.

[0289] Assume that the root beer flavoring utilized to make the above-described root beer float is flavored with a considerable quantity of vanilla flavoring. Further, assume that when making the vanilla ice cream, a considerable quantity of vanilla flavoring is also used. As virtual manifold process **126** may enable **684** the availability of the obtained data (e.g., ingredient and/or process data) to control logic subsystem (i.e., the subsystem orchestrating the one or more processes utilized to make the vanilla ice cream), upon reviewing this data, control logic subsystem **14** may alter the ingredients utilized to make the vanilla ice cream. Specifically, control logic subsystem **14** may reduce the quantity of vanilla flavoring utilized to make the vanilla ice cream to avoid an overabundance of vanilla flavoring within the root beer float.

[0290] Additionally, by enabling **684** the availability of the obtained data to subsequently-executed processes, procedures may be performed that would prove impossible had that data not been made available to the subsequently-executed processes. Continuing with the above-stated example, assume that it is determined empirically that consumers tend to not like any single-serving of a product that includes more than 10.0 mL of vanilla flavoring. Further, assume that 8.0 mL of vanilla flavoring is included within the root beer flavoring utilized to make the root beer soda for the root beer float, and another 8.0 mL of vanilla flavoring is utilized to make the vanilla ice cream utilized to make the root beer float. Therefore, if these two products (the root beer soda and the vanilla ice cream) are combined, the final product would be flavored with 16.0 mL of vanilla flavoring (which exceeds the empirically-defined not-to-exceed 10.0 mL rule).

[0291] Accordingly, if the ingredient data for the root beer soda was not stored **682** and the availability of such stored data was not enabled **684** by virtual manifold process **126**, the fact that

the root beer soda contains 8.0 mL of vanilla flavoring would be lost and a final product containing 16.0 mL of vanilla flavoring would be produced. Accordingly, this obtained and stored **682** data may be utilized to avoid (or reduce) the occurrence of any undesirable effect (e.g., an undesired flavor characteristic, an undesired appearance characteristic, an undesired odor characteristic, an undesired texture characteristic, and exceeding a maximum recommended dosage of a nutraceutical).

[0292] The availability of this obtained data may allow for subsequent processes to also be adjusted. For example, assume that the quantity of salt utilized to make the vanilla ice cream varies depending on the quantity of carbonated water utilized to make the root beer soda. Again, if the ingredient data for the root beer soda was not stored **682** and the availability of such stored data was not enabled **684** by virtual manifold process **126**, the quantity of carbonated water used to make the root beer soda would be lost and the ability to adjust the quantity of salt utilized to make the ice cream may be compromised.

[0293] As discussed above, virtual manifold process **126** may monitor **680** one or more processes occurring during a first portion of a multi-portion recipe being executed on e.g., processing system **10** to obtain data concerning at least of portion of the one or more processes. The one or more processes monitored **680** may be executed within a single manifold of the processing system **10** or may be representative of a single portion of a multi-portion procedure executed within a single manifold of processing system **10**.

[0294] For example, when making the root beer soda, a single manifold may be used that has four inlets (e.g., one for the root beer flavoring, one for the carbonated water, one for the non-carbonated water, and one for the high fructose corn syrup) and one outlet (as all of the root beer soda is being provided to a single secondary manifold).

[0295] However, if instead of having one outlet, the manifold has two outlets (one having a flow rate of four times the other), virtual manifold process **126** may consider this process to include two separate and distinct portions being executed simultaneously within the same manifold. For example, 80% of all of the ingredients may be mixed together to produce 80% of the total quantity of root beer soda; while the remaining 20% of all of the ingredients may be simultaneously mixed together (in the same manifold) to produce 20% of the root beer soda. Accordingly, virtual manifold process **126** may enable **684** the data obtained concerning the first portion (i.e., the 80% portion) to be made available to the downstream process that utilizes the 80% of the root beer soda and enable **684** the data obtained concerning the second portion (i.e., the 20% portion) to be made available to the downstream process that utilizes the 20% of the root beer soda.

[0296] Additionally/alternatively, the single portion of a multi-portion procedure executed within a single manifold of processing system **10** may be indicative of one process that occurs within a single manifold that executes a plurality of discrete processes. For example, when making vanilla ice cream within the freezing manifold, the individual ingredients may be introduced, mixed, and reduced in temperature until frozen. Accordingly, the process of making vanilla ice cream may include an ingredient introduction process, an ingredient mixing process, and an ingredient freezing process, each of which may be individually monitored **680** by virtual manifold process **126**.

[0297] As discussed above, product module assembly **250** (of microingredient subsystem **18** and plumbing/control subsystem **20**) may include a plurality of slot assemblies **260**, **262**, **264**, **266** configured to releasably engage a plurality of product containers **252**, **254**, **256**, **258**. Unfortunately, when servicing processing system **10** to refill product containers **252**, **254**, **256**, **258**, it may be possible to install a product container within the wrong slot assembly of product module assembly **250**. A mistake such as this may result in one or more pump assemblies (e.g., pump assemblies **270**, **272**, **274**, **276**) and/or one or more tubing assemblies (e.g., tubing bundle **304**) being contaminated with one or more microingredients. For example, as root beer flavoring (i.e., the microingredient contained within product container **256**) has a very strong taste, once a particular pump assembly/tubing assembly is used to distribute e.g., root beer flavoring, it can no longer be used to

distribute a microingredient having a less-strong taste (e.g., lemon-lime flavoring, iced tea flavoring, and lemonade flavoring).

[0298] Additionally and as discussed above, product module assembly **250** may be configured to releasably engage bracket assembly **282**. Accordingly, in the event that processing system **10** includes multiple product module assemblies and multiple bracket assemblies, when servicing processing system **10**, it may be possible to install a product module assembly onto the wrong bracket assembly. Unfortunately, such a mistake may also result in one or more pump assemblies (e.g., pump assemblies **270**, **272**, **274**, **276**) and/or one or more tubing assemblies (e.g., tubing bundle **304**) being contaminated with one or more microingredients.

[0299] Accordingly, processing system **10** may include an RFID-based system to ensure the proper placement of product containers and product modules within processing system **10**. Referring also to FIGS. **23** & **24**, processing system **10** may include RFID system **700** that may include RFID antenna assembly **702** positioned on product module assembly **250** of processing system **10**.

[0300] As discussed above, product module assembly **250** may be configured to releasably engage at least one product container (e.g., product container **258**). RFID system **700** may include RFID tag assembly **704** positioned on (e.g., affixed to) product container **258**. Whenever product module assembly **250** releasably engages the product container (e.g., product container **258**), RFID tag assembly **704** may be positioned within e.g., upper detection zone **706** of RFID antenna assembly **702**. Accordingly and in this example, whenever product container **258** is positioned within (i.e. releasably engages) product module assembly **250**, RFID tag assembly **704** should be detected by RFID antenna assembly **702**.

[0301] As discussed above, product module assembly **250** may be configured to releasably engage bracket assembly **282**. RFID system **700** may further include RFID tag assembly **708** position on (e.g. affixed to) bracket assembly **282**. Whenever bracket assembly **282** releasably engages product module assembly **250**, RFID tag assembly **708** may be positioned within e.g., lower detection zone **710** of RFID antenna assembly **702**.

[0302] Accordingly, through use of RFID antenna assembly **702** and RFID tag assemblies **704**, **708**, RFID system **700** may be able to determine whether or not the various product containers (e.g., product containers **252**, **254**, **256**, **258**) are properly positioned within product module assembly **250**. Further, RFID system **700** may be able to determine whether or not product module assembly **250** is properly positioned within processing system **10**.

[0303] While RFID system **700** shown to include one RFID antenna assembly and two RFID tag assemblies, this is for illustrative purposes only and is not intended to be a limitation of this disclosure, as other configurations are possible. Specifically, a typical configuration of RFID system **700** may include one RFID antenna assembly positioned within each slot assembly of product module assembly **250**. For example, RFID system **700** may additionally include RFID antenna assemblies **712**, **714**, **716** positioned within product module assembly **250**. Accordingly, RFID antenna assembly **702** may determine whether a product container is inserted into slot assembly **266** (of product module assembly **250**); RFID antenna assembly **712** may determine whether a product container is inserted into slot assembly **264** (of product module assembly **250**); RFID antenna assembly **714** may determine whether a product container is inserted into slot assembly **262** (of product module assembly **250**); and RFID antenna assembly **716** may determine whether a product container is inserted into slot assembly **260** (of product module assembly **250**). Further, since processing system **10** may include multiple product module assemblies, each of these product module assemblies may include one or more RFID antenna assemblies to determine which product containers are inserted into the particular product module assembly.

[0304] As discussed above, by monitoring for the presence of an RFID tag assembly within lower detection zone **710** of RFID antenna assembly **702**, RFID system **700** may be able to determine whether product module assembly **250** is properly positioned within processing system **10**.

Accordingly, any of RFID antenna assemblies **702**, **712**, **714**, **716** may be utilized to read one or

more RFID tag assemblies affixed to bracket assembly **282**. For illustrative purposes, product module assembly **282** is shown to include only a single RFID tag assembly **708**. However, this is for illustrative purposes only and is not intended to be a limitation of this disclosure, as other configurations are possible. For example, bracket assembly **282** may include multiple RFID tag assemblies, namely RFID tag assembly **718** (shown in phantom) for being read by RFID antenna assembly **712**; RFID tag assembly **720** (shown in phantom) for being read by RFID antenna assembly **714**; and RFID tag assembly **722** (shown in phantom) for being read by RFID antenna assembly **716**.

[0305] One or more of the RFID tag assemblies (e.g., RFID tag assemblies **704**, **708**, **718**, **720**, **722**) may be passive RFID tag assemblies (e.g., RFID tag assemblies that do not require a power source). Additionally, one or more of the RFID tag assemblies (e.g., RFID tag assemblies **704**, **708**, **718**, **720**, **722**) may be a writable RFID tag assembly, in that RFID system **700** may write data to the RFID tag assembly. Examples of the type of data storable within the RFID tag assemblies may include, but is not limited to: a quantity identifier for the product container, a production date identifier for the product container, a discard date identifier for the product container, an ingredient identifier for the product container, a product module identifier, and a bracket identifier.

[0306] With respect to the quantity identifier, in some embodiments, each volume of ingredient pumped from a container including an RFID tag, the tag is written to include the updated volume in the container, and/or, the amount pumped. Where the container is subsequently removed from the assembly, and replaced into a different assembly, the system will read the RFID tag and will know the volume in the container and/or the amount that has been pumped from the container. Additionally, the dates of pumping may also be written on the RFID tag.

[0307] Accordingly, when each of the bracket assemblies (e.g. bracket assembly **282**) is installed within processing system **10**, an RFID tag assembly (e.g. RFID tag assembly **708**) may be attached, wherein the attached RFID tag assembly may define a bracket identifier (for uniquely identifying the bracket assembly). Accordingly, if processing system **10** includes ten bracket assemblies, ten RFID tag assemblies (i.e., one attached to each bracket assembly) may define ten unique bracket identifiers (i.e. one for each bracket assembly).

[0308] Further, when a product container (e.g. product container **252**, **254**, **256**, **258**) is manufactured and filled with a microingredient, an RFID tag assembly may include: an ingredient identifier (for identifying the microingredient within the product container); a quantity identifier (for identifying the quantity of microingredient within the product container); a production date identifier (for identifying the date of manufacture of the microingredient); and a discard date identifier (for identifying the date on which the product container should be discarded/recycled).

[0309] Accordingly, when product module assembly **250** is installed within processing system **10**, RFID antenna assemblies **702**, **712**, **714**, **716** may be energized by RFID subsystem **724**. RFID subsystem **724** may be coupled to control logic subsystem **14** via databus **726**. Once energized, RFID antenna assemblies **702**, **712**, **714**, **716** may begin scanning their respective upper and lower detection zones (e.g. upper detection zone **706** and lower detection zone **710**) for the presence of RFID tag assemblies.

[0310] As discussed above, one or more RFID tag assemblies may be attached to the bracket assembly with which product module assembly **250** releasably engages. Accordingly, when product module assembly **250** is slid onto (i.e. releasably engages) bracket assembly **282**, one or more of RFID tag assemblies **708**, **718**, **720**, **722** may be positioned within the lower detection zones of RFID antenna assemblies **702**, **712**, **714**, **716** (respectively). Assume, for illustrative purposes, that bracket assembly **282** includes only one RFID tag assembly, namely RFID tag assembly **708**. Further, assume for illustrative purposes that product containers **252**, **254**, **256**, **258** are being installed within slot assemblies **260**, **262**, **264**, **266** (respectively). Accordingly, RFID subsystem **714** should detect bracket assembly **282** (by detecting RFID tag assembly **708**) and should detect product containers **252**, **254**, **256**, **258** by detecting the RFID tag assemblies (e.g., RFID tag

assembly **704**) installed on each product container.

[0311] The location information concerning the various product modules, bracket assemblies, and product containers, may be stored within e.g. storage subsystem **12** that is coupled to control logic subsystem **14**. Specifically, if nothing has changed, RFID subsystem **724** should expect to have RFID antenna assembly **702** detect RFID tag assembly **704** (i.e. which is attached to product container **258**) and should expect to have RFID antenna assembly **702** detect RFID tag assembly **708** (i.e. which is attached to bracket assembly **282**). Additionally, if nothing has changed: RFID antenna assembly **712** should detect the RFID tag assembly (not shown) attached to product container **256**; RFID antenna assembly **714** should detect the RFID tag assembly (not shown) attached to product container **254**; and RFID antenna assembly **716** should detect the RFID tag assembly (not shown) attached to product container **252**.

[0312] Assume for illustrative purposes that, during a routine service call, product container **258** is incorrectly positioned within slot assembly **264** and product container **256** is incorrectly positioned within slot assembly **266**. Upon acquiring the information included within the RFID tag assemblies (using the RFID antenna assemblies), RFID subsystem **724** may detect the RFID tag assembly associated with product container **258** using RFID antenna assembly **262**; and may detect the RFID tag assembly associated with product container **256** using RFID antenna assembly **702**. Upon comparing the new locations of product containers **256**, **258** with the previously stored locations of product containers **256**, **258** (as stored on storage subsystem **12**), RFID subsystem **724** may determine that the location of each of these product containers is incorrect.

[0313] Accordingly, RFID subsystem **724**, via control logic subsystem **14**, may render a warning message on e.g. informational screen **514** of user-interface subsystem **22**, explaining to e.g. the service technician that the product containers were incorrectly reinstalled. Depending on the types of microingredients within the product containers, the service technician may be e.g. given the option to continue or told that they cannot continue. As discussed above, certain microingredients (e.g. root beer flavoring) have such a strong taste that once they have been distributed through a particular pump assembly and/or tubing assembly, the pump assembly/tubing assembly can no longer be used for any other microingredient. Additionally and as discussed above, the various RFID tag assemblies attached to the product containers may define the microingredient within the product container.

[0314] Accordingly, if a pump assembly/tubing assembly that was used for lemon-lime flavoring is now going to be used for root beer flavoring, the service technician may be given a warning asking them to confirm that this is what they want to do. However, if a pump assembly/tubing assembly that was used for root beer flavoring is now going to be used for lemon-lime flavoring, the service technician may be provided with a warning explaining that they cannot proceed and must switch the product containers back to their original configurations or e.g., have the compromised pump assembly/tubing assembly removed and replaced with a virgin pump assembly/tubing assembly. Similar warnings may be provided in the event that RFID subsystem **724** detects that a bracket assembly has been moved within processing system **10**.

[0315] RFID subsystem **724** may be configured to monitor the consumption of the various microingredients. For example and as discussed above, an RFID tag assembly may be initially encoded to define the quantity of microingredient within a particular product container. As control logic subsystem **14** knows the amount of microingredient pumped from each of the various product containers, at predefined intervals (e.g. hourly), the various RFID tag assemblies included within the various product containers may be rewritten by RFID subsystem **724** (via an RFID antenna assembly) to define an up-to-date quantity for the microingredient included within the product container.

[0316] Upon detecting that a product container has reached a predetermined minimum quantity, RFID subsystem **724**, via control logic subsystem **14**, may render a warning message on informational screen **514** of user-interface subsystem **22**. Additionally, RFID subsystem **724** may

provide a warning (via informational screen **414** of user-interface subsystem **22**) in the event that one or more product containers has reached or exceeded an expiration date (as defined within an RFID tag assembly attached to the product container).

[0317] While RFID system **700** is described above as having an RFID antenna assembly affixed to a product module and RFID tag assemblies affixed to bracket assemblies and product containers, this is for illustrative purposes only and is not intended to be a limitation of this disclosure.

Specifically, the RFID antenna assembly may be positioned on any product container, a bracket assembly, or product module. Additionally, the RFID tag assemblies may be positioned on any product container, bracket assembly, or product module. Accordingly, in the event that an RFID tag assembly is affixed to a product module assembly, the RFID tag assembly may define a project module identifier that e.g. defines a serial number for the product module.

[0318] Due to the close proximity of the slot assemblies (e.g., slot assemblies **260, 262, 264, 266**) included within product module assembly **250**, it may be desirable to configure RFID antenna assembly **702** in a manner that allows it to avoid reading e.g., product containers positioned within adjacent slot assemblies. For example, RFID antenna assembly **702** should be configured so that RFID antenna assembly **702** can only read RFID tag assemblies **704, 708**; RFID antenna assembly **712** should be configured so that RFID antenna assembly **712** can only read RFID tag assembly **718** and the RFID tag assembly (not shown) affixed to product container **256**; RFID antenna assembly **714** should be configured so that RFID antenna assembly **714** can only read RFID tag assembly **720** and the RFID tag assembly (not shown) affixed to product container **254**; and RFID antenna assembly **716** should be configured so that RFID antenna assembly **716** can only read RFID tag assembly **722** and the RFID tag assembly (not shown) affixed to product container **252**.

RFID Cross Read Mitigation

[0319] In some embodiments, upon machine start up, for example, and in some embodiments, when the machine door is open, a scan of the RFID tag assemblies is performed to map the location of the various elements within machine, including, but not limited to, the location of each product container. As described herein, an accurate mapping is critical for many reasons, including, but not limited to, maintaining recipes and dispensing products as well as for maintaining the quality of the products dispensed. In some embodiments, to mitigate unintentional reading by RFID antenna assemblies of, e.g., product containers positioned within adjacent slot assemblies, various embodiments of the method for scanning tags, described below, may be used.

[0320] Referring now also to FIG. **73**, the RFID tag assemblies are all scanned and then the scanning data is evaluated to determine the position of each RFID tag assembly. If an RFID tag assembly is attributed to more than one slot after the scan, then the scanning data is further evaluated to determine the correct slot in which to assign the RFID tag assembly. In some embodiments, time in slot, fitment maps and RSSI values are used to determine the correct location of the RFID tag assembly.

[0321] With respect to time in slot, in some embodiments, this may be a count of the number of scan cycles an RFID tag assembly has been identified in each slot to which it was assigned prior to the scan in which the RFID tag assembly was attributed to more than one slot. If an RFID tag assembly has been in the slot in which it was assigned prior to the scan (“current slot”) for its life and the scan attributed it to a different slot as well as the current slot, the time in the current slot will be significantly greater than the different slot. In some embodiments, the system will then assign the RFID tag assembly to the slot in which it has been assigned to for the highest number of scans, which, in this example, is the current slot.

[0322] In some embodiments, the product container may be a “double wide” product container and, for these embodiments, the product container will require two slots adjacent and within the same product module. In some embodiments, the product module is a quad product module and therefore is configured to receive four product containers, however, with respect to double wide product container, the quad product module is configured to receive two double wide product containers

and/or two single product container and one double wide product container. With respect to the double wide product containers, because these cannot span over two product modules (i.e., cannot cross product module boundaries), where an RFID tag assembly attached to a double wide product container has been read in more than one slot, and one of the slots is, for example, an odd number slot (i.e., slot **1** or **3** in a quad product module), then the system may use this information to eliminate that slot as a candidate for the position of the RFID tag assembly. Thus, in some embodiments,

[0323] The system may use fitment map information to establish the true/correct position of the double wide product container.

[0324] In some embodiments, where an RFID tag assembly has been read in multiple slots and all of the slots over one have not been eliminated using the time in slot and/or fitment map methods, then the system compares the received signal strength indicator (“RSSI”) values. In some embodiments, the slot with the higher RSSI value will be assigned as the position of the RFID tag assembly.

[0325] If after scanning all of the RFID tag assemblies multiple RFID tag assemblies are attributed to one slot (“the slot”), then after the scan, the system may complete the following method to determine the correct RFID tag assembly to assign to the slot. In some embodiments, time in slot, fitment maps and RSSI values are used to determine the correct location of the RFID tag assembly.

[0326] With respect to time in slot, in some embodiments, this may be a count of the number of scan cycles an RFID tag assembly has been identified in the slot. If a RFID tag assembly has been in another slot in which it was assigned prior to the scan (“current slot”) for its life and the scan attributed it to a different slot, i.e., the slot, the time in the current slot will be significantly greater than the different slot, i.e., the slot. In some embodiments, the system will then assign the RFID tag assembly to the slot in which it has been assigned to for the highest number of scans, which, in this example, is the current slot. However, if a RFID tag assembly has been in the slot for a predetermined period of time that is longer than any of the other candidate RFID tag assembly for the slot, then the RFID tag assembly that has been in the slot the longest will be assigned to the slot.

[0327] In some embodiments, the product container may be a “double wide” product container and, for these embodiments, the product container will require two slots adjacent and within the same product module. In some embodiments, the product module is a quad product module and therefore is configured to receive four product containers, however, with respect to double wide product containers, the quad product module is configured to receive two double wide product containers and/or two single product container and one double wide product container. With respect to the double wide product containers, because these cannot span over two product modules (i.e., cannot cross product module boundaries), where one of the RFID tag assembly read for the slot is attached to a double wide product container and the slot is, for example, an odd number slot (i.e., slot **1** or **3** in a quad product module), or otherwise could not accommodate the double wide product container, then the system may use this information to eliminate that product module/RFID tag assembly from being a candidate for the slot. Thus, in some embodiments, the system may use fitment map information to establish the true/correct position of the double wide product container.

[0328] In some embodiments, where multiple RFID tag assemblies have been read in the slot and all of the RFID tag assemblies over one have not been eliminated using the time in slot and/or fitment map methods, then the system compares the receive signal strength indicator (“RSSI”) values. In some embodiments, the RFID tag assembly with the higher RSSI value for the antenna associated with the slot will be assigned as the position of the slot.

[0329] Accordingly and referring also to FIG. **25**, one or more of RFID antenna assemblies **702**, **712**, **714**, **716** may be configured as a loop antenna. While the following discussion is directed towards RFID antenna assembly **702**, this is for illustrative purposes only and is not intended to be a limitation of this disclosure, as the following discussion may be equally applied to RFID antenna

assemblies **712, 714, 716**.

[0330] RFID antenna assembly **702** may include first capacitor assembly **750** (e.g., a 2.90 pF capacitor) that is coupled between ground **752** and port **754** that may energize RFID antenna assembly **702**. A second capacitor assembly **756** (e.g., a 2.55 pF capacitor) maybe positioned between port **754** and inductive loop assembly **758**. Resistor assembly **760** (e.g., a 2.00 Ohm resistor) may couple inductive loop assembly **758** with ground **752** while providing a reduction in the Q factor to increase the bandwidth and provide a wider range of operation.

[0331] As is known in the art, the characteristics of RFID antenna assembly **702** may be adjusted by altering the physical characteristics of inductive loop assembly **758**. For example, as the diameter “d” of inductive loop assembly **758** increases, the far field performance of RFID antenna assembly **702** may increase. Further, as the diameter “d” of inductive loop assembly **758** decreases; the far field performance of RFID antenna assembly **702** may decrease.

[0332] Specifically, the far field performance of RFID antenna assembly **702** may vary depending upon the ability of RFID antenna assembly **702** to radiate energy. As is known in the art, the ability of RFID antenna assembly **702** to radiate energy may be dependent upon the circumference of inductive loop assembly **708** (with respect to the wavelength of carrier signal **762** used to energize RFID antenna assembly **702** via port **754**).

[0333] Referring also to FIG. **26** and in a preferred embodiment, carrier signal **762** may be a 915 MHz carrier signal having a wavelength of 12.89 inches. With respect to loop antenna design, once the circumference of inductive loop assembly **758** approaches or exceeds 50% of the wavelength of carrier signal **762**, the inductive loop assembly **758** may radiate energy outward in a radial direction (e.g., as represented by arrows **800, 802, 804, 806, 808, 810**) from axis **812** of inductive loop assembly **758**, resulting in strong far field performance. Conversely, by maintaining the circumference of inductive loop assembly **758** below 25% of the wavelength of carrier signal **762**, the amount of energy radiated outward by inductive loop assembly **758** will be reduced and far field performance will be compromised. Further, magnetic coupling may occur in a direction perpendicular to the plane of inductive loop assembly **758** (as represented by arrows **814, 816**), resulting in strong near field performance.

[0334] As discussed above, due to the close proximity of slot assemblies (e.g., slot assemblies **260, 262, 264, 266**) included within product module assembly **250**, it may be desirable to configure RFID antenna assembly **702** in a manner that allows it to avoid reading e.g., product containers positioned within adjacent slot assemblies. Accordingly, by configuring inductive loop assembly **758** so that the circumference of inductive loop assembly **758** is below 25% of the wavelength of carrier signal **762** (e.g., 3.22 inches for a 915 MHz carrier signal), far field performance may be reduced and near field performance may be enhanced. Further, by positioning inductive loop assembly **758** so that the RFID tag assembly to be read is either above or below RFID antenna assembly **702**, the RFID tag assembly may be inductively coupled to RFID antenna assembly **702**. For example, when configured so that the circumference of inductive loop assembly **758** is 10% of the wavelength of carrier signal **762** (e.g., 1.29 inches for a 915 MHz carrier signal), the diameter of inductive loop assembly **758** would be 0.40 inches, resulting in a comparatively high level of near field performance and a comparatively low level of far field performance.

[0335] Referring also to FIGS. **27 & 28**, processing system **10** may be incorporated into housing assembly **850**. Housing assembly **850** may include one or more access doors/panels **852, 854** that e.g., allow for the servicing of processing system **10** and allow for the replacement of empty product containers (e.g., product container **258**). For various reasons (e.g., security, safety, etc), it may be desirable to secure access doors/panels **852, 854** so that the internal components of beverage dispensing machine **10** can only be accessed by authorized personnel. Accordingly, the previously-described RFID subsystem (i.e., RFID subsystem **700**) may be configured so that access doors/panels **852, 854** may only be opened if the appropriate RFID tag assembly is positioned proximate RFID access antenna assembly **900**. An example of such an appropriate RFID tag

assembly may include an RFID tag assembly that is affixed to a product container (e.g., RFID tag assembly **704** that is affixed to product container **258**).

[0336] RFID access antenna assembly **900** may include multi-segment inductive loop assembly **902**. A first matching component **904** (e.g., a 5.00 pF capacitor) may be coupled between ground **906** and port **908** that may energize RFID access antenna assembly **900**. A second matching component **910** (e.g., a 16.56 nanoHenries inductor) may be positioned between port **908** and multi-segment inductive loop assembly **902**. Matching components **904**, **910** may adjust the impedance of multi-segment inductive loop assembly **902** to a desired impedance (e.g., 50.00 Ohms). Generally, matching components **904**, **910** may improve the efficiency of RFID access antenna assembly **900**.

[0337] RFID access antenna assembly **900** may include a reduction in the Q factor of element **912** (e.g., a 50 Ohm resistor) that may be configured to allow RFID access antenna assembly **900** to be utilized over a broader range of frequencies. This may also allow RFID access antenna assembly **900** to be used over an entire band and may also allow for tolerances within the matching network. For example, if the band of interest of RFID access antenna assembly **900** is 50 MHz and reduction of Q factor element (also referred to herein as a “de-Qing element”) **912** is configured to make the antenna 100 MHz wide, the center frequency of RFID access antenna assembly **900** may move by 25 MHz without affecting the performance of RFID access antenna assembly **900**. De-Qing element **912** may be positioned within multi-segment inductive loop assembly **902** or positioned somewhere else within RFID access antenna assembly **900**.

[0338] As discussed above, by utilizing a comparatively small inductive loop assembly (e.g., inductive loop assembly **758** of FIGS. **25** & **26**), far field performance of an antenna assembly may be reduced and near field performance may be enhanced. Unfortunately, when utilizing such a small inductive loop assembly, the depth of the detection range of the RFID antenna assembly is also comparatively small (e.g., typically proportional to the diameter of the loop). Therefore, to obtain a larger detection range depth, a larger loop diameter may be utilized. Unfortunately and as discussed above, the use of a larger loop diameter may result in increased far field performance.

[0339] Accordingly, multi-segment inductive loop assembly **902** may include a plurality of discrete antenna segments (e.g., antenna segments **914**, **916**, **918**, **920**, **922**, **924**, **926**), with a phase shift element (e.g., capacitor assemblies **928**, **930**, **932**, **934**, **936**, **938**, **940**). Examples of capacitor assemblies **928**, **930**, **932**, **934**, **936**, **938**, **940** may include 1.0 pF capacitors or varactors (e.g., voltage variable capacitors) for example, 0.1-250 pF varactors. The above-described phase shift element may be configured to allow for the adaptive controlling of the phase shift of multi-segment inductive loop assembly **902** to compensate for varying conditions; or for the purpose of modulating the characteristics of multi-segment inductive loop assembly **902** to provide for various inductive coupling features and/or magnetic properties. An alternative example of the above-described phase shift element is a coupled line (not shown).

[0340] As discussed above, by maintaining the length of an antenna segment below 25% of the wavelength of the carrier signal energizing RFID access antenna assembly **900**, the amount of energy radiated outward by the antenna segment will be reduced, far field performance will be compromised, and near field performance will be enhanced. Accordingly each of antenna segments **914**, **916**, **918**, **920**, **922**, **924**, **926** may be sized so that they are no longer than 25% of the wavelength of the carrier signal energizing RFID access antenna assembly **900**. Further, by properly sizing each of capacitor assemblies **928**, **930**, **932**, **934**, **936**, **938**, **940**, any phase shift that occurs as the carrier signal propagates around multi-segment inductive loop assembly **902** may be offset by the various capacitor assemblies incorporated into multi-segment inductive loop assembly **902**. Accordingly, assume for illustrative purposes that for each of antenna segments **914**, **916**, **918**, **920**, **922**, **924**, **926**, a 90° phase shift occurs. Accordingly, by utilizing properly sized capacitor assemblies **928**, **930**, **932**, **934**, **936**, **938**, **940**, the 90° phase shift that occurs during each segment may be reduced/eliminated. For example, for a carrier signal frequency of 915 MHz and an antenna

segment length that is less than 25% (and typically 10%) of the wavelength of the carrier signal, a 1.2 pF capacitor assembly may be utilized to achieve the desired phase shift cancellation, as well as tune segment resonance.

[0341] While multi-segment inductive loop assembly **902** is shown as being constructed of a plurality of linear antenna segments coupled via miter joints, this is for illustrative purposes only and is not intended to be a limitation of this disclosure. For example, a plurality of curved antenna segments may be utilized to construct multi-segment inductive loop assembly **902**. Additionally, multi-segment inductive loop assembly **902** may be configured to be any loop-type shape. For example, multi-segment inductive loop assembly **902** may be configured as an oval (as shown in FIG. **28**), a circle, a square, a rectangle, or an octagon.

[0342] While the system is described above as being utilized within a processing system, this is for illustrative purposes only and is not intended to be a limitation of this disclosure, as other configurations are possible. For example, the above-described system may be utilized for processing/dispensing other consumable products (e.g., ice cream and alcoholic drinks).

Additionally, the above-described system may be utilized in areas outside of the food industry. For example, the above-described system may be utilized for processing/dispensing: vitamins; pharmaceuticals; medical products, cleaning products; lubricants; painting/staining products; and other non-consumable liquids/semi-liquids/granular solids and/or fluids.

[0343] While the system is described above as having the RFID tag assembly (e.g., RFID tag assembly **704**) that is affixed to the product container (e.g., product container **258**) positioned above the RFID antenna assembly (e.g., RFID antenna assembly **702**), which is positioned above the RFID tag (e.g., RFID tag assembly **708**) that is affixed to bracket assembly **282**, this for illustrative purposes only and is not intended to be a limitation of this disclosure, as other configurations are possible. For example, the RFID tag assembly (e.g., RFID tag assembly **704**) that is affixed to the product container (e.g., product container **258**) may be positioned below the RFID antenna assembly (e.g., RFID antenna assembly **702**), which may be positioned below the RFID tag (e.g., RFID tag assembly **708**) that is affixed to bracket assembly **282**.

[0344] As discussed above, by utilizing comparatively short antenna segments (e.g., antenna segments **914**, **916**, **918**, **920**, **922**, **924**, **926**) that are no longer than 25% of the wavelength of the carrier signal energizing RFID antenna assembly **900**, far field performance of antenna assembly **900** may be reduced and near field performance may be enhanced.

[0345] Referring also to FIG. **29**, if a higher level of far field performance is desired from the RFID antenna assembly, RFID antenna assembly **900a** may be configured to include far field antenna assembly **942** (e.g., a dipole antenna assembly) electrically coupled to a portion of multi-segment inductive loop assembly **902a**. Far field antenna assembly **942** may include first antenna portion **944** (i.e., forming the first portion of the dipole) and second antenna portion **946** (i.e., forming the second portion of the dipole). As discussed above, by maintaining the length of antenna segments **914**, **916**, **918**, **920**, **922**, **924**, **926** below 25% of the wavelength of the carrier signal, far field performance of antenna assembly **900a** may be reduced and near field performance may be enhanced. Accordingly, the sum length of first antenna portion **944** and second antenna portion **946** may be greater than 25% of the wavelength of the carrier signal, thus allowing for an enhanced level of far field performance.

[0346] Referring also to FIG. **30**, as discussed above (e.g., with reference to FIG. **27**) processing system **10** may be incorporated into housing assembly **850**. Housing assembly **850** may include one or more access doors/panels (e.g., upper door **852**, and lower door **854**) that e.g., allow for the servicing of processing system **10** and allow for the replacement of empty product containers (e.g., product container **258**). Touch screen interface **500** may be disposed on upper door **852**, allowing facile user access. Upper door **852** may also provide access to dispenser assembly **1000**, which may allow a beverage container (e.g., container **30**) to be filled with a beverage (e.g., via nozzle **24**; not shown), ice, or the like. Additionally, lower door **854** may include RFID interrogation region **1002**,

e.g., which may be associated with RFID access antenna assembly **900**, e.g., to permit one or more of access doors/panels **852**, **854** to be opened. Interrogation region **1002** is depicted for illustrative purposes only, as RFID access antenna assembly **900** may be equally located in various alternative locations, including locations other than access doors/panels **852**, **854**.

[0347] Referring also to FIGS. **51-53**, an exemplary embodiment of the user interface assembly **5100** is depicted, which may be incorporated into the housing assembly **850** shown in FIG. **30**. The user interface assembly may include the touch screen interface **500**. User interface assembly **5100** may include a touch screen **5102**, a frame **5104**, a border **5106**, a seal **5108**, and a system controller enclosure **5110**. The border **5106** may space the touch screen **5102**, and may also serve as a clean visual border. The touch screen **5102**, in the exemplary embodiment, is a capacitive touch screen, however, on other embodiments, other types of touch screens may be used. However, in the exemplary embodiment, due to the capacitive nature of the touch screen **5102** it may be desirable to maintain a predetermined distance between the touch screen **5102** and the door **852** via the border **5106**.

[0348] The seal **5108** may protect the display shown in FIG. **52** as **5200**) and may serve to prevent moisture and/or particulates from reaching the display **5200**. In the exemplary embodiment, the seal **5108** contacts the door of the housing assembly **852** to better maintain a seal. In the exemplary embodiment, the display **5200** is an LCD display and is held by the frame by at least one set of spring fingers **5202**, which may engage the display **5200** and retain the display **5200**. In the exemplary embodiment, the display **5200** is a 15" LCD display such as model LQ150X1LGB1 from Sony Corporation, Tokyo, Japan. However, in other embodiments, the display may be any type of display. The spring fingers **5202** may additionally serve as springs, to allow for tolerances within the user interface assembly **5100**, thus, in the exemplary embodiment, the touch screen **5102** is allowed to float relative to the display **5200**. In the exemplary embodiment, the touch screen **5102** is a projected capacitive touch screen such as model ZYP15-10001D by Zytronics of Blaydon on Tyne, UK, but in other embodiments, the touch screen may be another type of touch screen and/or another capacitive touch screen. In the exemplary embodiment, the seal is a foam in place gasket, which in the exemplary embodiment, is made from polyurethane foam die-cut, but in other embodiments, may be made from silicone foam or other similar materials. In some embodiments, the seal may be an over molded seal or any other type of sealing body.

[0349] In the exemplary embodiment, the user interface assembly **5100** includes four sets of spring fingers **5202**. However, other embodiments may include a greater or fewer number of spring fingers **5202**. In the exemplary embodiment, the spring fingers **5202** and the frame **5104** are made from ABS, but in other embodiments, may be made from any material.

[0350] Referring also to FIG. **53**, the user interface assembly **5100**, in the exemplary embodiment, also includes at least one PCB as well as at least one connector **5114**, which, in some embodiments, may be covered by a connector cap **5116**.

[0351] Referring also to FIG. **31**, consistent with an exemplary embodiment, processing system may include upper cabinet portion **1004a** and lower cabinet portion **1006a**. However, this should not be construed as a limitation on this disclosure, as other configurations may be equally utilized. With additional reference also to FIGS. **32** and **33**, upper cabinet portion **1004a** (e.g., which may be covered, at least in part, by upper door **852**) may include one or more features of plumbing subsystem **20**, described above. For example, upper cabinet portion **1004a** may include one or more flow control modules (e.g., flow control module **170**), a fluid chilling system (e.g., cold plate **163**, not shown), a dispensing nozzle (e.g., nozzle **24**, not shown), plumbing for connection to high-volume ingredient supplies (e.g., carbon dioxide supply **150**, water supply **152**, and HFCS supply **154**, not shown), and the like. Additionally, upper cabinet portion **1004a** may include ice hopper **1008** for storing ice, and ice dispensing chute **1010**, for dispensing ice from ice hopper **1008** (e.g., into beverage containers).

[0352] Carbon dioxide supply **150** may be provided by one or more carbon dioxide cylinders, e.g.,

which may be remotely located and plumbed to processing system **10**. Similarly, water supply **152** may be provided as municipal water, e.g., which may also be plumbed to processing system **10**. High fructose corn syrup supply **154** may include, for example, one or more reservoirs (e.g., in the form of five gallon bag-in-box containers), which may be remotely stored (e.g., in a back room, etc.). High fructose corn syrup supply **154** may also be plumbed to processing system **10**. Plumbing for the various high-volume ingredients may be achieved via conventional hard or soft line plumbing arrangements.

[0353] As discussed above, carbonated water supply **158**, water supply **152**, and high fructose corn syrup supply **154** may be remotely located and plumbed to processing system **10** (e.g., to flow control modules **170**, **172**, **174**). Referring to FIG. **34**, a flow control module (e.g., flow control module **172**) may be coupled to a high-volume ingredient supply (e.g., water **152**) via quick plumbing connection **1012**. For example, water supply **152** may be coupled to plumbing connection **1012**, which may be releasably coupled to flow control module **172**, thereby completing plumbing of water supply **152** to flow control module **170**.

[0354] Referring to FIGS. **35**, **36A**, **36B**, **37A**, **37B**, and **37**, another embodiment of the upper cabinet portion (e.g., upper cabinet portion **1004b**) is shown. Similar to the above-described exemplary embodiment, upper cabinet portion **1004b** may include one or more features of plumbing subsystem **20**, described above. For example, upper cabinet portion **1004b** may include one or more flow control modules (e.g., flow control module **170**), a fluid chilling system (e.g., cold plate **163**, not shown), a dispensing nozzle (e.g., nozzle **24**, not shown), plumbing for connection to high-volume ingredient supplies (e.g., carbon dioxide supply **150**, water supply **152**, and HFCS supply **154**, not shown), and the like. Additionally, upper cabinet portion **1004b** may include ice hopper **1008** for storing ice, and ice dispensing chute **1010**, for dispensing ice from ice hopper **1008** (e.g., into beverage containers).

[0355] Referring also to FIGS. **36A-36b**, upper cabinet portion **1004b** may include power module **1014**. Power module **1014** may house, e.g., a power supply, one or more power distribution busses, controllers (e.g., control logic subsystem **14**) user interface controllers, storage device **12**, etc. Power module **1014** may include one or more status indicators (indicator lights **1016**, generally), and power/data connections (e.g., connections **1018** generally).

[0356] Referring also to FIGS. **37A**, **37B**, and **37C**, flow control module **170** may be mechanically and fluidly coupled to upper cabinet portion **1004b** via connection assembly **1020**, generally. Connection assembly **1020** may include a supply fluid passage, e.g., which may be coupled to a high-volume ingredient supply (e.g., carbonated water **158**, water **160**, high-fructose corn syrup **162**, etc) via inlet **1022**. Inlet **1024** of flow control module **170** may be configured to be at least partially received in outlet passage **1026** of connection assembly **1020**. Accordingly, flow control module **170** may receive high-volume ingredients via connection assembly **1020**. Connection assembly **1020** may further include a valve (e.g., ball valve **1028**) movable between an opened and closed position. When ball valve **1028** is in the opened position, flow control module **170** may be fluidly coupled to a high-volume ingredient supply. Similarly, when ball valve **1028** is in the closed position, flow control module **170** may be fluidly isolated from the high-volume ingredient supply.

[0357] Ball valve **1028** may be moved between the opened and closed position by rotatably actuating locking tab **1030**. In addition to opening and closing ball valve **1028**, locking tab **1030** may engage flow control module **170**, e.g., thereby retaining flow control module relative to connection assembly **1020**. For example, shoulder **1032** may engage tab **1034** of flow control module **170**. Engagement between shoulder **1032** and tab **1034** may retain inlet **1024** of flow control module **170** in outlet passage **1026** of connection assembly **1020**. Retaining inlet **1024** of flow control module **170** in outlet passage **1026** of connection assembly **1020** may additionally facilitate maintaining a fluid-tight connection between flow control module **170** and connection assembly **1020** (e.g., by maintaining satisfactory engagement between inlet **1024** and outlet **1026**).

[0358] Locking tab face **1036** of locking tab **1030** may engage outlet connector **1038** (e.g., which

may be fluidly coupled to an outlet of flow control module **170**). For example, as shown, locking tab face **1036** may engage face **1040** of outlet connector **1038**, retaining outlet connector **1038** in fluid tight engagement with flow control module **170**.

[0359] Connection assembly **1020** may facilitate the installation/removal of flow control module **170** from processing system **10** (e.g., to allow replacement of a damaged/malfunctioning flow control module). Consistent with the depicted orientation, locking tab **1030** may be rotated counterclockwise (e.g., approximately one quarter of a turn in the illustrated embodiment). Counterclockwise rotation of locking tab **130** may disengage outlet connector **1038** and tab **1034** of flow control module **170**. Outlet connector **1038** may be disengaged from flow control module **170**. Similarly, inlet **1024** of flow control module **170** may be disengaged from outlet passage **1026** of connection assembly **1020**. Additionally, counterclockwise rotation of locking tab **1030** may rotate ball valve **1028** to the closed position, thereby closing the fluid supply passage connected to the high-volume ingredient. As such, once locking tab **1030** is rotated to allow flow control module **170** to be removed from connection assembly **1020**, the fluid connection to the high-volume ingredient is closed, e.g., which may reduce/prevent contamination of processing system by the high-volume ingredients. Tab extension **1042** of locking tab **1030** may inhibit the removal of flow control module **170** from connection assembly **1020** until ball valve **1028** is in a fully closed position (e.g., by preventing the fluid disengagement and removal of flow control module **170** until ball valve **1028** has been rotated 90 degrees to a fully closed position).

[0360] In a related manner, flow control module **170** may be coupled to connection assembly **1020**. For example, with locking tab **1030** rotated counterclockwise, inlet **1024** of flow control module **170** may be inserted into outlet passage **1026** of connection assembly **1020**. Outlet connector **1038** may be engaged with the outlet (not shown) of flow control module **170**. Locking tab **1030** may be rotated clockwise, thereby engaging flow control module **170** and outlet connector **1038**. In the clockwise rotated position, connection assembly **1020** may retain inlet **1024** of flow control module **170** in fluid tight connection with outlet passage **1026** of connection assembly. Similarly, outlet connector **1038** may be retained in fluid tight connection with the outlet of flow control module **170**. Further, clockwise rotation of locking tab **1030** may move ball valve **1028** to the opened position, thereby fluidly coupling flow control module **170** to the high-volume ingredient.

[0361] With additional reference also to FIG. **38**, lower cabinet portion **1006a** may include one or more features of microingredient subsystem **18**, and may house one or more on-board consumable ingredient supplies. For example, lower cabinet portion **1006a** may include one or more microingredient towers (e.g., microingredient towers **1050**, **1052**, **1054**) and supply **1056** of non-nutritive sweetener (e.g., an artificial sweetener or combination of a plurality of artificial sweeteners). As shown, microingredient towers **1050**, **1052**, **1054** may include one or more product module assemblies (e.g., product module assembly **250**), which may each be configured to releasably engage one or more product containers (e.g., product containers **252**, **254**, **256**, **258**, not shown). For example, microingredient towers **1050** and **1052** may each include three product module assemblies, and microingredient tower **1054** may include four product module assemblies.

[0362] Referring also to FIGS. **39** and **40**, one or more of the microingredient towers (e.g., microingredient tower **1052**) may be coupled to an agitation mechanism, e.g., which may rock, linearly slide, or otherwise agitate microingredient tower **1052**, and/or a portion thereof. The agitation mechanism may aid in maintaining a mixture of separable ingredients stored on microingredient tower **1052**. The agitation mechanism may include, for example, agitation motor **1100**, which may drive agitation arm **1102** via linkage **1104**. Agitation arm **1102** may be driven in a generally vertical oscillatory motion, and may be coupled to one or more product module assemblies (e.g., product module assemblies **250a**, **250b**, **250c**, **250d**), thereby imparting a rocking agitation to product module assemblies **250a**, **250b**, **250c**, **250d**. A safety shut-off may be associated with lower door **854**, e.g., which may disable the agitation mechanism when lower cabinet door **1154** is open.

[0363] As discussed above, RFID system **700** may detect the presence, location (e.g., product module assembly and slot assembly) and contents of various product containers. Accordingly, RFID system **700** may render a warning (e.g., via RFID subsystem **724** and/or control logic subsystem **14**) if a product container including contents that require agitation have been installed in a microingredient tower (e.g., microingredient tower **1052**) that is not coupled to the agitation container. Further, control logic subsystem **14** may prevent the product container which is not being agitated from being utilized.

[0364] As discussed above, the product module assemblies (e.g., product module assembly **250**) may be configured with four slot assemblies, and may, therefore, be referred to as a quad product module and/or quad product module assembly. With additional reference also to FIG. **41**, product module assembly **250** may include a plurality of pump assemblies (e.g., pump assemblies **270**, **272**, **274**, **276**). For example, one pump assembly (e.g., pump assemblies **270**, **272**, **274**, **276**) may be associated with each of the four slot assemblies of product module **250** (e.g., in the case of a quad product module). Pump assemblies **270**, **272**, **274**, **276** may pump product from product containers (not shown) releasably engaged in corresponding slot assemblies of product module assembly **250**.

[0365] As shown, each product module assembly (e.g., product module assemblies **250a**, **250b**, **250c**, **250d**) of the microingredient towers (e.g., microingredient tower **1052**) may be coupled to a common wiring harness, e.g., via connector **1106**. As such, microingredient tower **1052** may be electrically coupled to, for example, control logic subsystem **14**, a power supply, etc., via a single connection point.

[0366] Referring also to FIG. **42**, as discussed above, product module **250** may include a plurality of slot assemblies (e.g., slot assemblies **260**, **262**, **264**, **266**). Slot assemblies **260**, **262**, **264**, **266** may be configured to releasably engage a product container (e.g., product container **256**). Slot assemblies **260**, **262**, **264**, **266** may include respective doors **1108**, **1110**, **1112**. As shown, two or more of the slot assemblies (e.g., slot assemblies **260**, **262**) may be configured to releasably engage a double wide product container (e.g., a product container configured to be releasably engaged in two slot assemblies), and/or two separate product containers including complimentary products (e.g., separate ingredients for a two ingredient beverage recipe). Accordingly, slot assemblies **260**, **262** may include a double-wide door (e.g., door **1108**) covering both slot assemblies **260**, **262**.

[0367] Doors **1108**, **1110**, **1112** may releasably engage a hinge rail to allow pivotal opening and closing of doors **1108**, **1108**, **1112**. For example, doors **1108**, **1110**, **1112** may include a snap-fit feature, allowing doors **1108**, **1108**, **1112** to be snapped onto, and off of, the hinge rail. Accordingly, doors **1108**, **1110**, **1112** may be snapped onto, or off of, the hinge rail allow replacement of broken doors, reconfiguration of the doors (e.g., to replace a double-wide door with two single-wide doors, or vice versa).

[0368] Each door (e.g., door **1110**) may include a tongue feature (e.g., tongue **1114**) which may engage a cooperating feature of a product container (e.g., notch **1116** of product container **256**). Tongue **1114** may transfer force to product container **256** (e.g., via notch **1116**), and may assist insertion and removal of product container **256** into, and out of, slot assembly **264**. For example, during insertion, product container **256** may be at least partially inserted into slot assembly **264**. When door **1110** is closed, tongue **1114** may engage notch **1116**, and transfer door closing force to product container **256**, securing seating product container **256** in slot assembly **264** (e.g., as a result of the leverage provided by door **1110**). Similarly, tongue **1114** may at least partially engage notch **1116** (e.g., may be at least partially captured by a lip of notch **1116**), and may apply a removal force (e.g., again as a result of the leverage provided by door **1110**) to product container **256**.

[0369] Product module **250** may include one or more indicator lights, e.g., which may convey information regarding the status of a one or more slot assemblies (e.g., slot assemblies **260**, **262**, **264**, **266**). For example, each of the doors (e.g., door **1112**) may include a light pipe (e.g., light pipe **1118**) optically coupled to a light source (e.g., light source **1120**). Light pipe **1118** may include, for example, a segment of clear or transparent material (e.g., a clear plastic such as acrylic, glass, etc.)

that may transmit light from light source **1120** to the front of door **1112**. Light source **1120** may include, for example, one or more LED's (e.g., a red LED and a green LED). In the case of a double-wide door (e.g., door **1108**) only a single light pipe and single light source, associated with the single light pipe, corresponding to one of the slot assemblies may be utilized. The unused light source, corresponding to the other slot assembly of the double-wide door, may be blocked off by at least a portion of the door.

[0370] As mentioned, light pipe **1118** and light source **1120** may convey various information regarding the slot assembly, product container, etc. For example, light source **1120** may provide a green light (which may be conveyed via light pipe **1118** to the front of door **1112**) to indicate an operational status of slot assembly **266** and a non-empty status of the product container releasably engaged in slot assembly **266**. Light source **1120** may provide a red light (which may be conveyed via light pipe **1118** to the front of door **1112**) to indicate that the product container releasably engaged in slot assembly **266** is empty. Similarly, light source **1120** may provide a flashing red light (which may be conveyed via light pipe **1118** to the front of door **1112**) to indicate a malfunction or fault associated with slot assembly **266**. Various additional/alternative information may be indicated using light source **1120** and light pipe **1118**. Further, additional related lighting schemes may also be utilized (e.g., flashing green light, orange light resulting from the light source providing both a green and a red light, and the like).

[0371] Referring also to FIGS. **43A**, **43B**, and **43C**, product container **256** may, for example, include a two piece housing (e.g., include front housing portion **1150** and rear housing portion **1152**). Front housing portion **1150** may include protrusion **1154**, e.g., which may provide lip **1156**. Lip **1156** may facilitate handling of product container **256** (e.g., during insertion and/or removal of product container from slot assembly **264**).

[0372] Rear housing portion **1152** may include fitment feature **1158a**, e.g., which may fluidly couple the product container (e.g., product container **256**) to a mating fitment of a pump assembly (e.g., pump assembly **272** of product module **250**). Fitment feature **1158a** may include a blind mate fluid connector, which may fluidly couple product container **256** to pump assembly **272** when fitment feature is pressed onto a cooperating feature (e.g., a stem) of pump assembly **272**. Various alternative fitment features (e.g., fitment feature **1158b** depicted in FIG. **44**) may be provided to provide fluid coupling between product container **256** and various pump assemblies.

[0373] Front housing portion **1150** and rear housing portion **1152** may include separate plastic components which may be joined to form product container **256**. For example, front housing portion **1150** and rear housing portion **1152** may be heat staked together, adhesively bonded, ultrasonically welded, or otherwise joined in a suitable manner. Product container **256** may further include product pouch **1160**, which may be at least partially disposed within front housing portion **1150** and rear housing portion **1152**. For example, product pouch **1160** may be filled with a consumable (e.g., a beverage flavoring), and positioned within front housing portion **1150** and rear housing portion **1152**, which may be subsequently joined to house product pouch **1160**. Product pouch **1160** may include, for example, a flexible bladder that may collapse as the consumable is pumped from product pouch **1160** (e.g., by pump assembly **272**).

[0374] Product pouch **1160** may include gussets **1162**, which may improve the volumetric efficiency of product container **256**, e.g., by allowing product pouch **1160** to occupy a relatively larger portion of the interior volume defined by front housing portion **1150** and rear housing portion **1152**. Additionally, gussets **1162** may facilitate the collapse of product pouch **1162** as the consumable is pumped out of product pouch **1160**. Additionally, fitment feature **1158a** may be physically joined to product pouch **1160**, e.g., via ultrasonic welding.

[0375] As mentioned above, in addition to the microingredient towers, lower cabinet portion **1006a** may include supply **1056** of a large volume microingredient. For example, in some embodiments, the large volume microingredient may be a non-nutritive sweetener (e.g., an artificial sweetener or combination of a plurality of artificial sweeteners). Some embodiments may include

microingredients in which larger volumes are required. In these embodiments, one or more large volume microingredient supplies may be included. In the embodiment as shown, supply **1056** may be a non-nutritive sweetener which may include, for example, a bag-in-box container, e.g., which is known to include a flexible bladder containing the non-nutritive sweetener product disposed within a generally rigid box, e.g., which may protect the flexible bladder against rupture, etc. For purposes of illustration only, the non-nutritive sweetener example will be used. However, in other embodiments, any microingredient may be stored in the large volume microingredient supply. In some alternate embodiments, other types of ingredients may be stored in a supply similar to supply **1056** as described herein. The term “large volume microingredient” refers to a microingredient identified as a frequent use microingredient in which, for the products being dispensed, is used frequently enough that a greater than one microingredient pump assembly is used.

[0376] Supply **1056** of non-nutritive sweetener may be coupled to a product module assembly, e.g., which may include one or more pump assemblies (e.g., as previously described above). For example, supply **1056** of non-nutritive sweetener may be coupled to a product module including four pump assemblies as described above. Each of the four pump assemblies may include a tube or line directing non-nutritive sweetener from the respective pump assembly to nozzle **24**, for dispensing the non-nutritive sweetener (e.g., in combination with one or more additional ingredients).

[0377] Referring to FIGS. **45A** and **45B**, lower cabinet portion **1006b** may include one or more features of microingredient subsystem **18**. For example, lower cabinet portion **106b** may house one or more microingredient supplies. The one or more microingredient supplies may be configured as one or more microingredient shelves (e.g., microingredient shelves **1200**, **1202**, **1204**) and a supply **1206** of non-nutritive sweetener. As shown, each microingredient shelf (e.g., microingredient shelf **1200**) may include one or more product module assemblies (e.g., product module assemblies **250d**, **250e**, **250f**) configured in a generally horizontal arrangement. One or more of the microingredient shelves may be configured to agitate (e.g., in a generally similar manner to microingredient tower **1052** described above).

[0378] Continuing with the above-described embodiment, in which the one or more microingredient supplies may be configured as one or more microingredient shelves, and as discussed above, shelf **1200** may include a plurality of product module assemblies (namely, product module assemblies **250d**, **250c**, **250f**). Each product module assembly (e.g., product module assembly **250f**) may be configured to releasably engage one or more product containers (e.g., product container **256**) in a respective slot assembly (e.g., slot assemblies **260**, **262**, **264**, **266**).

[0379] Additionally, each of product module assemblies **250d**, **250c**, **250f** may include a respective plurality of pump assemblies. For example, and referring also to FIGS. **47A**, **47B**, **47D**, **47E**, and **47F**, product module assembly **250d** may generally include pump assemblies **270a**, **270b**, **270d**, and **270e**. A respective one of pump assemblies **270a**, **270b**, **270c**, **270d** may be associated with one of slot assemblies **260**, **262**, **264**, **266**, e.g., for pumping ingredients contained within a respective product container (e.g., product container **256**). For example, each of pump assemblies **270a**, **270b**, **270c**, **270d** may include a respective fluid coupling stem (e.g., fluid coupling stems **1250**, **1252**, **1254**, **1256**), e.g., which may fluidly couple to a product container (e.g., product container **256**) via a cooperating fitment (e.g., fitment feature **1158a**, **1158b** shown in FIGS. **43B** and **44**).

[0380] Referring to FIG. **47E**, a cross sectional view of the pump module assembly **250d** is shown. The assembly **250d** includes a fluid inlet **1360** which is shown in the cross sectional view of the fitment. The fitment mates with the female part (shown in FIG. **43B** as **1158a**) of the product containers (not shown, shown as **256** in FIG. **43B**, amongst other figures). The fluid from the product container enters the pump assembly **250d** at the fluid inlet **1360**. The fluid flows into the capacitive flow sensor **1362** and then through the pump **1364**, past the backpressure regulator **1366** and to the fluid outlet **1368**. As shown herein, the fluid flow path through the pump module assembly **250d** allows the air to flow through the assembly **250d** without being trapped within the

assembly. The fluid inlet **1360** is on a lower plane than the fluid exit **1368**. Additionally, the fluid travels vertically towards the flow sensor and then when traveling in the pump, is again at a higher plane than the inlet **1360**. Thus, the arrangement allows the fluid to continually flow upwards allowing air to flow through the system without getting trapped. Thus, the pump module assembly **250d** design is a self-priming and purging positive displacement fluid delivery system.

[0381] Referring to FIGS. **47E** and **47F**, the backpressure regulator **1366** may be any backpressure regulator, however, the exemplary embodiment of the backpressure regulator **1366** for pumping small volumes is shown. The backpressure regulator **1366** includes a diaphragm **1367** including “volcano” features and a molded o-ring about the outer diameter. The o-ring creates a seal. A piston is connected to the diaphragm **1367**. A spring, about the piston, biases the piston and the diaphragm in a closed position. In this embodiment, the spring is seated on an outer sleeve. When the fluid pressure meets or exceeds the cracking pressure of the piston/spring assembly, the fluid flows past the backpressure regulator **1366** and towards the fluid exit **1368**. In the exemplary embodiment, the cracking pressure is approximately 7-9 psi. The cracking pressure is tuned to the pump **1364**. Thus, in various embodiments, the pump may be different from the one described, and in some of those embodiment, another embodiment of the backpressure regulator may be used.

[0382] With additional reference to FIG. **48**, outlet plumbing assembly **1300** may be configured to releasably engage pump assemblies **270a**, **270b**, **270c**, **270d**, e.g., for supplying ingredients from a respective product module assembly (e.g., product module assembly **250d**) to plumbing/control subsystem **20**. Outlet plumbing assembly **1300** may include a plurality of plumbing fitments (e.g., fitments **1302**, **1304**, **1306**, **1308**) configured to fluidly couple to respective pump assemblies **270a**, **270b**, **270c**, **270d**, e.g., for fluidly coupling pumping assemblies **270a**, **270b**, **270c**, **270d** to plumbing/control subsystem **20** via fluid lines **1310**, **1312**, **1314**, **1316**.

[0383] Releasable engagement between outlet plumbing assembly **1300** and product module assembly **250d** may be effectuated, e.g., via a camming assembly providing facile engagement and release of outlet plumbing assembly **1300** and product module assembly **250d**. For example, the camming assembly may include handle **1318** rotatably coupled to fitment support **1320**, and cam features **1322**, **1324**. Cam features **1322**, **1324** may be engageable with cooperating features (not shown) of product module assembly **250d**. With reference to FIG. **47C**, rotational movement of handle **1318** in the direction of the arrow may release outlet plumbing assembly **1300** from product module assembly **250d**, e.g., allowing outlet plumbing assembly **1300** to be lifted away, and removed, from product module assembly **250d**.

[0384] With particular reference to FIGS. **47D** and **47E**, product module assembly **250d** may similarly be releasably engageable to microingredient shelf **1200**, e.g., allowing facile removal/installation of product module assembly **250** to microingredient shelf **1200**. For example, as shown, product module assembly **250d** may include release handle **1350**, e.g., which may be pivotally connected to product module assembly **250d**. Release handle **1350** may include, e.g., locking cars **1352**, **1354** (e.g., most clearly depicted in FIGS. **47A** and **47D**). Locking cars **1352**, **1354** may engage cooperating features of microingredient shelf **1200**, e.g., thereby retaining product module assembly **250d** in engagement with microingredient shelf **1200**. As shown in FIG. **47E**, release handle **1350** may be pivotally lifted in the direction of the arrow to disengage locking cars **1352**, **1354** from the cooperating features of microingredient shelf **1200**. Once disengaged, product module assembly **250d** may be lifted from microingredient shelf **1200**.

[0385] One or more sensors may be associated with one or more of handle **1318** and/or release handle **1350**. The one or more sensors may provide an output indicative of a locking position of handle **1318** and/or release handle **1350**. For example, the output of the one or more sensors may indicate whether handle **1318** and/or release handle **1350** is in an engaged or a disengaged position. Based upon, at least in part the output of the one or more sensor, product module assembly **250d** may be electrically and/or fluidly isolated from plumbing/control subsystem **20**. Exemplary sensors may include, for example, cooperating RFID tags and readers, contact switches, magnetic position

sensors, or the like.

[0386] As discussed above and referring again to FIG. 47E, flow sensor **308** may be utilized to sense flow of the above-described micro-ingredients through (in this example) pump assembly **272** (See FIG. 5A-5H). As discussed above, flow sensor **308** may be configured as a capacitance-based flow sensor (See FIGS. 5A-5F); as illustrated as flow sensor **1356** within FIG. 47E. Additionally and as discussed above, flow sensor **308** may be configured as a transducer-based, pistonless flow sensor (See FIG. 5G); as illustrated as flow sensor **1358** within FIG. 47E. Further and as discussed above, flow sensor **308** may be configured as a transducer-based, piston-enhanced flow sensor (See FIG. 5H); as illustrated as flow sensor **1359** within FIG. 47E.

[0387] As discussed above, transducer assembly **328** (See FIGS. 5G-5H) may include: a linear variable differential transformer (LVDT); a needle/magnetic cartridge assembly; a magnetic coil assembly; a Hall Effect sensor assembly; a piezoelectric buzzer element; a piezoelectric sheet element; an audio speaker assembly; an accelerometer assembly; a microphone assembly; and an optical displacement assembly.

[0388] Further, while the above-described examples of flow sensor **308** are meant to be illustrative, they are not intended to be exhaustive, as other configurations are possible and are considered to be within the scope of this disclosure. For example, while transducer assembly **328** is shown to be positioned outside of diaphragm assembly **314** (See FIG. 5G-5H), transducer assembly **328** may be positioned within chamber **318** (See FIG. 5G-5H).

[0389] Referring also to FIGS. 49A, 49B, 49C, an exemplary configuration of supply **1206** of non-nutritive sweetener. Supply **1206** of non-nutritive sweetener may generally include housing **1400** configured to receive non-nutritive sweetener container **1402**. Non-nutritive sweetener container **1402** may include, for example, a bag-in-box configuration (e.g., a flexible bag containing the non-nutritive sweetener disposed within a generally rigid, protective housing). Supply **1206** may include coupling **1404** (e.g., which may be associated with pivotal wall **1406**), which may fluidly couple to a fitment associated with non-nutritive container **1402**. The configuration and nature of coupling **1404** may vary according to the cooperating fitment associated with non-nutritive container **1402**.

[0390] Referring also to FIG. 49C, supply **1206** may include one or more pump assemblies (e.g., pump assemblies **270c**, **270f**, **270g**, **270h**). The one or more pump assemblies **270c**, **270f**, **270g**, **270h** may be configured similar to the above-discussed product module assemblies (e.g., product module assembly **250**). Coupling **1404** may be fluidly coupled to coupling **1404** via plumbing assembly **1408**. Plumbing assembly **1408** may generally include inlet **1410**, which may be configured to be fluidly connected to coupling **1404**. Manifold **1412** may distribute non-nutritive sweetener received at inlet **1410** to one or more distribution tubes (e.g., distribution tubes **1414**, **1416**, **1418**, **1420**). Distribution tubes **1414**, **1416**, **1418**, **1420** may include respective connectors **1422**, **1424**, **1426**, **1428** configured to be fluidly coupled to respective pump assemblies **270c**, **270f**, **270g**, **270h**.

[0391] Referring now to FIG. 50, plumbing assembly **1408**, in the exemplary embodiments, includes an air sensor **1450**. The plumbing assembly **1408** thus includes a mechanism for sensing whether air is present. In some embodiments, if the fluid entering through the fluid inlet **1410** includes air, the air sensor **1450** will detect the air and, in some embodiments, may send a signal to stop pumping from the large volume microingredient. This function is desired in many dispensing systems, and particularly in ones where if the volume of the large volume microingredient is incorrect, the dispensed product may be compromised and/or dangerous. Thus, the plumbing assembly **1408** including an air sensor assures air is not pumped and in embodiments where medicinal products are dispensed, for example, is a safety feature. In other products, this embodiment of the plumbing assembly **1408** is part of a quality assurance feature.

[0392] While the various electrical components, mechanical components, electro-mechanical components, and software processes are described above as being utilized within a processing

system that dispenses beverages, this is for illustrative purposes only and is not intended to be a limitation of this disclosure, as other configurations are possible. For example, the above-described processing system may be utilized for processing/dispensing other consumable products (e.g., ice cream and alcoholic drinks). Additionally, the above-described system may be utilized in areas outside of the food industry. For example, the above-described system may be utilized for processing/dispensing: vitamins; pharmaceuticals; medical products, cleaning products; lubricants; painting/staining products; and other non-consumable liquids/semi-liquids/granular solids or any fluids.

[0393] As discussed above, the various electrical components, mechanical components, electro-mechanical components, and software processes of processing system **10** generally (and FSM process **122**, virtual machine process **124**, and virtual manifold process **126** specifically) may be used in any machine in which on-demand creation of a product from one or more substrates (also referred to as “ingredients”) is desired.

[0394] In the various embodiments, the product is created following a recipe that is programmed into the processor. As discussed above, the recipe may be updated, imported or changed by permission. A recipe may be requested by a user, or may be preprogrammed to be prepared on a schedule. The recipes may include any number of substrates or ingredients and the product generated may include any number of substrates or ingredients in any concentration desired.

[0395] The substrates used may be any fluid, at any concentration, or, any powder or other solid that may be reconstituted either while the machine is creating the product or before the machine creates the product (i.e., a “batch” of the reconstituted powder or solid may be prepared at a specified time in preparation for metering to create additional products or dispensing the “batch” solution as a product). In various embodiments, two or more substrates may themselves be mixed in one manifold, and then metered to another manifold to mix with additional substrates.

[0396] Thus, in various embodiments, on demand, or prior to actual demand but at a desired time, a first manifold of a solution may be created by metering into the manifold, according to the recipe, a first substrate and at least one additional substrate. In some embodiments, one of the substrates may be reconstituted, i.e., the substrate may be a powder/solid, a particular amount of which is added to a mixing manifold. A liquid substrate may also be added to the same mixing manifold and the powder substrate may be reconstituted in the liquid to a desired concentration. The contents of this manifold may then be provided to e.g., another manifold or dispensed.

[0397] In some embodiments, the methods described herein may be used in conjunction with mixing on-demand dialysate, for use with peritoneal dialysis or hemodialysis, according to a recipe/prescription. As is known in the art, the composition of dialysate may include, but is not limited to, one or more of the following: bicarbonate, sodium, calcium, potassium, chloride, dextrose, lactate, acetic acid, acetate, magnesium, glucose and hydrochloric acid.

[0398] The dialysate may be used to draw waste molecules (e.g., urea, creatinine, ions such as potassium, phosphate, etc.) and water from the blood into the dialysate through osmosis, and dialysate solutions are well-known to those of ordinary skill in the art.

[0399] For example, a dialysate typically contains various ions such as potassium and calcium that are similar to their natural concentration in healthy blood. In some cases, the dialysate may contain sodium bicarbonate, which is usually at a concentration somewhat higher than found in normal blood. Typically, the dialysate is prepared by mixing water from a source of water (e.g., reverse osmosis or “RO” water) with one or more ingredients: e.g., an “acid” (which may contain various species such as acetic acid, dextrose, NaCl, CaCl, KCl, MgCl, etc.), sodium bicarbonate (NaHCO₃), and/or sodium chloride (NaCl). The preparation of dialysate, including using the appropriate concentrations of salts, osmolarity, pH, and the like, is also well-known to those of ordinary skill in the art. As discussed in detail below, the dialysate need not be prepared in real-time, on-demand. For instance, the dialysate can be made concurrently or prior to dialysis, and stored within a dialysate storage vessel or the like.

[0400] In some embodiments, one or more substrates, for example, the bicarbonate, may be stored in powder form. Although for illustrative and exemplary purposes only, a powder substrate may be referred to in this example as “bicarbonate”, in other embodiments, any substrate/ingredient, in addition to, or instead of, bicarbonate, may be stored in a machine in powder form or as another solid and the process described herein for reconstitution of the substrate may be used. The bicarbonate may be stored in a “single use” container that, for example, may empty into a manifold. In some embodiments, a volume of bicarbonate may be stored in a container and a particular volume of bicarbonate from the container may be metered into a manifold. In some embodiments, the entire volume of bicarbonate may be completely emptied into a manifold, i.e., to mix a large volume of dialysate.

[0401] The solution in the first manifold may be mixed in a second manifold with one or more additional substrates/ingredients. In addition, in some embodiments, one or more sensors (e.g., one or more conductivity sensors) may be located such that the solution mixed in the first manifold may be tested to ensure the intended concentration has been reached. In some embodiments, the data from the one or more sensors may be used in a feedback control loop to correct for errors in the solution. For example, if the sensor data indicates the bicarbonate solution has a concentration that is greater or less than the desired concentration, additional bicarbonate or RO may be added to the manifold.

[0402] In some recipes in some embodiments, one or more ingredients may be reconstituted in a manifold prior to being mixed in another manifold with one or more ingredients, whether those ingredients are also reconstituted powders/solids or liquids.

[0403] Thus, the system and methods described herein may provide a means for accurate, on-demand production or compounding of dialysate, or other solutions, including other solutions used for medical treatments. In some embodiments, this system may be incorporated into a dialysis machine, such as those described in U.S. patent application Ser. No. 12/072,908, filed Feb. 27, 2008, which is now U.S. Pat. No. 8,246,826 issued Aug. 21, 2012 (Attorney Docket No. F65) each of which is herein incorporated by reference in its entirety. In other embodiments, this system may be incorporated into any machine where mixing a product, on-demand, may be desired.

[0404] Water may account for the greatest volume in dialysate, thus leading to high costs, space and time in transporting bags of dialysate. The above-described processing system **10** may prepare the dialysate in a dialysis machine, or, in a stand-alone dispensing machine (e.g., on-site at a patient's home), thus eliminating the need for shipping and storing large numbers of bags of dialysate. This above-described processing system **10** may provide a user or provider with the ability to enter the prescription desired and the above-described system may, using the systems and methods described herein, produce the desired prescription on-demand and on-site (e.g., including but not limited to: a medical treatment center, pharmacy or a patient's home). Accordingly, the systems and methods described herein may reduce transportation costs as the substrates/ingredients are the only ingredient requiring shipping/delivery.

[0405] In addition to the various embodiments of the flow control modules discussed and described above, referring to FIGS. **56-64**, various additional embodiments of a variable line impedance, a flow measurement device (or sometimes referred to as “flow meter”) and a binary valve for a flow control module are shown.

[0406] Referring to FIGS. **56-59** collectively, the exemplary embodiment of this embodiment of the flow control module **3000** may include a fluid inlet **3001**, a piston housing **3012**, a primary orifice **3002**, a piston **3004** a piston spring **3006**, a cylinder **3005** about the piston and a secondary orifice(s) **3022**. The piston spring **3006** biases the piston **3004** in a closed position, seen in FIG. **56**. The flow control module **3000** also includes a solenoid **3008** which includes a solenoid housing **3010** and an armature **3014**. A downstream binary valve **3016** is actuated by a plunger **3018** which is biased in an open position by a plunger spring **3020**.

[0407] The piston **3004**, cylinder **3005**, piston spring **3006** and piston housing **3012** may be made

from any material which, in some embodiments, may be selected based on the fluid intended to flow through the flow control module. In the exemplary embodiment, the piston **3004** and the cylinder **3005** are made from an alumina ceramic, however, in other embodiments, these components may be made from another ceramic or stainless steel. In various embodiments, these components may be made from any material desired and may be selected depending on the fluid. In the exemplary embodiment, the piston spring **3006** is made from stainless steel, however, in various embodiments; the piston spring **3006** may be made from a ceramic or another material. In the exemplary embodiment, the piston housing **3012** is made from plastic. However, in other embodiments, the various parts may be made from stainless steel or any other dimensionally stable, corrosion resistant material. Although as shown in FIGS. **56-59**, the exemplary embodiment includes a binary valve, in some embodiments, the flow control module **3000** may not include a binary valve. In these embodiments, the cylinder **3005** and the piston **3004**, where in the exemplary embodiment, as discussed above, are made from alumina ceramic, may be match ground to a free running fit, or may be manufactured to impart a very tight clearance between the two components to provide a close, free running fit.

[0408] The solenoid **3008** in the exemplary embodiment is a constant force solenoid **3008**. In the exemplary embodiments, the constant force solenoid **3008** shown in FIGS. **56-59** may be used. The solenoid **3008** includes a solenoid housing **3010** which, in the exemplary embodiment, is made from 416 stainless steel. In the exemplary embodiment, the constant force solenoid **3008** includes a spike. In this embodiment, as the armature **3014** approaches the spikes, the force is roughly constant and minimally variant with respect to position. The constant force solenoid **3008** exerts magnetic force onto the armature **3014**, which, in the exemplary embodiment, is made from 416 stainless steel. In some embodiments the armature **3014** and/or the solenoid housing **3012** may be made from a ferritic stainless steel or any other magnetic stainless steel or other material having desirable magnetic properties. The armature **3014** is connected to the piston **3004**. Thus, the constant force solenoid **3008** provides force to linearly move the piston **3004** from a closed position (shown in FIGS. **56** and **57**) to an open position (shown in FIGS. **58** and **59**) with respect to the secondary orifice(s) **3022**. Thus, the solenoid **3008** actuates the piston **3004** and the current applied to control the constant force solenoid **3008** is proportional to the force exerted on the armature **3014**.

[0409] The size of the primary orifice **3002** may be selected so that the maximum pressure drop for the system is not exceeded and such that the pressure across the primary orifice **3002** is significant enough to move the piston **3004**. In the exemplary embodiment, the primary orifice **3002** is about 0.180 inch. However, in various embodiments, the diameter may be larger or smaller depending on the desired flow rate and pressure drop. Additionally, obtaining the maximum pressure drop at a particular flow rate minimizes the total amount of travel by the piston **3004** to maintain a desired flow rate.

[0410] The constant force solenoid **3008** and the piston spring **3006** exert roughly a constant force over piston **3004** travel. The piston spring **3006** acts on the piston **3004** in the same direction as the fluid flow. A pressure drop occurs upon the entrance of fluid through the primary orifice **3002**. The constant force solenoid **3008** (also referred to as a “solenoid”) counters the fluid pressure by exerting force on the armature **3014**.

[0411] Referring now to FIG. **56**, the flow control module **3000** is shown in a closed position, with no fluid flow. In the closed position, the solenoid **3008** is de-energized. The piston spring **3006** biases the piston **3004** to the closed position, i.e., the secondary orifice(s) (shown in FIGS. **58-59** as **3022**) are fully closed. This is beneficial for many reasons, including, but not limited to, a fail safe flow switch in the event the flow control module **3000** experiences a loss of power. Thus, when power is not available to energize the solenoid **3008**, the piston **3004** will move to “normally closed” state.

[0412] Referring also to FIGS. **57-59**, the energy or current applied to the solenoid **3008** controls the movement of the armature **3014** and the piston **3004**. As the piston **3004** moves further towards

the fluid inlet **3001**, this opens the secondary orifice(s) **3022**. Thus, the current applied to the solenoid **3008** may be proportional to the force exerted on the armature **3014** and the current applied to the solenoid **3008** may be varied to obtain a desired flow rate. In the exemplary embodiment of this embodiment of the flow control module the flow rate corresponds to the current applied to the solenoid **3008**; as current is applied the force on the piston **3004** increases. [0413] To maintain a constant force profile on the solenoid **3008**, it may be desirable to maintain the travel of the armature **3014** roughly within a predefined area. As discussed above, the spike in the solenoid **3008** contribute to the maintenance of near constant force as the armature **3014** travels. This is desirable in some embodiments for when the secondary orifice(s) **3022** are open, maintaining near constant force will maintain a near constant flow rate.

[0414] As the force from the solenoid **3008** increases, in the exemplary embodiment, the force from the solenoid **3008** moves the piston **3004** linearly towards the fluid inlet **3001** to initiate flow through the secondary orifice(s) **3022**. This causes the fluid pressure within the flow control module to decrease. Thus, the primary orifice **3002** (linked to the piston **3004**), together with the secondary orifice(s) **3022**, act as a flow meter and variable line impedance; the pressure drop across the primary orifice **3002** (which is in indicator of flow rate) remains constant through varying the cross sectional areas of the secondary orifice(s) **3022**. The flow rate, i.e., the pressure differential across the primary orifice **3002**, dictates the amount of movement of the piston **3004**, i.e., the variable line impedance of the fluid path.

[0415] Referring now to FIGS. **58-59**, in the exemplary embodiment, the variable line impedance includes at least one secondary orifice **3022**. In some embodiments, for example, the embodiments shown in FIGS. **58-59**, the secondary orifice **3022** includes multiple apertures. Embodiments including multiple apertures may be desirable as they allow for structural integrity maintenance and minimize piston travel while providing a total secondary orifice size sufficient for a desired flow rate at a maximum pressure drop.

[0416] Referring to FIGS. **56-59**, to equalize pressure that may be introduced by blow-by during operation, in the exemplary embodiment, the piston **3004** includes at least one radial groove **3024**. In the exemplary embodiment, the piston **3004** includes two radial grooves **3024**. In other embodiments, the piston **3004** may include three or more radial grooves. The at least one radial groove **3024** provides both a means for equalizing the pressure from the blow-by, thus, centering the piston **3004** in the cylinder **3005** which may reduce blow-by. Centering of the piston **3004** may also provide a hydrodynamic bearing effect between the cylinder **3005** and the piston **3004**, thus reducing friction. In some embodiments, any other means for reducing friction may be used, which include, but are not limited to, coating the piston **3004** to reduce friction and/or incorporating the use of ball bearings. Coatings which may be used include, but are not limited to diamond-like-coating (“DLC”) and titanium nitride. Reducing friction is beneficial for reduction of hysteresis in the system thus reducing flow control errors in the system.

[0417] In the exemplary embodiment, for a given variable line impedance device, the current as well as the method of applying the current to yield a given flow rate may be determined. The various modes of applying the current include, but are not limited to, dithering the current, sinusoidal dither, dither scheduling the current or using various Pulse Width Modulation (“PWM”) techniques. Current control may be used to produce various flow rates and various flow types, for example, but not limited to, choppy or pulsatile flow rates or smooth flow rates. For example, sinusoidal dithering may be used to reduce hysteresis and friction between the cylinder **3005** and the piston **3004**. Thus, predetermined schedules may be determined and used for a given desired flow rate.

[0418] Referring now to FIG. **64**, an example of a solenoid control method which may be applied to the variable line impedance device shown in FIGS. **56-63** is shown. In this control method, a dither function is shown that applies lower amplitude dither at low flow rates and higher amplitude dither at as the flow rates increase. The dither may be specified either as a step function, where

dither may increase at a specified threshold, or as a ramp function, which may become constant above a specified threshold. FIG. 64 shows an example of a dither ramp function. Both dither frequency and dither amplitude may be varied with the current command. In some embodiments, the dither function may be replaced by a lookup table that specifies optimal dither characteristics or other dither scheduling for any desired flow rate.

[0419] Upstream fluid pressure may increase or decrease. However, the variable line impedance compensates for pressure changes and maintains the constant desired flow rate through use of the constant force solenoid, together with the spring and the plunger. Thus, the variable line impedance maintains a constant flow rate even under variable pressure. For example, when the inlet pressure increases, because the system includes a fixed sized primary orifice 3002, the pressure drop across the primary orifice 3002 will cause the piston 3004 to move toward the fluid outlet 3036 and “turn down” the opening of the secondary orifice(2) 3022. This is accomplished through linear movement of the piston 3004 towards the fluid outlet 3036.

[0420] Conversely, when the inlet pressure decreases, because the system has a fixed sized primary orifice 3002, the pressure drop across the primary orifice 3002 will cause the piston 3004 to “turn up” the opening of the secondary orifice(s) 3022 thus keeping flowrate constant. This is accomplished through linear movement of the piston 3004 towards the fluid inlet 3001.

[0421] The exemplary embodiment also includes a binary valve. Although shown in the exemplary embodiment, in some embodiments, a binary valve may not be used, for example, where the tolerances between the piston and the secondary orifice are such that the piston may act as a binary valve to the secondary orifice. Referring now to FIGS. 56-59, the binary valve in the exemplary embodiment is downstream from the secondary orifice 3022. In the exemplary embodiment, the binary valve is a piloted diaphragm 3016 actuated by a plunger 3018. In the exemplary embodiment, the diaphragm 3016 is an over molded metal disc, however, in other embodiments, the diaphragm 3016 may be made from any material suitable for the fluid flowing through the valve, which may include, but is not limited to, metals, elastomers and/or urethanes or any type of plastic or other material suitable for the desired function. It should be noted that although the FIGS. illustrate the membrane seated in the open position, in practice, the membrane would be unseated. The plunger 3018 is directly actuated by the piston 3004 and in its resting position; the plunger spring 3020 biases the plunger 3018 in the open position. As the piston 3004 returns to a closed position, the force generated by the piston spring 3006 is great enough to overcome to plunger spring 3020 bias and actuate the plunger 3018 to the closed position of the binary valve. Thus, in the exemplary embodiment, the solenoid provides the energy for both the piston 3004 and the plunger 3018, thus, controls both the flow of fluid through the secondary orifice 3022 and through the binary valve.

[0422] Referring to FIGS. 56-59, the progressive movement of the piston 3004 may be seen with respect to increased force from the solenoid 3008. Referring to FIG. 56, both the binary valve and the secondary orifice (not shown) are closed. Referring to FIG. 57, current has been applied to the solenoid and the piston 3004 has moved slightly, while the binary valve is open due to the plunger spring 3020 bias. In FIG. 58, the solenoid 3008 having applied additional current, the piston 3004 has moved further to primary orifice 3002 and has opened the secondary orifice 3022 slightly. Referring now to FIG. 59, increased current from the solenoid 3008 has moved the piston 3004 further towards the fluid inlet 3001 (or further into the solenoid 3008 in this embodiment), and the secondary orifice 3022 is fully open.

[0423] The embodiments described above with respect to FIGS. 56-59 may additionally include one or more sensors, which may include one or more, but not limited to, the following: a piston position sensor and/or a flow sensor. One or more sensors may be used to verify that fluid flow is established when the solenoid 3008 is energized. A piston position sensor, for example, may detect whether or not the piston is moving. A flow sensor may detect whether the piston is moving or not moving.

[0424] Referring now to FIGS. **60-61**, in various embodiments, the flow control module **3000** may include one or more sensors. Referring to FIG. **60**, the flow control module **3000** is shown with an anemometer **3026**. In one embodiment, one or more thermistor(s) are located in close proximity to a thin wall contacting the fluid path. The thermistor(s) may dissipate a known power amount, e.g., 1 Watt, and thus, a predictable temperature increase may be expected for either stagnant fluid or flowing fluid. As the temperature will increase less where fluid is flowing, the anemometer may be used as a fluid flow sensor. In some embodiments, the anemometer may also be used to determine the temperature of the fluid, whether or not the sensor is additionally detecting the presence of fluid flow.

[0425] Referring now to FIG. **61**, the flow control module **3000** is shown with a paddle wheel **3028**. A cut-away view of the paddle wheel sensor **3030** is shown in FIG. **62**. The paddle wheel sensor **3030** includes a paddle wheel **3028** within the fluid path, an Infrared (“IR”) emitter **3032** and an IR receiver **3034**. The paddle wheel sensor **3030** is a metering device and may be used to calculate and/or confirm flow rate. The paddle wheel sensor **3030** may, in some embodiments, be used to simply sense whether fluid is flowing or not. In the embodiment shown in FIG. **62**, the IR diode **3032** shines and as fluid flows, the paddle wheel **3028** turns, interrupting the beam from IR diode **3032**, which is detected by the IR receiver **3034**. The rate of interruption of the IR beam may be used to calculate flow rate.

[0426] As shown in FIGS. **56-59**, in some embodiments, more than one sensor may be used in the flow control module **3000**. In these embodiments, both an anemometer sensor and a paddle wheel sensor are shown. While, in other embodiments, either the paddle wheel (FIG. **61**) or the anemometer (FIG. **60**) sensor is used. However, in various other embodiments, one or more different sensors may be used to detect, calculate or sense various conditions of the flow control module **3000**. For example, but not limited to, in some embodiments, a Hall Effect sensor may be added to the magnetic circuit of the solenoid **3010** to sense flux.

[0427] In some embodiments, the inductance in the coil of the solenoid **3008** may be calculated to determine the position of the piston **3004**. In the solenoid **3008** in the exemplary embodiment, reluctance varies with armature **3014** travel. The inductance may be determined or calculated from the reluctance and thus, the position of the piston **3004** may be calculated based on the calculated inductance. In some embodiments, the inductance may be used to control the movement of the piston **3004** via the armature **3014**.

[0428] Referring now to FIG. **63**, one embodiment of the flow control module **3000** is shown.

[0429] This embodiment of the flow control module **3000** may be used in any of the various embodiments of the dispensing system described herein. Further, the variable flow impedance mechanism may be used in place of the various variable flow impedance embodiments described above. Further, in various embodiments, the flow control module **3000** may be used in conjunction with a downstream or upstream flow meter.

[0430] Referring to FIG. **65**, the fluid path is indicated through one embodiment of the flow control module **3000**. In this embodiment, the flow control module **3000** includes both a paddle wheel **3028** sensor and an anemometer **3026**. However, as discussed above, some embodiments of the flow control module **3000** may include additional sensors or less sensors than shown in FIG. **65**.

[0431] In some embodiments, one or more of pump assemblies **270**, **272**, **274**, **276** shown in FIG. **4** may be a solenoid piston pump assembly that is driven by an electrical circuit and logic that allows the flow to be monitored. An example of an embodiment of a solenoid pump **270** and drive circuitry are shown in FIG. **66**, where the pump **270** is energized by passing current through the coil **3214**. The resulting magnetic flux may drive the solenoid slug or piston **3216** to the left and may compress the return spring **3210**. The pumped fluid may flow through the piston **3216** and check valve **3218** as the piston **3218** moves to the left. The spring **3210** may return the piston **3216** to the right when coils **3214** are no longer applying enough magnetic flux to hold the spring compressed. As the piston **3216** moves to the right, the check valve **3218** may close and force the

fluid out of the pump. In some embodiments, pumps available from ULKA Costruzioni Elettromeccaniche S.p.A. of Pavia, Italy may be used.

[0432] The solenoid piston pump may move a given volume of fluid from left to right each time the piston compresses the spring to the left hand side of FIG. 66 and returns to the original position on the right. The solenoid piston pump may be energized by a number of driving circuits that are well known in the art. The various modes of applying the current include, but are not limited to, dithering the current, sinusoidal dither, dither scheduling the current and/or using various Pulse Width Modulation (“PWM”) techniques.

[0433] Some embodiments include where the driving circuit is connected to a power supply by a circuit capable of creating a variable current through the coils 3214 and measuring the current flow through the solenoid. The circuit may measure the current flow indirectly by measuring other parameters which may include, but are not limited to, one or more of the following: the voltage across the solenoid coil and/or the duty cycle of the periodic current flow. In some embodiments, as shown in FIG. 66, multiple solenoid pump may be connected to a power supply via a PWM controller 3203 and a current sensor 3207. However, in some embodiments, one solenoid pump may be connected to a power supply via a PWM controller 3203 and a current sensor 3207. The PWM controller 3203 may operate at a high frequency to control the voltage supplied to the coil superimposed on a slower frequency to control the cycling of the pump. In some embodiments, the PWM controller 3203 may energize the pump at a frequency optimized for pump operation, referred to herein as “optimized pump frequency”. The optimized pump frequency may, in some embodiments, be determined by one or more variables including, but not limited to, the stiffness of the spring 3210, the mass of the piston 3216, and/or the viscosity of the fluid. In some embodiments, the pump frequency may be approximately 20 Hz. However in other embodiments, the pump frequency may be greater than or less than 20 Hz. The PWM controller 3203 may control the voltage while energizing the pump by cycling at a high frequency at a range of duty cycles. In some embodiments the PWM controller 3203 cycles at 10 kHz while energizing the pump coil. In some embodiments, the methodology for generating the above-described drive signal is one disclosed in U.S. patent application Ser. No. 11/851,344, entitled SYSTEM AND METHOD FOR GENERATING A DRIVE SIGNAL, which was filed on 6 Sep. 2007, now U.S. Pat. No. 7,905,373 (Attorney Docket F45), issued Mar. 15, 2011, which is hereby incorporated herein by reference in its entirety.

[0434] In some embodiments, the PWM controller 3203 may vary the voltage during the time the pump is energized. In some embodiments, the PWM controller 3203 may hold the voltage constant while the pump is energized. In some embodiments, the PWM controller 3203 may initially raise the voltage to the desired level and hold the voltage constant during the pump energization, then ramp the voltage down to zero at a desired rate. In some embodiments, the voltage may be ramped down to zero to minimized noise in the drive circuits of the other pumps sharing a common power supply.

[0435] In some embodiments, the duty cycle may be fixed to provide a constant voltage or, in some embodiments, the duty cycle may be varied to provide a time varying voltage while energizing the pump. In some embodiments, the PWM controller 3203 and current sensor 3207 may be linked to the control logic subsystem 14. In some embodiments, the control logic subsystem 14 may control the flow of fluids through the pump by commanding the pump duty cycle. The control logic subsystem 14 may vary the voltage applied to the pump by varying the high frequency duty cycle. The control logic subsystem 14 may monitor and record the current through the pump. The control logic subsystem 14 may vary the high frequency duty cycle of the PWM controller 3203 to control the current measured by the current sensor 3207. In some embodiments, the control logic subsystem 14 may monitor the current sensor signal to identify abnormal flow conditions.

[0436] One embodiment of the PWM controller and current sensor is shown schematically in FIG. 67. This embodiment is one embodiment and in various other embodiments the arrangement of the

PWM controller and current sensor may vary. Q5 is the transistor for PWMing the current to the solenoid. The R54 is a high-side current-sense resistor used by U11 current-sense/difference amplifier with output signal CURRENT1. The connectors J12 and J13 are the electrical interface to the solenoid. F3 is a fuse for catastrophic fault isolation. D10 is for snubbing energy stored in solenoid inductance. The power supply provides 28.5V DC power. However, in some embodiments, the schematic may vary.

[0437] In some embodiments, the flow through the solenoid pump **270** may be monitored by measuring the current flow through the solenoid coil **3214**. The coil is an inductor-resistor element which allows a rising current flow after the voltage is applied. The position of the piston **3216** relative to the coil **3214** affects the inductance of the coil and thus affects the shape of the current rise.

[0438] A “functional pump stroke” is defined herein as a pump stroke that moves a volume of fluid out the pump that is a significant fraction of the rated volume per stroke for the given pump. A functional pump stroke may be further defined as not exceeding the design temperature or current limits for the coil **3214**. One example of a functional pump stroke is shown in FIG. **68A**. The current through the solenoid coil is plotted as line **3310** that starts at zero and rises toward a steady state value. Line **3325** plots the 2nd time derivative of the current through the solenoid. The timing and size of the 2nd derivative peak **3325** may be indicative of the timing and speed of the piston. The current measurements may indicate a number of abnormal conditions including, but not limited to, one or more of the following: air or vacuum in the pump, blocked or occluded line, excessive coil temperature, and/or abnormal coil current.

[0439] In some embodiments, the control logic subsystem **14** may determine if one or more micro-ingredient product containers, for example, product containers **254**, **256**, **258** shown in FIG. **4**, are empty or unable to supply additional ingredient, by monitoring the signal from the current sensor **3207**. Product containers **254**, **256**, **258** are herein used as an example of one embodiment, however, in various other embodiments, the number of product containers may vary. The condition of an empty product container **254**, **256**, **258** or a blocked line upstream of the valve **270** is herein referred to as a “Sold-Out Condition”.

[0440] The micro-ingredient product container **254**, **256**, **258** may contain RFID tags that store a value that represents the amount of liquid left in the product container **254**, **256**, **258**. This value is herein referred to as the “Fuel Gauge” and has units of milliliters (mL). The Fuel Gauge is set to a full value when the product container **254**, **256**, **258** is filled. In use the Fuel Gauge value may be periodically updated by the control logic subsystem **14**.

[0441] In some embodiments, the control logic subsystem **14** may determine the Sold-Out Condition (of a product container) exists based in part on the output of the current sensor **3207**.

[0442] In some embodiments, the control logic subsystem **14** may determine the Sold-Out Condition exists in a micro-ingredient product container **254**, **256**, **258** based in part on the Fuel Gauge value of the container. In some embodiments, the control logic subsystem **14** may determine the Sold-Out Condition based on one or more inputs including but not limited to one or more of the following: the current sensor output, the Fuel Gauge value and/or the status of the pour. The output of the current sensor **3207** during each pump stroke may be processed by the control logic subsystem **14** to determine if the stroke was a functional stroke, a Sold-Out Stroke or a non-functional stroke. The functional stroke was defined above and the Sold-Out Stroke and non-functional strokes will be more fully described below.

[0443] In some embodiments, the control logic subsystem **14** determines a Sold-Out condition exists if a given number/threshold of consecutive Sold-Out Strokes occurs. The threshold number of consecutive Sold-Out Strokes varies with the Fuel Gauge value and with the status of the pour. For example, in some embodiments, the control logic subsystem **14** may declare a Sold-Out Condition when the Fuel Gauge is above a threshold volume, for example, 60 mLs, and the pump experiences a threshold number of Sold-Out Strokes in a row, for example, 60 Sold-Out Strokes in

a row, however these values are given merely by example and in various other embodiments, these values may differ. The sensitivity of the Sold-Out Algorithm is reduced in some embodiments, because the Fuel Gauge indicates a substantial amount of fluid left in the container. When the Fuel Gauge is below the threshold volume, which, in some embodiments, may be 60 mLs for example, the control logic subsystem **14** may declare a Sold-Out Condition if there are a threshold number of Sold-Out Strokes in a row, e.g. three (3) consecutive Sold-Out Strokes, or if the system determines that the threshold number of consecutive Sold-Out Strokes is reached, and there have been e.g. twelve (12) strokes to container **30** during the current pour. In some embodiments, if the Fuel Gauge is below the threshold volume, e.g. 60 mLs, and there have been less than e.g. **12** strokes during the current pour, the control logic subsystem **14** may declare a Sold-Out Condition after e.g. 20 consecutive Sold-Out Strokes. In some embodiments, the number of Sold-Out Strokes may be stored from pour to pour. The Sold-Out Stroke counter may be reset to zero anytime a functional stroke is recorded. The criteria for non-functional stroke are described below and include criteria for an occluded stroke, a temperature error and a current error.

[0444] In various embodiments, multiple pumps may pump fluid out of a common source to achieve a desired flow rate. The common source may include any fluid including, but not limited to non-nutritive sweetener (NNS). The control logic subsystem **14** may declare a Sold-Out Condition for example when any one pump produces a given number of consecutive Sold-Out Strokes. In some embodiments, the control logic subsystem **14** declares a Sold-Out Condition when any one of the pumps has 20 consecutive Sold-Out Strokes. However, in various other embodiments, the number of consecutive Sold-Out Strokes that indicate a Sold-Out Condition may vary.

[0445] In some embodiments, a Sold-Out Stroke may be detected by the control logic subsystem **14** by an algorithm that measures the peak amplitude of the 2.sup.nd order time derivative of the current and the timing of the peak amplitude. Referring to FIG. **68B**, an exemplary plot of the current **3350** and its 2.sup.nd derivative **3360** for a Sold-Out stroke is shown. The peak in the 2.sup.nd derivative **3360** of the current with respect to time at **3365** is higher and earlier than the peak **3325** for a normal pumping trace shown in FIG. **68A**.

[0446] A Sold-Out Stroke may be defined as a value of SO greater than a threshold value where SO is defined as:

$$[00004] \text{ SO} = \frac{\frac{d^2 I}{dt_{\text{max}}^2}}{(t_{\text{max}} - ft)^2} \quad [\text{EQN1}]$$

[0447] d.sup.2I/dt.sup.2.sub.max is the maximum value of the 2nd time derivative of the current, t.sub.max is the time from the start of current flow to d.sup.2I/dt.sup.2.sub.max and ft is a constant. The SO threshold value for a Sold-Out Stroke may be determined experimentally. The constant ft may be calibrated for each solenoid pump. The constant ft may be equal to 9.5 milliseconds.

[0448] In some embodiments, the SO value may be calculated from raw A-D measurement and the number of time steps.

$$[00005] \text{ SO} = \frac{\overset{\text{.Math.}}{I}_{\text{max}} * 2^{16}}{(t_{\text{max}} - ft)^2} \quad [\text{EQN2}]$$

Where $\ddot{I}_{\text{sub.max}}$ is the peak value for the 2.sup.nd derivative of the current and t.sub.max is the number of time steps after voltage is applied to the solenoid pump. The value of ft may be calibrated for each solenoid pump or may be set to 95. The SO threshold value is 327680 for this calculation.

[0449] In some embodiments, the 2.sup.nd time derivative of the current may be calculated by first filtering the current signal with an alpha beta filter:

$$[00006] \begin{aligned} I_i &= I_{i-1} + C_i \\ &= 0.9 \\ &= 0.1 \end{aligned} \quad [\text{EQN3}]$$

where $I_{\text{sub.i-1}}$ is the current calculated in the previous step, and $C_{\text{sub.i}}$ is the current read from

the A-D (in A-D counts), where one count equals 1.22 mA. The first and second derivatives of the current with respect to time may be calculated as

$$[00007] \dot{I} = \overset{k=0}{\underset{-15}{\text{Math.}}} I_k - 4 \overset{k=-12}{\underset{-15}{\text{Math.}}} I_k \quad [EQN4] \quad \overset{\text{Math.}}{\dot{I}} = \overset{k=0}{\underset{-15}{\text{Math.}}} \dot{I}_k - 4 \overset{k=-12}{\underset{-15}{\text{Math.}}} \dot{I}_k \quad [EQN5]$$

The 2.sup.nd derivative may be filtered with an alpha beta filter where $\alpha=0.85$ and $\beta=0.15$.

$$[00008] \overset{\text{Math.}}{\dot{I}}_i = \overset{\text{Math.}}{\dot{I}}_{i-1} + \overset{\text{Math.}}{\dot{I}}_i \quad [EQN6]$$

The determination of the 2nd time derivative of the current is described as an example and may be calculated by a number of alternate methods well known in the art.

[0450] In some embodiments, the control logic subsystem **14** may determine if the line supplying fluid to the container **30** in FIG. **1** is blocked or occluded based on the signal from the current sensor **3207**. Referring to FIG. **68C**, an exemplary plot of the current **3370** and its 2.sup.nd derivative **3380** for a occluded stroke is shown. The value of the 2.sup.nd time derivative **3382** at 5 ms or 50 time steps may be significantly higher than the 2.sup.nd time derivative of the current in a functional pumping stroke **3322** in FIG. **68A**. Referring to FIG. **68D**, an exemplary plot of the 2.sup.nd time derivative of the current for pumping strokes **3320** and for an occluded stroke **3380** is shown. In some embodiments, the control logic subsystem **14** may determine that an occluded condition exists if the 2.sup.nd time derivative of the current flow is above an occluded threshold value at a specified time. The specified time and threshold values may be determined experimentally. The specified time and threshold values may be determined for each pump.

[0451] In some embodiments the occlusion value OCC may be determined by the following equation:

$$[00009] OCC = \overset{\text{Math.}}{\dot{I}}_{50} + (A * R - B) \quad [EQN7]$$

Where $\dot{I}_{50}$ is the 2.sup.nd time derivative of the current at 5 ms after voltage is applied to the solenoid pump, R is the resistance of the coil and A and B are empirical constants. In some embodiments, the resistance R may be measured during the maximum current flow at the end of the piston stroke which may occur e.g. 14.0 ms after voltage is first applied to the pump. The resistance may be calculated from the applied voltage and measured current. The applied voltage may be calculated from the voltage of the power supply **3209** times the PWM duty cycle. The power supply voltage may be an assumed value or it may be measured. The current may be measured by the current sensor **3207**.

[0452] In some embodiments the OCC value may be calculated from raw A-D measurement and the number of time steps as:

$$[00010] OCC = \overset{\text{Math.}}{\dot{I}}_{50} + (3.84 * \text{Resistance} - 9216) \quad [EQN8]$$

The occluded threshold for this equation may be -2304. Alternatively the occluded threshold may be set to a value **2048** above the OCC value for a functional pump stroke. The OCC value for a normal pump stroke may be determined on a manufacturing test and the value recorded for each pump. Therefore the OCC value may vary in various embodiments.

[0453] The resistance is calculated as

$$[00011] \text{Resistance} = \frac{1195 * (5000 - PWM_{\text{Value}})}{I_{\text{Max}}} \quad [EQN9]$$

where the PWM_Value may vary between 200 and 2000 (27.36 volts to 17.1 volts). The $I_{\text{sub.max}}$ is the highest current during the time that the valve is energized.

[0454] The coil temperature may be determined from the output of the current sensor. The coil temperature may be calculated from the known temperature coefficient of the coil wire material and the resistance at a known temperature.

$$[00012] \text{Temperature} = \frac{\text{Resistance}}{T_{\text{coef}} * R_{T0}} + T0 \quad [EQN10]$$

In some embodiments, copper wire may be used for the coil with a temperature coefficient of 0.4%/

° C. and the resistance of the coil is 7 ohms at 20° C.

$$[00013] \text{ Temperature} = \frac{\text{Resistance}}{0.004*7} + 20 \quad [\text{EQN11}]$$

where Temperature is the coil temperature in degrees C., Resistance is calculated as described above and has units of ohms. The control logic subsystem **14** may declare a temperature error when the measured temperature, calculated from the coil resistance as described above, exceeds a maximum allowed value. In some embodiments, the maximum allowed temperature for the coil temperature may be 120 degrees C. However, in various other embodiments the maximum allowed temperature for the coil temperature may be less than or greater than 120 degrees C.

[0455] In some embodiments, the control logic subsystem **14** may control current by adjusting the PWM command sent to the PWM controller **3203** based on the output of the current sensor **3207**. In some embodiments, the PWM command value is limited to values between 200 and 2000 (27.36 and 17.1 volts respectively). However, in various other embodiments the PWM command value may not be limited and in some embodiments where the PWM command value is limited, the values may be greater than or less than the range listed herein by example. The current may be controlled to a maximum value $I_{\text{sub.Max}}$ through the following equation:

$$[00014] \quad \begin{aligned} i &= I_{\text{Max}} - I_{\text{target}} \\ \text{PWM} &= \text{PWM}_{\text{prev}} + \left(-\frac{i}{2}\right) \end{aligned} \quad [\text{EQN12}]$$

In some embodiments, the control logic subsystem **14** may compare the measured maximum current $I_{\text{sub.Max}}$ to the target current $I_{\text{sub.Target}}$ for each stroke. In some embodiments, the control logic subsystem **14** may declare a current error if the absolute current difference [absolute value of ($I_{\text{sub.Max}} - I_{\text{sub.Target}}$)] exceeds a given current error threshold. In some embodiments, the current error threshold may be 1.22 A, however in various other embodiments the maximum current error threshold may be less than or greater than 1.22 A.

[0456] In some embodiments, the control logic subsystem **14** may determine that the pump **270** is unable to deliver fluid. In some embodiments, the control logic subsystem **14** may monitor the number of consecutive Occluded Strokes based on the occluded threshold described above. In some embodiments, the control logic subsystem **14** may monitor the number of times coil-temperature errors occur. In some embodiments, the control logic subsystem **14** may monitor the number of times a current error occurs. The logic controller subsystem **14** may determine that the pump **270** is unable to deliver fluid if a sufficient number of consecutive non-functional strokes occur. A non-functional stroke may include, but is not limited to, one or more of the following: an occluded stroke, excessive temperature and/or current error. In some embodiments, the control logic subsystem **14** may declare that the pump is unable to deliver fluid if e.g. 3 non-functional strokes occur consecutively. The non-functional stroke count may in some embodiments return to zero as soon as a functional stroke occurs. However in various other embodiments the number of non-functional strokes required to declare the pump is unable to deliver fluid may be less than or greater than 3.

Noise Detect

[0457] In addition to the Sold-Out calculations and methods described above, in some embodiments, Sold-Out may also be determined by analyzing the standard deviation of the Sold-out values to detect noise. This may be desirable for many reasons, including, but not limited to, the ability to determine a Sold-Out condition sooner. In this method, the Sold-Out condition may be determined by measuring the variability of the current signal/Sold-Out values. In some embodiments, by detecting noise a Sold-Out condition may be determined.

[0458] Referring to FIG. 74, this data represents results showing the Sold-Out value. In this example, the product was not found to be Sold-Out until the end of the data set. However, during this time, and before the product was found to be Sold-Out, the product was under-delivered where the Sold-Out value was noisy.

[0459] In some embodiments, a method to determine a Sold-Out condition may include analyzing the noise of the Sold-Out value. In some embodiments, the standard deviation may be used to detect the noise. The standard deviation is shown below:

$$[00015] \quad = \sqrt{\frac{1}{N} \cdot \text{Math.} \sum_{t=1}^N (x_t - \bar{x})^2} \quad [\text{EQN13}]$$

[0460] The standard deviation equation may be simplified to make the equation more efficient for use by removing constants and eliminating square roots and multiplications. In some embodiments, the simplified equation may be used. The resulting equation is an approximation of standard deviation, at least in terms of the signal to noise ratio for the Sold-Out data, while relying only on add, subtract, and shift operations.

$$[00016] \quad \bar{x} = \left[\text{Math.} \sum_{i=1}^8 x_i \right] \gg 3 = \text{Math.} \sum_{i=1}^8 x_i - \bar{x} \cdot \text{Math.} \quad [\text{EQN14}]$$

[0461] Referring now to FIG. 75, the standard deviation estimate is shown compared with the Sold-Out Value. As shown, the calculations above measure the difference between normal pumping and the noise condition. In various embodiments, a predetermined, pre-programmed threshold may be set to indicate a noise condition. In various embodiments, a standard deviation/estimated standard deviation threshold may be preset/pre-programmed at 10. However, in other embodiments, the threshold amount may be greater than or less than 10.

[0462] In some embodiments, the standard deviation method to determine Sold-Out may be pre-programmed to be inactive when the Fuel Gauge is above a threshold amount, which, in some embodiments, may be 60 mL, but in other embodiments, the threshold amount may be greater than or less than 60 mL.

[0463] In some embodiments, the equation 15, shown below, may be used, where x is the calculated Sold Out value described above.

$$[00017] \quad \bar{x} = \left[\text{Math.} \sum_{i=1}^8 x_i \right] \gg 3 = \text{Math.} \sum_{i=1}^8 x_i - \bar{x} \cdot \text{Math.} \quad [\text{EQN15}]$$

In some embodiments, the system may determine the product is Sold-Out (and, in some embodiments, when the system determines that the product is Sold-Out for a given pulse, the system increments a counter, as described above) if, for a given pulse, the Sold-Out value is greater than a predetermined/pre-set threshold or if the standard deviation or estimated standard deviation is greater than a predetermined/pre-set threshold. For each of these conditions, in some embodiments, a counter is incremented. In some embodiments, once the counter reaches a predetermined/pre-set threshold, the product container is Sold-Out.

[0464] In some embodiments, a Fuel Gauge method is used. In some embodiments, the RFID tag assembly indicates the volume of product in the product container. In some embodiments, each time product is pumped out of the product container, the RFID tag assembly is updated with the updated volume by subtracting the volume pumped from the volume Fuel Gauge. In some embodiments, when the Fuel Gauge reaches a preset/predetermined threshold threshold, for example, in some embodiments, the preset/predetermined threshold may be -15 ml, the system may determine that the product container is Sold-Out even if the above-discussed Sold-Out methods do not determine that the product container is Sold-Out. In some embodiments, if the Fuel Gauge reaches a preset/predetermined threshold, the system may desensitize the Sold-Out and/or standard deviation equation. In some embodiments, this threshold may be 60.

[0465] In some embodiments, each of product module assemblies **250d**, **250e**, **250f** may include a respective plurality of pump assemblies. For example, and referring also to FIGS. **69A**, **69B**, **69D**, **69E**, and **69F**, product module assemblies **250d**, **250e**, **250f** in FIG. **4** may generally include pump assemblies **4270a**, **4270b**, **4270d**, and **4270c**. A respective one of pump assemblies **4270a**, **4270b**, **4270c**, **4270d** may be associated with one of slot assemblies **260**, **262**, **264**, **266**, e.g., for pumping ingredients contained within a respective product container (e.g., product container **256**). For

example, each of pump assemblies **4270a**, **4270b**, **4270c**, **4270d** may include a respective fluid coupling stem (e.g., fluid coupling stems **1250**, **1252**, **1254**, **1256**), e.g., which may fluidly couple to a product container (e.g., product container **256**) via a cooperating fitment (e.g., fitment feature **1158a**, **1158b** shown in FIGS. **43B** and **44**).

[0466] Referring to FIG. **69E**, a cross sectional view of the pump module assembly **250d** is shown. The assembly **250d** includes a fluid inlet **4360** which is shown in the cross sectional view of the fitment. The fitment mates with the female part (shown in FIG. **43B** as **1158a**) of the product containers (not shown, shown as **256** in FIG. **43B**, amongst other figures). The fluid from the product container enters the pump assembly **250d** at the fluid inlet **4360**. The fluid flows through the pump **4364**, past the backpressure regulator **4366** and up to the fluid outlet **4368**. As shown herein, the fluid flow path through the pump module assembly **250d** allows the air to flow through the assembly **250d** without being trapped within the assembly. The fluid inlet **4360** is on a lower plane than the fluid exit **4368**. Additionally, the fluid travels vertically from the plane of the inlet and pump **4368** through the back pressure regulator **4366** to the plane of the exit **4368**. Thus, the arrangement allows the fluid to continually flow upwards allowing air to flow through the system without getting trapped. Thus, the pump module assembly **250d** design is a self-priming and purging positive displacement fluid delivery system.

[0467] Referring to FIGS. **69E** and **69F**, the backpressure regulator **4366** may be any backpressure regulator; however, an embodiment of the backpressure regulator **4366** for pumping small volumes is shown. The backpressure regulator **4366** includes a diaphragm **4367** including “volcano” features and a molded o-ring about the outer diameter. The o-ring creates a seal. A piston **4365** is connected to the diaphragm **4367**. A spring **4366**, about the piston **4365**, biases the piston and the diaphragm in a closed position. In this embodiment, the spring is seated on an outer sleeve **4369**. When the fluid pressure meets or exceeds the cracking pressure of the piston/spring assembly, the fluid flows past the backpressure regulator **4366** and towards the fluid exit **4368**. In some embodiments, the cracking pressure is approximately 7-9 psi. The cracking pressure may be tuned to the pump **4364**. In some embodiments, the cracking pressure may be adjusted by changing the position of the outer sleeve **4369**. The outer sleeve **4369** may be threaded into an outer wall **4370**. Turning the outer sleeve **4329** relative to the outer wall **4370** may change the preload on the spring **4368** and thus the cracking pressure. An adjustable regulator may be produced more cheaply than a regulator with a precisely fixed back-pressure. An adjustable regulator may then be adjusted and tuned to the individual pump during manufacturing and check-out testing. In various embodiments, the pump may be different from the one described, and in some of those embodiment, another embodiment of the backpressure regulator may be used.

[0468] Releasable engagement between outlet plumbing assembly **4300** and product module assembly **250d** may be effectuated, e.g., via a camming assembly providing facile engagement and release of outlet plumbing assembly **4300** and product module assembly **250d**. For example, the camming assembly may include handle **4318** rotatably coupled to fitment support **4320**, and cam features **4322**, **4324**. Cam features **4322**, **4324** may be engageable with cooperating features (not shown) of product module assembly **250d**. With reference to FIG. **69C**, rotational movement of handle **4318** in the direction of the arrow may release outlet plumbing assembly **4300** from product module assembly **250d**. e.g., allowing outlet plumbing assembly **4300** to be lifted away, and removed, from product module assembly **250d**.

[0469] With particular reference to FIGS. **69D** and **69E**, product module assembly **250d** may similarly be releasably engaged to microingredient shelf **1200**, e.g., allowing facile removal/installation of product module assembly **250d** to microingredient shelf **1200**. For example, as shown, product module assembly **250d** may include release handle **4350**, e.g., which may be pivotally connected to product module assembly **250d**. Release handle **4350** may include, e.g., locking cars **4352**, **4354** (e.g., most clearly depicted in FIGS. **69A** and **69D**). Locking cars **4352**, **4354** may engage cooperating features of microingredient shelf **1200**, e.g., thereby retaining

product module assembly **250d** in engagement with microingredient shelf **1200**. As shown in FIG. **69E**, release handle **4350** may be pivotally lifted in the direction of the arrow to disengage locking cars **4352**, **4354** from the cooperating features of microingredient shelf **1200**. Once disengaged, product module assembly **250d** may be lifted from microingredient shelf **1200**.

[0470] One or more sensors may be associated with one or more of handle **4318** and/or release handle **4350**. The one or more sensors may provide an output indicative of a locking position of handle **4318** and/or release handle **4350**. For example, the output of the one or more sensors may indicate whether handle **4318** and/or release handle **4350** is in an engaged or a disengaged position. Based upon, at least in part the output of the one or more sensor, product module assembly **250d** may be electrically and/or fluidly isolated from plumbing/control subsystem **20**. Exemplary sensors may include, for example, cooperating RFID tags and readers, contact switches, magnetic position sensors, or the like.

[0471] The flow may be monitored by measuring the current flow through the solenoid piston pump **4364** as described above. One or more constants used to interpret the current flow measurements may be calibrated to individual pumps in the product module assembly **250d**. These calibration constants may be determined during check-out testing as part of the manufacturing process. The calibration constants may be stored in an e-prom that is connected to the electronics board via a removal plug. Referring to FIGS. **69C**, **69D** and **69E**, the e-prom may be mounted in a plug **4380** that is connected to the pump electronic board **4386** after assembly. The e-prom plug **4380** may connect to a USB mount **4387** on the electronic board **4386** to assure good mechanical attachment. The e-prom plug **4380** may seal liquid from the electronics by sealing on the inside of the port **4282** of the electronic case. The e-prom **4380** may be attached via a lanyard to a mount **4384** on the case of the product module assemblies **250d**. The e-prom plug **4380** may be kept with the pump assembly **4390** when the electronics board **4386** is replaced. A separate e-prom advantageously separates the electronics into a plug **4380** that is matched to a specific pump assembly **4390** and an electronic board that can be used with any pump assembly. The electronics board **4386** and the pump assembly **4390** may include features including but not limited to clips for electrical contacts **4392**, slots **4393** and threaded holds **4394** to facilitate quick disassembly and reassembly.

[0472] In some embodiments, the processing system **10** may include an external communication module **4500**, one embodiment of which is shown in FIG. **70A**, that may allow service personnel and or consumers to communicate with the processing system **10** using, for example, but not limited to, one or more of the following: RFID tags and/or bar codes and/or other formats. In some embodiments, the external communication module **4500** may incorporate the previously described RFID access antenna assembly **900**. The external communication module **4500** may include a number of devices that may receive or send communications including, but not limited to, one or more of the following: a radio frequency antenna **4530**, an optical bar code reader **4510**, blue tooth antenna, camera and/or other short range communication hardware. The processing system **10** may use information obtained by the external communication module **4500** to, for example, facilitate service and maintenance by a number of actions including, but not limited to, one or more of the following: unlocking service doors, informing the service provider of errors, required maintenance, failed equipment, required parts, and/or identifying those containers which may need to be replaced. The external communication module **4500** may provide consumers/users with one or more options for interacting with the processing system including, but not limited to, one or more of the following: redeeming coupons and/or providing individual services including, but not limited to, one or more of the following: personalized beverages and/or accepting payment and/or tracking use and/or awarding prizes. In some embodiments, the external communication module **4500** may communicate with the control logic subsystem **14** and receive electrical power via a wired connection at connector **4552**. The external communication module **4500** may communicate with the control logic subsystem **14** via wireless communication.

[0473] In some embodiments, the external communication module **4500** may be mounted near the front surface of the housing assembly **850**. In some embodiments, the external communication module **4500** may be mounted in the structure of the processing system **10** such that the bar code reader or other optical device has an unobstructed view to the outside. In some embodiments, the RFID antenna may also be mounted within an inch of the front surface of the processing system **10** [0474] In some embodiments, the external communication module **4500** may include a bar code reader/decoder **4510**. The barcode reader/decoder **4510** may read any optical code presented within its line of sight. In some embodiments, the optical code may be presented in a number of formats including, but not limited to, one or more of the following: as a printed item and/or as an image on an electronic device and/or on a smart phone and/or on a personal digital assistant and/or on the screen of a computer or any other device capable of displaying an optical code.

[0475] In some embodiments, the RFID antenna reader may receive a signal from a variety of devices presented to the processing system **10** by, for example, service personnel and/or users/consumers. The list of possible RFID devices includes, but is not limited to, one or more of the following: key fobs and/or plastic cards and/or paper cards.

[0476] One embodiment of the external communication module **4500** is shown in FIGS. **70A** and **70B**. In some embodiments, the module may be housed in a case **4502**. In some embodiments, the case **4502** may be plastic, however, in various other embodiments, the case may be made from a different material. In some embodiments, the case **4502** may be open on one side to receive the RFID sensor close to the outside of the housing assembly **850**. In some embodiments, the case **4502** may include one or more, or a plurality, of flanges **4504**. The flanges **4504** may be used to secure the module to the structure of the processing system **10** or to the skin of the housing assembly **850**.

[0477] Many of the individual components of one embodiment may be seen in the exploded drawing of the external communication module **4500** shown in FIG. **70B**. In this embodiment, the RFID antenna assembly **4530** (FIG. **70**) may include an antenna **4548**, a resonator **4540**, resonator spacers **4546**, **4544**, and an outlet junction **4552**. The barcode reader/decoder **4510** may be held by a foam mount **4520**. The foam mount **4520** may retain the barcode reader/decoder **4510** within the case **4502** during installation of the external communication module **4500** in the processing system **10**. The foam mount **4520** may be secured within the external communication module **4500** by the spacer **4522** that passes through a matching hole in the foam mount **4520**. The RFID antenna assembly **4530** and the foam mount **4520** may be secured to the case **4502** by one or more screws (and/or bolts and/or other attachment mechanisms) that pass through the PCB of the RFID antenna assembly **4530** and are thread into molded bosses in the case **4502**.

[0478] In some embodiments, the external communication module **4500** may be mounted in the structure of the upper door **4600** as shown in FIG. **71A**. In some embodiments, the external communication module **4500** may be secured to the upper door **4600** with mechanical fasteners including, but not limited to, one or more of the following: screws and/or rivets and/or snaps through the flanges **4504**, or other mechanical fasteners or the like. In some embodiments, the upper door **4600** may be part of the internal structure of the housing assembly **850**. In some embodiments, an upper door skin **4610** may be attached to the upper door **4600**.

[0479] In some embodiments, an alignment bracket **4630** may be attached to the upper door skin **4610**. In some embodiments, the alignment bracket **4630** may align the barcode reader/decoder **4510** to the windows **4620** in the upper door skin **4610** as shown in FIGS. **71B** and **71C**. In some embodiments, the alignment bracket may be aligned with the windows **4620** and attached with, for example, including, but not limited to, one or more of the following: glue and/or double sided tape and/or other non-mechanical attachment methods compatible with a plastic skin on the inside of the upper door skin **4610**. However, in some embodiments, mechanical fasteners may be used. In some embodiments, the alignment bracket may be attached with mechanical fasteners to the upper door skin **4610** which may include, but not limited to, one or more of screws and/or rivets and/or snaps.

In some embodiments, the alignment bracket **4630** may be aligned to the windows **4620** with a sticker (not shown) or other indicator that may be attached or may be indicated on the upper door skin **4610** and provides visual marks to aid in the proper alignment of the alignment bracket **4630** to the windows **4620**. In some embodiments, the visual marks may include, but are not limited to, embossing and/or marked on and/or stuck on letters and/or symbols and/or colors and/or any other indicator that may assist with proper alignment.

[0480] In some embodiments, the alignment bracket **4630** may align the barcode reader/decoder **4510** independently of the alignment of the external communication module **4500**. In some embodiments, the bracket, one embodiment of which is shown in detail in FIG. **72**, provides two side tabs **4632**, a top tab **4636** and a bottom tab **4634** to constrain the barcode reader/decoder **4510** in two dimensions (X & Y) to align with the windows **4620**. However, in various other embodiments, the number and location of the tabs may vary. The flexible foam mount **4520** assists the barcode reader/decoder **4510** to translate in two dimensions (X & Y) and to rotate about the Z axis as the alignment bracket **4630** guides the barcode reader/decoder **4510** during the insertion of the external communication module **4500** into the upper door **4600**. In some embodiments, the foam mount **4520** may constrain the barcode reader/decoder so that the external communication module **4500** can be installed in the upper door. In some embodiments, the foam mount **4520** may further constrain barcode reader/decoder **4510** so that the leading corners of the barcode reader/decoder contact the tapered sections of the tabs **4631**, **4634** and **4636**. In some embodiments, the barcode reader/decoder **4510** may be constrained in the Z axis by the alignment bracket **4630** and the PCB **4550** of the RFID antenna. In some embodiments, the upper door skin **4610** and the PCB **4550** may provide a limited amount of compliance to allow for tolerance stackup in the Z direction between the upper door skin **4610**, external communication module **4500** and the barcode reader/decoder **4510**.

[0481] In some embodiments the barcode reader/decoder **4510** may be retained in the external communication module **4500** by flexible brackets. The flexible brackets may provide enough flexibility to allow the barcode reader/decoder **4510** to translate and rotate as needed to align with the alignment bracket. The flexible brackets may constrain the barcode reader/decoder within a limited range to allow insertion of the module into the upper door **4600**. The flexible brackets **4520** may further constrain the barcode reader/decoder **4510** so that the leading corners of the barcode reader/decoder contact the tapered sections of the tabs **4631**, **4634** and **4636** during the insertion process.

[0482] In some embodiments, the tabs **4632**, **4634**, **4636** on the alignment bracket **4630** may include an angled section **4633** that guides the barcode reader/decoder **4510** into alignment with the windows **4620**. In some embodiments, each tab includes a straight section near the base **4631** that is perpendicular to the base and constrains the movement of the barcode reader/decoder **4510** in the X & Y directions. In some embodiments, the distance between the straight sections of opposing tabs may be slightly larger than the barcode reader/decoder which may be beneficial for many reasons, including, but not limited to, ease of assembly and alignment accuracy. In some embodiments, the tab may have larger or smaller tapered sections to allow installation through openings in the upper door **4600**.

[0483] In some embodiments, the external communication module **4500** may allow consumers/users to interact with the processing system **10** by a variety of methods including, but not limited to, a communication interface tethered to the external communication module **4500**, a communication interface retractably tethered to the external communication module **4500**, and/or a wireless communication interface (e.g., Bluetooth technology and/or a wireless network or in various embodiments, any wireless communication interface). In some embodiments, the communication interface may be implemented by an application on one or more of consumers'/users' devices. In some embodiments, the wireless communication interface may be implemented by one or more applications on one or more consumers'/users' devices. In some

embodiments, one or more consumers'/users' desktop may be wireless capable devices including, but not limited to, smartphones, computers, desktop computers, laptop computers, MP3 players, and/or tablet computers. In some embodiments, the external communication module **4500** may be part of or communicate with an automation network.

[0484] As stated above, in some embodiments, the product dispensing system may have a processing system **10**. Referring now also to FIG. **79**, in some embodiments, processing system may contain a power module **7900**. In some embodiments, the power module **7900** may include a control and power distribution component **7902**, an AC power switch **7904**, a power supply **7906**, and an AC motor control **7908**. In some embodiments, the power module **7900** may include a communication interface (e.g. a controller area network (CAN) bus, Ethernet, etc.) to allow communication between subsystems within the processing system **10**. In some embodiments, the communication interface may extend from the control and power distribution component **7902**. In some embodiments, the communication interface may allow communication between the control and power distribution component **7902** and user interface subsystem **22**.

[0485] Referring now also to FIGS. **80-81**, in some embodiments, processing system **10** may include a power module **8000**. The power module **8000** may include a power distribution control **8002** and a power supply unit **8008**. In some embodiments, the power module **8000** may include a connection **8014** to connect the power supply unit **8008** to an AC power switch **8010**. In some embodiments, AC power may be routed through the AC power switch **8010** before AC power is sent to the power supply unit **8008** via connection **8014**. In some embodiments, the power supply unit **8008** may contain an AC motor control. In some embodiments, the power distribution control **8002** may contain a machine control processor **8004**. In some embodiments, the power distribution control **8002** may contain a power distribution module **8006**. In some embodiments, a connection **8012** may connect the power supply unit **8008** and the power distribution control **8002**. In some embodiments, the connection **8012** may be used for a variety of purposes including, but not limited to, one or more of the following: transmitting DC power from the power supply unit **8008** to the power distribution control **8002** and/or transmitting control data between the machine control processor **8004** and the power supply unit **8008**. In some embodiments, the power supply unit **8008** may supply power to the power distribution control **8002** via a connection to the power distribution module **8006**. In some embodiments, the power distribution module **8006** may send power to the machine control processor **8004**. In some embodiments, the machine control processor **8004** may control the processing system **10** via a microprocessor and a communication interface (e.g. a CAN bus, Ethernet, etc.) routed through the power distribution module **8006**. In some embodiments, the communication interface may allow communication between the machine control processor **8004** and a user interface module **8032** via connection **8048**. In some embodiments, the machine control processor **8004** may communicate with the user interface module **8032** remotely (i.e. the user interface module **8032** may be physically decoupled from the power module **8000**, and connection **8048** may be a wireless connection). For example, in some embodiments, the machine control processor **8004** may communicate with the user interface module **8032** using Bluetooth technology or a wireless network. In various embodiments, the user interface module **8032** may be attached to the housing assembly **850** in one or more mechanisms for attachment which may include, but are not limited to, one or more of the following: a tether, a retractable tether, VELCRO, one or more clips, and/or one or more brackets. In some embodiments, the user interface module **8032** may be physically decoupled from the housing assembly **850** and interact with the product dispensing system remotely. In some embodiments, a consumer/user may use the user interface module **8032** to interact with the product dispensing system in a variety of ways which may include, but is not limited to, one or more of the following: redeeming coupons and/or providing individual services including, but not limited to, one or more of the following: personalized beverages and/or accepting payment and/or tracking use and/or awarding prizes.

[0486] In some embodiments, power module **8000** may have some advantages over power module

7900. In some embodiments, power module **8000** may have three components (the power supply unit **8008**, power distribution control **8002**, and AC power switch **8010**) instead of the one-component configuration of power module **7900**. This may be referred to herein as the “three-component configuration”. In some embodiments, the three-component configuration may be smaller in size and therefore may more easily be accommodated into the housing assembly **850** than the one-component configuration. In various embodiments, the three-component configuration may be beneficial/desirable for many reasons, including, but not limited to, enabling easy field replacement as one component that may be in need of replacement may be replaced without also replacing the other two components. For example, in some embodiments, processing system **10** may be updated and/or replaced with a processing system having more or less power. In the preceding example, the power supply unit **8008** may be replaced without replacing the power distribution control **8002** or the AC power switch **8010**. Also, in some embodiments, the machine control processor **8004** and power distribution module **8006** may be separate components of the power distribution control **8002**. In some embodiments, the machine control processor **8004** and power distribution module **8006** being separate components may be beneficial/desirable for many reasons, including, but not limited to, to the ability to update the processing system **10** by replacing one without necessarily replacing one or more of the other components. For example, in some embodiments, it may be desirable to add additional processing power to the processing system **10**. Thus, in some embodiments, the machine control processor **8004** may be replaced without replacing the power distribution module **8006**.

[0487] In some embodiments, for example, the product dispensing system may be updated to include additional nozzles. Thus, in these embodiments, the power distribution module **8006** may be replaced without also replacing the machine control processor **8004**.

[0488] In some embodiments, the three-component configuration may contribute to reducing the overall cost of the processing system **10** based on increased design flexibility. For example, in some embodiments, separating the power supply unit **8008** from the product distribution control **8002** may allow for an “off the shelf” power supply (i.e. a commercial power supply sold in substantial quantities) to be used within the three-component configuration. In some embodiments, a power supply unit optimal for a power grid in a specific country may be used within the three-component configuration, therefore, contributing to modularity which may be beneficial for many reasons, including, but not limited to, changing out only the power supply unit to configure the processing system **10** for use with various power grids.

[0489] In some embodiments, the three-component configuration may allow the power supply unit **8008** to be placed in a location within the housing assembly **850** so as to expel an optimal amount of generated heat. Thus, in some embodiments, power supply unit **8008** may be placed in the rear of the housing assembly **850**.

[0490] In some embodiments, the three-component configuration may allow for the use of a first communication interface within the processing system **10** and a second communication interface between the power distribution control **8002** and the user interface module **8032**. For example, in some embodiments, the processing system **10** may run on a CAN bus interface, but the connection between the power distribution control **8002** and the user interface module **8032** may be an Ethernet communication interface.

[0491] In some embodiments, the connection between the power distribution control **8002** and the user interface module **8032** may be wireless. For example, in some embodiments, the connection between the power distribution control **8002** and the user interface module **8032** may be a wireless network or a BLUETOOTH connection (in various embodiments, other connection types may be used). In some embodiments, the different communication interfaces may allow for the user interface module **8032** to be fully customizable.

[0492] In some embodiments, the three-component configuration may allow for separation of the beverage selection function of the processing system **10** from the beverage delivery/distribution

control function of the processing system **10**. For example, in some embodiments, the beverage selection function of the processing system **10** may reside in the user interface module **8032**, and the beverage delivery/distribution control function of the processing system **10** could reside in the machine control processor **8004**.

[0493] Referring now also to FIG. **82**, a schematic of one embodiment of the power module **8000** connections to a variety of subsystems and devices within the processing system is shown. This is one embodiment and should not be construed as a limitation on the disclosure, as other configurations may be utilized. In some embodiments, one or more of the connections shown may be used, however, in other embodiments, all of the connections shown may be used. In some embodiments, the connections may vary and may not include the connections shown.

[0494] In some embodiments, the power module **8000** may be connected to a variety of subsystems and devices within the processing system via connections **8012**, **8014**, **8044**, **8046**, **8048**, **8050**, **8052**, **8054**, **8056**, **8058**, **8060**, **8062**, **8064**. In some embodiments, the power distribution control **8002** (“PDC”) may communicate with the flow control modules **8020**, the RFID devices **8022**, and the quad product modules **8024** via connections **8056**, **8054**, and **8052** respectively. In some embodiments, the power distribution control **8002** may send power to the flow control modules **8020**, the RFID devices **8022**, and the quad product modules **8024** and may send commands to and receive information from the flow control modules **8020**, the RFID devices **8022**, and the quad product modules **8024** via a communication interface.

[0495] In some embodiments, the power distribution control **8002** may communicate with a carbonation tank **8030** via connection **8050**. In some embodiments, the carbonation tank **8030** may communicate information to the power distribution control **8002** concerning the level of carbonated water in the carbonation tank **8030**. In some embodiments, the power distribution control **8002** may communicate with the user interface module **8032** via connection **8048**. In some embodiments, the power distribution control **8002** may send power to the user interface module **8032** and may receive commands from and send information to the user interface module **8032** via a communication interface. In some embodiments, the power distribution control **8002** may communicate with a lower door sensor **8038** via connection **8044**. In some embodiments, the lower door sensor **8038** may communicate information to the power distribution control **8002** concerning whether the lower door **854** of the housing assembly **850** is open or closed. In some embodiments, the power distribution control **8002** may communicate with a nozzle light **8040** via connection **8046**. In some embodiments, the power distribution control **8002** may send power to the nozzle light **8040** when the upper door **852** of the housing assembly **850** is open. In some embodiments, the power distribution control **8002** may send power to the nozzle light **8040** when the product dispensing system is dispensing a beverage.

[0496] In some embodiments, the power distribution control **8002** may communicate with a product agitation motor **8026** via connection **8058**. In some embodiments, the product agitation motor **8026** may be a DC motor. In some embodiments, the product agitation motor **8026** may be an AC motor. In some embodiments, the power distribution control **8002** may send power to the product agitation motor **8026** when an agitation mechanism needs to be activated. In some embodiments, the product agitation motor **8026** may communicate to the power distribution control **8002** information concerning the location of one or more product module assemblies (e.g., product module assemblies **250a**, **250b**, **250c**, **250d**) of one or more microingredient towers (e.g., microingredient towers **1050**, **1052**, **1054**) that are being agitated by the agitation mechanism. In some embodiments, the power distribution control **8002** may communicate to the product agitation motor **8026** information concerning when to stop agitating one or more product module assemblies (e.g., product module assemblies **250a**, **250b**, **250c**, **250d**) being agitated and the position to place the one or more product module assemblies (e.g., product module assemblies **250a**, **250b**, **250c**, **250d**) at rest. In some embodiments, the product agitation motor **8026** may communicate to the power distribution control **8002** information concerning the location of one or more product

module assemblies (e.g., product module assemblies **250d**, **250c**, **250f**) of one or more microingredient shelves (e.g., microingredient shelves **1200**, **1202**, **1204**) that are being agitated by the agitation mechanism. In some embodiments, the power distribution control **8002** may communicate to the product agitation motor **8026** information concerning when to stop agitating one or more product module assemblies (e.g., product module assemblies **250d**, **250c**, **250f**) being agitated and what position to place the one or more product module assemblies (e.g., product module assemblies **250d**, **250c**, **250f**) at rest.

[0497] In some embodiments, the power distribution control **8002** may communicate with an ice chute actuator **8028** via connection **8060**. In some embodiments, the power distribution control **8002** may send power to the ice chute actuator **8028** when the ice dispensing chute **1010** should open. In some embodiments, the power supply unit **8008** (“PSU”) may communicate with a carbonation pump motor **8034** via a connection **8062**. In some embodiments, the carbonation pump motor **8034** may be an AC motor. In some embodiments, the carbonation pump motor **8034** may be a DC motor. In some embodiments, the power distribution control **8002** may signal the power supply unit **8008** to send power to the carbonation pump motor **8034** when the carbonation pump motor **8034** needs to pump CO₂ and water into the carbonation tank **8030**. In some embodiments, the power supply unit **8008** may communicate with an ice agitation motor **8036** via connection **8064**. In some embodiments, the ice agitation motor **8036** may be an AC motor. In some embodiments, the ice agitation motor **8036** may be a DC motor.

[0498] In some embodiments, the power distribution control **8002** may signal the power supply unit **8008** to send power to the ice agitation motor **8036** to churn ice in the ice hopper **1008**. In some embodiments, the ice hopper **1008** may churn ice to dispense ice through the ice dispensing chute **1010**. In some embodiments, the ice hopper **1008** may churn ice to prevent the formation of an ice bridge on top of the cold plate **163**. For example, in some embodiments, the ice hopper **1008** may churn ice when a preset volume of fluid has travelled through the cold plate **163**. In some embodiments, the volume of fluid may be measured by the flow control modules **8020**. As another example, in some embodiments, the ice hopper **1008** may churn ice when a preset amount of time has passed since the ice hopper **1008** last churned ice.

[0499] Referring now also to FIGS. **82-83**, an embodiment of a schematic of a configuration of connections **8012**, **8014**, **8044**, **8046**, **8048**, **8050**, **8052**, **8054**, **8056**, **8058**, **8060**, **8062**, **8064** of the power module **8000** is shown. This is one embodiment and should not be construed as a limitation on the disclosure, as other configurations may be utilized. In some embodiments, one or more of the connections shown may be used, however, in other embodiments, all of the connections shown may be used. In some embodiments, the connections may vary and may not include the connections shown.

[0500] In some embodiments, connection **8012** may be DC power line **8012a** and CAN bus line **8012b**. In some embodiments, connection **8014** may be an AC power line. In some embodiments, connection **8044** may be an input line to the power distribution control **8002**. In some embodiments, connection **8046** may be a power drive line (a line that only sends power when necessary). In some embodiments, connection **8048** may be DC power line **8048a** and Ethernet line **8048b**. In some embodiments, connection **8050** may be an input line to the power distribution control **8002**. In some embodiments, connections **8052**, **8054**, and **8056** may be DC power lines **8052a**, **8054a**, **8056a** and CAN bus lines **8052b**, **8054b**, **8056b** respectively. In some embodiments, connection **8058** may be an input to the power distribution control line **8058a** and a power drive line **8058b**. In some embodiments, connections **8060**, **8062**, **8064** may be power drive lines.

[0501] As discussed above, other examples of such products producible by processing system **10** may include but are not limited to: dairy-based products (e.g., milkshakes, floats, malts, frappes); coffee-based products (e.g., coffee, cappuccino, espresso); soda-based products (e.g., floats, soda w/fruit juice); tea-based products (e.g., iced tea, sweet tea, hot tea); water-based products (e.g., spring water, flavored spring water, spring water w/vitamins, high-electrolyte drinks, high-

carbohydrate drinks); solid-based products (e.g., trail mix, granola-based products, mixed nuts, cereal products, mixed grain products); medicinal products (e.g., infusible medicants, injectable medicants, ingestible medicants); alcohol-based products (e.g., mixed drinks, wine spritzers, soda-based alcoholic drinks, water-based alcoholic drinks); industrial products (e.g., solvents, paints, lubricants, stains); and health/beauty aid products (e.g., shampoos, cosmetics, soaps, hair conditioners, skin treatments, topical ointments).

[0502] A number of implementations have been described. Nevertheless, it will be understood that various modifications may be made. Accordingly, other implementations are within the scope of the following claims.

[0503] While the principles of the invention have been described herein, it is to be understood by those skilled in the art that this description is made only by way of example and not as a limitation as to the scope of the invention. Other embodiments are contemplated within the scope of the present invention in addition to the exemplary embodiments shown and described herein.

Modifications and substitutions by one of ordinary skill in the art are considered to be within the scope of the present invention.

Claims

1. A product dispensing system comprising: a controller; a first flow control device configured to regulate a first medicinal ingredient; a first flow measurement device configured to provide a feedback signal based upon a volume of the first medicinal ingredient flowing within the first flow control device; a second flow control device configured to regulate a second medicinal ingredient; and a second flow measurement device configured to provide a feedback signal based upon a volume of the second medicinal ingredient flowing within the second flow control device, wherein said controller provides a first control signal to the first flow control device for controlling the supply of a quantity of the first medicinal ingredient based upon, at least in part, a predetermined recipe, wherein said controller provides a second control signal to the second flow control device for controlling the supply of a quantity of the second medicinal ingredient based upon, at least in part, the predetermined recipe.
 2. The product dispensing system of claim 1, wherein the first and second flow measuring devices are positive displacement flow measuring devices.
 3. The product dispensing system of claim 2, wherein the positive displacement flow measuring devices are gear-based positive displacement flow measuring devices.
 4. The product dispensing system of claim 1, further comprising: a pump module configured to releasably engage the supply of the first medicinal ingredient.
 5. The product dispensing system of claim 4, the pump module including a bracket assembly configured to releasably engage a plurality of supplies of the first medicinal ingredient.
 6. The product dispensing system of claim 4, wherein the pump module is a solenoid piston pump assembly configured to provide a calibratedly determined volume of the first medicinal ingredient.
 7. The product dispensing system of claim 1, further comprising: a pump module configured to releasably engage the supply of the second medicinal ingredient.
 8. The product dispensing system of claim 7, the pump module including a bracket assembly configured to releasably engage a plurality of supplies of the second medicinal ingredient.
 9. The product dispensing system of claim 7, wherein the pump module is a solenoid piston pump assembly configured to provide a calibratedly determined volume of the second medicinal ingredient.
-