

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250283418

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Warburg; Thomas P. et al.

TURBINE ENGINE WITH A BLADE ASSEMBLY HAVING A SET OF COOLING CONDUITS

Abstract

A gas turbine engine having a blade assembly with a platform, an airfoil, and a shank. The airfoil has a plurality of cooling conduits, and the shank has a plurality of inlet passages to provide cooling fluid to the cooling conduits in the airfoil. The cooling fluid is vented through a plurality of cooling holes along the airfoil. The blade assembly has specific geometries that improve durability.

Inventors: Warburg; Thomas P. (West Chester, OH), Noeth; Zachary R. (Loveland, OH), Fishback; Kelli Marie (Liberty Township, OH), Myers; Marie (Cincinnati, OH), Webster; Zachary Daniel (Cincinnati, OH), Whittington; Kurt Thomas (Maineville, OH), Gallier; Kirk D. (Liberty Township, OH), Buhler; Jared Peter (Lynn, MA)

Applicant: General Electric Company (Evendale, OH)

Family ID: 1000008618723

Appl. No.: 19/074060

Filed: March 07, 2025

Related U.S. Application Data

us-provisional-application US 63562542 20240307

Publication Classification

Int. Cl.: F01D5/18 (20060101)

U.S. Cl.:

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This patent claims the benefit of U.S. Provisional Patent Application No. 63/562,542, titled “TURBINE ENGINE WITH A BLADE ASSEMBLY HAVING A SET OF COOLING CONDUITS,” which was filed on Mar. 7, 2024. Priority to U.S. Provisional Patent Application No. 63/562,542 is hereby claimed.

TECHNICAL FIELD

[0002] The present subject matter relates generally to a blade assembly for a turbine engine, and more specifically to a turbine engine with a blade assembly having a set of cooling conduits.

BACKGROUND

[0003] A gas turbine engine typically includes a turbomachine, with a fan in some implementations. The turbomachine generally includes a compressor, combustor, and turbine in serial flow arrangement. The compressor compresses air which is channeled to the combustor where it is mixed with fuel. The mixture is then ignited to generate hot combustion gases. The combustion gases are channeled to the turbine, which extracts energy from the combustion gases for powering the compressor and fan, if used, as well as for producing useful work to propel an aircraft in flight or to power a load, such as an electrical generator.

[0004] During operation of the gas turbine engine, various systems generate a relatively large amount of heat and stress. For example, a substantial amount of heat or stress can be generated during operation of the thrust generating systems, lubrication systems, electric motors and/or generators, hydraulic systems or other systems. A design that mitigates heat loads and/or stresses on an engine component is advantageous.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] A full and enabling disclosure of the present disclosure, including the best mode thereof, directed to one of ordinary skill in the art, is set forth in the specification, which makes reference to the appended figures, in which:

[0006] FIG. 1 is a schematic cross-sectional view of a gas turbine engine, in accordance with an exemplary embodiment of the present disclosure.

[0007] FIG. 2 is a schematic cross-sectional view of a turbine section of the gas turbine engine of FIG. 1, in accordance with an exemplary embodiment of the present disclosure.

[0008] FIG. 3 is a perspective view of a blade assembly including a middle inlet passage for use in the gas turbine engine of FIG. 1, in accordance with an exemplary embodiment of the present disclosure.

[0009] FIG. 4 is a schematic used to calculate a stator rotor seal radius of the blade assembly of FIG. 3.

[0010] FIG. 5 is a side view of the blade assembly of FIG. 3 showing multiple planes, in accordance with an exemplary embodiment of the present disclosure.

[0011] FIG. 6 is a side schematic view of a cooling circuit of the blade assembly of FIG. 3.

[0012] FIG. 7 is a cross-sectional view of the blade assembly of FIG. 3 depicting the cooling circuit.

[0013] FIG. 8 is a cross-sectional view of a splitter of the cooling circuit of FIG. 6.

[0014] FIG. 9 is a schematic diagram illustrating the cross-sectional shape(s) of the cooling conduit portions of the middle inlet passage of FIG. 3 taken at a plurality of planes of FIG. 5.

[0015] FIG. 10 is a schematic used to calculate a degree of change along the suction side of the middle inlet passage of the blade assembly of FIG. 3.

DETAILED DESCRIPTION

[0016] Reference will now be made in detail to present embodiments of the disclosure, one or more examples of which are illustrated in the accompanying drawings. The detailed description uses numerical and letter designations to refer to features in the drawings. Like or similar designations in the drawings and description have been used to refer to like or similar parts of the disclosure.

[0017] Aspects of the disclosure generally relate to a blade assembly having conduits located within the blade assembly. Specifically, the blade assembly includes an airfoil with a plurality of cooling conduits and a shank with a plurality of inlet passages. The airfoil also includes cooling holes fluidly coupled to the plurality of cooling conduits within the airfoil.

[0018] The blade assembly may be a blade assembly in a turbine section of a gas turbine engine. For example, the blade assembly may be a stage one blade assembly of a high pressure turbine, which typically experiences the highest thermal and mechanical stresses.

[0019] The shank may be used to attach the blade assembly to a turbine disk. In some implementations the shank is formed as a dovetail received in the turbine disk. A platform of the blade assembly together with other circumferentially arranged platforms and seals of other blade assemblies define a substantially continuous annular ring that limits (e.g., prevents, reduces) hot gas leakage from the flow path into the turbine disk cavity. The airfoil extends radially from the platform, away from the turbine disk while the shank extends radially from the platform, toward the turbine disk.

[0020] High engine temperatures and operational forces impart relatively large thermal and mechanical stresses on the blade assemblies. In addition, the cooling conduits and the inlet passages in the blade assembly result in stress redistribution. For example, the size of the cooling conduits and the inlet passages affects the thickness of the airfoil wall and the shank wall, which affects stress distribution in the blade assembly. Relatively large stresses can contribute to an unexpected or premature part replacement. Therefore, there is a need for a blade assembly with greater durability to increase time on wing.

[0021] Connection references (e.g., attached, coupled, connected, and joined) are to be construed broadly and can include intermediate structural elements between a collection of elements and relative movement between elements unless otherwise indicated. As such, connection references do not necessarily infer those two elements are directly connected and in fixed relation to one another. The exemplary drawings are for purposes of illustration only and the dimensions, positions, order and relative sizes reflected in the drawings attached hereto can vary.

[0022] As used herein, a “stage” of either a compressor or a turbine of a gas turbine engine is a set of blade assemblies and an adjacent set of vane assemblies, with both sets of the blade assemblies and the vane assemblies circumferentially arranged about an engine centerline. A pair of circumferentially adjacent vanes in the set of vane assemblies are referred to as a nozzle. The blade assemblies rotate relative to the engine centerline. In one example, the blade assemblies are mounted to a rotating structure, such as a disk.

[0023] As used herein, the word “exemplary” means “serving as an example, instance, or illustration.” Any implementation described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other implementations. Additionally, unless specifically identified otherwise, all embodiments described herein should be considered exemplary.

[0024] As used herein, the terms “first”, “second”, “third”, and “fourth” can be used interchangeably to distinguish one component from another and are not intended to signify location

or importance of the individual components.

[0025] As used herein, a “set” or a set of elements can include any number of said elements, including one.

[0026] As used herein, the terms “forward” and “aft” refer to relative positions within a gas turbine engine and refer to the normal operational attitude or direction of travel of the gas turbine engine. For example, with regard to a gas turbine engine, forward refers to a position relatively closer to the nose of an aircraft and aft refers to a position relatively closer to a tail of the aircraft.

[0027] As used herein, the terms “upstream” and “downstream” refer to a location along a fluid flowpath with respect to a direction of fluid flow along the fluid flow path and reference location along the fluid flowpath.

[0028] As used herein, the term “fluid” refers to a gas or a liquid and “fluidly coupled” means a fluid can flow between the coupled regions.

[0029] As used herein, forms “a”, “an”, and “the” include plural references unless the context clearly dictates otherwise.

[0030] As used herein, a radial direction (denoted “R”) is a direction that is perpendicular to a base plane on a shank of a blade assembly.

[0031] As used herein, an axial direction (denoted “A”) is a direction that is perpendicular to a shank leading-edge plane on the shank of the blade assembly and perpendicular to the axial direction.

[0032] As used herein, a tangential direction (denoted “T”) is a direction that is perpendicular to the radial direction and the axial direction.

[0033] A stator rotor seal radius (denoted “SRSR”) is a radius of curvature of an upper edge of a stator rotor seal on a blade assembly.

[0034] The term redline exhaust gas temperature (referred to herein as “redline EGT”) refers to a maximum permitted takeoff temperature documented in a Federal Aviation Administration (“FAA”)-type certificate data sheet. For example, in certain exemplary embodiments, the term redline EGT may refer to a maximum permitted takeoff temperature of an airflow after a first stage stator downstream of an HP turbine of an engine that the engine is rated to withstand. The term redline EGT is sometimes also referred to as an indicated turbine exhaust gas temperature or indicated turbine temperature.

[0035] The term redline core speed (referred to herein as “redline CS”) refers to a maximum rotational speed of a gas turbine engine permitted at takeoff as documented in the FAA-type certificate data sheet. For example, the redline core speed CS is the rate at which the drive shaft for the gas turbine engine rotates, which defines the rotational speed of the particular blade assembly within the gas turbine engine.

[0036] As used herein “cooling conduit” refers to a flow path that conveys a cooling fluid that is formed in a blade assembly.

[0037] As used herein, a “cooling conduit portion” refers to a discrete portion of a cooling conduit at a cross-sectional plane of a blade assembly.

[0038] As used herein “inlet passage” refers to a cooling conduit formed in a shank of the blade assembly.

[0039] As used herein a “leading-edge inlet passage” refers to the inlet passage in the shank of the blade assembly that is adjacent to the leading edge of the blade assembly.

[0040] As used herein a “trailing-edge inlet passage” refers to the inlet passage in the shank of the blade assembly that is adjacent to the trailing edge of the blade assembly.

[0041] As used herein “a middle inlet passage” refers to an inlet passage that is between a leading-edge inlet passage and a trailing-edge inlet passage.

[0042] As used herein, “a base plane” of a blade assembly refers to the plane defined by the base of a shank of the blade assembly.

[0043] A number of cooling conduits fed by middle inlet passage (denoted “N.sub.1”) refers to the

number of distinct cooling conduits that are downstream of the middle inlet passage.

[0044] A number of cooling conduit portions spanning pressure surface to suction surface (denoted “N.sub.2”) refers to the number of cooling conduit portions that span from the pressure surface to the suction side of a blade assembly and are fed from the middle inlet passage of a blade assembly.

[0045] As used herein, the maximum normalized cooling conduit portion area (denoted “A.sub.max”) refers to the greatest normalized area of the cross-sectional areas of a set of cooling conduit portions of the middle inlet passage.

[0046] A degree of change of cooling conduit portions along a suction side of an airfoil of the blade assembly (denoted “DCCPASS”) refers to an angle measured between the lines along the suction side of cooling conduit portions of the middle inlet passage at two cross-sectional planes.

[0047] All measurements referred to herein are taken of the blade assembly prior to use or as a cold component.

[0048] Referring now to the drawings, FIG. 1 is a schematic view of a gas turbine engine 10. As a non-limiting example, the gas turbine engine 10 can be used on an aircraft. The gas turbine engine 10 includes an engine core extending along an engine centerline 20 and including, at least, a compressor section 12, a combustor 14, and a turbine section 16 in serial flow arrangement. In some examples, the gas turbine engine 10 includes a fan (not shown) that is driven by the engine core to provide thrust and provides air to the compressor section 12. The gas turbine engine 10 includes a drive shaft 18 that rotationally couples the fan, compressor section 12, and turbine section 16, such that rotation of one affects the rotation of the others, and defines a rotational axis along the engine centerline 20 for the gas turbine engine 10.

[0049] In the illustrated example, the compressor section 12 includes a low-pressure (LP) compressor 22 and a high-pressure (HP) compressor 24 serially fluidly coupled to one another. The turbine section 16 includes an HP turbine 26 and an LP turbine 28 serially fluidly coupled to one another. The drive shaft 18 operatively couples the LP compressor 22, the HP compressor 24, the HP turbine 26 and the LP turbine 28 to one another. In some implementations, the drive shaft 18 includes an LP spool (not illustrated) and an HP spool (not illustrated), where the LP spool couples the LP compressor 22 to the LP turbine 28, and the HP spool couples the HP compressor 24 to the HP turbine 26.

[0050] The compressor section 12 includes a plurality of axially spaced stages. Each stage includes a set of circumferentially-spaced rotating blade assemblies and a set of circumferentially-spaced stationary vane assemblies. In one configuration, the compressor blade assemblies for a stage of the compressor section 12 are mounted to a disk, which is mounted to the drive shaft 18. Each set of blade assemblies for a given stage can have its own disk. In one implementation, the vane assemblies of the compressor section 12 are mounted to a casing which extends circumferentially about the turbine engine 10. In a counter-rotating gas turbine engine, the vane assemblies are mounted to a drum, which is similar to the casing, except the drum rotates in a direction opposite the blade assemblies, whereas the casing is stationary. It will be appreciated that the representation of the compressor section 12 is merely schematic. The number of stages can vary.

[0051] Similar to the compressor section 12, the turbine section 16 includes a plurality of axially spaced stages, with each stage having a set of circumferentially-spaced, rotating blade assemblies and a set of circumferentially-spaced, stationary vane assemblies. In one configuration, the turbine blade assemblies for a stage of the turbine section 16 are mounted to a disk which is mounted to the drive shaft 18. Each set of blade assemblies for a given stage can have its own disk. In one implementation, the vane assemblies of the turbine section are mounted to the casing in a circumferential manner.

[0052] The combustor 14 is provided serially between the compressor section 12 and the turbine section 16. The combustor 14 is fluidly coupled to at least a portion of the compressor section 12 and the turbine section 16 such that the combustor 14 at least partially fluidly couples the compressor section 12 to the turbine section 16. As a non-limiting example, the combustor 14 is

fluidly coupled to the HP compressor **24** at an upstream end of the combustor **14** and to the HP turbine **26** at a downstream end of the combustor **14**.

[0053] During operation of the gas turbine engine **10**, ambient or atmospheric air is drawn into the compressor section **12** via the fan, upstream of the compressor section **12**, where the air is compressed defining a pressurized air. The pressurized air then flows into the combustor **14** where the pressurized air is mixed with fuel and ignited, thereby generating hot combustion gases. Some work is extracted from these combustion gases by the HP turbine **26**, which drives the HP compressor **24**. The combustion gases are discharged into the LP turbine **28**, which extracts additional work to drive the LP compressor **22**, and the exhaust gas is ultimately discharged from the gas turbine engine **10** via an exhaust section (not illustrated) downstream of the turbine section **16**. The driving of the LP turbine **28** drives the LP spool to rotate the fan and the LP compressor **22**. The pressurized airflow and the combustion gases together define a working airflow that flows through the fan, compressor section **12**, combustor **14**, and turbine section **16** of the gas turbine engine **10**.

[0054] Turning to FIG. **2**, a portion of the turbine section **16** is schematically illustrated. The turbine section **16** includes sets of blade assemblies **30** circumferentially mounted to corresponding disks **32**. The number of individual blade assemblies of the set of blade assemblies **30** mounted to each disk **32** may vary. While shown schematically in FIG. **2**, it should be understood that the turbine section **16** can be a single stage turbine, or can include additional stages as shown.

[0055] Stationary vane assemblies **34** are mounted to a stator ring **36** located distally exterior of each of the disks **32**. A nozzle **38** is defined by the space between circumferentially-adjacent pairs of vane assemblies **34**. The number of nozzles **38** provided on the stator ring **36** may vary.

[0056] During operation of the gas turbine engine **10**, a flow of hot gas or heated fluid flow (denoted “HF”) exits the combustor **14** and enters the turbine section **16**. The heated fluid flow HF is directed through the nozzles **38** and impinges on the blade assemblies **30**, which rotates the blade assemblies **30** circumferentially around the engine centerline **20** and cause rotation of the drive shaft **18**. The engine core is configured to generate a redline exhaust gas temperature (EGT) in a range of 988 degrees Celsius (° C.) to 1120° C.

[0057] FIG. **3** is a perspective view of a single blade assembly **30** for the gas turbine engine **10** (FIG. **1**). The blade assembly **30** may correspond to a stage one blade assembly of the HP turbine **26**. The blade assembly **30** includes a shank **40**, a platform **50**, and an airfoil **60** (also referred to as a blade or blade portion). The blade assembly **30** can be constructed as a single unitary part or component (e.g., a monolithic structure). In other examples, the shank **40**, the platform **50**, and/or the airfoil **60** can be constructed as separate parts or components that are coupled together to form the blade assembly **30**.

[0058] A directional reference system is illustrated in FIG. **3**. The shank **40** extends between a base **42** and the platform **50**. The base **42** of the shank **40** is a flat surface that defines a plane, referred to herein as the base plane (denoted “BP”). A radial direction (denoted “R”) of the blade assembly **30** is a direction that is perpendicular to the base plane BP. Further, the shank **40** extends between a shank leading-edge **44** and a shank trailing-edge **46**. The shank leading-edge **44** is a flat surface that defines a plane, referred to herein as the shank leading-edge plane (denoted “SLEP”). An axial direction (denoted “A”) of the blade assembly **30** is a direction that is perpendicular to the shank leading-edge plane SLEP. A tangential direction (denoted “T”) is a direction perpendicular to both the radial direction R and the axial direction A.

[0059] The shank **40** is configured, by way of non-limiting example as a dovetail **47**, to mount to the disk **32** (FIG. **2**) of the engine **10** in order to rotatably drive the blade assembly **30**. The shank **40** includes a plurality of inlet passages **48** (shown in dashed lines) for receiving a cooling fluid (denoted “CF”) (e.g., bleed air) to cool the blade assembly **30**. In the illustrated example, the plurality of inlet passages **48** includes a leading-edge inlet passage **48l**, a middle inlet passage **48m**, and a trailing-edge inlet passage **48t**. Each of the inlet passages **48l**, **48m**, **48t** extends between the

base **42** and one or more cooling conduits in the airfoil **60**, disclosed in further detail herein. The inlet passages **48l**, **48m**, **48t** receive the cooling fluid CF at the base **42**. The cooling fluid CF flows through the inlet passages **48l**, **48m**, **48t** and into the one or more cooling conduits in the airfoil **60**. While in this example there are three inlet passages, in other examples, the shank **40** can include more or fewer inlet passages.

[0060] The airfoil **60** extends radially outward from the platform **50** to define a root **61**, connected to the platform **50**, and a tip **62** opposite the root **61**. Additionally, the airfoil **60** includes an outer wall **63** defining an exterior surface **59** defining a pressure side **64** and a suction side **65** opposite the pressure side **64**. The airfoil **60** extends between an airfoil leading-edge **66** and an airfoil trailing-edge **67** downstream from the airfoil leading-edge **66**. The airfoil leading-edge **66** and the airfoil trailing-edge **67** separate the pressure side **64** from the suction side **65**. In the illustrated example, the blade assembly **30** has a plurality of cooling conduits **70** (shown in dashed lines) formed within the airfoil **60**. Further, the blade assembly **30** has one or more cooling holes **69** formed in the outer wall **63** of the airfoil **60** to fluidly couple the plurality of cooling conduits **70** within the airfoil **60** to an exterior of the blade assembly **30**. In the illustrated example, the cooling holes **69** are near the airfoil trailing-edge **67** along the pressure side **64**. In other examples, the cooling holes **69** can be disposed in other locations. The plurality of cooling conduits **70** can include multiple conduits that extend radially through the airfoil **60**. In some examples, one or more of the cooling conduits **70** are fluidly coupled to certain ones of the inlet passages **48l**, **48m**, **48t**.

[0061] The platform **50** has a first surface **51**, referred to as an upper surface, and a second surface **52**, referred to as a lower surface, opposite the upper surface **51**. The airfoil **60** is coupled to and extends radially outward from the upper surface **51**, and the shank **40** is coupled to and extends radially inward from the lower surface **52**. The platform **50** extends between a platform leading-edge **53** and a platform trailing-edge **54**, opposite the platform leading-edge **53**, in the axial A direction. The platform **50** further extends between a first slashface **55** and a second slashface **56**, opposite the first slashface **55**, in the tangential T direction. When assembled, consecutive blade assemblies **30** are arranged in a circumferential direction about the engine centerline **20** (FIG. 1) with sequential slashfaces **55**, **56** facing each other.

[0062] During operation of the gas turbine engine **10**, the heated fluid flow HF flows along the blade assembly **30**. The airfoil leading-edge **66** is defined by a stagnation point with respect to the heated fluid flow HF. The heated fluid flow HF flows generally in the axial direction, from forward to aft, while the local directionality can vary as the heated fluid flow HF is driven or turned within the gas turbine engine **10**. The cooling fluid flow CF is fed to the plurality of inlet passages **48** and flows into the plurality of cooling conduits **70** to cool the airfoil **60**. The cooling fluid flow CF is provided throughout the airfoil **60** and exhausted from the plurality of cooling conduits **70** via the cooling holes **69** as a cooling film. Multiple blade assemblies **30** are arranged circumferentially such that the platforms **50** of the blade assemblies **30** form a continuous ring. The platform **50** helps to radially contain the heated fluid flow HF to protect the disk **32**. The platform **50** acts to seal the space radially inward of the platform **50** between the flow path of the heated fluid flow H and the disk **32** (FIG. 2). The disk **32** requires significant cooling to ensure the durability of the HP turbine **26** components.

[0063] Materials used to form the blade assembly **30** include, but are not limited to, steel, refractory metals such as titanium, or superalloys based on nickel, cobalt, or iron, ceramic matrix composites, or combinations thereof. The structures can be formed by a variety of methods, including additive manufacturing, casting, electroforming, or direct metal laser melting, in non-limiting examples.

[0064] As shown in FIG. 3, the platform **50** has a stator rotor seal **57** that extends axially forward from the platform leading-edge **53**. The stator rotor seal **57** facilitates sealing of a forward buffer cavity (not shown) defined within the rotor assembly. The stator rotor seal **57** has an upper surface

79, a lower surface **81** opposite the upper surface **79**, and a forward surface **82** between the upper surface **79** and the lower surface **81**. The stator rotor seal **57** has an upper edge **83** between the upper surface **79** and the forward surface **82**. The upper edge **83** is curved or arc-shaped. In particular, the upper edge **83** is curved between a first end point **84** at the first slashface **55** and a second end point **85** at the second slashface **56**. The upper edge **83** of stator rotor seal **57** has a center point **86** that forms the peak of the arc. The upper edge **83** of the stator rotor seal **57** has a radius of curvature, referred to herein as a stator rotor seal radius (denoted “SRSR”). The center of the radius of curvature mis the engine centerline **20** (FIG. 1).

[0065] As shown in FIG. 4, the SRSR (i.e., the radius of curvature of the upper edge **83** of the stator rotor seal **57**) can be calculated using the straight-line distance(S) between the two the end points **84**, **85**, and the maximum deflection (D), in the radial R direction, between the two end points **84**, **85** and the center point **86** of the arc. The SRSR can be calculated using $SRSR=(D/2)+(S.\sup.2/(8\times D))$.

[0066] FIG. 5 is a side view of the blade assembly **30**. As disclosed above, the base plane BP is a plane defined by the base **42** and is perpendicular to the radial direction R. A first plane (denoted “P1”) is parallel to the base plane BP and is located at a first radial distance (denoted “R1”) from the base plane BP. A second plane (denoted “P2”) is parallel to the base plane BP and is located at a second radial distance (denoted “R2”) from the base plane BP. A third plane (denoted “P3”) is parallel to the base plane BP and is located at a third radial distance (denoted “R3”) from the base plane BP. A fourth plane (denoted “P4”) is parallel to the base plane BP and is located at a fourth radial distance (denoted “R4”) from the base plane. A fifth plane (denoted “P5”) is parallel to the base plane BP and is located at a fifth radial distance (denoted “R5”) from the base plane. A sixth plane (denoted “P6”) is parallel to the base plane BP and is located at a sixth radial distance (denoted “R6”) from the base plane.

[0067] Each of the planes P1, P2, P3, P4, P5, P6 extend perpendicular to the radial direction R. The first radial distance R1 is less than the second radial distance R2, which is less than the third radial distance R3, which is less than the fourth radial distance R4, which is less than fifth radial distance, which is less than the sixth radial distance: $R1<R2<R3<R4<R5<R6$. Table 1 includes the radial distances, R1, R2, R3, R4, R5, R6 of the planes, P1, P2, P3, P4, P5, P6 from the base plane, BP.

TABLE-US-00001

Plane	Radial Distance from Base Plane
P1	R1 0.0167 meters
P2	R2 0.0197 meters
P3	R3 0.0215 meters
P4	R4 0.0234 meters
P5	R5 0.0245 meters
P6	R6 0.0449 meters

The first plane P1, the second plane P2, the third plane P3, the fourth plane P4, and the fifth plane P5 extend through the shank **40**. The sixth plane P6 extends through the airfoil **60**. The platform **50**, the root **61**, the tip **62**, the airfoil leading-edge **66**, and the airfoil trailing edge **67** are labeled in FIG. 5.

[0068] FIG. 6 is a schematic side view of a cooling circuit **90** of the blade assembly **30** of FIGS. 3-5. The cooling circuit **90** includes the leading inlet passages **48l**, the middle inlet passage **48m**, and the aft inlet passage **48t** of FIG. 3. In FIG. 6, the inlet passages **48l**, **48m**, **48t** continue to the cooling conduits **70** of FIG. 3. In FIG. 6, the middle inlet passage **48m** leads to a middle conduit **92** of the cooling conduits **70**. It should be appreciated that the leading inlet passages **48l** and the aft inlet passage **48t** also lead to cooling conduits of the cooling conduit **70**, which are not illustrated in FIG. 6 to avoid obscuring the middle conduit **92**. In FIG. 6, the planes P1, P2, P3, P4, P5, P6 of FIG. 5 are labeled.

[0069] In FIG. 6, the middle inlet passage **48m** includes a splitter section **100**. The middle conduit **92** includes a forward serpentine cooling conduit **102** and an aft serpentine cooling conduit **104**, which branches off from the middle inlet passage **48m** at the splitter section **100**. The cooling flow (CF) flows through the middle inlet passage **48m** is divided at the splitter section **100** into a first flow F1 through the forward serpentine cooling conduit **102** and a second flow F2 flows through the aft serpentine cooling conduit **104**.

[0070] The forward serpentine cooling conduit **102** includes a first forward section **110** defined from the splitter section **100** to a first forward bend **112**, a second forward section **114** defined from the first forward bend **112** to a second forward bend **116**, and a third forward section **118** defined from the second forward bend **116** to a forward end **120**. The aft serpentine cooling conduit **104** includes a first aft section **130** defined from the splitter section **100** to a first aft bend **132**, a second aft section **134** defined from the first aft bend **132** to a second aft bend **136**, and a third aft section **138** defined from the second aft bend **136** to an aft end **140**. The quantity (i.e., number) of conduits fed by the middle inlet passage **48m** (denoted “N.sub.1”) refers to the number of distinct cooling conduits that are downstream of the middle inlet passage **48m**. In FIG. 6, the middle inlet passage **48m** feeds two distinct cooling conduits, namely the forward serpentine cooling conduit **102** and the aft serpentine cooling conduit **104**.

[0071] FIG. 7 is a cross-sectional view of the airfoil **60** of the blade assembly **34** along P6 of FIG. 5. In FIG. 7, the pressure side **64**, the suction side **65**, the airfoil leading edge **66**, and the airfoil trailing edge **67** of the airfoil **60** are labeled. In FIG. 7, the sections **110**, **114**, **118** of the forward serpentine cooling conduit **102** of FIG. 6 and the sections **130**, **134**, **138** of the aft serpentine cooling conduit **104** of FIG. 5 are labeled. In FIG. 7, the sections **110**, **114**, **118** are adjacent to the suction side **65** and offset from the pressure side **64**. In FIG. 7, the sections **130**, **134**, **138** are adjacent to the pressure side **64** and the suction side **65**. In FIG. 7, portions of the cross-section of the airfoil **60** include dashed sections. In some examples, some or all of the areas of the dashed sections include other conduits of the cooling circuit **90**, such as cooling conduits extending from the leading inlet passages **48l** and/or the aft inlet passage **48t**.

[0072] In FIG. 7, the sections **130**, **134**, **138** of the aft section have a first cooling conduit portion **142**, a second cooling conduit portion **144**, and a third cooling conduit portion **146**, respectively. As used herein, the quantity (e.g., number) of cooling conduit portions spanning from the pressure surface **64** to the suction surface **65** (denoted “N.sub.2”) refers to the number of cooling conduit portions fed from the middle inlet passage that span at least 60% of the thickness of the airfoil measured perpendicular to the camber line of the airfoil **60** and from the geometric center of the respective cooling conduit portion. In FIG. 7, the blade assembly **34** includes three cooling conduit portions that span from the pressure surface **64** to the suction surface **65**, namely the cooling conduit portions **142**, **144**, **146**.

[0073] FIG. 8 is a cross-sectional view of the blade assembly **30** at the splitter section **100** of FIG. 6 at P6 of FIG. 6. In FIG. 8, the first section **110** of the forward serpentine cooling conduit **102** and the first section **130** of the aft serpentine cooling conduit **104**. At P6, the first section **110** of the forward serpentine cooling conduit **102** has a first cross-sectional area **147A** and a first major axis **148A**. At P6, the first section **130** of the aft serpentine cooling conduit **104** has a second cross-sectional area **147B** and a second major axis **148B**. In FIG. 8, the major axes **148A**, **148B** form a general L-shape (e.g., a boomerang shape). In FIG. 8, the first cross-sectional area **147A** is less than the second cross-sectional area **147B**.

[0074] FIG. 9 is a schematic diagram illustrating the cross-sectional shape of the middle inlet passage **48m** taken at P1, P2, P3, P4, and P5 of FIG. 5. In FIG. 9, the first middle inlet passage **48m** defines a first cooling conduit portion **150** at P1, a second cooling conduit portion **152** at P2, a third cooling conduit portion **154** at P3, a fourth cooling conduit portion **156** at P4, and a fifth cooling conduit portion **158** at P5. The first cooling conduit portion **150** has a first cross-sectional area **162**, the second cooling conduit portion **152** has a second cross-sectional area **164**, the third cooling conduit portion **154** has a third cross-sectional area **166**, the fourth cooling conduit portion **156** has a fourth cross-sectional area **168**, and the fifth cooling conduit portion **158** has a fifth cross-sectional area **170**. As used herein, the maximum normalized cooling conduit portion area (denoted “A.sub.max”) refers to the greatest area of the cross-sectional area **164**, **166**, **168**, **170** normalized by the first cross-sectional area **162**. The A.sub.max can be calculated by the following equation:

$$[00001] A_{\max} = \max \left\{ \frac{A_i}{A_1} \right\}_{i=2}^5$$

where A.sub.1 is the first cross-sectional area **162**, A.sub.2 is the second cross-sectional area **164**, A.sub.3 is the third cross-sectional area **166**, A.sub.4 is the fourth cross-sectional area **168**, and A.sub.5 is the fifth cross-sectional area **170**.

[0075] FIG. **10** is a schematic used to calculate the degree of change along the suction side **176** (denoted “DCCPASS”) of the middle inlet passage **48m** of the blade assembly **34** of FIG. **3**. The DCCPASS **176** is determined between the first cooling conduit portion **150** and the fifth cooling conduit portion **158**. To determine the DCCPASS **176**, a first line **172** and a second line **174** are marked on the first cooling conduit portion **150** and the fifth cooling conduit portion **158**, respectively. The first line **172** is defined between a first point **178A** and a second point **178B**. To determine the location of the points **178A**, **178B**, a first bounding circle **180** is drawn around the perimeter of the first cooling conduit portion **150**. The first bounding circle **180** is the smallest circle that fully bounds the first cooling conduit portion **150**. The first point **178A** is the point on the perimeter of the first cooling conduit portion **150** that is spaced 15 degrees from a line extending from a center of the first bounding circle **180** toward the suction side **65** (e.g., the 12:30 o'clock position on the first bounding circle **180**, etc.). The second point **178B** is the point on the perimeter of the first cooling conduit portion **150** that is spaced 45 degrees from a line extending from a center of the first bounding circle **180** toward the suction side **65** (e.g., the 1:30 o'clock position on the first bounding circle **180**, etc.).

[0076] The second line **174** is defined between a third point **184A** and a fourth point **184B**. To determine the location of the points **184A**, **184B**, a second bounding circle **186** is drawn around the perimeter of the fifth cooling conduit portion **158**. The second bounding circle **186** is the smallest circle that fully bounds the fifth cooling conduit portion **158**. The third point **184A** is the point on the perimeter of the first cooling conduit portion **150** that is spaced 15 degrees from a line extending from a center of the second bounding circle **186** toward the suction side **65** (e.g., the 12:30 o'clock position on the second bounding circle **186**, etc.). The fourth point **184B** is the point on the perimeter of the fifth cooling conduit portion **158** that is spaced 45 degrees from a line extending from a center of the second bounding circle **186** toward the suction side **65** (e.g., the 1:30 o'clock position on the second bounding circle **186**, etc.). The DCCPASS **176** is the angle formed between the first line **172** and the second line **174**.

[0077] The blade assemblies **30** of the HP turbine **26** and, specifically, the stage one blade assemblies **30** of the HP turbine **26** have the highest flow path temperature of any blade set. These stage one blade assemblies also rotate at extremely high angular velocities. The extreme temperature environment and the high rotational speeds impart large forces on the stage one blade assemblies **30** that can lead to creep and fatigue, especially along the suction side of the airfoil. Creep and fatigue may result in an unexpected or premature part replacement that limits engine Time on Wing (TOW). Therefore, there is a need for a blade assembly with high durability that can withstand these large centrifugal stresses and reduce (e.g., minimize) creep and fatigue.

[0078] The inventors created blade assemblies with relatively high durability (e.g., creep and fatigue resistance) for a defined engine operating environment characterized by the redline EGT and the redline CS. The inventors developed multiple blade assemblies and determined that it is beneficial to vary the geometry of the middle inlet passage **48m**. Further geometry changes to the inlet passage enable control regarding an amount of cooling fluid provided to the cooling conduits. The blade assemblies disclosed herein include cooling conduits and inlet passages that are sized specifically to ensure adequate cooling capabilities while also improving creep and fatigue resistance. The inventors determined that the sizing and shape of the middle inlet passage **48m** were a significant cause for creep and fatigue in the airfoil **60**. More specifically, the shape and size of the middle inlet passage **48m**, such as the DCCPASS **176**, the maximum normalized area of the cooling conduit portions **150**, **152**, **154**, **156**, **158** for a specific set of operating characteristics.

[0079] The inventors determined that the degree of change along the suction side DCCPASS 176, the maximum normalized area A.sub.max, the number of have a significant effect on durability, the number of cooling conduits fed by middle inlet passage N.sub.1, and the number of cooling conduit portions spanning pressure surface to suction surface N.sub.2 provide values that contribute to a relationship associated with improved creep and fatigue resistance for the blade assembly 30.

[0080] Table 2 below illustrates fourteen examples (denoted Ex. 1-14) of blade assemblies 30 developed by the inventors. As stated above, the inventors created solutions (examples 1-10 of Table 2) with relatively high blade durability (e.g., reduced creep and fatigue, absence of crack formation or propagation after a number of engine cycles) for a defined engine environment when compared to solutions without such high blade durability (examples 11-14 of Table 2) Table 2 includes the degree of change of cooling conduit portions along the suction side DCCPASS values of FIG. 10, stator rotor seal radius SRSR values of FIG. 4, the number of cooling conduit portions fed by the middle inlet passage 48m N.sub.1 of FIG. 6, and the number of cooling conduit portions fed spanning pressure surface to suction surface N.sub.2 of FIG. 7 for each of the examples.

TABLE-US-00002 TABLE 2 Parameter DCCPASS SRSR N.sub.1 N.sub.2 Units Degrees (°)
Meters (m) — — Ex. 1 21.00 0.224 2 3 Ex. 2 33.00 0.239 2 3 Ex. 3 26.84 0.232 2 3 Ex. 4 24.60
0.237 2 3 Ex. 5 32.94 0.235 2 3 Ex. 6 22.64 0.236 2 3 Ex. 7 22.90 0.225 2 3 Ex. 8 32.81 0.225 2 3
Ex. 9 27.71 0.237 2 3 Ex. 10 25.72 0.236 2 3 Ex. 11 12.20 0.235 2 2 Ex. 12 9.70 0.236 2 2 Ex. 13
13.70 0.225 2 2 Ex. 14 8.70 0.237 2 2

[0081] The inventors found that blade assembly designs with parameters defined in Examples 1-10 exhibit relatively high structural integrity and durability while remaining within current engine constraints. Conversely, Examples 11-14 have relatively low durability for the particular engine environment.

[0082] The examples developed by the inventors shown in Table 2 can be characterized by an Expression (EQ) that can be used to distinguish those designs in Examples 1-10 that meet the performance (durability) requirements from those designs in Examples 11-14 that do not meet the performance requirements. As such, the Expression (EQ) can be used to identify an improved blade assembly design, better suited for a particular engine operating environment and taking into account the constraints imposed on blade assembly design with cooling holes used in such a system.

[0083] The Expression (EQ) is defined as:

$$[00002]EQ = 0.19 * \left(\frac{DCCPASS(^{\circ})}{2^{\circ}}\right)^2 * \left(\frac{N_2}{8}\right)^3 * \left(\frac{SRSR(m)}{1m}\right) * \left(\frac{N_1}{0.1}\right),$$

in which DCCPASS refers to the degree of change along the suction side of the middle inlet passage 48m. SRSR refers to the stator rotor seal radius of the blade assembly 30. N.sub.1 refers to the number of cooling conduits fed by the middle inlet passage 48m of the blade assembly 30.

N.sub.2 refers to the number of cooling conduit portions fed by the middle inlet passage spanning from the pressure side to the suction side. Values for the Expression (EQ) for each of the examples of Table 2 are shown in Table 3.

TABLE-US-00003 TABLE 3 Parameter DCCPASS SRSR N.sub.1 N.sub.2 EQ Units Degrees (°)
Meters (m) — — — Ex. 1 21.00 0.224 2 3 4.949 Ex. 2 33.00 0.239 2 3 13.039 Ex. 3 26.84 0.232 2
3 8.373 Ex. 4 24.60 0.237 2 3 7.185 Ex. 5 32.94 0.235 2 3 12.774 Ex. 6 22.64 0.236 2 3 6.047 Ex.
7 22.90 0.225 2 3 5.911 Ex. 8 32.81 0.225 2 3 12.134 Ex. 9 27.71 0.237 2 3 9.118 Ex. 10 25.72
0.236 2 3 7.821 Ex. 11 12.20 0.235 2 2 0.519 Ex. 12 9.70 0.236 2 2 0.329 Ex. 13 13.70 0.225 2 2
0.627 Ex. 14 8.70 0.237 2 2 0.266

[0084] Based on the Expression (EQ) values of Examples 1-10 in Table 2, it was determined that blade assembly designs with an EQ value in the range of 4.949 to 13.039 (i.e., $4.949 \leq EQ \leq 13.039$) advantageously meet the durability requirements while remaining within desired tolerances and being capable of use in existing engine systems.

[0085] Benefits are realized when the manufactured component including the blade assembly 30 has a geometry where Expression (EQ) falls within the range 4.949 to 13.039 (i.e.,

4.949≤EQ≤13.039). Such benefits include a reduction in stress in the airfoil and shank and an improvement in blade cooling, which increases the lifetime of the blade assembly **30** and therefore extends the time between a need for replacement parts. This provides for increased durability for the blade assembly **30**, which decreases required maintenance and costs, while increasing overall engine reliability.

[0086] Further still, the benefits included herein provide for a blade assembly **30** that fits within existing engines. For example, the values for Expression (EQ) as provided herein take existing engines into consideration, permitting replacement of current blade assemblies with replacement blade assemblies (or new blade assemblies) having the parameters of the blade assembly **30** described herein. Such consideration provides for replacing and improving current engine systems without requiring the creation of new engine parts capable of holding the blade assembly **30**. This provides for improving current engine durability without increasing costs to prepare new engines or further adapt existing engines.

[0087] Table 4 below illustrates minimum and maximum values for the degree of change of cooling conduit portions along suction side DCCPASS, the number of cooling conduits fed by middle inlet passage **48m** N.sub.1, the number of cooling conduit portions fed by the middle inlet passage spanning from the pressure side to the suction side N.sub.2, and the stator rotor seal radius SRSR along with a range of values for Expression (EQ) suited for a blade assembly that meets the durability requirements.

TABLE-US-00004	TABLE 4	Parameter:	Element:	Minimum:	Maximum:	Units:	DCCPASS	Degree
		of Change	Along Suction	21.0	33.0	Degrees	Side (°)	N.sub.1
		No. of Cooling	Conduits Fed by	3	3			
		— Mid Circuit	N.sub.2	No. of Cooling	Conduit Portions	2	2	— Spanning
								Pressure Surface to
								Suction Surface
		SRSR	Stator Rotor Seal	Radius	0.224	0.239	Meters (m)	EQ
								Expression
								4.949
								13.039
								n/a

[0088] Additional benefits associated with the blade assembly **30** with the stator rotor seal **57** and the middle inlet passage **48m** described herein include a quick assessment of design parameters in terms of blade assembly size and cooling conduit geometry, engine operational conditions, and blade and vane assembly numbers for engine design and particular blade design. Narrowing these multiple factors to a region of possibilities saves time, money, and resources. The blade assembly **30** with the stator rotor seal **57** and the middle inlet passage **48m** described herein enables the development and production of high-performance turbine engines and blade assemblies across multiple performance metrics within a given set of constraints.

[0089] As noted above, designs such as Examples 11-14 of Tables 2 and 3 were found to have relatively low durability for a particular engine environment. This is reflected in the associated Expression (EQ) value outside the range of 4.949 to 13.039. Lower durability results in less time on wing (TOW) and greater maintenance costs.

[0090] Additionally or alternatively, designs outside the range of EQ may attempt to increase durability by making sacrifices in terms of weight, aerodynamic performance, and efficiency. For example, the standard practice for solving the problem of improving blade assembly durability has been to utilize stronger material. However, such materials lead to increased costs, system weight, and overall space occupied by the blade assembly. With a material-driven solution, the overall engine efficiency may be reduced and related components may have to be redesigned to compensate for the stronger materials. In some cases, this result of such a redesign is impractical or impossible. Therefore, a solution for reducing stresses located in airfoils presently used in existing engines is needed, without requiring redesign of related components or without sacrificing overall engine efficiency.

[0091] In other examples, increasing size of the airfoil or related components, utilizing stronger material, and/or providing additional cooling features can combat centrifugal and thermal stresses. However, such increased size, stronger materials, and additional cooling features can lead to increased costs, system weight, overall space occupied by the blade assembly, and performance

loss, as well as increased local stresses at the cooling conduits due to increased weight and size relating to the centrifugal forces. Increased cooling features results in a relatively less amount of material utilized, which can result in an increase in local stresses at the cooling conduits. Therefore, a solution for reducing stress at the cooling conduits is needed without otherwise increasing stress(es), weight, size, or decreasing engine efficiency.

[0092] As disclosed above, the inventors have found that the examples 1-10 of Tables 2 and 3 provide successful solutions without the need to increase thickness, weight, strength, or the number of cooling features. Examples 1-10 of Tables 2 and 3 illustrate that designs having an Expression (EQ) value from 4.949 to 13.039. (i.e., $4.949 \leq EQ \leq 13.039$) achieve increased durability without penalties to size, weight, strength, or stress. In other words, rather than making areas of the airfoil thicker, or using heavier, stronger materials, or adding additional cooling features, effective stress reduction can be achieved by the examples 1-10 of Tables 2 and 3.

[0093] As disclosed above, the inventors created blade assemblies with relatively high durability (e.g., creep and fatigue resistance) for a defined engine operating environment.

[0094] To the extent one or more structures provided herein can be known in the art, it should be appreciated that the present disclosure can include combinations of structures not previously known to combine, at least for reasons based in part on conflicting benefits versus losses, desired modes of operation, or other forms of teaching away in the art.

[0095] This written description uses examples to disclose the present disclosure, including the best mode, and also to enable any person skilled in the art to practice the disclosure, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the disclosure is defined by the claims, and can include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they include structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

[0096] Further aspects of the disclosure are provided by the subject matter of the following clauses:

[0097] A blade assembly for a gas turbine engine, the blade assembly comprising a platform having an upper surface and a lower surface, the platform having a stator rotor seal with an upper edge having a radius of curvature defined as a stator rotor seal radius (SRSR), wherein the stator rotor seal radius (SRSR) is 0.224 meters to 0.239 meters, an airfoil extending from the upper surface of the platform, the airfoil having an exterior surface, the exterior surface defining a pressure side and a suction side, the airfoil including a leading-edge and a trailing-edge, a shank coupled to the lower surface, the shank having a base defining a base plane, and a middle inlet passage located within the shank, the middle inlet passage having a first cooling conduit portion at a first plane radially spaced 0.0167 meters from the base plane, the first cooling conduit portion having a first cross-sectional area, the first cooling portion defining a first bounding circle, the first cooling portion having a first point at a first 12:30 o'clock position on the first bounding circle, and a second point at a first 1:30 o'clock position on the first bounding circle, the first point and the second point defining a first line, a second cooling conduit portion at a second plane radially spaced 0.0197 meters from the base plane, the second cooling conduit portion having a second cross-sectional area, a third cooling conduit portion at a third plane radially spaced 0.0215 meters from the base plane, the third cooling conduit portion having a third cross-sectional area, a fourth cooling conduit portion at a fourth plane radially spaced 0.0234 meters from the base plane, the fourth cooling conduit portion having a fourth cross-sectional area, a fifth cooling conduit portion at a fifth plane radially spaced 0.0245 meters from the base plane, the fifth cooling conduit portion having a fifth cross-sectional area, the second cooling portion defining a second bounding circle, the second cooling portion having a third point at a second 12:30 o'clock position on the second bounding circle; and a fourth point at a third 1:30 o'clock position on the second bounding circle, the third point and the fourth point defining a second line wherein the middle inlet passage defines a

maximum normalized cooling conduit portion area (A.sub.max) ranging between 1.30 and 2.10, A.sub.max defined by:

$$[00003] A_{\max} = \max \left\{ \frac{A_i}{A_1} \right\}_{i=2}^5$$

wherein the first line and the second line define a degree of change of the cooling conduit portions along the suction side (DCCPASS) ranging between 21.0 and 33.0 degrees (°), and a plurality of cooling conduits located within the airfoil, the plurality of cooling conduits including a first quantity (N.sub.1) of cooling conduits fed by the middle inlet passage, wherein the first quantity is 2, wherein the plurality of cooling conduits define a second quantity (N.sub.2) of cooling conduit portions spanning between the suction side and the pressure side, wherein the second quantity is 3, and wherein:

$$[00004] 4.949 \leq 0.19 * \left(\frac{DCCPASS(^{\circ})}{2^{\circ}} \right)^2 * \left(\frac{N_2}{8} \right)^3 * \left(\frac{SRSR(m)}{1m} \right) * \left(\frac{N_1}{01} \right) \leq 13.039.$$

[0098] The blade assembly of any preceding clause, further including a plurality of inlet passages located within the shank, the plurality of inlet passages including the middle inlet passage.

[0099] The blade assembly of any preceding clause, wherein each of the inlet passages extends between the base and one or more of the plurality of cooling conduits.

[0100] The blade assembly of any preceding clause, wherein the plurality of inlet passages further includes a leading-edge inlet passage and a trailing-edge inlet passage.

[0101] The blade assembly of any preceding clause, wherein the shank is configured as a dovetail.

[0102] The blade assembly of any preceding clause, wherein the blade assembly is a stage one blade assembly of a high pressure turbine of the gas turbine engine.

[0103] The blade assembly of any preceding clause, wherein the quantity (N.sub.1) of cooling conduits fed by the middle inlet passage includes a forward serpentine cooling conduit in the airfoil, and an aft serpentine cooling conduit in the airfoil.

[0104] The blade assembly of any preceding clause, wherein the middle inlet passage is fluidly coupled to the forward serpentine cooling conduit and the aft serpentine cooling conduit at a splitter, the splitter including a first cooling conduit portion at a sixth plane radially spaced 0.449 meters from the base plane, the first cooling conduit portion associated with the forward serpentine cooling conduit, the first cooling conduit portion having a first major axis, and a second cooling conduit portion at the sixth plane, the second cooling conduit portion associated with the aft serpentine cooling conduit, the second cooling conduit portion having a second major axis, wherein the first major axis and the second major axis define an L-shape.

[0105] The following claims are hereby incorporated into this Detailed Description by this reference, with each claim standing on its own as a separate embodiment of the present disclosure.

Claims

1. A blade assembly for a gas turbine engine, the blade assembly comprising: a platform having an upper surface and a lower surface, the platform having a stator rotor seal with an upper edge having a radius of curvature defined as a stator rotor seal radius (SRSR), wherein the stator rotor seal radius (SRSR) is 0.224 meters to 0.239 meters; an airfoil extending from the upper surface of the platform, the airfoil having an exterior surface, the exterior surface defining a pressure side and a suction side, the airfoil including a leading-edge and a trailing-edge; a shank coupled to the lower surface, the shank having a base defining a base plane; and a middle inlet passage located within the shank, the middle inlet passage having: a first cooling conduit portion at a first plane radially spaced 0.0167 meters from the base plane, the first cooling conduit portion having a first cross-sectional area, the first cooling portion defining a first bounding circle, the first cooling portion having: a first point at a first 12:30 o'clock position on the first bounding circle; and a second point at a first 1:30 o'clock position on the first bounding circle, the first point and the second point defining a first line; a second cooling conduit portion at a second plane radially spaced 0.0197

meters from the base plane, the second cooling conduit portion having a second cross-sectional area; a third cooling conduit portion at a third plane radially spaced 0.0215 meters from the base plane, the third cooling conduit portion having a third cross-sectional area; a fourth cooling conduit portion at a fourth plane radially spaced 0.0234 meters from the base plane, the fourth cooling conduit portion having a fourth cross-sectional area; a fifth cooling conduit portion at a fifth plane radially spaced 0.0245 meters from the base plane, the fifth cooling conduit portion having a fifth cross-sectional area, the fifth cooling portion defining a second bounding circle, the second cooling portion having: a third point at a second 12:30 o'clock position on the second bounding circle; and a fourth point at a third 1:30 o'clock position on the second bounding circle, the third point and the fourth point defining a second line; wherein the middle inlet passage defines a maximum normalized cooling conduit portion area ($A_{\text{sub.max}}$) ranging between 1.30 and 2.10, $A_{\text{sub.max}}$ defined by: $A_{\text{max}} = \max\{\frac{A_i}{A_1}\}_{i=2}^5$ wherein the first line and the second line define a degree of change of the cooling conduit portions along the suction side (DCCPASS) ranging between 21.0 and 33.0 degrees ($^{\circ}$); and a plurality of cooling conduits located within the airfoil, the plurality of cooling conduits including a first quantity ($N_{\text{sub.1}}$) of cooling conduits fed by the middle inlet passage, wherein the first quantity is 2, wherein the plurality of cooling conduits define a second quantity ($N_{\text{sub.2}}$) of cooling conduit portions spanning between the suction side and the pressure side, wherein the second quantity is 3, and wherein:

$$4.949 \leq 0.19 * \left(\frac{DCCPASS(^{\circ})}{2^{\circ}}\right)^2 * \left(\frac{N_2}{8}\right)^3 * \left(\frac{SRSR(m)}{1m}\right) * \left(\frac{N_1}{01}\right) \leq 13.039.$$

2. The blade assembly of claim 1, further including a plurality of inlet passages located within the shank, the plurality of inlet passages including the middle inlet passage.
 3. The blade assembly of claim 2, wherein each of the inlet passages extends between the base and one or more of the plurality of cooling conduits.
 4. The blade assembly of claim 2, wherein the plurality of inlet passages further includes a leading-edge inlet passage and a trailing-edge inlet passage.
 5. The blade assembly of claim 1, wherein the shank is configured as a dovetail.
 6. The blade assembly of claim 1, wherein the blade assembly is a stage one blade assembly of a high pressure turbine of the gas turbine engine.
 7. The blade assembly of claim 1, wherein the quantity ($N_{\text{sub.1}}$) of cooling conduits fed by the middle inlet passage includes: a forward serpentine cooling conduit in the airfoil; and an aft serpentine cooling conduit in the airfoil.
 8. The blade assembly of claim 7, wherein the middle inlet passage is fluidly coupled to the forward serpentine cooling conduit and the aft serpentine cooling conduit at a splitter, the splitter including: a first cooling conduit portion at a sixth plane radially spaced 0.449 meters from the base plane, the first cooling conduit portion associated with the forward serpentine cooling conduit, the first cooling conduit portion having a first major axis; and a second cooling conduit portion at the sixth plane, the second cooling conduit portion associated with the aft serpentine cooling conduit, the second cooling conduit portion having a second major axis, wherein: the first major axis and the second major axis define an L-shape.
 9. The blade assembly of claim 1, wherein each of the second quantity of cooling conduit portions span at least 60% of the thickness of the airfoil.
-