

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409573
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Arndt; Steven Wayne et al.

Shaver

Abstract

A shaver includes a housing including first and second housing halves defining an interior chamber, the housing having an operational end and an opposite, bottom end, the interior chamber containing a motor acting through a transmission and configured for reciprocally driving a pair of laterally reciprocating drive fingers. Each drive finger includes an elongate finger drive element extending from the operational end. A resilient seal having slits accommodating the finger drive elements is captured in corresponding seal cavities in each of the housing halves. The seal and the housing halves are configured for placing the seal in at least one of radial and axial compression upon assembly of the housing halves together.

Inventors: Arndt; Steven Wayne (Geneseo, IL), De Frang; Curtis J. (Rock Falls, IL), Groen; Kyle (Sterling, IL)

Applicant: WAHL CLIPPER CORPORATION (Sterling, IL)

Family ID: 85287793

Assignee: WAHL CLIPPER CORPORATION (Sterling, IL)

Appl. No.: 17/458902

Filed: August 27, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230064384 A1	Mar. 02, 2023

Publication Classification

Int. Cl.: B26B19/04 (20060101); B26B19/06 (20060101); B26B19/10 (20060101); B26B19/38 (20060101)

U.S. Cl.:

CPC **B26B19/048** (20130101); **B26B19/063** (20130101); **B26B19/10** (20130101);
B26B19/3853 (20130101);

Field of Classification Search

CPC: B26B (19/10); B26B (19/102-107); B26B (19/048); B26B (19/06-063); B26B (19/3853);
 B26B (19/3866)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3104662	12/1962	Morawetz	N/A	N/A
3950847	12/1975	Duda	30/34.1	B26B 19/10
4118863	12/1977	Sandy	N/A	N/A
5050300	12/1990	Miska	30/34.1	B26B 19/3866
5131148	12/1991	Wahl	N/A	N/A
5207731	12/1992	Bukoschek	N/A	N/A
5400508	12/1994	Deubler	N/A	N/A
D374504	12/1995	Wahl	N/A	N/A
D914979	12/2020	Fleming et al.	N/A	N/A
2002/0023351	12/2001	Simms	30/41	B26B 21/446
2002/0073550	12/2001	Long	30/41.6	B26B 19/44
2002/0078570	12/2001	Andrew	N/A	N/A
2004/0083865	12/2003	Stevens	N/A	N/A
2006/0107530	12/2005	Shimizu	30/43.92	B26B 19/046
2006/0288581	12/2005	Rogatschnig	30/34.1	B26B 19/3853
2008/0020619	12/2007	Shigeta	439/271	B26B 19/3873
2008/0216320	12/2007	Royle	30/539	B26B 19/14
2009/0025229	12/2008	Kappes	30/43.92	B26B 19/048
2010/0269350	12/2009	Iwashita	30/43.92	B26B 19/048
2016/0156244	12/2015	Komori	310/17	H02K 5/10
2017/0225343	12/2016	Suzuki	N/A	B26B 19/3866
2018/0085934	12/2017	Erndt	N/A	B26B 19/40
2018/0085938	12/2017	Peter	N/A	B26B 19/048
2018/0085950	12/2017	Fischer	N/A	B26B 19/3866
2019/0299438	12/2018	Erndt	N/A	B26B 19/3866

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2021/023603	12/2020	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion received for PCT/US2022/036909, mailed Oct. 18, 2022. cited by applicant

Supplementary European Search Report received in Application No. 22861863.3, dated Jun. 12, 2025. cited by applicant

Primary Examiner: Eiseman; Adam J

Assistant Examiner: Crosby, Jr.; Richard D

Attorney, Agent or Firm: Greer, Burns & Crain, Ltd

Background/Summary

BACKGROUND

(1) The present invention relates generally to dry shavers, and more particularly to improvements in the internal construction and assembly of such shavers for reducing components and simplifying assembly.

(2) As is well known in the art, dry shavers include a motorized housing that drives a pair of laterally reciprocating drive fingers. Each drive finger engages a linearly-extending cutting blade element, that reciprocates against a perforated foil for cutting hairs extending through the foil perforations. Dry shavers typically have a shaver head component that includes the foils and a supporting body.

(3) Users of conventional dry shavers are accustomed to periodically removing and/or partially disassembling the shaver head for cleaning foils and blade elements. In some cases, the shaver housing is exposed to liquids, e.g. water, cleaning solutions and sanitizing liquids during this cleaning process. Designers of shavers accordingly have been faced with including seals for preventing the entry of unwanted fluids and debris into the shaver interior which houses the electric motor and other electronic components. Conventional shavers often include designated plates and associated threaded fasteners for securing such seals in place.

(4) Another design aspect of conventional dry shavers is that the drive fingers are incompletely or loosely retained in the shaver housing, such that unwanted vibration, noise and inconsistent performance have been experienced. Further, during periodic disassembly, the drive fingers readily separate from each other and are cumbersome to reassemble. This separation is also problematic during the initial assembly of the shaver, requiring the assembler to carefully hold the drive fingers tightly together while inserting them into the housing as a unit.

(5) Still another design aspect of conventional dry shavers is the construction of the shaver head. Although the users periodically disassemble these components, conventional foil cartridges are cumbersome to disassemble and reassemble, and the perforated foil is subject to damage during disassembly or reassembly.

(6) Lastly, designers of dry shavers are constantly striving for reducing operational vibration and noise, as well as simplifying the assembly for reducing manufacturing costs.

(7) Thus, there is a need for an improved dry shaver that addresses the above-listed design factors.

SUMMARY

(8) The above-listed need is met or exceeded by the present dry shaver, which, among other things, features an improved drive finger seal construction, including a molded seal frame or basket, and specialized recesses in the shaver housing that compress the seal and frame for enhanced assembly and liquid repellant properties as the shaver housing halves are fastened together. As such, the seal is retained in operational position in the housing without the need for specialized brackets and threaded fasteners. In addition, the shaver drive fingers are secured in designated cavities in the shaver housing that accommodates multiple contact points of the fingers for more secure retention. Also, the drive fingers are engageable with each other for assembly into, as well as disassembly from, the shaver housing as a unit.

(9) Another feature of the present shaver is a foil cartridge having spring clips at each end that are

releasably accommodated in associated tracks in the shaver head body. As such, the foil cartridge is relatively easily disassembled from the shaver head for periodic cleaning. The tracks are also configured for facilitating location of the foil cartridge upon reassembly.

(10) Still another feature of the present shaver is an improved motor retention system. A resilient motor cover is constructed and arranged for holding the motor in a fixed position in the shaver housing interior. Included on the cover are formations that engage at least one of the housing halves and transmit a compressive force on the motor without the use of designated threaded fasteners. The motor cover includes formations that also exert holding pressure on a circuit board located between the motor and one of the housing halves.

(11) More specifically, a shaver is provided, including a housing including first and second housing halves defining an interior chamber, the housing having an operational end and an opposite, bottom end, the housing interior containing a motor acting through a transmission and configured for reciprocally driving a pair of laterally reciprocating drive fingers. Each drive finger includes an elongate finger drive element extending from the operational end. A resilient seal having slits accommodating the finger drive elements is captured in corresponding seal cavities in each of the housing halves. The seal and the housing halves are configured for placing the seal in at least one of radial and axial compression upon assembly of the housing halves together.

(12) In an embodiment, the seal is provided with a supporting frame or basket, and the basket is accommodated in the seal cavities in the first and second housing halves for enhancing the at least one of radial and axial compression exerted upon the seal upon the assembly of the housing. More preferably, the housing halves each have an inclined basket engagement rib in the basket cavity constructed and arranged so that as the housing halves are joined, increasing compressive force is exerted on the basket. Once the seal and the basket are in compressed position in the assembled shaver housing, liquids and other debris such as hair clippings are prevented from infiltrating into the housing interior.

(13) In an embodiment, the pair of drive fingers includes a short drive finger and a long drive finger, each finger having a foot including at least one integrally formed spring element having an attachment end, referred to as an attachment box, each attachment box being secured in at least one of the housing halves. Preferably, at least one of the attachment boxes has multiple attachment points for operationally retaining the drive finger in the housing upon housing assembly, while permitting lateral reciprocation of the drive finger relative to the operational end.

(14) In a further embodiment, the multiple attachment points include a domed rib with a pair of elongate sides located on an upper surface of the finger attachment box, and a pair of laterally-spaced ribs depending from a lower surface of the attachment box. Also preferred is that the short drive finger and the long drive finger are attachable to each other for common assembly into the housing. Further, each drive finger has a pair of integrally-formed spring elements, one located at each of a forward end and a rear end, and each spring element has a finger attachment box at the attachment end. The attachment boxes of the short drive finger are engageable with the attachment boxes of the long drive finger for assembly of the fingers into or out of the shaver as a unit.

(15) More specifically, in an embodiment, one of the drive fingers has at least one male engagement formation, and the other of the drive fingers has at least one female engagement formation matingly engaging the male engagement formation for retaining the two drive fingers together for assembly as a unit into the shaver. In an embodiment, one male engagement formation is a tab, and the female engagement formation is a slot.

(16) In another embodiment, a shaver head releasably is provided that is attachable to the operational end of the shaver housing, and the shaver head includes a shaver head body with a pair of perforated shaver foil cartridges releasably secured thereto. In a preferred embodiment, the shaver head body has opposed ends defining a pair of cartridge tracks, and each foil cartridge has a pair of spring clips, each clip constructed and arranged for releasably engaging a corresponding one of the tracks.

- (17) In an embodiment, each spring clip has a dogleg free end, and each track has a landing for releasably receiving the clip in an operational position, and such that user pressure on the cartridge towards the housing releases engagement between the dogleg free end and the landing for releasing the cartridge from the shaver head body. Preferably, the cartridge tracks have flared lower ends for facilitating locating engagement of the clips.
- (18) In an embodiment, a motor cover is provided that is constructed and arranged for holding the motor in a fixed position in the housing interior chamber, the motor cover being dimensioned for exerting a compressive force on the motor as the housing halves are secured together. In addition, the motor cover retains the motor in the housing without the use of threaded fasteners.
- (19) In an embodiment, a printed circuit board is located in the housing interior chamber between the motor and a closely adjacent one of the housing halves, the motor cover having formations for engaging and restraining the printed circuit board in position as the housing halves are secured together.
- (20) In another embodiment, a shaver is provided, including a housing including first and second housing halves defining an interior chamber, the housing having an operational end and an opposite, bottom end, the housing interior chamber containing a motor acting through a transmission and configured for reciprocally driving a pair of laterally reciprocating drive fingers, each finger including an elongate finger drive element extending from the operational end. The pair of drive fingers includes a short drive finger and a long drive finger, each finger is attachable to each other for common assembly into the housing.
- (21) In yet another embodiment, a shaver is provided, including, a housing including first and second housing halves defining an interior chamber, the housing has an operational end and an opposite, bottom end, the housing interior containing a motor acting through a transmission and configured for reciprocally driving a pair of laterally reciprocating drive fingers, each finger including an elongate finger drive element extending from the operational end.
- (22) A shaver head is releasably attachable to the operational end of the housing, and includes a shaver head body with a pair of perforated shaver foil cartridges releasably secured thereto. The shaver head body has opposed ends defining a pair of cartridge tracks, and each foil cartridge has a pair of spring clips, each clip constructed and arranged for releasably engaging a corresponding one of the tracks.
- (23) In still another embodiment, a shaver is provided, including a housing having first and second housing halves defining an interior chamber, the housing having an operational end and an opposite, bottom end, the interior chamber containing a motor acting through a transmission and configured for reciprocally driving a pair of laterally reciprocating drive fingers, each finger including an elongate finger drive element extending from the operational end.
- (24) A motor cover is provided that is constructed and arranged for holding the motor in a fixed position in the housing interior chamber, the motor cover being dimensioned for exerting a compressive force on the motor as the housing halves are secured together.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a top perspective view of the present shaver;
- (2) FIG. 2 is a fragmentary vertical section of the present shaver;
- (3) FIG. 3 is a partially exploded, fragmentary top perspective view of the present shaver;
- (4) FIG. 4 is a cross-section taken along the line 4-4 of FIG. 3 and in the direction generally indicated;
- (5) FIG. 5 is a bottom exploded view of the present drive fingers;
- (6) FIG. 6 is a fragmentary cross-section of the present shaver housing taken along the line 6-6 of

FIG. 3 and in the direction generally indicated;

(7) FIG. 7 is a fragmentary perspective view of the interior chamber of the present shaver;

(8) FIG. 8 is a cross-section taken along the line 8-8 of FIG. 7 and in the direction generally indicated;

(9) FIG. 9 is a fragmentary perspective view of the present shaver;

(10) FIG. 10 is front elevational view of the present shaver foil cartridge;

(11) FIG. 11 is a cross-section taken along the line 11-11 of FIG. 16 and in the direction generally indicated;

(12) FIG. 12 is a cross-section taken along the line 12-12 of FIG. 1 in the direction generally indicated;

(13) FIG. 13 is a top perspective view of the present motor cover;

(14) FIG. 14 is a fragmentary elevational view of the interior of the present shaver;

(15) FIG. 15 is a cross-section along the line 15-15 of FIG. 14 and in the direction generally indicated;

(16) FIG. 16 is a fragmentary top perspective view of the present shaver;

(17) FIG. 17 is an enlarged, fragmentary cross-section taken from FIG. 16; and

(18) FIG. 18 is a cross-section taken along the line 18-18 of FIG. 16 and in the direction generally indicated.

DETAILED DESCRIPTION

(19) Referring now to FIG. 1, the present dry shaver is generally designated 10, and includes a housing 12 made up of a first housing half 12a and a second housing half 12b. The housing halves 12a and 12b are secured together using threaded fasteners (not shown). For the purposes of the present discussion, it will be assumed that while in one embodiment, a particular feature is shown on the first housing half 12a, it is contemplated that such a feature is also suitable for the second housing half 12b. Included on the housing 12 is an operational end 14 and an opposite bottom end 16. A detachable shaver head 18 is releasably secured to the operational end 14. At least one resilient grip pad 20 is optionally provided and are affixed to the housing 12. A power switch 22 is preferably located on a front surface 24 of the housing, and at least one shaver head release button 26 is located on at least one side 28 of the housing. However, the location of the switch 22 and the button 26 may vary to suit the application. Optionally, the shaver head 18 is provided with a protective cover (not shown), and grip-enhancing formations 30 are formed in the housing 12.

(20) Referring now to FIGS. 2-4, the housing halves 12a, 12b define between them an interior chamber 32 in which are defined locations for a motor 34, a power transmission 36, typically an off-center cam, and a pair of laterally reciprocating drive fingers, preferably designated a long drive finger 38, and a short drive finger 40. The drive fingers 38, 40 are driven in alternating, laterally reciprocating motion by the motor 34 acting through the power transmission 36. Each of the drive fingers 38, 40 includes an elongate finger drive element 42 extending from the housing operational end 14 into the shaver head 18 (see FIG. 1) and described in more detail below.

(21) To prevent the unwanted entry of liquids and other debris such as hair clippings into the housing interior chamber 32, a resilient seal 50 is provided, being made of a water-impermeable, rubber-like material, and preferably having a polygonal, pad-like shape. Included on the seal 50 is a pair of slits 52 dimensioned to slidably accommodate the finger drive elements 42 along their full reciprocal travel stroke. Also, the seal 50 is retained or captured in a seal cavity 54 defined by each of the housing halves 12a, 12b.

(22) A feature of the present shaver 10 is that the seal 50 and the housing halves 12a, 12b are configured for placing the seal in at least one of radial and axial compression upon assembly of the housing halves together. The desired compression is provided by at least one inclined basket rib 56 in the seal cavity 54 which engage at least one of the seal 50 and a supporting frame or basket 58 which is made of a relatively rigid material such as hard plastic, and overlies the seal 50. As the housing halves 12a, 12b are brought together during shaver assembly, the seal 50 is dimensioned to

be oversized in the seal cavity **54**, and the basket ribs **56** are configured so that as the housing halves are brought together, increasing compressive force is exerted on at least one of the frame **58** and the seal **50**. Upon assembly, the seal **50** prevents the unwanted entry of liquids and other debris such as hair clippings into the interior chamber **32**. Such a configuration departs from those prior designs described above which employ a designated plate and fasteners used to compress said plate. Rather, the illustrated embodiment herein advantageously leverages the compressive force created by the act of closing housing halves **12a**, **12b** together. That compressive force is transferred through frame **58** to seal **50** as described above. As a result, the use of additional fasteners to ensure proper compressive force against seal **50** is not required, thereby reducing both the complexity of manufacture and cost.

(23) Referring now to FIGS. **2-8**, additional features of the present shaver **10** are that the drive fingers **38**, **40** are more securely held within the housing **12** for reduction of operational noise and vibration, and are more easily assembled into and disassembled from, the housing as a unit. Specifically referring to FIGS. **2** and **5**, each drive finger **38**, **40** includes a foot **60** configured for connecting the drive finger to the housing **12**. Each foot **60** has at least one and preferably a pair of integrally formed spring elements **62**, preferably a leaf spring, which at a free or attachment end **64** is configured for being engaged in the housing halves **12a**, **12b** for securing the foot in the housing **12**. Each spring element **62** projects from one of a forward end **66** and a rear end **68** of the foot **60**.

(24) Referring now to FIGS. **2** and **6**, attachment ends **64** of each of the feet **60** have multiple attachment points for operationally retaining the drive finger **38**, **40** in the housing **12** upon housing assembly, while permitting lateral reciprocation of the drive fingers relative to the operational end **14**. Each attachment end **64** is formed as an attachment box, with a domed rib **70** having a pair of elongate sides **72** located on an upper surface **74** of the attachment box, and a pair of laterally-spaced ribs **76** depending from a lower surface **78** of the attachment box. This arrangement loosely defines a triangle as seen in FIG. **2**, which increases stability of the drive fingers **38**, **40** in the housing **12**, thus reducing noise and vibration.

(25) To positively retain the drive fingers **38**, **40** in the housing **12**, housing half **12b** has a pair of attachment box cavities **80** (FIG. **6**) configured for slidably capturing and tightly retaining the attachment boxes **64** having the above-described configuration. While housing half **12b** is illustrated as having box cavities **80**, it is contemplated by the invention herein that either or both housing halves **12a**, **12b** could contain the aforementioned box cavities **80**. Each attachment box cavity **80** includes an upper recess **82** receiving the domed rib and tightly engaging the elongate sides **72**, and a pair of spaced sidewalls **84** each engaging one of the ribs **76**. Preferably, the cavity **80** is also provided with a vertically projecting lug **86** that prevents lateral movement of the attachment box **64** in the attachment box cavity **80**. It is also preferred that each housing half **12a**, **12b** is provided with access holes **88** (FIG. **6**) that the user can use to disengage the attachment boxes **64** using a pin, screwdriver, toothpick or the like once the housing **12** is opened for maintenance. Also, a view of the drive fingers **38**, **40** mounted next to each other in the housing interior **32** and the ribs **76** engaged in the attachment box cavity **80** is seen in FIG. **8**. The above-described construction simplifies shaver assembly by reducing the number of components needed to assemble the shaver, and also simplifying assembly itself by eliminating the number of threaded fasteners needed.

(26) Referring now to FIG. **5**, it will be seen that the respective long drive finger **38** and the short drive finger **40** are attachable to each other for common assembly into, and disassembly from, the housing **12** by virtue of the configuration of the attachment boxes **64**. In a preferred embodiment, the respective attachment boxes **64** are releasably engageable using mating formations. More specifically, one of the drive fingers **38**, **40** has at least one male engagement formation **90**, and the other of the drive fingers has at least one female engagement formation **92** matingly engaging the male engagement formation for retaining the two drive fingers together for assembly as a unit into, or disassembly from, the shaver **10**. As illustrated, in one embodiment, the long drive finger **38** has

the male engagement formation **90** in the form of a tab extending from the attachment box **64**, and the short drive finger **40** has the female engagement formation **92** in the formation of a slot defined by the upper surface **74**, the laterally spaced depending ribs **76**, and a laterally projecting demi-tab **94**. Preferably, the tab **90** and the slot **92** are configured with close tolerances so that there is a frictional retention of the two drive fingers **38, 40** together at these points.

(27) Each of the drive fingers **38, 40** has an elongate drive slot **96** in the foot **60** that accommodates a lobed cam **98** (FIGS. **2, 4**) of the power transmission **36**. These drive slots **96** are used to create the alternating reciprocal movement of the drive fingers **38, 40** that create the shaving action of the shaver **10**. Referring now to FIGS. **9-11, 16** and **17**, the shaver head **18** includes a shaver head body **100** releasably attachable to the operational end **14** of the housing **12** by virtue of at least one recess **102** (FIG. **11**) engaged by a clip **104** connected to the shaver head release button **26** (FIG. **3**).

Another feature of the present shaver **10** is that perforated shaver foil cartridges **106** are easily removed from the shaver head **18** for replacement or cleaning. As is customary in the art, there are two such foil cartridges **106** for each shaver **10**. This exchange of the shaver foil cartridges **106** is easily accomplished by the user without the use of tools, and with reduced risk of damaging a perforated foil surface **108** that serves as the fixed cutting blade and engages the user's skin during shaving.

(28) Referring to FIGS. **9** and **11**, the shaver head body **100** has opposed ends **110**, each with an inner surface **112** defining a pair of cartridge tracks **114**. In the preferred embodiment, the cartridge tracks **114** are laterally outwardly flared at lower ends **116** for facilitating locating engagement of the cartridges **106**. Also, each cartridge track **114** has a recessed landing surface **118**.

(29) Referring now to FIGS. **9** and **10**, each foil cartridge **106** has a pair of spring clips **120**, each clip projecting axially from an end **122, 124** of the cartridge and being constructed and arranged for releasably engaging a corresponding one of the tracks **114**. Each spring clip **120** has a dogleg free end **126** defining an axially-extending angle that is releasably retained in the recessed landing surface **118**. User pressure on the cartridge **106** in a direction indicated by the arrow "A" in FIG. **10** towards the housing **12** releases engagement between the dogleg free end **126** and the landing **118** for releasing the cartridge from the shaver head body **100**. When the new or cleaned shaver foil cartridge **106** is replaced into the shaver head body **100**, a reverse motion is used, and the clips **120** are guided into position by the flared lower ends **116** of the tracks **114** until the dogleg free ends **126** are located in the landings **118**.

(30) As seen in FIG. **17**, the landings **118** are configured with a ramp **119** that helps to hold the foil cartridges **106** vertically in place and prevent unwanted release of the foil cartridges when the shaver head **18** is removed.

(31) Referring to FIGS. **16** and **18**, the finger drive elements **42** have a forked upper end **128** that engages a lug **130** on a moving blade **132** having a plurality of cutting blades **134**. Driven by the drive elements **42**, the moving blade **132** reciprocates against an inner surface of the shaver foil surface **108** to create the shaving action of the shaver **10**. When the user removes the shaver head **18**, the moving blade **132** remains on the shaver **10**.

(32) Referring now to FIGS. **12-15**, another feature of the present shaver is depicted. To reduce operational noise and vibration, reduce assembly components and steps, the motor **34** is secured within the interior chamber **32** using a motor cover **136**. The motor cover **136** is made of resilient, rubber-like material, and is configured for partially surrounding the motor **34** and for compressing the motor against an opposite housing half as the housing halves **12a, 12b** are joined. At least one, and in the illustrated embodiment three cone-shaped, hollow pillars **138** are integrally formed with the motor cover **136** and at an upper end **140** receive projections **142** depending from an inner surface **144** of the first housing half **12a**. As such, the motor cover **136** retains the motor **34** in position without the use of threaded fasteners, and also electrically insulates the motor from a battery (not shown).

(33) At an opposite end **146**, the pillars **138** engage a printed circuit board **148**. In this

configuration, the pillars **138** transmit the compressive force generated by the assembly of the housing **12** and, while retaining the motor **34** in position, also press the printed circuit board **148** against the other housing half **12b**.

(34) Referring again to FIG. **13**, the motor cover **136** is preferably provided with at least one and preferably a plurality of spacer ribs **150**, preferably positioned in spaced, parallel arrangement on an upper surface **152** of the motor cover. The ribs assist in providing compression for holding the motor **34** in position, and also help compensate for clearance issues arising from part tolerances or the like when closing the housing halves **12a**, **12b** together.

(35) While a particular embodiment of the present shaver has been described herein, it will be appreciated by those skilled in the art that changes and modifications may be made thereto without departing from the invention in its broader aspects and as set forth in the following claims.

Claims

1. A shaver, comprising: a housing including first and second housing halves defining an interior chamber, said housing having an operational end and an opposite, bottom end; said interior chamber containing a motor acting through a transmission and configured for reciprocally driving a pair of laterally reciprocating drive fingers, each said finger including an elongate finger drive element extending from said operational end; a resilient seal including slits accommodating said finger drive elements and being captured in corresponding complementary seal cavities in each of said housing halves; said housing halves each have an inclined basket engagement rib constructed and arranged so that as said housing halves are joined, increasing compressive force is exerted on said seal for placing the seal in at least radial compression so that said seal is held in place by said at least radial compression upon assembly of the housing halves together; and said pair of drive fingers includes a short drive finger and a long drive finger, each said finger having a foot including at least one integrally formed spring element having an attachment end, each said attachment end being secured in at least one of said housing halves, and each said finger directly engaging a moving blade.

2. A shaver, comprising: a housing including first and second housing halves defining an interior chamber, said housing having an operational end and an opposite, bottom end; said interior chamber containing a motor acting through a transmission and configured for reciprocally driving a pair of laterally reciprocating drive fingers, each said finger including an elongate finger drive element extending from said operational end; a resilient seal including slits accommodating said finger drive elements and being captured in corresponding complementary seal cavities in each of said housing halves; said seal and said housing halves are configured for placing the seal in at least one of radial and axial compression so that said seal is held in place by said compression upon assembly of the housing halves together; and said pair of drive fingers includes a short drive finger and a long drive finger, each said finger having a foot including at least one integrally formed spring element having an attachment end, each said attachment end being secured in at least one of said housing halves, and each said finger directly engaging a moving blade.

3. The shaver of claim 2, wherein said seal is configured for preventing infiltration of fluids and debris into said housing interior.

4. The shaver of claim 2, wherein at least one of said attachment ends has multiple attachment points for operationally retaining said drive finger in said housing upon housing assembly while permitting lateral reciprocation of said drive finger relative to said operational end.

5. The shaver of claim 4, wherein said multiple attachment points include a domed rib with a pair of elongate sides located on an upper surface of a finger attachment box, and a pair of laterally-spaced ribs depending from a lower surface of said attachment box.

6. The shaver of claim 2, wherein said short drive finger and said long drive finger are attachable to each other for common assembly into said housing.

7. The shaver of claim 6, wherein each of said drive fingers has a pair of integrally-formed spring elements, one located at each of a forward end and a rearward end, each said spring element has a finger attachment box at said attachment end, and said attachment boxes of said short drive finger are engageable with said attachment boxes of said long drive finger.

8. The shaver of claim 7, wherein one of said drive fingers has at least one male engagement formation, and the other of said drive fingers has at least one female engagement formation matingly engaging said male engagement formation for retaining said two drive fingers together for assembly as a unit into said shaver.

9. The shaver of claim 8, wherein said at least one male engagement formation is a tab, and said at least one female engagement formation is a slot.

10. The shaver of claim 2, further including a shaver head releasably attachable to said operational end of said housing, said shaver head including a shaver head body with a pair of perforated shaver foil cartridges releasably secured thereto.

11. The shaver of claim 10, wherein said shaver head body has opposed ends defining a pair of cartridge tracks, and each said foil cartridge has a pair of spring clips, each said clip constructed and arranged for releasably engaging a corresponding one of said tracks.

12. The shaver of claim 11, wherein each said spring clip has a dogleg free end, and each said track has a landing for releasably receiving said clip in an operational position, and such that user pressure on said cartridge towards said housing releases engagement between said dogleg free end and said landing for releasing said cartridge from said shaver head body.

13. The shaver of claim 11, wherein said cartridge tracks have flared lower ends for facilitating locating engagement of said clips.

14. The shaver of claim 2, further including a motor cover being a separate component from said housing halves and constructed and arranged for holding said motor in a fixed position in said housing interior chamber, said motor cover being dimensioned for exerting a compressive force on said motor as said housing halves are secured together.

15. The shaver of claim 14, wherein said motor cover retains said motor in said housing without the use of threaded fasteners.

16. The shaver of claim 14, further including a printed circuit board located in said housing interior chamber between said motor and a closely adjacent one of said first and second housing halves, said motor cover having formations for engaging and restraining said printed circuit board in position as said housing halves are secured together.

17. A shaver, comprising: a housing including first and second housing halves defining an interior chamber, said housing having an operational end and an opposite, bottom end; said interior chamber containing a motor acting through a transmission and configured for reciprocally driving a pair of laterally reciprocating drive fingers, each said finger including an elongate finger drive element extending from said operational end; a resilient seal including slits accommodating said finger drive elements and being captured in corresponding complementary seal cavities in each of said housing halves; said seal and said housing halves are configured for placing the seal in at least one of radial and axial compression so that said seal is held in place by said compression upon assembly of the housing halves together; a shaver head releasably attachable to said operational end of said housing, said shaver head including a shaver head body with a pair of perforated shaver foil cartridges releasably secured thereto; said shaver head body has opposed ends defining a pair of cartridge tracks, and each said foil cartridge has a pair of spring clips, each said clip constructed and arranged for releasably engaging a corresponding one of said tracks; and each said spring clip has a dogleg free end, and each said track has a landing for releasably receiving said clip in an operational position, and such that user pressure on said cartridge towards said housing releases engagement between said dogleg free end and said landing for releasing said cartridge from said shaver head body.
