

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410694
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Wensrich; Jeffrey et al.

Downhole setting tool and method of use

Abstract

A system and method of use are disclosed that enable a simplified operational procedure of isolating portions of a well bore. Specifically, a self-venting setting tool is described, that in an embodiment, utilizes well bore fluid as the inflation fluid for a downhole packing device. Simply exposing the tool to a pressure greater than atmospheric pressure readies the system for the setting of downhole packing devices. Otherwise, a typical system may be required to undergo a complex venting procedure prior to deployment or be susceptible to failure due to gas regions within the wellbore prior to reaching a desired location for the subsequent wellbore isolation.

Inventors:	Wensrich; Jeffrey (Houston, TX), Schroit; Sam (Houston, TX)
Applicant:	BN Technology Holdings Inc. (Houston, TX)
Family ID:	85507082
Assignee:	BN TECHNOLOGY HOLDINGS INC. (Houston, TX)
Appl. No.:	18/691028
Filed (or PCT Filed):	September 12, 2022
PCT No.:	PCT/US2022/043247
PCT Pub. No.:	WO2023/039258
PCT Pub. Date:	March 16, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240401448 A1	Dec. 05, 2024

Related U.S. Application Data

Publication Classification**Int. Cl.:** E21B43/12 (20060101); E21B33/12 (20060101); E21B33/127 (20060101); E21B43/38 (20060101)**U.S. Cl.:****CPC** E21B43/128 (20130101); E21B33/1275 (20130101); E21B43/38 (20130101);**Field of Classification Search****CPC:** E21B (43/128); E21B (43/38); E21B (33/1275)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4378051	12/1982	Cholet	166/383	E21B 23/00
5398753	12/1994	Obrejanu	294/86.18	E21B 23/042
5947198	12/1998	McKee	166/66.4	E21B 17/206
6012518	12/1999	Pringle	166/66.4	E21B 41/00
6112809	12/1999	Angle	175/45	E21B 47/26
6142237	12/1999	Christmas	166/66.4	E21B 17/06
6196325	12/2000	Connell	166/242.6	E21B 17/041
6213202	12/2000	Read, Jr.	166/242.6	E21B 17/06
6582145	12/2002	Malone	403/31	E21B 33/122
6715554	12/2003	Cunningham	166/368	E21B 33/047
7458423	12/2007	Vercaemer	166/227	E21B 43/11
7540327	12/2008	Billingham	166/55.7	E21B 41/00
7607477	12/2008	Stoesz	166/242.6	G02B 6/52
7661477	12/2009	Sheiretov	166/301	E21B 17/1021
7878244	12/2010	Nold, III	166/264	E21B 49/10
8591200	12/2012	Marica	417/388	F04B 5/00
9664004	12/2016	Martinez	N/A	E21B 23/00
10190389	12/2018	Bane	N/A	E21B 23/0421
10920587	12/2020	Yuratich	N/A	E21B 49/10
11156057	12/2020	Wensrich	N/A	E21B 34/08
11332984	12/2021	Mahbod	N/A	E21B 17/1071
11428066	12/2021	Andersen	N/A	E21B 43/26
11608697	12/2022	Schroit	N/A	H02K 7/116
11719084	12/2022	Wensrich	166/308.1	E21B 33/12
11761314	12/2022	Schroit	166/377	F04B 17/03
11788372	12/2022	Andersen	166/297	E21B 29/02
12037858	12/2023	Hallundbaek	N/A	F04B 53/16
12105226	12/2023	Schroit	N/A	G01S 7/497
12146384	12/2023	Quero	N/A	E21B 34/063

2008/0190605	12/2007	Clapp	166/185	E21B 49/087
2009/0025926	12/2008	Briquet	166/242.6	E21B 49/10
2009/0229817	12/2008	Partouche	166/242.6	E21B 17/028
2011/0315403	12/2010	Nard	166/387	E21B 33/128
2013/0000887	12/2012	Smith	166/179	E21B 33/1216
2015/0285042	12/2014	Porel	417/399	F04B 17/03
2016/0145958	12/2015	Richards	166/65.1	E21B 23/0412
2019/0242209	12/2018	Anthony	N/A	E21B 33/128
2021/0355760	12/2020	Mahbod	N/A	E21B 17/1014

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2951658	12/2018	CA	E21B 23/06
3231521	12/2022	CA	E21B 23/06
2386143	12/2002	GB	E21B 23/00
2451767	12/2008	GB	E21B 43/128

Primary Examiner: Lembo; Aaron L

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims the benefit of priority of U.S. Provisional Patent Application Ser. No. 63/243,603 filed on Sep. 13, 2021; the application being incorporated by reference herein.

BACKGROUND OF THE INVENTION

(1) The present disclosure relates generally to a method of providing wellbore fluid to effectuate a change in a downhole tool. Specifically, the method of the present invention relates to setting an inflatable packing device, packer or plug at a location in a wellbore, and an apparatus or assembly usable for performing the method.

BACKGROUND OF THE RELATED ART

(2) A bottom hole assembly (BHA) is an apparatus that is adapted for use within a wellbore that extends into the earth to reach a target subterranean formation that is expected to contain valuable hydrocarbons, such as oil, gas and combinations thereof. A bottom hole assembly may be run into an existing wellbore on a wireline that may provide a physical tether as well as providing connections for electrical power delivery and data communication between the bottom hole assembly and a computer system at the surface near the wellbore. Furthermore, a bottom hole assembly may include one or more downhole tools, components or subsystems that perform one or more functions of the bottom hole assembly.

(3) Certain downhole tools may include a pump. A downhole tool comprising a pump may be activated to provide pressurized fluid to a subsystem within the downhole tool or elsewhere within the BHA.

(4) Many downhole tools are actuated or operated in response to the application of pressurized fluid. Examples of these devices include hydraulically set packers and liner hangers, pressure actuated perforating gun firing heads, inflatable plugs and inflatable packers. In all these devices, the application of pressurized fluid, to the downhole tool, effectuates a change in the downhole tool. Inflatable packing down hole tools such as packers, plugs, bridge plugs, and the like, are commonly utilized in the operation or maintenance of subterranean wells. These inflatable packing devices normally comprise an inflatable elastomeric balder concentrically disposed around a

central body portion such as a tube or mandrel. Typically, a sheath of reinforcing slats or ribs is concentrically disposed around the balder and thick-walled elastomeric packing cover is concentrically disposed around at least a central portion of the sheath. Such inflatable packing downhole tools may be deployed in a wellbore by using tubing, a downhole electric wireline or a slick line to support the down hole tool and to lower the down hole tool to a location in the wellbore. Typically, the inflatable packing down hole tool is connected to the electric wire line or slick line at the bottom of a downhole hole tool comprising a pump, which may be known as a setting tool. A BHA of these components may be lowered into the wellbore at a location below the extent of the production tubing and the setting tool may provide pressurized fluid from the wellbore to the inflatable packing downhole tool. The setting tool may intake fluid from within the well, pressurize the fluid and deliver the fluid to the inflatable packer. Alternatively, the inflation fluid may be transported to the vicinity of the inflatable packing device and then pumped into the inflatable packer by the setting tool. After the inflatable packing device is sufficiently inflated to contact and seal the wellbore, it is released from the electric wireline or slick line, and the electric wireline or slick line is retrieved from the wellbore. In this manner, the bottom hole assembly may be used to isolate portions of the wellbore for water-shut off, pressure isolation, sand isolation; or in conjunction with a formation fracturing process, formation treatment process, other processes, or other downhole operations.

(5) Current state of the art setting tools which utilize wellbore fluid as the pumping fluid to effectuate a change in inflatable packing downhole tools, i.e. inflate, require a complicated gas venting procedure prior to deploying the BHA into a wellbore. This is required to ensure that when the pump is activated downhole, it provides fluid at pressure to the inflatable packing downhole tool. The setting tools which require venting prior to deployment are also susceptible to having the pump system displaced with gas during deployment to a desired location in the wellbore, for example, when deploying through a region of high-pressure gas. When this occurs, the tool must be brought to surface and the venting procedure repeated.

(6) Therefore, an improved downhole setting tool, a self-venting downhole setting tool, is disclosed herein, which automatically vents when exposed to a wellbore fluid which may be provided to the inflatable packing downhole tool.

BRIEF SUMMARY

(7) The primary purpose of the invention disclosed herein is an improved down hole setting tool for inflating and/or setting an inflatable packing downhole tool or packer in a wellbore. Additionally, an improved method of inflating and/or setting an inflatable packing downhole tool or packer in a wellbore is disclosed.

(8) A BHA comprising a self-venting setting tool downhole tool (which hereinafter may be referred to as the downhole tool or the self-venting setting tool) and an inflatable packer down hole tool is lowerable into a wellbore and is operable to set an inflatable plug or packer therein. The downhole tool is releasably connected to the inflatable packer down hole tool and includes a pump that is fluidically connected with the inflatable packer downhole tool and operable to inflate the packer. A filter module is disposed on the downhole end of the downhole tool and includes an intake fluid passageway that has an inlet in fluid communication with a fluid in the wellbore and a pump intake chamber of the downhole tool. A fluid communication passageway, known as a vent passageway, is provided in fluid communication from the pump intake chamber to the wellbore, for the purpose of evacuating a gas (e.g. air or other gases typically found in a downhole wellbore environment) from the pump intake chamber during the deployment of the BHA and/or during operation of the downhole tool pump. The vent passageway preferably only allows gas out of the pump intake chamber to the wellbore and no fluid into the pump intake chamber from the wellbore. For example, with a ball check valve, flapper valve, restrictor or the like. The vent passageway may however, allow wellbore fluid to enter the pump intake chamber during deployment of the BHA and/or during operation of the downhole tool pump.

- (9) In an embodiment, the downhole tool comprises a controller module, compensator module, power module, drive sub, pump module, intake sub and filter module. The pump resides in a pump intake chamber of the pump module, receives mechanical power from the above power module and through the drive sub. The drive sub is mechanically secured to the uphole end of the pump module and provides a fluid communication passageway, the vent passageway, from the pump intake chamber to the wellbore. The intake sub is mechanically secured to the downhole end of the pump module and the uphole end of the filter module and provides a fluid communication passageway from the filter module to the pump intake chamber. An output fluid passageway is provided from the pump outlet, through the intake sub and through the filter module.
- (10) In another embodiment, a bottom hole assembly (BHA) comprises the self-venting setting tool and an isolation tool, for example, an inflatable packer downhole tool.
- (11) In a further embodiment, there is provided a method of isolating a portion of the wellbore, the method comprising the steps of: deploying the BHA on wireline; venting gas residing in and/or entering the pump intake chamber during deployment or operation, from the wellbore or inflatable packer downhole tool; positioning the BHA at a desired location in the wellbore; activating the downhole tool to provide fluid to the isolation tool; pressurizing the isolation tool to engage the wellbore; isolating a portion of the wellbore above the isolation tool from a portion of the wellbore below the isolation tool; disconnecting the downhole tool from the isolation tool and removing the downhole tool from the wellbore.
-

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

- (1) FIG. 1 is a block diagram of the modules of a bottom hole assembly including a self-venting setting tool.
- (2) FIGS. 2A-C are diagrams of a bottom hole assembly, the bottom hole assembly including a self-venting setting tool and an isolation tool being run into a wellbore on a wireline, the isolation tool in the wellbore set to isolate a wellbore region above the isolation tool from a portion of wellbore below the isolation tool and the isolation tool left in the wellbore.
- (3) FIG. 3 is a view of the self-venting setting tool.
- (4) FIG. 4 is a top view of the self-venting setting tool from lines 4-4 of FIG. 3.
- (5) FIGS. 5A and 5B are cross-sectional partial views of the self-venting setting tool along line 5-5 of the FIG. 4.
- (6) FIG. 6 is close-up view of a portion of FIG. 5B, the pump module and part of the drive sub, indicated on FIG. 5B.
- (7) FIG. 7 is close-up view of a portion of FIG. 5B, part of the filter module indicated on FIG. 5B.
- (8) FIG. 8A is a view of the intake sub.
- (9) FIG. 8B is a top view of the intake sub.
- (10) FIG. 9 is a partial section view of an embodiment of a self-venting setting tool predominantly showing the pump module.
- (11) FIG. 10 is a partial section view of an embodiment of a self-venting setting tool predominantly showing the pump module.
- (12) FIG. 11 is a partial section view of an embodiment of a self-venting setting tool predominantly showing the pump module.
- (13) FIG. 12 is a partial section view of an embodiment of a self-venting setting tool predominantly showing the pump module.
- (14) FIG. 13 is a partial section view of an embodiment of a self-venting setting tool predominantly showing a fluid source module.
- (15) FIG. 14 is a schematic of an embodiment of a self-venting setting tool disposed within a fluid

reservoir module.

(16) FIG. 15A is a partial view of a self-venting setting tool showing fluid control devices, membrane check valves installed.

(17) FIG. 15B is a view of a membrane check valve.

(18) FIG. 15C is a section view of a membrane check valve.

(19) FIG. 16A is a view of a ball check valve.

(20) FIG. 16B is a section view of a ball check valve.

(21) FIG. 17A is a view of an umbrella valve assembly.

(22) FIG. 17B is a section view of an umbrella valve assembly.

(23) FIG. 18A is a view of a flapper valve.

(24) FIG. 18B is a section view of a flapper valve.

(25) FIG. 19A is a view of a screen insert.

(26) FIG. 19B is a section view of a screen insert.

(27) FIG. 20A is a view of a filter cartridge.

(28) FIG. 20B is a section view of a filter cartridge.

(29) FIG. 21 is a partial view of a bottom hole assembly showing the lower end of a self-venting setting tool connected to an isolation tool.

DETAILED DESCRIPTION

(30) An embodiment provides a self-venting setting tool downhole tool (which hereinafter may be referred to as the downhole tool or the self-venting setting tool) for use within a wellbore that extends into a subterranean formation. The downhole tool may be part of a bottom hole assembly comprised of other downhole tools or components. The self-venting setting tool may be connected to a wireline that extends from a wireline unit or truck located near an opening into the wellbore. The wireline may be used to provide physical support of the downhole tool as it is raised and lowered into and within the wellbore, supply electrical power to electronic components within the downhole tool, and/or provide for data communication between the downhole tool and control systems outside the wellbore. While the wireline may be sufficient for raising and lowering the downhole tool within a substantially vertical wellbore or portion of a wellbore, a downhole tool on a wireline as a part of a BHA may further include a tractor that can push or pull the downhole tool along the wellbore regardless of the orientation of the wellbore, such as in a horizontal portion of a wellbore.

(31) In an embodiment, the self-venting setting tool comprises a controller module electrically connected to the wireline, a compensator module, a power module comprising an electrical motor, a drive sub, pump module, intake sub and a fluid source module including a fluid source.

(32) The pump module is comprised of a pump module housing and a pump which resides in a pump intake chamber such that when it receives mechanical power from the motor within the power module by a drive shaft which extends through the drive sub and supported by bearings, it draws in fluid from the pump intake chamber. The pump may have one or pump intake ports and a pump output. The drive shaft additionally extends through a rotary seal which retains oil within the uphole power module and compensator module, and is coupled to the shaft of the pump. The drive sub is mechanically secured to the uphole end of the pump module housing, secures the pump and provides one or more fluid communication passageways from the pump intake chamber to the wellbore, vent passageways.

(33) The intake sub is mechanically secured to the downhole end of the pump module and the uphole end of the fluid source module and provides one or more fluid communication passageways from the fluid source module to the pump intake chamber. An output fluid passageway, which may also be referred to as the output side of the downhole tool is comprised of an output tube and a passage within the intake sub and a bottom sub, is provided from the pump outlet.

(34) The fluidically connected passageways from and including the fluid source module to pump intake ports, may collectively be referred to as the intake side of the downhole tool.

- (35) In an alternative embodiment, the fluid source module is positioned above the pump module within the self-venting setting tool.
- (36) In an alternative embodiment, the fluid source module is secured to the uphole end of the pump module and on the downhole end of the drive sub.
- (37) The intake of the one or more vent passageways from the pump intake chamber, vent passageway intakes, are preferably located uphole from the pump intake ports. In this way, having accumulated gas at or near the pump intake ports is avoided.
- (38) In an embodiment, the downhole tool is void of a fluid source module and when the pump is activated, fluid is drawn into the pump module through one or more passageways fluidically connected to the wellbore, which may additionally function as vent passageways when the self-venting setting tool is exposed to wellbore pressure greater than atmospheric pressure.
- (39) The power module comprising the electrical motor may include a speed reducing gearbox and is disposed to receive power and communication signals from a control module. The electric motor preferably receives electrical power through a wireline cable but may receive some or all its electrical power from a battery within the BHA.
- (40) The control module comprises a controller in electronic communication with the power module for receiving a current signal from the electrical motor and is in electronic communication with electrical motor for sending a control signal to the electrical motor. The controller may, for example, control the operation of the electrical motor to maintain a desired rotational speed of the pump the power module powers, thereby controlling the flowrate of the self-venting setting tool. Additionally, the controller may, for example, control the operation of the electrical motor to maintain a desired torque of the pump the power module powers, thereby controlling the pressure output of the self-venting setting tool.
- (41) The controller may be an analog circuit or a digital processor, such as an application specific integrated circuit (ASIC) or array of field-programmable gate arrays (FPGAs). Accordingly, embodiments may implement any one or more aspects of control logic in the controller that is on-board the downhole tool or in a computing system that is in data communication with the controller. A computing system may be located at the surface to provide a user-interface for monitoring and controlling the operation of the downhole tool and may be in data communication with the controller over the wireline cable. The control module preferably receives electrical power through a wireline cable but may receive some or all of its electrical power from a battery within the BHA.
- (42) In an embodiment the pump is a fixed displacement pump.
- (43) In an embodiment the pump is variable displacement pump.
- (44) In an embodiment the pump is an axial piston pump.
- (45) In an embodiment the pump is an external gear pump.
- (46) In an embodiment the pump is a gerotor pump.
- (47) In an embodiment the pump is an internal gear pump.
- (48) In an embodiment the pump is a radial piston pump.
- (49) In an embodiment the pump is a screw pump.
- (50) In an embodiment the pump is a swash plate pump.
- (51) In an embodiment the pump is a vane pump.
- (52) In an embodiment, the drive sub is void of vent passageways and alternatively the pump module housing comprises one or more vent passageways uphole from the pump intake ports.
- (53) In an embodiment, the pump housing comprises one more vent passageways disposed to vent gas from within the pump and output hydraulic passageway to the pump intake chamber or wellbore.
- (54) In an embodiment, the pump module housing also functions as the pump housing, the pump housing mechanically secured to a sub on an uphole end and mechanically secured to the intake sub on the downhole end, the pump disposed to receive mechanical power from the power module.

(55) In an embodiment a fluid control device is disposed to control fluid through the vent passageways.

(56) In an embodiment, a fluid control device is located on the one or more vent passageways to predominantly allow fluid flow in one direction, from the pump intake chamber to the wellbore.

(57) In an embodiment the fluid control device is a ball check valve.

(58) In an embodiment, the fluid control device is a flapper valve.

(59) In an embodiment the fluid control device is an umbrella valve.

(60) In another embodiment, the fluid control device is a mesh screen, and is provided along the vent passageways to allow fluid flow from the wellbore to the pump intake chamber and gas to flow from the pump intake chamber to the wellbore, while limiting the size of particulate that may be carried into the pump intake chamber by the fluid.

(61) In an embodiment, a ported screw is provided along the one or more vent passageways to allow fluid flow from the wellbore to the pump intake chamber and gas to flow from the pump intake chamber to the wellbore.

(62) In an embodiment, the ported screw is a restrictor.

(63) In a preferred embodiment, the one or more vent passageways are in fluid communication with the wellbore above the bottom hole assembly.

(64) In a preferred embodiment, a wireline bottom hole assembly is provided for use within a wellbore that extends into a subterranean formation, comprising: a downhole tool having a pump module including a pump, a pump intake port and a pump output; a fluid source module disposed below the pump and in fluid communication with the wellbore above the bottom hole assembly, having a ported housing and a first fluid volume; the pump intake port disposed to intake fluid from the fluid source module; an electric motor operable to power the pump; a vent passageway in fluid communication with the pump, having a vent passageway intake on an uphole side of the pump intake port and disposed to vent fluid from the pump module to the wellbore; an output passageway extending from the pump output, through the fluid source module.

(65) In a preferred embodiment, the fluid source module is a filter module; the filter module comprising a ported housing, a filter which may be known as a filter cartridge, and a flow-through tube. The ported housing allows fluid communication with the wellbore fluid residing exterior to the ported housing, such that fluid may flow from the wellbore through the ported housing into a first fluid volume being an outer annular volume, through the filter and into a second fluid volume being an inner annular fluid volume. The flow-through tube enables fluid communication from the pump through the filter module and bottom sub connected thereto. In this embodiment, the one or more fluid communication passageways of the intake sub extend from the second fluid volume, the inner annular fluid volume of the to the pump intake chamber such that when the pump is activated, fluid is drawn into the pump by the one or more pump intake ports from the wellbore, through the filter and provided to the output side of the self-venting setting tool. The filter may be a mesh screen selected to limit the size of a particulate within the fluid passing therethrough.

(66) In the preferred embodiment, the output passageway comprises the flow-through tube enabling fluid communication from the pump, out of the downhole end of the fluid source module.

(67) In an embodiment, wherein the fluid source module is a filter module, the filter module comprises a filter disposed interior the first fluid volume and the ported housing; a second fluid volume within the filter, wherein the second fluid volume is in fluid communication with a pump intake port.

(68) In a preferred embodiment, the filter module is in fluid communication with the wellbore above the bottom hole assembly.

(69) In an embodiment, the filter module is only in fluid communication with the wellbore above the bottom hole assembly and the intake side of the downhole tool.

(70) In an embodiment, the filter module is only in fluid communication with the wellbore above the bottom hole assembly, the intake side of the downhole tool and the output side of the downhole

tool.

(71) In an embodiment, the fluid source module is a ported module comprising a ported housing, an inner fluid volume, a bottom sub and a flow through tube enabling fluid communication from the pump, through the ported module and bottom sub.

(72) In an embodiment, the fluid source module is a reservoir module and the self-venting setting tool is disposed therein. In this embodiment, fluid may alternatively vent to the interior of the reservoir module via the vent passageways. The reservoir module comprises; a reservoir outer housing, a reservoir inner body isolating reservoir fluid within the reservoir outer housing from well fluid allowed to communicate through one or more ports in the reservoir outer housing. As fluid is drawn into the pump intake chamber by the pump and fluid is provided out of the self-venting setting tool through a bottom adapter of the reservoir module secured to the downhole end of the self-venting setting tool, wellbore pressure acts on the reservoir inner body through the one or more ports in the reservoir outer housing to provide wellbore pressure to the pump intake chamber.

(73) In an embodiment, a portion of the self-venting setting tool is disposed within the reservoir module such that the interior of the reservoir module is fluidically connected to the pump intake chamber or pump module.

(74) In an embodiment, the reservoir module is above the pump intake chamber and one or more fluid passages fluidically connect the reservoir module with the pump intake chamber or the pump module.

(75) In an embodiment, the self-venting setting tool is void of a fluid source module

(76) Statements made herein referring to a component, opening or port being “above”, “below”, “uphole” or “downhole” relative to another component, opening or port should be interpreted as if the downhole tool or bottom hole assembly has been run into a wellbore. It should be noted that even a horizontal wellbore, or any non-vertical well bore, still has an “uphole” direction defined by the path of the wellbore that leads to the surface and a “downhole” direction that is generally opposite to the “uphole” direction.

(77) An embodiment provides a method of delivering fluid out of bottom hole comprising a self-venting setting tool downhole tool including a pump, the method comprising: deploying the bottom hole assembly within a wellbore that extends into a subterranean formation; exposing the bottom hole assembly to a wellbore fluid pressure above atmospheric pressure; allowing fluid to enter the bottom hole assembly and sufficiently displace gas within an intake side of the downhole tool by venting the gas through one or more vent passageways to the wellbore; activating the pump; the pump intaking fluid from a fluid source in fluid communication with the wellbore.

(78) In an embodiment the bottom hole assembly is deployed via wireline.

(79) In an embodiment, the method further comprises displacing gas within an output side of the self-venting setting tool downhole tool.

(80) In an embodiment, the method includes displacing gas with fluid from a fluid source module.

(81) In an embodiment, the method further comprises activating the pump after displacing and venting gas within the intake side of the self-venting setting tool and prior to displacing and venting gas from the output side of the self-venting setting tool.

(82) In an embodiment, the method further comprises activating the pump after displacing and venting gas from within the intake side and output side of the self-venting setting tool.

(83) In an embodiment, the method further comprises venting gas through one or more fluid control devices disposed along the vent passageways.

(84) In an embodiment, the method further comprises venting gas through one or more mesh screens disposed along the one or more vent passageways to allow fluid flow from the wellbore to the interior of the self-venting setting tool. The mesh screen selected to control the size of a particulate within the fluid passing therethrough.

(85) In a preferred embodiment of the method, the fluid source includes a ported housing, a filter

and a fluid volume; the fluid volume in fluid communication with the pump, and the wellbore above the bottom hole assembly through the filter and the ported housing.

(86) In an embodiment, there is provided a method of isolating a portion of the wellbore, the method comprising the steps of: deploying a bottom hole assembly on a wireline into a wellbore; the bottom hole assembly comprising a downhole tool and an isolation tool fluidically connected thereto, and a fluid source; the downhole tool including a pump; exposing the downhole tool to a fluid pressure; displacing gas within an intake side of the downhole tool; venting gas through one or more vent passageways to the wellbore by allowing fluid to enter downhole tool and sufficiently displace gas therein; positioning the bottom hole assembly at a desired location in the wellbore; activating the self-venting setting tool to provide fluid to the isolation tool from the fluid source; pressurizing the isolation tool to engage the wellbore wall; isolating a portion of the wellbore above the isolation tool from a portion of the wellbore below the isolation tool.

(87) In a preferred embodiment, the fluid pressure is greater than atmospheric pressure.

(88) In a preferred embodiment, the fluid source is a filter module.

(89) In an embodiment, the gas is displaced with fluid from the filter module.

(90) In an embodiment, the method further comprises the self-venting setting tool automatically venting gas through one or more vent passageways to the wellbore by providing fluid from the fluid source to the output hydraulic passageway, the output side of the self-venting setting tool, after activation of the self-venting setting tool.

(91) In an embodiment, the method further comprises venting gas through one or more fluid control devices disposed along the one or more vent passageways.

(92) In an embodiment, the method further comprises disconnecting self-venting setting tool from the isolation tool and removing the self-venting setting tool from the wellbore.

(93) In an embodiment of the method wherein the gas is displaced with fluid from the filter module, the filter module comprises; a ported housing, a filter and a fluid volume in fluid communication with the pump, and the wellbore above the bottom hole assembly through the filter and the ported housing.

(94) In an embodiment, the one or more fluid control devices is one or more restrictors.

(95) In an embodiment of the method, the isolation tool is an inflatable plug.

(96) In an embodiment of the method, the isolation tool is an inflatable packer.

(97) In an embodiment of the method wherein the fluid source is a filter module, the filter module additionally comprises a flow-through tube enabling fluid communication from the pump, out of the downhole end of the self-venting setting tool.

(98) In an embodiment of the method, the fluid source is a reservoir module comprising a reservoir outer housing, a reservoir inner body isolating reservoir fluid within the reservoir outer housing from well fluid allowed to communicate through one or more ports in the reservoir outer housing.

(99) In an embodiment, the fluid source is a fluid volume filtered by a filter and in fluid communication with the wellbore.

(100) In an embodiment, the fluid source is a volume of fluid in the interior of a filter, the volume fluidically connected to the wellbore fluid exterior to the self-venting setting tool.

(101) In an embodiment, the fluid source is a fluid volume in the interior of a ported housing in fluid communication with the wellbore.

(102) In an embodiment, the fluid source is fluid in a reservoir module.

(103) In an embodiment, the fluid source is a fluid volume in the interior of a reservoir module provided with fluid prior to deployment within a wellbore.

(104) In an embodiment of a method wherein the fluid source module is a reservoir module, the method further comprises supplying the reservoir module with fluid prior to the deployment step.

(105) FIG. 1 is a diagram of a bottom hole assembly (BHA) 10 comprising a self-venting setting tool 90 (the downhole tool) disposed to pressurize an isolation tool 100. The self-venting setting tool comprises a control module 20 disposed to send and receive signals from other modules of the

self-venting setting tool **90** including signals to and from a power module **40** located below the control module **20**. A compensator module **30** is located above the power module **40** and below the control module **20**. The power module **40** converts electrical power into mechanical power and transmits the mechanical power through a below mounted drive sub **50** to a pump module **60**. Fluid is supplied to the pump module **60** from a fluid source module **80** and through intake sub **70**. Fluid from the pump module **60** is delivered through the intake sub **70**, through the fluid source module **80** and to the isolation tool **100**.

(106) In FIG. 2A, the BHA **10** is disposed in a wellbore **6** with the wireline cable **5** coupled to the tool **90** via a cable head **15**. The cable is coupled to a truck or unit (not shown) at the surface above the wellbore **6**. The wireline cable **5** may provide physical support to the self-venting setting tool **90**, supply electrical power to the self-venting setting tool **90**, and enable data communication between the self-venting setting tool **90** and a computing system **22** at the surface above the wellbore **6**. The arrow **8** illustrates an uphole direction and the arrow **7** illustrates a downhole direction defined by the wellbore passageway to the surface.

(107) In FIG. 2B, the BHA **10** has been run into the wellbore **6** to a location where the isolation tool **100** is above target subterranean formation **11**. In this location, the isolation tool **100** is pressurized to seal against the wall of the wellbore **9**, where the wall is typically an inside surface of a metal casing string. With the isolation tool **100** sealed within the wellbore **6**, the region of the wellbore above or uphole of the isolation tool **100** is fluidically isolated from the region of the wellbore below or downhole of the isolation **100**. In FIG. 2C, the self-venting setting tool **90** has been disconnected from the isolation tool **100**, the isolation tool **100** left in the wellbore **6** and the self-venting setting tool **90** removed from the wellbore **6**.

(108) FIG. 5A-5B are cross-sectional partial views of an embodiment of a self-venting setting tool **90** along line 5-5 of FIG. 4 with a filter module as the fluid source module **80**. FIG. 4 is a view of the self-venting setting tool **90** from line 4-4 of FIG. 3. The downhole tool **90** has a cable head **15** at its proximal (uphole) end for securing the wireline cable **5** (see also FIGS. 2A-2C). The wireline cable **5** may include a physical support line, an electrical power supply line, and a data communication line. The physical support line, such as a braided metal cable, may terminate at the cable head **15**, but the electrical power supply line and data communication line extend through the cable head **15** to a control module **20** which is comprised of a controller **21** in electronic communication with a power module **40** mounted below the control module **20** and a compensator module **30**. The power module **40** comprises an electrical motor **41** and a speed reducing gearbox **42**. The controller module **20** is disposed to receive a current signal form the electrical motor **41** and to send a control signal to the electrical motor **41**. The electrical motor **41** is disposed to transmit mechanical power to the speed reducing gearbox **42**. The speed reducing gearbox **42** is disposed to transmit rotational mechanical power to the transmission shaft **43**, which extends out of the power module **40**, into and through a drive sub **50** to the pump module **60**. The transmission shaft **43** additionally extends through a rotary seal **45** which retains oil within the uphole power module **40** and compensator module **30**. The shaft **63** of pump **61** is coupled to the transmission shaft **43** with coupler **44**. The pump **61** of the pump module **60** resides in the pump intake chamber **64** and inside the pump module housing **65** of the pump module **60**.

(109) The drive sub **50** is mechanically secured to the uphole end of the pump module **60** pump housing **65**, secures the pump **61** and provides one or more fluid communication passageways, vent passageways **51**, from the pump intake chamber **64** to the wellbore. See also FIG. 6. Each of one or more vent passageway's intake **51A** from the pump intake chamber **64**, is preferably located uphole from the pump intake ports **66**.

(110) A fluid control device **52** resides along the vent passageway to control fluid passing therethrough, to and from the self-venting setting tool **90**.

(111) In an embodiment, the fluid control device **52** may control the physical properties of fluid entering the self-venting setting tool **90**, for example, the size or amount of solids which may be

inside the fluid entering the self-venting setting tool **90**.

(112) A mesh screen **52** resides along the vent passageways such that the size of particulates which may enter the pump intake chamber from the wellbore is controlled. The mesh screen is preferably sized to allow gas to escape from the pump intake chamber **64**, through the vent passageways **51**, to the wellbore.

(113) See also FIGS. **8A** and **8B**. The intake sub **70** is mechanically secured to the downhole end of the pump module **60** and the uphole end of the fluid source module **80** and provides one or more fluid communication passageways, intake passageways **71**, therethrough. A pump adapter **62** is secured and sealed to the pump output **59** and a central through hole **72** of intake sub **70**.

(114) See also FIG. **7**. In an embodiment, the fluid source module **80** is a filter module and is secured to the lower end of the intake sub **70**. The filter module **80** comprises a ported housing **81**, to allow wellbore fluid to flow through, enter a first volume being an outer annular fluid volume **82**, and flow through a filter cartridge **83** to second volume being an inner annular volume **84** in fluid communication with the pump intake chamber **64** by means of intake passageways **71**. See also FIG. **20A-20B**. A bottom sub **86** is secured to the lower end of the ported housing **81** and a flow through tube **85** extends from the intake sub **70**, to the bottom sub **86**. A continuous hydraulic flow path; output hydraulic passageway **68**, which may also be known as the output side of the self-venting setting tool, extends from the pump output out the downhole end of the bottom sub **86** and is comprised of a through hole in the pump adapter **62**, passage **72** of the intake sub, flow through tube **85** and a through hole **87** through the bottom sub.

(115) With reference to FIG. **5A**, the compensator module **30** comprises a compensator piston **38** spring loaded by spring **39** and disposed to translate within compensator bore **36**. A volume on the downhole side of the compensator piston **38** is in fluid communication with the tool exterior; for example, the wellbore **6**, and a hydraulic fluid volume on the uphole side of the compensator piston **38** is in fluid communication with the interior of the power module **40** and the interior volume of the drive sub **50** in which the transmission shaft **43** resides.

(116) FIG. **9** is a partial section view of an embodiment of a self-venting setting tool. In this embodiment, the drive sub **50** is void of vent passageways and alternatively the pump module housing **65** comprises one or more vent passageways **51** uphole from the pump intake ports **66**.

(117) FIG. **10** is a partial section view of an embodiment of a self-venting setting tool. In this embodiment, the pump housing **69** comprises one more vent passageways **51** disposed to vent gas from within the pump internal cavities **67** and output hydraulic passageway **68** to the pump intake chamber **64**. The pump module is mechanically secured to a drive sub **50** on an uphole end and mechanically secured to the intake sub **70** on the downhole end, the pump **61** disposed to receive mechanical power from the power module **40** via transmission shaft **43**.

(118) FIG. **11** is a partial section view of an embodiment of a self-venting setting tool. In this embodiment, the pump module housing **65** is also the pump housing **69**, the pump housing mechanically secured to a drive sub **50** on an uphole end comprising one or more vent passageways **51** and mechanically secured to the intake sub **70** on the downhole end, the pump **61** disposed to receive mechanical power from the power module **40** by transmission shaft **43**.

(119) FIG. **12** is a partial section view of an embodiment of a self-venting setting tool. In this embodiment, the pump module housing **65** is also the pump housing **69**, the pump housing mechanically secured to a drive sub **50** on an uphole end and mechanically secured to the intake sub **70** on the downhole end, the pump **61** disposed to receive mechanical power from the power module **40**. The drive sub is void of vent passageways and alternatively, the pump housing comprises one or more vent passageways **51**.

(120) Referring to FIG. **13**, in an embodiment, the fluid source module is a ported module **110** comprising a ported housing **111**, an inner fluid volume **112**, a bottom sub **86** and a flow through tube **85** enabling fluid communication from the pump, through the ported module **110** and bottom sub **86**.

(121) Referring to FIG. 14, in an embodiment, the self-venting setting tool **90** is disposed in a fluid source module **120**. The fluid source module in this embodiment is a reservoir module **120** comprising; a reservoir outer housing **121**, a reservoir inner body **122** isolating reservoir fluid within the reservoir outer housing **121** filled prior to deployment, from well fluid allowed to communicate through one or more ports **123** in the reservoir outer housing **121**. A bottom adapter **124** secures the reservoir outer housing **121** to the downhole end of the self-venting setting tool **90** and provides a flow path **125** to and through the lower end of the reservoir module **120**. As fluid is drawn into the pump intake chamber **64** by the pump **61** and pumped through the bottom adapter **124** of the reservoir module **120**, pressure may act on the reservoir inner body **122** through the one or more ports **123** in the reservoir outer housing **121** to apply pressure to the pump intake chamber **64**. Fluid may vent to the interior of the reservoir module **120** through the vent passageways **51**.

(122) In an embodiment of a BHA, an isolation tool is fluidically connected to the downhole end of the bottom adapter **124**.

(123) In an embodiment, a fluid control device **52** is included along one or more vent passageways **51**.

(124) FIG. 15A is a partial view of a self-venting setting **90** which shows fluid control devices **52** installed. FIG. 15B is a membrane check valve and FIG. 15C is a section view of a membrane check valve **126** comprising a valve body **131** including vent holes **132**, a flexible membrane **133** centrally fastened to the valve body **131**. When pressure exterior **135** to the membrane check valve **126** is greater than or equal to interior **136** pressure, the membrane **133** obstructs the passage of flow through the vent holes **132**. When pressure exterior **135** to the membrane check valve **126** is less than the interior **136** pressure, the membrane **133** flexes toward the exterior **135** to allow the passage of flow through the vent holes **132**.

(125) In an embodiment, the fluid control device **52** is a membrane check valve **126**.

(126) FIG. 16A is a ball check valve. FIG. 16B is a section view of a ball check valve **127** comprising a valve body **140** including vent holes **132**, a ball **139**, a ball seat **138** and a spring **141**. When pressure on an exterior **135** to the ball check valve **127** is greater than or equal to the interior **136** pressure, the spring **141** ensures ball **138** obstructs the passage of flow through the vent holes **132**. When pressure exterior **135** to the ball check valve **127** is less than the interior **136** pressure and the interior **136** applies sufficient force to overcome the force of the spring **141** acting on the ball **139**, the ball **139** will move toward the exterior **135** to allow the passage of flow through the vent holes **132**.

(127) In an embodiment, the fluid control device **52** is a ball check valve **127**.

(128) FIG. 17A is an umbrella check valve assembly **129** and FIG. 17B is a section view of the umbrella check valve assembly **129** comprising a valve body **142** including vent holes **132**, an umbrella valve **143** centrally fastened to the valve body **142**. When pressure exterior **135** to the umbrella valve **143** is greater than or equal to interior **136** pressure, the umbrella valve **143** obstructs the passage of flow through the vent holes **132**. When pressure exterior **135** to the umbrella valve **143** is less than the interior **136** pressure, the umbrella valve **143** flexes toward the exterior **135** to allow the passage of flow through the vent holes **132**.

(129) In an embodiment, the fluid control device **52** is an umbrella valve assembly **129**.

(130) In an embodiment, the fluid control device **52** is an umbrella valve **129**.

(131) FIG. 18A is a flapper valve and FIG. 18B is a section view of a flapper valve **128** comprising a valve body **144** including vent holes **132**, a flexible membrane **145** fastened on one side to the valve body **144**. When pressure exterior **135** to the flapper valve **128** is greater than or equal to interior **136** pressure, the flexible membrane **145** obstructs the passage of flow through the vent holes **132**. When pressure exterior **135** to the flapper valve **128** is less than the interior **136** pressure, the flexible membrane **145** flexes toward the exterior **135** to allow the passage of flow through the vent holes **132**.

(132) In an embodiment, the fluid control device **52** is a flapper valve **128**.

(133) FIG. 19A is a screen insert. FIG. 19B is a section view of a screen insert **130** comprising a screen insert body **147** and a screen **146** which controls the size of a particulate within a fluid passing therethrough.

(134) In an embodiment, the screen **146** mesh size is selected to control the size of a particulate within a fluid passing therethrough which is tolerable and able to be pumped by pump **61**.

(135) In an embodiment, the fluid control device **52** is a screen insert **130**.

(136) In an embodiment, the fluid control device is a screw having one or more ports or through-holes, the screw threaded into the pump module housing **65**, the drive sub **50** or the pump housing.

(137) When the self-venting setting tool is submerged in well-fluid from a gas environment, well-fluid flows into the filter module **80** through the ported housing **81**, into annular fluid volume **82**, through the cartridge filter **83** to inner annular volume **84**, through the intake passageways **71** of intake sub **70**, into pump intake chamber **64**, and into pump **61** through pump ports **66**.

(138) An embodiment provides a method of delivering fluid out of a self-venting setting tool **90**, the method comprising: exposing the self-venting setting tool **90** to a fluid pressure; displacing gas within a fluid source module **80**, one or more intake passageways **71**, a pump intake chamber **64**, one or more internal pump cavities **67**, generally, an intake side of the self-venting setting tool, by venting gas residing therein, through one or more vent passageways **51** to a wellbore **6** such that when the self-venting setting tool **90** is activated, the pump **61** draws in fluid from a fluid source module **80** and delivers it to the output hydraulic passageway **68** which extends out the downhole end of the self-venting setting tool **90**; activating the self-venting setting tool **90**; delivering fluid out of the self-venting setting tool **90**.

(139) In an embodiment, the vent passageways are in fluid communication with the wellbore above the bottom hole assembly.

(140) In an embodiment the method further comprises venting the output hydraulic passageway **68** of the self-venting setting tool **90**.

(141) In a further embodiment, there is provided a method of isolating a portion of a well bore, the method comprising the steps of: deploying the BHA **10** comprising the self-venting setting tool **90** and an isolation **100** tool on a wireline **5**; exposing the self-venting setting tool **90** to the wellbore **6** fluid pressure, which may be during deployment into the wellbore **6**, to sufficiently displace gas within a fluid source module **80**, one or more intake passageways **71**, a pump intake chamber **64**, and internal pump cavities **67**, the intake side of the self-venting setting tool, by venting gas therein through one or more vent passageways **51** to the wellbore **6**; positioning the BHA **10** at a desired location in the wellbore **6**; activating the self-venting setting tool **90** to provide fluid to the isolation tool **100**; pressurizing the isolation tool **100** to engage the wellbore wall **9**; isolating a portion of the wellbore **6** above the isolation tool **100** from a portion of the wellbore **6** below the isolation tool **100**. See also FIG. 21.

(142) In an embodiment, the method further comprises venting the output hydraulic passageway **68** of the self-venting setting tool **90**.

(143) In an embodiment of the method, the pump **61** is activated after displacing and venting gas within the intake passageway and some or all of the internal pump cavities **67**, and prior to displacing and venting gas of the output hydraulic passageway **68**.

(144) In an embodiment, the method further comprises venting gas through one or more fluid control devices **52** disposed along the vent passageways **51**.

(145) In an embodiment of the method, gas is vented through one or more vent passageways **51** to the wellbore **6** by providing fluid from a fluid source module **80** to the output hydraulic passageway **68** after activation of the self-venting setting tool.

(146) In an embodiment, the method further comprises disconnecting the self-venting setting tool **90** from the isolation tool **100** and removing the self-venting setting tool **90** from the wellbore.

(147) In an embodiment, the isolation tool **100** is an inflatable packer.

(148) In an embodiment, the isolation tool **100** is an inflatable plug.

- (149) In an embodiment, the isolation tool **100** is an inflatable straddle packer.
- (150) In an embodiment, the isolation tool **100** is a bridge plug.
- (151) In an embodiment, the isolation tool **100** is a production packer
- (152) In an embodiment, the isolation tool **100** is a permanent packer.
- (153) In an embodiment, the isolation tool **100** is a cement retainer.
- (154) In an embodiment, the isolation tool **100** is a frac plug.
- (155) The terminology used herein is for the purpose of describing particular embodiments only and is not intended to limit the scope of the claims. As used herein, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, components and/or groups, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. The terms “preferably,” “preferred,” “prefer,” “optionally,” “may,” and similar terms are used to indicate that an item, condition or step being referred to is an optional (not required) feature of the embodiment. The term “seal”, as in the engaging of a sealing element to a wellbore, is used for the purpose of describing particular embodiments. The term “seal” should not be limited in scope to a perfect seal and may be a partial seal.
- (156) The corresponding structures, materials, acts, and equivalents of all means or steps plus function elements in the claims below are intended to include any structure, material, or act for performing the function in combination with other claimed elements as specifically claimed. Embodiments have been presented for purposes of illustration and description, but it is not intended to be exhaustive or limited to the embodiments in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art after reading this disclosure. The disclosed embodiments were chosen and described as non-limiting examples to enable others of ordinary skill in the art to understand these embodiments and other embodiments involving modifications suited to a particular implementation.

Claims

1. A wireline bottom hole assembly for use within a wellbore that extends into a subterranean formation, comprising a self-venting setting tool; the self-venting setting tool including: a pump module having a pump, a pump intake port and a pump output; a fluid source module disposed below the pump and in fluid communication with the wellbore above the bottom hole assembly, having a ported housing and a first fluid volume; the pump intake port disposed to intake fluid from the fluid source module; an electric motor operable to power the pump; a vent passageway in fluid communication with the pump, having a vent passageway intake on an uphole side of the pump intake port and disposed to vent gas from the pump module to the wellbore above the pump; an output passageway extending from the pump output, through the fluid source module.
2. The bottom hole assembly of claim 1, further comprising an isolation tool connected to the self-venting setting tool and disposed to receive fluid therefrom, via the output passageway.
3. The bottom hole assembly of claim 1, wherein the fluid source module is a filter module, the filter module further comprising: a filter disposed interior the first fluid volume and the ported housing; a second fluid volume within the filter, wherein the second fluid volume is in fluid communication with the pump intake port.
4. The bottom hole assembly of claim 1, wherein the output passageway comprises a flow-through tube enabling fluid communication from the pump, out of the downhole end of the fluid source module.
5. The bottom hole assembly of claim 1, additionally comprising a fluid control device disposed to control fluid through the vent passageway.

6. The bottom hole assembly of claim 1, wherein the pump is an axial displacement pump.
 7. The bottom hole assembly of claim 1, wherein the electric motor receives electrical power through a wireline cable.
 8. The bottom hole assembly of claim 1, further comprising: a battery coupled to the electric motor for supplying electrical power to the electric motor.
 9. The bottom hole assembly of claim 5, wherein the fluid control device is a mesh screen which may limit the size of a particulate in fluid flowing therethrough.
 10. The bottom hole assembly of claim 5, wherein the fluid control device is a restrictor.
 11. A method of delivering fluid out of the self-venting setting tool of claim 1, the method comprising: deploying by wireline, a bottom hole assembly including the self-venting setting tool within a wellbore that extends into a subterranean formation; exposing the self venting setting tool to wellbore fluid pressure within the wellbore above atmospheric pressure; displacing gas within an intake side of the self-venting setting tool; venting the displaced gas through one or more vent passageways to the wellbore; activating the pump; the pump intaking fluid from a fluid source in fluid communication with the wellbore.
 12. The method of claim 11, wherein gas is additionally displaced within an output side of the downhole tool.
 13. The method of claim 11, wherein the gas is displaced with fluid from the fluid source module in fluid communication with the wellbore.
 14. The method of claim 12, wherein the pump is activated after displacing gas within the intake side of the downhole tool and prior to displacing and venting gas from the output side of the downhole hole tool.
 15. The method of claim 12, wherein the pump is activated after displacing and venting gas from within the intake side and output side of the downhole tool.
 16. The method of claim 12, further comprising: venting gas through one or more fluid control devices disposed along the vent passageways.
 17. The method of claim 11, wherein the fluid source includes a ported housing, a filter and a fluid volume; the fluid volume in fluid communication with the pump, and the wellbore above the bottom hole assembly through the filter and the ported housing.
 18. A method of isolating a portion of a wellbore, the method comprising: deploying the bottom hole assembly of claim 2 into the wellbore; exposing the self-venting setting tool to wellbore fluid pressure to displace gas within an intake side of the self-venting setting tool venting the gas through one or more vent passageways to the wellbore; positioning the bottom hole assembly at a desired location in the wellbore; activating the self-venting setting tool to provide fluid to the isolation tool; pressurizing the isolation tool to engage the wellbore wall; isolating a portion of the wellbore above the isolation tool from a portion of the wellbore below the isolation tool.
 19. The method of claim 18, further comprising: venting gas through one or more fluid control devices disposed along the one or more vent passageways.
 20. The method of claim 18, wherein the self-venting setting tool is activated after displacing and venting gas within the intake side of the self-venting setting tool to the wellbore.
-