

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411300
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Rakoto-Sam; Lucas et al.

Cassette with reversible securing component and system

Abstract

A reversible fiber optic cassette for mounting in a rack comprising a cassette receiving tray, the tray comprising a plurality of cassette engaging features is disclosed. The cassette comprises a cassette body comprising optic fiber receptacles arranged along a front of thereof, a multifiber receptacle along a back thereof and a plurality of optic fiber segments each between a respective one of the optic fiber receptacles and the multifiber receptacle, and a securing component comprising a main part comprising a first surface and a second surface opposite the first surface, a cassette engaging part extending from the first surface for engaging with the cassette body, a tray engaging feature extending from the second surface and engageable with one of the cassette engaging features. The reversible securing component is secureable on either side of the cassette body using the cassette engaging feature.

Inventors: Rakoto-Sam; Lucas (Montreal, CA), Lyonnais-Bourque; Simon (Montreal, CA), Crawford; Dwayne (Pointe-Claire, CA)

Applicant: BELDEN CANADA ULC (Saint-Laurent, CA)

Family ID: 85478719

Assignee: BELDEN CANADA ULC (Saint-Laurent, CA)

Appl. No.: 17/932560

Filed: September 15, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230084170 A1	Mar. 16, 2023

Related U.S. Application Data

us-provisional-application US 63261222 20210915

Publication Classification

Int. Cl.: G02B6/38 (20060101); G02B6/44 (20060101); G02B6/46 (20060101)

U.S. Cl.:

CPC G02B6/4453 (20130101); G02B6/562 (20230501);

Field of Classification Search

CPC: G02B (6/562)

USPC: 385/135

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5996149	12/1998	Heimbrock	5/601	A61B 6/04
2006/0150458	12/2005	Feroli	40/661	G09F 3/18
2009/0074498	12/2008	Nakai	400/208	B41J 35/24
2014/0068641	12/2013	Kuroda	720/730	G11B 15/68
2014/0314384	12/2013	Nair	385/135	G02B 6/4446
2016/0077298	12/2015	Wiltjer	N/A	G02B 6/4453
2017/0131500	12/2016	Sauter	N/A	G02B 6/4455
2018/0271632	12/2017	Berg	N/A	A61C 3/04
2019/0101717	12/2018	Pilon	N/A	G02B 6/44526
2019/0162924	12/2018	Fontaine	N/A	G02B 6/4452
2019/0187394	12/2018	Fontaine	N/A	G02B 6/44526
2019/0219786	12/2018	Crawford	N/A	G02B 6/562
2019/0302388	12/2018	Ellison	N/A	G02B 6/4455
2020/0057226	12/2019	Sievers	N/A	G02B 6/4455
2022/0260799	12/2021	Van Baelen	N/A	G02B 6/4455
2022/0260800	12/2021	Van Baelen	N/A	G02B 6/4455
2022/0291469	12/2021	Roa-Quispe	N/A	G02B 6/4453
2023/0384549	12/2022	Pilon	N/A	G02B 6/4455
2024/0036283	12/2023	Vogel	N/A	G02B 6/4455
2024/0126038	12/2023	Enge	N/A	G02B 6/4453

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3221718	12/2018	CA	G02B 6/4455
WO-2017083256	12/2016	WO	G02B 6/4452

Primary Examiner: Kianni; Kaveh C

Attorney, Agent or Firm: MH2 Technology Law Group, LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This Application claims priority under 35 USC § 119(e) of U.S. provisional application Ser. No. 63/261,222 filed on Sep. 15, 2021 which is incorporated herein in its entirety by reference.

FIELD OF THE INVENTION

(1) The present invention relates to a cassette with reversible securing component and system.

BACKGROUND TO THE INVENTION

(2) The prior discloses reversible fiber optic cassettes for use with other cassettes on a tray. One drawback of these prior art cassettes is that they require two sets of features, one on each side of the cassette, in order to secure and remove the cassette from the tray.

SUMMARY OF THE INVENTION

(3) The present addresses the above and other drawbacks by providing a reversible fiber optic cassette for mounting in a rack comprising a cassette receiving tray, the tray comprising a plurality of cassette engaging features. The cassette comprises an elongate cassette body comprising a plurality of optic fiber receptacles arranged along a front of thereof, a multifiber receptacle along a back thereof and a plurality of optic fiber segments, each of the segments between a respective one of the optic fiber receptacles and the multifiber receptacle, and a securing component comprising: a main part comprising a first surface and a second surface opposite the first surface, a cassette engaging part extending from the first surface for engaging with the cassette body, and a tray engaging feature extending from the second surface and engageable with one of the cassette engaging features. The reversible securing component is secureable on either side of the cassette body using the cassette engaging feature.

(4) There is also provided a reversible fiber optic cassette system comprising a tray comprising a plurality of cassette engaging features, and at least one cassette, each of the at least one cassette comprising an elongate cassette body and a reversible securing component comprising a main part comprising a first surface and a second surface opposite the first surface, a cassette part feature extending from the first surface for engaging with the cassette body, and a tray engaging feature extending from the second surface and configured for engaging with one of the cassette engaging features and wherein the reversible securing component is secureable on either side of the cassette body.

(5) Additionally, there is provided a securing component for mounting a cassette to a cassette receiving tray, the tray comprising a plurality of cassette engaging features and the cassette comprising a cassette body. The securing component comprises a main part comprising a first surface and a second surface opposite the first surface, a cassette engaging part extending from the first surface for engaging with the cassette body, and a tray engaging feature extending from the second surface and engageable with one of the cassette engaging features. The reversible securing component is secureable on either side of the cassette body using the cassette engaging feature.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1A provides a raised front right assembled perspective view of a cassette with reversible securing component and system in accordance with an illustrative embodiment of the present invention;

(2) FIG. 1B provides a raised front right exploded perspective view of a cassette with reversible securing component and system in accordance with an illustrative embodiment of the present invention;

- (3) FIG. 2A provides a raised front right perspective view of a cassette with reversible securing component in accordance with an illustrative embodiment of the present invention;
- (4) FIG. 2B provides a raised rear right perspective view of a cassette with reversible securing component in accordance with an illustrative embodiment of the present invention;
- (5) FIG. 2C provides a raised front right exploded perspective view of a cassette with reversible securing component in accordance with an illustrative embodiment of the present invention;
- (6) FIG. 3A provides a raised right front perspective view of a securing component in accordance with an illustrative embodiment of the present invention;
- (7) FIG. 3B provides a raised right front perspective view of a reversed securing component in accordance with an illustrative embodiment of the present invention; and
- (8) FIG. 4 provides a raised front right exploded perspective view of a cassette with reversible securing component in accordance with an alternative illustrative embodiment of the present invention.

DETAILED DESCRIPTION OF THE ILLUSTRATIVE EMBODIMENTS

(9) Referring now to FIG. 1A, a reversible fiber optic cassette with reversible securing component and system, generally referred to using the reference numeral **10**, will now be described. The system **10** comprises one or more cassettes **12** which are arrangeable side by side and releasably mounted to a tray **14** comprising a plurality of cassette engaging features **16**. The tray **14** is typically slideably mounted with other trays in a case which is dimensioned for securing in a 19" inch rack or the like (both not shown).

(10) Referring to FIG. 1B in addition to FIG. 1A the cassette engaging features **16** are illustratively molded as a strip **18** from a rigid material such as plastic and mounted on a forward edge **20** of the tray **14**. In this regard, the forward edge **20** of the tray **14** comprises features **22** which engage with molded features (not shown), such as tabs or the like, within the rearward edge **24** of the strip **18**. The strip **18** is assembled to the forward edge **20** of the tray **14** by inserting the forward edge **20** in the rearward edge **24** of the strip **18** until the features **22** are engaged by the tabs or the like.

(11) Referring now to FIGS. 2A through 2C, each cassette **12** comprises an elongate cassette body **26** or frame comprising a cable receiving region **28**, a plurality of optic fiber receptacles **30** arranged along a front **32** of the cassette body **26** and illustratively a multifiber receptacle **34** arranged along a back thereof **36**. In one embodiment the optic fiber receptacles **30** are configured for receiving a standard LC type plug for example terminating a single fiber optic cable or the like (both not shown). Additionally, the spacing between the optic fiber receptacles **30** is such that any two optic fiber receptacles **30** can receive two plugs (also not shown) in a duplex configuration. In one embodiment the multi fiber receptacle **34** is configured for receiving a standard MPO type plug terminating a 12× multi-fiber cable or the like (both not shown). The cable receiving region **28** comprises a plurality of retaining features **38** arranged along a generally circular path to receive and retain a plurality of optic fiber segments **40**.

(12) Still referring to FIGS. 2A through 2C, the cassette body **26** further comprises a pair of opposed side edges **42**, **44** interconnecting the front **32** and the back **36**. Referring to FIG. 2C, each of the side edges **42**, **44** comprises a pair of outward facing slots **46** therein. A removable and reversible securing component **48** is also provided which comprises a main part dimensioned to fit sideways across the cassette body **26**, illustratively towards a center thereof. The securing component **48** comprises a cassette engaging part for engaging with the cassette body **26** and comprising pairs of opposed flexible fingers **50** positioned along respective outer edges **52**, **54** of the securing component **48** extending away from a first surface **56** thereof. Additionally, there are provided a pair of stabilising tabs **58** extending away from a second surface **60** of the securing component **48** and which are engageable with selected ones of the cassette engaging features **16**.

(13) Referring to FIG. 2C, the reversible securing component **48** is mountable to a selected side of the cassette body **26** (both mounting options are shown in FIG. 2C, although a person of ordinary skill in the art will understand that only one option is useable at a time) by aligning the flexible

fingers **50** with respective ones of the outward facing slots **46** and inserting the flexible fingers **50** into the outward facing slots **46**. Hook features **62** on the flexible fingers **50** releasably engage with the opposed side edges **42, 44** thereby removably securing the reversible securing component **48** to the cassette body **26**.

(14) Referring to FIGS. 2B and 2C, in one embodiment the receptacles **30** are molded together as a block **64**, illustratively a block **64** of twelve (12) LC type receptacles. Similarly, an inside of the front **32** comprises a plurality of receptacles **66** molded or otherwise formed therein. In one embodiment, the receptacles **66** are configured for receiving a standard LC type plug (not shown) for example terminating a single fiber optic cable (reference **40** in FIG. 2A) or the like. The block **64** of receptacles **30** is attached to the front **32** for example by sonic welding, a suitable adhesive or the like and such that the receptacles **30** align with the receptacles **68**, with each receptacle **30**/receptacle **68** pair acting as a coupler assembly interconnecting optic fibers (not shown) terminated at each receptacle **30, 68** pair and such that the ferrules (not shown) of each of the terminated optic fibers are arranged along the same axis.

(15) Referring now to FIG. 1 and FIGS. 3A and 3B, the reversible securing component **48** further comprises a tray engaging feature **70** comprising a fixed end **72** and a flexible end **74** extending from the second surface **60** of the reversible securing component **48**. An actuator **76** is further provided which extends from the flexible end **74** through an aperture **78** in the main part. The actuatable surface of the actuator **76** comprises a series of small bumps **80** to prevent a user's finger from slipping when pressing the actuator **76**. As a person of ordinary skill in the art will now understand, the actuatable surface of the actuator **76** is accessible from the accessible side of the cassette **12** when the cassette **12** is installed on the tray **14**.

(16) Still referring to FIG. 1 and FIGS. 3A and 3B, on insertion of the cassette **12** onto the tray **14**, the stabilising tabs **58** are engaged by respective ones of a plurality of slots **78** in the strip **18** while the actuator **76** is slid into a slot **80** in the selected cassette engaging feature **16** and a hook **82** on the flexible end **74** of the tray engaging feature **70** moves into an aperture **84** in the cassette engaging feature **16**. A person of ordinary skill in the art will now understand that the hook **82** is biased into the aperture **84** by the flexible end **74** and such that the cassette **12** is securely held to the tray **14**. Similarly, in order to release the cassette **12** from the tray **14**, the actuator **76** is depressed thereby biasing the hook **82** out of the aperture **84** in the cassette engaging feature **16** thereby allowing the cassette **12** to be retracted from the tray **14**.

(17) Referring now to FIG. 4, in an alternative embodiment of a cassette **12**, each of the side edges **42, 44** comprises an outward facing slot **84** therein. The securing component **48** comprises a pair of opposed flexible tabs **86** positioned on respective outer edges **52, 54** of the securing component **48** and extending away from a first surface **56** thereof. Additionally, there are provided a pair of tray stabilising tabs **58** extending away from a second surface **60** of the securing component **48**. The reversible securing component **48** is mountable to a selected side of the cassette body **26** (both mounting options are shown in FIG. 4, although a person of ordinary skill in the art will understand that only one option is useable at a time) by aligning the flexible tabs **86** with respective ones of the outward facing slots **84** and inserting the flexible tabs **86** into the outward facing slots **84**. Hook features **88** on the flexible tabs **86** engage with the opposed side edges **42, 44** thereby removably securing the reversible securing component **48** to the cassette body **26**. In a particular embodiment, provision can also be made for securing a cable manager or the like (not shown) for example by providing additional securing features **90** on the first surface **56** of the securing component **48**.

(18) Although the present invention has been described hereinabove by way of specific embodiments thereof, it can be modified, without departing from the spirit and nature of the subject invention as defined in the appended claims.

Claims

1. A securing component for mounting a cassette to a cassette receiving tray, the tray comprising a plurality of cassette engaging features and the cassette comprising a cassette body, the securing component comprising: a first surface and a second surface opposite said first surface; a cassette engaging part extending from said first surface for engaging with said cassette body; a tray engaging feature extending from said second surface and configured to engage with one of the cassette engaging features; and wherein said securing component is configured to be secured on either side of said cassette body using said cassette engaging feature.
2. The securing component of claim 1, wherein the tray further comprises a plurality of slots and said first surface further comprises at least one stabilizing tab engageable within the slots.
3. The securing component of claim 1, wherein the cassette body is elongate and said first surface and second surface are each dimensioned to fit sideways across the cassette body.
4. The securing component of claim 3, wherein said first surface and second surface each fits sideways across said cassette body towards a center thereof.
5. The securing component of claim 4, wherein the cassette body further comprises a plurality of optic fiber receptacles arranged along a front of thereof, a multifiber receptacle along a back thereof and a plurality of optic fiber segments, each of said segments between a respective one of the optic fiber receptacles and the multifiber receptacle, a pair of opposed side edges connecting the front and the back and a pair of outward facing slots in each of the opposed side edges and wherein said main part comprises at least one of pair of opposed flexible fingers, one of each of said at least one pair of fingers positioned along each outer side edge of said first surface, said fingers extending away from said first surface for releasable engagement in respective slots in said side edges of said cassette body, and wherein the securing component is secureable on either side of the cassette body by inserting said flexible fingers in respective ones of the outward facing slots.
6. The securing component of claim 1, further comprising an actuator extending from a flexible end of said tray engaging feature through an aperture in said main part for selectively disengaging said tray engaging feature from an engaged one of the cassette engaging features and such that when the securing component is mounted on a first side of the cassette body, said actuator is actuatable from a second side of the cassette body.
7. A securing component for mounting a cassette to a cassette receiving tray, the securing component comprising: a first surface and a second surface opposite the first surface; a cassette engaging finger extending from the first surface for engaging with a cassette body; a tray engaging feature extending from the second surface and configured to engage with a cassette receiving tray; and wherein the securing component is configured to attach to the cassette body using the cassette engaging finger.
8. The component of claim 7, wherein the securing component further comprises at least one stabilizing tab that is configured to engage with at least one slot in the cassette receiving tray.
9. The component of claim 7, wherein the first surface and second surface are each dimensioned to fit sideways across the cassette.
10. The component of claim 7, wherein the first surface and second surface are each configured to fit sideways across the cassette towards a center thereof.
11. The component of claim 7, wherein the cassette further comprises a plurality of optic fiber receptacles arranged along a front of thereof, a multifiber receptacle along a back thereof and a plurality of optic fiber segments, each of the segments being between a respective one of the optic fiber receptacles and the multifiber receptacle.
12. The component of claim 11, wherein the cassette further comprises a pair of opposed side edges connecting the front and the back and a pair of outward facing slots in each of said opposed side edges and the cassette engaging finger comprises at least one pair of opposed flexible fingers, one of each of the at least one pair of opposed flexible fingers positioned along an outer side edge of the first surface and the second surface, the opposed flexible fingers extending away from the first

surface for releasable engagement in respective slots in the side edges of the cassette, wherein the first surface and the second surface are each configured to be secured on either side of the cassette by inserting the flexible fingers in respective ones of the outward facing slots.

13. The component of claim 7, further comprising an actuator extending from a flexible end of the tray engaging feature through an aperture in the first surface for selectively disengaging the tray engaging feature from an engaged cassette engaging finger and such that when the first surface and the second surface are mounted on a first side of the cassette, the actuator is configured to be actuated from a second side of the cassette.

14. A securing component for mounting a cassette to a cassette receiving tray, the securing component comprising: a first surface and a second surface opposite the first surface; a cassette engaging finger extending from the first surface for engaging with a cassette; a tray engaging feature extending from said second surface and configured to engage with a cassette receiving tray; wherein the cassette receiving tray comprises a slot; a stabilizing tab configured to operably engage with the slot; and wherein the securing component is configured to attach to the cassette using the cassette engaging finger.

15. The component of claim 14, wherein the slot is a first slot and the cassette receiving tray further comprises a second slot.

16. The component of claim 14, wherein the cassette receiving tray is structurally configured to retain a plurality of cassettes in a side-by-side arrangement.

17. The component of claim 14, wherein the first surface and second surface are each dimensioned to fit sideways across the cassette.

18. The component of claim 14, wherein the first surface and second surface each fits sideways across the cassette towards a center thereof.

19. The component of claim 14, wherein the cassette further comprises a plurality of optic fiber receptacles arranged along a front of thereof, a multifiber receptacle along a back thereof and a plurality of optic fiber segments, each of the segments being positioned between a respective one of the optic fiber receptacles and the multifiber receptacle.

20. The component of claim 19, wherein the cassette further comprises a pair of opposed side edges connecting the front and the back and a pair of outward facing slots in each of the opposed side edges and the cassette engaging finger comprises at least one of pair of opposed flexible fingers, one of each of the at least one pair of opposed flexible fingers positioned along each outer side edge of the first surface and the second surface, the opposed flexible fingers extending away from the first surface for releasable engagement in respective slots in the side edges of the cassette, wherein the first surface and the second surface are each configured to be secured on either side of the cassette by inserting the flexible fingers in respective ones of the outward facing slots.

21. The component of claim 20, wherein the cassette further comprises an actuator extending from a flexible end of the tray engaging feature through an aperture in the first surface for selectively disengaging the tray engaging feature from an engaged one of the opposed flexible fingers and such that when the first surface and the second surface are mounted on a first side of the cassette, the actuator is configured to be actuated from a second side of the cassette.
