

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411468
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Reynolds; Jordan C. et al.

Data assessment and selection for industrial automation environments

Abstract

Various embodiments of the present technology generally relate to solutions for improving industrial automation programming and data science capabilities with machine learning. More specifically, embodiments of the present technology include systems and methods for implementing machine learning engines within industrial programming and data science environments to improve performance, increase productivity, and add functionality. In an embodiment, a system comprises a user interface component configured to display a programming environment for editing control logic, wherein operational data from the industrial automation environment is accessible from within the programming environment through a data pipeline. A machine learning-based data science engine is configured to process the operational data from the industrial automation environment to generate processed data and identify a portion of the processed data relevant to a component of the control logic. The user interface component is further configured to surface the portion of the processed data in the programming environment.

Inventors: Reynolds; Jordan C. (Austin, TX), Hagerbaumer; John J. (Mequon, WI), Mahr; Troy W. (Pleasant Prairie, WI), Jacobsen; Thomas K. (Wake Forest, NC), Scaturchio; Giancarlo (Pisa, IT)

Applicant: Rockwell Automation Technologies, Inc. (Mayfield Heights, OH)

Family ID: 85718068

Assignee: Rockwell Automation Technologies, Inc. (Mayfield Heights, OH)

Appl. No.: 17/484752

Filed: September 24, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230096837 A1	Mar. 30, 2023

Publication Classification

Int. Cl.: G05B19/042 (20060101)

U.S. Cl.:

CPC G05B19/0426 (20130101); G05B2219/23077 (20130101)

Field of Classification Search

CPC: G05B (19/0426); G05B (2219/23077); G06N (3/08); G06N (5/01); G06N (7/01); G06N (20/10); G06N (20/20)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6633782	12/2002	Schleiss et al.	N/A	N/A
7644262	12/2009	Bromley et al.	N/A	N/A
10204191	12/2018	Asenjo	N/A	G06Q 10/06
10761495	12/2019	Binotto	N/A	B60W 30/182
10783162	12/2019	Montague et al.	N/A	N/A
10942710	12/2020	Dunn et al.	N/A	N/A
11042362	12/2020	Stump	N/A	G05B 19/41835
11249462	12/2021	Thomsen	N/A	G06F 16/283
11295047	12/2021	Asenjo	N/A	G06Q 10/06
11340592	12/2021	Mazur	N/A	G05B 19/4184
11599561	12/2022	Kafai	N/A	G06F 16/289
11774944	12/2022	Cella	700/275	G06N 20/00
11841699	12/2022	Sayyarodsari	N/A	G05B 19/41875
12085910	12/2023	Reynolds	N/A	G06F 9/453
12099911	12/2023	Cella	N/A	G05B 19/41865
12130611	12/2023	Reynolds	N/A	G06N 20/10
2002/0077711	12/2001	Nixon	700/51	C10G 11/187
2011/0302654	12/2010	Miettinen	N/A	N/A
2013/0006395	12/2012	Plache et al.	N/A	N/A
2013/0131840	12/2012	Govindaraj et al.	N/A	N/A
2015/0271608	12/2014	Sabin	N/A	N/A
2015/0378692	12/2014	Dang et al.	N/A	N/A
2016/0232457	12/2015	Gray	N/A	G06F 16/26
2017/0017903	12/2016	Gray	N/A	G06T 11/60
2017/0032058	12/2016	Arbel et al.	N/A	N/A
2017/0060541	12/2016	Saleh et al.	N/A	N/A
2018/0046173	12/2017	Ahmed	N/A	N/A
2018/0074470	12/2017	Nagatani et al.	N/A	N/A
2018/0330248	12/2017	Burhanuddin et al.	N/A	N/A

2019/0072943	12/2018	Przybylski	N/A	N/A
2019/0095449	12/2018	Uppunda	N/A	N/A
2019/0138511	12/2018	Margiolas	N/A	G06F 16/2272
2020/0082278	12/2019	Wu et al.	N/A	N/A
2020/0103838	12/2019	Bertinetti et al.	N/A	N/A
2020/0103873	12/2019	Stump et al.	N/A	N/A
2020/0387129	12/2019	Chandaria	N/A	N/A
2021/0042638	12/2020	Novotny	N/A	N/A
2021/0109764	12/2020	Thon	N/A	N/A
2021/0208545	12/2020	Zhang et al.	N/A	N/A
2021/0350282	12/2020	Schulz	N/A	N/A
2021/0397152	12/2020	Chen et al.	N/A	N/A
2022/0100175	12/2021	Riju et al.	N/A	N/A
2022/0171891	12/2021	Sinha	N/A	G05B 23/0281
2022/0358286	12/2021	Wilson-Thomas et al.	N/A	N/A
2023/0094187	12/2022	Reynolds	700/47	G06F 8/33
2023/0097885	12/2022	Reynolds	700/29	G05B 13/042
2023/0102717	12/2022	Reynolds	700/19	G05B 23/0216
2023/0195100	12/2022	Subramanian et al.	N/A	N/A
2023/0289623	12/2022	Zhang	N/A	G06N 20/00
2023/0297060	12/2022	Reynolds	700/46	G05B 19/056
2023/0297080	12/2022	Reynolds	700/28	G05B 19/056
2023/0297343	12/2022	Jin et al.	N/A	N/A
2023/0359173	12/2022	Hildebrandt et al.	N/A	N/A
2023/0419168	12/2022	Reynolds	N/A	G06F 18/2178

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
110083079	12/2018	CN	N/A
112558555	12/2020	CN	N/A

OTHER PUBLICATIONS

Canedo A, Goyal P, Huang D, Pandey A, Quiros G. Arducode: Predictive framework for automation engineering. IEEE Transactions on Automation Science and Engineering. Jul. 21, 2020;18(3):1417-28. cited by applicant

Extended European Search Report in EP22196136.0, mailed Jan. 30, 2023, 10 pages. cited by applicant

Extended European Search Report in EP22196588.2, mailed Jan. 31, 2023, 45 pages. cited by applicant

Extended European Search Report in EP22196838.1, mailed Feb. 20, 2023, 8 pages. cited by applicant

Final Office Action in U.S. Appl. No. 17/484,657, mailed Jul. 7, 2023, 10 pages. cited by applicant

Final Office Action in U.S. Appl. No. 17/484,690, mailed Dec. 27, 2023, 23 pages. cited by applicant

Final Office Action in U.S. Appl. No. 17/484,720, mailed Mar. 22, 2024, 77 pages. cited by applicant

Non-Final Office Action in U.S. Appl. No. 17/484,657, mailed Feb. 17, 2023, 10 pages. cited by applicant

Non-Final Office Action in U.S. Appl. No. 17/484,657, mailed Dec. 7, 2023, 10 pages. cited by applicant

applicant

Non-Final Office Action in U.S. Appl. No. 17/484,690, mailed Jun. 15, 2023, 16 pages. cited by applicant

Non-Final Office Action in U.S. Appl. No. 17/484,690, mailed Jun. 4, 2024, 24 pages. cited by applicant

Non-Final Office Action in U.S. Appl. No. 17/484,720, mailed Oct. 4, 2023, 49 pages. cited by applicant

Non-Final Office Action in U.S. Appl. No. 17/484,720, mailed Jul. 3, 2024, 47 pages. cited by applicant

Notice of Allowance in U.S. Appl. No. 17/484,657, mailed May 9, 2024, 5 pages. cited by applicant

Sun R, Mera A, Lu L, Choffnes D. Sok: Attacks on industrial control logic and formal verification-based defenses. In 2021 IEEE European Symposium on Security and Privacy (EuroS&P) Sep. 6, 2021 (pp. 385-402). IEEE. cited by applicant

Primary Examiner: Von Buhr; M. N.

Background/Summary

BACKGROUND

(1) Industrial manufacturing environments generate huge quantities of data at very fast speeds making the extraction of enterprise-level insights challenging. In industrial automation environments, control systems are used to drive various operations along an industrial line. Control code is used by industrial drives or programmable logic controllers to drive industrial assets, devices, and sensors in an industrial process. Operational data produced during runtime contains important information about inputs, outputs, operations, status, performance, or quality of the industrial process, but can be difficult to leverage in control code programming given the enormous amount of computing power and time that goes into data science and data analytics. Moreover, control programs are typically developed by programmers without access to or with limited access to runtime data, statistics, or the like. Important integrations, dependencies, variables, inputs, or outputs can be easily overlooked by control programmers because of the lack of accessibility to useful operational information. Moreover, an industrial process may have thousands of relevant variables, making it difficult for programmers to adequately provide connections and logic for every important variable, tag, or device. Manually editing control programs in response to various information in operational data can be an extremely difficult and time-consuming process that requires intimate knowledge of data science, data analytics, and process control. Data scientists face similar challenges in that they may be provided enormous amounts of operational data from one or more industrial automation environments with which they may wish to perform data mining, data processing, predictive modeling, or visualization, but the data scientist likely has no insight into the control logic or the industrial automation environment itself.

(2) Machine learning algorithms are designed to recognize patterns and automatically improve through training and the use of data. Many different types of machine learning models exist including classification models, regression models, clustering models, dimensionality reduction models, and deep learning models. Examples of machine learning algorithms include artificial neural networks, nearest neighbor methods, decision trees, ensemble random forests, support vector machines (SVMs), naïve Bayes methods, regressions, and more. A machine learning algorithm comprises an input layer and an output layer, wherein complex analyzation takes places between

the two layers. Various training methods are used to train machine learning algorithms wherein an algorithm is continually updated and optimized until a satisfactory model is achieved. One advantage of machine learning algorithms is their ability to learn by example, rather than needing to be manually programmed to perform a task, especially when the tasks would require a near-impossible amount of programming to perform the operations in which they are used.

(3) It is with respect to this general technical environment that aspects of the present disclosure have been contemplated. Furthermore, although a general environment is discussed, it should be understood that the described examples should not be limited to the general environment identified in the background.

(4) Overview

(5) This Overview is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

(6) Various embodiments of the present technology generally relate to solutions for improving industrial automation programming and data science capabilities with machine learning. More specifically, embodiments of the present technology include systems and methods for implementing machine learning engines within industrial programming and data science environments to improve performance, increase productivity, and add functionality. In an embodiment of the present technology, a system comprises a memory that stores executable components and a processor, operatively coupled to the memory, that executes the executable components. The executable components comprise a user interface component configured to display a programming environment for editing control logic for an industrial automation environment, wherein operational data from the industrial automation environment is accessible from within the programming environment through a data pipeline. The executable components further comprise a machine learning-based data science engine configured to process the operational data from the industrial automation environment to generate processed data for the industrial automation environment and identify a portion of the processed data relevant to a component of the control logic. The user interface component is further configured to surface the portion of the processed data in the programming environment.

(7) In an embodiment of the system, the user interface component is further configured to display a data science environment for analyzing the operational data from the industrial automation environment, wherein control data from the programming environment is accessible from within the data science environment through the data pipeline. A machine learning-based context engine is configured to process the control data from the programming environment to generate contextual data. The user interface component is further configured to surface a portion of the contextual data in the data science environment. In one implementation, the portion of the contextual data comprises a model of the control logic relevant to a selected portion of the operational data. The machine learning-based data science engine may comprise: at least one machine learning model configured to use the operational data from the industrial automation environment as input and produce the processed data for the industrial automation environment as output; and at one other machine learning model configured take the processed data as input and identify the portion of the processed data relevant to the component of the control logic. In some embodiments, the executable components further comprising a machine learning-based recommendation engine configured to, in the programming environment, generate a recommendation to add a component to based at least in part on the operational data. The component may comprise at least one of a variable, a tag, a sensor, a model, a device, an input, and an output. Surfacing the portion of the processed data in the programming environment may comprise surfacing at least one of a table and a graph in a region proximate to a portion of the control logic that is relevant to the processed data.

(8) In another embodiment of the present technology, a system comprises a memory that stores

executable components and a processor, operatively coupled to the memory, that executes the executable components. The executable components comprise a user interface component configured to display a data science environment for analyzing operational data from an industrial automation environment, wherein control data from a programming environment associated with the industrial automation environment is accessible from within the data science environment through a data pipeline. The executable components further comprise a machine learning-based context engine configured to process the control data from the programming environment to generate contextual data. The user interface component further is further configured to surface a portion of the contextual data in the data science environment.

(9) In yet another embodiment, a method of proving contextual data in an industrial programming environment comprises displaying, by a system comprising a processor, a programming environment for editing control logic for an industrial automation environment, wherein operational data from the industrial automation environment is accessible from within the programming environment through a data pipeline. The method further comprises processing, by a machine learning-based data science engine of the system, the operational data from the industrial automation environment to generate processed data for the industrial automation environment and identifying, by the machine learning-based data science engine of the system, a portion of the processed data relevant to a component of the control logic. The method further comprises surfacing the portion of the processed data in the programming environment.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Many aspects of the disclosure can be better understood with reference to the following drawings. The components in the drawings are not necessarily drawn to scale. Moreover, in the drawings, like reference numerals designate corresponding parts throughout the several views. While several embodiments are described in connection with these drawings, the disclosure is not limited to the embodiments disclosed herein. On the contrary, the intent is to cover all alternatives, modifications, and equivalents.

(2) FIG. 1 illustrates an overview of an industrial automation environment in which aspects of the present technology are implemented;

(3) FIG. 2 illustrates a user interface environment for programming control logic in accordance with some embodiments of the present technology;

(4) FIG. 3 illustrates an example of an industrial automation environment in which some embodiments of the present technology may be implemented;

(5) FIG. 4 illustrates a user interface environment for programming control logic in accordance with some embodiments of the present technology;

(6) FIG. 5 illustrates a user interface environment for programming control logic in accordance with some embodiments of the present technology;

(7) FIG. 6 illustrates a user interface environment for programming control logic in accordance with some embodiments of the present technology;

(8) FIG. 7 illustrates a user interface environment for programming control logic in accordance with some embodiments of the present technology;

(9) FIG. 8 illustrates a series of steps for utilizing machine learning in industrial automation programming environments in accordance with some embodiments of the present technology;

(10) FIG. 9 illustrates a series of steps for utilizing machine learning in industrial automation programming environments in accordance with some embodiments of the present technology;

(11) FIG. 10 illustrates a series of steps for utilizing machine learning in industrial automation programming environments in accordance with some embodiments of the present technology;

(12) FIG. 11 illustrates a series of steps for utilizing machine learning in industrial automation programming environments in accordance with some embodiments of the present technology; (13) FIG. 12 illustrates a series of steps for utilizing machine learning in industrial automation data science environments in accordance with some embodiments of the present technology; and (14) FIG. 13 illustrates an example of a computing device that may be used in accordance with some embodiments of the present technology.

(15) The drawings have not necessarily been drawn to scale. Similarly, some components or operations may not be separated into different blocks or combined into a single block for the purposes of discussion of some of the embodiments of the present technology. Moreover, while the technology is amendable to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and are described in detail below. The intention, however, is not to limit the technology to the particular embodiments described. On the contrary, the technology is intended to cover all modifications, equivalents, and alternatives falling within the scope of the technology as defined by the appended claims.

DETAILED DESCRIPTION

(16) The following description and associated figures teach the best mode of the invention. For the purpose of teaching inventive principles, some conventional aspects of the best mode may be simplified or omitted. The following claims specify the scope of the invention. Note that some aspects of the best mode may not fall within the scope of the invention as specified by the claims. Thus, those skilled in the art will appreciate variations from the best mode that fall within the scope of the invention. Those skilled in the art will appreciate that the features described below can be combined in various ways to form multiple variations of the invention. As a result, the invention is not limited to the specific examples described below, but only by the claims and their equivalents.

(17) Various embodiments of the present technology generally relate to solutions for improving industrial automation programming and data science capabilities with machine learning. More specifically, embodiments of the present technology include systems and methods for implementing machine learning engines within industrial programming and data science environments to improve performance, increase productivity, and add functionality. Generally, industrial control logic provides instructions for controlling and performing certain operations within an industrial environment via controllers (e.g., programmable logic controllers or “PLCs”), wherein the controllers execute the control code to control downstream devices and machinery. Engineers and/or programmers are generally responsible for generating the control logic used to drive industrial processes. Data scientists are generally responsible for analyzing and processing operational data produced by the industrial automation environment to find important correlations, build models, create visualizations, and generally produce information that may be useful at the enterprise level, control level, or the field level. The present technology serves to bring these environments together such that engineers may utilize operational data in a useful manner to improve control logic programming and data scientists may utilize control logic and modeling data to improve their analytic capabilities.

(18) Thus, the present technology serves to greatly enhance engineering and data science in industrial automation contexts by integrating their environments along with machine learning-based tools for assisted programming and assisted data analytics. In some embodiments, a machine learning-assisted programming environment is provided such that an engineer or programmer may be presented with recommended components, connections, and the like as they create code. In some examples, a machine learning-based engine (i.e., a “wizard”) may suggest automatic completions (“auto-completions”) of code, wherein a suggested auto-completion may include one or more components and connections. Suggested auto-completions may also include configurations or settings for components of the control code. A machine learning model, in an embodiment, consumes data from existing control code in the programming environment, or the integrated development environment (IDE), to create suggestions or automatic completions. As an engineer

writes control logic, the auto-complete program may suggest useful or relevant tags or surface relevant data in the context of the controlled process. The auto-complete program, in some embodiments, uses historical operational data to inform suggestions it makes in the programming environment.

(19) In addition to suggestions and auto-completions, the programming environment, in an embodiment, provides access to operational data as well as data science tools (e.g., data analysis tools, data presentation tools, data mining tools, modeling tools, etc.) for the user and/or the machine learning engine to use during a programming session. Operational data, in some examples, includes data from the industrial automation environment that the control code is used in. In other examples, the operational data includes data from other environments that may be similar to the environment in which the control code will be implemented.

(20) Moreover, in addition to operational data and data science tools being accessible from within the automation engineering environment or IDE, the present technology provides for automation engineering tools and data to be accessible from within a data science environment. A data science environment, as described herein, may include any computing environment in which data scientist functions, data analyst functions, data architect functions, statistician functions, database administrator functions, business analyst functions, or data and analytics manager functions may be performed. Such functions may include but are not limited to data mining, data modeling, predictive modeling, visualization, statistics, machine learning development, spreadsheet tools, systems development, enterprise resource planning, and business or enterprise-level intelligence. In an example, a data scientist may be presented with operational data collected from one or more industrial automation sites in an analytics environment while trying to mine for correlations and patterns. However, the data provides little to no information or context about the control logic, models, assets, or the like that produced the data. Thus, the data scientist may, in an example, select a piece of data and be presented with information, diagrams, or models relevant to the data. For example, a control diagram for a region proximate or in connection with a component that produced the particular chunk of data may be surfaced. In another example, a pipeline of data feeding into or out of the particular chunk of data may be surfaced. Other contextual information relevant to data that is typically available in a data science environment may be similarly surfaced, either through selection of a piece of data, selection of a menu that may provide contextual data, automatically surfaced, or the like. In an exemplary embodiment, surfacing relevant contextual data is performed in part by a machine learning-based context engine that identifies what contextual data is relevant to the particular chunk of data.

(21) In accordance with the present disclosure, an industrial asset library and wizard are provided in an industrial programming and/or automation engineering environment. An industrial asset library, in an example, provides a list of industrial assets including but not limited to models, controllers, sensors, actuators, and other devices and allows a user to choose and configure an asset. In some examples, the asset library presents for a user a list of only relevant assets that may be useful based on the control logic or target industrial environment, wherein determining which assets to include in the asset library is achieved via a machine learning engine trained to identify relevant assets based on the industrial environment and/or control logic. In another example, the industrial asset library is accessible to and used by a machine learning-based recommendation engine (i.e., the “wizard”) such that the recommendation engine can generate recommendations or auto-completions for the control logic.

(22) In some examples, the industrial asset library includes a library of machine learning models specific to industrial automation applications, wherein the library of machine learning models is accessible to automation engineers and the wizard. The library, in an embodiment, bucketizes inputs based on categories. As an example, categories that may be used to bucketize inputs include but are not limited to tag data, physical input devices, environmental inputs, economic or other macro-environment inputs, and cyclical or seasonal inputs. To provide relevant inputs, arrays of

different assets and/or characteristics may be utilized to assist automation engineers in finding valuable inputs to include in their logic.

(23) The wizard, in accordance with the present technology, helps integrate models, variables, inputs, tags, and the like into the control code. The wizard is a machine learning-backed recommendation and configuration engine that helps choose models, variables, inputs, tags, and the like as well as provides assistance with tag linking and input/output (I/O) linking. The one or more machine learning models of the wizard are streamed data to generate its predications, wherein the data may come from many different places including the live industrial environment or network databases. In one example, the wizard may provide a user with a “short list” of variables that the engineer may want to control, wherein the short list is a subset of a full list of available variables.

(24) In an example, an engineer or programmer may add an asset to the programming code in the programming environment. The wizard may then provide a list of tags that are related to the asset, available for linking to the asset, or commonly linked to the asset. Similarly, the engineer may choose to open a truncated list of tags from the library without the use of the recommendation wizard. The machine learning engine may, based on a starting set of devices, provide the engineer with the standard set of devices for a particular type of asset in the code. In another example, an engineer may be building a pipeline for a machine learning model they are implementing in the control code. In this example the wizard or asset library may be used to pull together the assets that should be used to make the machine learning model operable. The library or wizard may also suggest environmental factors, such as ambient air temperature, that are impactful in the data pipeline. Moreover, the wizard may be used to alert an engineer of any inconsistencies in the control code that may prevent it from functioning properly.

(25) In addition to the wizard and library, the present disclosure contemplates the addition of other data science tools into the IDE or programming environment. For example, operational data and industrial environment data may be accessible from within the IDE. In an example, an automation engineer using the IDE may be building control logic for a production line. While the programming environment provides information about the flow of the process, it also provides access to the historical data stream for the production line, such as the data for each tag and process object in the line. The engineer may select a tag, and a machine learning-based engine may identify inputs and tags upstream of the selected tag that likely have an influence on that tag. In this way, the engineer can rapidly find relevant data in the context of the process from within their IDE. The engineer can then assess the relevance of data points to what they are trying to improve.

(26) The present disclosure also contemplates the flip side of the previously discussed technology: the inclusion of contextual information from the programming and/or industrial environments in the data science environment. By integrating information from the programming and/or industrial environments into the data science environment, a data scientist may have far more contextual information for the data they are working with than they traditionally would. In this enhanced data science environment, connections may exist between the data science environment and the operational environment. In an exemplary embodiment, the data science environment includes an application programming interface (API) into the live environment, providing contextual information about a selected tag or column of data in some examples.

(27) A data scientist, in an example, may receive a dump of data from which they seek to find relationships, correlations, patterns, and the like that can be used later to design models. A data scientist may wish to determine which tags, datapoints, sensors, and instrumentation are relevant to solve a problem based on the statistical analysis of data. The lack of contextual information, however, may severely limit the ability of a data scientist to find important data and design effective models. Thus, integrating the data scientist's environment with the programming environment, along with machine learning-based programs, allows hints and other contextual information to be surfaced for a data scientist. Contextualizing the data with specific process steps, assets, equipment, I/O nodes, and the like allows a data scientist to accelerate the feature selection

process and identify which datapoints are relevant to a particular problem. This allows for a more streamlined and targetted data science process than mining for correlations in a non-contextualized dataset. In another example, statistics from sensor data may indicate that there is a heavy reliance one I/O node versus another. Surfacing such information about the different nodes can improve understanding and awareness of the automation process by the data scientist.

(28) In some embodiments, the programming environments and data science environments previously described are integrated into a singular, multi-purposeful environment such that the engineering and data science disciplines can effectively collaborate. In this way, a process engineer who is defining control logic for a line or asset, can leverage data science capabilities or collaborate with a data scientist to program the control logic in a more robust manner.

(29) Embodiments of the described technology may be implemented to perform variable relationship discovery. Variable relationship discovery may include finding correlations between variables, which is traditionally a manual process in which engineers use their own judgment to select variables that they think should be included in the process. However, when shifting to big data, it becomes far more difficult to identify how variables are related or correlated. Thus, in accordance with the present disclosure, machine learning models are used within the programming environment to help find potentially useful variables, models, or components for an industrial line.

(30) A relationship discovery engine comprising one or more machine learning models is used to analyze control code and consume data to identify which variables have a large impact on the process and important variable relationships. The data consumed may, in some embodiments, include operational data. A machine learning-based engine may be used to identify a variable that is heavily used in a particular industrial process but is not being used or is barely used in the control code. The programming environment thus notifies a user that the variable has been potentially overlooked and/or recommends the addition of the variable.

(31) In an example, a machine learning-based engine is used to determine that humidity is predictive of temperature increases in the industrial automation environment, but that a humidity variable is not included in the control code. Thus, a recommendation to add the humidity variable to the control logic is surfaced. In response to an acceptance of the recommendation, the variable may be added to the control logic and configured. In another example, variable relationship discovery is performed with respect to big data mining and data repositories. In such an example, a machine learning-based engine analyzes a code repository to determine dominant variables in a codebase. In certain implementations, the engine may look at various types of data available in the code base, including, in some instances, a comment section. Thus, when an engineer is programming an industrial line with the assistance of a machine learning engine, the engine may recognize that there are 100 tags available and three of them have not been used anywhere in the code. The engine further recognizes that those three missing tags are used in many other code repositories and informs the user of how the tags are typically used.

(32) In some examples the machine learning-based engine is used to recommend the insertion of a loop, a function, a variable, or the like as well as input to the component and assistance with configuring and/or connecting the component in the control code. Conversely, a machine learning-based engine may identify that a variable that is heavily used in the control code is absent or under-used in the data pipeline, suggesting that its inclusion in the pipeline and model may yield better predictions.

(33) Embodiments of the described technology may be further implemented to perform variable slimming. If, during runtime, extra variables are being output by the control logic that are not needed, computing power and storage are wasted. Data pipelines that are over-inclusive waste storage space and processing power, and extraneous data may reduce the predictive capability of some models. Thus, a machine learning-based engine may be used to inform, during a programming session, that a variable that is in the control program is not commonly used, isn't generally useful, or isn't useful in the particular industrial line based on historical process data. The

engine may therefore recommend removing the variable from the control logic or automatically analyze datasets for extraneous data and eliminate the data from the pipeline.

(34) In accordance with the present disclosure, a machine learning model comprises one or more machine learning algorithms that are trained based on historical data and/or training data. A machine learning model may employ one or more machine learning algorithms through which data can be analyzed to identify patterns, make decisions, make predictions, or similarly produce output that can inform control code and/or parameters. Different types of machine learning models may be used in accordance with the present technology including but not limited to classification models, regression models, clustering models, dimensionality reduction models, and deep learning models. Examples of machine learning algorithms that may be employed solely or in conjunction with one another include artificial neural networks, nearest neighbor methods, decision trees, ensemble random forests, support vector machines (SVMs), naïve Bayes methods, regressions, or similar machine learning techniques or combinations thereof capable of predicting output based on input data. Determining which machine learning methods to use may depend on the specific purpose or functions required for a particular industrial setting, the specific programming application used, or similar requirements. A machine learning engine, in some examples, outputs a prediction about what components might be beneficial to add or remove from the control logic. Similarly, a machine learning engine may output a recommendation to add or remove one or more components from the control logic, or a notification that a component that should be used or is typically used is missing. In other examples the machine learning engine outputs the predicted components or settings directly for integration into the control code. In yet another example, a machine learning engine provides a model of the control code or the industrial automation environment in such a way that a data scientist may use the contextual information to inform their analyses. Other outputs with a similar purpose may exist and are contemplated herein.

(35) FIG. 1 illustrates an overview of an industrial automation environment wherein engineering and data science environments are integrated as described herein. FIG. 1 includes automation environment **100**. Automation environment **100** comprises physical system **101** including controlled process **102**. Automation environment **100** further comprises digital twin **103** and modeling environment **110**. Modeling environment **110** comprises historical observations **111**, machine learning **112**, instructions and first principles **113**, and control logic **114**. Automation environment **100** further comprises data scientist **121**, engineer **122**, model **130**, controller **140**, actuators **150**, and sensors **160**.

(36) In the example of FIG. 1, digital twin **103** of physical system **101** is provided to modeling environment **110**, wherein modeling environment **110** is used by both data scientist **121** and engineer **122**. In one embodiment, data scientist **121** accessed modeling environment **110** through a different application than engineer **122**. In an alternative embodiment, data scientist **121** and engineer **122** use the same application for their data science and engineering purposes. In either embodiment, information from the data science portion of the modeling environment and the engineering portion of the modeling environment is shared and accessible for both functions—data scientist **121** can access contextual engineering data in performing data science tasks and engineer **122** can access operational data and data science tools. As shown, a machine learning-based engine is provided in both the engineering environment and the data science environment. Functionality of the machine learning-based engines may include generating recommendations, auto-completion functionality, providing contextual information, and other functionalities described herein. Instructions and first principles **113** is used to generate control logic **114**. Engineer **122** may utilize operational data or similar from the data science environment in producing both instructions and first principles **113** and control logic **114**. In some examples, a machine learning-based recommendation engine recommends adding components or editing control logic based in part on historical observations **111** and machine learning **112**.

(37) Model **130** is representative of one or more machine learning models implemented in control

code for controlling controlled process **102**. The one or more machine learning models may include predictive models for generating forward inferences and diagnostic models for identifying causal relationships. Model **130** includes one or more machine learning models that produces control logic as output for controller **140**. Controller **140** runs one or more prescriptive models for optimizing controlled process **102** or a portion of controlled process **102**. Controller **140** controls actuators **150** which actuate physical system **101** to perform controlled process **102**. Actuators **150** comprise one or more machine learning models for autonomous driving of physical system **101**. Sensors **160** collect data from physical system **101** running controlled process **102**. Sensors **160** comprise one or more machine learning models for describing output and current state from controlled process **102**. Output from controlled process **102** is also provided to modeling environment **110** and may be used for data science and/or engineering purposes.

(38) FIG. 2 illustrates a graphical user interface (GUI) of an industrial automation programming environment in accordance with some embodiments of the present technology. FIG. 2 comprises GUI **200**, which is representative of any user interface for writing and editing industrial control code. In some examples, GUI **200** is representative of modeling environment **110** from FIG. 1. GUI **200** includes workspace **210** for writing and editing control code. Workspace **210** includes control logic **220**, a current project for control code for an industrial automation process. GUI **200** also includes wizard **230**. In the present example, wizard **230** has recommended adding component **231**, component **232**, link **233**, component **234**, link **235**, and link **236** to control logic **220**.

(39) Wizard **230** comprises one or more machine learning models for predicting and/or recommending components for control logic. Wizard **230** may be configured to auto-complete all or a portion of existing control logic in workspace **210**. Wizard **230** may alternatively be configured to surface recommendations to add components to existing control logic in workspace **210**, wherein the recommendations may be verbal or may display the recommended additions themselves as is shown in the example of FIG. 2. In some examples a user of the engineering environment shown in FIG. 2 selects wizard **230** to trigger it to generate and show recommendations. In other examples, wizard **230** is displayed just to show that the wizard is operating and will automatically surface recommendations as they are generated.

(40) FIG. 3 illustrates an example of an industrial automation environment that may be representative of industrial automation environments as discussed herein. The industrial automation environment of FIG. 3 comprises enterprise environment **310**, control environment **320**, and field environment **330**. The industrial automation environment of FIG. 3 may include fewer or additional sub-environments than those shown. Likewise, the sub-environments of the industrial automation environment of FIG. 3 may include fewer or additional components, assets, or connections than shown.

(41) Enterprise environment **310** comprises engineering and design environment **311**, visualization environment **312**, and information environment **313**. Control environment **320** comprises database server **321**, management servers **322**, web server **323**, scheduling server **324**, and application server **325**. Each of database server **321**, management servers **322**, web server **323**, scheduling server **324**, and application server **325** may be representative of a single server or a plurality of servers. Field environment **330** comprises PLC **331**, which is coupled to human-machine interface (HMI) **332** and machine **133**. Field environment **330** also comprises PLC **334**, which is coupled to machine **335**. Field environment **330** further comprises PLC **336**, which is coupled to HMI **373** and machine **338**. Field environment **330** also comprises machine learning asset (MLA) **339**, which is coupled to HMI **340**.

(42) In some examples, engineering and design environment **311** is representative of any connected devices or environments on which control logic is programmed for operating devices in field environment **330**. Visualization environment **312** is representative of any connected devices or environments on which operational data is viewed and/or analyzed. Information environment **313** is representative of any connected devices or environments on the enterprise level on which any

other industrial automation information relevant to field environment **330** can be viewed, processed, analyzed, generated, or the like. Assets of control environment **320** are illustrative in nature such that one, none, or any combination of known server types may be in communication with the industrial automation environment of FIG. **3**. Similarly, field environment **330** is illustrative in nature such that one, none, or any combination of assets may be present.

(43) Each of PLC **331**, PLC **334**, and PLC **336** is representative of one or more programmable logic controllers, which may be coupled to one or more devices, machines, sensors, actuators, interfaces, or other asset types. Each of machine **333**, machine **335**, and machine **338** is representative of any industrial machine relevant to the industrial automation environment of FIG. **3**. Each of HMI **332**, HMI **337**, and HMI **340** is representative of any form of human-machine interface on which a user or operator in field environment **330** can view and/or interact with connected assets.

(44) Machine learning asset **339** is representative of any machine learning model implemented within the industrial automation environment of FIG. **3** as described herein. As previously discussed, machine learning asset **339** may take input from field environment **330** or external sources, such as any server in control environment **320**, to generate an output useful to controlling any processes or assets in field environment **330**. Machine learning asset **339** may be implemented in a fully closed-loop process or may receive external data for use in generating predictions and/or outputs.

(45) FIG. **4** illustrates an example of a programming environment in which machine learning assets can be programmed into an industrial process. FIG. **4** includes user interface **400**, which is representative of any user interface for generating control code. In some examples, user interface **400** is representative of modeling environment **110** from FIG. **1**. In some examples, user interface **400** is running in engineering and design environment **311** from FIG. **3**. User interface **400** includes explorer **410**, wherein explorer **410** comprises industrial asset libraries, the industrial asset libraries including model library **411**, programmable assets library **412**, and tags library **413**. User interface **400** includes workspace **440** comprising industrial line **420**. Industrial line **420** includes database **421**, external variable **422**, machine learning asset **423**, HMI **424**, PLC **425**, HMI **426**, machine **427**, temperature sensor **428**, and speed sensor **429**. User interface **400** further includes wizard **430** and suggestion **431**.

(46) In industrial line **420**, database **421** and external variable **422** provide input to machine learning asset **423**. Database **421** may comprise a model database that is operatively coupled to the industrial line such that machine learning asset **423** can be swapped with other models stored in database **421**. External variable **422** may be representative of any external information that may be used as input to machine learning asset **423**. Machine learning asset **423** is coupled to HMI **424**, which displays information relevant to the status or control of machine learning asset **423**. Machine learning asset **423** is coupled to PLC **425**, which is coupled to HMI **426**. HMI **426** displays information relevant to the status or control of PLC **425**. Machine **427** is coupled to and driven by PLC **425**. Temperature sensor **428** and speed sensor **429** measure temperature and speed associated with machine **427**.

(47) A programmer may develop or edit industrial line **420** within user interface **400** in accordance with the present disclosure. A programmer has access to model library **411** comprising machine learning models that can be used in industrial line **420**. A programmer also has access to programmable assets library **412** comprising programmable assets that can be used in industrial line **420**. A programmer also has access to tags library **413** comprising tags that can be used in industrial line **420**. In some examples, assets may be provided such that a programmer can “drag and drop” assets into their project such as industrial line **420** and connect assets to the existing model in the same way that other assets are typically connected in the programming environment. In some examples, the asset library presents for a user only a list of relevant assets that may be useful based on the control logic or target industrial environment, wherein determining which

assets to show in the asset library is achieved via a machine learning engine trained to identify relevant assets based on the industrial environment and/or control logic. In another example, the industrial asset library is accessible to and used by wizard **430** such that the recommendation engine can generate recommendations or auto-completions for the control logic.

(48) Wizard **430** helps integrate models, variables, inputs, tags, and the like into industrial line **420**. Wizard **430** is a machine learning-based recommendation and configuration engine that helps choose models, variables, inputs, tags, and the like as well as provides assistance with tag linking and I/O linking. Wizard **430** comprises one or more machine learning models. The one or more machine learning models of the wizard are streamed data to generate predications, wherein the data may come from many different places including the live industrial environment or network databases. In one example, the wizard may provide a user with a “short list” of assets that the engineer may want to add, wherein the short list is a subset of a full list of available assets.

(49) In the present example, wizard **430** has produced suggestion **431**, wherein suggestion **431** suggests adding PLC_2 to industrial line **420**. In an example, an engineer or programmer may accept the recommendation to add an asset to industrial line **420** in the programming environment. Wizard **430** may then provide a list of tags that are related to the asset, available for linking to the asset, or commonly linked to the asset. Similarly, the engineer may choose to open a truncated list of tags from the library without the use of wizard **430**.

(50) FIG. 5 illustrates a user interface of an industrial automation programming environment for performing variable relationship discovery in accordance with some embodiments of the present technology. FIG. 5 comprises GUI **500**, which is representative of any user interface for writing and editing industrial control code. In some examples, GUI **500** is representative of modeling environment **110** from FIG. 1. In some examples, GUI **500** may be running in engineering and design environment **311** from FIG. 3. GUI **500** includes workspace **520** for writing and editing control code. Workspace **520** includes control logic **510**. GUI **500** also includes wizard **530** and recommendation **531**. In the present example, wizard **230** has surfaced recommendations to add component **532**, component **533**, link **534**, component **535**, and link **536** to control logic **510**. Wizard **530** has also surfaced a recommendation to add a tag in recommendation **531**.

(51) Wizard **530** is representative of any machine learning-based engine capable of recommending industrial components for control code. In some examples wizard **230** consumes data from existing control code (i.e., control logic **510**) in the IDE to create suggestions and automatic completions as shown in the present example. As an automation engineer writes control logic, the wizard **530** may suggest useful or relevant tags or surface relevant data in the context of control logic **510**. Wizard **530**, in some embodiments, uses historical operational data to inform suggestions it makes in the IDE.

(52) Variable relationship discovery, in accordance with the present example, includes the use of machine learning models (i.e., those within wizard **530**) for finding correlations between variables to help discover potentially useful variables, models, or components for an industrial line. Wizard **530** may serve as a relationship discovery engine comprising one or more machine learning models used to analyze control logic **510** and consume data to identify which variables have a large impact on the process and important variable relationships. The data consumed may, in some embodiments, include operational data. Wizard **530** may be used to identify a variable that is heavily used in an associated industrial process but is not being used in control logic **510**. Wizard **530** thus surfaces recommendation **531** alerting the user that the variable has been potentially overlooked and recommends the inclusion of the variable.

(53) In some examples, wizard **530** is used to recommend the insertion of a loop, a function, a variable, or the like as well as input to the component and assist with configuring and/or connecting the component in the control code. Conversely wizard **530** may identify that a variable that is heavily used in the control code is absent or under-used in the data pipeline, suggesting that its inclusion in the pipeline and model may yield better predictions.

(54) FIG. 6 illustrates a user interface of an industrial automation programming environment for performing variable slimming in accordance with some embodiments of the present technology. FIG. 6 comprises GUI 600, which is representative of any user interface for writing and editing industrial control code. In some examples, GUI 600 is representative of modeling environment 110 from FIG. 1. In some examples, GUI 500 may be running in engineering and design environment 311 from FIG. 3. GUI 600 includes workspace 610, wherein workspace 610 comprises control logic 620 comprising tag 632. GUI 600 further comprises wizard 630 and recommendation 631. Wizard 630 is a machine learning-based engine comprising one or more machine learning models that may be used to inform, during a programming session, that a variable in the control program is not commonly used, is not generally useful, or is not useful in the particular industrial line based on historical process data. Wizard 630 may therefore recommend removing the variable from the control logic or automatically analyze datasets for extraneous data and eliminate the data from the pipeline.

(55) In the example of FIG. 6, wizard 630 has recommended removing tag 632, wherein the recommendation is expressed in a verbal format in recommendation 631 as well as with an indicator at tag 632 that it should be removed. In an example, a user of the programming environment may accept the recommendation to remove tag 632. In some embodiments, acceptance of the recommendation may include manually removing tag 632. In other embodiments, accepting the recommendation may include selecting a button to select the recommendation, at which time wizard 630 may remove tag 632 itself.

(56) FIG. 7 illustrates a user interface environment of an industrial automation programming environment integrated with an industrial data science environment. FIG. 7 includes GUI 700. GUI 700 includes workspace 710 comprising control logic 720, wherein control logic 720 comprises PLC 721. GUI 700 further includes wizard 730. GUI 700 further includes data table 740, wherein data table 740 comprises operational data related to PLC 721 of control logic 720. A user of the programming environment shown in FIG. 7 has used the “data access” menu to access operational data from PLC 721. However, in other embodiments, operational data may be surfaced in response to selection of PLC 721 in the GUI or may be automatically surfaced in some circumstances. The operational data related to PLC 721 is shown in a tabular format in the present example. However, operational data may be presented in a variety of ways including tables, charts, graphs, raw data format, data pipelines, or similar.

(57) In addition to the presentation of operational data, the technology herein provides for access to data science tools, such that an automation engineer working in GUI 700 may perform analyses or use the operational data to extract information useful to their engineering tasks.

(58) In an exemplary embodiment, data table 740 is surfaced as a result of actions taken by wizard 730. Wizard 730, in some examples, employs one or more machine learning models to find data relevant to control logic 720 and present the data in a way that may be useful or provide context for the automation engineer. Moreover, wizard 730 may, based on the operational data presented in data table 740, make one or more recommendations to add or remove inputs or outputs from PLC 721.

(59) FIG. 8 illustrates process 800 performed by a computing system for using an industrial programming wizard to assist writing or editing control logic for controlling industrial automation processes. Step 805 comprises, in a machine learning-based recommendation engine, generating a recommendation to add a component to the control logic based on an existing portion of the control logic. In generating the recommendation, the machine learning-based recommendation engine may employ one or more machine learning models to find that the component should be used or is typically used in similar environments. In step 810, a notification component surfaces the recommendation to add the component to the control logic in a user interface of the programming environment. In response to noticing the recommendation, a user may choose to accept or decline the recommendation to add the component.

(60) In step **815**, in response to an acceptance of the recommendation, a programming component adds the component to the control logic. Once the component has been added to the control logic, it may require configuration in order to work properly in the intended environment. In step **820**, a configuration component configures the component based at least in part on the existing portion of the control logic. In some examples, configuring the component may include the configuration component and/or the machine learning-based recommendation engine guiding the user through configuration of the component.

(61) FIG. **9** illustrates process **900** performed by a computing system for performing variable relationship discovery to assist writing or editing control logic for controlling an industrial automation process. In step **905**, a machine learning-based analysis engine identifies a variable that is available to be utilized in the control logic for controlling an industrial automation environment. In some examples of step **905**, identifying a variable that is available to be utilized comprises finding that the variable that is heavily used in an associated industrial process but is not being used in the control logic. In other examples of step **905**, identifying the variable comprises accessing a control code repository and concluding that the variable is often used in the same or similar programs. In step **910**, the machine learning-based analysis engine determines that the variable is not utilized in the control logic. Alternatively, step **910** may comprise determining that the variable is under-utilized in the control logic. In step **915**, a recommendation component surfaces a recommendation to add the variable to the control logic. Process **900** may further include receiving an acceptance or rejection of the recommendation and adding the variable to the control logic.

(62) FIG. **10** illustrates process **1000** performed by a computing system for performing variable slimming to assist in editing control logic for controlling an industrial automation process. In step **1005**, a machine learning-based analysis engine performs an analysis of operational data from an industrial automation environment. In step **1010**, the machine learning-based analysis engine performs an analysis of the control logic for controlling the industrial automation environment. In step **1015**, the machine learning-based analysis engine identifies, based on the analysis of the operational data and the analysis of the control logic, a variable that is in the control logic but is not used in the operational data. In step **1020**, a notification component surfaces a notification that the variable is in the control logic but is not used in the operational data. In some examples, the notification that the variable is in the control logic but is not used in the operational data includes a recommendation to remove the variable from the control logic. Process **1000** may further include receiving an acceptance or rejection of a recommendation to remove the variable and removing the variable from the control logic.

(63) FIG. **11** illustrates process **1100** performed by a computing system for providing contextual data in an industrial programming environment associated with an industrial automation environment. In step **1105**, a user interface component displays the programming environment for editing control logic associated with an industrial automation environment, wherein the operational data from the industrial automation environment is accessible from within the programming environment through a data pipeline. In step **1110**, a machine learning-based data science engine processes the operational data from the industrial automation environment to generate processed data for the industrial automation environment, wherein processed data may include any data that is formatted and presented in a useful way to a user of the programming environment. In step **1115**, the machine learning-based data science engine identifies a portion of the processed data relevant to a component of the control logic. In step **1120**, the user interface surfaces the portion of the processed data in the programming environment.

(64) FIG. **12** illustrates process **1200** performed by a computing system for providing contextual data in a data science environment associated with an industrial automation environment. In step **1205**, a user interface component displays a data science environment for analyzing operational data from an industrial automation environment, wherein control data from a programming environment associated with the industrial automation environment is accessible from within the

data science environment through a data pipeline. In step **1210**, a machine learning-based context engine processes the control data from the programming environment to generate contextual data. In step **1215**, the user interface component surfaces a portion of the contextual data in the data science environment. In some examples, the contextual data comprises a model or similar rendering of the control code or a portion of the control code as it may be displayed in the programming environment.

(65) FIG. **13** illustrates computing system **1301** to perform machine learning assisted programming and data analytics according to an implementation of the present technology. Computing system **1301** is representative of any system or collection of systems with which the various operational architectures, processes, scenarios, and sequences disclosed herein for utilizing machine learning models within industrial programming and data science environments may be employed. Computing system **1301** may be implemented as a single apparatus, system, or device or may be implemented in a distributed manner as multiple apparatuses, systems, or devices. Computing system **1301** includes, but is not limited to, processing system **1302**, storage system **1303**, software **1305**, communication interface system **1307**, and user interface system **1309** (optional). Processing system **1302** is operatively coupled with storage system **1303**, communication interface system **1307**, and user interface system **1309**.

(66) Processing system **1302** loads and executes software **1305** from storage system **1303**. Software **1305** includes and implements machine learning assisted control programming **1306**, which is representative of any of the programming and analytic processes discussed with respect to the preceding Figures, including but not limited to industrial asset libraries, wizards, variable relationship discovery, and variable slimming. When executed by processing system **1302** to provide model implementation functions, software **1305** directs processing system **1302** to operate as described herein for at least the various processes, operational scenarios, and sequences discussed in the foregoing implementations. Computing system **1301** may optionally include additional devices, features, or functionality not discussed for purposes of brevity.

(67) Referring still to FIG. **13**, processing system **1302** may comprise a micro-processor and other circuitry that retrieves and executes software **1305** from storage system **1303**. Processing system **1302** may be implemented within a single processing device but may also be distributed across multiple processing devices or sub-systems that cooperate in executing program instructions. Examples of processing system **1302** include general purpose central processing units, graphical processing units, application specific processors, and logic devices, as well as any other type of processing device, combinations, or variations thereof.

(68) Storage system **1303** may comprise any computer readable storage media readable by processing system **1302** and capable of storing software **1305**. Storage system **1303** may include volatile and nonvolatile, removable and non-removable media implemented in any method or technology for storage of information, such as computer readable instructions, data structures, program modules, or other data. Examples of storage media include random access memory, read only memory, magnetic disks, optical disks, optical media, flash memory, virtual memory and non-virtual memory, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other suitable storage media. In no case is the computer readable storage media a propagated signal.

(69) In addition to computer readable storage media, in some implementations storage system **1303** may also include computer readable communication media over which at least some of software **1305** may be communicated internally or externally. Storage system **1303** may be implemented as a single storage device but may also be implemented across multiple storage devices or sub-systems co-located or distributed relative to each other. Storage system **1303** may comprise additional elements, such as a controller, capable of communicating with processing system **1302** or possibly other systems.

(70) Software **1305** (including machine learning assisted control programming **1306**) may be

implemented in program instructions and among other functions may, when executed by processing system **1302**, direct processing system **1302** to operate as described with respect to the various operational scenarios, sequences, and processes illustrated herein. For example, software **1305** may include program instructions for performing variable slimming in control logic for industrial automation environments as described herein.

(71) In particular, the program instructions may include various components or modules that cooperate or otherwise interact to carry out the various processes and operational scenarios described herein. The various components or modules may be embodied in compiled or interpreted instructions, or in some other variation or combination of instructions. The various components or modules may be executed in a synchronous or asynchronous manner, serially or in parallel, in a single threaded environment or multi-threaded, or in accordance with any other suitable execution paradigm, variation, or combination thereof. Software **1305** may include additional processes, programs, or components, such as operating system software, virtualization software, or other application software. Software **1305** may also comprise firmware or some other form of machine-readable processing instructions executable by processing system **1302**.

(72) In general, software **1305** may, when loaded into processing system **1302** and executed, transform a suitable apparatus, system, or device (of which computing system **1301** is representative) overall from a general-purpose computing system into a special-purpose computing system customized to provide machine learning functionality to industrial programming and data science environments as described herein. Indeed, encoding software **1305** on storage system **1303** may transform the physical structure of storage system **1303**. The specific transformation of the physical structure may depend on various factors in different implementations of this description. Examples of such factors may include, but are not limited to, the technology used to implement the storage media of storage system **1303** and whether the computer-storage media are characterized as primary or secondary storage, as well as other factors.

(73) For example, if the computer readable storage media are implemented as semiconductor-based memory, software **1305** may transform the physical state of the semiconductor memory when the program instructions are encoded therein, such as by transforming the state of transistors, capacitors, or other discrete circuit elements constituting the semiconductor memory. A similar transformation may occur with respect to magnetic or optical media. Other transformations of physical media are possible without departing from the scope of the present description, with the foregoing examples provided only to facilitate the present discussion.

(74) Communication interface system **1307** may include communication connections and devices that allow for communication with other computing systems (not shown) over communication networks (not shown). Examples of connections and devices that together allow for inter-system communication may include network interface cards, antennas, power amplifiers, radiofrequency circuitry, transceivers, and other communication circuitry. The connections and devices may communicate over communication media to exchange communications with other computing systems or networks of systems, such as metal, glass, air, or any other suitable communication media. The aforementioned media, connections, and devices are well known and need not be discussed at length here.

(75) Communication between computing system **1301** and other computing systems (not shown), may occur over a communication network or networks and in accordance with various communication protocols, combinations of protocols, or variations thereof. Examples include intranets, internets, the Internet, local area networks, wide area networks, wireless networks, wired networks, virtual networks, software defined networks, data center buses and backplanes, or any other type of network, combination of networks, or variation thereof. The aforementioned communication networks and protocols are well known and need not be discussed at length here.

(76) While some examples provided herein are described in the context of a firmware extension development or deployment device, it should be understood that the condition systems and

methods described herein are not limited to such embodiments and may apply to a variety of other extension implementation environments and their associated systems. As will be appreciated by one skilled in the art, aspects of the present invention may be embodied as a system, method, computer program product, and other configurable systems. Accordingly, aspects of the present invention may take the form of an entirely hardware embodiment, an entirely software embodiment (including firmware, resident software, micro-code, etc.) or an embodiment combining software and hardware aspects that may all generally be referred to herein as a “circuit,” “module” or “system.” Furthermore, aspects of the present invention may take the form of a computer program product embodied in one or more computer readable medium(s) having computer readable program code embodied thereon.

(77) Unless the context clearly requires otherwise, throughout the description and the claims, the words “comprise,” “comprising,” and the like are to be construed in an inclusive sense, as opposed to an exclusive or exhaustive sense; that is to say, in the sense of “including, but not limited to.” As used herein, the terms “connected,” “coupled,” or any variant thereof means any connection or coupling, either direct or indirect, between two or more elements; the coupling or connection between the elements can be physical, logical, or a combination thereof. Additionally, the words “herein,” “above,” “below,” and words of similar import, when used in this application, refer to this application as a whole and not to any particular portions of this application. Where the context permits, words in the above Detailed Description using the singular or plural number may also include the plural or singular number respectively. The word “or,” in reference to a list of two or more items, covers all of the following interpretations of the word: any of the items in the list, all of the items in the list, and any combination of the items in the list.

(78) The phrases “in some embodiments,” “according to some embodiments,” “in the embodiments shown,” “in other embodiments,” and the like generally mean the particular feature, structure, or characteristic following the phrase is included in at least one implementation of the present technology, and may be included in more than one implementation. In addition, such phrases do not necessarily refer to the same embodiments or different embodiments.

(79) The above Detailed Description of examples of the technology is not intended to be exhaustive or to limit the technology to the precise form disclosed above. While specific examples for the technology are described above for illustrative purposes, various equivalent modifications are possible within the scope of the technology, as those skilled in the relevant art will recognize. For example, while processes or blocks are presented in a given order, alternative implementations may perform routines having steps, or employ systems having blocks, in a different order, and some processes or blocks may be deleted, moved, added, subdivided, combined, and/or modified to provide alternative or subcombinations. Each of these processes or blocks may be implemented in a variety of different ways. Also, while processes or blocks are at times shown as being performed in series, these processes or blocks may instead be performed or implemented in parallel or may be performed at different times. Further any specific numbers noted herein are only examples: alternative implementations may employ differing values or ranges.

(80) The teachings of the technology provided herein can be applied to other systems, not necessarily the system described above. The elements and acts of the various examples described above can be combined to provide further implementations of the technology. Some alternative implementations of the technology may include not only additional elements to those implementations noted above, but also may include fewer elements.

(81) These and other changes can be made to the technology in light of the above Detailed Description. While the above description describes certain examples of the technology, and describes the best mode contemplated, no matter how detailed the above appears in text, the technology can be practiced in many ways. Details of the system may vary considerably in its specific implementation, while still being encompassed by the technology disclosed herein. As noted above, particular terminology used when describing certain features or aspects of the

terminology should not be taken to imply that the terminology is being redefined herein to be restricted to any specific characteristics, features, or aspects of the technology with which that terminology is associated. In general, the terms used in the following claims should not be construed to limit the technology to the specific examples disclosed in the specification, unless the above Detailed Description section explicitly defines such terms. Accordingly, the actual scope of the technology encompasses not only the disclosed examples, but also all equivalent ways of practicing or implementing the technology under the claims.

(82) To reduce the number of claims, certain aspects of the technology are presented below in certain claim forms, but the applicant contemplates the various aspects of the technology in any number of claim forms. For example, while only one aspect of the technology is recited as a computer-readable medium claim, other aspects may likewise be embodied as a computer-readable medium claim, or in other forms, such as being embodied in a means-plus-function claim. Any claims intended to be treated under 35 U.S.C. § 112(f) will begin with the words “means for” but use of the term “for” in any other context is not intended to invoke treatment under 35 U.S.C. § 112(f). Accordingly, the applicant reserves the right to pursue additional claims after filing this application to pursue such additional claim forms, in either this application or in a continuing application.

Claims

1. A system comprising: a memory that stores executable components; and a processor, operatively coupled to the memory, that executes the executable components, the executable components comprising: a user interface component configured to display, in a user interface, a programming environment comprising a block-based representation of control logic executable by a programmable logic controller (PLC) in an industrial automation environment, wherein operational data from the industrial automation environment is accessible from within the programming environment through a data pipeline, and wherein the control logic is editable within the programming environment; and a machine learning-based data science engine configured to: process the operational data from the industrial automation environment to generate processed data for the industrial automation environment; and identify a portion of the processed data related to the control logic; and the user interface component further configured to display, in the user interface, the portion of the processed data in the programming environment.
2. The system of claim 1, the executable components further comprising: the user interface component further configured to display a data science environment for analyzing the operational data from the industrial automation environment, wherein control data from the programming environment is accessible from within the data science environment through the data pipeline; a machine learning-based context engine configured to process the control data from the programming environment to generate contextual data; and the user interface component further configured to display, in the user interface a portion of the contextual data in the data science environment.
3. The system of claim 2, wherein the portion of the contextual data comprises a model of the control logic related to a selected portion of the operational data.
4. The system of claim 1, wherein the machine learning-based data science engine comprises: at least one machine learning model configured to use the operational data from the industrial automation environment as input and produce the processed data for the industrial automation environment as output; and at least one other machine learning model configured to take the processed data as input and identify the portion of the processed data related to the control logic.
5. The system of claim 1, the executable components further comprising a machine learning-based recommendation engine configured to, in the programming environment, generate a recommendation to add a new component to the control logic based at least in part on the

operational data.

6. The system of claim 5, wherein the new component comprises at least one of a variable, a tag, a sensor, a model, a device, an input, and an output.

7. The system of claim 1, wherein displaying the portion of the processed data in the programming environment comprises surfacing at least one of a table and a graph in a region of the user interface proximate to an icon of the PLC.

8. A system comprising: a memory that stores executable components; and a processor, operatively coupled to the memory, that executes the executable components, the executable components comprising: a user interface component configured to: display, in a user interface, a data science environment for analyzing operational data from an industrial automation environment, wherein control data from a programming environment associated with the industrial automation environment is accessible from within the data science environment through a data pipeline, and receive, via the user interface, a user selection of a portion of the operational data; a machine learning-based context engine configured to: process the control data from the programming environment to generate contextual data, and identify a portion of the contextual data related to the selected portion of the operational data; and the user interface component further configured to display, in the user interface, the portion of the contextual data in the data science environment.

9. The system of claim 8, the executable components further comprising: the user interface component further configured to display, in the user interface, the programming environment comprising a block-based representation of control logic executable by a programmable logic controller (PLC) in the industrial automation environment, wherein the operational data from the industrial automation environment is accessible from within the programming environment through the data pipeline, and wherein the control logic is editable within the programming environment; and a machine learning-based data science engine configured to: process the operational data from the industrial automation environment to generate processed data for the industrial automation environment; and identify a portion of the processed data related to the control logic; and the user interface component further configured to display, in the user interface, the portion of the processed data in the programming environment.

10. The system of claim 9, wherein the machine learning-based data science engine comprises: at least one machine learning model configured to use the operational data from the industrial automation environment as input and produce the processed data for the industrial automation environment as output; and at least one other machine learning model configured to take the processed data as input and identify the portion of the processed data relevant to the component of the control logic.

11. The system of claim 9, wherein displaying the portion of the processed data in the programming environment comprises displaying at least one of a table and a graph in a region proximate to a portion of the control logic that is relevant to the contextual data.

12. The system of claim 9, the executable components further comprising a machine learning-based recommendation engine configured to, in the programming environment, generate a recommendation to add a new component to the control logic based at least in part on the operational data.

13. The system of claim 12, wherein the new component comprises at least one of a variable, a tag, a sensor, a model, a device, an input, and an output.

14. The system of claim 8, wherein the portion of the contextual data comprises a model of the control data.

15. A method of proving contextual data in an industrial programming environment, the method comprising: displaying, by a system comprising a processor and in a user interface, a programming environment comprising a block-based representation of control logic executable by a programmable logic controller (PLC) in an industrial automation environment, wherein operational data from the industrial automation environment is accessible from within the programming

environment through a data pipeline, and wherein the control logic is editable within the programming environment; and processing, by a machine learning-based data science engine of the system, the operational data from the industrial automation environment to generate processed data for the industrial automation environment; and identifying, by the machine learning-based data science engine of the system, a portion of the processed data related to the control logic; and displaying, by the system and in the user interface, the portion of the processed data in the programming environment.

16. The method of claim 15 further comprising: displaying, by the system and in the user interface, a data science environment for analyzing the operational data from the industrial automation environment, wherein control data from the programming environment is accessible from within the data science environment through the data pipeline; processing, by a machine learning-based context engine of the system, the control data from the programming environment to generate contextual data; and displaying, by the system and in the user interface, a portion of the contextual data in the data science environment.

17. The method of claim 16 wherein the portion of the contextual data comprises a model of the control logic relevant to a selected portion of the operational data.

18. The method of claim 15 wherein the machine learning-based data science engine comprises: at least one machine learning model configured to use the operational data from the industrial automation environment as input and produce the processed data for the industrial automation environment as output; and at least one other machine learning model configured to take the processed data as input and identify the portion of the processed data related to the control logic.

19. The method of claim 15 further comprising, by a learning-based recommendation engine of the system, in the programming environment, generating a recommendation to add a component to the control logic based at least in part on the operational data.

20. The method of claim 19 wherein the component comprises at least one of a variable, a tag, a sensor, a model, a device, an input, and an output.
