

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411786
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Cai; Jiongjun

Data remote transmission and charging circuit applied to VR device and device thereof

Abstract

A data remote transmission and charging circuit applied to a VR device and a data remote transmission and charging device include a first data sending and receiving circuit, a hub circuit, a second data sending and receiving circuit, a voltage stabilizing circuit, a boost circuit, and a charging circuit. The first data sending and receiving circuit is electrically connected to a data source terminal and the hub circuit. The hub circuit is electrically connected to the second data sending and receiving circuit and the voltage stabilizing circuit. The second data sending and receiving circuit is electrically connected to the VR device and the boost circuit. The voltage stabilizing circuit is electrically connected to the boost circuit. The boost circuit is electrically connected to the charging circuit. By providing above structure, data remote transmission between the data source terminal and the VR device is realized.

Inventors: Cai; Jiongjun (Shenzhen, CN)

Applicant: SHENZHEN DEONE INNOVATION TECHNOLOGY CO., LTD (Shenzhen, CN)

Family ID: 85364922

Assignee: SHENZHEN DEONE INNOVATION TECHNOLOGY CO., LTD (Shenzhen, CN)

Appl. No.: 18/297195

Filed: April 07, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240104039 A1	Mar. 28, 2024

Foreign Application Priority Data

CN	202222536193.5	Sep. 26, 2022
----	----------------	---------------

Publication Classification

Int. Cl.: G06F13/38 (20060101); G06F13/42 (20060101); H02J7/00 (20060101)

U.S. Cl.:

CPC G06F13/382 (20130101); G06F13/4282 (20130101); H02J7/007 (20130101); G06F2213/0042 (20130101)

Field of Classification Search

CPC: G06F (13/382); G06F (13/4282); G06F (2213/0042); H02J (7/007)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2015/0193167	12/2014	Hokari	711/115	G06F 13/4004
2016/0357235	12/2015	Messenger	N/A	G06F 1/28
2021/0313822	12/2020	Wan	N/A	H02J 7/02

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
108271092	12/2018	CN	G06F 13/4068
112886656	12/2023	CN	H02J 7/00032

Primary Examiner: Chen; Zhitong

Attorney, Agent or Firm: HOWARD M COHN and Associates, LLC

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to a technical field of virtual reality (VR) devices, and in particular to a data remote transmission and charging circuit applied to a VR device and a data remote transmission and charging device.

BACKGROUND

(2) In recent years, arising of virtual reality (VR) technology has made a combination of virtual and reality possible and brings people an unprecedented novelty experience. With development of the VR technology, an interaction between people and intelligent terminals (VR devices) becomes more and more frequent, and popularity of the VR devices makes aspects of people's lives convenient. In the prior art, when playing a VR game, a VR device and a data source (e.g., a computer) transmit data through a data line. During a game process, the charging protocol of the VR device is closed, and thus the VR device is unable to be charged while playing the game. Moreover, when a length of the data line exceeds 3 meters, there is wire voltage drop loss, which continuously consumes storage power in the VR device. When the storage power in the VR device is run out, a user can no longer play the game.

(3) Therefore, how to provide a device that can be applied to the VR devices so that the VR devices can be charged while playing the game is a pressing problem for those skilled in the art to solve.

SUMMARY

(4) In view of this, the present disclosure provides a data remote transmission and charging circuit applied to a VR device and a data remote transmission and charging device applied to the VR device.

(5) By arrangements of a first data sending and receiving circuit, the hub circuit, the second data sending and receiving circuit, a voltage stabilizing circuit, a voltage boost circuit, and a charging circuit, data remote transmission between a data source terminal and the VR device is realized, and charging of the VR device in a game state is realized.

(6) In a first aspect, the present disclosure provides the data remote transmission and charging circuit applied to the VR device. The data remote transmission and charging circuit comprises a first data sending and receiving circuit, a hub circuit, a second data sending and receiving circuit, a voltage stabilizing circuit, a boost circuit, and a charging circuit.

(7) The first data sending and receiving circuit is electrically connected to a data source terminal and the hub circuit. The first data sending and receiving circuit is configured to obtain first game data from the data source terminal and send the first game data to the hub circuit. The first data sending and receiving circuit is configured to receive second game data from the hub circuit.

(8) The hub circuit is electrically connected to the second data sending and receiving circuit and the voltage stabilizing circuit. The hub circuit is configured to obtain the first game data, perform data processing on obtained first game data, and send processed first game data to the second data sending and receiving circuit. The hub circuit is configured to store first charging protocol data and obtain second charging protocol data and second game data sent by the second data sending and receiving circuit. The hub circuit is configured to match the second charging protocol data with the first charging protocol data. If the second charging protocol data is matched with the first charging protocol data, the hub circuit sends a charging trigger signal to the charging circuit. If the second charging protocol data is not matched with the first charging protocol data, the hub circuit does not send the charging trigger signal to the charging circuit, performs data processing on obtained second game data, and sends processed second game data to the first data sending and receiving circuit.

(9) The second data sending and receiving circuit is electrically connected to the VR device and the boost circuit. The second data sending and receiving circuit is configured to obtain the processed first game data sent from the hub circuit. The second data sending and receiving circuit is configured to obtain the second charging protocol data and the second game data from the VR device and send the second charging protocol data and the second game data to the hub circuit.

(10) The voltage stabilizing circuit is electrically connected to the boost circuit and is configured to stabilize a voltage of the hub circuit.

(11) The boost circuit is electrically connected to the charging circuit and is configured to raise a voltage of the VR device.

(12) The charging circuit is configured to receive the charging trigger signal sent by the hub circuit and trigger the boost circuit into a boost working state.

(13) Furthermore, the boost circuit comprises a direct current to direct current (DC-DC) boost chip and a diode. An output end of the DC-DC boost chip is electrically connected to an input end of the voltage stabilizing circuit and a power supply end of the second data sending and receiving circuit. An input end of the DC-DC boost chip is electrically connected to a power supply end of the charging circuit. A ground (GND) end of the DC-DC boost chip is grounded. An anode of the diode is electrically connected to a power supply end of the first data sending and receiving circuit. A cathode of the diode is electrically connected to the output end of the DC-DC boost chip.

(14) Furthermore, the voltage stabilizing circuit comprises a low dropout regulator (LDO) voltage stabilizing chip. An output end of the LDO voltage stabilizing chip is electrically connected to a

power supply end of the hub circuit. An input end of the LDO voltage stabilizing chip is electrically connected to the output end of the DC-DC boost chip and the power supply end of the second data sending and receiving circuit. A GND end of the LDO voltage stabilizing chip is grounded.

(15) Furthermore, the hub circuit comprises a hub chip, and the hub chip has a model number of RTS5411.

(16) Furthermore, the DC-DC boost chip has a model number of MT3608.

(17) Furthermore, the LDO voltage stabilizing chip has a model number of PW6206.

(18) Furthermore, a voltage value of the voltage stabilizing circuit ranges from 3-5.2 V.

(19) Furthermore, a voltage value of the charging circuit ranges from 4.9-5.6 V.

(20) In a second aspect, the present disclosure provides the data remote transmission and charging device. The data remote transmission and charging device comprises the data remote transmission and charging circuit mentioned above. The data remote transmission and charging circuit is configured to realize data remote transmission between the data source terminal and the VR device; the data remote transmission and charging circuit is configured to charge the VR device.

(21) Compared with the prior art, in the data remote transmission and charging circuit and the data remote transmission and charging device of the present disclosure, by providing the first data sending and receiving circuit, the hub circuit, the second data sending and receiving circuit, the voltage stabilizing circuit, the boost circuit, and the charging circuit, the first data sending and receiving circuit is electrically connected to the data source terminal and the hub circuit, the hub circuit is electrically connected to the second data sending and receiving circuit and the voltage stabilizing circuit, and the second data sending and receiving circuit is electrically connected to the VR device, realizing the data remote transmission between the data source terminal and the VR device. Further, the boost circuit is electrically connected to the second data sending and receiving circuit, the voltage stabilizing circuit, and the charging circuit, so real-time charging of the VR device is realized when playing a VR game.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a schematic diagram of a data remote transmission and charging circuit applied to a virtual reality (VR) device according to one embodiment of the present disclosure.

(2) FIG. 2 is a schematic diagram of the data remote transmission and charging circuit applied to the VR device according to another embodiment of the present disclosure.

(3) FIG. 3 is a schematic diagram of the data remote transmission and charging device applied to the VR device according to one embodiment of the present disclosure.

DETAILED DESCRIPTION

(4) To facilitate a good understanding of purposes, structures, features, and efficacy, etc. of the present disclosure, a data remote transmission and charging circuit applied to a virtual reality (VR) device and a device thereof disclosed herein are further described in conjunction with the accompanying drawings and specific embodiments.

(5) As shown in FIG. 1, the present disclosure provides the data remote transmission and charging circuit applied to the VR device. The data remote transmission and charging circuit comprises a first data sending and receiving circuit **101**, a hub circuit **102**, a second data sending and receiving circuit **103**, a voltage stabilizing circuit **104**, a boost circuit **105**, and a charging circuit **106**.

(6) The first data sending and receiving circuit **101** is electrically connected to a data source terminal and the hub circuit **102**. The first data sending and receiving circuit **101** is configured to obtain first game data from the data source terminal and send the first game data to the hub circuit **102**. The first data sending and receiving circuit **101** is configured to receive second game data from the hub circuit **102**.

- (7) The hub circuit **102** is electrically connected to the second data sending and receiving circuit **103** and the voltage stabilizing circuit **104**. The hub circuit **102** is configured to obtain the first game data, perform data processing on obtained first game data, and send processed first game data to the second data sending and receiving circuit **103**. Further, the hub circuit **102** is configured to store first charging protocol data and obtain second charging protocol data and second game data sent by the second data sending and receiving circuit **103**. The hub circuit **102** is configured to match the second charging protocol data with the first charging protocol data. If the second charging protocol data is matched with the first charging protocol data, the hub circuit sends a charging trigger signal to the charging circuit. If the second charging protocol data is not matched with the first charging protocol data, the hub circuit does not send the charging trigger signal to the charging circuit **103**. The hub circuit **102** performs data processing on obtained second game data, and sends processed second game data to the first data sending and receiving circuit.
- (8) The second data sending and receiving circuit **103** is electrically connected to the VR device and the boost circuit **105**. The second data sending and receiving circuit **103** is configured to obtain the processed first game data sent from the hub circuit **102**. The second data sending and receiving circuit **103** is configured to obtain the second charging protocol data and the second game data from the VR device and send the second charging protocol data and the second game data to the hub circuit **102**.
- (9) The voltage stabilizing circuit **104** is electrically connected to the boost circuit **105** and is configured to stabilize a voltage of the hub circuit **102**.
- (10) The boost circuit **105** is electrically connected to the charging circuit **106** and is configured to raise a voltage of the VR device.
- (11) The charging circuit **106** is configured to receive the charging trigger signal sent by the hub circuit **102** and trigger the boost circuit into a boosted working state.
- (12) In the embodiment, the first data sending and receiving circuit **101** is electrically connected to the data source terminal and the hub circuit **102**, the hub circuit **102** is electrically connected to the second data sending and receiving circuit **103** and the voltage stabilizing circuit **104**, and the second data sending and receiving circuit **103** is electrically connected to the VR device, which realizes the data remote transmission between the data source terminal and the VR device. Further, the boost circuit **105** is electrically connected to the second data sending and receiving circuit **103**, the voltage stabilizing circuit **104**, and the charging circuit **106**, so real-time charging of the VR device is realized when playing a VR game.
- (13) As shown in FIG. 2, the boost circuit **105** comprises a DC-DC boost chip and a diode. An output end of the DC-DC boost chip is electrically connected to an input end of the voltage stabilizing circuit **104** and a power supply end of the second data sending and receiving circuit **103**. An input end of the DC-DC boost chip is electrically connected to a power supply end of the charging circuit **106**. A ground (GND) end of the DC-DC boost chip is grounded. An anode of the diode is electrically connected to a power supply end of the first data sending and receiving circuit. A cathode of the diode is electrically connected to the output end of the DC-DC boost chip. An arrangement of the diode effectively prevents a voltage of the charging circuit **106** from being too large, so that a current would not flow backwards through the first data sending and receiving circuit **101** to the data source terminal, and the data source terminal is prevented from burning out. In one optional embodiment, the DC-DC boost chip has a model number of MT3608.
- (14) The voltage stabilizing circuit **104** comprises a low dropout regulator (LDO) voltage stabilizing chip. An output end of the LDO voltage stabilizing chip is electrically connected to a power supply end of the hub circuit. An input end of the LDO voltage stabilizing chip is electrically connected to the output end of the DC-DC boost chip and the power supply end of the second data sending and receiving circuit **103**. A GND end of the LDO voltage stabilizing chip is grounded. In one optional embodiment, the LDO voltage stabilizing chip has a model number of PW6206.
- (15) The hub circuit **102** comprises a hub chip. In one optional embodiment, the hub chip has a

model number of RTS5411.

(16) In the embodiment, the first data sending and receiving circuit **101** further comprises a US_D- end, a US_D+ end, a US_SSTX- end, a US_SSTX+ end, a US_SSRX end, and a US_SSRX+ end.

(17) The hub chip comprises a US_D- end, a US_D+ end, a US_SSTX- end, a US_SSTX+ end, a US_SSRX end, a US_SSRX+ end, a USP_DM end, a USP_DP end, a USP_SSRX- end, a USP_SSRX+ end, a USP_SSTX- end, and a USP_SSTX+ end.

(18) The second data sending and receiving circuit **103** also comprises a USP_DM end, a USP_DP end, a USP_SSRX- end, a USP_SSRX+ end, a USP_SSTX- end, and a USP_SSTX+ end.

(19) The US_D- end of the first data sending and receiving circuit **101** is electrically connected with the US_D- end of the hub chip. The US_D+ end of the first data sending and receiving circuit **101** is electrically connected with the US_D+ end of the hub chip. The US_SSTX- end of the first data sending and receiving circuit **101** is electrically connected with the US_SSTX- end of the hub chip. The US_SSTX+ end of the first data sending and receiving circuit **101** is electrically connected with the US_SSTX+ end of the hub chip. The US_SSRX- end of the first data sending and receiving circuit **101** is electrically connected with the US_SSRX- end of the hub chip. The US_SSRX+ end of the first data sending and receiving circuit **101** is electrically connected with the US_SSRX+ end of the hub chip.

(20) The USP_DM end of the second data sending and receiving circuit **103** is electrically connected with the USP_DM of the hub chip. The USP_DP end of the second data sending and receiving circuit **103** is electrically connected with the USP_DP of the hub chip. The USP_SSRX- end of the second data sending and receiving circuit **103** is electrically connected with the USP_SSRX- of the hub chip. The USP_SSRX+ end of the second data sending and receiving circuit **103** is electrically connected with the USP_SSRX+ of the hub chip. The USP_SSTX- end of the second data sending and receiving circuit **103** is electrically connected with the USP_SSTX- of the hub chip. The USP_SSTX+ end of the second data sending and receiving circuit **103** is electrically connected with the USP_SSTX+ of the hub chip.

(21) In the embodiment, a voltage value of the hub chip of the hub circuit **102** ranges from 3-5.2 V. The voltage stabilizing circuit **104** is configured to stabilize the voltage of the hub circuit **102**, so a voltage value of the voltage stabilizing circuit **104** ranges from 3-5.2V, which can be 3V, 3.2V, 3.5V, 4V, 4.8V, 5.1V, etc., and is not limited therein.

(22) In the embodiment, a wire length between the second data sending and receiving circuit **103** and the hub circuit **102** ranges from 4-7 m. A wire length between the hub circuit **102** and the first data sending and receiving circuit **101** ranges from 0.1-1 m. A wire length between the boost circuit **105** and the charging circuit **106** ranges from 1-2 m. Therefore, in one optional embodiment of the present disclosure, a voltage value of the charging circuit **106** ranges from 4.9-5.6V and a current of the charging circuit **106** is 1.5 A. The charging circuit **106** compensates voltage lost in lengths of wires connected to the VR device and enables a voltage of the VR device to be output stably, thus allowing a user to stably play the VR game for a long time while allowing the charging of the VR device.

(23) In the embodiment, an interface of the first data sending and receiving circuit **101** is a USB interface, an interface of the second data sending and receiving circuit **103** is a TYPE-C interface, and an interface of the charging circuit **106** is a TYPE-C interface.

(24) A working process is as follow:

(25) When a USB male connector (i.e., USB interface) of the first data sending and receiving circuit **101** is inserted into a USB female connector of a computer (i.e., the date source terminal), a TYPE-C male connector of the second data sending and receiving circuit **103** (i.e., TYPE-C interface of the second data sending and receiving circuit **103**) is inserted into a TYPE-C female connector of the VR device, and a TYPE-C male connector of the charging circuit **106** (i.e., TYPE-C interface of the charging circuit **106**) is inserted into the Type-c female connector of the charger.

(26) At this time, the US_D- end, the US_D+ end, the US_SSTX- end, the US_SSTX+ end, the

US_SSRX end, and the US_SSRX+ end of the hub chip send game data to the computer through the US_D- end, the US_D+ end, the US_SSTX- end, the US_SSTX+ end, the US_SSRX end, and the US_SSRX+ end of the first data sending and receiving circuit **101**. The VR device sends the game data through the USP_DM end, the USP_DP end, the USP_SSRX- end, the USP_SSRX+ end, the USP_SSTX- end, and the USP_SSTX+ end of the second data sending and receiving circuit **103** to the USP_DM end, the USP_DP end, the USP_SSRX- end, the USP_SSRX+ end, the USP_SSTX- end, and the USP_SSTX+ end of the hub chip. Meanwhile, the USP_DM end and the USP_DP end of the hub chip communicate with a USP_DM end and a USP_DP end of the VR device for charging protocol. If the HUB chip is matched with the VR device through the charging protocol data, the charging circuit charges the VR device through boost circuit **105**. If the hub chip is not matched with the VR device through the charging protocol data, the charging circuit does not charge the VR device.

(27) As shown in FIG. 3, the present disclosure provides the data remote transmission and charging device **200**. The data remote transmission and charging device **200** comprises the data remote transmission and charging circuit as shown in FIGS. 1 and 2. The data remote transmission and charging device **200** is configured to realize data remote transmission between the data source terminal and the VR device; the data remote transmission and charging circuit is configured to charge the VR device.

(28) In summary, in the data remote transmission and charging circuit and the data remote transmission and charging device of the present disclosure, by providing the first data sending and receiving circuit, the hub circuit, the second data sending and receiving circuit, the voltage stabilizing circuit, the boost circuit, and the charging circuit, the first data sending and receiving circuit is electrically connected to the data source terminal and the hub circuit, the hub circuit is electrically connected to the second data sending and receiving circuit and the voltage stabilizing circuit, and the second data sending and receiving circuit is electrically connected to the VR device, which realizes the data remote transmission between the data source terminal and the VR device. Further, the boost circuit is electrically connected to the second data sending and receiving circuit, the voltage stabilizing circuit, and the charging circuit, so the real-time charging of the VR device is realized when playing the VR game.

(29) The above detailed descriptions are only illustrations of optional embodiments of the present disclosure and are not intended to limit the protection scope of the present disclosure. Therefore, all equivalent technical variations using the specification and the illustrations of the present disclosure are included in the protection scope of the present disclosure.

Claims

1. A data remote transmission and charging circuit applied to a virtual reality (VR) device, comprising: a first data sending and receiving circuit, a hub circuit, a second data sending and receiving circuit, a voltage stabilizing circuit, a boost circuit, and a charging circuit; wherein the first data sending and receiving circuit is electrically connected to a data source terminal and the hub circuit; the first data sending and receiving circuit is configured to obtain first game data from the data source terminal and send the first game data to the hub circuit; the first data sending and receiving circuit is configured to receive second game data from the hub circuit; wherein the hub circuit is electrically connected to the second data sending and receiving circuit and the voltage stabilizing circuit; the hub circuit is configured to obtain the first game data, perform data processing on obtained first game data, and send processed first game data to the second data sending and receiving circuit; the hub circuit is configured to store first charging protocol data and obtain second charging protocol data and second game data sent by the second data sending and receiving circuit; the hub circuit is configured to match the second charging protocol data with the first charging protocol data, if the second charging protocol data is matched with the first charging

protocol data, the hub circuit is configured to send a charging trigger signal to the charging circuit; if the second charging protocol data is not matched with the first charging protocol data, the hub circuit does not send the charging trigger signal to the charging circuit; and the hub circuit performs data processing on obtained second game data and sends processed second game data to the first data sending and receiving circuit; wherein the second data sending and receiving circuit is electrically connected to the VR device and the boost circuit; the second data sending and receiving circuit is configured to obtain the processed first game data sent from the hub circuit; the second data sending and receiving circuit is configured to obtain the second charging protocol data and the second game data from the VR device and send the second charging protocol data and the second game data to the hub circuit; wherein the voltage stabilizing circuit is electrically connected to the boost circuit and is configured to stabilize a voltage of the hub circuit; wherein the boost circuit is electrically connected to the charging circuit and is configured to raise a voltage of the VR device; wherein the charging circuit is configured to receive the charging trigger signal sent by the hub circuit and trigger the boost circuit into a boosted working state.

2. The data remote transmission and charging circuit according to claim 1, wherein the boost circuit comprises a DC-DC boost chip and a diode; an output end of the DC-DC boost chip is electrically connected to an input end of the voltage stabilizing circuit and a power supply end of the second data sending and receiving circuit; an input end of the DC-DC boost chip is electrically connected to a power supply end of the charging circuit; a ground (GND) end of the DC-DC boost chip is grounded; an anode of the diode is electrically connected to a power supply end of the first data sending and receiving circuit; a cathode of the diode is electrically connected to the output end of the DC-DC boost chip.

3. The data remote transmission and charging circuit according to claim 2, wherein the voltage stabilizing circuit comprises a low dropout regulator (LDO) voltage stabilizing chip; an output end of the LDO voltage stabilizing chip is electrically connected to a power supply end of the hub circuit; an input end of the LDO voltage stabilizing chip is electrically connected to the output end of the DC-DC boost chip and the power supply end of the second data sending and receiving circuit; and a GND end of the LDO voltage stabilizing chip is grounded.

4. The data remote transmission and charging circuit according to claim 1, wherein the hub circuit comprises a hub chip, and the hub chip has a model number of RTS5411.

5. The data remote transmission and charging circuit according to claim 2, wherein the DC-DC boost chip has a model number of MT3608.

6. The data remote transmission and charging circuit according to claim 3, wherein the LDO voltage stabilizing chip has a model number of PW6206.

7. The data remote transmission and charging circuit according to claim 1, wherein a voltage value of the voltage stabilizing circuit ranges from 3-5.2 V.

8. The data remote transmission and charging circuit according to claim 1, wherein a voltage value of the charging circuit ranges from 4.9-5.6 V.

9. A data remote transmission and charging device, comprising: the data remote transmission and charging circuit according to claim 1, wherein the data remote transmission and charging circuit is configured to realize data remote transmission between the data source terminal and the VR device; the data remote transmission and charging circuit is configured to charge the VR device.
