

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412469
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Yamada; Masahiro et al.

Information processing method, information processing device, and program

Abstract

An information processing method includes a step of acquiring movement information on a first mobile body including information on a first position through which the first mobile body is scheduled to pass in a first time slot and information on a travel direction of the first mobile body and a step of setting, as an exclusive area in the first time slot, an area between the first position and a second position on a travel direction side of the first mobile body from the first position based on the movement information on the first mobile body. The exclusive area is set in a manner that the second mobile body other than the first mobile body is not permitted to move within the exclusive area in the travel direction different from the travel direction of the first mobile body in the first time slot, and the second mobile body is permitted to move within the exclusive area in the same travel direction as the first mobile body in the first time slot.

Inventors: Yamada; Masahiro (Tokyo, JP), Chishiki; Yohei (Tokyo, JP), Takao; Kenji (Tokyo, JP)

Applicant: MITSUBISHI HEAVY INDUSTRIES, LTD. (Tokyo, JP)

Family ID: 85724621

Assignee: MITSUBISHI HEAVY INDUSTRIES, LTD. (Tokyo, JP)

Appl. No.: 18/125393

Filed: March 23, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230306839 A1	Sep. 28, 2023

Foreign Application Priority Data

JP	2022-049044	Mar. 24, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: G08G1/017 (20060101); G08G1/056 (20060101); G08G1/065 (20060101)

U.S. Cl.:

CPC G08G1/017 (20130101); G08G1/056 (20130101); G08G1/065 (20130101);

Field of Classification Search

CPC: G08G (1/017); G08G (1/056); G08G (1/065); G08G (1/066); G08G (1/166)

USPC: 701/117

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8751060	12/2013	Kinoshita	N/A	N/A
10467505	12/2018	Ishii	N/A	G06F 18/25
11074447	12/2020	Fox	N/A	G08G 5/55
2007/0294029	12/2006	D'Andrea et al.	N/A	N/A
2011/0106341	12/2010	Kinoshita	N/A	N/A
2018/0082155	12/2017	Ishii	N/A	G06F 18/25
2018/0097991	12/2017	Hachimura	N/A	H04N 23/64
2019/0072965	12/2018	Zhang	N/A	G08G 1/166
2019/0072966	12/2018	Zhang	N/A	G05D 1/646
2019/0286093	12/2018	Taira	N/A	G06F 3/017
2020/0233435	12/2019	Kichkaylo	N/A	N/A
2020/0307576	12/2019	Takegawa	N/A	B60K 35/28
2021/0021960	12/2020	Kobayashi	N/A	G01S 5/0027
2021/0192709	12/2020	Sibley	N/A	G06V 20/13
2021/0192754	12/2020	Sibley	N/A	G06N 20/00
2021/0271257	12/2020	Watanabe	N/A	G06F 18/24
2021/0272018	12/2020	Casas	N/A	G06N 7/01
2021/0312476	12/2020	Kita	N/A	G06Q 30/06
2021/0389769	12/2020	Hari	N/A	G05B 13/027
2022/0057812	12/2021	Ai et al.	N/A	N/A
2022/0144260	12/2021	Chen	N/A	B60W 30/0956
2022/0319318	12/2021	Takehara	N/A	B60W 40/04
2023/0082350	12/2022	Endo	701/41	G06V 20/588
2023/0104951	12/2022	Wakabayashi	701/41	B60W 40/04

2023/0324194	12/2022	Akbarzadeh	701/117	G01C 21/3415
2023/0358560	12/2022	Kanazawa	N/A	G01C 21/3815

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
111164381	12/2019	CN	G06T 19/00
3776514	12/2021	EP	G08G 1/166
4012338	12/2021	EP	G01C 21/3415
61-262903	12/1985	JP	N/A
2011-227716	12/2010	JP	N/A
5029622	12/2011	JP	N/A
2021124927	12/2020	JP	N/A
2021170165	12/2020	JP	G06V 20/584
10-2010-0139134	12/2009	KR	N/A
WO-2017208619	12/2016	WO	G06T 7/20
WO-2019187662	12/2018	WO	H04W 4/029

OTHER PUBLICATIONS

Extended European Search Report for European Application No. 23163409.8, dated Jun. 5, 2023.
cited by applicant
Japanese Office Action for Japanese Application No. 2022-049044, dated Jan. 30, 2024, with
English translation. cited by applicant

Primary Examiner: Trivedi; Atul
Attorney, Agent or Firm: Birch, Stewart, Kolasch & Birch, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application claims the benefit of priority to Japanese Patent Application Number 2022-049044 filed on Mar. 24, 2022. The entire contents of the above-identified application are hereby incorporated by reference.

TECHNICAL FIELD

(2) The disclosure relates to an information processing method, an information processing device, and a program.

RELATED ART

(3) A known technique for a plurality of mobile bodies that automatically move is to reserve an area where a mobile body is scheduled to move as an exclusive area (blocking area) and prevent another mobile body from entering the exclusive area. For example, JP 5029622 B describes determining, in attempting to reserve a first blocking area for a vehicle, whether a deadlock occurs when another vehicle passes through a second blocking area corresponding to the first blocking area. In JP 5029622 B, when it is determined that no deadlock occurs, the first blocking area can be

reserved.

SUMMARY

(4) However, there is room for improvement in suppressing a deadlock.

(5) The disclosure has been made to solve the above-described problem, and an object of the disclosure is to provide an information processing method, an information processing device, and a program that can suppress a deadlock.

(6) An information processing method according to the disclosure includes a step of acquiring movement information on a first mobile body including information on a first position through which the first mobile body is scheduled to pass in a first time slot and information on a travel direction of the first mobile body and a step of setting, as an exclusive area in the first time slot, an area between the first position and a second position on a travel direction side of the first mobile body from the first position based on the movement information on the first mobile body. The exclusive area is set in a manner that a second mobile body other than the first mobile body is not permitted to move within the exclusive area in a travel direction different from the travel direction of the first mobile body in the first time slot and that the second mobile body is permitted to move within the exclusive area in a travel direction identical to the travel direction of the first mobile body in the first time slot.

(7) An information processing device according to the disclosure includes a movement information acquisition unit configured to acquire movement information on a first mobile body including information on a first position through which the first mobile body is scheduled to pass in a first time slot and information on a travel direction of the first mobile body and a work setting unit configured to set, as an exclusive area in the first time slot, an area between the first position and a second position on a travel direction side of the first mobile body from the first position based on the movement information on the first mobile body. The exclusive area is set in a manner that a second mobile body other than the first mobile body is not permitted to move within the exclusive area in a travel direction different from the travel direction of the first mobile body in the first time slot and that the second mobile body is permitted to move within the exclusive area in a travel direction identical to the travel direction of the first mobile body in the first time slot.

(8) A program according to the disclosure causes a computer to execute a step of acquiring movement information on a first mobile body including information on a first position through which the first mobile body is scheduled to pass in a first time slot and information on a travel direction of the first mobile body and a step of setting, as an exclusive area in the first time slot, an area between the first position and a second position on a travel direction side of the first mobile body from the first position based on the movement information on the first mobile body. The exclusive area is set in a manner that a second mobile body other than the first mobile body is not permitted to move within the exclusive area in a travel direction different from the travel direction of the first mobile body in the first time slot and that the second mobile body is permitted to move within the exclusive area in a travel direction identical to the travel direction of the first mobile body in the first time slot.

(9) The disclosure can suppress a deadlock.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) The disclosure will be described with reference to the accompanying drawings, wherein like numbers reference like elements.

(2) FIG. 1 is a schematic view of a movement control system according to the present embodiment.

(3) FIG. 2 is a schematic view of a configuration of a mobile body.

(4) FIG. 3 is a schematic block diagram of a management device.

- (5) FIG. 4 is a schematic block diagram of an information processing device.
- (6) FIG. 5 is a schematic block diagram of a control device for the mobile body.
- (7) FIG. 6 is a table showing an example of movement destination information.
- (8) FIG. 7 is a table for explaining the setting of a work.
- (9) FIG. 8 is a schematic view for explaining setting of an exclusive area.
- (10) FIG. 9 is a schematic view for explaining setting of an exclusive area.
- (11) FIG. 10 is a schematic view explaining an example of setting of an exclusive area at an intersection.
- (12) FIG. 11 is a flowchart explaining a setting flow of an exclusive area according to the present embodiment.
- (13) FIG. 12 is a schematic view illustrating an example of an exclusive area in a second embodiment.
- (14) FIG. 13 is a schematic view illustrating another example of the exclusive area in the second embodiment.
- (15) FIG. 14 is a schematic view illustrating an example of an exclusive area in a third embodiment.
- (16) FIG. 15 is a schematic view illustrating an example of an exclusive area in a fourth embodiment.

DESCRIPTION OF EMBODIMENTS

(17) Hereinafter, preferred embodiments of the disclosure will be described in detail with reference to the accompanying drawings. Note that the disclosure is not limited to these embodiments, and when there are a plurality of embodiments, the disclosure is intended to include a configuration combining these embodiments.

First Embodiment

(18) Movement Control System

(19) FIG. 1 is a schematic view of a movement control system according to the present embodiment. As illustrated in FIG. 1, a movement control system 1 according to the present embodiment includes a mobile body 10, a management device 12, and an information processing device 14. The movement control system 1 is a system that controls the movement of the mobile body 10 belonging to a facility W. The facility W is a facility, such as a warehouse, that is logistically managed. The movement control system 1 causes the mobile body 10 to pick up and convey a target object P disposed within an area AR in the facility W. The area AR is, for example, a floor surface of the facility W, and is an area in which the target object P is placed and through which the mobile body 10 moves. In the present embodiment, the target object P is a conveyance target object composed of a pallet and a burden loaded on the pallet. The target object P includes an opening Pb into which a fork 24 of the mobile body 10 to be described later is inserted, and the opening Pb is formed in a front surface Pa of the target object P. However, the target object P is not limited to an object composed of a pallet and a burden loaded on the pallet, and may be only a burden without a pallet, for example.

(20) Hereinafter, an operation including movement along a route R (to be described later) by the mobile body 10 will be appropriately referred to as a work of the mobile body 10. Further, in the present embodiment, the mobile body 10 moves along the route R to load, convey, and unload the target object P, and thus a series of operations by the mobile body 10 to move along the route R, and load, convey, and unload the target object P can be said to be the work of the mobile body 10. Hereinafter, one direction along the area AR is referred to as an X direction, and a direction along the area AR that is orthogonal to the X direction is referred to as a Y direction. In the present embodiment, the Y direction is a direction orthogonal to the X direction. The X direction and the Y direction may be horizontal directions. A direction orthogonal to the X direction and the Y direction, more specifically, an upward direction in the vertical direction is referred to as a Z direction. In the present embodiment, unless otherwise specified, a “position” refers to a position

(coordinates) in a coordinate system in a two dimensional plane on the area AR (the coordinate system of the area AR). Also, unless otherwise specified, an “orientation” of the mobile body **10** or the like refers to an orientation of the mobile body **10** in the coordinate system of the area AR, and means a yaw angle (rotation angle) of the mobile body **10** with the X direction defined as 0 degrees when viewed from the Z direction.

(21) A plurality of placement areas **AR1** is disposed in the area AR in the facility W. The placement areas **AR1** are configured to be used as areas in which the target object P is placed. The target object P may be placed or may not be placed in each placement area **AR1** depending on the situation of the facility W. The position (coordinates), the shape, and the size of the placement area **AR1** are determined in advance. In the example illustrated in FIG. 1, the placement areas **AR1** are set on a shelf provided in the area AR, but are not limited thereto, and may be provided on the area AR (i.e., on the floor of the facility W), or may be provided in a loading platform of a vehicle that has conveyed the target object P into the facility W. In addition, in the present embodiment, the placement area **AR1** is defined for each target object P, and one target object P is placed in each placement area **AR1**, but the disclosure is not limited thereto. For example, the placement area **AR1** may be set as a free space in which a plurality of target objects P are placed. In addition, in the example in FIG. 1, the placement area **AR1** has a rectangular shape, but may have any shape and any size, and the number of the placement areas **AR1** is also optional.

(22) Waypoint

(23) In the area AR, a waypoint A is set for each position (coordinates). The route R along which the mobile body **10** moves is configured to connect the waypoints A. That is, a route connecting the waypoints A through which the mobile body **10** is scheduled to pass is the route R of the mobile body **10**. The waypoints A are set according to the layout of the facility W such as the positions of the placement areas **AR1** and passages. For example, the waypoints A are set in a matrix form in the area AR, and the positions and the number of the waypoints A are set such that a route R connecting a position facing one placement area **AR1** to a position facing any other placement area **AR1** can be set. The position facing the placement area **AR1** may be, for example, a position at which the mobile body **10** can pick up the target object P placed in the placement area **AR1**. In addition, the waypoints A include a waypoint A configured to be a charging point (in the example of FIG. 1, a waypoint A_n at which a charger CH is placed) or a waypoint A configured to be a waiting point (in the example of FIG. 1, a waypoint A_m). The waypoint A that is a charging point or a waiting point may be set at any position that does not overlap a route (the route used for conveyance) connecting the waypoints A facing the respective placement areas **AR1**.

(24) Mobile Body

(25) FIG. 2 is a schematic view of a configuration of a mobile body. The mobile body **10** is a device that can move automatically and convey the target object P. Further, in the present embodiment, the mobile body **10** is a forklift, and more specifically, a so-called automated guided vehicle (AGV) or a so-called automated guided forklift (AGF). However, the mobile body **10** is not limited to a forklift for conveying the target object P, and may be any device capable of moving automatically.

(26) As illustrated in FIG. 2, the mobile body **10** includes a vehicle body **20**, a wheel **20A**, a straddle leg **21**, a mast **22**, a fork **24**, a sensor **26A**, and a control device **28**. The straddle leg **21** is a shaft-like member that is disposed in pairs at one end portion of the vehicle body **20** in a front-back direction and protrudes from the vehicle body **20**. The wheel **20A** is disposed at a leading end of each of the straddle legs **21** and at the vehicle body **20**. That is, a total of three wheels **20A** are disposed, but the positions and the number of the wheels **20A** disposed may be optional. The mast **22** is movably attached to the straddle legs **21** and moves in the front-back direction of the vehicle body **20**. The mast **22** extends along the vertical direction (here, the direction Z) orthogonal to the front-back direction. The fork **24** is attached to the mast **22** so as to be movable in the direction Z. The fork **24** may be movable in a lateral direction of the vehicle body **20** (a direction intersecting

with the vertical direction and the front-back direction) with respect to the mast **22**. The fork **24** includes a pair of tines **24A** and **24B**. The tines **24A** and **24B** extend, from the mast **22**, toward the front direction of the vehicle body **20**. The tines **24A** and **24B** are arranged separated from each other in the lateral direction of the mast **22**. In the front-back direction, a direction to a side of the mobile body **10** where the fork **24** is disposed and a direction to a side where the fork **24** is not disposed are referred to as a front direction and a back direction, respectively.

(27) The sensors **26A** detect at least one of the position and the orientation of a target object present in the periphery of the vehicle body **20**. That is, it can be said that the sensor **26A** detects at least one of the position of the target object relative to the mobile body **10** and the orientation of the target object relative to the mobile body **10**. In the present embodiment, the sensor **26A** is disposed at a leading end of each of the straddle legs **21** in the front direction, and at the vehicle body **20** on a back direction side. However, the positions at which the sensors **26A** are disposed are not limited to these positions, the sensors **26A** may be disposed at any positions, and the number of the sensors **26A** disposed may be optional.

(28) The sensor **26A** is a sensor that emits a laser beam, for example. The sensor **26A** emits the laser beam while performing scanning in one direction (here, the lateral direction), and detects the position and the orientation of the target object based on the reflected light of the laser beam emitted. That is, the sensor **26A** is a so-called two-dimensional (2D) light detection and ranging (LiDAR) sensor. Note that the sensor **26A** is not limited to the one described above, may be a sensor that detects the target object using any method, for example, may be a so-called three-dimensional (3D)-LiDAR sensor in which scanning is performed in multiple directions, may be a so-called one dimensional (1D)-LiDAR sensor in which no scanning is performed, or may be a camera.

(29) The control device **28** controls the movement of the mobile body **10**. The control device **28** will be described later.

(30) Management Device

(31) FIG. **3** is a schematic block diagram of a management device. The management device **12** is a system that manages physical distribution in the facility **W**. The management device **12** is a warehouse control system (WCS) or a warehouse management system (WMS) in the present embodiment, but is not limited to a WCS and a WMS, and may be any system including a backend system such as any other production management system. The management device **12** may be disposed at any position, and may be disposed in the facility **W**, or may be disposed at a separate position from the facility **W** so as to manage the facility **W** from the separate position. The management device **12** is a computer and includes a communication unit **30**, a storage unit **32**, and a control unit **34** as illustrated in FIG. **3**.

(32) The communication unit **30** is a module used by the control unit **34** to communicate with an external device such as the information processing device **14**, and may include, for example, a Wi-Fi (registered trademark) module or an antenna. The communication method of the communication unit **30** is wireless communication in the present embodiment, but any communication method may be used. The storage unit **32** is a memory that stores various information such as computation contents of the control unit **34** and programs, and includes, for example, at least one of a primary storage device such as a random access memory (RAM) or a read only memory (ROM), and an external storage device such as a hard disk drive (HDD).

(33) The control unit **34** is an arithmetic device and includes, for example, an arithmetic circuit such as a central processing unit (CPU). The control unit **34** includes a movement destination information setting unit **40**. The control unit **34** reads a program (software) from the storage unit **32** and executes the program to implement the movement destination information setting unit **40** and perform the processing thereof. Note that the control unit **34** may execute such processing with a single CPU, or may include a plurality of CPUs and execute the processing with the plurality of CPUs. The movement destination information setting unit **40** may be implemented by a hardware

circuit. The program for the control unit **34** stored in the storage unit **32** may be stored in a recording medium that is readable by the management device **12**.

(34) The movement destination information setting unit **40** sets movement destination information indicating a movement destination of the mobile body **10**. The processing by the movement destination information setting unit **40** will be more specifically described later.

(35) Note that the management device **12** may execute processing other than the setting of the movement destination information. For example, the management device **12** may also set information for controlling a mechanism other than the mobile body **10** disposed in the facility **W** (for example, an elevator and a door).

(36) Information Processing Device

(37) FIG. **4** is a schematic block diagram of the information processing device. The information processing device **14** is a device that is disposed in the facility **W** and processes information related to the movement of the mobile body **10**. The information processing device **14** is, for example, a fleet control system (FCS), but is not limited thereto, and may be any device that processes information related to the movement of the mobile body **10**. The information processing device **14** is a computer and includes a communication unit **50**, a storage unit **52**, and a control unit **54** as illustrated in FIG. **4**. The communication unit **50** is a module used by the control unit **54** to communicate with an external device such as the management device **12** and the mobile body **10**, and may include, for example, an antenna or a Wi-Fi module. The communication method of the communication unit **50** is wireless communication in the present embodiment, but any communication method may be used. The storage unit **52** is a memory for storing various information such as computation contents of the control unit **54** and programs, and includes, for example, at least one of a primary storage device such as a RAM or a ROM, and an external storage device such as an HDD.

(38) The control unit **54** is an arithmetic device and includes an arithmetic circuit such as a CPU, for example. The control unit **54** includes a movement destination information acquisition unit **60**, a work setting unit **62**, and a movement information acquisition unit **64**. By reading and executing a program (software) from the storage unit **52**, the control unit **54** implements the movement destination information acquisition unit **60**, the work setting unit **62**, and the movement information acquisition unit **64**, and executes those processing. Note that the control unit **54** may execute such processing with a single CPU or may include a plurality of CPUs and execute the processing with the plurality of CPUs. At least a part of the movement destination information acquisition unit **60**, the work setting unit **62**, and the movement information acquisition unit **64** may be implemented by a hardware circuit. The program for the control unit **54** stored in the storage unit **52** may be stored in a recording medium that is readable by the information processing device **14**.

(39) The movement destination information acquisition unit **60** acquires the movement destination information, the work setting unit **62** sets the route **R** of the mobile body **10**, and the movement information acquisition unit **64** acquires movement information on the mobile body **10**. Specific contents of the above-described processing will be described below.

(40) Note that, in the present embodiment, the management device **12** and the information processing device **14** are separate devices, but may be an integrated device. That is, the management device **12** may have at least a part of the function of the information processing device **14**, and the information processing device **14** may have at least a part of the function of the management device **12**.

(41) Control Device for Mobile Body

(42) Next, the control device **28** for the mobile body **10** will be described. FIG. **5** is a schematic block diagram of a control device for the mobile body. The control device **28** is a device for controlling the mobile body **10**. The control device **28** is a computer and includes a communication unit **70**, a storage unit **72**, and a control unit **74** as illustrated in FIG. **5**. The communication unit **70** is a module used by the control unit **74** to communicate with an external device such as the

information processing device **14**, and may include, for example, an antenna or a Wi-Fi module. The communication method of the communication unit **70** is wireless communication in the present embodiment, but any communication method may be used. The storage unit **72** is a memory for storing various information such as computation contents of the control unit **74** and programs, and includes, for example, at least one of a primary storage device such as a RAM or a ROM, and an external storage device such as an HDD.

(43) The control unit **74** is an arithmetic device and includes an arithmetic circuit such as a CPU, for example. The control unit **74** includes a work acquisition unit **80** and a movement control unit **82**. By reading and executing a program (software) from the storage unit **72**, the control unit **74** implements the work acquisition unit **80** and the movement control unit **82**, and executes those processing. Note that the control unit **74** may execute such processing with a single CPU or may include a plurality of CPUs and execute the processing with the plurality of CPUs. At least a part of the work acquisition unit **80** and the movement control unit **82** may be implemented by a hardware circuit. In addition, the program for the control unit **74** stored in the storage unit **72** may be stored in a recording medium that is readable by the control device **28**.

(44) The work acquisition unit **80** acquires information indicating the route R of the mobile body **10**, the movement control unit **82** controls a movement mechanism such as a drive unit or a steering device of the mobile body **10** so as to control the movement of the mobile body **10**. Specific contents of the above-described processing will be described below.

(45) Processing of Movement Control System

(46) Next, the processing contents of the movement control system **1** will be described.

(47) Setting of Movement Destination Information

(48) The movement destination information setting unit **40** of the management device **12** sets movement destination information indicating a movement destination of the mobile body **10**. The movement destination information includes information indicating the position of the movement destination of the mobile body **10**. More specifically, in the present embodiment, the movement destination information setting unit **40** sets the movement destination information so as to include first position information (position information of a first position) and second position information (position information of a second position). The first position is a position which the mobile body **10** reaches first, and the second position is a position which the mobile body **10** reaches next to the first position. That is, in the example of the present embodiment, the first position is the position of a conveyance source of the target object P, and the second position is the position of a conveyance destination of the target object P. The movement destination information setting unit **40** may directly specify the position (coordinates) of the first position as the first position information. In addition, an identifier may be assigned to each waypoint A, and the movement destination information setting unit **40** may specify the identifier of a waypoint A corresponding to the first position as the first position information. The same applies to the second position information.

(49) FIG. **6** is a table showing an example of movement destination information. In the present embodiment, the movement destination information setting unit **40** sets the movement destination information for each target object P to be conveyed, in other words, for each work. That is, the movement destination information setting unit **40** associates target object information indicating a target object P to be conveyed, the first position information that is the conveyance source of the target object P, and the second position information indicating the conveyance destination of the target object P with each other so as to set the movement destination information for each target object P. Note that, for example, an identifier may be assigned to each target object P, and information indicating the identifier may be used as the target object information. Further, as illustrated in FIG. **6**, in the present embodiment, it is preferable for the movement destination information setting unit **40** to associate the target object information, the first position information, the second position information, and priority information with each other so as to set the movement destination information for each target object P. The priority information is information indicating a

priority order for conveying a target object P among a group of movement destination information for each target object P. That is, for example, a target object P having the highest priority in the priority information is to be conveyed first. FIG. 6 shows an example in which pieces of movement destination information are set as follows: movement destination information in which the priority is 0001 (first), the target object is P1, the first position is A1, and the second position is A2; movement destination information in which the priority is 0002 (second), the target object is P11, the first position is A11, and the second position is A3; movement destination information in which the priority is 0003 (third), the target object is P21, the first position is A21, and the second position is A4; movement destination information in which the priority is 0004 (fourth), the target object is P2, the first position is A31, and the second position is A5; and movement destination information in which the priority is 0005 (fifth), the target object is P21, the first position is A41, and the second position is A6. However, FIG. 6 is only an example, and the movement destination information may be optionally set in accordance with an order status or the like.

(50) In addition, the movement destination information setting unit 40 may set the movement destination information so as to include designation information for designating a mobile body 10 to move from the first position to the second position (a mobile body 10 to perform the work). That is, in the example of the present embodiment, the movement destination information setting unit 40 may associate the target object information, the first position information, the second position information, the priority information, and the designation information with each other so as to set the movement destination information for each target object P. In that case, for example, an identifier may be assigned to each mobile body 10, and information indicating the identifier may be used as the designation information.

(51) The movement destination information setting unit 40 may set the movement destination information in any method. For example, the movement destination information setting unit 40 may acquire an order information indicating a target object P to be conveyed, a conveyance source, and a conveyance destination, and set the movement destination information based on the order information. The movement destination information setting unit 40 transmits the set movement destination information to the information processing device 14 via the communication unit 30.

(52) Acquisition of Movement Destination Information

(53) The movement destination information acquisition unit 60 of the information processing device 14 acquires the movement destination information from the management device 12 via the communication unit 50.

(54) Setting of Work

(55) The work setting unit 62 of the information processing device 14 sets a work of the mobile body 10 based on the movement destination information. The work setting unit 62 sets the route R of the mobile body 10 to the movement destination as the work of the mobile body 10. In the present embodiment, the work setting unit 62 sets, as the route R of the mobile body 10, a first route to the first position (conveyance source) indicated by the first position information from an initial position at which the mobile body 10 is located immediately before starting to move to the first position and a second route to the second position (conveyance destination) indicated by the second position information from the first position. That is, the work setting unit 62 sets the route R of the mobile body 10 such that respective waypoints A from the initial position to the first position are set as the first route, and respective waypoints A from the first position to the second position are set as the second route. In the example of FIG. 1, the movement destination information indicates that the first position is a waypoint Ab and the second position is a waypoint Ac, and the work setting unit 62 sets, as the route R of the mobile body 10, the first route passing through respective waypoints A from the waypoint Aa, which is the initial position of the mobile body 10 selected, to the waypoint Ab and the second route passing through respective waypoints A from the waypoint Ab to the waypoint Ac.

(56) FIG. 7 is a table for explaining the setting of the work. When a plurality of mobile bodies 10

are deployed in the facility W, the work setting unit **62** selects a mobile body **10** that conveys a target object P as the work of the mobile body **10**. Also, when the movement destination information is set for a plurality of target objects P, the work setting unit **62** sets the route R of a mobile body **10** for each target object P. That is, the work setting unit **62** selects, for each target object P, a mobile body **10** that conveys the target object P, and sets the route of the selected mobile body **10**. In the example of FIG. 7, the work setting unit **62** selects a mobile body **10A** as the mobile body **10** that conveys a target object P₁ indicated by the movement information, and sets a route from the initial position of the mobile body **10A**, through A₁ as the first position, to A₂ as the second position (. . . waypoint A₁ . . .). Descriptions of mobile bodies selected for other target objects P illustrated in FIG. 7 and the routes (waypoints) thereof are the same as those above, and thus are omitted. Note that the work setting unit **62** may select a mobile body **10** in any manner, and may select a mobile body **10** for each target object P such that the time until the completion of the conveyance of all the target objects P is the shortest, for example. In the case where a target mobile body **10** has been designated as the designation information in the movement destination information, it is only necessary to select the mobile body **10** designated in the designation information.

(57) The work setting unit **62** transmits information on the set work to the mobile body **10** to which the set work is assigned. In the example of FIG. 7, the work setting unit **62** transmits information on the work for the target object P₁ and information on the work for the target object P₂ to the mobile body **10A**. The work setting unit **62** transmits information on the route R as the information on the work. The work setting unit **62** transmits information indicating respective waypoints A through which the route R passes as the information on the route R. For example, the work setting unit **62** may transmit position (coordinate) information of respective waypoints A through which the route R passes to the mobile body **10** as the information on the route R, or may transmit information indicating the identifiers of respective waypoints A through which the route R passes to the mobile body **10** as the information on the route R.

(58) Movement of Mobile Body

(59) The work acquisition unit **80** of a mobile body **10** acquires information on the route R set for the mobile body **10** from the information processing device **14**. The movement control unit **82** of the mobile body **10** moves the mobile body **10** along the route R acquired. The movement control unit **82** moves the mobile body **10** so that the mobile body **10** passes through respective waypoints A through which the route R passes. The mobile body **10** moves so as to pass through each waypoint A on the route R by sequentially grasping the position information of the mobile body **10** through the movement control unit **82**. The method of acquiring the position information of the mobile body **10** through the movement control unit **82** is optional. In the present embodiment, for example, a detection body (not illustrated) is disposed in the facility W, and the movement control unit **82** acquires the information on the position and the orientation of the mobile body **10** based on the detection of the detection body. Specifically, the mobile body **10** irradiates the detection body with a laser beam, receives light of the laser beam reflected from the detection body, and detects the position and the orientation of the mobile body **10** in the facility W. The method of acquiring the information on the position and the orientation of the mobile body **10** is not limited to using a detection body, and simultaneous localization and mapping (SLAM) may be used, for example.

(60) In the example of FIG. 1, the movement control unit **82** causes the mobile body **10** to move from the waypoint A_a, which is the initial position, to the waypoint A_b, which is the first position, so as to pass through each waypoint A from the waypoint A_a to the waypoint A_b. When the mobile body reaches the waypoint A_b, the movement control unit **82** controls the fork **24** to insert the fork **24** into the opening P_b of the target object P placed in the placement area AR₁ facing the waypoint A_b so as to pick up (load) the target object P. In this case, the movement control unit **82** may cause the sensor **26A** to detect the position and the orientation of the target object P at the waypoint A_b or at any position before reaching the waypoint A_b. Then, the movement control unit **82** may set an

approach route to the target object P based on the position and the orientation of the target object P, and approach the target object P along the approach route to pick up the target object P. That is, in that case, the movement control unit **82** may set a new approach route that allows a predetermined position and a predetermined orientation with respect to the position and the orientation of the target object P detected (the position and the orientation at which the mobile body **10** can pick up the target object P), and approach the target object P along the approach route. Alternatively, for example, the movement control unit **82** may cause the mobile body **10** to approach the target object P by performing feedback control (direct feedback control) based on the detection result of the position and the orientation of the target object P and the detection result of the position and the orientation of the mobile body **10**. In that case, switching to the direct feedback control may be performed during the approach along a route based on the position and the orientation of the target object P.

(61) After the mobile body **10** picks up the target object P, the movement control unit **82** causes the mobile body **10** to return to the waypoint Ab and then move to the waypoint Ac, which is the second position, so as to pass through each waypoint A from the waypoint Ab to the waypoint Ac. When the mobile body **10** reaches the waypoint Ac, the movement control unit **82** controls the fork **24** to drop (unload) the target object P in the placement area AR1 facing the waypoint Ac.

(62) After the mobile body **10** drops the target object P, the movement control unit **82** causes the mobile body **10** to return to the waypoint Ac. When a next route R in which the waypoint Ac is the initial position has already been set, the movement control unit **82** causes the mobile body **10** to move along that route R.

(63) Note that the movement control unit **82** moves the mobile body **10** while causing the sensor **26A** to detect the surroundings. The movement control unit **82** determines whether keeping moving the mobile body **10** causes the mobile body **10** to interfere with a surrounding object detected by the sensor **26A** and stops the movement of the mobile body **10** when it is determined that the mobile body interferes with the surrounding object. This suppresses the mobile body **10** from colliding with surrounding objects such as another mobile body and an obstacle. A determination criterion as to whether the surrounding object interferes with the mobile body **10** may be optional, and it may be determined that the object interferes when the distance from the mobile body to the object becomes less than a predetermined threshold value, for example.

(64) Exclusive Area

(65) Here, the mobile body **10** is controlled to move while suppressing collision with surrounding objects as described above, but a deadlock may occur between the mobile bodies **10**. On the other hand, in the present embodiment, setting an exclusive area T for the mobile body **10** in motion suppresses the occurrence of a deadlock. The exclusive area T is an area occupied by the mobile body **10**. That is, the mobile body **10** is permitted to enter the exclusive area T, but the other mobile body **10** is prohibited to enter the exclusive area T. Hereinafter, a setting method of the exclusive area T will be specifically described. Note that “deadlock” refers to a phenomenon in which each of a plurality of running programs or the like mutually waits for a result of other programs, and remains in a standby state and does not operate. In the present embodiment, “deadlock” may refer to a phenomenon in which the mobile bodies **10** remain stopped if there is a possibility that the mobile bodies **10** will collide with each other when the mobile bodies **10** keep moving along the current routes, and if it is impossible to set avoidance routes toward travel direction sides.

(66) Acquisition of Movement Information

(67) FIGS. **8** and **9** are schematic views for explaining setting of the exclusive area. Hereinafter, the mobile body **10** that is a setting target of the exclusive area T will be described as the first mobile body, and a time slot in which the exclusive area T is set will be described as the first time slot. In this case, the movement information acquisition unit **64** of the information processing device **14** acquires movement information on the first mobile body. The movement information acquisition unit **64** acquires, as movement information, position information on the first position where the

first mobile body is scheduled to be positioned in the first time slot and information on the travel direction of the first mobile body.

(68) The movement information acquisition unit **64** may acquire the position information on the first position by any method, and may acquire the position information on the first position based on the position information on the first mobile body, for example. In this case, for example, the movement information acquisition unit **64** may acquire the current position information on the first mobile body from the first mobile body, calculate the predicted position of the first mobile body in the first time slot based on the current position information on the first mobile body, and set the predicted position as the first position. For example, the first mobile body may calculate the predicted position of the first mobile body in the first time slot as the first position based on the current position information, and the movement information acquisition unit **64** may acquire, from the first mobile body, the position information on the first position calculated.

(69) The information on the travel direction of the first mobile body is information indicating the travel direction of the first mobile body in the route R. Since the route R (respective waypoints A to pass) of the first mobile body is set in advance by the work setting unit **62**, it is deemed that the travel direction of the first mobile body is also set in advance. Therefore, the movement information acquisition unit **64** can acquire the information on the travel direction of the first mobile body from the information on the route R of the first mobile body.

(70) FIG. **8** illustrates an example in which the first position of the mobile body **10A** (first mobile body) in the first time slot is the waypoint A.sub.1, and the travel direction of the mobile body **10A** at the waypoint A.sub.1 is a direction opposite to the Y direction (direction from the waypoint A.sub.1 toward the waypoint A.sub.2).

(71) Setting of Second Position

(72) The work setting unit **62** of the information processing device **14** sets the exclusive area T of the first mobile body based on the movement information on the first mobile body. The work setting unit **62** sets the second position, which is a position on the travel direction side from the first position, based on the position information on the first position and the travel direction in the first time slot. The work setting unit **62** may set any position on the travel direction side from the first position as the second position, and in the present embodiment, the second position is set based on the speed of the first mobile body. For example, the work setting unit **62** may calculate a distance L based on the following Formula (1) and set, as the second position, a position separated by the distance L from the first position toward the travel direction side. Note that the speed of the first mobile body here may be acquired optionally, and for example, the preset speed limit of the mobile body **10** may be set as the speed of the first mobile body, or the measured actual speed may be set as the speed of the first mobile body.

$$L = C.sub.1.Math.V.sup.2 + C.sub.2.Math.V + C.sub.3 \quad (1)$$

(73) V in Formula (1) is a moving speed of the first mobile body, and C.sub.1, C.sub.2, and C.sub.3 are preset coefficients. The coefficient C.sub.1 is preferably set in consideration of the braking distance of the mobile body **10**. The coefficient C.sub.2 is preferably set in consideration of an assumed maximum delay time (maximum delay time of arrival time at the first position) and a communication time between the mobile body **10** and the information processing device **14**. The coefficient C.sub.3 is preferably set in consideration of the size of the mobile body **10**.

(74) FIG. **8** illustrates an example in which the waypoint A.sub.4 present in the direction opposite to the Y direction from the waypoint A.sub.1 is set as the second position.

(75) (Setting of Exclusive Area)

(76) The work setting unit **62** sets an area (route) between the first position and the second position, in other words, an area on the front side in the travel direction from the first position, as the exclusive area T of the first mobile body in the first time slot. Furthermore, the work setting unit **62** sets, as the exclusive area T of the first mobile body in the first time slot, an area from the first position to the second position, in other words, respective waypoints A from the waypoint A set as

the first position to the waypoint A set as the second position. The work setting unit **62** sets position information on the area between the first position and the second position, that is, information indicating the position of the exclusive area T, as information on the exclusive area T. Furthermore, in addition to the information indicating the position of the exclusive area T, the work setting unit **62** also sets, as information on the exclusive area T, information on the travel direction of the first mobile body in the exclusive area T. FIG. **8** gives an example in which the area from the waypoint A.sub.1, which is the first position, to the waypoint A4, which is the second position, that is, the waypoints A.sub.1, A.sub.2, A.sub.3, and A.sub.4, are set as an exclusive area TA of the mobile body **10A** in the first time slot, and the travel direction of the mobile body **10A** in the exclusive area TA is on the side opposite to the Y direction (direction connecting waypoints A.sub.1, A.sub.2, A.sub.3, and A.sub.4).

(77) More specifically, the work setting unit **62** determines whether the exclusive area T of the first mobile body can be set based on the position information on the first position and the second position, the movement information on the first mobile body in the first position, and the information on the exclusive area T of another mobile body. Specifically, the work setting unit **62** acquires, as information on the exclusive area T of another mobile body, the position information on the exclusive area T already set for a mobile body other than the first mobile body and the information on the travel direction of the mobile body in the exclusive area T. Then, the work setting unit **62** determines whether there is an overlapping exclusive area in the exclusive area T of the other mobile body. The overlapping exclusive area is an exclusive area T that is set in the first time slot, overlaps an area (respective waypoints A) from the first position to the second position for the first mobile body, and has a travel direction different from the travel direction of the first mobile body. The exclusive area T of another mobile body overlapping the area from the first position to the second position of the first mobile body means that at least parts of the respective areas overlap each other. The travel direction being different from the travel direction of the first mobile body means that the travel direction of the first mobile body is different from the travel direction of the other mobile body in the overlapping area and furthermore means that the travel direction of the first mobile body is opposite to the travel direction of the other mobile body in the overlapping area.

(78) When there is the overlapping exclusive area, the work setting unit **62** does not set the exclusive area T of the first mobile body in the first time slot. That is, the work setting unit **62** does not set the exclusive area T of the first mobile body in a case where the other mobile body **10** has already reserved a position overlapping in different travel directions in the same time slot. FIG. **8** gives an example of a case where the waypoints A.sub.6, A.sub.5, A.sub.4, and A.sub.3 have been set as an exclusive area TB of the mobile body **10B** in the first time slot with the Y direction (direction connecting the waypoints A.sub.6, A.sub.5, A.sub.4, and A.sub.3) as the travel direction. In this case, the travel direction of the mobile body **10A** is opposite to the travel direction of the mobile body **10B** in the exclusive area TB, and the area from the first position to the second position is the waypoints A.sub.1, A.sub.2, A.sub.3, and A.sub.4 and overlap the exclusive area TB. Therefore, the exclusive area TA of the mobile body **10A** is not set.

(79) On the other hand, when there is no overlapping exclusive area, the work setting unit **62** sets the area from the first position to the second position as the exclusive area of the first mobile body in the first time slot. That is, the work setting unit **62** sets the exclusive area T of the first mobile body when an overlapping position is not reserved by the other mobile body **10** in the same time slot. Furthermore, the work setting unit **62** sets the exclusive area T in a case where the travel direction of the other mobile body **10** is the same as the travel direction of the first mobile body even if the other mobile body **10** has reserved the position overlapping in the same time slot. FIG. **9** gives an example of a case where the waypoints A.sub.3, A.sub.4, A.sub.5, and A.sub.6 have been set as an exclusive area TB of the mobile body **10B** in the first time slot with the opposite direction to the Y direction (direction connecting the waypoints A.sub.3, A.sub.4, A.sub.5, A.sub.6) as the

travel direction. In this case, the area from the first position to the second position of the mobile body **10A** is the waypoints A.sub.1, A.sub.2, A.sub.3, and A.sub.4 and overlaps the exclusive area TB, but the travel direction is the same as the travel direction of the mobile body **10B** in the exclusive area TB. Therefore, the exclusive area TA of the mobile body **10A** is set.

(80) (Transmission of Exclusive Area)

(81) After setting the exclusive area T of the first mobile body, the work setting unit **62** outputs, to the first mobile body, a command to permit movement within the exclusive area T in the first time slot. After acquiring the command to permit movement within the exclusive area T in the first time slot, the first mobile body can move within the exclusive area T in the first time slot. On the other hand, when the exclusive area TA of the mobile body **10A** is not set, the work setting unit **62** outputs, to the first mobile body, a command not to permit movement within the exclusive area T in the first time slot. However, not limited to this, the work setting unit **62** needs not output the command not to permit movement to the first mobile body. After acquiring the command not to permit or in a case of not acquiring the command to permit, the first mobile body does not move within the exclusive area T in the first time slot. That is, in this case, the first mobile body does not enter the exclusive area T and is positioned outside the exclusive area T in the first time slot.

(82) After the exclusive area T of the first mobile body is set in the first time slot, the work setting unit **62** does not permit the other mobile body **10** (second mobile body) to move within the exclusive area T in a travel direction different from that of the first mobile body in the first time slot. That is, in the example of FIG. **8**, in a case where the exclusive area TA of the mobile body **10A** is set, the exclusive area TB is not set for the mobile body **10B**, and the mobile body **10B** cannot move the waypoints A.sub.6, A.sub.5, A.sub.4, and A.sub.3 in the first time slot. On the other hand, the work setting unit **62** permits the other mobile body **10** (second mobile body) to move within the exclusive area T in the same direction as that of the first mobile body in the first time slot. That is, in the example of FIG. **9**, in a case where the exclusive area TA of the mobile body **10A** is set, the exclusive area TB is set for the mobile body **10B**, and the mobile body **10B** can move the waypoints A.sub.3, A.sub.4, A.sub.5, and A.sub.6 in the first time slot.

(83) The movement information acquisition unit **64** executes the processing of setting the exclusive area T and outputting a command as described above for each mobile body **10** at predetermined time intervals. That is, the movement information acquisition unit **64** sequentially updates the exclusive area T in accordance with the movement of each mobile body **10** by setting the exclusive area T on the front side of the mobile body **10** in the travel direction at predetermined time intervals for each mobile body **10**.

Example of Exclusive Area at Intersection

(84) FIG. **10** is a schematic view explaining an example of setting of an exclusive area at an intersection. FIG. **10** gives an example of a case where the route connecting the waypoints A.sub.1, A.sub.2, and A.sub.3 and the route connecting the waypoints A.sub.12, A.sub.2, and A.sub.11 intersect with each other. In FIG. **10**, the waypoints A.sub.12, A.sub.2, and A.sub.3 are set in the exclusive area TA with this order as the travel direction. In this case, the route having the waypoints A.sub.11, A.sub.2, and A.sub.3 in this order as the travel direction overlaps the exclusive area TA, but the travel direction is the same. Therefore, other mobile bodies can move along this route, in other words, this route can also be set as the exclusive area. The route having the waypoints A.sub.11, A.sub.2, and A.sub.1 in this order as the travel direction does not overlap the exclusive area TA. Therefore, other mobile bodies can move along this route, in other words, this route can also be set as the exclusive area. On the other hand, the route having the waypoints A.sub.1, A.sub.2, and A.sub.12 in this order as the travel direction overlaps the exclusive area TA and includes a section in which the travel direction is opposite. Therefore, other mobile bodies cannot move along this route, in other words, this route cannot be set as the exclusive area.

(85) Processing Flow

(86) Next, a setting flow of the exclusive area T described above will be described. FIG. **11** is a

flowchart explaining the setting flow of the exclusive area according to the present embodiment. As illustrated in FIG. 11, in the information processing device 14, the movement information acquisition unit 64 acquires movement information on the first mobile body (step S10), and the work setting unit 62 sets the first position and the second position based on the movement information on the first mobile body (step S12). The work setting unit 62 determines whether the other exclusive area T (overlapping exclusive area) having a different travel direction has been set in the same time slot between the first position and the second position (step S14), and if the overlapping exclusive area has not been set (step S14; No), the work setting unit 62 sets an area between the first position and the second position as the exclusive area T of the first mobile body (step S16). Thereafter, the process proceeds to step S18, and if the processing is to be ended (step S18; Yes), this processing is ended, and if the processing is not to be ended (step S18; No), the process returns to step S10, and the setting processing of the exclusive area T in the next time slot is continued. Also in a case where the overlapping exclusive area has been set, the processing proceeds to step S18, and the setting processing of the exclusive area T in the next time slot may be continued.

(87) As described above, in the present embodiment, the area on the front side in the travel direction of the first mobile body, that is, the area between the first position and the second position is set as the exclusive area T. The exclusive area T is set such that a mobile body traveling in a travel direction different from that of the first mobile body cannot enter, but a mobile body traveling in the same travel direction as that of the first mobile body can enter. In this way, setting the area on the front side in the travel direction as the exclusive area T can suppress occurrence of a deadlock even when, for example, a delay occurs in the movement of the mobile body 10. Setting the exclusive area T so as not to permit entry of a mobile body traveling in a different travel direction can appropriately suppress a deadlock due to mobile bodies 10 traveling in different directions facing each other. The deadlock can be suppressed by a simple procedure of not permitting movement in a different travel direction. Furthermore, setting the exclusive area T so as to permit entry of a mobile body traveling in the same travel direction reduces the movement restriction of the mobile body in the same direction where the risk of deadlock is low and can improve the throughput.

Second Embodiment

(88) Next, a second embodiment will be described. The second embodiment is different from the first embodiment in the setting method of the exclusive area T. In the second embodiment, the description of parts having the same configuration as those in the first embodiment will be omitted.

(89) FIG. 12 is a schematic view illustrating an example of an exclusive area in the second embodiment. Here, on a route where the first mobile body is scheduled to move, a position where the route branches to (intersects with) another route is defined as a first branch position, and a position where the route branches to (intersects with) another route next to the first branch position in the travel direction is defined as a second branch position. That is, the route does not branch to another route between the first branch position and the second branch position. In this case, when the second position set is positioned between the first branch position and the second branch position, the work setting unit 62 sets the first position to the second branch position as the exclusive area T. In the example of FIG. 12, the first position of the mobile body 10A is the waypoint A.sub.1, and the second position is the waypoint A.sub.4. Then, since the waypoint A.sub.4 is positioned between the waypoint A.sub.1 that is the first branch position and the waypoint A.sub.5 that is the second branch position, the work setting unit 62 sets respective waypoints A from the waypoint A.sub.1 to the waypoint A.sub.5 as the exclusive area TA of the mobile body 10A in the first time slot. Therefore, the exclusive area TB in which the mobile body 10B has the waypoints A.sub.7, A.sub.6, A.sub.5, A.sub.11, and A.sub.12 in this order as the travel direction is not set because the waypoint A.sub.5 overlaps the exclusive area TA and the travel direction at the waypoint A.sub.5 is opposite.

(90) As described above, in the second embodiment, when the second position is positioned on a non-branch route between the first branch position and the second branch position, the exclusive area T is extended to the second branch position adjacent to the second position on the travel direction side. This can more suitably suppress the deadlock. For example, in FIG. 12, if the area up to the waypoint A.sub.4, which is the second position, is set as the exclusive area TA, the mobile body 10B can enter the area up to the waypoint A.sub.5 in the same time slot. In this case, the mobile body 10A moves on the opposite side of the Y direction toward the waypoint A.sub.5, and the mobile body 10B moves on the Y direction side from the waypoint A.sub.5. This may cause the mobile bodies 10A and 10B to face each other and cause a deadlock. On the other hand, in the second embodiment, since the area up to the waypoint A.sub.5, which is the second branch position, is set to the exclusive area TA, the mobile body 10B cannot enter the area up to the waypoint A.sub.5, and the deadlock can be suitably suppressed.

(91) FIG. 13 is a schematic view illustrating another example of the exclusive area in the second embodiment. Here, as illustrated in FIG. 13, there is a case of setting, as the route of the mobile body 10B, a route for entering the exclusive area TA in a direction opposite to the travel direction of the mobile body 10A, and then turning back to the same direction as the travel direction of the mobile body 10A. As described above, in a case where the route of the mobile body 10B is directed to the opposite side of the travel direction of the mobile body 10A in the exclusive area TA and then turns back to the same direction side, the work setting unit 62 may set the exclusive area TB of the mobile body 10B. That is, in the example of FIG. 13, when the route of the mobile body 10B is in the order of the waypoints A.sub.6, A.sub.5, A.sub.4, and A.sub.5, the work setting unit 62 may set, as the exclusive area TB for the mobile body 10B, the waypoint A.sub.6, which is the first position, the waypoint A.sub.5, and the waypoint A.sub.4, and A.sub.5, which is the second position. That is, a deadlock with the mobile body 10A does not occur when the mobile body 10B is directed to the side opposite to the travel direction of the mobile body 10A, but later turns back and is directed to the travel direction side of the mobile body 10A. Therefore, even if the exclusive area TA of the mobile body 10A is set, the exclusive area TB of the mobile body 10B can be set.

Third Embodiment

(92) Next, a third embodiment will be described. The second embodiment is different from the first embodiment in the setting method of the exclusive area T. In the third embodiment, the description of parts having the same configuration as those in the first embodiment will be omitted. The third embodiment can also be applied to the second embodiment.

(93) FIG. 14 is a schematic view illustrating an example of an exclusive area in the third embodiment. The work setting unit 62 determines whether there is a neighboring exclusive area in the exclusive area T of another mobile body. The neighboring exclusive area refers to an exclusive area set on a route (waypoint A) at a position different from but close to the route of the first mobile body. Specifically, the neighboring exclusive area is the exclusive area T that is set in the first time slot (time slot in which the exclusive area of the first mobile body is set), exists within a predetermined distance range with respect to the area (respective waypoints A) from the first position to the second position for the first mobile body, and has a travel direction different from the travel direction of the first mobile body in a section that is within the predetermined distance range. Here, a travel direction being different from the travel direction of the first mobile body is not limited to the travel direction being opposite to the travel direction of the first mobile body and includes a direction intersecting the travel direction of the first mobile body. The predetermined distance here may be optionally set. For example, in a case where the mobile bodies 10 are positioned at respective positions separated by a predetermined distance, a distance at which the mobile bodies 10 interfere with each other may be set as the predetermined distance.

(94) When there is the neighboring exclusive area, the work setting unit 62 does not set the exclusive area T of the first mobile body in the first time slot. That is, the work setting unit 62 does not set the exclusive area T of the first mobile body when the other mobile body 10 has reserved a

route close in a different travel direction in the same time slot. FIG. 14 gives an example of a case where the waypoints A.sub.5, A.sub.6, A.sub.7, and A.sub.8 have been set as the exclusive area TB of the mobile body 10B in the first time slot with the Y direction (direction connecting waypoints A.sub.5, A.sub.6, A.sub.7, A.sub.8) as the travel direction. In this case, the travel direction of the mobile body 10A is opposite to the travel direction of the mobile body 10B in the exclusive area TB, and the area from the first position to the second position is the waypoints A.sub.1, A.sub.2, A.sub.3, and A.sub.4, and is within a predetermined distance range with respect to the exclusive area TB. Therefore, the exclusive area TA of the mobile body 10A is not set.

(95) On the other hand, when there is no neighboring exclusive area, the work setting unit 62 sets the area from the first position to the second position as the exclusive area of the first mobile body in the first time slot. That is, the work setting unit 62 sets the exclusive area T of the first mobile body when a neighboring position has not been reserved by the other mobile body 10 in the same time slot. Furthermore, even if the other mobile body 10 has reserved a neighboring position (neighboring exclusive area) in an overlapping time slot, the work setting unit 62 sets the exclusive area T when the travel direction of the mobile body 10 is the same as the travel direction of the first mobile body. That is, in the example of FIG. 14, when the travel direction of the mobile body 10B in the exclusive area TB is opposite to the Y direction, the waypoints A.sub.1, A.sub.2, A.sub.3, and A.sub.4 are set as the exclusive area T of the mobile body 10A.

(96) When the exclusive area T of the first mobile body is set in the first time slot, the work setting unit 62 does not permit the other mobile body 10 (second mobile body) to move along a route within a predetermined distance from the exclusive area T in a travel direction different from that of the first mobile body in the first time slot. That is, in the example of FIG. 14, in a case where the exclusive area TA of the mobile body 10A is set, the exclusive area TB is not set for the mobile body 10B, and the mobile body 10B cannot move the waypoints A.sub.5, A.sub.6, A.sub.7, and A.sub.8 in the first time slot. On the other hand, the work setting unit 62 permits the other mobile body 10 (second mobile body) to move within the exclusive area T in the same direction as that of the first mobile body in the first time slot. That is, in the example of FIG. 14, when the travel direction of the mobile body 10B is opposite to the Y direction, the exclusive area TB is also set in the mobile body 10B at the waypoints A.sub.8, A.sub.7, A.sub.6, and A.sub.5, and the mobile body 10B can move in the exclusive area TB in the first time slot.

(97) As described above, in the third embodiment, the route is different from the exclusive area T, but when the distance is short, movement on that route is not permitted. Therefore, the occurrence of a deadlock due to the plurality of mobile bodies 10 moving along close routes in the same time slot can be suppressed.

Fourth Embodiment

(98) Next, a fourth embodiment will be described. The fourth embodiment is different from the first embodiment in the setting method of the exclusive area T. In the fourth embodiment, the description of parts having the same configuration as those in the first embodiment will be omitted. The fourth embodiment is also applicable to the second embodiment and the third embodiment.

(99) FIG. 15 is a schematic view illustrating an example of an exclusive area in the fourth embodiment. In the fourth embodiment, the work setting unit 62 acquires information on the route R set for the first mobile body and information on the route R set for a mobile body other than the first mobile body. Then, the work setting unit 62 extracts an overlapping section that is a section overlapping with the route R set for a mobile body other than the first mobile body in the route R set for the first mobile body. The work setting unit 62 determines whether the route between the first position and the second position for the first mobile body overlaps the overlapping section. Here, the route between the first position and the second position overlapping the overlapping section means that at least parts of the route between the first position and the second position and the overlapping section overlap each other. When the route between the first position and the second position overlaps the overlapping section, the work setting unit 62 sets an area from the first

position to an end position in the overlapping section as the exclusive area T. The end position in the overlapping section refers to an end on the travel direction side of the first mobile body (waypoint A on the most travel direction side of the first mobile body) in the overlapping section. In the example of FIG. 12, since the route of the mobile body **10A** is in the order of the waypoint A.sub.1, the waypoints A.sub.2 to A.sub.5, and the waypoints A.sub.6 to A.sub.10, and the route of the mobile body **10B** is in the order of the waypoint A.sub.11, the waypoints A.sub.8 to A.sub.5, and the waypoints A.sub.4 to A.sub.0, the overlapping section is the waypoints A.sub.2 to A.sub.5 to A.sub.8. Then, assuming that the first position of the mobile body **10A** is the waypoint A.sub.1 and the second position is the waypoint A.sub.4, the work setting unit **62** sets the waypoint A.sub.1 to the waypoint A.sub.8 as the exclusive area TA of the mobile body **10A**.

(100) As described above, in the fourth embodiment, when the area from the first position to the second position overlaps the route of the other mobile body **10**, the exclusive area T is extended to the final point of the overlapped section. This can more suitably suppress the deadlock in a section in which routes are set in an overlapping manner.

Effects

(101) As described above, the information processing method according to the disclosure includes the steps of: acquiring movement information on a first mobile body including information on a first position through which the first mobile body is scheduled to pass in a first time slot and information on a travel direction of the first mobile body; and setting, as the exclusive area T in the first time slot, an area between the first position and a second position on a travel direction side of the first mobile body from the first position based on the movement information on the first mobile body. The exclusive area T is set in a manner that a second mobile body other than the first mobile body is not permitted to move within the exclusive area T in a travel direction different from the travel direction of the first mobile body in the first time slot and that the second mobile body is permitted to move within the exclusive area T in a travel direction identical to the travel direction of the first mobile body in the first time slot.

(102) According to the disclosure, setting the area on the front side in the travel direction as the exclusive area T in this manner can suppress occurrence of a deadlock even when, for example, a delay occurs in the movement of the mobile body **10**. Setting the exclusive area T so as not to permit entry of a mobile body traveling in a different travel direction can appropriately suppress a deadlock due to mobile bodies **10** traveling in different directions facing each other. The deadlock can be suppressed by a simple procedure of not permitting movement in a different travel direction. Furthermore, setting the exclusive area T so as to permit entry of a mobile body traveling in the same travel direction reduces the movement restriction of the mobile body in the same direction where the risk of deadlock is low and can improve the throughput.

(103) In the step of setting the exclusive area T, the second position is set based on the speed of the first mobile body. Setting the second position in this manner can more suitably suppress occurrence of a deadlock.

(104) In the step of setting the exclusive area T, in a case where, on the route on the travel direction side of the first mobile body, the second position is positioned between the first branch position at which the route on the travel direction side is branched to another route and the second branch position at which the route on the travel direction side is branched to another route next to the first branch position, an area from the first position to the second branch position is set as the exclusive area T. Setting the exclusive area T in this manner can more suitably suppress occurrence of a deadlock.

(105) The exclusive area T is set such that the second mobile body is not permitted to move along the route within a predetermined distance range from the exclusive area in the first time slot. Setting the exclusive area T in this manner can suppress the occurrence of a deadlock due to the plurality of mobile bodies **10** moving along close routes in the same time slot.

(106) The information processing method of the disclosure further includes the step of acquiring

information on a first route along which the first mobile body is scheduled to move and a second route along which the second mobile body is scheduled to move. In the step of setting the exclusive area T, in a case where the section between the first position and the second position overlaps the overlapping section in which the first route and the second route overlap, the area from the first position to the end position of the overlapping section on the travel direction side of the first mobile body is set as the exclusive area T. This can more suitably suppress the deadlock in a section in which routes are set in an overlapping manner.

(107) The embodiments of the disclosure have been described above, but the embodiment is not limited by the details of the embodiments above. Furthermore, the constituent elements of the above-described embodiments include elements that are able to be easily conceived by a person skilled in the art, and elements that are substantially the same, that is, elements of an equivalent scope. Furthermore, the constituent elements described above can be appropriately combined. Furthermore, it is possible to make various omissions, substitutions, and changes to the constituent elements within a range not departing from the scope of the above-described embodiments.

(108) While preferred embodiments of the invention have been described as above, it is to be understood that variations and modifications will be apparent to those skilled in the art without departing from the scope and spirit of the invention. The scope of the invention, therefore, is to be determined solely by the following claims.

Claims

1. An information processing method, comprising: a step of acquiring movement information on a first mobile body including information on a first position through which the first mobile body is scheduled to pass in a first time slot and information on a travel direction of the first mobile body; and a step of setting, as an exclusive area in the first time slot, an area between the first position and a second position on a travel direction side of the first mobile body from the first position based on the movement information on the first mobile body, wherein the exclusive area is set in a manner that a second mobile body other than the first mobile body is not permitted to move within the exclusive area in a travel direction different from the travel direction of the first mobile body in the first time slot and that the second mobile body is permitted to move within the exclusive area in a travel direction identical to the travel direction of the first mobile body in the first time slot, the method further comprises a step of outputting, after setting the exclusive area of the first mobile body, to the first mobile body, a command to permit movement within the exclusive area in the first time slot, when the second mobile body moves in the exclusive area in the same direction of travel as the first mobile body, outputting a command to allow movement to the second mobile body, and when the second mobile body moves in the exclusive area in a direction of travel different from the first mobile body, not outputting a command to allow movement to the second mobile body.
2. The information processing method according to claim 1, wherein in the step of setting, the second position is set based on a speed of the first mobile body.
3. The information processing method according to claim 1, wherein in the step of setting, in a case where, on a route on the travel direction side, the second position is positioned between a first branch position at which the route on the travel direction side is branched to another route and a second branch position at which the route on the travel direction side is branched to another route next to the first branch position, an area from the first position to the second branch position is set as the exclusive area.
4. The information processing method according to claim 1, wherein the exclusive area is set in a manner that the second mobile body is not permitted to move along a route within a predetermined distance range from the exclusive area in the first time slot.
5. The information processing method according to claim 1, further comprising a step of acquiring information on a first route on which the first mobile body is scheduled to move and a second route

on which the second mobile body is scheduled to move, wherein in the step of setting, in a case where a section between the first position and the second position overlaps an overlapping section in which the first route and the second route overlap, an area from the first position to an end position of the overlapping section on the travel direction side of the first mobile body is set as the exclusive area.

6. An information processing device, comprising: a movement information acquisition unit configured to acquire movement information on a first mobile body including information on a first position through which the first mobile body is scheduled to pass in a first time slot and information on a travel direction of the first mobile body; and a work setting unit configured to set, as an exclusive area in the first time slot, an area between the first position and a second position on a travel direction side of the first mobile body from the first position based on the movement information on the first mobile body, wherein the exclusive area is set in a manner that a second mobile body other than the first mobile body is not permitted to move within the exclusive area in a travel direction different from the travel direction of the first mobile body in the first time slot and that the second mobile body is permitted to move within the exclusive area in a travel direction identical to the travel direction of the first mobile body in the first time slot, the work setting unit outputs, after setting the exclusive area of the first mobile body, to the first mobile body, a command to permit movement within the exclusive area in the first time slot, when the second mobile body moves in the exclusive area in the same direction of travel as the first mobile body, outputs a command to allow movement to the second mobile body, and when the second mobile body moves in the exclusive area in a direction of travel different from the first mobile body, not output a command to allow movement to the second mobile body.

7. A non-transitory computer readable storage medium storing a program that causes a computer to execute: a step of acquiring movement information on a first mobile body including information on a first position through which the first mobile body is scheduled to pass in a first time slot and information on a travel direction of the first mobile body; and a step of setting, as an exclusive area in the first time slot, an area between the first position and a second position on a travel direction side of the first mobile body from the first position based on the movement information on the first mobile body, wherein the exclusive area is set in a manner that a second mobile body other than the first mobile body is not permitted to move within the exclusive area in a travel direction different from the travel direction of the first mobile body in the first time slot and that the second mobile body is permitted to move within the exclusive area in a travel direction identical to the travel direction of the first mobile body in the first time slot, and the program further causes the computer to execute: a step of outputting, after setting the exclusive area of the first mobile body, to the first mobile body, a command to permit movement within the exclusive area in the first time slot, when the second mobile body moves in the exclusive area in the same direction of travel as the first mobile body, outputting a command to allow movement to the second mobile body, and when the second mobile body moves in the exclusive area in a direction of travel different from the first mobile body, not outputting a command to allow movement to the second mobile body.
