

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412499
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Kim; Youngrog et al.

Electronic device for managing temperature, and operating method therefor

Abstract

Disclosed is an electronic device comprising: a sensor configured to measure a temperature of the electronic device; a flexible display wherein an area of the flexible display visible to the outside can be changed; a memory storing executable instructions; and at least one processor, comprising processing circuitry configured to access the memory and execute the instructions, wherein at least one processor, individually and/or collectively, is configured to: identify a first input for changing the size of the visible area of the flexible display, identify the temperature of the electronic device via the sensor based on the identification of the first input, and identify change conditions of the size of the flexible display based on the identified temperature.

Inventors: Kim; Youngrog (Suwon-si, KR), Kim; Kibeom (Suwon-si, KR), Choi; Junwoo (Suwon-si, KR), Kwak; Myunghoon (Suwon-si, KR), Lee; Jookwan (Suwon-si, KR), Park; Jihea (Suwon-si, KR), Kim; Yangwook (Suwon-si, KR), Lee; Junghyeob (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 85603161

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 18/605060

Filed: March 14, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240221563 A1	Jul. 04, 2024

Foreign Application Priority Data

KR	10-2021-0124843	Sep. 17, 2021
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/KR2022/013458 20220907 PENDING child-doc US 18605060

Publication Classification

Int. Cl.: **G09G3/00** (20060101); **G01K13/00** (20210101); **G06F3/04845** (20220101); **G06F3/16** (20060101); G06F3/01 (20060101); G06F3/0488 (20220101)

U.S. Cl.:

CPC **G09G3/035** (20200801); **G01K13/00** (20130101); **G06F3/04845** (20130101); G06F3/016 (20130101); G06F3/0488 (20130101); G06F3/167 (20130101); G09G2320/041 (20130101); G09G2354/00 (20130101)

Field of Classification Search

CPC: G09G (3/035); G09G (2320/041); G09G (2354/00); G01K (13/00); G01K (1/02); G06F (3/04845); G06F (3/016); G06F (3/0488); G06F (3/167); G06F (3/01); G06F (3/02); G06F (3/0484); G06F (3/16); G06F (1/16); G06F (1/20)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8836718	12/2013	Choi et al.	N/A	N/A
9098188	12/2014	Kim	N/A	N/A
9524057	12/2015	Cho et al.	N/A	N/A
10304417	12/2018	Park et al.	N/A	N/A
11062683	12/2020	Park et al.	N/A	N/A
11380283	12/2021	Shim et al.	N/A	N/A
11385684	12/2021	Kwon	N/A	N/A
11520387	12/2021	Koo et al.	N/A	N/A
2011/0157029	12/2010	Tseng	N/A	N/A
2012/0064946	12/2011	Voetberg	455/566	G06F 3/0481
2012/0127088	12/2011	Pance	345/173	G06F 3/04812
2014/0015784	12/2013	Oonishi	345/173	H04M 1/72403
2014/0282161	12/2013	Cash	N/A	N/A
2014/0372920	12/2013	Choi et al.	N/A	N/A
2015/0348493	12/2014	Chae	345/212	G09G 5/14
2017/0300217	12/2016	Brasseur et al.	N/A	N/A
2019/0088212	12/2018	Itoh et al.	N/A	N/A
2020/0090628	12/2019	Park et al.	N/A	N/A
2022/0121244	12/2021	Kwon	N/A	G06F 1/1652
2023/0029563	12/2022	Choi et al.	N/A	N/A
2023/0102896	12/2022	Koh et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
10-1638056	12/2015	KR	N/A
10-2018-0134236	12/2017	KR	N/A
10-1946365	12/2018	KR	N/A
10-2020-0064573	12/2019	KR	N/A
10-2021-0037548	12/2020	KR	N/A
10-2246554	12/2020	KR	N/A
10-2256681	12/2020	KR	N/A
2021/085658	12/2020	WO	N/A
2021/107225	12/2020	WO	N/A
2021/141162	12/2020	WO	N/A

OTHER PUBLICATIONS

International Search Report dated Dec. 29, 2022 in PCT/KR2022/013458, 4 pages. cited by applicant

Primary Examiner: Sherman; Stephen G

Attorney, Agent or Firm: Nixon & Vanderhye, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of International Application No. PCT/KR2022/013458 designating the United States, filed on Sep. 7, 2022, in the Korean Intellectual Property Receiving Office and claiming priority to Korean Patent Application No. 10-2021-0124843, filed on Sep. 17, 2021, in the Korean Intellectual Property Office, the disclosures of each of which are incorporated by reference herein in their entireties.

BACKGROUND

Field

(1) The disclosure relates to an electronic device for managing a temperature and an operating method therefor.

Description of Related Art

(2) An electronic device may provide various functions, such as the playback of media content, games, and web surfing, as well as voice calls or short messages. There is a need to expand a display of the electronic device for a user to conveniently use the various functions of the electronic device. However, as the display becomes wider, the portability of the electronic device may decrease. Thus, an electronic device capable of mounting a flexible display and changing a display area, for example, a foldable-, rollable-, or slidable-type electronic device has been developed. A wide screen may be provided, if necessary, to improve the convenience of use, while maintaining the excellent portability of the electronic device, by means of a structure in which it is able to expand or collapse the display area.

(3) The electronic device may include a driving unit which provides a physical force for expanding or collapsing the display area.

(4) A driving unit of an electronic device may malfunction due to a temperature, or the life of the driving unit of the electronic device may be shortened.

(5) When the driving unit malfunctions, an error in software may occur and a damage in hardware may occur in another component combined with the driving unit.

SUMMARY

(6) According to an example embodiment of the disclosure, an electronic device is provided. The electronic device may include: a sensor configured to measure a temperature of the electronic device, a flexible display, a size of an externally visible area of the flexible display being changeable, a memory storing executable instructions, and at least one processor, comprising processing circuitry, that individually and/or collectively, is configured to access the memory and execute the instructions. At least one processor, individually and/or collectively, may be configured to: identify a first input for changing the size of the visible area of the flexible display, identify the temperature of the electronic device via the sensor based on identifying the first input, and identify a size change condition of the flexible display based on the identified temperature.

(7) According to an example embodiment of the disclosure, a method of operating an electronic device is provided. The method may include: identifying a first input for changing a size of an externally visible area of a flexible display of the electronic device, identifying a temperature of the electronic device via a sensor of the electronic device based on identifying the first input, and identifying a size change condition of the flexible display of the electronic device based on the identified temperature.

(8) The technical problems to be addressed by the disclosure are not limited to the aforementioned problems, and any other technical problems not mentioned herein will be clearly understood from the following description by those skilled in the art to which the disclosure pertains.

(9) According to various example embodiments disclosed in the disclosure, an input for expanding or collapsing a display area may be delayed based on a temperature, thus preventing and/or reducing malfunctioning of the driving unit.

(10) Thus, the driving unit of the electronic device may be prevented/reduced from malfunctioning and/or the life of the driving unit of the electronic device may be improved.

(11) Furthermore, an error in software and/or a damage in hardware, which are/is caused by the malfunction of the driving unit of the electronic device, may be avoided.

(12) The effects that are achieved through various example embodiments of the disclosure may not be limited to what has been particularly described herein, and other advantages not described herein may be more clearly understood from the following detailed description by those skilled in the art.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and other aspects, features and advantages of certain embodiments of the present disclosure will be more apparent from the following detailed description, taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a block diagram illustrating an example electronic device in a network environment according to various embodiments;

(3) FIG. 2A included perspective views illustrating an example electronic device according to various embodiments;

(4) FIG. 2B includes perspective views illustrating an example electronic device according to various embodiments;

(5) FIG. 2C includes perspective views illustrating an example electronic device according to various embodiments;

(6) FIG. 2D is a diagram illustrating an example electronic device according to various embodiments;

(7) FIG. 2E is a diagram illustrating an example electronic device according to various embodiments;

- (8) FIG. 3 is a block diagram illustrating an example configuration of an electronic device according to various embodiments;
- (9) FIG. 4A is a flowchart illustrating an example operation of an electronic device according to various embodiments;
- (10) FIG. 4B is a diagram illustrating user interfaces of an electronic device according to various embodiments;
- (11) FIG. 5 is a flowchart illustrating an example operation of outputting a user interface in an electronic device according to various embodiments;
- (12) FIG. 6 is a graph illustrating a relationship between a temperature and latency according to various embodiments;
- (13) FIG. 7 is a diagram illustrating an example user interface output according to latency by an electronic device according to various embodiments;
- (14) FIG. 8 is a diagram illustrating an example user interface guiding an end point of a trigger input according to various embodiments;
- (15) FIG. 9 is a diagram illustrating an example user interface indicating a degree to which a state change condition is satisfied according to various embodiments;
- (16) FIG. 10 is a diagram illustrating an example user interface indicating a degree to which a state change condition is satisfied according to various embodiments;
- (17) FIG. 11A is a diagram illustrating an example user interface indicating a degree to which a state change condition is satisfied according to various embodiments;
- (18) FIG. 11B is a graph illustrating a relationship between changes in drag speed and color according to various embodiments;
- (19) FIG. 12 is a flowchart illustrating an example operation of adaptively correcting latency in an electronic device according to various embodiments;
- (20) FIG. 13A is a diagram illustrating a relationship between a position of a second input and latency according to various embodiments; and
- (21) FIG. 13B is a diagram illustrating an example user interface which changes depending on a second input and latency according to various embodiments.
- (22) With regard to description of drawings, the same or similar reference numbers may be used for the same or similar components.

DETAILED DESCRIPTION

- (23) FIG. 1 is a block diagram illustrating an example electronic device **101** in a network environment **100** according to various embodiments. Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In various embodiments, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In various embodiments, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**).
- (24) The processor **120** may include various processing circuitry and/or multiple processors. For example, as used herein, including the claims, the term “processor” may include various processing circuitry, including at least one processor, wherein one or more of at least one processor,

individually and/or collectively in a distributed manner, may be configured to perform various functions described herein. As used herein, when “a processor”, “at least one processor”, and “one or more processors” are described as being configured to perform numerous functions, these terms cover situations, for example and without limitation, in which one processor performs some of recited functions and another processor(s) performs other of recited functions, and also situations in which a single processor may perform all recited functions. Additionally, the at least one processor may include a combination of processors performing various of the recited/disclosed functions, e.g., in a distributed manner. At least one processor may execute program instructions to achieve or perform various functions. The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation. According to an embodiment, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(25) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(26) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(27) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

- (28) The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).
- (29) The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.
- (30) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.
- (31) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.
- (32) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.
- (33) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.
- (34) A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).
- (35) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.
- (36) The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.
- (37) The power management module **188** may manage power supplied to the electronic device **101**. According to an embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).
- (38) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.
- (39) The communication module **190** may support establishing a direct (e.g., wired)

communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

(40) The wireless communication module **192** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(41) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element including a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(42) According to various embodiments, the antenna module **197** may form a mmWave antenna

module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(43) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(44) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In an embodiment, the external electronic device **104** may include an internet-of-things (IOT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(45) FIG. 2A includes perspective views illustrating an example electronic device **101** according to various embodiments.

(46) Referring to FIG. 2A, the electronic device **101** may be a slidable-type electronic device. In an embodiment, the electronic device **101** may be a slidable-type electronic device, two surfaces of which are able to be extended and/or collapsed. In an embodiment, the two surfaces which are able to extended and/or collapsed may be surfaces facing opposite directions. For example, the two surfaces which are able to extended and/or collapsed may be a left side surface **20B** and a right side surface **20C**, when looking at a display **260** of the electronic device **101** from a front surface **20A**. For another example, the two surfaces which are able to extended and/or collapsed may be a flat surface and a bottom surface of the electronic device **101**, when looking at the display **260** of the electronic device **101** from the front surface **20A**.

(47) In an embodiment, the electronic device **101** may include a first housing **210**, a second housing **220**, a third housing **230**, and a display **260** (e.g., a display module **160** of FIG. 1).

(48) In an embodiment, the second housing **220** may be coupled to the first housing **210** such that a part of the second housing **220** is able to move to the outside of the first housing **210**. For example, the second housing **220** may be coupled to the first housing **210** to be movable in a first direction **1**. The first direction **1** may be a direction the left side surface **20B** of the electronic device **101**, in which the second housing **220** is formed, faces. In an embodiment, the second housing **220** may

move in the first direction **1** or a direction opposite to the first direction **1**.

(49) In an embodiment, the third housing **230** may be coupled to the first housing **210** such that a part of the third housing **230** is able to move to the outside of the first housing **210**. For example, the third housing **230** may be coupled to the first housing **210** to be movable in a second direction **2**. The second direction **2** may be a direction the right side surface **20C** of the electronic device **101**, in which the third housing **230** is formed, faces. In an embodiment, the third housing **230** may move in the second direction **2** or a direction opposite to the second direction **2**.

(50) In an embodiment, the electronic device **101** may include a collapsed state **281**, an expanded state **282**, and at least one intermediate state between the collapsed state **281** and the expanded state **282**. In an embodiment, the state (e.g., the collapsed state **281**, the expanded state **282**, and/or the intermediate state) of the electronic device **101** may be determined according to a relative position of the second housing **220** and/or the third housing **230** with respect to the first housing **210**.

(51) In an embodiment, at least a part (e.g., a second area **262** and a third area **263**) of the display **260** may be implemented as a flexible display and/or a rollable display. In an embodiment, the display **260** may include a touch panel layer.

(52) In an embodiment, the display **260** may include a first area **261**, the second area **262**, and the third area **263**. In an embodiment, the first area **261** of display **260** may be located between the second area **262** and the third area **263**. In an embodiment, the second area **262** of the display **260** may extend from the first area **261**. In an embodiment, the third area **263** of the display **260** may extend from the first area **261**.

(53) In an embodiment, as the second housing **220** moves in the first direction **1**, the second area **262** of the display **260** may be expanded. In an embodiment, as the second housing **220** moves in the direction opposite to the first direction **1**, the second area **262** of the display **260** may be collapsed.

(54) In an embodiment, as the third housing **230** moves in the second direction **2**, the third area **263** of the display **260** may be expanded. In an embodiment, as the third housing **230** moves in the direction opposite to the second direction **2**, the third area **263** of the display **260** may be collapsed.

(55) In an embodiment, when a specified signal is generated, the electronic device **101** may switch the state (e.g., the collapsed state **281**, the expanded state **282**, and/or the intermediate state) of the electronic device **101**. In an embodiment, the electronic device **101** may switch the state of the electronic device **101** by controlling a driving device (e.g., a motor) connected with the display **260** and/or the housing (e.g., at least one of the first housing **210**, the second housing **220**, or the third housing **230**).

(56) In an embodiment, the specified signal may be generated by means of an input module (e.g., a first input module **150** of FIG. **1** (e.g., a button, a wheel, a dial, a toggle, or a digital pen (e.g., a stylus pen))). For example, the specified signal may be generated by means of a hardware button or a software button provided on a screen.

(57) In an embodiment, the specified signal may be a touch, a drag, or a gesture input, which is input through the display **260**.

(58) FIG. **2B** includes perspective views illustrating an example electronic device **101** according to various embodiments. Compared to the electronic device **101** of FIG. **2A**, the electronic device **101** of FIG. **2B** may be a slidable-type electronic device, one surface of which is able to extended and/or collapsed. For example, the one surface which is able to extended and/or collapsed may be a left side surface **20B**, when looking at a display **260** of the electronic device **101** from a front surface **20A**. For another example, the one surface which is able to extended and/or collapsed may be a right side surface, a flat surface, and a bottom surface of the electronic device **101**, when looking at the display **260** of the electronic device **101** from the front surface **20A**.

(59) In an embodiment, the electronic device **101** may include a collapsed state **283**, an expanded state **284**, and at least one intermediate state between the collapsed state **283** and the expanded state

284. In an embodiment, the state (e.g., the collapsed state **283**, the expanded state **284**, and/or the intermediate state) of the electronic device **101** may be determined according to a relative position of the second housing **220** with respect to the first housing **210**.

(60) In an embodiment, when a specified signal is generated, the electronic device **101** may switch the state (e.g., the collapsed state **283**, the expanded state **284**, and/or the intermediate state) of the electronic device **101**. In an embodiment, the electronic device **101** may switch the state of the electronic device **101** by controlling a driving device (e.g., a motor) connected with the display **260** and/or the housing (e.g., at least one of the first housing **210** or the second housing **220**).

(61) FIG. 2C includes perspective views illustrating an example electronic device **101** according to various embodiments. The electronic device **101** of FIG. 2C may be a slidable-type electronic device, one surface of which is able to extended and/or collapsed, which is different from one surface capable of being extended and/or collapsed in the electronic device **101** of FIG. 2B. For example, the one surface which is able to extended and/or collapsed may be a right side surface **20C**, when looking at a display **260** of the electronic device **101** from a front surface **20A**. For another example, the one surface which is able to extended and/or collapsed may be a left side surface, a flat surface, and a bottom surface of the electronic device **101**, when looking at the display **260** of the electronic device **101** from the front surface **20A**.

(62) In an embodiment, the electronic device **101** may include a collapsed state **285**, an expanded state **286**, and at least one intermediate state between the collapsed state **285** and the expanded state **286**. In an embodiment, the state (e.g., the collapsed state **285**, the expanded state **286**, and/or the intermediate state) of the electronic device **101** may be determined according to a relative position of a third housing **230** with respect to the first housing **210**.

(63) In an embodiment, when a specified signal is generated, the electronic device **101** may switch the state (e.g., the collapsed state **285**, the expanded state **286**, and/or the intermediate state) of the electronic device **101**. In an embodiment, the electronic device **101** may switch the state of the electronic device **101** by controlling a driving device (e.g., a motor) connected with the display **260** and/or the housing (e.g., at least one of the first housing **210** or the third housing **230**).

(64) FIG. 2D is a diagram illustrating an example electronic device **101** according to various embodiments. Compared to the electronic device **101** of FIG. 2A, the electronic device **101** of FIG. 2D may be a slidable-type electronic device, one surface of which is able to extended and/or collapsed. For example, the one surface which is able to extended and/or collapsed may be a flat surface **20D**, when looking at a display **260** of the electronic device **101** from a front surface **20A**. For another example, the one surface which is able to extended and/or collapsed may be a left side surface, a right side surface, and a bottom surface of the electronic device **101**, when looking at the display **260** of the electronic device **101** from the front surface **20A**.

(65) In an embodiment, the electronic device **101** may include a collapsed state **287**, an expanded state **288**, and at least one intermediate state between the collapsed state **287** and the expanded state **288**. In an embodiment, the state (e.g., the collapsed state **287**, the expanded state **288**, and/or the intermediate state) of the electronic device **101** may be determined according to a relative position of the fourth housing **240** with respect to the first housing **210**.

(66) In an embodiment, when a specified signal is generated, the electronic device **101** may switch the state (e.g., the collapsed state **287**, the expanded state **288**, and/or the intermediate state) of the electronic device **101**. In an embodiment, the electronic device **101** may switch the state of the electronic device **101** by controlling a driving device (e.g., a motor) connected with the display **260** and/or the housing (e.g., at least one of the first housing **210** or the fourth housing **240**).

(67) FIG. 2E is a diagram illustrating an example electronic device **101** according to various embodiments.

(68) Compared to the electronic device **101** of FIG. 2A, the electronic device **101** of FIG. 2E may be a rollable-type electronic device.

(69) Referring to FIG. 2E, the electronic device **101** may include a housing **210**, a display **260**, a

holder **250**, and a second housing **270**.

(70) In an embodiment, as at least a part of the display **260** moves to the outside or inside of the housing **210** by manipulation of a user or a mechanical operation (e.g., driving of a motor), a visible area of the display **260**, which is visible to the outside of the housing **210**, may be expanded or collapsed in the electronic device **101**. For example, the display **260** may be configured to be fitted into the housing **210** while winding on a roller (not shown) disposed in the housing **210** and be drawn to the outside of the housing **210** while unwinding from the roller.

(71) In an embodiment, the electronic device **101** may include a rolled state **289**, an unrolled state **290**, and an intermediate state between the rolled state **289** and the unrolled state **290**.

(72) In an embodiment, the rolled state **289** may be defined as a state in which the visible area of the display **260**, which is visible to the outside of the electronic device **101**, has a minimum size. For example, the rolled state **289** may be a state in which the display **260** is wound as much as possible around a rotary axis R. For another example, the rolled state **298** may be a state in which the display **260** is able to no longer move towards the inside of the housing **210**.

(73) In an embodiment, at least a part of the display **260** may be visible to the outside of the housing **210** in the rolled state **289**. In an embodiment, in the rolled state **289**, the display **260** may be completely received in the housing **210** not to be visible to the outside of the housing **210**.

(74) In an embodiment, the unrolled state **290** may be defined as a state in which the visible area of the display **260**, which is visible to the outside of the housing **210**, has a maximum size. For example, the unrolled state **290** may be a state in which the display **260** is unwound as much as possible around the rotary axis R. For another example, the unrolled state **290** may be a state in which the display **260** is able to no longer move towards the outside of the housing **210**. The electronic device **101** may be configured to provide a relatively expanded display area as deformed from the rolled state **289** to the unrolled state **290**.

(75) In an embodiment, the electronic device **101** may further include any intermediate state (e.g., a free stop state) defined between the rolled state **289** and the unrolled state **290**. In the intermediate state, the display **260** visible to the outside of the housing **210** may be larger in size than the rolled state **289** and may be smaller in size than the unrolled state **290**. For example, the electronic device **101** may be deformed from the rolled state **289** to the unrolled state **290** through the intermediate state or may be deformed from the unrolled state **290** to the rolled state **289** through the intermediate state.

(76) In an embodiment, when a specified signal is generated, the electronic device **101** may switch the state (e.g., the rolled state **289**, the unrolled state **290**, and/or the intermediate state) of the electronic device **101**. In an embodiment, the electronic device **101** may switch the state of the electronic device **101** by controlling a driving device (e.g., a motor) connected with the display **260** and/or the housing (e.g., at least one of the first housing **210** or the second housing **270**).

(77) FIG. 3 is a block diagram illustrating an example configuration of an electronic device **301** according to various embodiments. The electronic device **301** of FIG. 3 may correspond, for example, and without limitation, to an electronic device **101** of FIGS. 1, 2A, 2B, 2C, 2D, and/or 2E.

(78) Referring to FIG. 3, the electronic device **301** may include a processor (e.g., including processing circuitry) **320**, a memory **330**, a driving unit (e.g., including a motor) **340**, an input module (e.g., including input circuitry) **350**, a display **360**, a sensor **376**, or any combination thereof. In an embodiment, the processor **320**, the memory **330**, the input module **350**, the display **360**, or the sensor **376** of FIG. 3 may correspond to a processor **120**, a memory **130**, an input module **150**, a display **160**, or a sensor **176** of FIG. 1, respectively.

(79) In an embodiment, the display **360** may be a flexible display (e.g., a slidable display or a scrollable display), a visible area of which changes in size. In an embodiment, the visible area may be an area of the display **360**, which is visible to a user according to a state (e.g., a collapsed state (e.g., a collapsed state **281**, **283**, **285**, or **287**), an expanded state (e.g., an expanded state **282**, **284**,

286, or 288), and/or an intermediate state thereof) of the electronic device 301.

(80) In an embodiment, the driving unit **340** may provide a physical force for supporting movement of a housing (not shown) of the electronic device **301**. For example, the driving unit **340** may provide a physical force for allowing a first portion and a second portion of the housing (not shown) of the electronic device **301** to be away from each other or close to each other.

(81) In an embodiment, the driving unit **340** may provide a physical force capable of expanding and/or collapsing the display **360** of the electronic device **301**. For example, the driving unit **340** may provide a physical force for a state change between the collapsed state (e.g., the collapsed state **281, 283, 285, or 287**), the intermediate state, or the expanded state (e.g., the expanded state **282, 284, 286, or 288**) of the display **360**. For another example, the driving unit **340** may provide a physical force for a state change between a rolled state (e.g., a rolled state **289**), an intermediate state, or an unrolled state (e.g., an unrolled state **290**) of the display **360**.

(82) In an embodiment, the driving unit **340** may be implemented as a physical device (e.g., a motor or an actuator) capable of providing a physical force.

(83) In an embodiment, the processor **320** may include various processing circuitry and/or multiple processors. For example, as used herein, including the claims, the term “processor” may include various processing circuitry, including at least one processor, wherein one or more of at least one processor, individually and/or collectively in a distributed manner, may be configured to perform various functions described herein. As used herein, when “a processor”, “at least one processor”, and “one or more processors” are described as being configured to perform numerous functions, these terms cover situations, for example and without limitation, in which one processor performs some of recited functions and another processor(s) performs other of recited functions, and also situations in which a single processor may perform all recited functions. Additionally, the at least one processor may include a combination of processors performing various of the recited/disclosed functions, e.g., in a distributed manner. At least one processor may execute program instructions to achieve or perform various functions, and may identify a first input. In an embodiment, the first input may be an input identified by means of the display **360**. In an embodiment, the first input may be a touch input, a pressure input, or a gesture input. In an embodiment, the gesture input may include drag, pan, swipe, scroll, or a combination thereof. In an embodiment, the first input may be an input identified by means of the input module **350**. In an embodiment, the input module **350** may include a physical button, a wheel, a dial, a digital pen (e.g., a stylus pen), and/or a toggle.

(84) In an embodiment, the processor **320** may discriminate whether the first input is a specified input. In an embodiment, the specified input may be a portion of an input for triggering a state change of the electronic device **301**. In an embodiment, the input for triggering the state change may be an input for expanding or collapsing a visible area of the display **360**. In an embodiment, the input for triggering the state change may be referred to as a trigger input.

(85) In an embodiment, the processor **320** may identify a temperature. In an embodiment, the processor **320** may identify a temperature of the electronic device **301** by means of the sensor **376**. In an embodiment, the processor **320** may identify temperatures of components (e.g., the display **360** and the driving unit **340**) of the electronic device **301** by means of the sensor **376**.

(86) In an embodiment, the processor **320** may apply the temperatures of the components of the electronic device **301** and weights for them to identify the temperature of the electronic device **301**. In an embodiment, the processor **320** may identify the temperature of the electronic device **301** with reference to Equation 1 below.

(87) [Equation1] Temperature = $\sum_{i=1}^N \alpha_i \times T_i$

(88) In Equation 1, N may be the number of components of the electronic device **301**, the temperature of which is measured. In Equation 1, i may be an integer which is greater than or equal to 1 and is less than or equal to N. α_i may be the weight applied to an ith configuration. The sum of weights may be 1. T_i may be the temperature of the ith configuration.

(89) In an embodiment, the processor **320** may identify the temperature of the electronic device **301** with reference to Equation 2 below.

(90) [Equation2] Temperature = $\alpha_l \times T_l + \sum_{i=1}^N \alpha_i \times T_i$

(91) In Equation 2, $T_{sub.i}$ may be the temperature of the area where the electronic device **301** is located. $\alpha_{sub.i}$ may be the weight applied to the temperature of the area. The sum of weights may be 1.

(92) In an embodiment, when it is discriminated that the first input is the specified input, the processor **320** may identify a temperature. In an embodiment, the processor **320** may continue identifying a temperature, regardless of the first input.

(93) According an embodiment, the processor **320** may identify a state change condition of the display **360**. In an embodiment, the state change condition may be a condition for triggering a state change of the display **360**. In an embodiment, the state change condition may include a length of the trigger input, an input time of the trigger input, a gesture type of the trigger input, or a combination thereof. For example, when the trigger input is a drag input, the state change condition may be that the trigger input is dragged by a specified length. In an embodiment, the state change condition may be referred to as a size change condition of the display **360**.

(94) In an embodiment, the processor **320** may identify a state change condition based on the temperature. For example, the more the temperature increases, the more the length of the trigger input may increase. For another example, the more the temperature increases, the more the input time of the trigger input may increase. For another example, as the temperature increases, the gesture of the trigger input may change to a gesture which requests more operations.

(95) In an embodiment, the processor **320** may identify latency based on the temperature and may identify a state change condition based on the latency. In an embodiment, the latency may be a time set to prevent/inhibit the electronic device **301** from changing a state at a relatively high temperature. In an embodiment, the latency may be a time required between the start of the trigger input and the end of the trigger input. In an embodiment, the more the temperature increases, the longer the latency may be. The latency will be described in greater detail below with reference to FIGS. 5, 6, and 7.

(96) In an embodiment, the processor **320** may output a user interface (UI) guiding a state change condition. In an embodiment, the processor **320** may output a user interface guiding a condition for triggering a state change. In an embodiment, the user interface may include a graphic UI (GUI), an auditory UI (AUI), a tangible UI (TUI), or a combination thereof.

(97) In an embodiment, the processor **320** may change a shape of the user interface. In an embodiment, the processor **320** may adjust the shape of the user interface, depending on the state change condition. In an embodiment, the processor **320** may adjust the shape of the user interface, depending on the temperature.

(98) In an embodiment, as the temperature increases, the processor **320** may change a color of the graphic user interface output on the display **360**. For example, the more the temperature increases, the higher the saturation of the user interface may be. For another example, the more the temperature increases, the lower the brightness of the user interface may be.

(99) In an embodiment, as the latency increases, the processor **320** may change a color of the graphic user interface output on the display **360**. For example, the more the latency increases, the higher the saturation of the user interface may be. For another example, the more the latency increases, the lower the brightness of the user interface may be.

(100) In an embodiment, as the temperature increases, the processor **320** may change intensity, a frequency, and/or a sound source of the auditory user interface output through a sound output module (e.g., a sound output module **155** of FIG. 1).

(101) In an embodiment, as the latency increases, the processor **320** may change intensity, a frequency, and/or a sound source of the auditory user interface output through the sound output

module (e.g., the sound output module **155** of FIG. **1**).

(102) In an embodiment, as the temperature increases, the processor **320** may change an amplitude and/or a frequency of the tangible user interface output through a haptic module (e.g., a haptic module **179** of FIG. **1**).

(103) In an embodiment, as the latency increases, the processor **320** may change an amplitude and/or a frequency of the tangible user interface output through the haptic module (e.g., the haptic module **179** of FIG. **1**).

(104) In an embodiment, the processor **320** may identify a second input. In an embodiment, the second input may be an input subsequent to the first input. In an embodiment, the second input may be an input consecutive from the first input. In an embodiment, the second input may configure a trigger input together with the first input. For example, the second input may be a drag input extending from a position at which the first input is input.

(105) In an embodiment, the second input may be an input identified by means of the display **360**. In an embodiment, the second input may be an input identified by means of the input module **350**.

(106) In an embodiment, the processor **320** may output a user interface based on the second input. In an embodiment, the processor **320** may adjust a shape of the user interface, depending on the second input. In an embodiment, the processor **320** may output a user interface indicating a degree to which the state change condition is satisfied depending on the second input.

(107) According an embodiment, the processor **320** may identify whether the second input satisfies the state change condition. According an embodiment, the processor **320** may identify whether the first input and the second input satisfy the state change condition.

(108) For example, the processor **320** may discriminate whether the second input is input by an input length required according to the state change condition. For another example, the processor **320** may discriminate whether the second input is input by an input time required according to the state change condition.

(109) In an embodiment, the processor **320** may adjust an area of the display **360**. In an embodiment, when the state change condition is satisfied, the processor **320** may adjust the area of the display **360**. In an embodiment, when the state change condition is satisfied, the processor **320** may control the driving unit **340** to adjust the area of the display **360**. In an embodiment, when the state change condition is satisfied, the processor **320** may control the driving unit **340** to expand and/or collapse the display **360**.

(110) FIG. **4A** is a flowchart illustrating an example operation of an electronic device **301** according to various embodiments. FIG. **4B** is a diagram illustrating example user interfaces **410** and **420** of an electronic device **301** according to various embodiments.

(111) Operations of FIG. **4A** may be performed by an electronic device **301** of FIG. **3**. The operations of FIG. **4A** may be performed by an electronic device **101** of FIG. **1**, **2A**, **2B**, **2C**, **2D**, or **2E**.

(112) Referring to FIG. **4A**, in operation **401**, the electronic device **301** may identify a first input. In an embodiment, the first input may be an input identified by means of a display **360**. In an embodiment, the first input may be an input identified by means of an input module **350**.

(113) In operation **402**, the electronic device **301** may discriminate (e.g., determine) whether the first input is a specified input. In an embodiment, the specified input may be a portion of an input for triggering a state change of the electronic device **301**. In an embodiment, the input for triggering the state change may be input for expanding or collapsing a visible area of the display **360**. In an embodiment, the input for triggering the state change may be referred to as a trigger input.

(114) Referring to FIG. **4B**, while the electronic device **301** is in a collapsed state **481**, it may identify the first input. In an embodiment, the electronic device **301** may identify the first input by means of the display **360**. In an embodiment, the first input may be a portion (e.g., touch) of a drag input for triggering a state change.

(115) In an embodiment, the electronic device **301** may output a user interface **410** indicating a position of the first input.

(116) In operation **403**, the electronic device **301** may identify a temperature. In an embodiment, the electronic device **301** may identify a temperature of the electronic device **301** by means of a sensor **376**. In an embodiment, the electronic device **301** may identify temperatures of components (e.g., the display **360** and a driving unit **340**) of the electronic device **301** by means of the sensor **376**.

(117) In operation **404**, the electronic device **301** may identify a state change (e.g., variable) condition of the display **360**. In an embodiment, the electronic device **301** may identify the state change condition based on the temperature. In an embodiment, the state change condition may include a length of the trigger input, an input time of the trigger input, a gesture type of the trigger input, or a combination thereof.

(118) Referring to FIG. **4B**, the electronic device **301** may output a user interface **420** guiding the state change condition. In an embodiment, the user interface **420** may have an area **425** according to a length **421** of the trigger input required according to the state change condition. The user interface **420** is illustrated, for example, as a circle in FIG. **4B**, but this is only an example. In an embodiment, the user interface **420** may be output in various forms capable of indicating a condition for releasing the trigger input. For example, the user interface **420** may be output as an oval, a polygon, and/or a straight shape. In an embodiment, the condition for releasing the trigger input may be a position of a release point of a touch and/or a drag length, when the trigger input is drag.

(119) In operation **405**, the electronic device **301** may identify a second input. In an embodiment, the second input may be an input subsequent to the first input. In an embodiment, the second input may be an input consecutive from the first input. In an embodiment, the second input may configure a trigger input together with the first input. In an embodiment, the second input may be an input identified by means of the display **360**. In an embodiment, the second input may be an input identified by means of the input module **350**.

(120) In operation **406**, the electronic device **301** may discriminate (e.g., determine) whether the second input satisfies the state change condition. In an embodiment, the electronic device **301** may discriminate whether the first input and the second input satisfy the state change condition.

(121) In operation **407**, the electronic device **301** may adjust an area of the display **360**. In an embodiment, the electronic device **301** may control the driving unit **340** to adjust the area of the display **360**. In an embodiment, the electronic device **301** may control the driving unit **340** to expand and/or collapse the display **360**.

(122) Referring to FIG. **4B**, the electronic device **301** may change from a collapsed state **481** to an expanded state **482**. In an embodiment, the electronic device **301** may change from the collapsed state **481** to the expanded state **482**, such that a second display area **461B** is visible together with a first display area **461A** in the display **461**.

(123) It is illustrated, for example in FIG. **4B** that the electronic device **301** changes from the collapsed state **481** to the expanded state **482** based on the first input and the second input, but this is only example. In an embodiment, the electronic device **301** may change from the expanded state **482** to the collapsed state **481** based on the first input and the second input. In an embodiment, the electronic device **301** may change among the collapsed state **481**, the expanded state **482**, or an intermediate state thereof (e.g., an intermediate state of the collapsed state **481** and the expanded state **482**) based on the first input and the second input.

(124) FIG. **5** is a flowchart illustrating an example operation of outputting a user interface in an electronic device **301** according to various embodiments.

(125) Operations of FIG. **5** may be performed by an electronic device **301** of FIG. **3**. The operations of FIG. **5** may be performed by an electronic device **101** of FIG. **1**, **2A**, **2B**, **2C**, **2D**, or **2E**.

(126) In an embodiment, the operations of FIG. 5 may be performed after operation 404 of FIG. 4A. In an embodiment, the operations of FIG. 5 may be performed in parallel with operation 404 of FIG. 4A. In an embodiment, the operations of FIG. 5 may be performed in parallel with operation 405 or 406 of FIG. 4A.

(127) Referring to FIG. 5, in operation 510, the electronic device 301 may identify latency according to a temperature. In an embodiment, the latency may be a time set to prevent/inhibit the electronic device 301 from changing a state at a relatively high temperature. In an embodiment, the latency may be a time required between the start of the trigger input and the end of the trigger input.

(128) In operation 520, the electronic device 301 may output a user interface corresponding to the latency.

(129) In an embodiment, the electronic device 301 may identify a state change condition corresponding to the latency (e.g., a length of the trigger input, an input time of the trigger input, a gesture type of the trigger input, or a combination thereof). In an embodiment, the electronic device 301 may output a user interface guiding the state change condition.

(130) FIG. 6 is a graph illustrating a relationship between a temperature and latency. FIG. 6 will be described with reference to the electronic device 301 of FIG. 3.

(131) In an embodiment, the electronic device 301 may classify a temperature of the electronic device 301 as a different temperature range. In an embodiment, the different temperature range may be classified as a normal temperature range, a warning temperature range, or a dangerous temperature range.

(132) Referring to FIG. 6, the electronic device 301 may set latency corresponding to the different temperature range. In an embodiment, the latency may be set according to the normal temperature range, the warning temperature range, or the dangerous temperature range.

(133) In an embodiment, an increase in latency according to an increase in temperature may adaptively increase depending on a temperature. In an embodiment, the increase in latency according to the increase in temperature may adaptively increase depending on a temperature range. For example, an increase in latency in the warning temperature range may be greater than an increase in latency in the normal temperature range.

(134) In an embodiment, as the temperature increases, the latency may gradually increase. In an embodiment, although the temperature increases, there may be a temperature range in which latency does not increase. For example, the latency may be set to upper latency at a specified temperature or more. In an embodiment, the specific temperature may be present in at least one of the normal temperature range, the warning temperature range, or the dangerous temperature range.

(135) In an embodiment, as the temperature decreases, the latency may gradually decrease. In an embodiment, although the temperature decreases, there may be a temperature range in which latency does not decrease. For example, the latency may be set to lower latency at the specified temperature or less. In an embodiment, the specific temperature may be present in at least one of the normal temperature range, the warning temperature range, or the dangerous temperature range.

(136) In an embodiment, the electronic device 301 may output a user interface guiding a state change condition based on the latency identified according to the temperature of the electronic device 301.

(137) FIG. 7 is a diagram illustrating an example user interface output according to latency by an electronic device 301 according to various embodiments. FIG. 7 will be described with reference to the electronic device 301 of FIG. 3.

(138) Reference numeral 701 indicates an example of outputting a user interface 711 indicating a position of a user input and a user interface 721 guiding a state change condition, depending on the user input which is input when the electronic device 301 is in a normal temperature range. In an embodiment, the user interface 721 may have an area 735 according to a length 731 of a trigger input required according to the state change condition.

(139) Reference numeral **703** indicates an example of outputting a user interface **712** indicating a position of a user input and a user interface **722** guiding a state change condition, depending on the user input which is input when the electronic device **301** is in a warning temperature range. In an embodiment, the user interface **722** may have an area **736** according to a length **732** of a trigger input required according to the state change condition.

(140) Reference numeral **705** indicates an example of outputting a user interface **713** indicating a position of a user input and a user interface **723** guiding a state change condition, depending on the user input which is input when the electronic device **301** is in a dangerous temperature range. In an embodiment, the user interface **723** may have an area **737** according to a length **733** of a trigger input required according to the state change condition.

(141) Referring to reference numerals **701**, **703**, and **705**, lengths **731**, **732**, and **733** of a second input required to trigger a state change may become long as it goes from the normal temperature range to the dangerous temperature range.

(142) Referring to reference numerals **701**, **703**, and **705**, areas **735**, **736**, and **737** of circles for guiding the second input required to trigger the state change may increase as they go from the normal temperature range to the dangerous temperature range.

(143) In an embodiment, colors of the user interfaces **721**, **722**, and **723** guiding the state change condition may change as they go from the normal temperature range to the dangerous temperature range. In an embodiment, saturation of the user interfaces **721**, **722**, and **723** may increase as it goes from the normal temperature range to the dangerous temperature range. In an embodiment, brightness of the user interfaces **721**, **722**, and **723** may decrease as it goes from the normal temperature range to the dangerous temperature range.

(144) In an embodiment, colors of the user interfaces **711**, **712**, and **713** indicating positions of user inputs may change as they go from the normal temperature range to the dangerous temperature range. In an embodiment, saturation of the user interfaces **711**, **712**, and **713** may increase as it goes from the normal temperature range to the dangerous temperature range. In an embodiment, brightness of the user interfaces **711**, **712**, and **713** may decrease as it goes from the normal temperature range to the dangerous temperature range.

(145) FIG. **8** is a diagram illustrating an example user interface guiding an end point of a trigger input according to various embodiments. FIG. **8** will be described with reference to the electronic device **301** of FIG. **3**.

(146) Reference numeral **801** indicates an example of outputting a user interface **811** indicating a position of a user input and a user interface **851** guiding an end point of a trigger input, depending on the user input which is input when the electronic device **301** is in a normal temperature range. In an embodiment, the user interface **851** may be displayed spaced apart from the user interface **811** at a length **831** of a trigger input required according to a state change condition.

(147) Reference numeral **803** indicates an example of outputting a user interface **812** indicating a position of a user input and a user interface **852** guiding an end point of a trigger input, depending on the user input which is input when the electronic device **301** is in a warning temperature range. In an embodiment, the user interface **852** may be displayed spaced apart from the user interface **812** at a length **832** of the trigger input required according to the state change condition.

(148) Reference numeral **805** indicates an example of outputting a user interface **813** indicating a position of a user input and a user interface **853** guiding an end point of a trigger input, depending on the user input which is input when the electronic device **301** is in a dangerous temperature range. In an embodiment, the user interface **853** may be displayed spaced apart from the user interface **813** at a length **833** of the trigger input required according to the state change condition.

(149) FIG. **9** is a diagram illustrating an example user interface **901** indicating a degree to which a state change condition is satisfied according to various embodiments. FIG. **9** will be described with reference to the electronic device **301** of FIG. **3**.

(150) Referring to FIG. **9**, the electronic device **301** may display user interfaces **921**, **922**, **923**, **924**,

925, and **926** which are adjacent to user interfaces **911**, **912**, **913**, **914**, **915**, and **916** indicating positions of user inputs and indicate degrees to which a state change condition is satisfied.

(151) In an embodiment, when the position of the user interface **911** corresponds to a starting point of a trigger input and when the position of the user interface **916** corresponds to an end point of the trigger input, the user interfaces **921**, **922**, **923**, **924**, **925**, and **926** may increase in area (e.g., shadow area) indicating the degree to which the state change condition is satisfied as the user input goes from the starting point to the end point.

(152) It is illustrated in FIG. **9** that the positions of the user interfaces **921**, **922**, **923**, **924**, **925**, and **926** are adjacent to the user interfaces **911**, **912**, **913**, **914**, **915**, and **916**, but this is only an example. In an embodiment, the positions of the user interfaces **921**, **922**, **923**, **924**, **925**, and **926** may be located around user interfaces (e.g., user interfaces **721**, **722**, and **723**) guiding the state change condition.

(153) FIG. **10** is a diagram illustrating an example user interface **1001** indicating a degree to which a state change condition is satisfied. FIG. **10** will be described with reference to the electronic device **301** of FIG. **3**.

(154) Referring to FIG. **10**, the electronic device **301** may display user interfaces **1021**, **1022**, **1023**, **1024**, **1025**, and **1026** which are adjacent to user interfaces **1011**, **1012**, **1013**, **1014**, **1015**, and **1016** indicating positions of user inputs and indicate degrees to which a state change condition is satisfied.

(155) In an embodiment, when the position of the user interface **1011** corresponds to a starting point of a trigger input and when the position of the user interface **1016** corresponds to an end point of the trigger input, the user interfaces **1021**, **1022**, **1023**, **1024**, **1025**, and **1026** may increase in value indicating the degree to which the state change condition is satisfied as the user input goes from the starting point to the end point.

(156) It is illustrated in FIG. **10** that the positions of the user interfaces **1021**, **1022**, **1023**, **1024**, **1025**, and **1026** are adjacent to the user interfaces **1011**, **1012**, **1013**, **1014**, **1015**, and **1016**, but this is only an example. In an embodiment, the positions of the user interfaces **1021**, **1022**, **1023**, **1024**, **1025**, and **1026** may be located around user interfaces (e.g., user interfaces **721**, **722**, and **723**) guiding the state change condition.

(157) FIG. **11A** is a diagram illustrating an example user interface **1101** according to a state of a trigger input according to various embodiments. FIG. **11B** is a graph illustrating a relationship between changes in drag speed and color according to various embodiments. FIGS. **11A** and **11B** will be described with reference to the electronic device **301** of FIG. **3**.

(158) In an embodiment, the electronic device **301** may change an output of a user interface depending on a state of a trigger input to notify a user of the state of the trigger input. In an embodiment, the state of the trigger input may include a speed of the trigger input.

(159) Referring to FIG. **11A**, the electronic device **301** may display user interfaces **1111**, **1112**, **1113**, **1114**, **1115**, and **1116** according to the state of the trigger input. In an embodiment, the more the speed of the trigger input increases, the more the electronic device **301** may increase saturation of the user interfaces **1111**, **1112**, **1113**, **1114**, **1115**, and **1116**. In an embodiment, the more the speed of the trigger input increases, the more the electronic device **301** may decrease brightness of the user interfaces **1111**, **1112**, **1113**, **1114**, **1115**, and **1116**.

(160) Referring to FIG. **11B**, the more the speed of a trigger input (e.g., drag) increases, the larger the electronic device **301** may set an amount of change in color (e.g., saturation and/or brightness) to be.

(161) FIG. **12** is a flowchart illustrating an example operation of adaptively correcting latency in an electronic device **301** according to various embodiments. FIG. **13A** is a diagram illustrating a relationship between a position of a second input and latency according to various embodiments. FIG. **13B** is a diagram illustrating an example user interface which changes depending on a second input and latency according to various embodiments.

(162) Operations of FIG. 12 may be performed by the electronic device 301 of FIG. 3. The operations of FIG. 12 may be performed by electronic device 101 of FIG. 1, 2A, 2B, 2C, 2D, or 2E.

(163) In an embodiment, the operations of FIG. 12 may be performed after operation 404 of FIG. 4A. In an embodiment, the operations of FIG. 12 may be performed in parallel with operation 404 of FIG. 4A. In an embodiment, the operations of FIG. 12 may be performed in parallel with operation 405 or 406 of FIG. 4A.

(164) Referring to FIG. 4A, in operation 1210, the electronic device 301 may discriminate (e.g., determine) whether a second input reaches a specified input interval. In an embodiment, the electronic device 301 may discriminate whether the second input reaches a last position of the specified input interval. In an embodiment, the specified input interval may be an input interval subsequent to an input interval where the second is located.

(165) Referring to FIG. 13A, a starting point 1311 and an end point 1316 of a trigger input may be divided into a plurality of intervals by a plurality of midpoints 1312, 1313, 1314, and 1315. In an embodiment, the electronic device 301 may distribute latency to a plurality of intervals. In an embodiment, when the trigger input starts, target times T1, T2, T3, T4, and T5 respectively distributed to the plurality of intervals may be identical to each other. In an embodiment, the sum of the target times may correspond to latency set when the trigger input starts. For example, when the latency set when the trigger input starts is 3 seconds, the target times may be 600 milliseconds.

(166) Referring to FIG. 13B, reference numeral 1301 may indicate a user interface 1331 indicating an input position when a user initiates a trigger input and a user interface 1321 guiding a state change condition. In an embodiment, the user interface 1331 may indicate that the trigger input is located at the starting point 1311. In an embodiment, the user interface 1321 may have an area according to a length of the trigger input corresponding to the set latency.

(167) For example, when the second input is located at the starting point 1311, the electronic device 301 may discriminate whether the second input reaches a last position (e.g., the first midpoint 1312) of a first interval divided by the starting point 1311 and the first midpoint 1312. For another example, when the second input is located at the first midpoint 1312, the electronic device 301 may discriminate whether the second input reaches a last position (e.g., the second midpoint 1313) of a second interval divided by the first midpoint 1312 and the second midpoint 1313.

(168) When it is discriminated (e.g., determined) that the second input reaches the specified input interval in operation 1210, the electronic device 301 may perform operation 1220. When it is discriminated (e.g., determined) that the second input does not reach the specified input interval in operation 1210, the electronic device 301 may perform operation 1210 again.

(169) In operation 1220, the electronic device 301 may identify whether there is a need to correct the latency.

(170) In an embodiment, the electronic device 301 may identify whether there is a need to correct the latency based on a time when the second input is located at the first midpoint 1312.

(171) In an embodiment, when the time when the second input is located at the first midpoint 1312 is shorter than a target time, the electronic device 301 may identify that there is the need to correct the latency.

(172) For example, when the first target time T1 is 600 milliseconds and when the time when the second input is located at the first midpoint 1312 is 500 milliseconds, the electronic device 301 may identify that there is the need to correct the latency. For another example, when the first target time T1 is 600 milliseconds and when the time when the second input is located at the first midpoint 1312 is 700 milliseconds, the electronic device 301 may identify that there is no need to correct the latency.

(173) When it is discriminated (e.g., determined) that there is the need to correct the latency in operation 1220, the electronic device 301 may perform operation 1230. When it is discriminated (e.g., determined) that there is no need to correct the latency in operation 1220, the electronic device 301 may perform operation 1210 again.

(174) In operation **1230**, the electronic device **301** may identify a correction time.

(175) In an embodiment, the electronic device **301** may identify a difference value of a time when it reaches the specified input interval at the target time as the correction time. In an embodiment, the electronic device **301** may equally distribute the correction time to the remaining intervals, thus adjusting target times of the remaining intervals.

(176) For example, when the first target time **T1** is 600 milliseconds and when the time when the second input is located at the first midpoint **1312** is 400 milliseconds, the electronic device **301** may identify the correction time as 200 milliseconds. In this case, the electronic device **301** may increase the target times of the remaining intervals by 50 milliseconds. Thus, the target time **T2** of the second interval divided by the first midpoint **1312** and the second midpoint **1313** may increase from 600 milliseconds to 650 milliseconds. Likewise, the target time **T3** of the third interval divided by the second midpoint **1313** and the third midpoint **1314**, the target time **T4** of the fourth interval divided by the third midpoint **1314** and the fourth midpoint **1315**, and the target time **T5** of the fifth interval divided by the fourth midpoint **1315** and the end point **1316** may also increase to 650 milliseconds.

(177) In operation **1240**, the electronic device **301** may update a user interface based on the correction time.

(178) Referring to FIG. **13B**, reference numeral **1302** may indicate a user interface **1332** indicating an input position when a user allows a trigger input to reach a specified position and a user interface **1322** guiding a state change condition. In an embodiment, the user interface **1322** may have an area which is wider than the user interface **1321** as the target times of the remaining intervals increase.

(179) In an embodiment, a time spent when the user allows the trigger input to reach a next specified position is greater than the target time, the user interface guiding the state change condition may become narrow in area. Referring to FIG. **13B**, reference numeral **1303** may indicate a user interface **1333** indicating an input position when the user allows a trigger input to reach a next specified position and a user interface **1323** guiding a state change condition. In an embodiment, the user interface **1323** may have an area which is narrower than the user interface **1322** as the target times of the remaining intervals decrease.

(180) An electronic device according to an example embodiment of the disclosure may include: a sensor configured to measure a temperature of the electronic device, a flexible display, a size of a visible area of which is changeable, at least one processor, comprising processing circuitry, and a memory storing instructions. at least one processor, individually and or collectively, may be configured to: cause the electronic device to identify a first input, identify the temperature of the electronic device via the sensor based on identifying the first input, identify a size change condition of the flexible display based on the identified temperature, identify a second input, and change the size of the visible area, based on the second input satisfying the size change condition.

(181) In an example embodiment, at least one processor, individually and/or collectively, may be configured to cause the electronic device to output a user interface for indicating the size change condition.

(182) In an example embodiment, the user interface may include a graphic user interface output on the flexible display.

(183) In an example embodiment, the graphic user interface may be configured to change in color and/or size based on the identified temperature.

(184) In an example embodiment, the graphic user interface may change in color and/or size based on a movement speed of the second input.

(185) In an example embodiment, the first input and the second input may include inputs applied to the flexible display.

(186) In an example embodiment, the second input may include a drag input extending from a position at which the first input is input, a size change condition may include the second input

being dragged by a specified length, wherein the specified length may vary based on the identified temperature.

(187) In an example embodiment, the electronic device may further include a speaker (e.g., a sound output module **155** of FIG. **1**). The user interface may include an auditory user interface configured to be output through the speaker.

(188) In an example embodiment, an input module comprising input circuitry may be included. The At least one processor, individually and/or collectively, may be configured to cause the electronic device to identify the first input and the second input via the input module. The input module may include at least one of a physical button, a dial, a toggle, a digital pen (e.g., a stylus pen), and/or a wheel.

(189) In an example embodiment, a haptic module (e.g., a haptic module **179** of FIG. **1**) including haptic circuitry may be included. The user interface may be a tangible user interface output through the haptic module.

(190) A method of operating an electronic device according to an example embodiment of the disclosure may include: identifying a first input, identifying a temperature of the electronic device using a sensor of the electronic device based on identifying the first input, identifying a size change condition of a flexible display of the electronic device based on the identified temperature, identifying a second input, and changing a size of a visible area of the flexible display, based on that the second input satisfying the size change condition.

(191) The method of the electronic device according to an example embodiment of the disclosure may further include outputting a user interface indicating the size change condition.

(192) In an example embodiment, the user interface may include a graphic user interface output on the flexible display.

(193) In an example embodiment, the graphic user interface may change in color and/or size depending on the identified temperature.

(194) In an based embodiment, the graphic user interface may change in color and/or size based on a movement speed of the second input.

(195) In an example embodiment, the first input and the second input may include inputs applied to the flexible display.

(196) In an example embodiment, the second input may include a drag input extending from a position at which the first input is input, the size change condition may include the second input being dragged by a specified length, wherein the specified length may vary with the identified temperature.

(197) In an example embodiment, a speaker (e.g., a sound output module **155** of FIG. **1**) may be included. The user interface may include an auditory user interface output through the speaker.

(198) In an example embodiment, it may be configured to identify the first input and the second input using an input module of the electronic device. The input module may include at least one of a physical button, a dial, or a wheel.

(199) In an example embodiment, the user interface may include a tangible user interface output through a haptic module (e.g., a haptic module **179** of FIG. **1**) of the electronic device.

(200) The electronic device according to various embodiments may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, a home appliance, or the like. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(201) It should be appreciated that various embodiments of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun

corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(202) As used in connection with various embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, or any combination thereof, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(203) Various embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., internal memory **136** or external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the “non-transitory” storage medium is a tangible device, and may not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(204) According to an embodiment, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(205) According to various embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to various embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations

may be executed in a different order or omitted, or one or more other operations may be added. (206) While the disclosure has been illustrated and described with reference to various example embodiments, it will be understood that the various example embodiments are intended to be illustrative, not limiting. It will be further understood by those skilled in the art that various changes in form and detail may be made without departing from the true spirit and full scope of the disclosure, including the appended claims and their equivalents. It will also be understood that any of the embodiment(s) described herein may be used in conjunction with any other embodiment(s) described herein.

Claims

1. An electronic device, comprising: a sensor configured to measure a temperature of the electronic device; a flexible display, a size of visible area of which is changeable; memory storing executable instructions; and at least one processor, comprising processing circuitry, configured to access the memory and execute the instructions, wherein at least one processor, individually and/or collectively, is configured to: identify an input for changing a size of the visible area of the flexible display; identify a temperature of the electronic device using the sensor based on identifying the input; based on the identified temperature being included in a first temperature range, change the size of the visible area of the flexible display according to a first specified condition; and based on the identified temperature being included in a second temperature range different from the first temperature range, change the size of the visible area of the flexible display according to a second specified condition, wherein the first specified condition includes a first delay time and the second specified condition includes a second delay time.
2. The electronic device of claim 1, wherein the second delay time is longer than the first delay time.
3. The electronic device of claim 1, wherein at least one processor, individually and/or collectively, is configured to: output a user interface indicating the first specified condition or the second specified condition.
4. The electronic device of claim 3, wherein the user interface includes a graphic user interface output on the flexible display, and wherein the graphic user interface is configured to change color and/or size based on the identified temperature.
5. The electronic device of claim 3, further comprising: a speaker, wherein the user interface includes an auditory user interface configured to be output through the speaker.
6. The electronic device of claim 3, further comprising: a haptic module comprising haptic circuitry, wherein the user interface includes a haptic user interface configured to be output through the haptic module.
7. The electronic device of claim 1, wherein the input for changing the size of the visible area of the flexible display includes a first input and a second input subsequent to the first input, wherein at least one processor, individually and/or collectively, is configured to: identify the temperature of the electronic device using the sensor based on identifying the first input; and change the size of the visible area of the flexible display based on the second input.
8. The electronic device of claim 7, wherein flexible display is configured to receive the first input and the second input.
9. The electronic device of claim 8, wherein the second input includes a drag input extending from a position at which the first input is input, wherein drag input is identified as an input for changing the size of the visible area of the flexible display based on the drag input being a specified length, and wherein the specified length corresponds to the identified temperature.
10. The electronic device of claim 7, wherein at least one processor, individually and/or collectively, is configured to output a graphic user interface indicating the first specified condition and the second specified condition, wherein the graphic user interface is configured to change color

and/or size based on a movement speed of the second input.

11. The electronic device of claim 1, further comprising: an input module comprising input circuitry, wherein at least one processor, individually and/or collectively, is configured to: identify the input via the input module, and wherein the input module includes at least one of a physical button, a dial, a toggle, a stylus pen, or a wheel.

12. The electronic device of claim 1, wherein the size of the visible area of the flexible display is changed after the first delay time or the second delay time.

13. A method of operating an electronic device, comprising: identifying an input for changing a size of a visible area of a flexible display of the electronic device; identifying a temperature of the electronic device using a sensor of the electronic device based on identifying first input; based on the identified temperature being included in a first temperature range, changing the size of the visible area of the flexible display according to a first specified condition; and based on the identified temperature being included in a second temperature range different from the first temperature range, changing the size of the visible area of the flexible display according to a second specified condition, wherein the first specified condition includes a first delay time and the second specified condition includes a second delay time.

14. The method of claim 13, wherein the second delay time is longer than the first delay time.

15. The method of claim 13, further comprising: outputting a user interface indicating the first specified condition or the second specified condition, wherein the user interface includes a graphic user interface output on the flexible display.

16. The method of claim 15, wherein the graphic user interface is configured to change in color and/or size based on the identified temperature.

17. The method of claim 13, wherein the input for changing the size of the visible area of the flexible display includes a first input and a second input subsequent to the first input, wherein the temperature is identified based on identifying the first input, and wherein the size of the visible area of the flexible display is changed based on the second input.

18. The method of claim 13, wherein the size of the visible area of the flexible display is changed after the first delay time or the second delay time.

19. A computer program product stored on a non-transitory machine-readable storage medium comprising instructions which, when executed by an electronic device, cause the electronic device to perform operations comprising: identifying an input for changing a size of a visible area of a flexible display of the electronic device; identifying a temperature of the electronic device using a sensor of the electronic device based on identifying first input; based on the identified temperature being included in a first temperature range, changing the size of the visible area of the flexible display according to a first specified condition; and based on the identified temperature being included in a second temperature range different from the first temperature range, changing the size of the visible area of the flexible display according to a second specified condition, wherein the first specified condition includes a first delay time and the second specified condition includes a second delay time.
