

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413107
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Chen; Feng-Tien

Magnetic power electricity generating system

Abstract

A magnetic power electricity generating system comprises an electrical machine unit and a control unit. The electrical machine unit comprises a first electrical machine with a first operating mode and a second operating mode. The first operating mode is that the first electrical machine is operated in a motor operating mode and the second operating mode is that the first electrical machine is operated in a motor operating mode and a generator operating mode simultaneously. The control unit is electrically connected respectively to the electrical machine unit and an external power supply for controlling the first electrical machine to be operated in the first operation mode or in the second operation mode. The magnetic power electricity generating system may further comprise a first flywheel coupled with the first electrical machine to enable the first electrical machine to supply electrical energy to external loadings.

Inventors:	Chen; Feng-Tien (Taichung, TW)
Applicant:	Chen; Feng-Tien (Taichung, TW)
Family ID:	85328507
Appl. No.:	18/097733
Filed:	January 17, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230268784 A1	Aug. 24, 2023

Foreign Application Priority Data

TW	111106757	Feb. 24, 2022
TW	111150902	Dec. 30, 2022

Publication Classification

Int. Cl.: H02K1/16 (20060101); H02K3/12 (20060101); H02K5/04 (20060101); H02K7/02 (20060101); H02K9/19 (20060101)

U.S. Cl.:

CPC H02K1/16 (20130101); H02K3/12 (20130101); H02K5/04 (20130101); H02K7/02 (20130101); H02K9/19 (20130101);

Field of Classification Search

CPC: H02K (1/16); H02K (3/12); H02K (5/04); H02K (7/02); H02K (9/19)

USPC: 310/216.001

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4417192	12/1982	Ghosh	N/A	N/A
10122240	12/2017	Tsai	N/A	N/A
11065979	12/2020	Demont et al.	N/A	N/A
11626779	12/2022	Shaw	310/68R	H02K 7/14
11757316	12/2022	Michaelides	310/156.01	H02K 21/16
2011/0089775	12/2010	Flynn	310/46	H02K 1/17
2012/0091836	12/2011	Hayashi	165/185	F16H 57/0412
2013/0241366	12/2012	Kim	310/67R	B60K 7/0007
2013/0257201	12/2012	Lemke	310/71	H02K 5/225
2015/0048713	12/2014	Caamano	310/216.106	H02K 1/148
2015/0295455	12/2014	Nemoto	310/216.094	H02K 21/14
2016/0056684	12/2015	Nemoto	310/51	H02K 21/14
2019/0379312	12/2018	Sakai	N/A	H02K 21/14
2020/0313518	12/2019	Rashkin et al.	N/A	N/A
2023/0268784	12/2022	Chen	310/216.001	H02K 1/16

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3 644 492	12/2019	EP	N/A

Primary Examiner: Johnson; Rashad H

Attorney, Agent or Firm: Birch, Stewart, Kolasch & Birch, LLP

Background/Summary

FIELD

(1) The disclosure relates to electrical equipment, and particularly to a magnetic power electricity generating system.

BACKGROUND

(2) As known in the prior art, either the motor or the generator can only operate in a single mode. In

other words, the motor can only be used as a power source, and the generator can only be used to supply electrical energy.

(3) In U.S. Pat. No. 4,417,192, a sectional winding for a three phase motor is provided. The sectional winding is divided into two winding sections for each phase, one of which is first connected to the power supply for starting the motor, and when the motor is started, another winding is then connected to the power supply. The object of this invention is to reduce the starting current to prevent thermal overloading. Although the invention discloses an aspect of dividing the winding of the motor into two sections, each winding section is only used to operate in the motor mode. Moreover, such a design has no energy saving effect.

(4) In U.S. Pat. No. 10,122,240, an electricity generation device with low power consumption is disclosed. The device has an operating module, a first motor, and a second motor. In operation, the electricity is inputted to the first motor to actuate the first motor in a short time, the first motor drives a transmission assembly of the operating module to rotate, and the transmission assembly drives a flywheel of the operating module to rotate. A generator rotor is mounted around the flywheel, and a generator stator is mounted around an inner peripheral surface of the body. The second motor is driven by the transmission assembly. When the flywheel reaches a certain rotational speed, the second motor only needs a low current input to keep operating. That is, the second motor can be continuously operated, and the flywheel generates rotor power, thereby achieving power generation at low energy consumption. Such a device has following disadvantages: 1. it must have two motors; 2. It must cooperate with a complex transmission assembly to operate; 3. its generator rotor is mounted in the flywheel, which will increase the electric energy consumed by the second motor; and 4. its generator rotors needs to use permanent magnets, whose magnetic force will decrease with time.

SUMMARY

(5) Therefore, one of the objectives of the disclosure is to provide a magnetic power electricity generating system with both motor and generator operating modes, when more power is required, it is only operated in the motor operating mode, and when being operated simultaneously in motor and generator operating modes, it can be in an energy-efficient manner to supply electrical energy to external loadings.

(6) Another objective of the disclosure is to provide a magnetic power electricity generating system which can apply the output power of flywheels to provide electric energy to external loadings.

(7) Accordingly, according to the disclosure, a magnetic power electricity generating system comprises an electrical machine unit and a control unit. The electrical machine unit comprises a first electrical machine with a first and second operating modes, wherein the first operating mode is that the first electrical machine is operated in a motor operating mode and the second operating mode is that the first electrical machine is operated in a motor operating mode and a generator operating mode simultaneously. The control unit is electrically connected respectively to the electrical machine unit and an external power supply for controlling the first electrical machine to be operated in the first operation mode or in the second operation mode.

(8) The magnetic power electricity generating system disclosed herein may have an aspect that the first electrical machine comprises a stator and a rotor. The stator comprises a stator body and a three-phase stator winding disposed in the stator body. Each phase stator winding of the three-phase stator winding comprises a first coil having a first number of magnetic poles and a first rated output power, and a second coil having a second number of magnetic poles and a second rated output power wherein the first number of magnetic poles is equal to the second number of magnetic poles, the first rated output power is greater than or equal to the second rated output power. The rotor comprises a rotor body with a third number of magnetic poles and a shaft extending along the axis of the rotor body. The rotor body is rotatably disposed in the stator body. The third number of magnetic poles is the same as the first number of magnetic poles and the second number of magnetic poles. Whereby, when the first coil and the second coil are simultaneously electrically

connected to an external power supply, the first electrical machine is operated in the first operating mode and when only the second coil electrically connected to the external power supply, the first electrical machine is operated in the second operating mode.

(9) The magnetic power electricity generating system disclosed herein may have a feature that the stator body includes an outer peripheral surface, a through hole, an inner peripheral surface defined by the through hole, and a plurality of first slots spaced apart from each other and extending from the inner peripheral surface to the outer peripheral surface. The first coil and the second coil are respectively installed in the first slots. And the rotor body is rotatably received in the through hole.

(10) The magnetic power electricity generating system disclosed herein may have another feature that the stator body includes an outer peripheral surface, a through hole, an inner peripheral surface defined by the through hole, and a plurality of first slots with a first depth and second slots with a second depth spaced apart from each other and extending from the inner peripheral surface to the outer peripheral surface wherein the first depth is greater than the second depth, the first coil is installed in the first slots, the second coil is installed in the second slots. And the rotor body is rotatably received in the through hole.

(11) The magnetic power electricity generating system disclosed herein may have another aspect that it further comprises a flywheel unit comprising a first flywheel coupled with the first electrical machine such that when the first flywheel is driven by the first operating mode, it will rotate to a predetermined speed to deliver energy to outside, and when the first flywheel is driven to the predetermined speed, the first electrical machine will be in the second operating mode to keep the flywheel driven in the predetermined speed and to supply electric energy to external loadings.

(12) The magnetic power electricity generating system disclosed herein may have another aspect that the electrical machine unit further comprises a second electrical machine having the first and second operating modes and coupled with the first flywheel.

(13) The magnetic power electricity generating system disclosed herein may have another aspect that the flywheel unit further comprises a second flywheel coupled with the first electrical machine.

(14) According to the disclosure, a magnetic power generation system assembly is also disclosed which comprises a plurality of the magnetic power generation systems. Each magnetic energy generating system is connected in a way that the power input of the latter magnetic power generation system is connected to the power output of the previous magnetic power generation system, the power input of the most front magnetic power generation system is connected with an external power supply, and the power output of the last magnetic power generation system is connected with an external loading. Thereby, the electrical energy output of the assembly has a multiplied effect.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Other features and advantages of the disclosure will become readily apparent to those skilled in the art from the following detailed description of the embodiments in the light of the accompanying drawings, in which:
- (2) FIG. 1 is an exploded perspective view of a first electrical machine of a first embodiment of the magnetic power electricity generating system according to the disclosure;
- (3) FIG. 2 is a cross-sectional view taken along the direction 2-2 of FIG. 1;
- (4) FIG. 3 is a block diagram illustrating the electric power connection of the first embodiment;
- (5) FIG. 4 is a block diagram illustrating the electric power connection of the stator winding of the first electrical machine and the control unit of the first embodiment;
- (6) FIG. 5 is a circuit diagram illustrating the electric power connection of the stator winding of the first electrical machine and the control unit of the first embodiment, wherein the stator winding is

connected in a Y connection;

(7) FIG. 6 is a circuit diagram illustrating the electric power connection of the stator winding of the first electrical machine and the control unit of a second embodiment, wherein the stator winding is connected in a delta connection;

(8) FIG. 7 is a cross-sectional view of a third embodiment of the electricity generating system by magnetic power according to the disclosure in the same direction as FIG. 2;

(9) FIG. 8 is a perspective view of the first electrical machine and a first flywheel of a fourth embodiment of the magnetic power electricity generating system according to the disclosure;

(10) FIG. 9 is an exploded perspective view of the first electrical machine and the first flywheel of the fourth embodiment;

(11) FIG. 10 is a cross-sectional view taken along the direction 10-10 of FIG. 8;

(12) FIG. 11 is a perspective view of a fifth embodiment of the magnetic power electricity generating system according to the disclosure;

(13) FIG. 12 is a perspective view of a sixth embodiment of the magnetic power electricity generating system according to the disclosure; and

(14) FIG. 13 is a schematic diagram illustrating the electric power connection of a magnetic power generation system assembly according to the disclosure.

DETAILED DESCRIPTION

(15) Referring firstly to FIG. 1 to FIG. 5, a first embodiment of the magnetic power electricity generating system according to the disclosure is shown at 10. The magnetic power electricity generating system 10 comprises a first electrical machine 20 and a control unit 40 electrically connected respectively to the first electrical machine 20 and an external power supply 12.

(16) The first electrical machine 20, as shown in FIG. 1, comprises a frame 22, a stator 24, a rotor 26 and a cooling means 30. The frame 22 includes a casing 220 and an end cover 222 with a central opening 2220 mounted on one side of the casing 220. The end cover 222 includes a protruding ring 2224 extending outward. The stator 24 is received in the casing 220. The rotor 26 is rotatably disposed within the stator 24.

(17) The stator 24, as shown in FIG. 2, comprises a stator body 240 and a stator winding 242 disposed in the stator 240 by a conventional way as known in the art. The stator body 240, in this embodiment, is configured by stacking a plurality of annular silicon-steel sheets. The stator body 240 includes an outer peripheral surface 2400, a through hole 2402, an inner peripheral surface 2404 defined by the through hole 2402, and a plurality of first slots 2406. Each of the first slots 2406 is spaced apart from each other and extends from the inner peripheral surface 2404 to the outer peripheral surface 2400. Each of the first slots 2406 includes an open end 2408 facing the rotor 26, a bottom end 2410 close to the outer peripheral surface 2400. The open end 2408 and the bottom 2410 define the depth $d_{sub.0}$ of the first slot 2406. In addition, each of the first slots 2406 has a first portion 2412 adjacent to the open end 2408 and a second portion 2414 adjacent to the bottom 2410. The depth of the first portion 2412 is $d_{sub.1}$, and the depth of the second portion 2414 is $d_{sub.2}$, wherein $d_{sub.1} + d_{sub.2} = d_{sub.0}$.

(18) The stator winding 242, as shown in FIG. 2 and FIG. 5, is a three-phase winding configured in a Y connection. In more detail, the stator winding 242 comprises an R-phase winding 244, an S-phase winding 246 and a T-phase winding 248. The R-phase winding 244 includes a R-phase first coil 2440 with a R-phase first input end 2443 and a R-phase first output end 2444 and a R-phase second coil 2442 with a R-phase second input end 2445 and a R-phase second output end 2446. The S-phase winding 246 includes an S-phase first coil 2460 with an S-phase first input end 2463 and an S-phase first output end 2464 and an S-phase second coil 2462 with a S-phase second input end 2465 and an S-phase second output end 2466. The T-phase winding 248 includes a T-phase first coil 2480 with a T-phase first input end 2483 and a T-phase first output end 2484 and a T-phase second coil 2482 with a T-phase second input end 2485 and a T-phase second output end 2486. In this embodiment, each of the R, S and T phase first coils 2440, 2460 and 2480 has a first wire

diameter of 1.0 mm, a first number of turns of 48, a first number of magnetic poles of 4 and a first rated output power of 7.5 HP. Each of the R, S and T phase second coils **2442**, **2462** and **24820** has a second wire diameter of 0.8 mm, a second number of turns of 28, a second number of magnetic poles of 4 and a second rated output power of 25 HP. Each of the R, S and T phase first coils **2440**, **2460** and **2480** is installed in the first portion **2412** of each of the first slots **2406** and each of the R, S and T phase second coils **2442**, **2462** and **2482** is installed in the second portion **2414** of each of the first slots **2406** such that the reluctance of the magnetic circuit passing through the R, S and T phase first coils **2440**, **2460** and **2480** can be reduced.

(19) The control unit **40**, as shown in FIG. 3-FIG. 5, includes an electrical control means **42** and a three-phase first switch **44**, a three-phase second switch **46** and a sensor **48**. Of course, the control unit **40** can also be other technical mechanisms, such as servo drives and distributors. The three-phase first switch **44** includes an R-phase first switch **440**, an S-phase first switch **442** and a T-phase first switch **444**. The R-phase first switch **440** includes a R-phase first contact **4400**, a R-phase second contact **4402** and a R-phase third contact **4404**. The S-phase first switch **442** includes an S-phase first contact **4420**, an S-phase second contact **4422** and an S-phase third contact **4424**. The T-phase first switch **444** includes a T-phase first contact **4440**, a T-phase second contact **4442** and a T-phase third contact **4444**.

(20) In the electrical connection, each of the first inputs **2443**, **2463** and **2483** of each of the R, S and T phase first coils **2440**, **2460** and **2480** is respectively connected to each of the first contact **4400**, **4420**, **4440** of each of the R, S and T first switch **440**, **442**, and **444**. Each of the second contact **4402**, **4422**, **4442** of each of the R, S and T first switch **440**, **442**, and **444** is respectively connected to the electrical control means **42** via line A, B, and C. Each of the first outputs **2444**, **2464** and **2484** of each of the R, S and T phase first coils **2440**, **2460** and **2480** is respectively connected to a neutral point. Each of the second inputs **2445**, **2465** and **2485** of each of the R, S and T phase second coils **2442**, **2462** and **2482** is respectively connected to the electrical control means **42** via line D, E, and F. Each of the second outputs **2446**, **2466** and **2486** of each of the R, S and T phase second coils **2440**, **2460** and **2480** is respectively connected to the neutral point. The electrical control means **42** is electrically connected to the R-phase output end, the S-phase output end and the T-phase output end of the external power supply **12**. In this embodiment, as shown in FIG. 3, the three-phase second switch **46** includes a R-phase second switch **460**, an S-phase second switch **462**, and a T-phase second switch **464**. The R-phase second switch **460** includes a R-phase fourth contact **4600**, a R-phase fifth contact **4602** and a R-phase sixth contact **4604**. The S-phase second switch **462** includes an S-phase fourth contact **4620**, an S-phase fifth contact **4622**, and an S-phase sixth contact **4624**. The T-phase second switch **464** includes a T-phase fourth contact **4640**, a T-phase fifth contact **4642** and a T-phase sixth contact **4644**. Each of the fourth contact **4600**, **4620** and **4640** of each of the R, S and T phase second switch **460**, **462** and **464** is respectively connected to each of the third contact **4404**, **4424** and **4444** of each of the R, S and T phase first switch **440**, **442** and **444**. Each of the fifth contact **4602**, **4622** and **4642** of each of the R, S and T phase second switch **460**, **462** and **464** is respectively connected to an external motor **70**. Each of the sixth contact **4604**, **4624** and **4644** of each of the R, S and T phase second switch **460**, **462** and **464** is respectively connected to an external energy storage unit **80**.

(21) The rotor **26**, as shown in FIG. 1, comprises a rotor body **260** with a third number of magnetic poles, an axis hole **262** and a shaft **264** received in the axis hole **262**. The rotor body **260** is rotatably disposed in the through hole **2402** of the stator body **240**. The third number of magnetic poles is the same as the first number of magnetic poles and the second number of magnetic poles. In addition, the shaft **264** extends outward from the central opening **2220** of the end cover **222**.

(22) The cooling means **30**, as shown in FIG. 1, is disposed between the casing **220** and the stator body **240** to keep the operating temperature of the first electrical machine **20** under a predetermined temperature. In this embodiment, the cooling means **30** includes a tubular body **300** with a plurality of channels **302** formed on the surface thereof for introducing cooling liquid, such as oil or water or

other the like, and two rubber washers **304**, **306** respectively disposed at the two side of the tubular body **300** to prevent the cooling liquid seeping out.

(23) Thus, when each of the first contact **4400**, **4420**, **4440** of each of the R, S and T first switch **440**, **442**, and **444** is connected to each of the second contact **4402**, **4422**, **4442** of each of the R, S and T first switch **440**, **442**, and **444** by the control of the electrical control means **42**, the external power supply **12** would simultaneously supply power to each of the first coil **2440**, **2460** and **2480** of the R, S and T phase winding **244**, **246** and **248**, and each of the second coil **2442**, **2462** and **2482** of the R, S and T phase winding **244**, **246** and **248**, at this time, the first electrical machine **20** will be operated in the first operating mode with a power of the sum of the first rated output power 75 HP and the second rated output power 25 HP. And then the sensor **48** will send a signal to the electrical control means **42** to turn each of the first contact **4400**, **4420**, **4440** of each of the R, S and T first switch **440**, **442**, and **444** off from each of the second contact **4402**, **4422**, **4442** of each of the R, S and T first switch **440**, **442**, and **444** and connect with each of the third contact **4404**, **4424** and **4444** of the R, S and T phase first switch **440**, **442** and **444** such that the first electrical machine **20** is simultaneously operated in a motor operating mode with the second rated out power 25 HP by the second coil **2442**, **2462** and **2482** of the R, S and T phase winding **244**, **246** and **248** and in a generator operating mode with the first rated out power 75 HP by the first coil **2440**, **2460** and **2480** of the R, S and T phase winding **244**, **246** and **248** for providing electric energy to the external motor **70** or the external energy storage unit **80**. It must be mentioned here that, in this embodiment, since having the same number of magnetic poles, the first coil **2440**, **2460** and **2480** and the second coil **2442**, **2462** and **248** will have equal mutual magnetic flux $\Phi_{\text{sub.m}}$ in the stator body **240**. Thus, when the input voltage of the power supply **12** is $V_{\text{sub.1}}$, and the output voltage of each of the first coil **2440**, **2460** and **2480** is $V_{\text{sub.2}}$, according to the formula of $V_{\text{sub.1}} = N_{\text{sub.1}} d\Phi_{\text{sub.m}}/dt$ and $V_{\text{sub.2}} = N_{\text{sub.2}} d\Phi_{\text{sub.m}}/dt$, the relationship of

$N_{\text{sub.1}}/N_{\text{sub.2}} = V_{\text{sub.1}}/V_{\text{sub.2}}$ can be obtained. If the voltage $V_{\text{sub.1}}$ is 220 volts, since the first number of turns $N_{\text{sub.1}}$ is 48 and the second number of turns $N_{\text{sub.2}}$ is 28, the output voltage $V_{\text{sub.2}}$ of each of the first coil **2440**, **2460** and **2480** is about $220 \times 48/28 = 377$ volts.

(24) Referring to FIG. 6, there shows a second embodiment of the magnetic power electricity generating system according to the disclosure. The difference between the second embodiment and the first embodiment is that the stator winding of the second embodiment is configured in a delta connection. For the convenience of explanation, the reference numbers of the second embodiment below are the same as those of the first embodiment. In the second embodiment, each of the first inputs **2443**, **2463** and **2483** of each of the R, S and T phase first coils **2440**, **2460** and **2480** is respectively connected to each of the first contact **4400**, **4420**, **4440** of each of the R, S and T first switch **440**, **442**, and **444**. Each of the second contact **4402**, **4422**, **4442** of each of the R, S and T first switch **440**, **442**, and **444** is respectively connected to the electrical control means **42** via line A, B, and C. The first output **2444** of R-phase first coil **2440** is connected to the first input **2463** of the S-phase first coil **2460**. The first output **2464** of the S-phase first coil is connected to the first input **2483** of the T-phase first coil **2480**. The first output **2484** of the T-phase first coil **2480** is connected to the first input **2443** of the R-phase first coil **2440**. Each of the second inputs **2445**, **2465** and **2485** of each of the R, S and T phase second coils **2442**, **2462** and **2482** is respectively connected to the electrical control means **42** via line D, F, and F. The second output **2446** of R-phase second coil **2442** is connected to the second input **2465** of the S-phase second coil **2462**. The second output **2466** of the S-phase second coil is connected to the second input **2485** of the T-phase first coil **2482**. The second output **2486** of the T-phase second coil **2482** is connected to the second input **2445** of the R-phase second coil **2442**.

(25) Referring to FIG. 7, a third embodiment of the magnetic power electricity generating system according to the disclosure is indicated generally at **100**. The difference between the magnetic power electricity generating system **100** and the magnetic power electricity generating system **10** is that the magnetic power electricity generating system **100** comprises a stator body **102** including

not only a plurality of first slots **104** but also a plurality of second slots **106** wherein the depth of the first slots **104** is greater than that of the second slots **106** and each of the second slots **106** is arranged between two adjacent first slots **104**. The first coil **108** of each phase stator winding is installed in the first slots **104** and the second coil **110** of each phase stator winding is installed in the second slots **106**. But it must be noted the arrangement herein is just an example.

(26) Referring to FIG. 8-FIG. 10, a fourth embodiment of the magnetic power electricity generating system according to the disclosure is indicated generally at **200**. The difference between the magnetic power electricity generating system **200** and the magnetic power electricity generating system **10** is that the magnetic power electricity generating system **200** further comprises a first flywheel **202** coupled with the first electrical machine **20**. The first flywheel **202** includes a recess **204** disposed on one side of the first flywheel **202** facing the first electrical machine **20** and a second axis hole **206**. When the first flywheel **202** is coupled with the first electrical machine **20**, the end cover **222** of the frame **22** is received in the recess **204** and the shaft **264** of the rotor **26** passes through the second axis hole **206**. In this embodiment, a pair of bearings **207**, **208**, a pressing plate **209** and an inner plug **210** are disposed between the protruding ring **2224** of the end cover **222** and the shaft **264**. And a nut **212** is used to fasten the first flywheel **202** and the shaft **264** together so that the first flywheel **202** will rotate along with the shaft **264**. Thus, when the first electrical machine **20** is operated in the first operating mode, the first flywheel **202** will be driven by the first electrical machine **20**. As the first flywheel **202** reaches a predetermined speed to deliver energy to outside, the sensor **48** will send a signal to the electrical control means **42** to control the first electrical machine **20** being operated in the second operating mode to keep the first flywheel **202** rotating at the predetermined speed such that the first coil **2440**, **2460** and **2480** of the R, S and T phase winding **244**, **246** and **248** will be worked as a generator by the energy delivered by the first flywheel **202** for providing electric energy to the external loadings. For example, if the number of magnetic poles of the first electrical machine **20** is 4, the number of turns of the first coil of each phase stator winding is 48, the magnetic flux of each magnetic pole is 0.025 Weber, and the rotational speed of the first flywheel **202** is at 1800 rpm, the frequency of the induced electromotive force of each phase is $f=4 \times 1800 / 120 = 60$ Hz, and the magnitude of the induced electromotive force of each phase is $E=4.44 \times 48 \times 60 \times 0.025 = 320$ volts.

(27) Referring to FIG. 11, a fifth embodiment of the magnetic power electricity generating system according to the disclosure is indicated generally at **500**. The difference between the magnetic power electricity generating system **500** and the magnetic power electricity generating system **200** is that the magnetic power electricity generating system **500** comprises a second electrical machine **502** being configured the same as the first electrical machine **20**, a second flywheel **504** coupled to one side of the second electrical machine **502** and a third flywheel **506** coupled to another side of the second electrical machine **502**.

(28) Referring to FIG. 12, a sixth embodiment of the magnetic power electricity generating system according to the disclosure is indicated generally at **600**. The difference between the magnetic power electricity generating system **600** and the magnetic power electricity generating system **200** is that the magnetic power electricity generating system **600** comprises a third electrical machine **602** being configured the same as the first electrical machine **20**, a fourth electrical machine **604** being configured the same as the first electrical machine **20** and a third flywheel **606** respectively coupled to the third and fourth electrical machine **602**, **604**.

(29) Referring lastly to FIG. 13, a magnetic power generation system assembly according to the disclosure is indicated generally at **700**. The magnetic power generation system assembly **700** comprises five magnetic power generation systems **701**, **702**, **703**, **704** and **705**. Each magnetic energy generating system of the magnetic power generation system assembly **700** is configured the same as the first electrical machine **20**. The first magnetic power generation system **701** has a three-phase input end **7011** connected to an external power supply and a three-phase output end **7012**. The second magnetic power generation system **702** has a three-phase input end **7021**

connected to the three-phase output end **7012** of the first magnetic power generation system **701** and a three-phase output end **7022**. The third magnetic power generation system **703** has a three-phase input end **7031** connected to the three-phase output end **7022** of the second magnetic power generation system **702** and a three-phase output end **7032**. The fourth magnetic power generation system **704** has a three-phase input end **7041** connected to the three-phase output end **7032** of the third magnetic power generation system **703** and a three-phase output end **7042**. The fifth magnetic power generation system **705** has a three-phase input end **7051** connected to the three-phase output end **7042** of the fourth magnetic power generation system **704** and a three-phase output end **7052** connected to an external loading. Thereby, when the electric energy consumed by the first magnetic energy generation system **701** operated in the second operating mode is X , the output electric energy of the first magnetic energy generation system **701** can be $1.2X$. When the electric energy consumed by the second magnetic energy generation system **702** operated in the second operating mode is $1.2X$, the output electric energy of the second magnetic energy generation system **702** can be $1.44X$. When the electric energy consumed by the third magnetic energy generation system **703** operated in the second operating mode is $1.44X$, the output electric energy of the third magnetic energy generation system **703** can be $1.73X$. When the electric energy consumed by the fourth magnetic energy generation system **704** operated in the second operating mode is $1.73X$, the output electric energy of the fourth magnetic energy generation system **704** can be $2.08X$. And when the electric energy consumed by the fifth magnetic energy generation system **705** operated in the second operating mode is $2.08X$, the output electric energy of the fifth magnetic energy generation system **704** can be $2.50X$. In other words, the magnetic power generation system assembly **700** can have an output electric energy being about 2.5 times of the original electric energy consumption.

(30) Although the above-described descriptions are described with reference to the embodiments of the present disclosure, it should be understood that those skilled in the art may be capable of variously modifying and changing the present disclosure within the spirit and the scope disclosed in the claims which will be described below. Further, differences related to modifications and changes should be understood to be included in the scope of the present disclosure defined in the appended claims.

Claims

1. A magnetic power electricity generating system, comprising: an electrical machine unit comprising a first electrical machine with a first and second operating modes, wherein the first operating mode is that the first electrical machine is operated in a motor operating mode and the second operating mode is that the first electrical machine is operated in a motor operating mode and a generator operating mode simultaneously; and a control unit electrically connected respectively to the electrical machine unit and an external power supply for controlling the first electrical machine to be operated in the first operation mode or in the second operation mode; wherein the first electrical machine comprises a stator comprising a stator body and a three-phase stator winding disposed in the stator body, each phase stator winding of the three-phase stator winding comprising a first coil having a first number of magnetic poles and a first rated output power, and a second coil having a second number of magnetic poles and a second rated output power, the first number of magnetic poles being equal to the second number of magnetic poles, the first rated output power being greater than or equal to the second rated output power; and a rotor comprising a rotor body with a third number of magnetic poles and a shaft extending along the axis of the rotor body, the rotor body rotatably disposed in the stator body, the third number of magnetic poles being the same as the first number of magnetic poles or the second number of magnetic poles; whereby, when the first coil and the second coil are simultaneously electrically connected to an external power supply by the control of the control unit, the first electrical machine is operated in the first operating mode and when only the second coil electrically is connected to the external

power supply by the control of the control unit, the first electrical machine is operated in the second operating mode; wherein the stator body includes an outer peripheral surface, a through hole, an inner peripheral surface defined by the through hole, and a plurality of first slots spaced apart from each other and extending from the inner peripheral surface to the outer peripheral surface; the first coils and the second coils are respectively installed in the first slots; the rotor body is rotatably received in the through hole; wherein each of the first slots of the stator body includes an open end facing the rotor, a bottom end close to the outer peripheral surface, a first portion adjacent to the open end to install the first coil and a second portion adjacent to the bottom end to install the second coil.

2. The magnetic power electricity generating system of claim 1, wherein each of the first coils includes a first input end and a first output end, each of the second coils includes a second input end and a second output end, the control unit includes an electrical control means and a three-phase first switch, each phase first switch of the three-phase first switch includes a first contact, a second contact and a third contact; the three-phase stator winding is respectively connected in a Y connection, the first input end of the first coil is electrically connected to the first contact of the each phase first switch, and the first output end of the first coil is electrically connected to a neutral point, the second input end of the second coil is electrically connected to the external power supply via the electrical control means, and the second output end of the second coil is connected to the neutral point, the second contact of the each phase first switch is connected to the external power supply via the electrical control means, and the third contact of the each phase first switch is electrically connected to an external loading; whereby, when the magnetic power electricity generating system is in operation, the electrical control means will connect the first contact of the each phase first switch with the second contact of the each phase first switch such that the external power supply will simultaneously supply power to the first coil and the second coil to operate the first electrical machine in the first operating mode and when the first electrical machine is operated in normal state, the electrical control means will disconnect the first contact of the each phase first switch with the second contact of the each phase first switch such that the first electrical machine is operated in the second operating mode to supply electrical to external loadings.

3. The magnetic power electricity generating system of claim 1, wherein each of the first coils includes a first input end and a first output end, each of the second coils includes a second input end and a second output end, the control unit includes an electrical control means and a three-phase first switch, each phase first switch of the three-phase first switch includes a first contact, a second contact and a third contact; the three-phase stator winding is respectively connected in a delta connection wherein each of the first inputs of the first coils is respectively connected to each of the first contacts of each of phase first switches, each of the second contacts of each of phase first switches is respectively connected to the electrical control means, each of the second inputs of each of the second coils is respectively connected to the electrical control means, whereby, when the magnetic power electricity generating system is in operation, the electrical control means will connect the first contact of the each phase first switch with the second contact of the each phase first switch such that the external power supply will simultaneously supply power to the first coil and the second coil to operate the first electrical machine in the first operating mode and when the first electrical machine is operated in normal state, the electrical control means will disconnect the first contact of the each phase first switch with the second contact of the each phase first switch such that the first electrical machine is operated in the second operating mode to supply electrical to external loadings.

4. The magnetic power electricity generating system of claim 2 or 3, wherein the control unit further includes a sensor for outputting a signal to the electrical control means to turn off the power supply of the first coils.

5. The magnetic power electricity generating system of claim 1, comprising a flywheel unit comprising a first flywheel coupled with the shaft of the rotor of the first electrical machine such

that when the first flywheel is driven by the first operating mode, it will rotate at a predetermined speed to deliver energy to outside, and when the first flywheel is driven by the second operating mode, it will keep at the predetermined speed and enable the first electrical machine to supply electrical energy to external loadings.

6. The magnetic power electricity generating system of claim 5, wherein the first flywheel includes a recess receiving the end cover and a through hole passed through by the shaft of the rotor.

7. A magnetic power electricity generating system, comprising: an electrical machine unit comprising a first electrical machine with a first and second operating modes, wherein the first operating mode is that the first electrical machine is operated in a motor operating mode and the second operating mode is that the first electrical machine is operated in a motor operating mode and a generator operating mode simultaneously; and a control unit electrically connected respectively to the electrical machine unit and an external power supply for controlling the first electrical machine to be operated in the first operation mode or in the second operation mode; wherein the first electrical machine comprises a stator comprising a stator body and a three-phase stator winding disposed in the stator body, each phase stator winding of the three-phase stator winding comprising a first coil having a first number of magnetic poles and a first rated output power, and a second coil having a second number of magnetic poles and a second rated output power, the first number of magnetic poles being equal to the second number of magnetic poles, the first rated output power being greater than or equal to the second rated output power; and a rotor comprising a rotor body with a third number of magnetic poles and a shaft extending along the axis of the rotor body, the rotor body rotatably disposed in the stator body, the third number of magnetic poles being the same as the first number of magnetic poles or the second number of magnetic poles; whereby, when the first coil and the second coil are simultaneously electrically connected to an external power supply by the control of the control unit, the first electrical machine is operated in the first operating mode and when only the second coil electrically is connected to the external power supply by the control of the control unit, the first electrical machine is operated in the second operating mode; and wherein the stator body includes an outer peripheral surface, a through hole, an inner peripheral surface defined by the through hole, and a plurality of first slots with a first depth and second slots with a second depth spaced apart from each other and extending from the inner peripheral surface to the outer peripheral surface, the first depth is greater than the second depth, the first coils are installed in the first slots, the second coils are installed in the second slots; and the rotor body is rotatably received in the through hole.
