

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413584
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Shet; Ravindra Balkrishna et al.

Method and system for self-onboarding of IoT devices

Abstract

Provided is a self-onboarding method for an IoT device. The method includes: identifying, by the IoT device, a trusted device and at least one wireless network in a vicinity of the IoT device; based on identifying the trusted device in the vicinity of the IoT device, establishing, by the IoT device, a connection with an onboarding server through the trusted device; based on identifying the at least one wireless network in the vicinity of the IoT device, sending, by the IoT device, a list of the at least one wireless network to the onboarding server using the connection; receiving, by the IoT device, self-provisioning information from the onboarding server; and onboarding, by the IoT device, through the at least one wireless network based on the self-provisioning information.

Inventors: Shet; Ravindra Balkrishna (Bengaluru, IN), Reddy; Ravi Kanth (Bengaluru, IN), Lasyath; Nabeel Mohamed Chemnad (Kasaragod, IN), Pabbineedi; Vijayachandra (Bangalore, IN), Sharma; Harit (Bareilly, IN), Ramegowda; Raghavendra Vaddarahalli (Mysore, IN), Deshpande; Nishant Bhaskar (Bangalore, IN), Kumar; Dixit (Bengaluru, IN), Taduru; Hariprasad (Bengaluru, IN)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 85774917

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 17/947848

Filed: September 19, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230107045 A1	Apr. 06, 2023

Foreign Application Priority Data

IN 202141044734 Oct. 01, 2021

Related U.S. Application Data

continuation parent-doc WO PCT/KR2022/013609 20220913 PENDING child-doc US 17947848

Publication Classification

Int. Cl.: H04L9/40 (20220101)

U.S. Cl.:

CPC H04L63/0876 (20130101); H04L63/0236 (20130101); H04L63/20 (20130101);

Field of Classification Search

CPC: H04L (63/0876); H04L (63/0236); H04L (63/20)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9465951	12/2015	Cudmore et al.	N/A	N/A
10292027	12/2018	Goluboff	N/A	N/A
10547613	12/2019	Roths et al.	N/A	N/A
11087890	12/2020	Turrin et al.	N/A	N/A
11399285	12/2021	Smith	N/A	H04W 12/35
2017/0208070	12/2016	Burns et al.	N/A	N/A
2018/0199204	12/2017	Roche et al.	N/A	N/A
2019/0058586	12/2018	Kumar et al.	N/A	N/A
2019/0250899	12/2018	Riedl	N/A	H04L 9/0825
2019/0332774	12/2018	Nix	N/A	N/A
2020/0004523	12/2019	Eroshkina	N/A	H04L 12/66
2020/0076896	12/2019	Anumala et al.	N/A	N/A
2020/0275273	12/2019	Smith	N/A	H04W 12/50
2021/0051147	12/2020	Hardy et al.	N/A	N/A
2021/0058784	12/2020	Kedalagudde	N/A	H04W 48/18

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
10-1844012	12/2017	KR	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion (PCT/ISA/210, PCT/ISA/237) issued Jan. 13, 2023 by the International Searching Authority in International Application No.

PCT/KR2022/013609. cited by applicant

Symington et al., "Trusted Internet of Things (IoT) Device Network-Layer Onboarding and

Lifecycle Management”, Sep. 8, 2020, In: NIST Cybersecurity White Paper (Draft), 90 pages total. cited by applicant

Ogrodowczyk et al., “IoT ecosystem over programmable SDN infrastructure for Smart City applications”, Oct. 10, 2016, Fifth European Workshop on Software-Defined Networks, 5 pages total. cited by applicant

Ericsson et al., “UE onboarding”, May 10, 2021, S2-2104217, 3GPP TSG-WG SA2 Meeting #145E e-meeting, S2-2104217, 16 pages total. cited by applicant

Communication issued Aug. 12, 2024 by the European Patent Office in European Application No. 22876710.9. cited by applicant

Primary Examiner: Korsak; Oleg

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is a bypass application of PCT International Application No. PCT/KR2022/013609, which was filed on Sep. 13, 2022, and claims priority to Indian Patent Application No. 202141044734, filed on Oct. 1, 2021, in the Indian Patent Office, the disclosure of which is incorporated herein by reference in its entirety.

BACKGROUND

1. Field

(2) The disclosure relates to an electronic device, and more specifically to a method and a system for self-onboarding of Internet of Things (IoT) devices.

2. Description of Related Art

(3) IoT devices are widely used in environments such as home, office, etc. and can be controlled remotely/indirectly through a network (e.g., internet) using a control application installed on another device on the same network. Capability of the IoT devices to access internet is one of the unique features that differentiates the IoT devices from conventional electrical appliances. However, the IoT devices are not capable to auto onboard for accessing the internet from a wireless network (e.g., Wi-Fi access point). Onboarding is the process of connecting a new device, first to the internet, then subsequently to its enabling services. Generally, a user needs to manually onboard the IoT devices to connect and control to the wireless network. To begin onboarding of the IoT devices, the user must be present with a master device (e.g., smartphone) in proximity to the IoT devices. Further, the user needs to launch an IoT device controlling application to discover the IoT devices. Further, the user needs to select a location (e.g., home, office, etc.) where the IoT devices are located. Further, the user needs to link the IoT devices with a user account. Further, the user needs to find the wireless network to which IoT devices have to connect. Upon finding the wireless network, the user needs to link the IoT devices with the wireless network by manually entering a password to the wireless network on behalf of the IoT devices. Performing manual onboarding of the IoT devices in this way requires upwards of 8 user interactions (e.g., clicks) and 12 updates to a User Interface (UI) of the IoT device controlling application needs, and still there is more than a 50% chance that the manual onboarding fails. The onboarding failure(s) may discourage the user from adopting the IoT devices.

(4) Furthermore, when a password of the wireless network is updated, the user is expected to re-configure the IoT devices by manually entering the updated password on behalf of the IoT devices. Also, when the IoT devices are moved around within a location or multiple locations, the user is

expected to re-configure the IoT devices with a new wireless network available at that location. Thus, it is desired to provide a useful solution for self-onboarding the IoT devices without any manual intervention.

SUMMARY

(5) Provided are method and a system for self-onboarding of an IoT device. The self-onboarding aims for the IoT device to reduce human effort in configuring the IoT device. The secure self-onboarding method for the IoT device runs in background and does not need any manual presence/intervention for configuring the IoT device on a wireless network. During an onboarding setup, the user and a master device need not be in a vicinity of the IoT device to be onboarded. In case of any failure in the onboarding, the IoT device retries itself without any manual intervention. Thus, the method reduces a failure rate of the onboarding and provides frustration free onboarding of the IoT device to the user with zero UI updates, and zero user clicks. Also, a device state of the IoT device may progress from plugged-in to ready-to-use (onboarded) in less than a minute, which improves user experience.

(6) Further, provided is a method to access the onboarding server via a secure network provided by helper nodes. Wireless access provided by a helper device (node) is highly secure as compared to any open network. The helper nodes belong to a manufacturer or an IoT service provider. Also, the method uses an asymmetric key system (i.e. public-private key system) for encryption and decryption of the security credential of the wireless network. Hence, the method provides high-end security to the security credential and the IoT device.

(7) According to an aspect of the disclosure, a self-onboarding method for an Internet of Things (IoT) device, includes: identifying, by the IoT device, a trusted device and at least one wireless network in a vicinity of the IoT device; based on identifying the trusted device in the vicinity of the IoT device, establishing, by the IoT device, a connection with an onboarding server through the trusted device; based on identifying the at least one wireless network in the vicinity of the IoT device, sending, by the IoT device, a list of the at least one wireless network to the onboarding server using the connection; receiving, by the IoT device, self-provisioning information from the onboarding server; and onboarding, by the IoT device, through the at least one wireless network based on the self-provisioning information.

(8) The establishing, by the IoT device, the connection with the onboarding server through the trusted device may include: sending, by the IoT device, an advertisement including an identifier of the IoT device to the trusted device; receiving, by the IoT device, onboarding metadata including onboarding server information and authentication information from the trusted device; and establishing, by the IoT device, the connection with the onboarding server through the trusted device based on the onboarding metadata.

(9) The establishing, by the IoT device, the connection with the onboarding server through the trusted device may include: identifying, by the IoT device, the onboarding server based on the onboarding server information; establishing, by the IoT device, the connection with the onboarding server through the trusted device based on the onboarding metadata; sending, by the IoT device, the onboarding metadata to the onboarding server; and receiving, by the IoT device, a permission to continue the connection with the onboarding server through the trusted device upon successfully authenticating the IoT device by the onboarding server based on the authentication information in the onboarding metadata.

(10) The self-provisioning information may include a location of the IoT device, a location of the at least one wireless network, and an encrypted security credential of the at least one wireless network.

(11) The onboarding, by the IoT device, through the at least one wireless network may include: disabling, by the IoT device, the connection with the onboarding server; determining, by the IoT device, a nearest wireless network from the at least one wireless network based on a location of the IoT device, and a location of the at least one wireless network in the self-provisioning information;

determining, by the IoT device, a security credential of the nearest wireless network by decrypting the encrypted security credential in the self-provisioning information; and onboarding, by the IoT device, through the nearest wireless network by logging in to the nearest wireless network using the security credential.

(12) According to an aspect of the disclosure, a self-onboarding method for an Internet of Things (IoT) device, includes: receiving, by an onboarding server, a request for connection including onboarding metadata from the IoT device through a trusted device; determining, by the onboarding server, that the IoT device is authorized based on the onboarding metadata; based on determining that the IoT device is authorized, establishing, by the onboarding server, a connection with the IoT device through the trusted device; and providing, by the onboarding server, self-provisioning information to the IoT device via the connection.

(13) The providing, by the onboarding server, the self-provisioning information to the IoT device, may include: receiving, by the onboarding server, a list of at least one wireless network in a vicinity of the IoT device from the IoT device using the connection; determining, by the onboarding server, a location of the IoT device based on the list of at least one wireless network; determining, by the onboarding server, an encrypted security credential and a location of at least one wireless network included in the list of the at least one wireless network, using a database; and sending, by the onboarding server, the self-provisioning information to the IoT device, the self-provisioning information including the location of the IoT device, the location of the at least one wireless network, and the encrypted security credential of the at least one wireless network to the IoT device.

(14) The list of at least one wireless network in the vicinity of the IoT device may include at least one of an identifier and an access point name for each wireless network included in the list.

(15) The self-onboarding method may further include: receiving, by the onboarding server, onboarded information from one or more onboarded devices through at least one wireless network in a vicinity of the one or more onboarded devices, wherein the onboarded information from each onboarded device may include an identifier of at least one wireless network in a vicinity of the onboarded device, a security credential of the at least one wireless network in the vicinity of the onboarded device, and a location of the at least one wireless network in the vicinity of the onboarded device; encrypting, by the onboarding server, the security credential of the at least one wireless network; and generating, by the onboarding server, the database based on the identifier of the at least one wireless network, the location of the at least one wireless network, and the encrypted security credential.

(16) According to an aspect of the disclosure, an Internet of Things (IoT) device includes: a memory configured to store instructions; and a processor configured to execute the instructions to implement a self-onboarding engine; wherein the self-onboarding engine is configured to: identify a trusted device and at least one wireless network in vicinity of the IoT device; based on identifying the trusted device in the vicinity of the IoT device, establish a connection with an onboarding server through the trusted device; based on identifying the at least one wireless network in the vicinity of the IoT device, send a list of the at least one wireless network to the onboarding server using the connection; receive self-provisioning information from the onboarding server; and perform onboarding through the at least one wireless network based on the self-provisioning information.

(17) The self-onboarding engine may be further configured to establish the connection with the onboarding server by: sending an advertisement including an identifier of the IoT device to the trusted device; receiving onboarding metadata including onboarding server information and authentication information from the trusted device; and establishing the connection with the onboarding server through the trusted device based on the onboarding metadata.

(18) The self-onboarding engine may be further configured to establish the connection by: identifying the onboarding server based on the onboarding server information; establishing the

connection with the onboarding server through the trusted device based on the onboarding metadata; sending the onboarding metadata to the onboarding server; and receiving a permission to continue the connection with the onboarding server through the trusted device upon successfully authenticating the IoT device by the onboarding server based on the authentication information in the onboarding metadata.

(19) The self-provisioning information may include a location of the IoT device, a location of the at least one wireless network, and an encrypted security credential of the at least one wireless network.

(20) The self-onboarding engine may be further configured to perform the onboarding through the at least one wireless network by: disabling the connection with the onboarding server; determining a nearest wireless network from the at least one wireless network based on a location of the IoT device, and a location of the at least one wireless network in the self-provisioning information; determining a security credential of the nearest wireless network by decrypting the encrypted security credential in the self-provisioning information; and onboarding through the nearest wireless network by logging in to the nearest wireless network using the security credential.

(21) According to an aspect of the disclosure, a onboarding server for self-onboarding an Internet of Things (IoT) device, includes: a memory configured to store instructions; and a processor configured to execute the instructions to implement a self-onboarding engine; wherein the self-onboarding engine is configured to: receive a request for connection including onboarding metadata from the IoT device through a trusted device; determine that the IoT device is authorized based on the onboarding metadata; based on determining that the IoT device is authorized, establish a connection with the IoT device through the trusted device; and provide self-provisioning information to the IoT device via the connection.

(22) The self-onboarding engine may be further configured to provide the self-provisioning information to the IoT device by: receiving a list of the at least one wireless network in the vicinity of the IoT device from the IoT device using the connection; determining a location of the IoT device based on the list of the at least one wireless network; determining an encrypted security credential and a location of at least one wireless network included in the list of the at least one wireless network, using a database; and sending the self-provisioning information to the IoT device, the self-provisioning information including the location of the IoT device, the location of the at least one wireless network, and the encrypted security credential of the at least one wireless network.

(23) The list of the at least one wireless network in the vicinity of the IoT device may include at least one of an identifier and an access point name for each wireless network included in the list.

(24) The self-onboarding engine may be further configured to: receive onboarded information from one or more onboarded devices through at least one wireless network in a vicinity of the one or more onboarded devices, wherein the onboarded information from each onboarded device includes an identifier of at least one wireless network in a vicinity of the onboarded device, a security credential of the at least one wireless network in the vicinity of the onboarded device, and a location of the at least one wireless network in the vicinity of the onboarded device; encrypt the security credential of the at least one wireless network; and generate the database based on the identifier of the at least one wireless network, the location of the at least one wireless network, and the encrypted security credential.

(25) These and other aspects of the embodiments herein will be better appreciated and understood when considered in conjunction with the following description and the accompanying drawings. It should be understood, however, that the following descriptions, while indicating preferred embodiments and numerous specific details thereof, are given by way of illustration and not of limitation. Many changes and modifications may be made within the scope of the embodiments, and the embodiments herein include all such modifications.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other aspects, features and advantages of certain embodiments of the present disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:
- (2) FIG. 1 is a block diagram of a system for self-onboarding of an IoT device, according to an embodiment;
- (3) FIG. 2 is a flow diagram illustrating a method for self-onboarding by the IoT device, according to an embodiment;
- (4) FIG. 3 is a flow diagram illustrating a method for self-onboarding by an onboarding server, according to an embodiment;
- (5) FIG. 4 illustrates an overview of creating a database of wireless networks and self-onboarding of the IoT device, according to an embodiment;
- (6) FIG. 5 illustrates an example scenario of self-onboarding the IoT device to a wireless network for a first time, according to an embodiment;
- (7) FIG. 6 illustrates an example scenario of self-onboarding the IoT device to the wireless network due to changing a security credential of the wireless network, according to an embodiment;
- (8) FIG. 7 illustrates an example scenario of self-onboarding the IoT device to the wireless network due to changing a location of the IoT device, according to an embodiment;
- (9) FIG. 8 illustrates an example scenario of self-onboarding the IoT device to the wireless network due to changing the wireless network within same location, according to an embodiment;
- (10) FIG. 9 illustrates a flow in an example scenario of self-onboarding the IoT device, according to an embodiment;
- (11) FIG. 10 is a flow diagram illustrating auto-reconfiguration of the IoT device, according to an embodiment;
- (12) FIGS. 11-12 illustrate example scenarios of obtaining the security credential by the IoT device, according to an embodiment;
- (13) FIG. 13 is a flow diagram illustrating authentication of a trusted device, according to an embodiment;
- (14) FIG. 14 is a flow diagram illustrating registration of the trusted device at the onboarding server, according to an embodiment;
- (15) FIG. 15 is a flow diagram illustrating authentication of the IoT device at the trusted device, according to an embodiment; and
- (16) FIG. 16 is a flow diagram illustrating authorization of the onboarding server, according to an embodiment.

DETAILED DESCRIPTION

(17) The embodiments herein and the various features and advantageous details thereof are explained more fully with reference to the non-limiting embodiments that are illustrated in the accompanying drawings and detailed in the following description, where similar reference characters denote corresponding features consistently throughout. Descriptions of well-known components and processing techniques are omitted so as to not unnecessarily obscure the embodiments herein. Also, the various embodiments described herein are not necessarily mutually exclusive, as some embodiments can be combined with one or more other embodiments to form new embodiments. The term “or” as used herein, refers to a non-exclusive or, unless otherwise indicated. The examples used herein are intended merely to facilitate an understanding of ways in which the embodiments herein can be practiced and to further enable those skilled in the art to practice the embodiments herein. Accordingly, the examples should not be construed as limiting the scope of the embodiments herein.

(18) As is traditional in the field, embodiments may be described and illustrated in terms of blocks which carry out a described function or functions. These blocks, which may be referred to herein as managers, units, modules, hardware components or the like, are physically implemented by analog and/or digital circuits such as logic gates, integrated circuits, microprocessors, microcontrollers, memory circuits, passive electronic components, active electronic components, optical components, hardwired circuits and the like, and may optionally be driven by firmware. The circuits may, for example, be embodied in one or more semiconductor chips, or on substrate supports such as printed circuit boards and the like. The circuits constituting a block may be implemented by dedicated hardware, or by a processor (e.g., one or more programmed microprocessors and associated circuitry), or by a combination of dedicated hardware to perform some functions of the block and a processor to perform other functions of the block. Each block of the embodiments may be physically separated into two or more interacting and discrete blocks without departing from the scope of the disclosure. Likewise, the blocks of the embodiments may be physically combined into more complex blocks without departing from the scope of the disclosure.

(19) The accompanying drawings are used to help easily understand various technical features and it should be understood that the embodiments presented herein are not limited by the accompanying drawings. As such, the present disclosure should be construed to extend to any alterations, equivalents and substitutes in addition to those which are particularly set out in the accompanying drawings. Although the terms first, second, etc. may be used herein to describe various elements, these elements should not be limited by these terms. These terms are generally only used to distinguish one element from another.

(20) Throughout this disclosure, the terms “trusted device” and “helper device” “helper node” are used interchangeably and mean the same.

(21) Accordingly, various embodiments of the present disclosure provide a self-onboarding method for an Internet of Things (IoT) device. The method includes scanning, by the IoT device, for identifying a trusted device and wireless networks in a vicinity of the IoT device. The method includes establishing, by the IoT device, a connection with an onboarding server through the trusted device in response to identifying the trusted device in the vicinity of the IoT device. The method includes sending, by the IoT device, a list of the wireless networks to the onboarding server using the connection, in response to identifying the wireless networks in the vicinity of the IoT device. The method includes receiving, by the IoT device, self-provisioning information from the onboarding server. The method includes automatically onboarding, by the IoT device, through the wireless networks based on the self-provisioning information.

(22) Accordingly, various embodiments of the present disclosure provide the self-onboarding method for the IoT device. The method includes receiving, by the onboarding server, a request for the connection including the onboarding metadata from the IoT device through the trusted device. The method includes determining, by the onboarding server, that the IoT device is authorized based on the onboarding metadata. The method includes establishing, by the onboarding server, the connection with the IoT device through the trusted device for providing the self-provisioning information to the IoT device.

(23) Accordingly, various embodiments of the present disclosure provide the IoT device for self-onboarding. The IoT device includes a self-onboarding engine, a memory, and a processor, where the self-onboarding engine is coupled to the memory and the processor. The self-onboarding engine is configured for scanning and identifying the trusted device and the wireless network(s) in a vicinity of the IoT device. The self-onboarding engine is configured for establishing the connection with the onboarding server through the trusted device in response to identifying the trusted device in the vicinity of the IoT device. The self-onboarding engine is configured for sending the list of the wireless network(s) to the onboarding server using the connection, in response to identifying the wireless network(s) in the vicinity of the IoT device. The self-onboarding engine is configured

for receiving the self-provisioning information from the onboarding server. The self-onboarding engine is configured for automatically onboarding through the wireless network(s) based on the self-provisioning information.

(24) Accordingly, various embodiments of the present disclosure provide the onboarding server for self-onboarding. The onboarding server includes a self-onboarding engine, a memory, a processor, where the self-onboarding engine is coupled to the memory and the processor. The self-onboarding engine is configured for receiving the request for connection including the onboarding metadata from the IoT device through the trusted device. The self-onboarding engine is configured for determining that the IoT device is authorized based on the onboarding metadata. The self-onboarding engine is configured for establishing the connection with the IoT device through the trusted device for providing the self-provisioning information to the IoT device.

(25) All onboarded devices synchronize security credentials of the wireless network to which the onboarded devices are connected with the onboarding server. Further, the onboarding server encrypts the security credentials using a public key and stores them in a database. At a time of purchase of a brand new IoT device, a manufacturer or a seller of the IoT device links the IoT device with a user account provided by the manufacturer/seller to the user. Also, the manufacturer/seller embeds a device ID and a private key with the IoT device. When the IoT device is plugged in by the user, then the IoT device starts Bluetooth low energy (BLE) advertisements and finds a nearby helper device. The helper device shares temporary network access and onboarding metadata with the IoT device. Further, the IoT device scans for available wireless network(s) and sends the list of the scanned wireless network(s) to the onboarding server along with an initial authentication token. Further, the onboarding server configures the self-provisioning information and determines the IoT device location based on the list of the scanned wireless network(s). Further, the IoT device receives the self-provisioning information and the encrypted security credential of each scanned wireless network from the onboarding server. Further, the IoT device decrypts the encrypted security credential using the private key. Further, the IoT device connects to one of the wireless network using the security credential and starts self-onboarding.

(26) According to an aspect of the present disclosure, the secure self-onboarding method for the IoT device runs in background and does not need any manual presence or intervention for configuring the IoT device on the wireless network. During onboarding set up, the user and a master device need not be in a vicinity of the IoT device to be onboarded. In case of any failure in the onboarding, the IoT device retries itself without any manual intervention. Thus, the proposed method reduces a failure rate in the onboarding and provides frustration free onboarding of the IoT device to the user with zero UI updates, and zero user clicks. Also, a device state of the IoT device from plugged-in to ready-to-use (onboarded) happens in less than a minute, which improves user experience.

(27) According to an aspect of the present disclosure, the IoT device accesses the onboarding server via a secure network provided by the helper node. Wireless access provided by the helper node is highly secure as compared to any open network. The helper node belongs to the manufacturer or an IoT service provider. Also, the proposed method uses an asymmetric key system (i.e. public-private key system) for secure transfer of the security credential of the wireless network between. Hence, the proposed method provides high end security to the security credential and the IoT device.

(28) Referring now to the drawings, and more particularly to FIGS. **1** through **16**, there are shown preferred embodiments.

(29) FIG. **1** is a block diagram of a system **1000** for self-onboarding of an IoT device **100**, according to an embodiment. In an embodiment, the system **1000** includes the IoT device **100**, an onboarding server **200**, a trusted device **300**, and one or more wireless network(s) **400**. Examples of the wireless network(s) **400** include, but are not limited to wireless fidelity access points (Wi-Fi APs) located at different/same rooms in a location (e.g., home, office). The trusted device **300** is an

onboarded device such as a smartphone, an Internet of Things (IoT) device, a laptop, a wearable device, etc. which is already a part of service provider's IoT network. In an embodiment, the trusted device is connected to the internet via the wireless network(s) **400**.

(30) Examples of the IoT device **100** include, but are not limited to, a smart television (smart TV), a smart refrigerator, a smart plug etc. In an embodiment, the IoT device **100** includes a self-onboarding engine **110**, a memory **120**, a processor **130**, and a communicator **140**. The self-onboarding engine **110** is implemented by the processor **130** or separate processing circuitry such as logic gates, integrated circuits, microprocessors, microcontrollers, memory circuits, passive electronic components, active electronic components, optical components, hardwired circuits, or the like, and may optionally be driven by a firmware. The circuits may, for example, be embodied in one or more semiconductor chips, or on substrate supports such as printed circuit boards and the like.

(31) Upon detecting an error for initiating a connection at the IoT device **100**, or detecting that the IoT device **100** is not onboarded, the self-onboarding engine **110** scans for identifying a trusted device **300** and the one or more wireless network(s) **400** in a vicinity of the IoT device **100**. Further, the self-onboarding engine **110** establishes a connection with an onboarding server **200** through the trusted device **300** in response to identifying the trusted device **300** in the vicinity of the IoT device **100**. Further, the self-onboarding engine **110** sends a list of the one or more identified wireless network(s) **400** to the onboarding server **200** using the connection as shown in **A105**, in response to identifying the one or more wireless network(s) **400** in the vicinity of the IoT device **100**.

(32) Further, the self-onboarding engine **110** receives self-provisioning information as shown in **A106**, from the onboarding server **200**. In an embodiment, the self-provisioning information includes a location (e.g., location ID) of the IoT device **100**, a location of the one or more wireless network(s) **400**, a room information of the location, and an encrypted security credential (e.g., encrypted password) of the one or more wireless network(s) **400**. Further, the self-onboarding engine **110** automatically connects to one of the wireless network(s) **400** and completes onboarding based on the self-provisioning information as shown in **A107**.

(33) In an embodiment, for establishing the connection with the onboarding server **200** through the trusted device **300**, the self-onboarding engine **110** sends an advertisement (e.g., BLE advertisement **A101**) including an Identifier (ID) of the IoT device **100** to the trusted device **300**. The ID of the IoT device **100** can be a serial number of the IoT device **100**, a QR code of the IoT device **100**, etc. Further, the trusted device **300** creates a temporary connection (e.g., BLE generic attribute profile (BLE GATT) connection **A102**, Wi-Fi hotspot) with the trusted device **300**. Further, the self-onboarding engine **110** receives onboarding metadata **A103** including onboarding server information (e.g., an identifier of the onboarding server **200**) and authentication information from the trusted device **300** via the temporary connection. Authentication between the IoT device **100** and the onboarding server **200** is challenging each other with encrypted nonce, where a receiving entity decrypts to authenticate a sender. When authentication on both sides is completed, then a secure session key will generate at both ends using an Elliptic-curve Diffie-Hellman (ECDH) method which ensures that the key is same at both ends. Further, the self-onboarding engine **110** establishes the connection with the onboarding server **200** through the trusted device **300** based on the onboarding metadata. In an embodiment, the self-onboarding engine **110** connects to a hotspot **A104** of the trusted device **300** for establishing the connection with the onboarding server **200**, where the hotspot **A104** of the trusted device **300** is a soft Wi-Fi AP and a temporary connection which requires no user intervention.

(34) In an embodiment, for establishing the connection with the onboarding server **200** through the trusted device **300** based on the onboarding metadata, the self-onboarding engine **110** identifies the onboarding server **200** based on the onboarding server information. Further, the self-onboarding engine **110** establishes the connection with the onboarding server **200** through the trusted device

300 based on the onboarding metadata. Further, the self-onboarding engine **110** sends the onboarding metadata **A105** to the onboarding server **200**. Further, the self-onboarding engine **110** receives a permission to continue the connection with the onboarding server **200** through the trusted device **300** upon successfully authenticating the IoT device **100** by the onboarding server **200** based on the authentication information in the onboarding metadata.

(35) In an embodiment, for automatically onboarding through the one or more wireless network(s) **400** based on the self-provisioning information, the self-onboarding engine **110** disables the connection of the IoT device **100** with the onboarding server **200** or the trusted device **300**. Further, the self-onboarding engine **110** determines a nearest wireless network from the one or more wireless network(s) **400** based on the location of the IoT device **100**, and the location of the one or more wireless network(s) **400** in the self-provisioning information. Further, the self-onboarding engine **110** determines a security credential (e.g., password) of the nearest wireless network by decrypting the encrypted security credential in the self-provisioning information. Further, the self-onboarding engine **110** automatically onboards through the nearest wireless network by logging in to the nearest wireless network using the security credential.

(36) The memory **120** stores instructions to be executed by the processor **130**. The memory **120** may include non-volatile storage elements. Examples of such non-volatile storage elements may include magnetic hard discs, optical discs, floppy discs, flash memories, or forms of electrically programmable memories (EPROM) or electrically erasable and programmable (EEPROM) memories. In addition, the memory **120** may, in some examples, be considered a non-transitory storage medium. The term “non-transitory” may indicate that the storage medium is not embodied in a carrier wave or a propagated signal. However, the term “non-transitory” should not be interpreted that the memory **120** is non-movable. In some examples, the memory **120** can be configured to store larger amounts of information than its storage space. In certain examples, a non-transitory storage medium may store data that can, over time, change (e.g., in random access memory (RAM) or cache). The memory **120** can be an internal storage unit or it can be an external storage unit of the IoT device **100**, a cloud storage, or any other type of external storage.

(37) The processor **130** is configured to execute instructions stored in the memory **120**. The processor **130** may be a general-purpose processor, such as a Central Processing Unit (CPU), an Application Processor (AP), or the like, a graphics-only processing unit such as a Graphics Processing Unit (GPU), a Visual Processing Unit (VPU) and the like. The processor **130** may include multiple cores to execute the instructions. The communicator **140** is configured for communicating internally between hardware components in the IoT device **100**. Further, the communicator **140** is configured to facilitate the communication between the IoT device **100** and other devices (wireless network **400**, trusted device **300**) via one or more networks (e.g., Radio technology). The communicator **140** includes an electronic circuit specific to a standard that enables wired or wireless communication.

(38) In an embodiment, the onboarding server **200** includes a self-onboarding engine **210**, a memory **220**, a processor **230**, and a communicator **240**. The self-onboarding engine **210** is implemented by the processor **230** or separate processing circuitry such as logic gates, integrated circuits, microprocessors, microcontrollers, memory circuits, passive electronic components, active electronic components, optical components, hardwired circuits, or the like, and may optionally be driven by a firmware. The circuits may, for example, be embodied in one or more semiconductor chips, or on substrate supports such as printed circuit boards and the like. In an embodiment, the onboarding server **200** includes a friendly web server **210A**, a policy validator **210B**, a device authenticator **210C**, a device user-account linker **210D**, a provisioning engine **210E**, a location finder **210F**, and a Wi-Fi locker **210G**. The friendly web server **210A**, the policy validator **210B**, the device authenticator **210C**, the device user-account linker **210D**, the provisioning engine **210E**, the location finder **210F**, and the Wi-Fi locker **210G** are implemented by the processor **230** or separate processing circuitry such as logic gates, integrated circuits, microprocessors,

microcontrollers, memory circuits, passive electronic components, active electronic components, optical components, hardwired circuits, or the like, and may optionally be driven by a firmware. The circuits may, for example, be embodied in one or more semiconductor chips, or on substrate supports such as printed circuit boards and the like.

(39) The self-onboarding engine **210** receives a request (i.e. self-onboarding request) for connection including onboarding metadata and the list of the one or more wireless network(s) **400** in the vicinity of the IoT device **100** from the IoT device **100** through the trusted device **300** as shown in A105, where the list of the one or more wireless network(s) **400** includes an ID or an Access Point (AP) name of each wireless network **400**. The ID of the wireless network **400** can be a serial number of the wireless network **400**, a QR code of the wireless network **400**, etc. Further, the self-onboarding engine **210** determines whether the IoT device **100** is authorized based on the onboarding metadata. Upon determining that the IoT device **100** is authorized, the self-onboarding engine **210** establishes the connection with the IoT device **100** through the trusted device **300** for providing the self-provisioning information to the IoT device **100** as shown in A106.

(40) In an embodiment, for providing the self-provisioning information to the IoT device **100**, the self-onboarding engine **210** determines the location of the IoT device **100** based on the list of the one or more wireless network(s) **400**. Further, the self-onboarding engine **210** determines the encrypted security credential and the location of the one or more wireless network(s) **400** from a database **224** based on the list of the one or more wireless network(s) **400**. Further, the self-onboarding engine **210** sends the self-provisioning information including the location of the IoT device **100**, the location of the one or more wireless network(s) **400**, and the encrypted security credential of the one or more wireless network(s) **400** to the IoT device **100**.

(41) In an embodiment, the self-onboarding engine **210** receives the onboarded information from onboarded devices (e.g., onboarded IoT device or a master device **500** such as a smartphone used for controlling onboarded IoT device and changing security credentials of wireless network(s) **400**) through the one or more wireless network(s) **400**, where the onboarded information includes the identifier, the AP name, the security credential and the location of the one or more wireless network(s) **400**. Further, the self-onboarding engine **210** encrypts the security credential of the one or more wireless network(s) **400**. Further, the self-onboarding engine **210** generates the database **224** of the one or more wireless network(s) **400** using the identifier, the AP name, the location, and the encrypted security credential of the one or more wireless network(s) **400**. The friendly web server **210A** initiates the self-onboarding procedure for the new IoT device **100** and handles the self-onboarding request and caters self-provisioning information to the IoT device **100**. The friendly web server **210A** authenticates the trusted device **300** and shares the onboarding metadata to the trusted device **300**. The policy validator **210B** validates policies **221** for the self-onboarding request and applies restriction of usage of the trusted device **300** to owners, location members, etc. The policies may include: Number of connected devices consume the internet of the trusted device **300** (e.g., maximum number the connected devices to consume the internet is allowed at any given point of time can be 10), Internet data utilized from the trusted device **300** for device onboarding (e.g., maximum of 50 MB per month can be utilized), Network bandwidth utilization, Self-owned device vs external devices, etc.

(42) The device authenticator **210C** authenticates the IoT device **100** and device related operations or command execution, and manages IoT device data for all users. The device user-account linker **210D** manages user accounts and associates the user accounts with the IoT device **100** or the onboarded devices. The provisioning engine **210E** generates the self-provisioning information, resolves the location ID for the IoT device **100**, and prioritizes the Wi-Fi AP list before serving to the IoT device **100**. The location finder **210F** assists the provisioning engine **210E** in resolving the location of the IoT device **100**, manages the locations of all IoT devices linked with the user accounts, and assigns the location ID for a new IoT device. The Wi-Fi locker **210G** fetches the ID, the location, the AP name, and the encrypted security credential of the Wi-Fi APs from the database

224 by performing a Wi-Fi AP to location mapping

(43) The memory **220** includes the database **224**. The memory **220** stores the policies **221**, a list of the onboarded devices **222**, and user accounts **223** registered to the onboarding server **200** or the trusted device **300**. The memory **220** stores instructions to be executed by the processor **230**. The memory **220** may include non-volatile storage elements. Examples of such non-volatile storage elements may include magnetic hard discs, optical discs, floppy discs, flash memories, or forms of electrically programmable memories (EPROM) or electrically erasable and programmable (EEPROM) memories. In addition, the memory **220** may, in some examples, be considered a non-transitory storage medium. The term “non-transitory” may indicate that the storage medium is not embodied in a carrier wave or a propagated signal. However, the term “non-transitory” should not be interpreted that the memory **220** is non-movable. In some examples, the memory **220** can be configured to store larger amounts of information than its storage space. In certain examples, a non-transitory storage medium may store data that can, over time, change (e.g., in RAM or cache). The memory **220** can be an internal storage unit or it can be an external storage unit of the onboarding server **200**, a cloud storage, or any other type of external storage.

(44) The processor **230** is configured to execute instructions stored in the memory **220**. The processor **230** may be a general-purpose processor, such as a central processing unit (CPU), an application processor (AP), or the like, a graphics-only processing unit such as a graphics processing unit (GPU), a visual processing unit (VPU) and the like. The processor **230** may include multiple cores to execute the instructions. The communicator **240** is configured for communicating internally between hardware components in the onboarding server **200**. Further, the communicator **240** is configured to facilitate the communication between the onboarding server **200** and other devices (trusted device **300**) via one or more networks (e.g., Radio technology). The communicator **240** includes an electronic circuit specific to a standard that enables wired or wireless communication.

(45) Although the FIG. **1** shows the hardware components of the system **1000** but it is to be understood that other embodiments are not limited thereon. In other embodiments, the system **1000** may include less or a greater number of components. Further, the labels or names of the components are used only for illustrative purpose and does not limit the scope of the invention. One or more components can be combined together to perform same or substantially similar function for self-onboarding of the IoT device **100**.

(46) FIG. **2** is a flow diagram **A200** illustrating a method for self-onboarding by the IoT device, according to an embodiment. In an embodiment, the method allows the self-onboarding engine **110** to perform operations **A201-A205** of the flow diagram **A200**. At **A201**, the method includes scanning for and identifying the trusted device **300** and the wireless network(s) **400** in a vicinity of the IoT device **100**. At **A202**, the method includes establishing the connection with the onboarding server **200** through the trusted device **300** in response to identifying the trusted device **300** in the vicinity of the IoT device **100**. At **A203**, the method includes sending the list of the wireless network **400s** to the onboarding server **200** using the connection, in response to identifying the wireless network(s) **400** in the vicinity of the IoT device **100**. At **A204**, the method includes receiving the self-provisioning information from the onboarding server **200**. At **A205**, the method includes automatically onboarding through one wireless network **400** based on the self-provisioning information.

(47) FIG. **3** is a flow diagram illustrating a method for self-onboarding by the onboarding server, according to an embodiment. In an embodiment, the method allows the self-onboarding engine **210** to perform operations **A301-A303** of the flow diagram **A300**. At **A301**, the method includes receiving the request for the connection including the onboarding metadata from the IoT device **100** through the trusted device **300**. At **A302**, the method includes determining that the IoT device **100** is authorized based on the onboarding metadata. At **A303**, the method includes establishing the connection with the IoT device **100** through the trusted device **300** for providing self-provisioning

information to the IoT device **100**.

(48) The various actions, acts, blocks, steps, operations, or the like in the flow diagrams (**A200**, **A300**) may be performed in the order presented, in a different order, or simultaneously. Further, in some embodiments, some of the actions, acts, blocks, steps, operations, or the like may be omitted, added, modified, skipped, or the like without departing from the scope of the invention.

(49) FIG. **4** illustrates an overview of creating the database **224** of the wireless network(s) **400** and self-onboarding of the IoT device **100**, according to an embodiment. The master device **500** stores a list of onboarded IoT devices (e.g., smart bulb) and controls operations (e.g., turn ON/OFF, increase/decrease brightness) of the onboarded IoT devices. The master device **500** knows the onboarded information including the wireless network(s) **400** to which the onboarded IoT devices are connected, the ID, the location ID, the security credentials, and the AP name of the wireless network(s) **400**. At **401**, the master device **500** provides the onboarded information to the onboarding server **200** via an internet connection. The onboarding server **200** encrypts the security credentials using a public key, and stores the ID, the location ID, the encrypted security credentials, and the AP name of the wireless network(s) **400** to the database **224**.

(50) Consider, the IoT device **100** (e.g., smart TV) is not onboarded. Upon detecting that the IoT device **100** is not onboarded, the IoT device **100** scans for nearby Wi-Fi APs. At **402**, the IoT device **100** connects to the onboarding server **200** via the trusted device **300** and sends the list of scanned Wi-Fi APs including the IDs/name of the scanned Wi-Fi APs to the onboarding server **200**. At **403**, the onboarding server **200** fetches the location ID, and the encrypted security credentials corresponding to each ID/name of the scanned Wi-Fi APs in the list and sends the location ID, and the encrypted security credentials of the scanned Wi-Fi APs to the IoT device **100**. At **404**, the IoT device **100** analyzes the received location IDs for identifying the Wi-Fi AP **400** nearest to the IoT device **100**. Further, the IoT device **100** decrypts the encrypted security credential of the Wi-Fi AP **400** using a private key, and obtains the security credential. At **405**, the IoT device **100** connects to the Wi-Fi AP **400** using the security credential and automatically onboards via the Wi-Fi AP **400**. At **406**, the master device **500** updates the list of onboarded IoT devices by adding the IoT device **100** (e.g., smart TV) also to the list of onboarded IoT devices.

(51) FIG. **5** illustrates an example scenario of self-onboarding the IoT device **100** to the wireless network **400** for the first time, according to an embodiment. At **501**, consider the user purchased the IoT device **100** (e.g., smart TV). At **502**, the user plugs the smart TV **100** for the first time, and the smart TV **100** is going to onboard for the first time. At **503**, upon detecting that the smart TV **100** is not onboarded, the smart TV **100** scans for the nearby trusted device **300**. At **504-505**, upon detecting the trusted device **300**, the smart TV **100** connects to the hotspot of the trusted device **300**, and uses the temporary internet connection provided by the hotspot to reach the onboarding server **200**. At **506**, the smart TV **100** retrieves the encrypted security credential of the nearby Wi-Fi APs from the onboarding server **200**. Further, the smart TV **100** decrypts the encrypted security credential using the private key and obtains the security credential. At **507**, the smart TV **100** connects to one of the nearby Wi-Fi AP **400** by automatically providing the security credential to the nearby Wi-Fi AP **400** for accessing the internet. At **508**, the smart TV **100** automatically completes the onboarding process by accessing the internet via the nearby Wi-Fi AP **400**.

(52) Unlike existing methods and systems, a manual onboarding of the IoT device **100** at the Wi-Fi AP is avoided using the proposed method. Also, the user need not be present with the master device (e.g., smartphone) during onboarding.

(53) FIG. **6** illustrates an example scenario of self-onboarding the IoT device **100** to the wireless network **400** due to changing the security credential of the wireless network, according to an embodiment. Consider, the IoT device **100** (e.g., smart TV) is already onboarded and connected to the Wi-Fi AP **400**. Later, at **601** the user has changed the password of the Wi-Fi AP **400**. The updated password of the Wi-Fi AP **400** was synchronized with the boarding server **200**. The boarding server **200** encrypts the updated password of the Wi-Fi AP **400** using the public key and

stores the encrypted updated password in the database **224**. The smart TV **100** tries to access the internet via the Wi-Fi AP **400** using the previous password but got a rejection from the Wi-Fi AP **400**.

(54) At **602**, the smart TV **100** goes offline and shows a connection error due to the rejection. At **603**, upon detecting the connection error or the offline for a pre-defined threshold time, the smart TV **100** starts the BLE scan and advertisement for finding the nearby trusted device **300**. At **604-605**, upon finding the trusted device **300**, the smart TV **100** connects to the hotspot of the trusted device **300**, and uses the temporary internet connection provided by the hotspot to reach the onboarding server **200**. At **606**, the smart TV **100** retrieves the encrypted updated password of the Wi-Fi AP **400** from the onboarding server **200**. Further, the smart TV **100** decrypts the encrypted updated password using the private key and obtains the updated password. At **607**, the smart TV **100** connects to one of the Wi-Fi AP **400** by automatically providing the updated password to the Wi-Fi AP **400** for accessing the internet. At **608**, the smart TV **100** automatically completes the onboarding process by accessing the internet via the Wi-Fi AP **400**.

(55) Unlike existing methods and systems, the proposed method allows the IoT device **100** to change from an offline state to a ready-to-use state in less than a minute, and avoids the manual re-configuration of the wireless network **400** in the IoT device **100**.

(56) FIG. 7 illustrates an example scenario of self-onboarding the IoT device **100** to the wireless network **400** due to changing the location of the IoT device **100**, according to an embodiment. Consider, at **701** the IoT device **100** (e.g., smart plug) is onboarded and connected to a Wi-Fi AP in an office of the user. So, the smart plug **100** is associated with the location ID of the office. At **702**, later the user carries the smart plug **100** from the office to a home of the user. At **703**, the smart plug **100** has electrically connected to a power supply of the home location to power up/down the smart TV (**100a**) in the home location. The internet is required for the powering up/down operation of the smart plug **100**. But, due to changing the location of the smart plug **100**, when the smart plug **100** tries to access the internet via the Wi-Fi AP **400** in the home, the Wi-Fi AP **400** detects a mismatch in the location ID associated with the smart plug **100** and the location ID associated with the Wi-Fi AP **400** in the home. Due to the mismatch in the location IDs, the Wi-Fi AP **400** does not allow the smart plug **100** to access the internet via the Wi-Fi AP **400** in the home.

(57) At **704**, upon detecting the connection error at the smart plug **100**, the smart plug **100** scans for the nearby trusted device **300**. At **705-706**, upon detecting the trusted device **300**, the smart plug **100** connects to the hotspot of the trusted device **300**, and uses the temporary internet connection provided by the hotspot to reach the onboarding server **200**. At **707**, the onboarding server **200** disassociates the smart plug **100** from the location ID of the office and associates the smart plug **100** with the location ID of the home for re-onboarding. At **708**, the smart plug **100** retrieves the encrypted security credential of the Wi-Fi AP in the home and the location ID of the home. Further, the smart plug **100** decrypts the encrypted security credential using the private key and obtains the security credential. At **709**, the smart plug **100** connects to the Wi-Fi AP **400** in the home by automatically providing the security credential to the Wi-Fi AP **400** for accessing the internet. At **710**, upon successfully matching the location IDs associated with the smart plug **100** and the Wi-Fi AP **400**, and receiving the correct security credential, the Wi-Fi AP **400** allows the smart plug **100** to access the internet via the Wi-Fi AP **400**. Further, the smart plug **100** automatically re-onboards using the internet.

(58) The proposed method is manual effort in dis-association of the IoT device **100** from the previous location ID, re-association of the IoT device **100** with the new location ID, and re-onboarding of the IoT device **100**.

(59) FIG. 8 illustrates an example scenario of self-onboarding the IoT device **100** to the wireless network due to changing the wireless network within the same location, according to an embodiment. Consider, at **801** the IoT device **100** (e.g., smart TV) is onboarded and connected to a Wi-Fi AP **400A** in a living room of the home of the user. So, the smart TV **100** only contains the

security credential of the Wi-Fi AP 400A in the living room. At 802, later the user shifts the smart TV 100 from the living room to a bedroom of the home, where a Wi-Fi AP 400B is located in the bedroom. The security credential of the Wi-Fi AP 400A is different from the security credential of the Wi-Fi AP 400B. At 803, upon turning on the smart TV 100, the smart TV 100 tries to access the internet via the Wi-Fi AP 400B by providing the security credential of the Wi-Fi AP 400A to the Wi-Fi AP 400B. The Wi-Fi AP 400B detects a mismatch in the security credential provided by the smart TV 100 and the security credential configured with the Wi-Fi AP 400B. Due to the mismatch in the security credentials, the Wi-Fi AP 400B rejects the smart TV 100 from accessing the internet via the Wi-Fi AP 400B.

(60) At 803, the smart TV 100 goes offline and shows a connection error due to the rejection. At 804, upon detecting the connection error, the smart TV 100 scans for the nearby trusted device 300. At 805-806, upon detecting the trusted device 300, the smart TV 100 connects to the hotspot of the trusted device 300, and uses the temporary internet connection provided by the hotspot to reach the onboarding server 200. At 807, the smart TV 100 retrieves the encrypted security credential of the Wi-Fi AP 400B from the onboarding server 200. Further, the smart TV 100 decrypts the encrypted security credential using the private key and obtains the security credential. At 808, the smart TV 100 connects to the Wi-Fi AP 400B in the bedroom by automatically providing the security credential to the Wi-Fi AP 400B for accessing the internet. At 809, the smart TV 100 automatically completes the onboarding process and accesses the internet via the Wi-Fi AP 400B.

(61) FIG. 9 illustrates a flow in an example scenario of self-onboarding the IoT device 100, according to an embodiment. Consider, the IoT device 100 (e.g., smart TV) is linked with the user account, the IoT device 100 has internet access, and the IoT device 100 knows the onboarding server 200 Uniform Resource Locator (URL) through the trusted device 300. In an embodiment, the onboarding server 200 includes a self-provisioning gateway 26, the provisioning engine 210E, an accio 25, a locksmith 24 (also called as Wi-Fi locker 210G), a device identity 23, an Open Connectivity Foundation (OCF) account 22, and an OCF connection 21. A device manufacturer of the IoT device 100 registers all the manufactured IoT devices with the device identity 23, where the device identity 23 posts the public key of all the registered IoT devices to the self-provisioning gateway 26. The self-provisioning gateway 26 stores the device's public key and validates a JWT token. The provisioning engine 210E generates the device ID, and generates a temporary token that includes a client ID and a secret.

(62) At 901, the IoT device 100 checks whether anyone owns the IoT device 100 with the onboarding server 200 by creating an application programming interface (API) self-onboard/session {sn=serial number of the IoT device 100, jwt=JWT token}. At 902, the self-provisioning gateway 26 checks whether the IoT device 100 is manufactured by the device manufacturer 600 who owns the onboarding server 200 by obtaining the public key of the IoT device 100 using the sn, and validating the JWT token using the device public key. If the JWT token is validated. At 903, the self-provisioning gateway 26 requests for the temporary token to the provisioning engine 210E. At 904-905, the provisioning engine 210E gets a manufacturer account global user identifier (saguid) for the given device sn from the accio 25. At 906, the provisioning engine 210E sends the device ID, saguid, and the temporary token to the self-provisioning gateway 26. At 907, upon getting the temporary token, the self-provisioning gateway 26 continues further transaction else returns an error status to the IoT device 100.

(63) Upon getting the temporary token, the self-provisioning gateway 26 identifies the IoT device 100, informs a user ID owned the IoT device 100, and device ID of the IoT device 100. At 908, the IoT device 100 scans for the Wi-Fi APs and provides the scanned Wi-Fi AP list to the onboarding server 200. Further, the IoT device 100 requests the onboarding server 200 for the permission to connect to any one of the Wi-Fi Aps and the onboarding information. The scanned Wi-Fi AP list includes Headers: X-IOT-TOKEN:Temp Token, saguid, [name1, name2]. At 908, the onboarding server 200 provides a response includes the security credentials of a few Wi-Fi APs to the IoT

device **100**. At **912**, the IoT device **100** starts onboarding using the security credentials by providing the temporary token, the device ID, and the saguid to the OCF connection **21**. At **913**, the OCF connection **21** starts signing up using a post oic/account at the OCF account **22**. At **912**, the OCF account **22** contains permission API (X-IOT-CLIENTDN) from the device identity **23**.

(64) FIG. **10** is a flow diagram illustrating the auto-reconfiguration of the IoT device **100**, according to an embodiment. In an embodiment, the onboarding server **200** includes the provisioning engine **210E**, the accio **25**, the locksmith **24**, the device identity **23**, the OCF account **22**, and the friendly web server **210A**. At **1001**, consider, the user modified the security credential of the Wi-Fi AP **400** using the master device **500**. At **1002**, the master device **500** synchronizes the updated security credential with the locksmith **24**. At **1003**, due to modifying the security credential, the IoT device **100** cannot access the internet via the Wi-Fi AP **400**. At **1004**, after waiting for internet access for the threshold duration, the IoT device **100** finds and connects to the trusted device **300**. At **1005**, a friendly web helper stack **30** of the trusted device **300** requests to the friendly web server **210A** for handling the IoT device **100**.

(65) Further, the friendly web server **210A** authenticates the IoT device **100** and provides a temporary encrypted Wi-Fi credential to the friendly web helper stack **30**. Further, the friendly web helper stack **30** shares the temporary encrypted Wi-Fi credential to the IoT device **100**. At **1006**, the IoT device **100** connects to the hotspot of the trusted device **300** using the temporary encrypted Wi-Fi credential. At **1007-1008**, the IoT device **100** retrieves the encrypted updated security credential of the Wi-Fi AP **400** from the provisioning engine **210E** via the friendly web helper stack **30**. At **1006**, the IoT device **100** determines the updated security credential from the encrypted updated security credential and connects to the Wi-Fi AP **400** using the updated security credential. At **1010**, the IoT device **100** accesses the internet and becomes online via the Wi-Fi AP **400**.

(66) FIGS. **11-12** illustrate example scenarios of obtaining the security credential by the IoT device **100**, according to an embodiment. In an embodiment, the onboarding server **200** includes the accio **25**, the locksmith **24**, the device identity **23**, an OCF account **22**, a self-onboarding server **27**, the OCF connection **21** and a Client Application Programming Interface (CAPI)/doorbell **31**.

(67) With reference to the FIG. **11**, at **1101** the IoT device manufacture **600** registers the IoT device **100** by providing the device serial number, the public key, etc. to the device identity **23**. At **1102**, a seller of the IoT device **100** associates the serial number of the IoT device **100** with the user account at a store **700** while selling the IoT device **100** to the user. At **1103**, upon associating the serial number of the IoT device **100** with the user account, the master device **500** of the user receives a push notification regarding the association from the accio **25**, where the user account is activated in the master device **500** to receive notifications from the onboarding server **200**. At **1104**, the master device **500** requests for the public key of the IoT device **100** to the CAPI/doorbell **31** by providing the serial number. Further, the CAPI/doorbell **31** forwards the request to the locksmith **24**. At **1105**, the locksmith **24** obtains the list IoT devices based on the saguid from the accio **25**.

(68) At **1106**, the locksmith **24** obtains the public key based on the serial number. Further, the locksmith **24** provides the public key to the CAPI/doorbell **31**. At **1107**, the CAPI/doorbell **31** forwards the public key to the master device **500**. At **1108**, the master device **500** requests for the encrypted security credentials of the nearby Wi-Fi AP to the CAPI/doorbell **31**. At **1109**, the IoT device **100** provides the scanned Wi-Fi AP list to the self-onboarding server **27** and requests for the permission to connect to any one of Wi-Fi AP. At **1110**, the self-onboarding server **27** obtains the saguid based on the serial number of the IoT device **100** from the device identity **23**. At **1111**, the self-onboarding server **27** obtains the encrypted security credential from the locksmith **24**. At **1112**, the self-onboarding server **27** sends the encrypted security credential to the IoT device **100**, and the IoT device **100** decrypts the encrypted security credential using the private key of the IoT device **100**.

(69) With reference to the FIG. **12**, at **1201** the IoT device manufacture **600** registers the IoT device **100** by providing the device serial number, the public key, etc. to the device identity **23**. At **1202**,

the master device **500** uploads the security credential includes the saguid, a Service Set Identifier (ssid), the password of the Wi-Fi APs to the CAPI **31** or the OCF connection **21**. At **1203**, the CAPI **31** or the OCF connection **21** provides the saguid and the Wi-Fi data (e.g., Wi-Fi AP name, passphrase, mac address, frequency, security type, etc.) to the locksmith **24**. At **1204**, the IoT device **100** provides the scanned Wi-Fi AP list to the self-onboarding server **27** and requests for the permission to connect to any one of Wi-Fi AP. At **1205**, the self-onboarding server **27** obtains the saguid based on the serial number of the IoT device **100** from the accio **25**. At **1206-1207**, the self-onboarding server **27** obtains the encrypted security credential from the locksmith **24**. At **1209**, the self-onboarding server **27** sends the encrypted security credential to the IoT device **100**, and the IoT device **100** decrypts the encrypted security credential using the private key of the IoT device **100**.

(70) FIG. **13** is a flow diagram illustrating authentication of the trusted device **300**, according to an embodiment. In an embodiment, the onboarding server **200** includes the accio **25**, the locksmith **24**, the device identity **23**, the OCF account **22**, a helper data router (chaser) **32**, and a client connection **33**. The helper data router **32** has an access to onboarding server internal service APIs through helper gateway. Consider, the user account is linked with the IoT device **100** that is currently in the offline state. The API has permission to share the Wi-Fi AP's security credential to the IoT device **100**. Operations **1301A-1301C** should complete by the onboarded device to operate the onboarded device as the trusted device **300**. The onboarded device must acquire Helper Data Router (HDR) token to permanently operate as the trusted device **300**. At **1301A-1301B**, the onboarded device obtains the HDR token from the client connection **33**.

(71) At **1301c**, the client connection **33** stores detail of the onboarded device that requested for operating as the trusted device. At **1301**, the IoT device **100** sends the onboarding request to the trusted device **300**. At **1302**, the trusted device **300** routes the onboarding request to the helper data router **32**. At **1303-1304**, the helper data router **32** validates the HDR token of the trusted device **300** by signing up using the post oic/account at the OCF account **22**. At **1305**, the OCF account **22** uses the permission API (X-IOT-CLIENTDN) from the accio **25**, and the device identity **23**. At **1306**, client connection **33** requests for the security credentials based on the device ID to the helper data router **32**. At **1307-1308**, the OCF account **22** gets the saguid for the given device ID and the encrypted security credentials of the user account from the locksmith **24**. At **1309**, the IoT device **100** connects to the Wi-Fi AP **400** upon receiving the encrypted security credentials from the onboarding server **200**.

(72) FIG. **14** is a flow diagram illustrating registration of the trusted device **300** at the onboarding server **200**, according to an embodiment. In an embodiment, the onboarding server **200** includes a destination cloud and a proxy cloud. The destination cloud includes a chaser with staging, Acceptance, Production, and a find my mobile (FMM) cloud with staging, PRODs. The proxy cloud includes the OCF connection **21**, the helper data router **32**, and a hub server. The onboarded device such as a smart TV that wishes to operate as the trusted device obtains the HDR token from the OCF connection **21**. Also, a hub that want to operate as the trusted device obtains the HDR token from the hub server. The OCF connection **21** and the hub server communicates with the helper data router **32** for allowing the onboarded device or the hub to operate as the trusted device. The helper data router **32** also receives data from the onboarded device. The helper data router **32** communicates with the chaser and the FMM cloud. The onboarded device, the hub, OCF connection **21** and the hub server are arranged at an authentication layer that leverages current authentication. The helper data router **32**, the chaser, and the FMM cloud are arranged at a routing layer that do parsing and routing. The chaser, and the FMM cloud are arranged at a processing layer that do validation and storing.

(73) FIG. **15** is a flow diagram illustrating authentication of the IoT device **100** at the trusted device **300**, according to an embodiment. In an embodiment, the onboarding server **200** includes a policy server **34**, the friendly web server **210A**, and the device identity **23**. At **1501**, a friendly web endpoint stack **35** of the IoT device **100** sends the BLE advertisement (i.e. Client Hello includes

client_serial_hash) to the friendly web helper stack **36** of the trusted device **300**. At **1502**, the friendly web helper stack **36** sends a friendly web access request includes the client_serial_hash to the friendly web server **210A**. At **1503A**, the friendly web server **210A** get IoT device's public key using the client_serial_hash from the device identity **23**. At **1503B**, the device identity **23** generates a server public key and a server private key. At **1503C**, the device identity **23** generate a shared key using ECDH, and shares to the friendly web server **210A**.

(74) At **1504**, the friendly web server **210A** sends a friendly Server challenge includes the server public key, a challenge server, and a nonce. At **1505**, the friendly web helper stack **36** sends a BLE server challenge includes the server public key, and the challenge, and the nonce to the friendly web endpoint stack **35**. At **1506**, the friendly web endpoint stack **35** generates the shared key using the ECDH. At **1507**, the friendly web endpoint stack **35** sends a BLE client response includes challenge_response to the friendly web helper stack **36**. At **1508**, the friendly web helper stack **36** sends a friendly web client response includes a challenge response to the friendly web server **210A**. At **1509-1510**, the friendly web server **210A** authenticates the policy server **34**, and sends a friendly web access response includes the client_serial_hash and a helper confirmation to the friendly web helper stack **36**.

(75) At **1511**, the friendly web helper stack **36** configures the Wi-Fi AP **400**. At **1512A**, the friendly web helper stack **36** sends a friendly web helper request includes the client_hash_serial, and the AP's security credential to the friendly web server **210A**. At **1512B**, the device identity **23** encrypts the AP's security credential using the shared key, and shares the encrypted AP's security credential to the friendly web server **210A**. At **1512C**, the friendly web server **210A** sends a friendly web helper response includes the encrypted AP's security credential to the friendly web helper stack **36**. At **1513**, the friendly web helper stack **36** sends a BLE server response includes the encrypted AP's security credential to the friendly web endpoint stack **35**. At **1514**, the friendly web helper stack **36** connects to the AP **400** based on the encrypted AP's security credential.

(76) FIG. **16** is a flow diagram illustrating authorization of the onboarding server **200**, according to an embodiment. In an embodiment, the onboarding server **200** includes the policy server **34**, the friendly web server **210A**, the policy validator **210B**, the device authenticator **210C**, and configurations **35**, where the configurations **35** defines maximum bandwidth, maximum devices connections, and a data limit. The policy validator **210B** contains number of device connections, and data utilized per saguid. The device authenticator **210C** performs user device mapping and contains information of registered helper nodes.

(77) At **1601**, upon receiving the BLE advertisement (e.g., Client Hello includes client_serial_hash) from the IoT device **100**, the friendly web helper stack **36** of the trusted device **300** sends the friendly web access request includes the client_serial_hash to the friendly web server **210A**. At **1602**, the friendly web server **210A** successfully handshakes with the friendly web helper stack **36**. At **1603**, the friendly web helper stack **36** checks for the policy with the friendly web server **210A** by checking whether a client serial number is true or false. At **1604**, the friendly web server **210A** authorizes the IoT device **100** with the policy server **34** for checking the policy. At **1604**, the policy server **34** gets the configurations **35**, data per user from the policy validator **210B**, and user devices information from the device authenticator **210C** for authorizing the IoT device **100**.

(78) The embodiments of the disclosure may be implemented using at least one hardware device and performing network management functions to control the elements.

(79) The foregoing description of the specific embodiments will so fully reveal the general nature of the embodiments herein that others can, by applying current knowledge, readily modify and/or adapt for various applications such specific embodiments without departing from the generic concept, and, therefore, such adaptations and modifications should and are intended to be comprehended within the meaning and range of equivalents of the disclosed embodiments. It is to be understood that the phraseology or terminology employed herein is for the purpose of description and not of limitation. Therefore, while the embodiments herein have been described in

terms of preferred embodiments, those skilled in the art will recognize that the embodiments herein can be practiced with modification within the scope of the embodiments as described herein.

Claims

1. A self-onboarding method for an Internet of Things (IoT) device, the self-onboarding method comprising: identifying, by the IoT device, a trusted device and at least one wireless network in a vicinity of the IoT device, wherein the trusted device is connected to the at least one wireless network and provides a temporary connection to reach an onboarding server; based on identifying the trusted device in the vicinity of the IoT device, establishing, by the IoT device, a connection with the onboarding server through the trusted device; based on identifying the at least one wireless network in the vicinity of the IoT device, sending, by the IoT device and through the trusted device, a list of the at least one wireless network to the onboarding server using the connection; receiving, by the IoT device, self-provisioning information from the onboarding server; and onboarding, by the IoT device, through the at least one wireless network based on the self-provisioning information, wherein the self-provisioning information comprises a location of the IoT device, a location of the at least one wireless network, and an encrypted security credential of the at least one wireless network.
2. The self-onboarding method of claim 1, wherein the establishing, by the IoT device, the connection with the onboarding server through the trusted device comprises: sending, by the IoT device, an advertisement comprising an identifier of the IoT device to the trusted device; receiving, by the IoT device, onboarding metadata comprising onboarding server information and authentication information from the trusted device via the temporary connection; and establishing, by the IoT device, the connection with the onboarding server through the trusted device based on the onboarding metadata.
3. The self-onboarding method of claim 2, wherein the establishing, by the IoT device, the connection with the onboarding server through the trusted device comprises: identifying, by the IoT device, the onboarding server based on the onboarding server information; establishing, by the IoT device, the connection with the onboarding server through the trusted device based on the onboarding metadata; sending, by the IoT device, the onboarding metadata to the onboarding server; and receiving, by the IoT device, a permission to continue the connection with the onboarding server through the trusted device upon successfully authenticating the IoT device by the onboarding server based on the authentication information in the onboarding metadata.
4. The method of claim 3, wherein the establishing, by the IoT device, the connection with the onboarding server through the trusted device comprises: sending, by the IoT device, data indicating a public key associated with the IoT device and a token; and establishing, by the IoT device, the connection with the onboarding server through the trusted device in response to a successful validation of the token with the public key.
5. The self-onboarding method of claim 1, wherein the onboarding, by the IoT device, through the at least one wireless network comprises: disabling, by the IoT device, the connection with the onboarding server; determining, by the IoT device, a nearest wireless network from the at least one wireless network based on the location of the IoT device, and the location of the at least one wireless network in the self-provisioning information; determining, by the IoT device, a security credential of the nearest wireless network by decrypting the encrypted security credential in the self-provisioning information; and onboarding, by the IoT device, through the nearest wireless network by logging in to the nearest wireless network using the security credential.
6. A self-onboarding method for an Internet of Things (IoT) device, the self-onboarding method comprising: receiving, by an onboarding server, a request for connection comprising onboarding metadata from the IoT device through a trusted device, wherein the trusted device is connected to at least one wireless network and is connected to the IoT device, and provides a temporary

connection to reach the onboarding server; determining, by the onboarding server, that the IoT device is authorized based on the onboarding metadata; based on determining that the IoT device is authorized, establishing, by the onboarding server, a connection with the IoT device through the trusted device; and providing, by the onboarding server, self-provisioning information to the IoT device via the connection, wherein the providing, by the onboarding server, the self-provisioning information to the IoT device, comprises: receiving, by the onboarding server, a list of at least one wireless network in a vicinity of the IoT device from the IoT device using the connection; determining, by the onboarding server, a location of the IoT device based on the list of at least one wireless network; determining, by the onboarding server, an encrypted security credential and a location of at least one wireless network included in the list of the at least one wireless network, using a database; and sending, by the onboarding server, the self-provisioning information to the IoT device, the self-provisioning information including the location of the IoT device, the location of the at least one wireless network, and the encrypted security credential of the at least one wireless network to the IoT device.

7. The method of claim 6, wherein the determining, by the onboarding server, that the IoT device is authorized comprises: receiving, by the onboarding server, a serial number and a token, from the IoT device; identifying, by the onboarding server, a public key associated with the IoT device based on the serial number; validating, by the onboarding server, the token with the public key; and determining, by the onboarding server, that the IoT device is authorized in response to a successful validation of the token with the public key.

8. The self-onboarding method of claim 6, wherein the list of at least one wireless network in the vicinity of the IoT device comprises at least one of an identifier and an access point name for each wireless network included in the list.

9. The self-onboarding method of claim 6, further comprising: receiving, by the onboarding server, onboarded information from one or more onboarded devices through at least one wireless network in a vicinity of the one or more onboarded devices, wherein the onboarded information from each onboarded device comprises an identifier of at least one wireless network in a vicinity of the onboarded device, a security credential of the at least one wireless network in the vicinity of the onboarded device, and the location of the at least one wireless network in the vicinity of the onboarded device; encrypting, by the onboarding server, the security credential of the at least one wireless network; and generating, by the onboarding server, the database based on the identifier of the at least one wireless network, the location of the at least one wireless network, and the encrypted security credential.

10. An Internet of Things (IoT) device comprising: a memory configured to store instructions; and a processor configured to execute the instructions to implement a self-onboarding engine; wherein the self-onboarding engine is configured to: identify a trusted device and at least one wireless network in vicinity of the IoT device, wherein the trusted device is connected to the at least one wireless network and provides a temporary connection to reach an onboarding server; based on identifying the trusted device in the vicinity of the IoT device, establish a connection with the onboarding server through the trusted device; based on identifying the at least one wireless network in the vicinity of the IoT device, send, through the trusted device, a list of the at least one wireless network to the onboarding server using the connection; receive self-provisioning information from the onboarding server; and perform onboarding through the at least one wireless network based on the self-provisioning information, and wherein the self-provisioning information comprises a location of the IoT device, a location of the at least one wireless network, and an encrypted security credential of the at least one wireless network.

11. The IoT device of claim 10, wherein the self-onboarding engine is further configured to establish the connection with the onboarding server by: sending an advertisement comprising an identifier of the IoT device to the trusted device; receiving onboarding metadata comprising onboarding server information and authentication information from the trusted device via the

temporary connection; and establishing the connection with the onboarding server through the trusted device based on the onboarding metadata.

12. The IoT device of claim 11, wherein the self-onboarding engine is further configured to establish the connection by: identifying the onboarding server based on the onboarding server information; establishing the connection with the onboarding server through the trusted device based on the onboarding metadata; sending the onboarding metadata to the onboarding server; and receiving a permission to continue the connection with the onboarding server through the trusted device upon successfully authenticating the IoT device by the onboarding server based on the authentication information in the onboarding metadata.

13. The IoT device of claim 10, wherein the self-onboarding engine is further configured to perform the onboarding through the at least one wireless network by: disabling the connection with the onboarding server; determining a nearest wireless network from the at least one wireless network based on the location of the IoT device, and the location of the at least one wireless network in the self-provisioning information; determining a security credential of the nearest wireless network by decrypting the encrypted security credential in the self-provisioning information; and onboarding through the nearest wireless network by logging in to the nearest wireless network using the security credential.

14. An onboarding server for self-onboarding an Internet of Things (IoT) device, the onboarding server comprising: a memory configured to store instructions; and a processor configured to execute the instructions to implement a self-onboarding engine; wherein the self-onboarding engine is configured to: receive a request for connection comprising onboarding metadata from the IoT device through a trusted device, wherein the trusted device is connected to at least one wireless network and is connected to the IoT device, and provides a temporary connection to reach the onboarding server; determine that the IoT device is authorized based on the onboarding metadata; based on determining that the IoT device is authorized, establish a connection with the IoT device through the trusted device; and provide self-provisioning information to the IoT device via the connection, and wherein the self-onboarding engine is further configured to provide the self-provisioning information to the IoT device by: receiving a list of the at least one wireless network in a vicinity of the IoT device from the IoT device using the connection; determining a location of the IoT device based on the list of the at least one wireless network; determining an encrypted security credential and a location of at least one wireless network included in the list of the at least one wireless network, using a database; and sending the self-provisioning information to the IoT device, the self-provisioning information including the location of the IoT device, the location of the at least one wireless network, and the encrypted security credential of the at least one wireless network.

15. The onboarding server of claim 14, wherein the list of the at least one wireless network in the vicinity of the IoT device comprises at least one of an identifier and an access point name for each wireless network included in the list.

16. The onboarding server of claim 14, wherein the self-onboarding engine is further configured to: receive onboarded information from one or more onboarded devices through at least one wireless network in a vicinity of the one or more onboarded devices, wherein the onboarded information from each onboarded device comprises an identifier of at least one wireless network in a vicinity of the onboarded device, a security credential of the at least one wireless network in the vicinity of the onboarded device, and the location of the at least one wireless network in the vicinity of the onboarded device; encrypt the security credential of the at least one wireless network; and generate the database based on the identifier of the at least one wireless network, the location of the at least one wireless network, and the encrypted security credential.
