

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12402554
B2
September 02, 2025
Kaeb; Paul A. et al.

Methods for maintaining a metered flow rate of fluid treated seed

Abstract

A stream of seed may be maintained at a metered flow rate through multiple stages of a treatment process. These multiple stages include dispensing, first application of fluid, second application of fluid, and seed transport. Seed transport may be accomplished through a conveyor configured to maintain the metered flow rate while providing static mixing, drying, and conditioning of the treated seed. The metered stream of seed may be treated within a first treatment applicator where a first wet treatment is applied, transferred through the incline conveyor, and treated again within a second treatment applicator where a second wet treatment is applied. Overtreating in multiple stages may layer consecutive seed treatments around the treated seed. A predetermined amount of seed treatment may be applied to the coated seed based on the metered flow rate established. Maintaining the metered flow rate through multiple stages eliminates the need for multiple metering steps.

Inventors: Kaeb; Paul A. (Sabetha, KS), Kaeb; Jason P. (Sabetha, KS), Edelman; Matthew J. (Sabetha, KS)

Applicant: KSi Conveyor, Inc. (Sabetha, KS)

Family ID: 74230646

Assignee: KSi Conveyor, Inc. (Sabetha, KS)

Appl. No.: 17/937810

Filed: October 04, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230148467 A1	May. 18, 2023

Related U.S. Application Data

Publication Classification

Int. Cl.: **A01C1/06** (20060101); **A01C1/00** (20060101); **B01F23/50** (20220101); **B01F23/60** (20220101); **B01F25/431** (20220101); **B01F35/53** (20220101); **B29B7/30** (20060101); **B29B7/58** (20060101); **B29B7/60** (20060101); **F26B3/06** (20060101); **F26B15/12** (20060101); **F26B15/22** (20060101); **F26B21/00** (20060101); **F26B25/14** (20060101); **A01C1/08** (20060101); **B01F101/09** (20220101)

U.S. Cl.:

CPC **A01C1/06** (20130101); **A01C1/00** (20130101); **B01F23/54** (20220101); **B01F23/60** (20220101); **B01F25/4316** (20220101); **B01F25/43161** (20220101); **B01F25/431971** (20220101); **B01F35/531** (20220101); **B29B7/30** (20130101); **B29B7/584** (20130101); **B29B7/60** (20130101); **F26B3/06** (20130101); **F26B15/12** (20130101); **F26B15/22** (20130101); **F26B21/004** (20130101); **F26B25/14** (20130101); **A01C1/08** (20130101); **B01F2101/09** (20220101); **B01F2215/0422** (20130101); **F26B2200/06** (20130101); **F26B2200/08** (20130101)

Field of Classification Search

CPC: **A01C** (1/06); **A01C** (1/00); **A01C** (1/08); **A01C** (7/06); **B01F** (23/54); **B01F** (23/60); **B01F** (25/4316); **B01F** (25/43161); **B01F** (25/431971); **B01F** (35/531); **B01F** (2101/09); **B01F** (2215/0422); **B29B** (7/30); **B29B** (7/584); **B29B** (7/60); **B29B** (9/16); **F26B** (3/06); **F26B** (15/12); **F26B** (15/22); **F26B** (21/004); **F26B** (25/14); **F26B** (2200/06); **F26B** (2200/08); **A01N** (5/02); **A01N** (25/04); **A01N** (25/16); **A01N** (25/26)

USPC: 34/87; 504/100; 504/101; 47/57.6; 47/58.1

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2580854	12/1951	Sherman	N/A	N/A
2880522	12/1958	Rollins	N/A	N/A
3096212	12/1962	Rosenleaf	N/A	N/A
3259199	12/1965	Noble et al.	N/A	N/A
3693942	12/1971	Foucalt	N/A	N/A
3968771	12/1975	Walgenbach et al.	N/A	N/A
4125332	12/1977	Shmednecht	N/A	N/A
4465017	12/1983	Simmons	47/DIG.9	B01J 2/006
4582047	12/1985	Williams	N/A	N/A
4591275	12/1985	Garthus	N/A	N/A
4756348	12/1987	Moller	N/A	N/A
4867343	12/1988	Ricciardi et al.	N/A	N/A
4910880	12/1989	Cole	N/A	N/A

5005514	12/1990	Verrico	N/A	N/A
5052545	12/1990	Gongen	N/A	N/A
5401534	12/1994	Bourreau	427/242	B01F 29/64
5407692	12/1994	Caridis et al.	N/A	N/A
5435945	12/1994	Paoli et al.	N/A	N/A
5499873	12/1995	Cummins et al.	N/A	N/A
5567238	12/1995	Long, Jr.	118/314	A01C 1/06
5615606	12/1996	Vos	N/A	N/A
5622561	12/1996	Cummins et al.	N/A	N/A
6209259	12/2000	Madigan et al.	N/A	N/A
6422381	12/2001	Eberlc et al.	N/A	N/A
8292065	12/2011	Neufeld et al.	N/A	N/A
8646383	12/2013	Howard	N/A	N/A
9096376	12/2014	Wood et al.	N/A	N/A
9790031	12/2016	Stenson et al.	N/A	N/A
9889785	12/2017	Horn	N/A	N/A
9957109	12/2017	Kaeb et al.	N/A	N/A
10986770	12/2020	Forsyth	N/A	N/A
11242209	12/2021	Graff et al.	N/A	N/A
11612868	12/2022	Jagan	118/57	A23P 20/18
2004/0177769	12/2003	Kobayashi	N/A	N/A
2012/0181093	12/2011	Fehr et al.	N/A	N/A
2013/0168209	12/2012	Fanshier et al.	N/A	N/A
2015/0359164	12/2014	Bardi	47/57.6	A01C 1/00
2018/0124994	12/2017	Kaeb	N/A	F26B 25/12
2019/0009989	12/2018	Francisco	N/A	N/A
2019/0075712	12/2018	Reineccius et al.	N/A	N/A
2021/0029867	12/2020	Edelman et al.	N/A	N/A
2021/0031156	12/2020	Edelman et al.	N/A	N/A
2021/0094060	12/2020	Heinen	N/A	N/A
2021/0094066	12/2020	Heinen	N/A	N/A
2021/0380345	12/2020	Kuckoski et al.	N/A	N/A
2022/0201925	12/2021	Edelman et al.	N/A	N/A
2022/0272891	12/2021	Smith	N/A	A01C 1/06
2023/0085702	12/2022	Schmehl et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
204223801	12/2014	CN	N/A
207491478	12/2017	CN	N/A
102014105423	12/2014	DE	N/A
2618040	12/1988	FR	N/A
2703268	12/1993	FR	N/A
2788795	12/1999	FR	N/A
221642	12/1923	GB	N/A
100773067	12/2006	KR	N/A
1020140121508	12/2013	KR	N/A
1166785	12/1984	SU	N/A
1496755	12/1988	SU	N/A
2020212868	12/2019	WO	N/A

OTHER PUBLICATIONS

AGI, Storm Pro Seed Treater, Storm Pro 2018, Nov. 28, 2017, 4 pages, vol. 1, www.aggrowth.com, Saskatchewan, Canada. cited by applicant

Benoit, Dion, Appliance for coating seeds in bulk form, by means of a liquid treatment product, This is a machine-translated text of a patent application originally published on Jan. 20, 1989 in France, No. FR2618040A1. cited by applicant

Brabender Technologie & Co KG GmbH, Dosing differential balance for liquid dosing, Oct. 22, 2015, 6 pages, This is a machine translation of a patent application originally published as DE102014105423A1 in Germany. cited by applicant

Ecnnet Co., Ltd, et al., The blending method and the apparatus for auto-controlling ratio of size of recycling aggregate, 32 pages, This is a machine translation of a foreign patent originally published on Nov. 2, 2007 as KR100773067B1, Korea. cited by applicant

Flexicon, Weigh Batching Systems, Bulk Handling Equipment and Systems, Published at least as early as Jul. 2, 2021, Flexicon Corporation. cited by applicant

GSI Intersystems, Bulk Weighers, Material Handling Bulk Weighers, Published Mar. 2016, 12 pages, AgCo., www.grainsystems.com. cited by applicant

Jiyuan Chaoqun Agricultural Technology Development Co., Ltd, A kind of agricultural seed mixes medicine device, 5 pages, This is a machine translated text of a patent application originally published on Jun. 15, 2018, China, No. CN207491478U. cited by applicant

KSI Conveyor, Inc. by Paul A. Kaeb, Statement regarding public sale, Sep. 17, 2021, 2 pages, Sabetha, Kansas, United States. cited by applicant

KSI Conveyor, Inc., "KSiAutoTreat V4.2 System User's Manual," Sep. 9, 2015, 84 pages, Sabetha, Kansas, USA. cited by applicant

KSI Conveyor, Inc., Client—SC 03 Quote, Aug. 19, 2021, 2 pages, KSi Conveyor, Inc., Sabetha, Kansas, United States. cited by applicant

KSI Conveyor, Inc., Installation Plan CL03, Aug. 19, 2021, 4 pages, KSi Conveyor, Inc., Sabetha, Kansas, United States. cited by applicant

Louis, Pollione, Apparatus for moistening powdery materials, especially those of the type having hydraulic (water-based) binders, This is a machine translated text of a patent originally published on Oct. 7, 1994 in France, No. FR2703268A1. cited by applicant

Precia Molen™, ABS-X Ex Hopper Scale, Bulk Discontinuous Weighing, Published at least as early as Jun. 14, 2022, 2 pages, Precia Molen™, France. cited by applicant

Toolots, Dynamic Quantitative Packaging System, published at least as early as Jun. 5, 2019, 1 page, Toolots Store, www.toolots.com, United States. cited by applicant

Weigh Right Automatic Scale Co., Entry Level Smart Net Weigh Scale, 2 pages, Published in Mar. 2016, Weigh Right Automatic Scale Co. , Joliet, IL, United States, www.weighright.com. cited by applicant

, Grain Drier, 8 pages, This is a machine translation of a patent application originally published on Oct. 16, 2014, South Korea, No. KR20140121508A. cited by applicant

Et al., A kind of automatically adjustable conveyor belt mixing device, 5 pages, This is a machine translated text of a patent application originally published on Mar. 25, 2015, China No. CN204223801U. cited by applicant

Luc Latteux, et al., Plant for processing waste recycling has adjustable regulator measuring height of material layer leaving plant and pegs ensuring rabbling of binder/material mixture, 5 pages, This is a machine translated text of a patent application originally published on Jul. 28, 2000, France, No. FR2788795A1. cited by applicant

, et al., Apparatus for metering, mixing and conveying loose materials, 4 pages, This is a machine translated text of a patent application originally published on Jul. 15, 1985, Soviet Union, No.

SU1166785A1. cited by applicant

, et al., Apparatus for metering, mixing and conveying loose materials, 4 pages, This is a machine translated text of a patent application originally published on Jul. 30, 1989, Soviet Union, No.

SU1496755A1. cited by applicant

Primary Examiner: McCormack; John P

Attorney, Agent or Firm: Coughlin Law Office, llc

Background/Summary

CROSS-REFERENCES (1) This application is a continuation of U.S. National Stage Application Ser. No. 17/595,531, entitled “Mixing and Drying Conveyor,” and filed on 18 Nov. 2021, which claims the benefit of PCT Application No. PCT/US2020/070324, entitled “Mixing and Drying Conveyor,” and filed on 29 Jul. 2020, which claims the benefit of U.S. Provisional Application No. 62/879,940, entitled “Mixing Inclined Belt Conveyor having Static Baffles with Seed Passages,” and filed 29 Jul. 2019, which are incorporated by reference herein in their entirety.

FIELD

(1) The present disclosure relates to a conveyor with a belt forming a trough, the conveyor capable of mixing, drying, conditioning, and applying a treatment material to a particulate material during conveyance.

BACKGROUND

(2) Agricultural seeds are often treated with treatments such as insecticides, fungicides, and other compositions before planting. The time window for planting—when the weather is warm enough and the fields are dry—is often very short. This means the seed dealer must quickly treat and deliver a high volume of seed to farmers who are ready to plant their fields. These seed treatments are commonly applied by spraying a liquid composition to the surface of seed, which requires a smaller quantity of seed treatment composition than the traditional field application of treatment fluids.

SUMMARY

(3) The last stage of treating seeds involves mixing and drying the wet, freshly treated seed. Seed treatment systems generally incorporate a mixing drum, such as the mixing drum disclosed in U.S. Pat. Nos. 8,985,931 and 10,194,577, both patents by Terry N. Kaeb et al and assigned to KSi Conveyor, Inc., the disclosures of which are incorporated by reference herein in their entirety. Drying drums can be expensive and take up substantial space. Alternative post-treatment plant seed mixing methods include screw conveyors, such as conventional steel augers, brush augers, and poly cupped flighting augers. Users may prefer belt conveyors over screw conveyors for transferring plant seeds. Belt conveyors are an effective solution for transporting particulate material at an incline. An endless belt is looped around rollers at the head and tail end of the conveyor. The endless belt may be spliced or made without splicing. The endless belt may incorporate texture on the carrying surface to assist with traction for carrying the load up an incline. For example, the carrying surface can incorporate chevrons to assist with carrying the load.

(4) In general, the disclosure features a conveyor having a conveyance structure. Partially disposed within the conveyance structure is a belt. A gas manifold, having one or more manifold outlets, may be disposed within or on an exterior of the conveyance structure.

(5) The conveyor may include a lid or sidewall through which the manifold outlets pass. A plurality of mixing baffles may be longitudinally spaced apart through the conveyor in a laterally alternating manner. The plurality of manifold outlet ports, operably connected to the manifold, may be

disposed laterally adjacent to the mixing baffles. The manifold may be operably connected to a vacuum source or pressurized air source. A filter may be disposed between the manifold and the vacuum source. A recirculating air system may provide the vacuum source and the pressurized air source. A vacuum port may be disposed at a head end of the conveyor.

(6) A stream of particulate matter may be conditioned with a conveyor. A pressurized gas source is connected to a portion of the conveyor. The stream of particulate material, such as seed, is carried through the conveyor on a belt. A mixing baffle induces turbulent backflow in the stream of particulate material.

(7) Debris may be extracted from the stream of particulate material with a negative pressure connected to the conveyor from the pressurized gas source. Humid air may be extracted from the conveyor with a negative pressure connected to the conveyor from the pressurized gas source. Introduce gas into the conveyor with a positive pressure from the pressurized gas source. The gas introduced into the conveyor may be atmospheric air or conditioned air, such as dehumidified air.

(8) The mixing and drying conveyor can be used for treating and overtreating seed. A metered stream of particulate material is provided to a first applicator. The metered stream of particulate material treated with a first treatment in the first applicator. The metered stream of particulate material having the first treatment is transferred to a second applicator. The stream of particulate material having the first treatment is then treated with a second treatment.

(9) The metered stream of particulate material having the first treatment is mixed in a first conveyor with a plurality of mixing baffles. The metered stream of particulate material having the first treatment is dried in the first conveyor by providing pressurized gas to the first conveyor. The metered stream of particulate material having the second treatment can be mixed in the second conveyor with a plurality of mixing baffles. The metered stream of particulate material having the second treatment can be dried in the second conveyor by providing pressurized gas within the second conveyor.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) Aspects are illustrated by way of example, and not by way of limitation, in the accompanying drawings, wherein:
- (2) FIG. 1 shows a top-side perspective view of a curvilinear structure of the conveyor with the contents of the conveyor below the lid shown in dashed lines;
- (3) FIG. 2 shows a top perspective view of a curvilinear structure of the conveyor with the lid removed showing alternating baffles;
- (4) FIG. 3 shows a top perspective view of a transition zone and conveyor with the lids shown in place;
- (5) FIG. 4 shows a top perspective view of the transition zone and conveyor with lids removed showing the alternating mixing baffles in place;
- (6) FIG. 5 shows a front close-up view of the transition zone showing the alternating mixing paddles in place;
- (7) FIG. 6 shows a top-side perspective view of a mixing paddle;
- (8) FIG. 7 shows a top-side perspective view of a mixing baffle;
- (9) FIG. 8 shows a top-side perspective view of a mixing baffle;
- (10) FIG. 9 shows a top-side perspective view of a mixing baffle;
- (11) FIG. 10 shows a top-side perspective view of a multiple stage seed treater using conveyors for mixing and drying;
- (12) FIG. 11 shows a top perspective view of a conveyor having mixing baffles and a conditioning apparatus disposed within a curvilinear structure;

- (13) FIG. 12 shows a top-side perspective view of a conveyor having mixing baffles and a conditioning apparatus disposed within the curvilinear structure;
- (14) FIG. 13 shows a top-side perspective view of a conditioning apparatus;
- (15) FIG. 14 shows a top-side perspective view of a conditioning apparatus having two gas manifolds mounted to the exterior portion of the curvilinear structure; and
- (16) FIG. 15 shows a top-side perspective view of a conditioning apparatus having two gas manifolds.

DETAILED DESCRIPTION

(17) FIG. 1 shows an internal view of a conveyor **110** with mixing apparatus **100**. The mixing apparatus may mix and dry particulate material during transportation up the incline belt conveyor. The particulate material is carried on the belt through the curvilinear structure **114**. The curvilinear structure **114** comprises the lower trough of the conveyor, through which the belt (not shown) travels. When the belt travels through the curvilinear structure, the belt takes on a similar curvilinear cross section. As the belt conforms to the curvilinear structure **114** when the belt moves through the transition portion of the conveyance structure. The particulate material is carried on the belt, as the belt is driven with a driven roller, through the curvilinear structure. Conforming the belt to the curvilinear structure provides a bed depth for increased transportation rates, provides side support for more aggressive mixing, and allows for complete cleanout of particulate matter at the head end of the conveyor. The complete cleanout of particulate matter may be advantageous when conveyors are moving material such as treated seed where customers are sensitive to cross-contamination.

(18) The belt has a carrying surface, which engages the particulate matter. The belt is endless, in that it is wrapped around a head roller and a tail roller, to make a continuous path. The belt may be spliced. The belt may be a solid woven belt with a cover such as a PVG Belt, Continental PVG 120S1 CBb. The PVG belt may have a polyester, single-ply interwoven outer cover. The PVG belt provides low stretch, excellent fastener retention, and good tear and wear resistance. The cover may also resist reactivity with seed treatment. Alternatively, the belt may be a solid woven belt with a cover of polyvinyl chloride or be a belt made wholly of rubber, or other materials.

(19) The moving belt of the conveyor transports particulate material from a tail end to a head end (in a downstream direction, shown by arrow **113**) as shown in FIG. 1. The rate of transfer or belt speed may range from 80 to 140 meters per minute (approximately 250 to 450 feet per minute). In one example, the belt transfers particulate material at a volume of 360 kilograms (approximately 800 pounds) per minute with a belt speed of 110 meters per minute (approximately 350 feet per minute). The belt may have a texture projection on the carrying surface to assist with traction and transfer of the particulate material up an incline. For example, the carrying surface can incorporate texture projections such as raised crescents, chevrons, or herringbones to assist with carrying the load on a solid belt. Raised chevrons may be beneficial in conveying the load during mixing. It may be beneficial to limit the height of the texture projection to less than 2.54 cm (1 inch), less than 1.904 cm ($\frac{3}{4}$ inch), less than 1.27 cm ($\frac{1}{2}$ inch), or less than 0.635 cm ($\frac{1}{4}$ inch), so the texture projection does not protect a substantial amount of the seed bed from interaction with the mixing baffles and to prevent the mixing baffles contacting the texture projection. The texture projection may be angled 90-degrees to maintain a perpendicular axis to the plane of the belt surface. Alternatively, the texture projections may be angled upstream, with an obtuse angle away from the perpendicular axis to the plane of the belt surface. Alternatively, the texture projections may be angled downstream, with an acute angle away from the perpendicular axis to the plane of the belt surface.

(20) The linear edges of the belt may be protected by a longitudinal guard. The guard may be L-shaped, C-shaped, or overlap the belt with a rounded lip or planar projection. The guard may be made from low- or high-density polyethylene, polytetrafluorethylene, or ultra-high molecular weight polyethylene, or other material that provides impact, chemical, abrasion, and moisture-

resistance and a low-friction surface. The guard may be disposed between the linear edges of the lid **120** and the outside edge of the curvilinear structure **114**. The guard overlaps the belt to prevent particulate material from wedging between the belt and the trough of the curvilinear structure **114**. The guard may prevent loss of seed, damage to seed, cross-contamination, and belt wear by preventing the turbulent flow of seed from entering between the belt and the curvilinear structure **114**.

(21) We recognized that a plurality of mixing baffles may be incorporated into a belt conveyor to mix seed—or other particulate material—being transported on the belt. Inserting a plurality of mixing baffles into the stream of the particulate material induces a turbulent backflow of the particulate material. Backflow of seed during conveyance may be generally regarded as contrary to the transportation purpose of conveyance in an incline conveyor. However, we recognized that backflow of seed could be induced to mix seed during belt conveyor transference. In the case of wet, freshly treated plant seed, this backflow may cause a mixing, polishing, and drying of the plant seed. Mixing distributes the seed treatment into an even coat by rubbing the individual seeds of the seed flow stream together. The belt movement generates the seed stream flow, which is then divided and mixed using the static mixing baffles.

(22) As shown in FIG. 2, the mixing apparatus **100** may comprise a plurality of mixing baffles **130A**, **130B**, **130C**, **130D**, **130E**, **130F**, **130G**, **130H** referred to in general as mixing baffles **130**. Utilizing mixing baffles within the conveyor **110** may eliminate the need for a mixing and drying drum, which may decrease the cost, time, and operational footprint of a seed treatment system.

(23) The mixing baffles partially obstruct the flow of seed, inducing a turbulent backflow, in an amount prescribed based on the shape and structure of the mixing baffles. The backflow disrupts the flow of the seed within the curvilinear structure **114**. An eddy or pocket within the seed flow stream may form behind the mixing baffles. The eddy may fill with gravity-induced backflow of seed from downstream thereby providing further mixing. The mixing baffles **130** may be made of a rigid durable material such as ultra-high-molecular-weight polyethylene, acrylonitrile butadiene styrene, steel, or other sufficiently rigid and durable material. Mixing baffles are longitudinally spaced apart within the curvilinear structure at a set distance above the carrying surface of the belt, or above the top of the texture projection

(24) As shown in FIG. 2, the mixing baffles **130** are mounted such that the downstream portion of the mixing baffle extends inwardly toward the center of the conveyor **110**. A first mixing baffle **130A** is mounted on a first lateral side **170** of the conveyor **110**. The first mixing baffle is slanted relative to the longitudinal axis of the conveyor. The slant of the mixing baffle directs lateral movement of the particulate material from the first lateral side **170** to a second lateral side **172** of the conveyor **110**. The particulate material may ricochet off the upstream surface **133** of the first mixing baffle **130A**, causing the particulate material to move backwards (upstream, see arrow **112** in FIG. 1) in the longitudinal axis of the conveyor and towards the opposite lateral side. The first mixing baffle is mounted to the conveyor with a peripheral portion **134** disposed upstream of a central portion **132**. The first mixing baffle can be mounted at less than a 50° angle (see angle α in FIG. 1) between a first plane **150** defined by the first mixing baffle **130A** and a vertical plane **152** tangential to the curvilinear structure **114** of the conveyor **110** at the sidewall **154**. In the situation where the particulate material is a quantity of a plant seed partially covered with a wet seed treatment, inducing backflow, and directing lateral movement spreads the wet seed treatment about the quantity of the plant seed.

(25) As shown in FIGS. 1 and 2, the mixing baffles **130** are disposed in alternating lateral sides. A first plurality of mixing baffles **130A**, **130C**, **130E**, and **130G** are disposed on the first lateral side **170** of the conveyor **110**. A second plurality of mixing baffles **130B**, **130D**, **130F**, and **130H** are disposed on the second lateral side **172** of the conveyor **110**. In this orientation, the first plurality of mixing baffles disposed on the first lateral side **170** cause seed to move from the first lateral side **170** to the second lateral side **172**. In a similar manner, the second plurality of mixing baffles

disposed on the second lateral side **172** cause particulate material to move from the second lateral side **172** to the first lateral side **170**.

(26) The mixing baffles **130** may be spaced apart longitudinally through a longitudinal portion **111** of the conveyor **110**. The mixing baffles **130** may be spaced apart every twelve inches. Seven mixing baffles may be disposed longitudinally within an eight-foot section of curvilinear structure as shown in FIG. 1. The curvilinear structure may have an eight-inch diameter cross section. Alignment of the mixing baffles may be: first mixing baffle **130A** is on the first lateral side **170**, with a first passage disposed in a first peripheral portion; second mixing baffle **130B** is on the second lateral side **172**, with a second passage disposed in a second peripheral portion; third mixing baffle **130C** is on the first lateral side **170**, with a third passage disposed in a third peripheral portion; the fourth mixing baffle **130D** is on the second lateral side **172**, with a fourth passage disposed in a central portion. Alternatively, the pattern of the passage location may alternate between being in a central portion **132** of certain mixing baffles and disposed in a peripheral portion **134** of other mixing baffles.

(27) As shown in FIG. 2, eight mixing baffles may be disposed longitudinally within a section of curvilinear structure. The curvilinear structure may have a nine-inch diameter cross section. A preferred pattern puts the passages in alternating locations, where a first mixing baffle **130A** is disposed in the first lateral side **170** with a peripheral passage, followed by a second mixing baffle **130B** disposed in the second lateral side **172** with a peripheral passage, followed by a third mixing baffle **130C** disposed in the first lateral side with a peripheral passage, followed by a fourth mixing baffle **130D** disposed in the second lateral side with a central passage **138**, followed by a fifth mixing baffle **130E** disposed in the first lateral side with a central passage, followed by a sixth mixing baffle **130F** disposed in the second lateral side with a peripheral passage, followed by a seventh mixing baffle **130G** disposed in the first lateral side with a central passage, and lastly followed by an eighth mixing baffle **130H** disposed in the second lateral side with a central passage. In this pattern, there is no clear passage for a portion of the particulate stream to travel through the curvilinear structure of the incline conveyor without encountering a mixing baffle. The pattern of the passage may alternate between inducing greater backflow within a central portion of the curvilinear structure **114** in a first section of the conveyor **110**, where mixing baffles contain a peripheral passage, followed by a second section with greater backflow along the lateral sides of the curvilinear structure **114**, where mixing baffles contain a central passage. At points along the longitudinal axis of the conveyor, backflow may deviate from the pattern of the passage by inserting a mixing baffle, where the passage deviates from the adjacent mixing baffles in that section of the conveyor **110**.

(28) As shown in FIGS. 3 and 4, one or more mixing baffles **130** may be mounted to an underside of a plurality of removable lid sections **120A**, **120B**, **120C**, **120D**, referred to in general as a lid **120**. The lid mounts to the curvilinear structure **114** or another portion of the conveyance structure. The lid prevents rain and debris from entering the conveyor **110** as well as preventing particulate material from exiting the conveyor **110**. The mixing baffles **130** are mounted directly to and perpendicular to the lid **120** with an L-shaped mounting bracket **160** as shown in FIG. 2. As shown in FIGS. 1 and 3, a lid **120** may comprise a plurality of apertures **163** corresponding to the mounting position of the mixing baffles **130**. Alternatively, the mixing baffles **130** may be mounted to scaffolding or directly to the conveyor frame (not shown). The scaffolding may be mounted to the conveyor frame or curvilinear structure **114**.

(29) The lid **120** may be removable as a whole unit or divided into removable lid sections, **120A**, **120B**, **120C**, **120D**, as shown in FIG. 3. The lid sections may be held to the conveyor **110** by releasable pins. The releasable pins are disposed through the conveyor frame, trusses **122**, or curvilinear structure **114**. The divided and removable lid sections provide access to the interior of the curvilinear structure. Removable lid sections aid in the maintenance and cleanout of the conveyor **110**. The removable lid sections may allow the operator or installer to optimize

adjustment and efficient placement of mixing baffles and ports. Access ports (not shown) may be disposed within the lid sections to allow the application of treatment material during conveyance, such as blending dry additives or mixing powdered, dry seed treatment with the seed flow. Dry additives may include biological inhibitors, particulate fertilizer, seed shiners, drying agents, talc, graphite, or other flowability agents and other seed treatments. Access ports may be covered with a transparent cover for observation. The access ports within the lid section may be of varied sizes and shapes. The conveyor may also include passive zones where mixing baffles or ports in the removable lid sections are not utilized.

(30) Since treatment absorbs or dries quickly with some seeds, such as wheat, mixing may need to occur further upstream prior to entering the tail inlet of the static mix conveyor. A transition zone **200** may be utilized at the tail end of the conveyor **110** as shown in FIGS. **3** and **4**. The transition zone is the portion of the conveyor where the belt transitions from a flat profile from the drive or idler roller, usually where loading of the conveyor happens, into the curvilinear portion where the belt conforms to the curvilinear portion. The transition zone may incorporate one or more mixing paddles **230** to induce mixing prior to inline static mixing within the conveyor **110**. As shown, two mixing paddles may be disposed within the transition zone. Placement of the mixing paddles **230** in the transition zone **200** allows for more aggressive mixing prior to mixing within the static mix conveyor. The mixing paddles partially obstruct the flow of seed, inducing a prescribed amount of backflow within the transition zone.

(31) The mixing paddles **230** may be mounted to a sidewall **154** of the transition zone as shown in FIG. **5**. The mixing paddles **230** are mounted perpendicular to the floor of the transition zone with a U-shaped mounting bracket **260**, as shown in FIG. **5**. A U-shaped mounting bracket **260** is attached to the sidewall **154** of the transition zone. The U-shaped mounting bracket and sidewall may comprise a plurality of apertures **163** corresponding to the mounting position of the mixing paddles. The mixing paddles are mounted to the sidewall **154** with a peripheral portion disposed upstream of a central portion. The first mixing paddle **230A** is mounted on the second lateral side **172** of the transition zone. The first mixing paddle **230A** is slanted relative to the longitudinal portion **111** of the transition zone **200** as shown in FIG. **3**. The slant of the mixing paddle directs lateral movement of the particulate material from the second lateral side **172** towards the first lateral side **170** within the transition zone **200** and partially determines how aggressive the mixing rate is. In addition, mounting a second mixing paddle **230B** on an opposite sidewall **154** and slanted relative to the longitudinal portion **111** of the transition zone directs lateral movement of the particulate material from the first lateral side **170** back towards the second lateral side **172** of the transition zone. The particulate material ricochets off an upstream surface **133** of each mixing paddle, bouncing particulate material backwards and towards an opposite sidewall **154** within the transition zone. In the situation where the particulate material is a quantity of a plant seed partially covered with a wet seed treatment, inducing backflow, and directing lateral movement within the transition zone spreads the wet seed treatment about the quantity of the plant seed sooner than can occur within the conveyor **110**. Alternatively, the mixing paddles **230** may be oriented 90-degrees to the previous position so they are on the same plane as the floor of the transition zone. Such orientation allows particulate material to flow over the mixing paddles in a cascading manner under the force of gravity.

(32) The mixing paddles **230** may be made of a rigid durable material such as ultra-high-molecular-weight polyethylene, acrylonitrile butadiene styrene, or steel. As shown in FIG. **6**, the mixing paddle **230** may comprise a first aperture **161** and a second aperture **162** for securing the mixing paddle to the U-shaped mounting bracket **260** or other mounting bracket. The mixing paddle **230** may comprise a central downward extending portion, a peripheral downward extending portion, and a lower portion that extends laterally in one or both lateral directions. In FIG. **6**, the mixing paddle does not comprise a passage, and the downward extending section, the central portion **132** and the peripheral portion **134** form a uniform mixing paddle. The lower portion **136** extends

laterally. The peripheral portion **134** and the lower portion **136** of the mixing paddle comprise an arc having a profile corresponding to the shape of the belt within the transition zone. The belt within the transition zone is not curved to the same extent as when the belt rides within the curvilinear structure **114** owing to the more planar cross section of the transition zone **200**. The lower portion **136** is disposed near the carrying surface of the belt to engage the bottom of the stream of particulate material. The laterally extending portion may be semi-circular, otherwise curvilinear, rectangular, or other shape to fit the confines of the transition zone to induce thorough mixing. The mixing paddles **230** may be a solid piece or have passage cutouts. The mixing paddle may have one or multiple passages to induce increased flowability of material through the transition zone. The size and angle of the mixing paddles may also be changed to induce transfer of particulate material. The mixing paddles can be mounted at less than a 50° angle as previously defined for example.

(33) There is a compromise between particulate material transfer rate and the amount of mixing—the more backflow and lateral movement is induced, the less downstream movement there is of the particulate material. The mixing baffles reduce the transfer rate by between 30%-70%, or between 40%-60%, or, in a preferred embodiment, approximately 50%. For example, in a conveyor having a transfer rate of 900 kilograms (approximately 2,000 pounds) per minute without mixing paddle, at 28° incline and with a belt speed of 110 meters per minute (approximately 350 feet per minute), the addition of mixing baffles may reduce the transfer capacity to 450 kilograms (approximately 1,000 pounds) per minute. In a larger conveyor having a transfer capacity of 1,800 kilograms (approximately 4,000 pounds) per minute, at 28° incline and with a belt speed of 110 meters per minute (approximately 350 feet per minute), the addition of mixing baffles may reduce the transfer capacity to 900 kilograms (2,000 pounds) per minute.

(34) To provide a thorough mixing while maintaining flow rates, a passage **138** can be provided in one or more of the mixing baffles **130** or mixing paddles **230**. A mixing baffle **130** is shown in FIG. 7 having a passage **138** disposed in a peripheral portion **134** of the mixing baffle. Alternatively, a mixing baffle **130** is shown in FIG. 8 having a passage **138** disposed in a central portion **132** of the mixing baffle to induce thorough mixing and material transfer. The lower portion **136** of the mixing baffle comprises an arc having a profile corresponding to the curvilinear structure **114**. The lower portion **136** of the mixing baffles and paddles are disposed near the carrying surface of the belt to engage the bottom of the stream of particulate material. In the example of a seed treatment system, the belt may incorporate texture projections on the carrying surface to assist with traction for carrying the load up an incline, such as raised chevrons that assist with carrying the load. The lower portion **136** of the mixing baffles and paddles are disposed at a predetermined distance from the raised chevrons. The bottom of the mixing baffles and paddles may be located above the raised chevrons by less than three average diameters of the particulate material, or less than five average diameters of the particulate material, or less than 10 average diameters of the particulate material. Alternatively, the bottom of the mixing baffles and paddles may be located above the raised chevrons by approximately 0.5 cm (approximately ¼ inch), 1 cm (approximately ⅜ inch), 2.5 cm (approximately 1 inch). Similarly, the arc of lower portion **136** of the mixing baffle follows the belt conformed to the curvilinear structure **114** around to the sidewall **154** at a similar spacing. Having a space in between the top of the belt texture and the bottom of the mixing baffles and paddles prevents seed damage from friction or pinching.

(35) As shown in FIG. 7, the mixing baffle **130** comprises a first aperture **161** and a second aperture **162** for securing the mixing baffle to a mounting bracket **160**. The mixing baffle also comprises a downward extending section. In FIG. 7, the downward extending section is the central portion **132**. The lower portion **136** extends laterally. Alternatively, as shown in FIG. 8 the downward extending section is the peripheral portion **134**. In both FIGS. 7 and FIG. 8, the mixing baffle **130** has a downward extending portion and a lateral extending portion. The passage **138** may be semi-circular, otherwise curvilinear, rectangular, or other aperture shape to allow a top portion of the

seed stream to flow over the lower portion **136**. The mixing baffle **130** shown in FIGS. 7 and 8 having a semi-circular passage **138** induces thorough mixing and material transfer. In FIG. 9, there is no passage disposed in the mixing baffle **130**. Alternatively, the mixing baffle **130** may have a central downward extending portion and have a lower portion that extends laterally in one or both lateral directions. The mixing baffle **130** may have one or multiple passages therethrough.

(36) The mixing baffles **130** and mixing paddles **230** may have a tapered or beveled edge. The peripheral portion **134** and the lower portion **136** of the mixing baffles and paddles may be tapered or beveled. The passage **138** of the mixing baffles or paddles may also be tapered or beveled individually, or in combination with the peripheral portion **134** and the lower portion **136**. The tapered or beveled edges of the mixing baffles and paddles may be angular or rounded. The rounded edge makes for a smoother surface for seed to slide over during material transfer. The angular edge may be 90 degrees or canted to less than a 90-degree angle.

(37) The mixing baffle **130** can be statically mounted to the lid **120**, the conveyor frame (not shown), or the curvilinear structure **114**. The statically mounted mixing baffle can be bolted or welded within the curvilinear structure, or otherwise securely mounted within the curvilinear structure. Alternatively, the mixing baffles and paddles can be adjustably mounted, where the mixing baffles and paddles can be selectively deployed. An acme screw, spring, pneumatic device, or hydraulic actuator may be used in adjusting the pitch of the mixing baffles within the curvilinear structure. The mixing baffle **130** can be mounted to a hinge bracket. The hinge bracket may comprise an actuator, spring, acme screw or other deploying mechanism. In this way, the mixing baffle can be selectively deployed to enable the conveyor to have a transfer-speed-maximizing mode and a mixing mode. The hinge bracket may be limited at an angle less than or equal to 90 degrees.

(38) The conveyor **110** may apply continuous static mixing, drying, or conditioning of seed in multiple stages. An advantage of staging mixing and drying conveyors between seed treatment applicators allows employment of multiple seed treatments between stages of conditioning. The static mixing of seed in multiple stages within static mix conveyors allows for additional mixing, drying, and conditioning time for seed treatments requiring longer durations. Alternative treatments may be utilized with mixing and drying conveyors having a plurality of removable lid sections and ports. Alternative treatments may include introducing dry additives, blending powdered, dry seed treatment, or a combination thereof. As shown in FIG. 10, a seed package (not shown) is deposited into a hopper **300** allowing the seed to flow through a seed flow control meter, such as a loss-in-weight seed flow control solution utilizing a variable position gate sold by KSi Conveyor, Inc., Sabetha, Kansas as the KSi® VariRate® loss-in-weight seed meter or a volumetric seed wheel (for example, the disclosure of U.S. patent application Ser. No. 12/848,412 by Reineccius). The metered seed flow then enters a first seed treatment applicator **320**. The first seed treatment applicator applies a first treatment to the seed flow. According to a recipe, the first seed treatment applicator applies a predetermined amount of the first treatment based on the metered seed flow rate. The seed flow having a first treatment enters a transition zone **200A** of a first conveyor **110A**, where mixing baffles may mix the freshly treated seed as described above.

(39) The first conveyor **110A** transports the seed flow towards a second seed treatment applicator **330**. After mixing of the first application of seed treatment within the first conveyor **110A**, the first static mix conveyor deposits the metered seed flow into the second applicator for a second treatment. A second metering step is not needed, because the flow of seed through the first applicator and through the first conveyor maintains the seed flow rate. Maintaining the metered seed flow through the first applicator, the first conveyor, and the second applicator may provide an advantage for overtreating because the seed moves continually through the system, without the need to collect the treated seed in a bag, box, or hopper, where the seed must be re-metered.

(40) The second seed treatment applicator **330** applies the second treatment to the metered seed flow. The seed flow treated with a second treatment then enters a transition zone **200B** of a second

conveyor **110B**, where mixing can begin as described above. After conditioning within the second static mix conveyor, the seed flow may be collected into a package (box, bag, etc.) or dispensed into a customer transport container (such as a trailer, wagon, planter, etc.). Additional seed treatment may be realized by including additional stages of treatment and mixing with a similar arrangement or even repeat prior treatments. Treatment of seed in multiple stages allows for consecutive coatings or layers of treatment around the seed. Treatments may comprise a fungicide, insecticide, fertilizer, mineral additives, inhibitors, bacteria, microbial, or stimulators. When seed treatment is performed in multiple stages, we discovered there is better process control. Metering the seed flow at the start of the process, the remaining steps can maintain a seed flow rate of around 360 kilograms (approximately 800 pounds) per minute through multiple conveyors and seed treatment applicators, without a need for a subsequent metering step.

(41) The conveyor **110** may be made operably connected to a pressurized gas source to induce positive pressure within the conveyor atmosphere. As shown in FIGS. **10** and **12**, the conveyor **110** may comprise a conditioning apparatus **400** having a plurality of ports made operably connected to a gas manifold **408**. As particulate material passes through the conveyor, the conditioning apparatus effectuates drying and conditioning of the stream of particulate material. The gas manifold may be made operable by at least one inlet port **402** disposed through the curvilinear structure **114** or lid **120**. The inlet port **402** may introduce conditioned air at any point along the longitudinal portion **111** of the conveyor **110**. Conditioned air assists in the cooling and drying of the wet, freshly treated seed during conveyance by the belt within the conveyor. Conditioned air may come from any conditioning source such as an air conditioner or dehumidifier. Alternatively, the conditioned air may be introduced into the conveyor **110** through a plurality of lines connected to multiple ports disposed within the curvilinear structure **114** or lid **120**. The gas manifold **408** may be made from any hose type or material such as metal pipe, formed hard plastic, and other durable materials having an inner flowable passage. The gas manifold may include a plurality of conditioning outlets **410** disposed through the wall of the gas manifold. The gas manifold containing conditioning outlets introduces conditioned air to specific areas within the seed flow. The conditioning outlets may be made from any hose type or material such as metal pipe, formed hard plastic, and other durable materials having an inner flowable passage. The gas manifold **408** may be disposed within the curvilinear structure **114** of the conveyor **110**. The gas manifold may be placed above or below the movable belt. The gas manifold **408** may follow a path within the curvilinear structure **114** congruent with the passages disposed in the mixing baffles **130**. Alternatively, the gas manifold may contain a plurality of conditioning sections at less than a 50° angle (see angle β in FIG. **12**) between a first plane **450** defined by a conditioning section **409** and a vertical plane **452** tangential to the longitudinal portion **111** of the conveyor **110** at the sidewall **154**. In the situation where the particulate material is a quantity of a seed covered with a wet seed treatment, a conditioning outlet **410** may be positioned within the seed flow at a point laterally adjacent to a mixing baffle **130**. The conditioning outlets, as shown in FIG. **13** and FIG. **15**, may direct pressurized gas in a downstream direction (arrow **113**), upstream direction, or a lateral direction for drying wet seed treatment about the quantity of the plant seed as well as directing longitudinal movement of the seed flow.

(42) Alternatively, the conditioned air may be introduced into the conveyor **110** via a gas manifold **408** disposed outside the curvilinear structure **114** or mounted on an exterior portion of the conveyor **110** as shown in FIG. **14**. The gas manifold may include a plurality of conditioning outlets **410** disposed through the lid **120** of the conveyor **110**. As shown in FIGS. **14** and **15**, the conditioning outlets **410** may direct pressurized gas in a perpendicular plane to the downstream direction (arrow **113**) flow of particulate material. Alternatively, the conditioning outlets **410** may be positioned directly within or below the seed flow to introduce conditioned air to specific areas around or within the seed flow, such as directly downstream of a mixing baffle. In the situation where particulate material is a quantity of a seed covered with a wet seed treatment, a conditioning outlet **410** may be positioned at a point where seed flow experiences greatest turbulence from

backflow induced by the mixing baffles **130**.

(43) In another function, the plurality of conditioning outlets **410** may effectuate extraction by forming a vacuum when the inlet port **402** is operably connected with a vacuum source. The applied vacuum within the gas manifold **408** effectuates air currents within the conveyor **110** to entrain and extract lighter particles such as debris, chaff, dust, humidity, or excess treatment. Alternatively, conditioned air may be introduced in combination with extraction. In one example, as depicted in FIGS. **14** and **15**, extraction is applied to a first inlet port **402A** connected to a first gas manifold **408A**, while conditioning is applied to a second inlet port **402B** connected to a second gas manifold **408B**. The combination induces positive flow of conditioned air through the seed flow while vacuuming draws the lighter, entrained particles out of the seed flow. The conditioning outlets serving as extraction ports may be screened to prevent particulate material from entering the conditioning outlets.

(44) It is understood that the invention is not confined to the particular construction and arrangement of parts herein described. That although the drawings and specification set forth a preferred embodiment, and although specific terms are employed, they are used in a description sense only and embody all such forms as come within the scope of the following claims.

(45) In the Summary above, the Detailed Description, and in the accompanying drawings, reference is made to particular features including method steps of the invention. The reader should understand that the disclosure of the invention in this specification includes all possible combinations of such particular features. For example, where a particular feature is disclosed in the context of a particular aspect or embodiment of the invention, or a particular claim, that feature can also be used, to the extent possible, in combination with and/or in the context of other particular aspects and embodiments of the invention, and in the invention generally. It is understood that the invention is not confined to the particular construction and arrangement of parts herein described. That although the drawings and specification set forth a preferred embodiment, and although specific terms are employed, they are used in a description sense only and embody all such forms as come within the scope of the following claims.

(46) The term “comprises”, and its grammatical equivalents are used in this document to mean that other components, steps, etc. are optionally present. For example, an article “comprising” or “which comprises” components A, B, and C can consist of components A, B, and C, or can contain not only components A, B, and C but also one or more other components.

Claims

1. A method comprising the steps of: a. providing a metered stream of seed to a first applicator; b. treating the metered stream of seed with a first treatment; c. transferring the metered stream of seed having the first treatment to a second applicator; d. treating the metered stream of seed having the first treatment with a second treatment; and e. maintaining the metered stream of seed at a metered flow rate between the first applicator and the second applicator.
2. The method of claim 1, further comprising the step of: a. mixing the metered stream of seed having the first treatment within a first conveyor with a plurality of static mixing baffles.
3. The method of claim 2, further comprising the step of: a. drying the metered stream of seed having the first treatment in the first conveyor by providing pressurized gas within the first conveyor.
4. The method of claim 3, further comprising the steps of: a. mixing the metered stream of seed having the second treatment in a second conveyor with a plurality of mixing baffles; and b. drying the metered stream of seed having the second treatment in the second conveyor by providing pressurized gas to the second conveyor.
5. A method comprising the steps of: a. providing a seed flow, having a first wet treatment, at a metered seed flow rate; and b. applying a second wet treatment on the seed flow based on the

metered seed flow rate further comprising the step of: c. maintaining the seed flow at the metered seed flow rate between the first liquid applicator and the second liquid applicator.

6. The method of claim 5, further comprising the step of: a. mixing the seed flow at the metered seed flow rate within an incline conveyor having a plurality of static mixing baffles.

7. The method of claim 5, further comprising the step of: a. transferring the seed flow, having the first wet treatment, from a first liquid applicator to a second liquid applicator.

8. The method of claim 7, wherein the seed flow is transferred from the first liquid applicator to the second liquid applicator by an incline conveyor.

9. The method of claim 5, further comprising the step of: a. spraying the first wet treatment on the seed flow according to a recipe based on the metered seed flow rate.

10. The method of claim 5, wherein the first wet treatment is applied to the seed flow within a first treatment applicator and the second wet treatment is applied to the seed flow within a second treatment applicator.

11. The method of claim 10, further comprising the step of: a. maintaining the seed flow at the metered seed flow rate through an incline conveyor disposed between the first treatment applicator and the second treatment applicator.

12. A method comprising the steps of: a. metering a stream of treated seed; b. maintaining the metered stream of treated seed through an incline conveyor; c. delivering the metered stream of treated seed to a seed treatment applicator; and d. treating the metered stream of treated seed with a second treatment fluid with the seed treatment applicator.

13. The method of claim 12, further comprising the step of: a. drying the metered stream of treated seed within the incline conveyor.

14. The method of claim 13, further comprising the step of: a. introducing a pressurized gas into the incline conveyor.

15. The method of claim 12, further comprising the step of: a. mixing and drying the metered stream of treated seed within the incline conveyor.

16. The method of claim 12, further comprising the step of: a. transferring the metered stream of treated seed from the incline conveyor to the seed treatment applicator.

17. A method comprising the steps of: a. applying a first liquid treatment to a seed flow based on a metered seed flow rate; b. mixing the seed flow while maintaining the metered seed flow rate; and c. drying the seed flow while maintaining the metered seed flow rate further comprising the steps of: d. transferring the seed flow from a first applicator with an incline conveyor; and e. maintaining the metered seed flow rate through the first applicator and the incline conveyor; further comprising the step of: f. applying a second liquid treatment to the seed flow based on the metered seed flow rate from the incline conveyor into a second applicator.
