

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12402805
B2
September 02, 2025
Hacking; S. Adam et al.

Wearable device for coupling to a user, and measuring and monitoring user activity

Abstract

A system for measuring an angle of a joint of a user includes a center hub, a first arm, a second arm, a magnet, and a sensor. The center hub includes a first hub and a second hub. The first arm is configured for attachment to a first limb portion of the user at a first outer end and to the first hub at a first inner end. The second arm is configured for attachment to a second limb portion of the user at a second outer end and to the second hub at a second inner end, wherein the first hub is pivotally coupled to the second hub. The magnet is coupled to the second hub. The sensor is disposed in the center hub and configured to detect a rotation of the magnet.

Inventors: Hacking; S. Adam (Nashua, NH), Tamragouri; Sucheta (Nashua, NH), Cote; Jeff (Raymond, NH), Lipszyc; Daniel (Glasgow, MT), Taveras; Mikael (Boston, MA)

Applicant: ROM TECHNOLOGIES, INC. (Brookfield, CT)

Family ID: 74869141

Assignee: ROM Technologies, Inc. (Brookfield, CT)

Appl. No.: 17/974043

Filed: October 26, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230051751 A1	Feb. 16, 2023

Related U.S. Application Data

division parent-doc US 17017062 20200910 PENDING child-doc US 17974043
us-provisional-application US 62991295 20200318
us-provisional-application US 62911515 20191007

Publication Classification

Int. Cl.: **A61B5/107** (20060101); **A61B5/00** (20060101); **A61B5/11** (20060101)

U.S. Cl.:

CPC **A61B5/1071** (20130101); **A61B5/1121** (20130101); **A61B5/6801** (20130101);
A61B2562/166 (20130101)

Field of Classification Search

CPC: A61B (5/1071); A61B (5/1121); A61B (5/6801); A61B (5/4528); A61B (5/742); A61B
(5/6842); A61B (5/6828); A61B (5/6833); A61B (2562/166); A61B (2562/0223); A61B
(2562/164); A61B (2505/09); A61B (2560/0223)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
823712	12/1905	Uhlmann	N/A	N/A
4499900	12/1984	Petrofsky et al.	N/A	N/A
4822032	12/1988	Whitmore et al.	N/A	N/A
4860763	12/1988	Schminke	N/A	N/A
4869497	12/1988	Stewart et al.	N/A	N/A
4932650	12/1989	Bingham et al.	N/A	N/A
5137501	12/1991	Mertesdorf	N/A	N/A
5161430	12/1991	Febey	N/A	N/A
5202794	12/1992	Schnee et al.	N/A	N/A
5240417	12/1992	Smithson et al.	N/A	N/A
5247853	12/1992	Dalebout	N/A	N/A
5256117	12/1992	Potts et al.	N/A	N/A
D342299	12/1992	Birrell et al.	N/A	N/A
5282748	12/1993	Little	N/A	N/A
5284131	12/1993	Gray	N/A	N/A
5316532	12/1993	Butler	N/A	N/A
5318487	12/1993	Golen	N/A	N/A
5324241	12/1993	Artigues et al.	N/A	N/A
5336147	12/1993	Sweeney, III	N/A	N/A
5338272	12/1993	Sweeney, III	N/A	N/A
5356356	12/1993	Hildebrandt	N/A	N/A
5361649	12/1993	Slocum, Jr.	N/A	N/A
D359777	12/1994	Hildebrandt	N/A	N/A
5429140	12/1994	Burdea et al.	N/A	N/A
5458022	12/1994	Mattfeld et al.	N/A	N/A
5487713	12/1995	Butler	N/A	N/A

5566589	12/1995	Buck	N/A	N/A
5580338	12/1995	Scelta et al.	N/A	N/A
5676349	12/1996	Wilson	N/A	N/A
5685804	12/1996	Whan-Tong et al.	N/A	N/A
5738636	12/1997	Saringer et al.	N/A	N/A
5860941	12/1998	Saringer et al.	N/A	N/A
5950813	12/1998	Hoskins et al.	N/A	N/A
6007459	12/1998	Burgess	N/A	N/A
D421075	12/1999	Hildebrandt	N/A	N/A
6053847	12/1999	Stearns et al.	N/A	N/A
6077201	12/1999	Cheng	N/A	N/A
6102834	12/1999	Chen	N/A	N/A
6110130	12/1999	Kramer	N/A	N/A
6155958	12/1999	Goldberg	N/A	N/A
6162189	12/1999	Girone et al.	N/A	N/A
6182029	12/2000	Friedman	N/A	N/A
D438580	12/2000	Shaw	N/A	N/A
6253638	12/2000	Bermudez	N/A	N/A
6267735	12/2000	Blanchard et al.	N/A	N/A
6273863	12/2000	Avni et al.	N/A	N/A
D450100	12/2000	Hsu	N/A	N/A
D450101	12/2000	Hsu	N/A	N/A
D451972	12/2000	Easley	N/A	N/A
D452285	12/2000	Easley	N/A	N/A
D454605	12/2001	Lee	N/A	N/A
6371891	12/2001	Speas	N/A	N/A
D459776	12/2001	Lee	N/A	N/A
6413190	12/2001	Wood et al.	N/A	N/A
6430436	12/2001	Richter	N/A	N/A
6436058	12/2001	Krahner et al.	N/A	N/A
6450923	12/2001	Vatti	N/A	N/A
6474193	12/2001	Farney	N/A	N/A
6491649	12/2001	Ombrellaro	N/A	N/A
6514085	12/2002	Slattery et al.	N/A	N/A
6535861	12/2002	OConnor et al.	N/A	N/A
6543309	12/2002	Heim	N/A	N/A
6589139	12/2002	Butterworth	N/A	N/A
6601016	12/2002	Brown et al.	N/A	N/A
6602191	12/2002	Quy	N/A	N/A
6613000	12/2002	Reinkensmeyer et al.	N/A	N/A
6626800	12/2002	Casler	N/A	N/A
6626805	12/2002	Lightbody	N/A	N/A
6640122	12/2002	Manoli	607/139	A61B 5/6804
6640662	12/2002	Baxter	N/A	N/A
6652425	12/2002	Martin et al.	N/A	N/A
6820517	12/2003	Farney	N/A	N/A
6865969	12/2004	Stevens	N/A	N/A
6890312	12/2004	Priester et al.	N/A	N/A
6895834	12/2004	Baatz	N/A	N/A

6902513	12/2004	McClure	N/A	N/A
7058453	12/2005	Nelson et al.	N/A	N/A
7063643	12/2005	Arai	N/A	N/A
7156665	12/2006	OConnor et al.	N/A	N/A
7156780	12/2006	Fuchs et al.	N/A	N/A
7169085	12/2006	Killin et al.	N/A	N/A
7204788	12/2006	Andrews	N/A	N/A
7209886	12/2006	Kimmel	N/A	N/A
7226394	12/2006	Johnson	N/A	N/A
RE39904	12/2006	Lee	N/A	N/A
7406003	12/2007	Burkhardt et al.	N/A	N/A
7507188	12/2008	Nurre	N/A	N/A
7594879	12/2008	Johnson	N/A	N/A
7628730	12/2008	Watterson et al.	N/A	N/A
D610635	12/2009	Hildebrandt	N/A	N/A
7778851	12/2009	Schoenberg et al.	N/A	N/A
7809601	12/2009	Shaya et al.	N/A	N/A
7815551	12/2009	Merli	N/A	N/A
7833135	12/2009	Radow et al.	N/A	N/A
7837472	12/2009	Elsmore et al.	N/A	N/A
7890342	12/2010	Yruko	N/A	N/A
7955219	12/2010	Birrell et al.	N/A	N/A
7969315	12/2010	Ross et al.	N/A	N/A
7988599	12/2010	Ainsworth et al.	N/A	N/A
8012107	12/2010	Einav et al.	N/A	N/A
8021270	12/2010	D'Eredita	N/A	N/A
8038578	12/2010	Olrik et al.	N/A	N/A
8079937	12/2010	Bedell	N/A	N/A
8113991	12/2011	Kutliroff	N/A	N/A
8172724	12/2011	Solomon	N/A	N/A
8177732	12/2011	Einav et al.	N/A	N/A
8287434	12/2011	Zavadsky et al.	N/A	N/A
8298123	12/2011	Hickman	N/A	N/A
8371990	12/2012	Shea	N/A	N/A
8419593	12/2012	Ainsworth et al.	N/A	N/A
8465398	12/2012	Lee et al.	N/A	N/A
8503086	12/2012	French	N/A	N/A
8506458	12/2012	Dugan	N/A	N/A
8515777	12/2012	Rajasenan	N/A	N/A
8540515	12/2012	Williams et al.	N/A	N/A
8540516	12/2012	Williams et al.	N/A	N/A
8556778	12/2012	Dugan	N/A	N/A
8607465	12/2012	Edwards	33/471	G01B 3/56
8613689	12/2012	Dyer et al.	N/A	N/A
8615529	12/2012	Reiner	N/A	N/A
8672812	12/2013	Dugan	N/A	N/A
8751264	12/2013	Beraja et al.	N/A	N/A
8784273	12/2013	Dugan	N/A	N/A
8818496	12/2013	Dziubinski et al.	N/A	N/A
8823448	12/2013	Shen	N/A	N/A

8845493	12/2013	Watterson et al.	N/A	N/A
8849681	12/2013	Hargrove et al.	N/A	N/A
8864628	12/2013	Boyette et al.	N/A	N/A
8893287	12/2013	Gjonej et al.	N/A	N/A
8911327	12/2013	Boyette	N/A	N/A
8979711	12/2014	Dugan	N/A	N/A
9004598	12/2014	Weber	N/A	N/A
9044630	12/2014	Lampert et al.	N/A	N/A
9167281	12/2014	Petrov et al.	N/A	N/A
D744050	12/2014	Colburn	N/A	N/A
9248071	12/2015	Brenda	N/A	N/A
9256711	12/2015	Horseman	N/A	N/A
9272091	12/2015	Skelton	N/A	N/A
9272185	12/2015	Dugan	N/A	N/A
9283434	12/2015	Wu	N/A	N/A
9295878	12/2015	Corbalis et al.	N/A	N/A
9311789	12/2015	Gwin	N/A	N/A
9312907	12/2015	Auchinleck et al.	N/A	N/A
9367668	12/2015	Flynt et al.	N/A	N/A
9409054	12/2015	Dugan	N/A	N/A
9443205	12/2015	Wall	N/A	N/A
9474935	12/2015	Abbondanza et al.	N/A	N/A
9480873	12/2015	Chuang	N/A	N/A
9481428	12/2015	Gros	N/A	N/A
9514277	12/2015	Hassing et al.	N/A	N/A
9566472	12/2016	Dugan	N/A	N/A
9579056	12/2016	Rosenbek et al.	N/A	N/A
9629558	12/2016	Yuen et al.	N/A	N/A
9640057	12/2016	Ross	N/A	N/A
9707147	12/2016	Levital et al.	N/A	N/A
9713744	12/2016	Suzuki	N/A	N/A
D794142	12/2016	Zhou	N/A	N/A
9717947	12/2016	Lin	N/A	N/A
9737761	12/2016	Govindarajan	N/A	N/A
9757612	12/2016	Weber	N/A	N/A
9773330	12/2016	Douglas	N/A	N/A
9782621	12/2016	Chiang et al.	N/A	N/A
9802076	12/2016	Murray et al.	N/A	N/A
9802081	12/2016	Ridgel et al.	N/A	N/A
9813239	12/2016	Chee et al.	N/A	N/A
9827445	12/2016	Marcos et al.	N/A	N/A
9849337	12/2016	Roman et al.	N/A	N/A
9868028	12/2017	Shin	N/A	N/A
9872087	12/2017	DelloStritto et al.	N/A	N/A
9872637	12/2017	Kording et al.	N/A	N/A
9914053	12/2017	Dugan	N/A	N/A
9919198	12/2017	Romeo et al.	N/A	N/A
9937382	12/2017	Dugan	N/A	N/A
9939784	12/2017	Berardinelli	N/A	N/A
9974478	12/2017	Brokaw	N/A	N/A

9977587	12/2017	Mountain	N/A	N/A
9993181	12/2017	Ross	N/A	N/A
9997082	12/2017	Kaleal	N/A	N/A
10004946	12/2017	Ross	N/A	N/A
10026052	12/2017	Brown et al.	N/A	N/A
D826349	12/2017	Oblamski	N/A	N/A
10055550	12/2017	Goetz	N/A	N/A
10058473	12/2017	Oshima et al.	N/A	N/A
10074148	12/2017	Cashman et al.	N/A	N/A
10089443	12/2017	Miller et al.	N/A	N/A
10111643	12/2017	Shulhauser et al.	N/A	N/A
10130311	12/2017	De Sapio et al.	N/A	N/A
10137328	12/2017	Baudhuin	N/A	N/A
10143395	12/2017	Chakravarthy et al.	N/A	N/A
10155134	12/2017	Dugan	N/A	N/A
10159872	12/2017	Sasaki et al.	N/A	N/A
10173094	12/2018	Gomberg et al.	N/A	N/A
10173095	12/2018	Gomberg et al.	N/A	N/A
10173096	12/2018	Gomberg et al.	N/A	N/A
10173097	12/2018	Gomberg et al.	N/A	N/A
10198928	12/2018	Ross et al.	N/A	N/A
10226663	12/2018	Gomberg et al.	N/A	N/A
10231664	12/2018	Ganesh	N/A	N/A
10244990	12/2018	Hu et al.	N/A	N/A
10258823	12/2018	Cole	N/A	N/A
10322315	12/2018	Foley et al.	N/A	N/A
10325070	12/2018	Beale et al.	N/A	N/A
10327697	12/2018	Stein et al.	N/A	N/A
10362940	12/2018	Tran	N/A	N/A
10369021	12/2018	Zoss et al.	N/A	N/A
10380866	12/2018	Ross et al.	N/A	N/A
10413222	12/2018	Kayyali	N/A	N/A
10413238	12/2018	Cooper	N/A	N/A
10424033	12/2018	Romeo	N/A	N/A
10430552	12/2018	Mihai	N/A	N/A
D866957	12/2018	Ross et al.	N/A	N/A
10468131	12/2018	Macoviak et al.	N/A	N/A
10475323	12/2018	Ross	N/A	N/A
10475537	12/2018	Purdie et al.	N/A	N/A
10492977	12/2018	Kapure et al.	N/A	N/A
10507358	12/2018	Kinnunen et al.	N/A	N/A
10542914	12/2019	Forth et al.	N/A	N/A
10546467	12/2019	Luciano, Jr. et al.	N/A	N/A
10569122	12/2019	Johnson	N/A	N/A
10572626	12/2019	Balram	N/A	N/A
10576331	12/2019	Kuo	N/A	N/A
10581896	12/2019	Nachenberg	N/A	N/A
10625114	12/2019	Ercanbrack	N/A	N/A
10646746	12/2019	Gomberg et al.	N/A	N/A
10660534	12/2019	Lee et al.	N/A	N/A

10678890	12/2019	Bitran et al.	N/A	N/A
10685092	12/2019	Paparella et al.	N/A	N/A
10741285	12/2019	Moturu	N/A	N/A
10777200	12/2019	Will et al.	N/A	N/A
10786181	12/2019	Echols	N/A	A61B 5/1122
D899605	12/2019	Ross et al.	N/A	N/A
10792495	12/2019	Izvorski et al.	N/A	N/A
10814170	12/2019	Wang et al.	N/A	N/A
10857426	12/2019	Neumann	N/A	N/A
10867695	12/2019	Neagle	N/A	N/A
10874905	12/2019	Belson et al.	N/A	N/A
D907143	12/2020	Ach et al.	N/A	N/A
10881911	12/2020	Kwon et al.	N/A	N/A
10918332	12/2020	Belson et al.	N/A	N/A
10931643	12/2020	Neumann	N/A	N/A
10987176	12/2020	Poltaretskyi et al.	N/A	N/A
10991463	12/2020	Kutzko et al.	N/A	N/A
11000735	12/2020	Orady et al.	N/A	N/A
11045709	12/2020	Putnam	N/A	N/A
11065170	12/2020	Yang et al.	N/A	N/A
11065527	12/2020	Putnam	N/A	N/A
11069436	12/2020	Mason et al.	N/A	N/A
11071597	12/2020	Posnack et al.	N/A	N/A
11075000	12/2020	Mason et al.	N/A	N/A
D928635	12/2020	Hacking et al.	N/A	N/A
11087865	12/2020	Mason et al.	N/A	N/A
11094400	12/2020	Riley et al.	N/A	N/A
11101028	12/2020	Mason et al.	N/A	N/A
11107591	12/2020	Mason	N/A	N/A
11139060	12/2020	Mason et al.	N/A	N/A
11185735	12/2020	Arn et al.	N/A	N/A
11185738	12/2020	McKirdy et al.	N/A	N/A
D939096	12/2020	Lee	N/A	N/A
D939644	12/2020	Ach et al.	N/A	N/A
D940797	12/2021	Ach et al.	N/A	N/A
D940891	12/2021	Lee	N/A	N/A
11229727	12/2021	Tatonetti	N/A	N/A
11229788	12/2021	John	N/A	N/A
11265234	12/2021	Guaneri et al.	N/A	N/A
11270795	12/2021	Mason et al.	N/A	N/A
11272879	12/2021	Wiedenhoefer et al.	N/A	N/A
11278766	12/2021	Lee	N/A	N/A
11282599	12/2021	Mason et al.	N/A	N/A
11282604	12/2021	Mason et al.	N/A	N/A
11282608	12/2021	Mason et al.	N/A	N/A
11284797	12/2021	Mason et al.	N/A	N/A
D948639	12/2021	Ach et al.	N/A	N/A
11295848	12/2021	Mason et al.	N/A	N/A
11298284	12/2021	Bayerlein	N/A	N/A

11309085	12/2021	Mason et al.	N/A	N/A
11317975	12/2021	Mason et al.	N/A	N/A
11325005	12/2021	Mason et al.	N/A	N/A
11328807	12/2021	Mason et al.	N/A	N/A
11337648	12/2021	Mason	N/A	N/A
11347829	12/2021	Sclar et al.	N/A	N/A
11348683	12/2021	Guaneri et al.	N/A	N/A
11370328	12/2021	Main	N/A	N/A
11376470	12/2021	Weldemariam	N/A	N/A
11404150	12/2021	Guaneri et al.	N/A	N/A
11410768	12/2021	Mason et al.	N/A	N/A
11422841	12/2021	Jeong	N/A	N/A
11437137	12/2021	Harris	N/A	N/A
11495355	12/2021	McNutt et al.	N/A	N/A
11508258	12/2021	Nakashima et al.	N/A	N/A
11508482	12/2021	Mason et al.	N/A	N/A
11515021	12/2021	Mason	N/A	N/A
11515028	12/2021	Mason	N/A	N/A
11524210	12/2021	Kim et al.	N/A	N/A
11527326	12/2021	McNair et al.	N/A	N/A
11532402	12/2021	Farley et al.	N/A	N/A
11534654	12/2021	Silcock et al.	N/A	N/A
D976339	12/2022	Li	N/A	N/A
11541274	12/2022	Hacking	N/A	N/A
11553969	12/2022	Lang et al.	N/A	N/A
11621067	12/2022	Nolan	N/A	N/A
11636944	12/2022	Hanrahan et al.	N/A	N/A
11654327	12/2022	Phillips et al.	N/A	N/A
11663673	12/2022	Pyles	N/A	N/A
11673024	12/2022	Omid-Zohoor	N/A	N/A
11701548	12/2022	Posnack et al.	N/A	N/A
11776676	12/2022	Savolainen	N/A	N/A
11944579	12/2023	Sankai	N/A	N/A
11957960	12/2023	Bissonnette et al.	N/A	N/A
12004871	12/2023	Fazeli	N/A	N/A
12057210	12/2023	Akinola et al.	N/A	N/A
12205704	12/2024	Hosoi et al.	N/A	N/A
2001/0044573	12/2000	Manoli	N/A	N/A
2002/0010596	12/2001	Matory	N/A	N/A
2002/0072452	12/2001	Torkelson	N/A	N/A
2002/0143279	12/2001	Porier	602/5	A61B 5/1071
2002/0160883	12/2001	Dugan	N/A	N/A
2002/0183599	12/2001	Castellanos	N/A	N/A
2003/0013072	12/2002	Thomas	N/A	N/A
2003/0036683	12/2002	Kehr et al.	N/A	N/A
2003/0064860	12/2002	Yamashita et al.	N/A	N/A
2003/0064863	12/2002	Chen	N/A	N/A
2003/0083596	12/2002	Kramer	600/595	A61B 5/1071

2003/0092536	12/2002	Romanelli et al.	N/A	N/A
2003/0181832	12/2002	Carnahan et al.	N/A	N/A
2004/0072652	12/2003	Alessandri et al.	N/A	N/A
2004/0102931	12/2003	Ellis et al.	N/A	N/A
2004/0106502	12/2003	Sher	N/A	N/A
2004/0147969	12/2003	Mann et al.	N/A	N/A
2004/0172093	12/2003	Rummerfield	N/A	N/A
2004/0194572	12/2003	Kim	N/A	N/A
2004/0197727	12/2003	Sachdeva et al.	N/A	N/A
2004/0204959	12/2003	Moreano et al.	N/A	N/A
2005/0015118	12/2004	Davis et al.	N/A	N/A
2005/0020411	12/2004	Andrews	N/A	N/A
2005/0043153	12/2004	Krietzman	N/A	N/A
2005/0049122	12/2004	Vallone et al.	N/A	N/A
2005/0085346	12/2004	Johnson	N/A	N/A
2005/0085353	12/2004	Johnson	N/A	N/A
2005/0115561	12/2004	Stahmann	N/A	N/A
2005/0143641	12/2004	Tashiro	N/A	N/A
2005/0274220	12/2004	Reboullet	N/A	N/A
2006/0003871	12/2005	Houghton et al.	N/A	N/A
2006/0046905	12/2005	Doody et al.	N/A	N/A
2006/0058648	12/2005	Meier	N/A	N/A
2006/0064136	12/2005	Wang	N/A	N/A
2006/0064329	12/2005	Abolfathi et al.	N/A	N/A
2006/0129432	12/2005	Choi et al.	N/A	N/A
2006/0199700	12/2005	LaStayo et al.	N/A	N/A
2006/0247095	12/2005	Rummerfield	N/A	N/A
2006/0277074	12/2005	Einav	N/A	N/A
2007/0042868	12/2006	Fisher et al.	N/A	N/A
2007/0118389	12/2006	Shipon	N/A	N/A
2007/0137307	12/2006	Gruben et al.	N/A	N/A
2007/0173392	12/2006	Stanford	N/A	N/A
2007/0184414	12/2006	Perez	N/A	N/A
2007/0194939	12/2006	Alvarez et al.	N/A	N/A
2007/0219059	12/2006	Schwartz	N/A	N/A
2007/0271065	12/2006	Gupta et al.	N/A	N/A
2007/0287597	12/2006	Cameron	N/A	N/A
2008/0021834	12/2007	Holla et al.	N/A	N/A
2008/0077619	12/2007	Gilley et al.	N/A	N/A
2008/0082356	12/2007	Friedlander et al.	N/A	N/A
2008/0096726	12/2007	Riley et al.	N/A	N/A
2008/0153592	12/2007	James-Herbert	N/A	N/A
2008/0161166	12/2007	Lo	N/A	N/A
2008/0161733	12/2007	Einav et al.	N/A	N/A
2008/0183500	12/2007	Banigan	N/A	N/A
2008/0281633	12/2007	Burdea et al.	N/A	N/A
2008/0300914	12/2007	Karkanias et al.	N/A	N/A
2008/0312040	12/2007	Ochi	N/A	N/A
2009/0011907	12/2008	Radow et al.	N/A	N/A
2009/0037334	12/2008	Hsu	N/A	N/A

2009/0058635	12/2008	LaLonde et al.	N/A	N/A
2009/0070138	12/2008	Langheier et al.	N/A	N/A
2009/0157617	12/2008	Herlocker	N/A	N/A
2009/0211395	12/2008	Mule	N/A	N/A
2009/0270227	12/2008	Ashby et al.	N/A	N/A
2009/0287503	12/2008	Angell et al.	N/A	N/A
2009/0299766	12/2008	Friedlander et al.	N/A	N/A
2010/0048358	12/2009	Tchao et al.	N/A	N/A
2010/0062818	12/2009	Haughay, Jr.	N/A	N/A
2010/0076786	12/2009	Dalton et al.	N/A	N/A
2010/0121160	12/2009	Stark et al.	N/A	N/A
2010/0173747	12/2009	Chen et al.	N/A	N/A
2010/0216168	12/2009	Heinzman et al.	N/A	N/A
2010/0234184	12/2009	Le Page et al.	N/A	N/A
2010/0248899	12/2009	Bedell et al.	N/A	N/A
2010/0248905	12/2009	Lu	N/A	N/A
2010/0262052	12/2009	Lunau	602/5	A61B 5/6828
2010/0268304	12/2009	Matos	N/A	N/A
2010/0293003	12/2009	Abbo	N/A	N/A
2010/0298102	12/2009	Bosecker et al.	N/A	N/A
2010/0326207	12/2009	Topel	N/A	N/A
2010/0332583	12/2009	Szabo	N/A	N/A
2011/0010188	12/2010	Yoshikawa et al.	N/A	N/A
2011/0047108	12/2010	Chakrabarty et al.	N/A	N/A
2011/0082007	12/2010	Birrell	N/A	N/A
2011/0087137	12/2010	Hanoun	N/A	N/A
2011/0119212	12/2010	De Bruin et al.	N/A	N/A
2011/0172059	12/2010	Watterson et al.	N/A	N/A
2011/0195819	12/2010	Shaw et al.	N/A	N/A
2011/0218462	12/2010	Smith	N/A	N/A
2011/0218814	12/2010	Coats	N/A	N/A
2011/0275483	12/2010	Dugan	N/A	N/A
2011/0281249	12/2010	Gammell et al.	N/A	N/A
2011/0306846	12/2010	Osorio	N/A	N/A
2012/0041771	12/2011	Cosentino et al.	N/A	N/A
2012/0065987	12/2011	Farooq et al.	N/A	N/A
2012/0116258	12/2011	Lee	N/A	N/A
2012/0130196	12/2011	Jain et al.	N/A	N/A
2012/0130197	12/2011	Kugler et al.	N/A	N/A
2012/0167709	12/2011	Chen et al.	N/A	N/A
2012/0183939	12/2011	Aragones et al.	N/A	N/A
2012/0190502	12/2011	Paulus et al.	N/A	N/A
2012/0232438	12/2011	Cataldi et al.	N/A	N/A
2012/0259648	12/2011	Mallon et al.	N/A	N/A
2012/0259649	12/2011	Mallon et al.	N/A	N/A
2012/0278759	12/2011	Curl et al.	N/A	N/A
2012/0295240	12/2011	Walker et al.	N/A	N/A
2012/0296455	12/2011	Ohnemus et al.	N/A	N/A
2012/0310667	12/2011	Altman et al.	N/A	N/A

2013/0066647	12/2012	Andrie	N/A	N/A
2013/0108594	12/2012	Martin-Rendon et al.	N/A	N/A
2013/0110545	12/2012	Smallwood	N/A	N/A
2013/0123071	12/2012	Rhea	N/A	N/A
2013/0123667	12/2012	Komatireddy et al.	N/A	N/A
2013/0137550	12/2012	Skinner et al.	N/A	N/A
2013/0137552	12/2012	Kemp et al.	N/A	N/A
2013/0158368	12/2012	Pacione	N/A	N/A
2013/0165195	12/2012	Watterson	N/A	N/A
2013/0178334	12/2012	Brammer	N/A	N/A
2013/0211281	12/2012	Ross et al.	N/A	N/A
2013/0253943	12/2012	Lee et al.	N/A	N/A
2013/0274069	12/2012	Watterson et al.	N/A	N/A
2013/0296987	12/2012	Rogers et al.	N/A	N/A
2013/0318027	12/2012	Almogy et al.	N/A	N/A
2013/0332616	12/2012	Landwehr	N/A	N/A
2013/0345025	12/2012	van der Merwe	N/A	N/A
2014/0006042	12/2013	Keefe et al.	N/A	N/A
2014/0011640	12/2013	Dugan	N/A	N/A
2014/0031174	12/2013	Huang	N/A	N/A
2014/0062900	12/2013	Kaula et al.	N/A	N/A
2014/0074179	12/2013	Heldman et al.	N/A	N/A
2014/0089836	12/2013	Damani et al.	N/A	N/A
2014/0108035	12/2013	Akbay	N/A	N/A
2014/0113261	12/2013	Akiba	N/A	N/A
2014/0113768	12/2013	Lin et al.	N/A	N/A
2014/0135173	12/2013	Watterson	N/A	N/A
2014/0155129	12/2013	Dugan	N/A	N/A
2014/0163439	12/2013	Uryash et al.	N/A	N/A
2014/0172442	12/2013	Broderick	N/A	N/A
2014/0172460	12/2013	Kohli	N/A	N/A
2014/0172514	12/2013	Schumann et al.	N/A	N/A
2014/0188009	12/2013	Lange et al.	N/A	N/A
2014/0194250	12/2013	Reich et al.	N/A	N/A
2014/0194251	12/2013	Reich et al.	N/A	N/A
2014/0200414	12/2013	Osorio	N/A	N/A
2014/0207264	12/2013	Quy	N/A	N/A
2014/0207486	12/2013	Carty et al.	N/A	N/A
2014/0228649	12/2013	Rayner et al.	N/A	N/A
2014/0246499	12/2013	Proud et al.	N/A	N/A
2014/0256511	12/2013	Smith	N/A	N/A
2014/0257837	12/2013	Walker et al.	N/A	N/A
2014/0274565	12/2013	Boyette et al.	N/A	N/A
2014/0274622	12/2013	Leonhard	N/A	N/A
2014/0275816	12/2013	Sandmore	N/A	N/A
2014/0303540	12/2013	Baym	N/A	N/A
2014/0309083	12/2013	Dugan	N/A	N/A
2014/0322686	12/2013	Kang	N/A	N/A
2014/0347265	12/2013	Aimone et al.	N/A	N/A
2014/0371816	12/2013	Matos	N/A	N/A

2014/0372133	12/2013	Austrum et al.	N/A	N/A
2015/0025816	12/2014	Ross	N/A	N/A
2015/0045700	12/2014	Cavanagh et al.	N/A	N/A
2015/0046192	12/2014	Raduchel	N/A	N/A
2015/0051721	12/2014	Cheng	N/A	N/A
2015/0065213	12/2014	Dugan	N/A	N/A
2015/0073814	12/2014	Linebaugh	N/A	N/A
2015/0088544	12/2014	Goldberg	N/A	N/A
2015/0094192	12/2014	Skwortsow et al.	N/A	N/A
2015/0099458	12/2014	Weisner et al.	N/A	N/A
2015/0099952	12/2014	Lain et al.	N/A	N/A
2015/0111644	12/2014	Larson	N/A	N/A
2015/0112230	12/2014	Iglesias	N/A	N/A
2015/0112702	12/2014	Joao et al.	N/A	N/A
2015/0130830	12/2014	Nagasaki	N/A	N/A
2015/0141200	12/2014	Murray et al.	N/A	N/A
2015/0142142	12/2014	Campana Aguilera et al.	N/A	N/A
2015/0149217	12/2014	Kaburagi	N/A	N/A
2015/0151162	12/2014	Dugan	N/A	N/A
2015/0157938	12/2014	Domansky et al.	N/A	N/A
2015/0161331	12/2014	Oleynik	N/A	N/A
2015/0161876	12/2014	Castillo	N/A	N/A
2015/0174446	12/2014	Chiang	N/A	N/A
2015/0196804	12/2014	Koduri	N/A	N/A
2015/0196805	12/2014	Koduri	N/A	N/A
2015/0199494	12/2014	Koduri	N/A	N/A
2015/0217056	12/2014	Kadavy et al.	N/A	N/A
2015/0251074	12/2014	Ahmed et al.	N/A	N/A
2015/0257679	12/2014	Ross	N/A	N/A
2015/0265209	12/2014	Zhang	N/A	N/A
2015/0290061	12/2014	Stafford et al.	N/A	N/A
2015/0331997	12/2014	Joao	N/A	N/A
2015/0335950	12/2014	Eder	N/A	N/A
2015/0335951	12/2014	Eder	N/A	N/A
2015/0339442	12/2014	Oleynik	N/A	N/A
2015/0341812	12/2014	Dion et al.	N/A	N/A
2015/0351664	12/2014	Ross	N/A	N/A
2015/0351665	12/2014	Ross	N/A	N/A
2015/0360069	12/2014	Marti et al.	N/A	N/A
2015/0379232	12/2014	Mainwaring et al.	N/A	N/A
2015/0379430	12/2014	Dirac et al.	N/A	N/A
2016/0004820	12/2015	Moore	N/A	N/A
2016/0007885	12/2015	Basta	N/A	N/A
2016/0015995	12/2015	Leung et al.	N/A	N/A
2016/0023081	12/2015	Popa-Simil et al.	N/A	N/A
2016/0045170	12/2015	Migita	N/A	N/A
2016/0081594	12/2015	Gaddipati	N/A	N/A
2016/0086500	12/2015	Kaleal, III	N/A	N/A
2016/0096073	12/2015	Rahman et al.	N/A	N/A

2016/0117471	12/2015	Belt et al.	N/A	N/A
2016/0132643	12/2015	Radhakrishna et al.	N/A	N/A
2016/0140319	12/2015	Stark	N/A	N/A
2016/0143593	12/2015	Fu et al.	N/A	N/A
2016/0151670	12/2015	Dugan	N/A	N/A
2016/0158534	12/2015	Guarraia et al.	N/A	N/A
2016/0166833	12/2015	Bum	N/A	N/A
2016/0166881	12/2015	Ridgel et al.	N/A	N/A
2016/0193306	12/2015	Rabovsky et al.	N/A	N/A
2016/0197918	12/2015	Turgeman et al.	N/A	N/A
2016/0213924	12/2015	Coleman	N/A	N/A
2016/0250519	12/2015	Watterson	N/A	N/A
2016/0275259	12/2015	Nolan et al.	N/A	N/A
2016/0287166	12/2015	Tran	N/A	N/A
2016/0302666	12/2015	Shaya	N/A	N/A
2016/0302721	12/2015	Wiedenhoefer et al.	N/A	N/A
2016/0317869	12/2015	Dugan	N/A	N/A
2016/0322078	12/2015	Bose et al.	N/A	N/A
2016/0325140	12/2015	Wu	N/A	N/A
2016/0332028	12/2015	Melnik	N/A	N/A
2016/0345841	12/2015	Jang et al.	N/A	N/A
2016/0354636	12/2015	Jang	N/A	N/A
2016/0361025	12/2015	Reicher et al.	N/A	N/A
2016/0361597	12/2015	Cole et al.	N/A	N/A
2016/0373477	12/2015	Moyle	N/A	N/A
2017/0004260	12/2016	Moturu et al.	N/A	N/A
2017/0011179	12/2016	Arshad et al.	N/A	N/A
2017/0032092	12/2016	Mink et al.	N/A	N/A
2017/0033375	12/2016	Ohmori et al.	N/A	N/A
2017/0042467	12/2016	Herr et al.	N/A	N/A
2017/0046488	12/2016	Pereira	N/A	N/A
2017/0065851	12/2016	Deluca et al.	N/A	N/A
2017/0080320	12/2016	Smith	N/A	N/A
2017/0091422	12/2016	Kumar et al.	N/A	N/A
2017/0095670	12/2016	Ghaffari et al.	N/A	N/A
2017/0095692	12/2016	Chang et al.	N/A	N/A
2017/0095693	12/2016	Chang et al.	N/A	N/A
2017/0100637	12/2016	Princen et al.	N/A	N/A
2017/0106242	12/2016	Dugan	N/A	N/A
2017/0113092	12/2016	Johnson	N/A	N/A
2017/0128769	12/2016	Long et al.	N/A	N/A
2017/0132947	12/2016	Maeda et al.	N/A	N/A
2017/0136296	12/2016	Barrera et al.	N/A	N/A
2017/0136298	12/2016	Bae	N/A	N/A
2017/0143261	12/2016	Wiedenhoefer et al.	N/A	N/A
2017/0147752	12/2016	Toru	N/A	N/A
2017/0147789	12/2016	Wiedenhoefer et al.	N/A	N/A
2017/0148297	12/2016	Ross	N/A	N/A
2017/0168555	12/2016	Munoz et al.	N/A	N/A
2017/0169177	12/2016	Beale	N/A	N/A

2017/0173391	12/2016	Wiebe	N/A	N/A
2017/0181698	12/2016	Wiedenhoefer et al.	N/A	N/A
2017/0190052	12/2016	Jaekel et al.	N/A	N/A
2017/0202724	12/2016	De Rossi	N/A	N/A
2017/0209766	12/2016	Riley et al.	N/A	N/A
2017/0220751	12/2016	Davis	N/A	N/A
2017/0228517	12/2016	Saliman et al.	N/A	N/A
2017/0235882	12/2016	Orlov et al.	N/A	N/A
2017/0235906	12/2016	Dorris et al.	N/A	N/A
2017/0243028	12/2016	LaFever et al.	N/A	N/A
2017/0258370	12/2016	Plotnik-Peleg et al.	N/A	N/A
2017/0262604	12/2016	Francois	N/A	N/A
2017/0265800	12/2016	Auchinleck et al.	N/A	N/A
2017/0266501	12/2016	Sanders et al.	N/A	N/A
2017/0270260	12/2016	Shetty	N/A	N/A
2017/0278209	12/2016	Olsen et al.	N/A	N/A
2017/0281390	12/2016	Abdul-Hafiz	N/A	A61F 5/013
2017/0282015	12/2016	Wicks et al.	N/A	N/A
2017/0283508	12/2016	Demopulos et al.	N/A	N/A
2017/0286621	12/2016	Cox	N/A	N/A
2017/0296861	12/2016	Burkinshaw	N/A	N/A
2017/0300654	12/2016	Stein et al.	N/A	N/A
2017/0304024	12/2016	Nobrega	N/A	N/A
2017/0312614	12/2016	Tran et al.	N/A	N/A
2017/0323481	12/2016	Tran et al.	N/A	N/A
2017/0329917	12/2016	McRaith et al.	N/A	N/A
2017/0329933	12/2016	Brust	N/A	N/A
2017/0333755	12/2016	Rider	N/A	N/A
2017/0337033	12/2016	Duyan et al.	N/A	N/A
2017/0337334	12/2016	Stanczak	N/A	N/A
2017/0344726	12/2016	Duffy et al.	N/A	N/A
2017/0347923	12/2016	Roh	N/A	N/A
2017/0352157	12/2016	Madabhushi	N/A	N/A
2017/0360586	12/2016	Dempers et al.	N/A	N/A
2017/0368413	12/2016	Shavit	N/A	N/A
2018/0017806	12/2017	Wang et al.	N/A	N/A
2018/0036591	12/2017	King et al.	N/A	N/A
2018/0036593	12/2017	Ridgel et al.	N/A	N/A
2018/0052962	12/2017	Van Der Koijk et al.	N/A	N/A
2018/0056104	12/2017	Cromie et al.	N/A	N/A
2018/0056130	12/2017	Bitran et al.	N/A	N/A
2018/0060494	12/2017	Dias et al.	N/A	N/A
2018/0070864	12/2017	Schuster	N/A	N/A
2018/0071565	12/2017	Gomberg et al.	N/A	N/A
2018/0071566	12/2017	Gomberg et al.	N/A	N/A
2018/0071569	12/2017	Gomberg et al.	N/A	N/A
2018/0071570	12/2017	Gomberg et al.	N/A	N/A
2018/0071571	12/2017	Gomberg et al.	N/A	N/A
2018/0071572	12/2017	Gomberg et al.	N/A	N/A

2018/0075205	12/2017	Moturu et al.	N/A	N/A
2018/0078182	12/2017	Chen	N/A	N/A
2018/0078843	12/2017	Tran et al.	N/A	N/A
2018/0085615	12/2017	Astolfi et al.	N/A	N/A
2018/0089385	12/2017	Gupta	N/A	N/A
2018/0096111	12/2017	Wells et al.	N/A	N/A
2018/0099178	12/2017	Schaefer et al.	N/A	N/A
2018/0102190	12/2017	Hogue et al.	N/A	N/A
2018/0103859	12/2017	Provenzano	N/A	N/A
2018/0113985	12/2017	Gandy et al.	N/A	N/A
2018/0116741	12/2017	Garcia Kilroy et al.	N/A	N/A
2018/0117417	12/2017	Davis	N/A	N/A
2018/0130555	12/2017	Chronis et al.	N/A	N/A
2018/0133551	12/2017	Chang	N/A	N/A
2018/0140927	12/2017	Kito	N/A	N/A
2018/0146870	12/2017	Shemesh	N/A	N/A
2018/0177612	12/2017	Trabish	N/A	A61B 5/4528
2018/0178061	12/2017	O'larte et al.	N/A	N/A
2018/0199855	12/2017	Odame et al.	N/A	N/A
2018/0200577	12/2017	Dugan	N/A	N/A
2018/0220935	12/2017	Tadano et al.	N/A	N/A
2018/0228682	12/2017	Bayerlein et al.	N/A	N/A
2018/0232492	12/2017	Al-Alul et al.	N/A	N/A
2018/0236307	12/2017	Hyde et al.	N/A	N/A
2018/0240552	12/2017	Tuyl et al.	N/A	N/A
2018/0253991	12/2017	Tang et al.	N/A	N/A
2018/0255110	12/2017	Dowlatkah et al.	N/A	N/A
2018/0256079	12/2017	Yang et al.	N/A	N/A
2018/0263530	12/2017	Jung	N/A	N/A
2018/0263535	12/2017	Cramer	N/A	N/A
2018/0263552	12/2017	Graman et al.	N/A	N/A
2018/0264312	12/2017	Pompile et al.	N/A	N/A
2018/0271432	12/2017	Auchinleck et al.	N/A	N/A
2018/0272184	12/2017	Vassilaros et al.	N/A	N/A
2018/0280784	12/2017	Romeo et al.	N/A	N/A
2018/0290017	12/2017	Fung	N/A	N/A
2018/0296143	12/2017	Anderson et al.	N/A	N/A
2018/0296157	12/2017	Bleich et al.	N/A	N/A
2018/0318122	12/2017	LeCursi et al.	N/A	N/A
2018/0326243	12/2017	Badi et al.	N/A	N/A
2018/0330058	12/2017	Bates	N/A	N/A
2018/0330810	12/2017	Gamarnik	N/A	N/A
2018/0330824	12/2017	Athey et al.	N/A	N/A
2018/0353812	12/2017	Lannon et al.	N/A	N/A
2018/0360340	12/2017	Rehse et al.	N/A	N/A
2018/0366225	12/2017	Mansi et al.	N/A	N/A
2018/0373844	12/2017	Ferrandez-Escamez et al.	N/A	N/A
2019/0005195	12/2018	Peterson	N/A	N/A

2019/0009135	12/2018	Wu	N/A	N/A
2019/0019163	12/2018	Batey et al.	N/A	N/A
2019/0019573	12/2018	Lake et al.	N/A	N/A
2019/0019578	12/2018	Vaccaro	N/A	N/A
2019/0030415	12/2018	Volpe, Jr.	N/A	N/A
2019/0031284	12/2018	Fuchs	N/A	N/A
2019/0046794	12/2018	Goodall et al.	N/A	N/A
2019/0060708	12/2018	Fung	N/A	N/A
2019/0065970	12/2018	Bonutti et al.	N/A	N/A
2019/0066832	12/2018	Kang et al.	N/A	N/A
2019/0076701	12/2018	Dugan	N/A	N/A
2019/0080802	12/2018	Ziobro et al.	N/A	N/A
2019/0083846	12/2018	Eder	N/A	N/A
2019/0088356	12/2018	Oliver et al.	N/A	N/A
2019/0090744	12/2018	Mahfouz	N/A	N/A
2019/0096534	12/2018	Joao	N/A	N/A
2019/0105551	12/2018	Ray	N/A	N/A
2019/0108912	12/2018	Spurlock, III	N/A	N/A
2019/0111299	12/2018	Radcliffe et al.	N/A	N/A
2019/0115097	12/2018	Macoviak et al.	N/A	N/A
2019/0117156	12/2018	Howard et al.	N/A	N/A
2019/0118038	12/2018	Tana et al.	N/A	N/A
2019/0118066	12/2018	Cardona	N/A	N/A
2019/0126099	12/2018	Hoang	N/A	N/A
2019/0132948	12/2018	Longinotti-Buitoni et al.	N/A	N/A
2019/0134454	12/2018	Mahoney et al.	N/A	N/A
2019/0137988	12/2018	Cella et al.	N/A	N/A
2019/0143191	12/2018	Ran et al.	N/A	N/A
2019/0143193	12/2018	Kim	N/A	N/A
2019/0145774	12/2018	Ellis	N/A	N/A
2019/0163876	12/2018	Remme et al.	N/A	N/A
2019/0167988	12/2018	Shahriari et al.	N/A	N/A
2019/0172587	12/2018	Park et al.	N/A	N/A
2019/0175988	12/2018	Volterrani et al.	N/A	N/A
2019/0183715	12/2018	Kapure et al.	N/A	N/A
2019/0200920	12/2018	Tien et al.	N/A	N/A
2019/0209891	12/2018	Fung	N/A	N/A
2019/0214119	12/2018	Wachira et al.	N/A	N/A
2019/0223797	12/2018	Tran	N/A	N/A
2019/0224528	12/2018	Omid-Zohoor et al.	N/A	N/A
2019/0228856	12/2018	Leifer	N/A	N/A
2019/0232108	12/2018	Kovach et al.	N/A	N/A
2019/0240103	12/2018	Hepler et al.	N/A	N/A
2019/0240541	12/2018	Denton et al.	N/A	N/A
2019/0244540	12/2018	Errante et al.	N/A	N/A
2019/0247718	12/2018	Blevins	N/A	N/A
2019/0251456	12/2018	Constantin	N/A	N/A
2019/0261959	12/2018	Frankel	N/A	N/A
2019/0262084	12/2018	Roh	N/A	N/A

2019/0269343	12/2018	Ramos Murguialday et al.	N/A	N/A
2019/0274523	12/2018	Bates et al.	N/A	N/A
2019/0275368	12/2018	Maroldi	N/A	N/A
2019/0283247	12/2018	Chang	N/A	N/A
2019/0304584	12/2018	Savolainen	N/A	N/A
2019/0307983	12/2018	Goldman	N/A	N/A
2019/0314681	12/2018	Yang	N/A	N/A
2019/0344123	12/2018	Rubin et al.	N/A	N/A
2019/0354632	12/2018	Mital et al.	N/A	N/A
2019/0362242	12/2018	Pillai et al.	N/A	N/A
2019/0366146	12/2018	Tong et al.	N/A	N/A
2019/0371472	12/2018	Blanchard	N/A	N/A
2019/0385199	12/2018	Bender et al.	N/A	N/A
2019/0388728	12/2018	Wang et al.	N/A	N/A
2019/0392936	12/2018	Arric et al.	N/A	N/A
2019/0392939	12/2018	Basta et al.	N/A	N/A
2020/0005928	12/2019	Daniel	N/A	N/A
2020/0015736	12/2019	Alhathal	N/A	N/A
2020/0034665	12/2019	Ghanta	N/A	N/A
2020/0034707	12/2019	Kivatinos et al.	N/A	N/A
2020/0038703	12/2019	Cleary et al.	N/A	N/A
2020/0051446	12/2019	Rubinstein	N/A	N/A
2020/0054922	12/2019	Azaria	N/A	N/A
2020/0066390	12/2019	Svendrys et al.	N/A	N/A
2020/0085300	12/2019	Kwatra et al.	N/A	N/A
2020/0090802	12/2019	Maron	N/A	N/A
2020/0093418	12/2019	Kluger et al.	N/A	N/A
2020/0121987	12/2019	Loh	N/A	N/A
2020/0129808	12/2019	Fomin	N/A	N/A
2020/0139194	12/2019	Min	N/A	N/A
2020/0143922	12/2019	Chekroud et al.	N/A	N/A
2020/0151595	12/2019	Jayalath et al.	N/A	N/A
2020/0151646	12/2019	De La Fuente Sanchez	N/A	N/A
2020/0152339	12/2019	Pulitzer et al.	N/A	N/A
2020/0160198	12/2019	Reeves et al.	N/A	N/A
2020/0170876	12/2019	Kapure et al.	N/A	N/A
2020/0176098	12/2019	Lucas et al.	N/A	N/A
2020/0188774	12/2019	Fung	N/A	N/A
2020/0197744	12/2019	Schweighofer	N/A	N/A
2020/0221975	12/2019	Basta et al.	N/A	N/A
2020/0237291	12/2019	Raja	N/A	N/A
2020/0237452	12/2019	Wolf et al.	N/A	N/A
2020/0261763	12/2019	Park	N/A	N/A
2020/0267487	12/2019	Siva	N/A	N/A
2020/0275886	12/2019	Mason	N/A	N/A
2020/0289045	12/2019	Hacking et al.	N/A	N/A
2020/0289046	12/2019	Hacking et al.	N/A	N/A
2020/0289879	12/2019	Hacking et al.	N/A	N/A
2020/0289880	12/2019	Hacking et al.	N/A	N/A

2020/0289881	12/2019	Hacking et al.	N/A	N/A
2020/0289889	12/2019	Hacking et al.	N/A	N/A
2020/0293712	12/2019	Potts et al.	N/A	N/A
2020/0303063	12/2019	Sharma et al.	N/A	N/A
2020/0312447	12/2019	Bohn et al.	N/A	N/A
2020/0320454	12/2019	Almashor	N/A	N/A
2020/0334972	12/2019	Gopalakrishnan	N/A	N/A
2020/0346072	12/2019	Shah	N/A	N/A
2020/0353314	12/2019	Messinger	N/A	N/A
2020/0357299	12/2019	Patel et al.	N/A	N/A
2020/0365256	12/2019	Hayashitani et al.	N/A	N/A
2020/0391080	12/2019	Powers	N/A	N/A
2020/0395112	12/2019	Ronner	N/A	N/A
2020/0398083	12/2019	Adelsheim	N/A	N/A
2020/0401224	12/2019	Cotton	N/A	N/A
2020/0402662	12/2019	Esmailian et al.	N/A	N/A
2020/0410374	12/2019	White	N/A	N/A
2020/0410385	12/2019	Otsuki	N/A	N/A
2020/0411162	12/2019	Lien et al.	N/A	N/A
2020/0411170	12/2019	Brown	N/A	N/A
2021/0005224	12/2020	Rothschild et al.	N/A	N/A
2021/0005319	12/2020	Otsuki et al.	N/A	N/A
2021/0008413	12/2020	Asikainen et al.	N/A	N/A
2021/0015560	12/2020	Boddington et al.	N/A	N/A
2021/0027889	12/2020	Neil et al.	N/A	N/A
2021/0035674	12/2020	Volosin et al.	N/A	N/A
2021/0050086	12/2020	Rose et al.	N/A	N/A
2021/0065855	12/2020	Pepin et al.	N/A	N/A
2021/0074178	12/2020	Ilan et al.	N/A	N/A
2021/0076981	12/2020	Hacking et al.	N/A	N/A
2021/0077860	12/2020	Posnack et al.	N/A	N/A
2021/0077884	12/2020	De Las Casas Zolezzi et al.	N/A	N/A
2021/0082554	12/2020	Kalia et al.	N/A	N/A
2021/0093891	12/2020	Sheng	N/A	N/A
2021/0098099	12/2020	Neumann	N/A	N/A
2021/0098129	12/2020	Neumann	N/A	N/A
2021/0101051	12/2020	Posnack et al.	N/A	N/A
2021/0113890	12/2020	Posnack et al.	N/A	N/A
2021/0125696	12/2020	Liu et al.	N/A	N/A
2021/0127974	12/2020	Mason et al.	N/A	N/A
2021/0128080	12/2020	Mason et al.	N/A	N/A
2021/0128255	12/2020	Mason et al.	N/A	N/A
2021/0128978	12/2020	Gilstrom et al.	N/A	N/A
2021/0134412	12/2020	Guaneri et al.	N/A	N/A
2021/0134425	12/2020	Mason et al.	N/A	N/A
2021/0134428	12/2020	Mason	N/A	N/A
2021/0134429	12/2020	Mason	N/A	N/A
2021/0134430	12/2020	Mason et al.	N/A	N/A
2021/0134432	12/2020	Mason et al.	N/A	N/A

2021/0134456	12/2020	Posnack et al.	N/A	N/A
2021/0134457	12/2020	Mason et al.	N/A	N/A
2021/0134458	12/2020	Mason et al.	N/A	N/A
2021/0134463	12/2020	Mason et al.	N/A	N/A
2021/0138304	12/2020	Mason et al.	N/A	N/A
2021/0142875	12/2020	Mason et al.	N/A	N/A
2021/0142893	12/2020	Guaneri et al.	N/A	N/A
2021/0142898	12/2020	Mason et al.	N/A	N/A
2021/0142903	12/2020	Mason et al.	N/A	N/A
2021/0144074	12/2020	Guaneri et al.	N/A	N/A
2021/0186419	12/2020	Van Ee et al.	N/A	N/A
2021/0187348	12/2020	Phillips et al.	N/A	N/A
2021/0202090	12/2020	ODonovan et al.	N/A	N/A
2021/0202103	12/2020	Bostic et al.	N/A	N/A
2021/0205660	12/2020	Shavit	N/A	N/A
2021/0217516	12/2020	Nash	N/A	N/A
2021/0236020	12/2020	Matijevich et al.	N/A	N/A
2021/0240853	12/2020	Carlson	N/A	N/A
2021/0244998	12/2020	Hacking et al.	N/A	N/A
2021/0245003	12/2020	Turner	N/A	N/A
2021/0251562	12/2020	Jain	N/A	N/A
2021/0272677	12/2020	Barbee	N/A	N/A
2021/0338469	12/2020	Dempers	N/A	N/A
2021/0343384	12/2020	Purushothaman et al.	N/A	N/A
2021/0345879	12/2020	Mason et al.	N/A	N/A
2021/0345975	12/2020	Mason et al.	N/A	N/A
2021/0350888	12/2020	Guaneri et al.	N/A	N/A
2021/0350898	12/2020	Mason et al.	N/A	N/A
2021/0350899	12/2020	Mason et al.	N/A	N/A
2021/0350901	12/2020	Mason et al.	N/A	N/A
2021/0350902	12/2020	Mason et al.	N/A	N/A
2021/0350914	12/2020	Guaneri et al.	N/A	N/A
2021/0350926	12/2020	Mason et al.	N/A	N/A
2021/0354002	12/2020	Schaefer	N/A	N/A
2021/0361514	12/2020	Choi et al.	N/A	N/A
2021/0366587	12/2020	Mason et al.	N/A	N/A
2021/0375425	12/2020	Zhang	N/A	N/A
2021/0383909	12/2020	Mason et al.	N/A	N/A
2021/0391091	12/2020	Mason	N/A	N/A
2021/0398668	12/2020	Chock et al.	N/A	N/A
2021/0407670	12/2020	Mason et al.	N/A	N/A
2021/0407681	12/2020	Mason et al.	N/A	N/A
2022/0000556	12/2021	Casey et al.	N/A	N/A
2022/0015838	12/2021	Posnack	N/A	N/A
2022/0016480	12/2021	Bissonnette et al.	N/A	N/A
2022/0016482	12/2021	Bissonnette	N/A	N/A
2022/0016485	12/2021	Bissonnette	N/A	N/A
2022/0016486	12/2021	Bissonnette	N/A	N/A
2022/0020469	12/2021	Tanner	N/A	N/A
2022/0044806	12/2021	Sanders et al.	N/A	N/A

2022/0047921	12/2021	Bissonnette	N/A	N/A
2022/0066548	12/2021	Helot	N/A	N/A
2022/0079690	12/2021	Mason et al.	N/A	N/A
2022/0080256	12/2021	Arn et al.	N/A	N/A
2022/0080265	12/2021	Watterson	N/A	N/A
2022/0105384	12/2021	Hacking et al.	N/A	N/A
2022/0105385	12/2021	Hacking et al.	N/A	N/A
2022/0105390	12/2021	Yuasa	N/A	N/A
2022/0115133	12/2021	Mason et al.	N/A	N/A
2022/0118218	12/2021	Bense et al.	N/A	N/A
2022/0122724	12/2021	Durlach et al.	N/A	N/A
2022/0126169	12/2021	Mason	N/A	N/A
2022/0133576	12/2021	Choi et al.	N/A	N/A
2022/0148725	12/2021	Mason et al.	N/A	N/A
2022/0158916	12/2021	Mason et al.	N/A	N/A
2022/0176039	12/2021	Lintereur et al.	N/A	N/A
2022/0181004	12/2021	Zilca et al.	N/A	N/A
2022/0193491	12/2021	Mason	N/A	N/A
2022/0230729	12/2021	Mason	N/A	N/A
2022/0238222	12/2021	Neuberg	N/A	N/A
2022/0238223	12/2021	Mason	N/A	N/A
2022/0258935	12/2021	Kraft	N/A	N/A
2022/0262483	12/2021	Rosenberg et al.	N/A	N/A
2022/0262504	12/2021	Bratty et al.	N/A	N/A
2022/0266094	12/2021	Mason et al.	N/A	N/A
2022/0270738	12/2021	Mason et al.	N/A	N/A
2022/0273985	12/2021	Jeong et al.	N/A	N/A
2022/0273986	12/2021	Mason	N/A	N/A
2022/0288460	12/2021	Mason	N/A	N/A
2022/0288461	12/2021	Ashley et al.	N/A	N/A
2022/0288462	12/2021	Ashley et al.	N/A	N/A
2022/0293257	12/2021	Guaneri et al.	N/A	N/A
2022/0300787	12/2021	Wall et al.	N/A	N/A
2022/0304881	12/2021	Choi et al.	N/A	N/A
2022/0304882	12/2021	Choi	N/A	N/A
2022/0305291	12/2021	Hibbard	N/A	N/A
2022/0305328	12/2021	Choi et al.	N/A	N/A
2022/0314072	12/2021	Bissonnette et al.	N/A	N/A
2022/0314075	12/2021	Mason et al.	N/A	N/A
2022/0323826	12/2021	Khurana	N/A	N/A
2022/0327714	12/2021	Cook et al.	N/A	N/A
2022/0327807	12/2021	Cook et al.	N/A	N/A
2022/0328181	12/2021	Mason et al.	N/A	N/A
2022/0330823	12/2021	Janssen	N/A	N/A
2022/0331663	12/2021	Mason	N/A	N/A
2022/0338761	12/2021	Maddahi et al.	N/A	N/A
2022/0339052	12/2021	Kim	N/A	N/A
2022/0339501	12/2021	Mason et al.	N/A	N/A
2022/0370851	12/2021	Guidarelli et al.	N/A	N/A
2022/0384010	12/2021	Kanayama	N/A	N/A

2022/0384012	12/2021	Mason	N/A	N/A
2022/0392591	12/2021	Guaneri et al.	N/A	N/A
2022/0395232	12/2021	Locke	N/A	N/A
2022/0401783	12/2021	Choi	N/A	N/A
2022/0415469	12/2021	Mason	N/A	N/A
2022/0415471	12/2021	Mason	N/A	N/A
2023/0001268	12/2022	Bissonnette et al.	N/A	N/A
2023/0013530	12/2022	Mason	N/A	N/A
2023/0014598	12/2022	Mason et al.	N/A	N/A
2023/0029639	12/2022	Roy	N/A	N/A
2023/0047253	12/2022	Gnanasambandam et al.	N/A	N/A
2023/0048040	12/2022	Hacking et al.	N/A	N/A
2023/0051751	12/2022	Hacking et al.	N/A	N/A
2023/0058605	12/2022	Mason	N/A	N/A
2023/0060039	12/2022	Mason	N/A	N/A
2023/0072368	12/2022	Mason	N/A	N/A
2023/0078793	12/2022	Mason	N/A	N/A
2023/0119461	12/2022	Mason	N/A	N/A
2023/0190100	12/2022	Stump	N/A	N/A
2023/0197240	12/2022	Rosenberg	N/A	N/A
2023/0201656	12/2022	Hacking et al.	N/A	N/A
2023/0207097	12/2022	Mason	N/A	N/A
2023/0207124	12/2022	Walsh et al.	N/A	N/A
2023/0215539	12/2022	Rosenberg et al.	N/A	N/A
2023/0215552	12/2022	Khotilovich et al.	N/A	N/A
2023/0218950	12/2022	Belson et al.	N/A	N/A
2023/0245747	12/2022	Rosenberg et al.	N/A	N/A
2023/0245748	12/2022	Rosenberg et al.	N/A	N/A
2023/0245750	12/2022	Rosenberg et al.	N/A	N/A
2023/0245751	12/2022	Rosenberg et al.	N/A	N/A
2023/0249599	12/2022	Nicola	N/A	N/A
2023/0253089	12/2022	Rosenberg et al.	N/A	N/A
2023/0255555	12/2022	Sundaram et al.	N/A	N/A
2023/0263428	12/2022	Hull et al.	N/A	N/A
2023/0274813	12/2022	Rosenberg et al.	N/A	N/A
2023/0282329	12/2022	Mason et al.	N/A	N/A
2023/0364472	12/2022	Posnack	N/A	N/A
2023/0368886	12/2022	Rosenberg	N/A	N/A
2023/0377710	12/2022	Chen et al.	N/A	N/A
2023/0377711	12/2022	Rosenberg	N/A	N/A
2023/0377712	12/2022	Rosenberg	N/A	N/A
2023/0386639	12/2022	Rosenberg	N/A	N/A
2023/0390627	12/2022	Bolton	N/A	N/A
2023/0395231	12/2022	Rosenberg	N/A	N/A
2023/0395232	12/2022	Rosenberg	N/A	N/A
2024/0029856	12/2023	Rosenberg	N/A	N/A
2024/0058651	12/2023	Bissonnette	N/A	N/A
2024/0177846	12/2023	Gnanasambandam	N/A	N/A
2024/0203580	12/2023	Mason	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3193419	12/2021	CA	N/A
2885238	12/2006	CN	N/A
101964151	12/2010	CN	N/A
201889024	12/2010	CN	N/A
202220794	12/2011	CN	N/A
102670381	12/2011	CN	N/A
103263336	12/2012	CN	N/A
103390357	12/2012	CN	N/A
103473631	12/2012	CN	N/A
103488880	12/2013	CN	N/A
103501328	12/2013	CN	N/A
103721343	12/2013	CN	N/A
203677851	12/2013	CN	N/A
104335211	12/2014	CN	N/A
105263448	12/2015	CN	N/A
105620643	12/2015	CN	N/A
105683977	12/2015	CN	N/A
103136447	12/2015	CN	N/A
105894088	12/2015	CN	N/A
105930668	12/2015	CN	N/A
205626871	12/2015	CN	N/A
106127646	12/2015	CN	N/A
106236502	12/2015	CN	N/A
106510985	12/2016	CN	N/A
106621195	12/2016	CN	N/A
107066819	12/2016	CN	N/A
107430641	12/2016	CN	N/A
107551475	12/2017	CN	N/A
107736982	12/2017	CN	N/A
107930021	12/2017	CN	N/A
108078737	12/2017	CN	N/A
208224811	12/2017	CN	N/A
109191954	12/2018	CN	N/A
109363887	12/2018	CN	N/A
208573971	12/2018	CN	N/A
110148472	12/2018	CN	N/A
110201358	12/2018	CN	N/A
110215188	12/2018	CN	N/A
110322957	12/2018	CN	N/A
110808092	12/2019	CN	N/A
110931103	12/2019	CN	N/A
110993057	12/2019	CN	N/A
111105859	12/2019	CN	N/A
111111110	12/2019	CN	N/A
111370088	12/2019	CN	N/A
111460305	12/2019	CN	N/A

111790111	12/2019	CN	N/A
112071393	12/2019	CN	N/A
212141371	12/2019	CN	N/A
112289425	12/2020	CN	N/A
212624809	12/2020	CN	N/A
112603295	12/2020	CN	N/A
213190965	12/2020	CN	N/A
113384850	12/2020	CN	N/A
113499572	12/2020	CN	N/A
215136488	12/2020	CN	N/A
113885361	12/2021	CN	N/A
114049961	12/2021	CN	N/A
114203274	12/2021	CN	N/A
216258145	12/2021	CN	N/A
114632302	12/2021	CN	N/A
114694824	12/2021	CN	N/A
114898832	12/2021	CN	N/A
114983760	12/2021	CN	N/A
217472652	12/2021	CN	N/A
110270062	12/2021	CN	N/A
218420859	12/2022	CN	N/A
115954081	12/2022	CN	N/A
95019	12/1896	DE	N/A
7628633	12/1976	DE	N/A
8519150	12/1984	DE	N/A
3732905	12/1987	DE	N/A
19619820	12/1995	DE	N/A
29620008	12/1996	DE	N/A
19947926	12/2000	DE	N/A
102018202497	12/2017	DE	N/A
102018211212	12/2018	DE	N/A
102019108425	12/2019	DE	N/A
199600	12/1985	EP	N/A
0383137	12/1989	EP	N/A
634319	12/1994	EP	N/A
0919259	12/1998	EP	N/A
1034817	12/1999	EP	N/A
1159989	12/2000	EP	N/A
1391179	12/2003	EP	N/A
1968028	12/2007	EP	N/A
2564904	12/2012	EP	N/A
2575064	12/2012	EP	N/A
1909730	12/2013	EP	N/A
2815242	12/2013	EP	N/A
2869805	12/2014	EP	N/A
2997951	12/2015	EP	N/A
2688472	12/2015	EP	N/A
3264303	12/2017	EP	N/A
3323473	12/2017	EP	N/A
3547322	12/2018	EP	N/A

3627514	12/2019	EP	N/A
3671700	12/2019	EP	N/A
3688537	12/2019	EP	N/A
3731733	12/2019	EP	N/A
3984508	12/2021	EP	N/A
3984509	12/2021	EP	N/A
3984510	12/2021	EP	N/A
3984511	12/2021	EP	N/A
3984512	12/2021	EP	N/A
3984513	12/2021	EP	N/A
4054699	12/2021	EP	N/A
4112033	12/2022	EP	N/A
2527541	12/1982	FR	N/A
3127393	12/2022	FR	N/A
141664	12/1919	GB	N/A
2336140	12/1998	GB	N/A
2372459	12/2001	GB	N/A
2512431	12/2013	GB	N/A
2591542	12/2021	GB	N/A
201811043670	12/2017	IN	N/A
2000005339	12/1999	JP	N/A
2003225875	12/2002	JP	N/A
2005227928	12/2004	JP	N/A
2005227928	12/2004	JP	N/A
2009112336	12/2008	JP	N/A
2013515995	12/2012	JP	N/A
2014104139	12/2013	JP	N/A
3193662	12/2013	JP	N/A
3198173	12/2014	JP	N/A
5804063	12/2014	JP	N/A
2018102842	12/2017	JP	N/A
2019028647	12/2018	JP	N/A
2019134909	12/2018	JP	N/A
6573739	12/2018	JP	N/A
6659831	12/2019	JP	N/A
2020057082	12/2019	JP	N/A
6710357	12/2019	JP	N/A
6775757	12/2019	JP	N/A
2021027917	12/2020	JP	N/A
6871379	12/2020	JP	N/A
2022521378	12/2021	JP	N/A
3238491	12/2021	JP	N/A
7198364	12/2021	JP	N/A
7202474	12/2022	JP	N/A
7231750	12/2022	JP	N/A
7231751	12/2022	JP	N/A
7231752	12/2022	JP	N/A
20020009724	12/2001	KR	N/A
200276919	12/2001	KR	N/A
20020065253	12/2001	KR	N/A

100582596	12/2005	KR	N/A
101042258	12/2010	KR	N/A
101258250	12/2012	KR	N/A
101325581	12/2012	KR	N/A
20140128630	12/2013	KR	N/A
20150017693	12/2014	KR	N/A
20150078191	12/2014	KR	N/A
101580071	12/2014	KR	N/A
101647620	12/2015	KR	N/A
20160093990	12/2015	KR	N/A
20170038837	12/2016	KR	N/A
20180004928	12/2017	KR	N/A
20190029175	12/2018	KR	N/A
20190056116	12/2018	KR	N/A
101988167	12/2018	KR	N/A
101969392	12/2018	KR	N/A
102055279	12/2018	KR	N/A
20200019548	12/2019	KR	N/A
102088333	12/2019	KR	N/A
20200025290	12/2019	KR	N/A
20200029180	12/2019	KR	N/A
102097190	12/2019	KR	N/A
102116664	12/2019	KR	N/A
102116968	12/2019	KR	N/A
20200056233	12/2019	KR	N/A
102120828	12/2019	KR	N/A
102121586	12/2019	KR	N/A
102142713	12/2019	KR	N/A
102162522	12/2019	KR	N/A
20200119665	12/2019	KR	N/A
102173553	12/2019	KR	N/A
102180079	12/2019	KR	N/A
102188766	12/2019	KR	N/A
102196793	12/2019	KR	N/A
20210006212	12/2020	KR	N/A
102224188	12/2020	KR	N/A
102224618	12/2020	KR	N/A
102246049	12/2020	KR	N/A
102246050	12/2020	KR	N/A
102246051	12/2020	KR	N/A
102246052	12/2020	KR	N/A
20210052028	12/2020	KR	N/A
102264498	12/2020	KR	N/A
102352602	12/2021	KR	N/A
102352603	12/2021	KR	N/A
102352604	12/2021	KR	N/A
20220004639	12/2021	KR	N/A
102387577	12/2021	KR	N/A
102421437	12/2021	KR	N/A
20220102207	12/2021	KR	N/A

102427545	12/2021	KR	N/A
102467495	12/2021	KR	N/A
102467496	12/2021	KR	N/A
102469723	12/2021	KR	N/A
102471990	12/2021	KR	N/A
20220145989	12/2021	KR	N/A
20220156134	12/2021	KR	N/A
102502744	12/2022	KR	N/A
20230019349	12/2022	KR	N/A
20230019350	12/2022	KR	N/A
20230026556	12/2022	KR	N/A
20230026668	12/2022	KR	N/A
20230040526	12/2022	KR	N/A
20230050506	12/2022	KR	N/A
20230056118	12/2022	KR	N/A
102528503	12/2022	KR	N/A
102531930	12/2022	KR	N/A
102532766	12/2022	KR	N/A
102539190	12/2022	KR	N/A
2014131288	12/2015	RU	N/A
2607953	12/2016	RU	N/A
M474545	12/2013	TW	N/A
I442956	12/2013	TW	N/A
M638437	12/2022	TW	N/A
1998009687	12/1997	WO	N/A
0149235	12/2000	WO	N/A
0151083	12/2000	WO	N/A
2001050387	12/2000	WO	N/A
2001056465	12/2000	WO	N/A
02062211	12/2001	WO	N/A
02093312	12/2001	WO	N/A
2003043494	12/2002	WO	N/A
2005018453	12/2004	WO	N/A
2005074369	12/2004	WO	N/A
2006004430	12/2005	WO	N/A
2006012694	12/2005	WO	N/A
2007102709	12/2006	WO	N/A
2008114291	12/2007	WO	N/A
2008140780	12/2007	WO	N/A
2009003170	12/2007	WO	N/A
2009008968	12/2008	WO	N/A
2011025322	12/2010	WO	N/A
2012128801	12/2011	WO	N/A
2013002568	12/2012	WO	N/A
2023164292	12/2012	WO	N/A
2013122839	12/2012	WO	N/A
2014011447	12/2013	WO	N/A
2014163976	12/2013	WO	N/A
2015026744	12/2014	WO	N/A
2015065298	12/2014	WO	N/A

2015082555	12/2014	WO	N/A
2016151364	12/2015	WO	N/A
2016154318	12/2015	WO	N/A
2017030781	12/2016	WO	N/A
2017166074	12/2016	WO	N/A
2017091691	12/2016	WO	N/A
2017165238	12/2016	WO	N/A
2018027080	12/2017	WO	N/A
2018081795	12/2017	WO	N/A
2018171853	12/2017	WO	N/A
2019022706	12/2018	WO	N/A
2019143940	12/2018	WO	N/A
2020014710	12/2019	WO	N/A
2020075190	12/2019	WO	N/A
2020130979	12/2019	WO	N/A
2020149815	12/2019	WO	N/A
2020229705	12/2019	WO	N/A
2020245727	12/2019	WO	N/A
2020249855	12/2019	WO	N/A
2020252599	12/2019	WO	N/A
2020256577	12/2019	WO	N/A
2021021447	12/2020	WO	N/A
2021022003	12/2020	WO	N/A
2021038980	12/2020	WO	N/A
2021055427	12/2020	WO	N/A
2021061061	12/2020	WO	N/A
2021090267	12/2020	WO	N/A
2021138620	12/2020	WO	N/A
2021216881	12/2020	WO	N/A
2021236961	12/2020	WO	N/A
2022047006	12/2021	WO	N/A
2022092493	12/2021	WO	N/A
2022092494	12/2021	WO	N/A
2022212883	12/2021	WO	N/A
2022212921	12/2021	WO	N/A
2022216498	12/2021	WO	N/A
2022251420	12/2021	WO	N/A
2023008680	12/2022	WO	N/A
2023008681	12/2022	WO	N/A
2023022319	12/2022	WO	N/A
2023022320	12/2022	WO	N/A
2023052695	12/2022	WO	N/A
2023091496	12/2022	WO	N/A
2023215155	12/2022	WO	N/A
2023230075	12/2022	WO	N/A
2024013267	12/2023	WO	N/A
2024107807	12/2023	WO	N/A

OTHER PUBLICATIONS

Jeong et al., "Computer-assisted upper extremity training using interactive biking exercise (iBikE) platform," Sep. 2012, pp. 1-5, 34th Annual International Conference of the IEEE EMBS. cited by applicant

Malloy, Online Article "AI-enabled EKGs find difference between numerical age and biological age significantly affects health, longevity", Website:

<https://newsnetwork.mayoclinic.org/discussion/ai-enabled-ekgs-find-difference-between-numerical-age-and-biological-age-significantly-affects-health-longevity/>, Mayo Clinic News Network, May 20, 2021, retrieved: Jan. 23, 2023, p. 1-4. cited by applicant

HCL Fitness, HCL Fitness PhysioTrainer Pro, 2017, retrieved on Aug. 19, 2021, 7 pages, <https://www.amazon.com/HCL-Fitness-Physio-Trainer-Electronically-Controlled/dp/B0759YMW78/>. cited by applicant

International Searching Authority, International Preliminary Report on Patentability of International Application No. PCT/US2017/50895, Date of Mailing Dec. 11, 2018, 52 pages. cited by applicant

International Searching Authority, Search Report and Written Opinion for International Application No. PCT/US2017/50895, Date of Mailing Jan. 12, 2018, 6 pages. cited by applicant

International Searching Authority, Search Report and Written Opinion for International Application No. PCT/US2020/021876, Date of Mailing May 28, 2020, 8 pages. cited by applicant

International Searching Authority, Search Report and Written Opinion for International Application No. PCT/US2020/051008, Date of Mailing Dec. 10, 2020, 9 pages. cited by applicant

International Searching Authority, Search Report and Written Opinion for International Application No. PCT/US2020/056661, Date of Mailing Feb. 12, 2021, 12 pages. cited by applicant

International Searching Authority, Search Report and Written Opinion for International Application No. PCT/US2021/032807, Date of Mailing Sep. 6, 2021, 11 pages. cited by applicant

Matrix, R3xm Recumbent Cycle, retrieved on Aug. 4, 2020, 7 pages,

<https://www.matrixfitness.com/en/cardio/cycles/r3xm-recumbent>. cited by applicant

ROM3 Rehab, ROM3 Rehab System, Apr. 20, 2015, retrieved on Aug. 31, 2018, 12 pages, <https://vimeo.com/125438463>. cited by applicant

Barrett et al., "Artificial intelligence supported patient self-care in chronic heart failure: a paradigm shift from reactive to predictive, preventive and personalised care," EPMA Journal (2019), pp. 445-464. cited by applicant

Oerkild et al., "Home-based cardiac rehabilitation is an attractive alternative to No. cardiac rehabilitation for elderly patients with coronary heart disease: results from a randomised clinical trial," BMJ Open Accessible Medical Research, Nov. 22, 2012, pp. 1-9. cited by applicant

Bravo-Escobar et al., "Effectiveness and safety of a home-based cardiac rehabilitation programme of mixed surveillance in patients with ischemic heart disease at moderate cardiovascular risk: A randomised, controlled clinical trial," BMC Cardiovascular Disorders, 2017, pp. 1-11, vol. 17:66. cited by applicant

Thomas et al., "Home-Based Cardiac Rehabilitation," Circulation, 2019, pp. e69-e89, vol. 140. cited by applicant

Thomas et al., "Home-Based Cardiac Rehabilitation," Journal of the American College of Cardiology, Nov. 1, 2019, pp. 133-153, vol. 74. cited by applicant

Thomas et al., "Home-Based Cardiac Rehabilitation," HHS Public Access, Oct. 2, 2020, pp. 1-39. cited by applicant

Dittus et al., "Exercise-Based Oncology Rehabilitation: Leveraging the Cardiac Rehabilitation Model," Journal of Cardiopulmonary Rehabilitation and Prevention, 2015, pp. 130-139, vol. 35. cited by applicant

Chen et al., "Home-based cardiac rehabilitation improves quality of life, aerobic capacity, and readmission rates in patients with chronic heart failure," Medicine, 2018, pp. 1-5 vol. 97:4. cited by applicant

Lima de Melo Ghisi et al., “A systematic review of patient education in cardiac patients: Do they increase knowledge and promote health behavior change?,” Patient Education and Counseling, 2014, pp. 1-15. cited by applicant

Fang et al., “Use of Outpatient Cardiac Rehabilitation Among Heart Attack Survivors—20 States and the District of Columbia, 2013 and Four States, 2015,” Morbidity and Mortality Weekly Report, vol. 66, No. 33, Aug. 25, 2017, pp. 869-873. cited by applicant

Beene et al., “AI and Care Delivery: Emerging Opportunities For Artificial Intelligence To Transform How Care Is Delivered,” Nov. 2019, American Hospital Association, pp. 1-12. cited by applicant

Jennifer Bresnick, “What is the Role of Natural Language Processing in Healthcare?”, pp. 1-7, published Aug. 18, 2016, retrieved on Feb. 1, 2022 from <https://healthitanalytics.com/features/what-is-the-role-of-natural-language-processing-in-healthcare>. cited by applicant

Alex Bellec, “Part-of-Speech tagging tutorial with the Keras Deep Learning library,” pp. 1-16, published Mar. 27, 2018, retrieved on Feb. 1, 2022 from <https://becominghuman.ai/part-of-speech-tagging-tutorial-with-the-keras-deep-learning-library-d7f93fa05537>. cited by applicant

Kavita Ganesan, All you need to know about text preprocessing for NLP and Machine Learning, pp. 1-14, published Feb. 23, 2019, retrieved on Feb. 1, 2022 from <https://towardsdatascience.com/all-you-need-to-know-about-text-preprocessing-for-nlp-and-machine-learning-bclc5765ff67>. cited by applicant

Badreesh Shetty, “Natural Language Processing (NLP) for Machine Learning,” pp. 1-13, published Nov. 24, 2018, retrieved on Feb. 1, 2022 from <https://towardsdatascience.com/natural-language-processing-nlp-for-machine-learning-d44498845d5b>. cited by applicant

Davenport et al., “The Potential For Artificial Intelligence In Healthcare”, 2019, Future Healthcare Journal 2019, vol. 6, No. 2: Year: 2019, pp. 1-5. cited by applicant

Ahmed et al., “Artificial Intelligence With Multi-Functional Machine Learning Platform Development For Better Healthcare And Precision Medicine”, 2020, Database (Oxford), 2020:baaa010. doi: 10.1093/database/baaa010 (Year: 2020), pp. 1-35. cited by applicant

Ruiz Ivan et al., “Towards a physical rehabilitation system using a telemedicine approach”, Computer Methods in Biomechanics and Biomedical Engineering: Imaging & Visualization, vol. 8, No. 6, Jul. 28, 2020, pp. 671-680, XP055914810. cited by applicant

De Canniere Helene et al., “Wearable Monitoring and Interpretable Machine Learning Can Objectively Track Progression in Patients during Cardiac Rehabilitation”, Sensors, vol. 20, No. 12, Jun. 26, 2020, XP055914617, pp. 1-15. cited by applicant

Boulanger Pierre et al., “A Low-cost Virtual Reality Bike for Remote Cardiac Rehabilitation”, Dec. 7, 2017, Advances in Biometrics: International Conference, ICB 2007, Seoul, Korea, pp. 155-166. cited by applicant

Yin Chieh et al., “A Virtual Reality-Cycling Training System for Lower Limb Balance Improvement”, BioMed Research International, vol. 2016, pp. 1-10. cited by applicant

Website for “Pedal Exerciser”, p. 1, retrieved on Sep. 9, 2022 from <https://www.vivehealth.com/collections/physical-therapy-equipment/products/pedalexerciser>. cited by applicant

Website for “Functional Knee Brace with ROM”, p. 1, retrieved on Sep. 9, 2022 from <http://medicalbrace.gr/en/product/functional-knee-brace-with-goniometer-mbtelescopicknee/>. cited by applicant

Website for “ComfySplints Goniometer Knee”, pp. 1-5, retrieved on Sep. 9, 2022 from <https://www.comfysplints.com/product/knee-splints/>. cited by applicant

Website for “BMI FlexEze Knee Corrective Orthosis (KCO)”, pp. 1-4, retrieved on Sep. 9, 2022 from <https://orthobmi.com/products/bmi-flexeze%C2%AE-knee-corrective-orthosis-kco>. cited by applicant

Website for “Neoprene Knee Brace with goniometer—Patella Rom MB.4070”, pp. 1-4, retrieved

on Sep. 9, 2022 from <https://www.fortuna.com.gr/en/product/neoprene-knee-brace-with-goniometer-patella-rom-mb-4070/>. cited by applicant

Kuiken et al., “Computerized Biofeedback Knee Goniometer: Acceptance and Effect on Exercise Behavior in Post-total Knee Arthroplasty Rehabilitation,” Biomedical Engineering Faculty Research and Publications, 2004, pp. 1-10. cited by applicant

Ahmed et al., “Artificial intelligence with multi-functional machine learning platform development for better healthcare and precision medicine,” Database, 2020, pp. 1-35. cited by applicant

Davenport et al., “The potential for artificial intelligence in healthcare,” Digital Technology, Future Healthcare Journal, 2019, pp. 1-5, vol. 6, No. 2. cited by applicant

Website for “OxeFit XS1”, pp. 1-3, retrieved on Sep. 9, 2022 from <https://www.oxefit.com/xs1>. cited by applicant

Website for “Preva Mobile”, pp. 1-6, retrieved on Sep. 9, 2022 from <https://www.precor.com/en-us/resources/introducing-preva-mobile>. cited by applicant

Website for “J-Bike”, pp. 1-3, retrieved on Sep. 9, 2022 from <https://www.magneticdays.com/en/cycling-for-physical-rehabilitation>. cited by applicant

Website for “Excy”, pp. 1-12, retrieved on Sep. 9, 2022 from <https://excy.com/portable-exercise-rehabilitation-excy-xcs-pro/>. cited by applicant

Website for “OxeFit XP1”, p. 1, retrieved on Sep. 9, 2022 from <https://www.oxefit.com/xp1>. cited by applicant

Alcaraz et al., “Machine Learning as Digital Therapy Assessment for Mobile Gait Rehabilitation,” 2018 IEEE 28th International Workshop on Machine Learning for Signal Processing (MLSP), Aalborg, Denmark, 2018, 6 pages. cited by applicant

Androutsou et al., “A Smartphone Application Designed to Engage the Elderly in Home-Based Rehabilitation,” Frontiers in Digital Health, Sep. 2020, vol. 2, Article 15, 13 pages. cited by applicant

Silva et al., “SapoFitness: A mobile health application for dietary evaluation,” 2011 IEEE 13th International Conference on U e-Health Networking, Applications and Services, Columbia, MO, USA, 2011, 6 pages. cited by applicant

Wang et al., “Interactive wearable systems for upper body rehabilitation: a systematic review,” Journal of NeuroEngineering and Rehabilitation, 2017, 21 pages. cited by applicant

Marzolini et al., “Eligibility, Enrollment, and Completion of Exercise-Based Cardiac Rehabilitation Following Stroke Rehabilitation: What Are the Barriers?,” Physical Therapy, vol. 100, No. 1, 2019, 13 pages. cited by applicant

Nijjar et al., “Randomized Trial of Mindfulness-Based Stress Reduction in Cardiac Patients Eligible for Cardiac Rehabilitation,” Scientific Reports, 2019, 12 pages. cited by applicant

Lara et al., “Human-Robot Sensor Interface for Cardiac Rehabilitation,” IEEE International Conference on Rehabilitation Robotics, Jul. 2017, 8 pages. cited by applicant

Ishraque et al., “Artificial Intelligence-Based Rehabilitation Therapy Exercise Recommendation System,” 2018 IEEE MIT Undergraduate Research Technology Conference (URTC), Cambridge, MA, USA, 2018, 5 pages. cited by applicant

Zakari et al., “Are There Limitations to Exercise Benefits in Peripheral Arterial Disease?,” Frontiers in Cardiovascular Medicine, Nov. 2018, vol. 5, Article 173, 12 pages. cited by applicant

You et al., “Including Blood Vasculature into a Game-Theoretic Model of Cancer Dynamics,” Games 2019, 10, 13, 22 pages. cited by applicant

Jeong et al., “Computer-assisted upper extremity training using interactive biking exercise (iBikE) platform,” Sep. 2012, 34th Annual International Conference of the IEEE EMBS, 5 pages. cited by applicant

International Search Report and Written Opinion for PCT/US2023/014137, dated Jun. 9, 2023, 13 pages. cited by applicant

Website for “Esino 2022 Physical Therapy Equipments Arm Fitness Indoor Trainer Leg Spin Cycle

Machine Exercise Bike for Elderly,” <https://www.made-in-china.com/showroom/esinogroup/product-detailYdZlwGhCMKVR/China-Esino-2022-Physical-Therapy-Equipments-Arm-Fitness-Indoor-Trainer-Leg-Spin-Cycle-Machine-Exercise-Bike-for-Elderly.html>, retrieved on Aug. 29, 2023, 5 pages. cited by applicant

Abeddash, “An Interoperable Electronic Medical Record-Based Platform For Personalized Predictive Analytics”, ProQuest LLC, Jul. 2017, 185 pages. cited by applicant

Gerbild et al., “Physical Activity to Improve Erectile Dysfunction: A Systematic Review of Intervention Studies,” *Sexual Medicine*, 2018, 15 pages. cited by applicant

Chrif et al., “Control design for a lower-limb paediatric therapy device using linear motor technology,” *Article*, 2017, pp. 119-127, Science Direct, Switzerland. cited by applicant

Robben et al., “Delta Features From Ambient Sensor Data are Good Predictors of Change in Functional Health,” *Article*, 2016, pp. 2168-2194, vol. 21, No. 4, *IEEE Journal of Biomedical and Health Informatics*. cited by applicant

Kantoch et al., “Recognition of Sedentary Behavior by Machine Learning Analysis of Wearable Sensors during Activities of Daily Living for Telemedical Assessment of Cardiovascular Risk,” *Article*, 2018, 17 pages, *Sensors*, Poland. cited by applicant

Warburton et al., “International Launch of the Par-Q+ and ePARmed-X+ Validation of the PAR-Q+ and ePARmed-X+,” *Health & Fitness Journal of Canada*, 2011, 9 pages, vol. 4, No. 2. cited by applicant

Ahmed et al., “Artificial Intelligence With Multi-Functional Machine Learning Platform Development For Better Healthcare And Precision Medicine,” *Database (Oxford)*, 2020, pp. 1-35, vol. 2020. cited by applicant

Davenport et al., “The Potential For Artificial Intelligence in Healthcare,” *Future Healthcare Journal*, 2019, pp. 94-98, vol. 6, No. 2. cited by applicant

Jeong et al., “Remotely controlled biking is associated with improved adherence to prescribed cycling speed,” *Technology and Health Care* 23, 2015, 7 pages. cited by applicant

Laustsen et al., “Telemonitored exercise-based cardiac rehabilitation improves physical capacity and health-related quality of life,” *Journal of Telemedicine and Telecare*, 2020, DOI: 10.1177/1357633X18792808, 9 pages. cited by applicant

Blasiak et al., “CURATE.AI: Optimizing Personalized Medicine with Artificial Intelligence,” *SLAS Technology: Translating Life Sciences Innovation*, 2020, 11 pages. cited by applicant

Abidi, Samina; A Knowledge-Modeling Approach to Integrate Multiple Clinical Practice Guidelines to Provide Evidence-Based Clinical Decision Support for Managing Comorbid Conditions; *Journal of Medical Systems* 41.12: 1-19. Springer Nature B.V. (Dec. 2017) (Year: 2017). cited by applicant

Fuller, Carole G.; Diagnosis and treatment considerations with comorbid developmentally disabled populations; *Journal of Clinical Psychology* 54.1: 1-10. John Wiley and Sons Inc. (Jan. 1998) (Year: 1998). cited by applicant

He, Jianxing et al. The practical implementation of artificial intelligence technologies in medicine. *Nature Medicine*; New York vol. 25, Iss. 1. Jan. 2019. (Year: 2019). cited by applicant

CG. Acampora, D. J. Cook, P. Rashidi and A. V. Vasilakos, “A Survey on Ambient Intelligence in Healthcare,” in *Proceedings of the IEEE*, vol. 101, No. 12, pp. 2470-2494, Dec. 2013, doi: 10.1109/JPROC.2013.2262913. (Year: 2013). cited by applicant

H. Demirkan, “A Smart Healthcare Systems Framework,” in *IT Professional*, vol. 15, No. 5, pp. 38-45, Sep.-Oct. 2013, doi: 10.1109/MITP.2013.35. (Year: 2013). cited by applicant

W. Rashwan, J. Fowler and A. Arisha, “A Multi-Method Scheduling Framework for Medical Staff,” 2018 Winter Simulation Conference (WSC), Gothenburg, Sweden, 2018, pp. 1464-1475, doi: 10.1109/WSC.2018.8632247. (Year: 2018). cited by applicant

Marios et al., “The effect of tele-monitoring on exercise training adherence, functional capacity,

Primary Examiner: Robertson; Jennifer

Assistant Examiner: Patel; Nidhi N

Attorney, Agent or Firm: Dickinson Wright PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a divisional (and claims priority and benefit) of U.S. patent application Ser. No. 17/017,062, filed Sep. 10, 2020, which claims priority to and the benefit of: U.S. Prov. Pat. App. No. 62/991,295, filed Mar. 18, 2020, U.S. Prov. Pat. App. No. 62/911,515, filed Oct. 7, 2019, U.S. Prov. Pat. App. No. 62/904,013, filed Sep. 23, 2019, U.S. Prov. Pat. App. No. 62/901,464, filed Sep. 17, 2019, and U.S. Prov. Pat. App. No. 62/901,411, filed Sep. 17, 2019. (2) Each of these above-referenced applications is incorporated herein by reference in its entirety.

TECHNICAL FIELD

(1) This disclosure generally relates to wearable devices and, in particular, to coupling a wearable device to a user and measuring and monitoring activity of the user.

BACKGROUND

(2) A patient often requires physical therapy to recover from surgery, such as a knee replacement surgery. The physical therapy can include exercise to increase the patient's strength, flexibility and stability. If a patient over-extends his or her muscles or joints, the muscles or joints, surrounding tissues or repaired tissues may become further injured. If a patient does not exercise his or her muscles or joints to gain the appropriate range of motion, the joint may become stiff and require additional surgery. Measuring and monitoring the range of motion during physical therapy can help prevent further injury to the patient and result in a faster recovery time.

(3) A goniometer is an instrument that can be used to measure ranges of motion or joint angles of a patient's body. A standard goniometer consists of a stationary arm that cannot move independently, a moving arm attached to a fulcrum in the center of a body, and the body being a protractor of which 0 to 180 or 360 degrees are drawn. The stationary arm is attached to one limb or part of the patient's body (e.g., a thigh) and the moving arm is attached to another limb or part of the patient's body (e.g., a lower leg). The fulcrum can be a rivet or screw-like device at the center of the body that allows the moving arm to move freely on the body of the device in order for a clinician to obtain a measurement of the angle of movement of the patient's joint (e.g., a knee). The measurements can be used to track progress in a rehabilitation program. Each time a patient has a rehabilitation session, the clinician places and hold, or attaches the goniometer device onto the patient, for example, using straps. The patient may have different clinicians setting up the goniometer device and measuring the joint movement. Based on the experience of the clinician, or other person, the goniometer device may be attached onto different locations on the patient, which can affect the accuracy and reproducibility of the measurements. The accuracy of the repeated measurements may also be compromised due to issues with or the sensitivity of the device.

SUMMARY

(4) Exemplary implementations of a system for measuring an angle of a joint of a user are disclosed. The system can include a center hub, a first arm, a second arm, a magnet, and a sensor. The center hub includes a first hub and a second hub. The first arm is configured for attachments to

a first limb portion of the user at a first outer end and to the first hub at a first inner end. The second arm is configured for attachments to a second limb portion of the user at a second outer end and to the second hub at a second inner end, wherein the first hub is pivotally coupled to the second hub. The magnet is coupled to the second hub. The sensor is disposed in the center hub and configured to detect a rotation of the magnet.

(5) Other implementations of a system for measuring an angle of a joint of a user can include a center hub, first and second coupling apparatuses, and first and second arms. The center hub has a first hub and a second hub. The first arm is configured for attachment to a first limb portion of the user at a first outer end and to the first hub at a first inner end. The second arm is configured for attachment to a second limb portion of the user at a second outer end and to the second hub at a second inner end, wherein the first hub is pivotally coupled to the second hub and configured to rotate 360 degrees about an axis. The system further comprises a magnet, a printed circuit board (PCB), and a sensor. The magnet is coupled to the second hub. The PCB is removably disposed in the center hub. The sensor is coupled to the PCB and configured to detect a rotation of the magnet.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The disclosure is best understood from the following detailed description when read in conjunction with the accompanying drawings. It is emphasized that, according to common practice, the various features of the drawings are not to scale. On the contrary, the dimensions of the various features are arbitrarily expanded or reduced for clarity.

(2) For a detailed description of example embodiments, reference will now be made to the accompanying drawings in which:

(3) FIGS. 1A and 1B are perspective views of a wearable device for measuring and recording movement in accordance with aspects of the present disclosure.

(4) FIGS. 2A and 2B are top and bottom perspective views of a goniometer in accordance with aspects of the present disclosure.

(5) FIGS. 3A and 3B are top and side views of a goniometer in accordance with aspects of the present disclosure.

(6) FIG. 4 is an exploded view of a goniometer in accordance with aspects of the present disclosure.

(7) FIGS. 5A-C are side views of the goniometer with its arms rotating in accordance with aspects of the present disclosure.

(8) FIG. 6 is a perspective view of the goniometer with its arms twisting in accordance with aspects of the present disclosure.

(9) FIGS. 7A-D are top schematic views of the attachment in accordance with aspects of the present disclosure.

(10) FIGS. 8A-D are views of an attachment in accordance with aspects of the present disclosure.

(11) FIGS. 9A-D are views of first and second layers of the attachment in accordance with aspects of the present disclosure.

(12) FIGS. 10A-D are views of a pod of the attachment in accordance with aspects of the present disclosure.

(13) FIGS. 11A and 11B are perspective and cross-sectional views of a coupling apparatus in accordance with aspects of the present disclosure.

(14) FIGS. 12A and 12B are perspective views of the attachment and a goniometer attachment in accordance with aspects of the present disclosure.

(15) FIG. 13 is a cross sectional view of the goniometer in accordance with aspects of the present disclosure.

- (16) FIGS. **14A-C** are perspective and top views of a center hub of the goniometer closed, open, and with components removed in accordance with aspects of the present disclosure.
- (17) FIGS. **15A** and **15B** are top and bottom views of a printed circuit board (PCB) in accordance with aspects of the present disclosure.
- (18) FIGS. **16A** and **16B** are graphs illustrating test data in accordance with aspects of the present disclosure.
- (19) FIG. **17** is a perspective view of the alignment device, with the alignment device shown aligned relative to the center of the joint of the user.
- (20) FIG. **18** is a perspective view of the user illustrating the markings on the skin of the user at the center of the joint, and on the opposing limb portions.
- (21) FIG. **19** is a perspective view illustrating the attachments being aligned with the markings on the opposing limb portions.
- (22) FIG. **20** is a perspective view illustrating the wearable device being coupled to the attachment, and aligned relative to the center of the joint.
- (23) FIG. **21** is a perspective view illustrating an alternative embodiment of the alignment device, and illustrating the light beams at the center of the joint and on the opposing limb portions, which are configured to assist the clinician in aligning the attachments and wearable device relative to the center of the joint.
- (24) FIG. **22** is a perspective view illustrating yet another alternative embodiment of the alignment device, and illustrating the diodes at the center of the joint, on the opposing limb portions, and on the wearable device.
- (25) FIGS. **23A-23E** are various views of an embodiment of a pedometer that may be coupled to the goniometer.
- (26) FIG. **24** is a plan view of another embodiment of an alignment device.
- (27) FIGS. **25-34** are schematic sequential images of an embodiment of alignment and installation method.

NOTATION AND NOMENCLATURE

- (28) Various terms are used to refer to particular system components. Different companies may refer to a component by different names—this document does not intend to distinguish between components that differ in name but not function. In the following discussion and in the claims, the terms “including” and “comprising” are used in an open-ended fashion, and thus should be interpreted to mean “including, but not limited to” Also, the term “couple” or “couples” is intended to mean either an indirect or direct connection. Thus, if a first device couples to a second device, that connection may be through a direct connection or through an indirect connection via other devices and connections.
- (29) The terminology used herein is for the purpose of describing particular example embodiments only, and is not intended to be limiting. As used herein, the singular forms “a,” “an,” and “the” may be intended to include the plural forms as well, unless the context clearly indicates otherwise. The method steps, processes, and operations described herein are not to be construed as necessarily requiring their performance in the particular order discussed or illustrated, unless specifically identified as an order of performance. It is also to be understood that additional or alternative steps may be employed.
- (30) The terms first, second, third, etc. may be used herein to describe various elements, components, regions, layers and/or sections; however, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms may be only used to distinguish one element, component, region, layer or section from another region, layer or section. Terms such as “first,” “second,” and other numerical terms, when used herein, do not imply a sequence or order unless clearly indicated by the context. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings of the example embodiments. The phrase “at least one of,” when used

with a list of items, means that different combinations of one or more of the listed items may be used, and only one item in the list may be needed. For example, “at least one of: A, B, and C” includes any of the following combinations: A, B, C, A and B, A and C, B and C, and A and B and C. In another example, the phrase “one or more” when used with a list of items means there may be one item or any suitable number of items exceeding one.

(31) Spatially relative terms, such as “inner,” “outer,” “beneath,” “below,” “lower,” “above,” “upper,” “top,” “bottom,” and the like, may be used herein. These spatially relative terms can be used for ease of description to describe one element's or feature's relationship to another element(s) or feature(s) as illustrated in the figures. The spatially relative terms may also be intended to encompass different orientations of the device in use, or operation, in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, elements described as “below” or “beneath” other elements or features would then be oriented “above” the other elements or features. Thus, the example term “below” can encompass both an orientation of above and below. The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptions used herein interpreted accordingly.

DETAILED DESCRIPTION

(32) The following discussion is directed to various embodiments of the invention. Although one or more of these embodiments may be preferred, the embodiments disclosed should not be interpreted, or otherwise used, as limiting the scope of the disclosure, including the claims. In addition, one skilled in the art will understand that the following description has broad application, and the discussion of any embodiment is meant only to be exemplary of that embodiment, and not intended to intimate that the scope of the disclosure, including the claims, is limited to that embodiment.

(33) In accordance with aspects of the present disclosure, FIGS. 1A and 1B illustrate an exemplary system or wearable device **100** for measuring and recording flexion and extension at a joint **107** of a user **102**. The wearable device **100** comprises first and second coupling apparatuses, or attachments, **112**, **114**, **118**, **120** (hereinafter referred to as first and second attachments **118**, **120**) and may be configured to be removably coupled to the user **102** at opposing limb portions **104**, **106** of the joint **107**. For example, and as illustrated in FIGS. 1A and 1B, the first and second attachments **118**, **120** may be coupled to a leg of a user at opposing limb portions **104**, **106**, e.g., thigh **104**, and calf **106**, of the knee or joint **107** of the user **102**. As will be appreciated by those of skill in the art, the first and second attachments **118**, **120** may be coupled to the user at opposing limb portions of any other joint of a patient or user **102**. It is further contemplated that the wearable device **100** may be utilized for measuring flexion and extension of joints in animals, a joint of a robot, or any other desired joint or joint equivalent.

(34) To position the wearable device **100** relative to the joint **107**, a person, such as a clinician, may identify a joint center **108**, where the joint center **108** may be used to align the wearable device **100** to the joint **107**. The clinician may use an alignment device **300** to identify and mark the joint center **108**. For example, the alignment device **300** may be used to mark the skin of the user **102** at the joint center **108** with a marker, pen, or any other desired tool. Further, the alignment device **300** may be used to identify and mark positions at opposing limb portions **104**, **106** for the first and second attachments **118**, **120** relative to the joint center.

(35) With reference to FIGS. 2A-6, the wearable device **100** comprises an exemplary device or apparatus **110**, such as a goniometer. Hereinafter, the device or apparatus **110** may be referred to as a goniometer **110**. The goniometer **110** is configured to measure the angular flexion and extension at the joint **107** of the user **102**. The goniometer **110** has a top **122**, a bottom **124**, and opposing sides **126**. The goniometer **110** may comprise a center hub **116** aligned coaxially with an axis A, and first and second arms **128**, **130**, wherein the arms **128**, **130** couple to, and are rotatable about, the axis A and the center hub **116**. More specifically, first and second inner ends **132**, **134** of the respective arms **128**, **130** couple to the center hub **116**. The arms **128**, **130** extend outwardly from

the center hub **116** to respective first and second outer ends **168**, **170**. In an alternative embodiment, the arms **128**, **130** may be integrally formed with the center hub **116**. Embodiments of the goniometer can enable various rotational or pivotal motions, such as with an axle, a rack and pinion system, etc.

(36) With reference to FIGS. 3A and 3B, the goniometer **110** can have a length L that extends from the first outer end **136** to the second outer end **138**. The length L can vary depending on the relative position of the first and second arms **128**, **130**. For example, a maximum length L of the goniometer **110** may be measured when the arms **128**, **130** are positioned opposing one another. Whereas, when the arms **128**, **130** are positioned parallel, and respectively directly above and below one another, a minimum length L of the goniometer **110** may be measured between the outer ends **136**, **138** to an opposite side of the center hub **116**. A width W of the goniometer may be measured as a diameter of the center hub **116**. Further, a height H of the goniometer **110** may be measured from a bottom of the second arm **130** to a top of the first arm **128**, or to a top of the center hub **116**, whichever is greater.

(37) In an exemplary embodiment, the center hub **116** comprises a first or upper hub **146** and a second or lower hub **148**. The hubs **146**, **148** are coaxially aligned with one another, and with axis A. Moreover, the hubs **146**, **148** may be configured to rotate about the axis A for 360 degrees, and relative to one another. Further, each of the hubs **146**, **148** may have a link arm **143** for coupling between the hubs **146**, **148** and the respective arms **128**, **130**. For example, the first arm **128** may be coupled to the link arm **143** of the first hub **146**, and the second arm **130** may be coupled to the link arm **143** of the second hub **148**.

(38) In operation, embodiments of the arms **128**, **130** may rotate, pivot, flex or extend relative to the center hub **116**. This design can account for the complex motion of a joint, slippage of the joint, and the broad range of shapes and sizes of the patient's joint **107**. In addition, this design can maintain the position of the center hub relative to the joint center **108**. Embodiments of the device can enable freedom of motion in many planes but not in the rotational plane of the joint. This enables the device to fit many different people but still make accurate measurements.

(39) More specifically, and as best illustrated in FIG. 4, the first and second arms **128**, **130** may each include an inner link **142** disposed adjacent to the respective inner ends **132**, **134**, and an outer link **144** disposed between the inner link **142** and the outer ends **168**, **170**. With reference to FIGS. 5A-C, the inner link **142** may couple to the link arm **143** in order to couple between respective arms **128**, **130** and hubs **146**, **148**. The inner link **142** may be configured to facilitate the pivot, flex, or extension of the respective arm **128**, **130** relative to the center hub **116**. A pin **164** may be used to couple the inner link **142** and the link arm **143** of each arm **128**, **130** to allow for the pivot, flexion, or extension of the respective arms **128**, **130**. The pin **164** may be disposed perpendicular to the length of the arms **128**, **130**.

(40) The outer link **144** may couple to the inner link **142** and respective outer ends **136**, **138**. With reference to FIG. 6, the outer link **144** may be configured to couple to the inner link **142** to facilitate rotation of the respective arms **128**, **130** relative to the center hub **116**. A screw **162** may be configured to couple the outer link **144** to the inner link **142** to facilitate rotation of the respective arms **128**, **130** about the screw **162**, all relative to the center hub **116**. The screw **162** may align parallel with the length of the respective arm **128**, **130**. It is to be appreciated that the first and second arms **128**, **130** may rotate +/- eighteen degrees, or any other desired amount, in one or more directions. Further yet, and with reference to FIGS. 5A-C, the outer link **144** may be configured to couple to the respective outer ends **136**, **138** to facilitate further pivot, flexion, or extension of the respective arms **128**, **130** relative to the center hub **116**. A pin **164** may be used to couple the outer link **144** and the respective outer ends **136**, **138** to allow for further pivot, flexion, or extension, of the respective arms **128**, **130** relative to the center hub **116**. The pin **164** may be disposed perpendicular to the length of the respective arms **128**, **130**.

(41) The first and second outer ends **136**, **138** may comprise first and second goniometer

attachments **168, 170**, which may be integral with, or coupled to the respective outer ends **136, 138**. It is to be appreciated the goniometer attachments **168, 170** may couple, or be integral with, the arms **128, 130** at any desired location, or in any desired configuration. The first and second goniometer attachments **168, 170** may be configured to removably couple with the attachments **118, 120**. Further, each goniometer attachment **168, 170** can comprise one or more bosses **200**, and one or more magnets **158** positioned next to the bosses **200** to facilitate the coupling and alignment of the goniometer attachments **168, 170** and the attachments **118, 120**. The bosses **200** and magnets **158** further facilitate the alignment of the goniometer **110** relative to the attachments **118, 120**. The arms **128, 130** may also include one or more arm alignment holes **140** configured to align with the attachments **118, 120**, or an alignment mark on a user **102**. The arms **128, 130** may further have one or more wings **202** that extend from a side **126** of the goniometer **110**, such as from the first or second goniometer attachments **168, 170**. The wings **202** can be formed from or coupled to the first or second goniometer attachments **168, 170**. The wings **202** can be a tab or have any other desired shape. The wings **202** may be configured to assist a user in moving the arms **128, 130** of the goniometer perpendicularly relative to the attachments to facilitate uncoupling the goniometer **110** from the attachments **118, 120** without uncoupling the attachments **118, 120** from the user **102**.

(42) With reference to FIGS. 7-9, the attachments **118, 120** may comprise first and second layers **172, 174** and a pod **176** coupled together with one another. When coupled to one another, each of the layers **172, 174** and the pod **176** may be concentric with one another. The first attachment **118** may be the same as and interchangeable with the second attachment **120**. The first layer **172**, the second layer **174**, and the pod **176** may be generally oval-shaped or any other desired shape. The first layer **172** may be larger than the second layer **174**, and the second layer **174** may be larger than the pod **176**. Further, the first layer **172** may be thinner than the second layer **174**, and the pod **176** can be thicker than the first and second layers **172, 174**.

(43) The first layer **172** may have a top **182** and a bottom **184**, and may be formed from a pad, coated paper, plastic, woven fabric, latex, or any other desired material. For example, the top **182** may be formed from a pad and the bottom **184** may comprise an adhesive material **236**, such as a medical-grade adhesive or other suitable material. The adhesive material **236** couples to the skin of the user **102** to couple the attachments **118, 120** to the user **102**. Further, the top **182** may also have an adhesive layer **194**, which may be smaller in area than the first layer **172**. Further, the adhesive layer **194** can be less than or equal to the area of the second layer **174**. The adhesive layer **194** may be ovular in shape, and define one or more notches or voids in an outer periphery. Further, the first layer **172** can define notches **180** in an outer periphery for assisting in aligning the first attachment **118** relative to a predetermined location, or mark, on the user **102**. The notches **180** can be v-shaped or have any other desired shape. Further yet, the first layer **172** may define a pair of voids or alignment holes **178**, which may assist in the alignment of the first attachment **118** relative to a predetermined location, or mark, on the user **102**. The alignment holes **178** and notches **118** of the first layer **172** may be the same as, or aligned with, the notches or voids of the adhesive layer **194**.

(44) The second layer **174** may have a top **186** and a bottom **188**, and may be formed of a foam material or any other desired material. The second layer **174** may couple to the adhesive layer **194** of the first layer **172**. To prevent uncoupling, the foam material of the second layer **174** may dampen forces between the goniometer **110** and the attachments **118, 120**. The top **186** of the second layer **174** may also have an adhesive layer **195** on an upper surface **238** of the top **186**, which may be smaller in area than the area of the pod **176**. The adhesive layer **195** may have an ovular shape, or any other desired shape. Further, the adhesive layer **195** and the second layer **174** may have one or more holes, or one or more cutouts that may be aligned with the alignment hole **178** of the first layer **172** to align the adhesive layer **195** and the second layer **174** with the first layer **172**. The adhesive layers **194, 195** can be formed of an adhesive material or any other desired coupling material, such as a hook- or a loop-type material. The first layer **172** can have a length **L1** and a width **W1**. The second layer **174** can have a length **L2** and a width **W2**. The adhesive layer

195 can have a length **L3** and a width **W3**.

(45) As illustrated in FIGS. **10A-D**, the pod **176** has a top **190** and a bottom **192**. The pod **176** can include one or more notches **196**. For example, notches **196** can be located at opposing ends of the pod **176**. The notches **196** can be used for alignment of the first coupling apparatus **112**, the pod **176**, or any other desired feature of the wearable device **100**. The pod **176** can include one or more magnets **160**. The magnet **160** may be a neodymium magnet or any other desired magnet. The pod **176** can have a recess for housing the magnet **160**. The magnet **160** can be circular or any other desired shape. Two magnets **160** can be disposed in the pod **176** at opposing ends of the pod **176**. The pod **176** can be sized to be received by and detachably coupled to the upper surface **238** of the second layer **174**.

(46) More specifically, the pod **176** has an underside, such as the bottom **192**, which may couple to the upper surface **238** of the second layer **174**. The bottom **192** can have one or more hooks or loops, to couple to the upper surface **238**. Alternatively, the upper surface **238** and the bottom **192** may comprise an adhesive material to facilitate the detachable coupling between the upper surface **238** and the pod **176**. The top **190** of the pod **176** may have one or more recesses **198**. The recess **198** may be ovular in shape or have any other desired shape. The recesses **198** may also have tapered edges to assist a user **102** in uncoupling from the pod **176** by moving the arms **128**, **130** perpendicularly relative to the pod **176**. Two recesses **198** may be formed in the pod **176** at opposing ends or sides of the pod **176**.

(47) With reference to FIGS. **11-12**, the recesses **198** are sized to receive the bosses **200** to align the goniometer **110** relative to the attachments **118**, **120**. Moreover, the recesses **198** are sized to allow slight movement of the bosses **200** to compensate for slight translational movement of the joints **128**, **130** while the goniometer **110** is worn by the user **102**. This movement may reduce the stress between, and prevent uncoupling of, the attachments **118**, **120** to the skin, clothing, brace, or any other desired location on the user **102**.

(48) When the user **102** moves the first or second limb portions **104**, **106**, the first or second arms **128**, **130** move or rotate with the first and second hubs **146**, **148**. The goniometer **110** can measure the rotation of joint **107** by measuring the angle between the first and second hubs **146**, **148**. To achieve this, and with reference to FIGS. **4**, **13-15**, the center hub **116** defines an opening for receiving and containing a printed circuit board (PCB) **152**, a sensor **216**, a retaining ring **154**, a magnet **156**, or any other components of the goniometer **110** which cooperate with one another to measure relative angular movement between the arms **128**, **130**. More specifically, the first and second hubs **146**, **148** may define the opening of the center hub **116**.

(49) For enclosing the opening, a cover **150** may be attached to the center hub **116**, and more specifically to the first hub **146**. The cover **150** can be detachably coupled to the first hub **146** or any other desired location. The cover **150** can also be configured to inhibit movement of the PCB **152** and other components located within the center hub **116**. For example, when the cover is closed, a bottom portion of the cover **150** may apply direct or indirect pressure to the PCB **152**. The cover **150** may have a snap mechanism **226**, such as a finger snap or any other desired mechanism, configured to attach and detach the cover to the center hub **116**.

(50) The magnet **156** may couple to the second hub **148**, and the sensor **216** also disposed in the center hub **116** is configured to detect rotation of the magnet **156**. The sensor **216** can be configured to measure the rotation of the magnet **156** to a sensitivity up to one-hundredth of a degree, or to any other desired sensitivity.

(51) As illustrated in FIGS. **13-14C**, the center hub **116** includes the first hub **146** positioned rotatably above the second hub **148**. An outward notch **208** may be coupled to the first hub **146**, or any other desired location. The outward notch **208** may be formed with the first hub **146** or attached to the first hub **146**. The PCB **152** may be removably disposed in the center hub **116**. The PCB **152** may have an inward notch **210**. The outward notch **208** may be configured to couple with the inward notch **210** to align the sensor **216** and the magnet **156**. The alignment can restrict

movement of the PCB 152 within the center hub 116.

(52) When the cover 150 is removed, the PCB 152 may be accessed. FIG. 14B illustrates a battery housing 206 coupled to the PCB 152. The battery housing 206 may be attached to a top side 212 of the PCB 152. The battery housing 206 may be formed of conductive metal or any other desired material. When the cover 150 is attached to the first hub 146, the cover 150 may apply pressure to the battery housing 206, which may secure PCB 152 within the center hub 116. A battery 204 may be detachably coupled to the battery housing 206. The battery 204 may be a lithium ion battery or any other desired battery or power source. The battery housing 206 may have tabs or any other desired contact points for conduction with the battery 204. The battery 204 may be removed from the battery housing 206 to turn the goniometer 110 off or for replacement of the battery 204. For example, when the cover 150 is opened or removed from the first hub 146, the PCB 152 may be removed from the center hub 116 and the battery 204 may be replaced. To maintain calibration of the goniometer 110 after a battery replacement, the inward notch 210 of the PCB 152 is configured for receiving the outward notch 208 of the first hub 146.

(53) In FIG. 14C, the cover 150 and the PCB 152 are removed from the center hub 116. As shown, the second hub 148 may include a magnet housing 224. The magnet housing 224 may be located in the center of the second hub 148 or any other desired location. The magnet housing 224 may be coupled to the PCB 152 using a weld, an adhesive, a tack, or any other desired attachment. The magnet housing 224 may be configured to receive the magnet 156. The magnet 156 may be configured to have north and south polarity within the center hub 116 or any other desired polarity. The magnet housing 224 may include a lip at a top of the magnet housing 224 or have any other desired configuration. The retaining ring 154 may be configured to couple the magnet 156 to the second hub 148. The retaining ring 154 may be coupled to the second hub 148 around the magnet housing 224. For example, the retaining ring 154 may be positioned between the lip or top of the magnet housing 224 and the second hub 148. The retaining ring 154 may secure the magnet within the magnet housing 224. The retaining ring 154 may move with the second hub 148 and the magnet 156 as the second hub 148 rotates with the second arm 130.

(54) FIG. 15A illustrates the top side 212 of the PCB 152. As described above, the battery housing 206 may be attached to the top side 212. FIG. 15B illustrates a bottom side 214 of the PCB 152 in accordance with aspects of the present disclosure. The PCB 152 includes components coupled to the bottom side 214. The components may comprise a circuit 220 including resistors, LEDs, transistors, capacitors, inductors, transducers, diodes, switches, the sensor 216, a transmitter 222, or any other desired component. The components may be attached to the PCB 152 using a surface mount method, a through-hole method, or any other desired method. The PCB 152 may include additional and/or fewer components and is not limited to those illustrated in FIGS. 15A and B.

(55) The circuit 220 may be configured to generate an electrical signal based on the rotation of the magnet 156. The circuit 220 may be configured to transmit the electrical signal in real time. The circuit 220 may transmit the electrical signal. For example, a transmitter 222 may be coupled to the PCB 152 and configured to transmit an electrical signal based on the rotation of the magnet 156 to an external device. The transmitter 222 may include wired or wireless transmission, such as Bluetooth™, WiFi, NFC or any other means or method of desired transmission. The external device may be a mobile phone, a computer, a tablet, or any other desired device. The external device may have a user interface. The user interface may be configured to receive the electrical signal and display data obtained from the electrical signal. The data may include the angle of the joint 107, or any other desired information.

(56) The user interface may include an app that receives the data, manipulates the data, records the data, and displays aspects of the data. For example, the app may display the angle of the joint 107 of a user 102, a history of the angle of the joint 107, duration of the angle, or any other desired information, such as a measurement of the angle in real time.

(57) The sensor 216 may be a Hall Effect sensor, or any other desired sensor (e.g., a magnetic

position sensor AS5601 using internal MEMS Hall Effect sensors). The sensor **216** may be coupled to the PCB **152** or any other desired device. The sensor **216** may be coupled to the bottom side **214** of the PCB **152** at a location directly above the magnet **156** when the PCB **152** is disposed within the center hub **116**. The PCB **152** and the sensor **216** may rotate with the first hub **146** and the first arm **128**. The magnet **156** may rotate with the second hub **148** and the second arm **130**. The design of the wearable device **100**, including the configuration of the sensor **216** and the magnet **156**, may improve the accuracy of the measurements of the angle of the joint **107**.

(58) FIG. **16A** is an exemplary graph **228** with line **232** depicting, while the wearable device **100** is attached to the user **102**, the accuracy of measurements of angles of the joint **107** by the wearable device **100**. FIG. **16B** is an exemplary graph **230** with line **234** depicting the accuracy of measurements of angles of the joint **107** by a different measurement device attached to a user using Velcro™ straps. The standard deviation of the measurements made by the different measurement device shown by line **234** is greater than the standard deviation of the measurements made by the wearable device **100** shown by line **232**. Users, such as clinicians or patients, are able to more accurately initially place and realign the first and second attachments **118** and **120** of the wearable device **100** as compared to using the Velcro™ straps. The configuration of the first and second arms **128**, **130** of the wearable device **100** to fit different users may increase accuracy of the measurements. The configuration of the components, including the PCB **152**, the sensor **216**, and the magnet **156** within the center hub **116** of the wearable device **100** may further increase accuracy of the measurements. The wearable device **100** may be configured to measure the angle of the joint **107** up to an accuracy of measurement up to a one hundredth degree. The different measurement device may have an accuracy up to five degrees. In other words, the measurements taken by the different measurement device may have an accuracy of about $\pm$ five degrees, such as about ± 1 degree, or even $\pm$ about 0.01 degree from the actual angle of the joint **107**.

(59) With reference to FIGS. **17** and **18**, the alignment device **300** may be used to assist a clinician to align the wearable device **100** (see FIG. **20**) on opposing limb **104**, **106** portions of the joint **107** of the user **102** relative to a center of the joint **107**. Properly aligning the wearable device **100** relative to the joint **107** facilitates greater accuracy and precision of the measurements made with the wearable device **100**. Hence, the need for a device, such as alignment device **300**, to assist in aligning the wearable device **100** relative to the joint **107** of a patient **102**.

(60) The alignment device **300** comprises a first segment **302** and a second segment **304** pivotably coupled to the first segment **302** at a pivot point P. More specifically, the segments **302**, **304** each have a coupling end **306** where the segments **302**, **304** pivotably couple to one another at the pivot point P. Moreover, the pivot point P is spaced adjacently and equidistant from each coupling end **306** of the segments **302**, **304**. Further yet, when the segments **302**, **304** are pivotally coupled, center axes C of each segment **302**, **304** intersect at the pivot point P.

(61) The alignment device **300** further includes voids **308** defined by each segment **302**, **304**, and the voids **308** facilitate the marking of the skin of the user **102** during use of the alignment device **300**. The voids **308** are spaced equidistant on each segment **302**, **304** from the pivot point P, and the spacing between, and size, of each void **308** is commensurate with the spacing between, and size, of each alignment hole **178** of the attachments **118**, **120** (see FIGS. **19** and **20**). Further yet, when the attachments **118**, **120** are coupled to the goniometer attachments **168**, **170**, the spacing between, and position of, each void **308** and the pivot point P is commensurate with the spacing between the center hub **116** and the alignment holes **178** of the attachments **118**, **120**.

(62) Using the alignment device **300**, the clinician may locate the center of the joint **107** of the user **102**, and then position the pivot point P at the center of the joint **107**. When the joint **107** of the user **102** is a knee, the clinician may locate the lateral epicondyle of the knee, and position the pivot point P adjacent to the lateral epicondyle. With the pivot point P positioned adjacent to the lateral epicondyle, the clinician may centrally position each segment **302**, **304** adjacent to the opposing limb portions **104**, **106** of the joint **107**. The clinical may rely on the center axes C of each segment

302, 304 to assist in centrally aligning with the segments **302, 304** to the opposing limb portions **104, 106**. With reference to FIGS. **17** and **18**, with the segments **302, 304** centrally aligned with the opposing limb portions **104, 106**, the clinician may use the voids **308** to mark the skin of the user **102**. Thereafter, and with reference to FIGS. **19** and **20**, the clinician may coaxially align the alignment holes **178** of the attachments **118, 120** with the markings on the skin of the user **102** to facilitate the alignment, and coupling to the user **102**, of the wearable device **100** relative to the center of the joint **107**. Further, the clinician may use pegs to assist in aligning with the attachments **118, 120** coaxially with the marks.

(63) Alternatively, and with reference to FIGS. **21** and **22**, an alignment device **400** may be used to assist a clinician to facilitate the alignment of the wearable device **100** relative to a center of the joint **107** of the user. More specifically, alignment device **400** may rely on data from an imaging device **402** of the joint **107** to assist the clinician in positioning the wearable device **100** on the user **102**. The imaging device **402** may be an x-ray, ultrasound, any other imaging device capable of providing image data in 2D, 3D or 4D to the alignment device **400**, or any other imaging device. A processor **404** of the alignment device **400** receives and processes the image data from the imaging device **402**, and the processor **400** facilitates communication from the alignment device **400** to the clinician for the proper positioning of the attachments **118, 120**, or the wearable device **100**.

(64) In one embodiment, and with reference to FIG. **21**, the alignment device **400** may include one or more lasers **406** that produce a light beam. In this embodiment, the processor **404** may communicate with the lasers **406** to cause the lasers **406** to be positioned such that light beams causes spots of light on the skin of the user **102** on the center of the joint **107** and on opposing limb portion **104, 106**. The spacing between, and size of, the spots of light are commensurate with the spacing between, and size of, each alignment hole **178** of the attachments **118, 120**. The clinician may rely on the spots to align the wearable device **100** to center of the joint **107**. Alternatively, the clinician may mark the locations of the spots of light on the skin, similar to the markings used with alignment device **300**, and rely on the markings to align the wearable device **100** to the center of the joint **107**. Further yet, the wearable device **100** may have indicia which the clinician may align with the light beams to facilitate alignment of the wearable device **100**. In yet another alternative, the light beam may create an outline of the wearable device **100** on the skin of the user **102**, where the outline may be commensurate to a perimeter of the wearable device, and may be used to properly align the wearable device **100** to the center of the joint **107**.

(65) In another embodiment of the alignment device **400**, and with reference to FIG. **22**, to assist the clinician in aligning the wearable device **100** relative to a center of the joint **107** of the user **102**, the imaging device **402** may communicate with diodes **408** positioned on the user **102** and/or the wearable device **100**. The diodes **408** may provide position data to the processor **404** such that the processor **404** may communicate with, and position, the lasers **406** to assist the clinician in the positioning of the attachments **118, 120**. Alternatively, with the position data of the diodes **408**, the processor **404** may communicate, to the clinician, with a clinician communication device **410**, to assist in the alignment of the wearable device **100**. Further yet, the wearable device **100** may also have diodes **408**, which may communicate with the imaging device **402**. Relying on position data of the diodes **408** from the imaging device **402**, the processor **404** may cause the speaker **412** or the display **414** to provide respective audio or image outputs to communicate instructions, to the clinician, to facilitate the alignment of the wearable device **100**. For example, the speaker **412** may provide audio guidance to the clinician, such as “move wearable device 5 mm to the left,” to assist in the positioning of the wearable device **100**. In another example, the display **414** may provide visual guidance to the user **107** on the location of the wearable device **100**, and instructions for adjusting its position to achieve proper alignment. The display **414** may be a monitor, or iPad, or any other device for providing an image to the user, such as 3D goggles. Of course, any of the above techniques could be used in combination with one another to assist the clinician to properly align the wearable device **100**.

(66) FIGS. 23A-23E depict an embodiment of an ambulation monitor or pedometer **1701**. Versions of the pedometer **1701** can count the number of steps that a user takes, such as a daily count of steps post-operatively. Such a device can be carried by the user or attached to the user or to a peripheral of the user, such as the goniometer **110**. The pedometer **1701** is operational to track steps of the user even if the user requires a walker or other assistance device.

(67) In some versions, the pedometer **1701** can include the ability to attach to the magnets of the goniometer **110** to ensure accurate tracking of all steps of the user. The pedometer **1701** can include metallic elements that are magnetically attracted to the magnets of the goniometer **110**. Alternatively, additional magnets **1703** mounted to the pedometer **1701**. Embodiments of the pedometer **1701** can further include a body **1705**, a removable cap **1707**, a circuit board **1709** including one or more sensors (e.g., a motion sensor such as an accelerometer, mechanical sensor or other electromechanical sensor), a battery **1711** and fasteners **1713**.

(68) FIG. 24 is a plan view of another embodiment of an alignment device **1300**. Alignment device **1300** can be used in manners that are similar to the previously described alignment devices.

(69) FIGS. 25-34 are schematic sequential images of an embodiment of alignment and installation method. As shown in FIG. 25, the patient or user can change their own pods **176**. Alternatively, another person can help the user change their pods **176**. Although these images are shown for the user's right leg, the actions are mirrored for the user's left leg.

(70) Before either pod **176** is removed (FIG. 26), a permanent ink marker can be used to mark the user's skin with four marks (e.g., triangles) inside the four V-shaped notches on each of the user's current pods **176**. A total of eight triangular marks can be made, including four marks on the pod attached to the user's upper leg and four marks on the pod attached to the user's lower leg. These marks can be used to correctly position the new pods **176**.

(71) Starting at the edge of one of the pods **176** (FIG. 27), the adhesive portion of the pod can be gently peeled away and off of the user's skin. Repeat for the second pod **176**, and discard both of the old pods **176**. After removing both old pods **176** from the user's skin (FIG. 28), the user can wait 24 hours before putting on new pods **176**. This gives the skin time to "air out" and restore itself after being covered for a week. The area may be cleaned with mild soap to avoid removal of the ink markings. If one or more of the markings are fading, they can be re-marked before they disappear entirely.

(72) In FIG. 29, the area is cleansed with a simple hand soap, rinsed and dried. In FIG. 30, two new pods **176** are removed from their packaging and correctly oriented such that the "1" tab is pointing toward the center of the user, and the "2" tab is pointing outward away from the user. In FIG. 31, the V-notches in the pod are aligned with the triangles drawn on the user's upper leg. The same hand as the leg working on is used to hold the center of the pod **176** onto the leg so that the V-notches are aligned with the triangle marks. With the other hand, the tab "1" is gently pulled to expose the adhesive on the back of the pod **176**. The center of the pod **176** is kept in place as the backing paper is removed. Once the "1" backing paper is removed, the adhesive flap is rolled down so that it sticks to the skin smoothly and without getting wrinkled. The V-notches should still be aligned with the triangle marks. The adhesive is gently pressed onto the skin, making sure it has fully adhered to the skin. Next, the "2" tab is removed from the rest of the backing paper. The rest of the adhesive is rolled onto the skin. The entire adhesive can be smoothed to make sure it has fully adhered to the skin.

(73) In FIG. 32, another pod **176** is oriented on the lower leg so that the "1" tab is pointing toward the center of the body and the "2" tab is pointing away from the body. Next, the V-notches in the pod are aligned with the triangle marks drawn on the lower leg. Using the same hand as the leg being worked on, the center of the pod **176** is held onto the leg so that the V-notches are aligned with the triangle marks. With the other hand, the "1" tab is removed to expose the adhesive on the back of the pod **176**. The center of the pod **176** should be held in place as the backing paper is removed. Once the "1" tab backing paper is removed, the adhesive flap is rolled down so that it

sticks to the skin smoothly and without getting wrinkled. The V-notches should still be aligned with the triangle marks. Gently press the adhesive onto the skin, making sure it has fully adhered to the skin. The “2” tab is gently removed to roll the rest of the adhesive onto the skin. Smooth down the entire adhesive to make sure it has fully adhered to the skin.

(74) The fingertips can be used to flatten the edges of the adhesive fully against the skin (FIG. 33). Rub gently to increase adhesion for both pods **176**. The pods **176** are now changed and the goniometer **110** is ready to attach to the user. Hold the goniometer **110** close to the magnets on the pods **176** and let them snap into place via the magnets. Positioning of the pods **176** can be checked by attaching the goniometer **110** and flexing the leg (FIG. 34). If the goniometer **110** pops off of one or both of the pods **176**, the detached pod **176** has been re-applied too far from the correct position. Check to see if any V-notches are not well aligned with the triangle marks on the skin. If this is the case, remove that pod **176** and reapply a new pod **176**, making sure it is aligned more closely to the triangle marks on the skin.

(75) Pod Function

(76) A pair of truncated pull tab pod assemblies, one adhered to the upper leg, and one to the lower leg, act as anchors to the ends of the goniometer, which measures the angle of the knee over the course of the patient's sessions. Although the goniometer is removed between sessions, the pair of pods are to be left in place for about a week. Once a week, the patient or caregiver replaces the first set of pod assemblies with new pod assemblies. Repeat weekly. Location targets marked on the legs can be “refreshed” by the patient to provide for repeatable placement locations for each new pair of pod assemblies. The “semi-continuous” measurement anchor points provided by the pods allow for a reliable assessment of range of motion over the duration of the therapy.

(77) Pod Description

(78) The pod assembly can include three basic layers. The bottom layer can be highly compliant, hypoallergenic, breathable, and adheres to the skin. The middle layer can be a thin foam that is moderately compliant. The top layer can be a rigid plastic molded part that has locating features and a pair of magnets and is adhered to the middle layer with an adhesive.

(79) Four location notches in the bottom layer can provide for reliable marking of initial pod locations such that subsequent pods can be placed accurately in the same location and orientation. The middle layer can act as a transitional material between the larger, compliant layer and the smaller pod with snaps. Features in the rigid pod can include the top layer as location features to assemble to the goniometer and to the pod template. The magnets, mating with similar magnets in the goniometer, provide the retention force to allow use of the goniometer during a session. Before assembly to the body, the pod comes from the package with two release papers with large pull tabs that cover the adhesive of the bottom layer.

(80) Pod Design Aspects

(81) The pods can be consistent anchor points for the goniometer. When the goniometer is not in place during a session, either the pods can act as attachment points for the goniometer or a pedometer. For the goniometer to provide relevant and reliable range of motion information for clinical use, the pods can be initially located accurately with respect to physiological landmarks and reliably replaced. The pod assembly allows for accurate initial placement and reliable replacement. A combination of novel features and functions in the pod assembly and the alignment assembly allow for these features. Within the pod assembly, the V-notches in allow for accurate replacement of subsequent pods. The asymmetric release paper adhesive backing and large numbered pull tabs allow for the easy location and highly reliable placement and adhesion to the skin. Once the skin is marked with the four targets triangles, the patient can easily locate and orient a new pod by aligning the V-notches to the marked triangles. This “peel-in-place” feature allows for targeting and adhering to be decoupled. Once the first section of the adhesive is revealed and adhered to the skin it acts as an anchor for the following steps. The patient or caregiver can pull the second pull tab and reveal the rest of the adhesive, and can simply smooth the rest of the pod onto

the skin with little concern it will be out of place.

(82) Alignment Assembly Function

(83) The alignment assembly allows physiological landmarks of the patient to be used for accurate pods placements for use with the goniometer. The skin over the lateral epicondyle is located and a circular sticker is placed on the patient's skin or clothing over both the greater trochanter and lateral malleolus. A knee pivot anchor of the alignment assembly can be accurately placed over the lateral epicondyle. The pod is placed with the alignment assembly such that it “points” to either the greater trochanter or lateral malleolus target sticker. Once aligned, the assembly is stabilized and affixed. The process is repeated for other pods as described herein.

(84) Alignment Assembly Description

(85) The alignment arm can be a long chipboard part that has a hole to accept the knee pivot anchor, “pointing” features at the far end to help align with the physiological landmarks, and a hole in the mid-section that aligns to and snaps to features on pods. The distance between these two holes in the template assists in final placement of the pods, and corresponds to hard dimensions in the goniometer. The knee pivot anchor can be a plastic part with a pad of adhesive that snaps into a hole in the end of the template and allows for rotation such that it can be used for both segments of the leg. The center of the anchor can be hollow so that a mark can be placed over the lateral epicondyle. The “skin-side” of the anchor is designed to be flexible, such that the adhesive pad assembled to it can conform to the side of the knee and provide a good adhesion point for use. This part can be removed.

(86) These designs provide accuracy, repeatability, and ease of use for both the patient and the caregiver. The “peel-in-place” release paper design can be superior to the conventional “peel then place” method for the pods. The “mark after placement” method for initial alignment rather than conventional “mark (with a template) then place” method also is an advantage. The release paper can be asymmetric to allow for holding during the first release paper pull. The release paper can use pull tabs to number the release paper in the order of release. In addition to being an ergonomic aid (a “third hand”) for stabilizing the assembly to the leg, the locked pivot point, used for both pod placements insures that the pod-to-pod distance will be well controlled, and within the tolerances of use with the corresponding and highly repeatable goniometer geometry.

(87) Other embodiments can include one or more of the following items or components.

(88) 900

(89) A system for measuring an angle of a joint of a user, comprising: a center hub, the center hub having a first hub and a second hub; a first arm configured for attachment to a first limb portion of the user at a first outer end and to the first hub at a first inner end; a second arm configured for attachment to a second limb portion of the user at a second outer end and to the second hub at a second inner end, wherein the first hub is pivotally coupled to the second hub; a magnet coupled to the second hub; and a sensor disposed in the center hub and configured to detect a rotation of the magnet.

(90) The system further comprising a printed circuit board (PCB) removably disposed in the center hub, the PCB having an inward notch; and an outward notch coupled to the first hub, wherein the outward notch is configured to couple with the inward notch to align the sensor and the magnet.

(91) The system further comprising a cover detachably coupled to the first hub, wherein the cover is configured to inhibit movement of the PCB within the center hub.

(92) The system wherein the sensor is a Hall Effect sensor coupled to the PCB.

(93) The system wherein the sensor is configured to measure the rotation of the magnet up to a precision of about ± 0.01 degree.

(94) The system further comprising a retaining ring configured to couple the magnet to the second hub.

(95) The system wherein the magnet is configured with north and south polarity within the center hub.

- (96) The system further comprising a circuit configured to generate an electrical signal based on the rotation of the magnet and to transmit the electrical signal in real time.
- (97) The system further comprising a user interface configured to receive the electrical signal and display data obtained from the electrical signal.
- (98) The system wherein the data includes the angle of the joint of the user.
- (99) The system wherein the first hub and the second hub are configured to rotate 360 degrees about an axis.
- (100) A system for measuring an angle of a joint of a user, comprising: a center hub, the center hub having a first hub and a second hub; a first arm configured for attachment to a first limb portion of the user at a first outer end and to the first hub at a first inner end; a second arm configured for attachment to a second limb portion of the user at a second outer end and to the second hub at a second inner end, wherein the first hub is pivotally coupled to the second hub and configured to rotate 360 degrees about an axis; a magnet coupled to the second hub; a printed circuit board (PCB) removably disposed in the center hub; and a sensor coupled to the PCB and configured to detect a rotation of the magnet.
- (101) The system further comprising a battery housing coupled to the PCB; and a battery detachably coupled to the battery housing.
- (102) The system further comprising a transmitter coupled to the PCB and configured to transmit an electrical signal based on the rotation of the magnet.
- (103) The system further comprising a user interface configured to receive the electrical signal and display data obtained from the electrical signal, wherein the data has the angle of the joint of the user.
- (104) The system wherein the first and second arms are adhesively attached to respective ones of the first and second limb portions of the user.
- (105) A system for measuring an angle of a joint of a user, comprising: a center hub, the center hub having a first hub and a second hub, wherein the first hub has an outward notch; a first and second coupling apparatus configured to be adhesively attached to first and second limb portions proximal to the joint of the user; a first arm configured for attachment to a first coupling apparatus at a first outer end and to the first hub at a first inner end; a second arm configured for attachment to a second coupling apparatus at a second outer end and to the second hub at a second inner end, wherein the first hub is pivotally coupled to the second hub; a magnet coupled to the second hub; a printed circuit board (PCB) having an inward notch and removably disposed in the center hub; a sensor coupled to the PCB and configured to detect a rotation of the magnet, wherein the outward notch is configured to fit within the inward notch to align the sensor and the magnet; and a transmitter coupled to the PCB and configured to transmit an electrical signal based on the rotation of the magnet, wherein the electrical signal has data of the angle of the joint of the user.
- (106) The system further comprising a cover coupled to the center hub, wherein the cover has a snap mechanism configured to attach and detach the cover.
- (107) The system wherein the first and second arms have sections configured to rotate the first and second arms about $\pm$ ten degrees.
- (108) The system wherein the first and second arms have sections configured to twist the first and second arms about $\pm$ eighteen degrees.
- (109) 1000
- (110) An apparatus for coupling a device to a user, the apparatus comprising: a first layer having a top and a bottom, wherein the bottom comprises an adhesive material configured to couple the device to the user; a second layer concentric with the first layer and coupled to the top of the first layer, and the second layer is smaller in size than the first layer and has an upper surface area; a pod concentric with the second layer and sized to be received by and detachably coupled to the upper surface area, and the pod is configured to detachably couple the pod to the device.
- (111) The apparatus wherein, to prevent the apparatus from uncoupling from the user, the second

layer comprises a material configured to dampen forces acting between the device and the apparatus and caused by relative movement between the device and the apparatus.

(112) The apparatus wherein the adhesive material is a medical grade adhesive.

(113) The apparatus wherein the upper surface area comprises one of hooks and loops, wherein the pod has an underside comprised of one of hooks and loops, and wherein the upper surface and the underside are detachably coupled by the hooks and loops.

(114) The apparatus wherein the first layer defines a notch for assisting in aligning the apparatus relative to a predetermined location on the user.

(115) The apparatus wherein the notch is V-shaped.

(116) The apparatus wherein the first layer defines a pair of alignment holes.

(117) The apparatus wherein, to facilitate alignment of the apparatus relative to a predetermined location on the user, the upper surface of the second layer comprises an adhesive material to enable detachable coupling between the upper surface and the pod.

(118) The apparatus wherein, when the device couples to the apparatus, the pod defines a recess for positioning and aligning the device relative to the apparatus.

(119) The apparatus wherein the pod comprises a magnet positioned adjacent to the recess to detachably couple the pod to the apparatus.

(120) An apparatus for coupling a device to a user, the apparatus comprising: a first layer with a first periphery, and the first layer has a top and a bottom, wherein the bottom comprises an adhesive material configured to couple the apparatus to the user, and the first layer defines a plurality of notches spaced apart from one another and disposed about the first periphery of the first layer, and the first layer defines a pair of alignment holes, and the notches and the alignment holes align the apparatus relative to a predetermined location on the user; a second layer smaller in size than, and concentric with, the first layer, and the second layer has a lower surface that couples to the first layer and an upper surface, wherein the upper surface presents an area that comprises an adhesive material; a pod concentric with the second layer and sized to be received by and detachably coupled to the area of the upper surface area, and the pod has a magnet to allow the pod to be detachably coupled to the device, and the pod defines a recess for positioning and aligning the device relative to the apparatus when the device couples to the pod. The apparatus wherein, to prevent the apparatus from uncoupling from the user, the second layer comprises a material configured to dampen forces acting between and caused by relative movement between the device and the apparatus.

(121) An apparatus for measuring flexion and extension of a joint of a user, said apparatus comprising: a first attachment and a second attachment, each comprising: a first layer with a top and a bottom, wherein the bottom comprises an adhesive material for coupling, on opposite sides of the joint, the attachments to the user; a second layer concentric with the first layer, and the second layer has a lower surface that couples to the first layer and an upper surface; and a pod concentric with the second layer and detachably coupled to the upper surface; and a goniometer for measuring flexion and extension of the joint of the user, and the goniometer is detachably coupled to, and spans between, the pods of the attachments.

(122) The apparatus wherein, to prevent the attachments from uncoupling from the user, the second layer comprises a material configured to dampen forces acting between the goniometer and the attachments and caused by relative movement between the goniometer and the attachments.

(123) The apparatus wherein the goniometer has a pair of arms rotatably coupled to and about a center hub, and each arm has a boss for aligning and coupling each arm to a respective pod.

(124) The apparatus wherein each pod defines a recess for receiving and detachably coupling to one of the bosses of the goniometer, and for positioning the goniometer relative to each attachment.

(125) The apparatus wherein, to prevent the goniometer from uncoupling from the attachments, the bosses are sized to be movable within the recesses to allow movement of the bosses in the recesses.

(126) The apparatus wherein, to detachably couple the goniometer to the attachments, magnets are

disposed adjacent to each boss and each recess.

(127) The apparatus wherein wings extend outwardly from the sides of each arm of the goniometer configured to enable a user to move the arms of the goniometer perpendicularly relative to the attachments, and to uncouple the goniometer from the attachments.

(128) The apparatus wherein the edges of the pod are tapered, such configuration enabling a user to further move the arms of the goniometer perpendicularly relative to the attachments, and to uncouple the goniometer from the attachments.

(129) 1010

(130) An apparatus for coupling a device to a user, the apparatus comprising: a first layer having a top and a bottom, wherein the bottom comprises an adhesive material configured to couple the device to the user; a second layer concentric with the first layer and coupled to the top of the first layer, and the second layer is smaller in size than the first layer and has an upper surface area; a pod concentric with the second layer and sized to be received by and detachably coupled to the upper surface area, and the pod is configured to detachably couple the pod to the device; and a pedometer configured to count steps of the user and configured to be removably attached to the apparatus.

(131) The apparatus wherein, to prevent the apparatus from uncoupling from the user, the second layer comprises a material configured to dampen forces acting between the device and the apparatus and caused by relative movement between the device and the apparatus.

(132) The apparatus wherein the adhesive material is a medical grade adhesive.

(133) The apparatus wherein the upper surface area comprises one of hooks and loops, wherein the pod has an underside comprised of one of hooks and loops, and wherein the upper surface and the underside are detachably coupled by the hooks and loops.

(134) The apparatus wherein the first layer defines a notch for assisting in aligning the apparatus relative to a predetermined location on the user.

(135) The apparatus wherein the notch is V-shaped.

(136) The apparatus wherein the first layer defines a pair of alignment holes.

(137) The apparatus wherein, to facilitate alignment of the apparatus relative to a predetermined location on the user, the upper surface of the second layer comprises an adhesive material to enable detachable coupling between the upper surface and the pod.

(138) The apparatus wherein, when the device couples to the apparatus, the pod defines a recess for positioning and aligning the device relative to the apparatus.

(139) The apparatus wherein the pod comprises a magnet positioned adjacent to the recess to detachably couple the pod to the apparatus.

(140) An apparatus for coupling a device to a user, the apparatus comprising: a first layer with a first periphery, and the first layer has a top and a bottom, wherein the bottom comprises an adhesive material configured to couple the apparatus to the user, and the first layer defines a plurality of notches spaced apart from one another and disposed about the first periphery of the first layer, and the first layer defines a pair of alignment holes, and the notches and the alignment holes align the apparatus relative to a predetermined location on the user; a second layer smaller in size than, and concentric with, the first layer, and the second layer has a lower surface that couples to the first layer and an upper surface, wherein the upper surface presents an area that comprises an adhesive material; a pod concentric with the second layer and sized to be received by and detachably coupled to the area of the upper surface area, and the pod has a magnet to allow the pod to be detachably coupled to the device, and the pod defines a recess for positioning and aligning the device relative to the apparatus when the device couples to the pod; and a pedometer configured to count steps of the user and configured to be removably attached to the apparatus.

(141) The apparatus wherein, to prevent the apparatus from uncoupling from the user, the second layer comprises a material configured to dampen forces acting between and caused by relative movement between the device and the apparatus.

(142) An apparatus for measuring flexion and extension of a joint of a user, said apparatus

comprising: a first attachment and a second attachment, each comprising: a first layer with a top and a bottom, wherein the bottom comprises an adhesive material for coupling, on opposite sides of the joint, the attachments to the user; a second layer concentric with the first layer, and the second layer has a lower surface that couples to the first layer and an upper surface; and a pod concentric with the second layer and detachably coupled to the upper surface; and a goniometer for measuring flexion and extension of the joint of the user, and the goniometer is detachably coupled to, and spans between, the pods of the attachments; and a pedometer configured to count steps of the user and configured to be removably attached to the apparatus.

(143) The apparatus wherein, to prevent the attachments from uncoupling from the user, the second layer comprises a material configured to dampen forces acting between the goniometer and the attachments and caused by relative movement between the goniometer and the attachments.

(144) The apparatus wherein the goniometer has a pair of arms rotatably coupled to and about a center hub, and each arm has a boss for aligning and coupling each arm to a respective pod.

(145) The apparatus wherein each pod defines a recess for receiving and detachably coupling to one of the bosses of the goniometer, and for positioning the goniometer relative to each attachment.

(146) The apparatus wherein, to prevent the goniometer from uncoupling from the attachments, the bosses are sized to be movable within the recesses to allow movement of the bosses in the recesses.

(147) The apparatus wherein, to detachably couple the goniometer to the attachments, magnets are disposed adjacent to each boss and each recess.

(148) The apparatus wherein wings extend outwardly from the sides of each arm of the goniometer configured to enable a user to move the arms of the goniometer perpendicularly relative to the attachments, and to uncouple the goniometer from the attachments.

(149) The apparatus wherein the edges of the pod are tapered, such configuration enabling a user to further move the arms of the goniometer perpendicularly relative to the attachments, and to uncouple the goniometer from the attachments.

(150) 1500

(151) An apparatus for measuring flexion and extension at a joint of a user, the apparatus comprising: a center hub having a first hub, and a second hub coaxially aligned with and rotatably coupled to the first hub; a first arm coupled to and rotatable with the first hub; and a second arm coupled to and rotatable with the second hub wherein, to maintain a position of the center hub relative to the joint of the user, the first and second arms pivotably and rotatably couple to a respective first and second hub such that rotation, flexion, and extension of the first and second arms are allowed.

(152) The apparatus of claim 1, wherein each of the first and second arms comprise an inner link for pivotably coupling the first and second arms to the first and second hubs, and the inner links are configured to allow the first and second arms to flex and extend relative to the center hub.

(153) The apparatus wherein each of the first and second arms comprise an outer link coupled to the inner link, and the outer links are configured to rotate the first and second arms relative to the center hub.

(154) The apparatus further comprising a screw configured to couple one of the inner and one of the outer links, wherein the screw is aligned parallel to a length of a respective one of the first and second arms, and wherein, to allow the rotation of the first and second arms relative to the center hub, the screw provides for rotation of the inner and outer links.

(155) The apparatus wherein each of the first and second arms comprises an outer end coupled to the outer link, and the outer end is configured to flex and extend relative to the center hub such that further flexion and extension of the first and second arms relative to the center hub are enabled.

(156) The apparatus further comprising link arms extending outwardly from each of the first and second hubs, wherein the link arms couple to respective ones of the first and second arms.

(157) The apparatus further comprising pins configured to couple between a respective outer link and a respective outer end, and between a respective inner link and a respective link arm, and

wherein the pins are aligned perpendicular to a length of a respective arm, and wherein the pins provide for the flexion and extension of the first and second arms relative to the center hub.

(158) The apparatus wherein the arms include a magnet and a boss.

(159) An apparatus for measuring flexion and extension at a joint of a user, the apparatus comprising: a center hub that has an upper hub, and a lower hub coaxially aligned with and rotatably coupled to the upper hub; an arm coupled to, and rotatable with, each of the upper and lower hubs, and the arms pivotably and rotatably couple to the hubs to allow rotation, flexion, and extension of the arms, and to restrict movement of the center hub relative to the joint of the user.

(160) The apparatus further comprising link arms that extend outwardly from each of the upper and lower hubs, and the arms couple to a respective hub at a respective link arm.

(161) The apparatus wherein pins couple each of the link arms and each of the arms, and the pins are aligned perpendicular to the length of a respective arm and configured to allow flexion and extension of the arms, and a screw couples between each of the link arms and each of the arms, and each screw is aligned parallel with the length of a respective arm configured to allow rotation of each arm about each screw.

(162) The apparatus wherein the arms include a magnet and a boss for aligning and coupling the arms to attachments.

(163) An apparatus for measuring flexion and extension at a joint of a user, the apparatus comprising: a center hub comprising: an upper hub and a first link arm that extends outwardly from the upper hub; a lower hub coaxially aligned with and rotatably coupled to the upper hub, and a second link arm extends outwardly from the lower hub; an arm pivotably coupled to each of the first and second link arms, and each arm comprises: an inner link for pivotably coupling the arm to a respective first and second link arm and for allowing the arm to flex and extend relative to the center hub; an outer link rotatably coupled to the inner link to allow the arm to rotate relative to the center hub; an outer end pivotably coupled to the outer link to allow the outer end of the arm to flex and extend relative to the outer link and the center hub.

(164) The apparatus wherein the link arms are integrally formed with the hubs.

(165) The apparatus wherein the link arms are coupled to the respective hubs, and the link arms are configured to allow flexion and extension of the arms relative to the center hub.

(166) The apparatus wherein the link arms couple to the respective hubs and are configured to allow rotation of the arms relative to the center hub.

(167) The apparatus wherein a pin couples the inner link and the link arm, and the pin is aligned perpendicular to the length of the arm, and the pin provides for the pivotable coupling between the inner links and link arm.

(168) The apparatus wherein a pin couples the outer link and the outer end, and the pin is aligned perpendicular to the length of the arm, and the pin provides for the pivotable coupling between the outer link and the outer end.

(169) The apparatus wherein a screw couples the inner and outer link, and the screw is aligned parallel with the length of the arm, and the screw provides for the rotatable coupling between the inner link and outer link.

(170) The apparatus wherein the arms include a magnet and a boss.

(171) 1700

(172) An apparatus for assisting a person in aligning, relative to a center of a joint of a user, a wearable device on opposing limb portions of the joint of the user, the wearable device has attachments, each attachment defines alignment holes spaced from each other, and the alignment holes have a size, the apparatus comprising: a first segment; a second segment coupled to the first segment at a pivot point, and when positioned adjacent the center of the joint, the pivot point aligns the apparatus relative to the center of the joint; the first and second segments each defining voids, the voids are spaced on each of the first and second segments equidistant from the pivot point, and the spacing between, and size of, the voids is commensurate with the spacing between, and size of,

the alignment holes of the respective attachments; and whereby the person pivots the segments to centrally align the segments relative to the respective opposing limb portions of the user, and the person marks locations on the respective opposing limb portions through the voids, wherein the alignment holes of the attachments are aligned with respective marks to align the attachments and to couple the wearable device to the user.

(173) The apparatus wherein the first and second segments each have center axes, the center axes intersect at the pivot point, and prior to marking locations on the respective opposing limb portions, the person pivots each segment to centrally align the center axes with the respective centers of the opposing limb portions.

(174) The apparatus wherein the second segment pivotably couples to the first segment at the pivot point.

(175) The apparatus wherein the second segment couples to the first coupling end at a pivot point by overlaying with the first segment.

(176) The apparatus wherein the pivot point is spaced adjacent to and equidistant from first and second coupling ends of the respective first and second segments.

(177) The apparatus wherein the alignment holes of the attachments are aligned coaxially with respective marks to align the attachments, and enable the wearable device to be mounted on the user.

(178) A method for assisting a person in aligning a wearable device relative to a center of a joint of a user, on opposing limb portions of the joint of the user, the wearable device has attachments, each attachment defines alignment holes spaced from each other, and each alignment hole has a size, the method comprising: providing an apparatus having a first segment and a second segment pivotably coupled to the first segment at a pivot point; providing voids defined in each of the first and second segments, the voids are spaced an equidistant from the pivot point on each of the first and second segments, and the spacing between, and size of, the voids is commensurate with the spacing between, and size of, the alignment holes of the respective attachments; locating the center of the joint; aligning the pivot point of the apparatus with the center of the joint; pivoting each segment to centrally align the segments relative to respective opposing limb portions; marking locations on the respective opposing limb portions through the voids; positioning the alignment holes of the attachments with respective marks to align the attachments and the wearable device on the user; and coupling the attachments and the wearable device to the user.

(179) The method further comprising: providing center axes of the first and second segments, and the center axes intersect at the pivot point; pivoting each segment to centrally align the center axes with the center of the respective opposing limb portion.

(180) The method further comprising: providing pegs; and coaxially aligning the pegs with the markings to facilitate alignment of the alignment holes of the attachments with each mark.

(181) The method wherein the step of locating the center of the joint is further defined as locating the lateral epicondyle of a knee joint.

(182) An apparatus for assisting a person in aligning a wearable device relative to a center of a joint of a user, on opposing limb portions of the joint of the user, the wearable device has attachments, each attachment defines alignment holes spaced from each other, and the alignment holes have a size, the apparatus comprising: an imaging device for locating a position of the joint of the user and the opposing limb portions; a laser configured to provide a beam of light; a processor in communication with the imaging device and the laser; and the processor is configured to receive and process data from the imaging device representative of the position of the joint of the user and the opposing limb portions, the processor communicates with the lasers to position the laser such that the light beam forms spots of light on the user at the center of the joint and on the opposing limb portions of the user commensurate with the spacing between, and size of, the alignment holes of the respective attachments, and wherein the alignment holes of the attachments are aligned with respective alignment holes of the attachments to couple the wearable device on the user.

(183) A method for assisting a person in aligning a wearable device relative to a center of a joint of a user, on opposing limb portions of the joint of the user, the wearable device has attachments, each attachment defines alignment holes spaced from each other, and each alignment hole has a size, the method comprising: providing an imaging device; providing a laser configured to provide a beam of light; providing a processor configured to communicate with the imaging device and the laser; locating with the imaging device positions of the joint and the opposing limb portions; communicating data from the imaging device to the processor, the data being representative of the positions of the joint and the opposing limb portions; processing the data with the processor; calculating with the processor positions of the laser to provide the laser beam to form spots of light on the user at the center of the joint and the opposing limb portions, and the foregoing is commensurate with the spacing between, and size of, the alignment holes of the respective attachments; communicating instructions to the laser; moving the laser to the positions; and aligning the alignment holes of the attachments with the respective spots of light to align the attachments and to couple the wearable device to the user.

(184) The method further comprising the step of marking on the opposing limb portions the location of the laser beam, and aligning the alignment holes of the attachments coaxial with respective marks to align the attachments and to couple the wearable device to the user.

(185) An apparatus for assisting a person in aligning a wearable device relative to a center of a joint of a user and on opposing limb portions of the joint of the user, the apparatus comprising: diodes coupled to the wearable device, the joint, and the opposing limb portions; an imaging device for locating positions of the diodes; a personal communication device configured to communicate with a person; a processor in communication with the imaging device and the personal communication device; and the processor is configured to receive and process data from the imaging device representative of the positions of the diodes, and the processor communicates with the personal communication device to provide instructions representative of action to be taken by the person to align the wearable device relative to the center of joint of the user. The apparatus wherein the personal communication device is a display.

(186) The apparatus wherein the personal communication device is a speaker.

(187) A method for assisting a person in aligning a wearable device on opposing limb portions of a joint of a user relative to a center of the joint of the user, the method comprising:

(188) providing a diode coupled to the wearable device, the joint, and the opposing limb portions of the user; providing an imaging device for locating a position of the diodes; providing a personal communication device configured to communicate with a person; providing a processor configured to communicate with the imaging device and the personal communication device; locating with the imaging device the position of the diodes; communicating, from the imaging device to the processor, data representative of the position of the diodes; processing of the data by the processor; calculating by the processor a position of the wearable device relative to the joint and the opposing limb portions; calculating by the processors a position of the wearable device, and instructions for the person to align the wearable device relative to the center of the joint of the patient; communicating by the processors to the personal communication device the instructions to be provided to the person for aligning the wearable device relative to the center of the joint of the user; and communicating to the person with the personal communication device.

(189) The method wherein the step of communicating to the person with the personal communication device further comprises providing audio instruction through a speaker to the personal communication device.

(190) The method wherein the step of communication to the person with the communication device further comprises providing visual instruction through a display to the personal communication device.

(191) An apparatus for assisting a person in aligning, relative to a center of a joint of a user, a wearable device on opposing limb portions of the joint of the user, the wearable device has

attachments, each attachment defines alignment holes spaced from each other, and the alignment holes have a size, the apparatus comprising: a first segment; a second segment coupled to the first segment at a pivot point, and when positioned adjacent the center of the joint, the pivot point aligns the apparatus relative to the center of the joint; the first and second segments each defining voids, the voids are spaced on each of the first and second segments equidistant from the pivot point, and the spacing between, and size of, the voids is commensurate with the spacing between, and size of, the alignment holes of the respective attachments; and whereby the person pivots the segments to centrally align the segments relative to the respective opposing limb portions of the user, and the person marks locations on the respective opposing limb portions through the voids, wherein the alignment holes of the attachments are aligned with respective marks to align the attachments and to couple the wearable device to the user.

(192) The apparatus wherein the first and second segments each have center axes, the center axes intersect at the pivot point, and prior to marking locations on the respective opposing limb portions, the person pivots each segment to centrally align the center axes with the respective centers of the opposing limb portions.

(193) The apparatus wherein the second segment pivotably couples to the first segment at the pivot point.

(194) The apparatus wherein the second segment couples to the first coupling end at a pivot point by overlaying with the first segment.

(195) The apparatus wherein the pivot point is spaced adjacent to and equidistant from first and second coupling ends of the respective first and second segments.

(196) The apparatus wherein the alignment holes of the attachments are aligned coaxially with respective marks to align the attachments, and enable the wearable device to be mounted on the user.

(197) A method for assisting a person in aligning a wearable device relative to a center of a joint of a user, on opposing limb portions of the joint of the user, the wearable device has attachments, each attachment defines alignment holes spaced from each other, and each alignment hole has a size, the method comprising: providing an apparatus having a first segment and a second segment pivotably coupled to the first segment at a pivot point; providing voids defined in each of the first and second segments, the voids are spaced an equidistant from the pivot point on each of the first and second segments, and the spacing between, and size of, the voids is commensurate with the spacing between, and size of, the alignment holes of the respective attachments; locating the center of the joint; aligning the pivot point of the apparatus with the center of the joint; pivoting each segment to centrally align the segments relative to respective opposing limb portions; marking locations on the respective opposing limb portions through the voids; positioning the alignment holes of the attachments with respective marks to align the attachments and the wearable device on the user; and coupling the attachments and the wearable device to the user.

(198) The method further comprising: providing center axes of the first and second segments, and the center axes intersect at the pivot point; pivoting each segment to centrally align the center axes with the center of the respective opposing limb portion.

(199) The method further comprising: providing pegs; and coaxially aligning the pegs with the markings to facilitate alignment of the alignment holes of the attachments with each mark.

(200) The method wherein the step of locating the center of the joint is further defined as locating the lateral epicondyle of a knee joint.

(201) An apparatus for assisting a person in aligning a wearable device relative to a center of a joint of a user, on opposing limb portions of the joint of the user, the wearable device has attachments, each attachment defines alignment holes spaced from each other, and the alignment holes have a size, the apparatus comprising: an imaging device for locating a position of the joint of the user and the opposing limb portions; a laser configured to provide a beam of light; a processor in communication with the imaging device and the laser; and the processor is configured to receive

and process data from the imaging device representative of the position of the joint of the user and the opposing limb portions, the processor communicates with the lasers to position the laser such that the light beam forms spots of light on the user at the center of the joint and on the opposing limb portions of the user commensurate with the spacing between, and size of, the alignment holes of the respective attachments, and wherein the alignment holes of the attachments are aligned with respective alignment holes of the attachments to couple the wearable device on the user.

(202) A method for assisting a person in aligning a wearable device relative to a center of a joint of a user, on opposing limb portions of the joint of the user, the wearable device has attachments, each attachment defines alignment holes spaced from each other, and each alignment hole has a size, the method comprising: providing an imaging device; providing a laser configured to provide a beam of light; providing a processor configured to communicate with the imaging device and the laser; locating with the imaging device positions of the joint and the opposing limb portions; communicating data from the imaging device to the processor, the data being representative of the positions of the joint and the opposing limb portions; processing the data with the processor; calculating with the processor positions of the laser to provide the laser beam to form spots of light on the user at the center of the joint and the opposing limb portions, and the foregoing is commensurate with the spacing between, and size of, the alignment holes of the respective attachments; communicating instructions to the laser; moving the laser to the positions; and aligning the alignment holes of the attachments with the respective spots of light to align the attachments and to couple the wearable device to the user.

(203) The method further comprising the step of marking on the opposing limb portions the location of the laser beam, and aligning the alignment holes of the attachments coaxial with respective marks to align the attachments and to couple the wearable device to the user.

(204) An apparatus for assisting a person in aligning a wearable device relative to a center of a joint of a user and on opposing limb portions of the joint of the user, the apparatus comprising: diodes coupled to the wearable device, the joint, and the opposing limb portions; an imaging device for locating positions of the diodes; a personal communication device configured to communicate with a person; a processor in communication with the imaging device and the personal communication device; and the processor is configured to receive and process data from the imaging device representative of the positions of the diodes, and the processor communicates with the personal communication device to provide instructions representative of action to be taken by the person to align the wearable device relative to the center of joint of the user.

(205) The apparatus wherein the personal communication device is a display.

(206) The apparatus wherein the personal communication device is a speaker.

(207) A method for assisting a person in aligning a wearable device on opposing limb portions of a joint of a user relative to a center of the joint of the user, the method comprising: providing a diode coupled to the wearable device, the joint, and the opposing limb portions of the user; providing an imaging device for locating a position of the diodes; providing a personal communication device configured to communicate with a person; providing a processor configured to communicate with the imaging device and the personal communication device; locating with the imaging device the position of the diodes; communicating, from the imaging device to the processor, data representative of the position of the diodes; processing of the data by the processor; calculating by the processor a position of the wearable device relative to the joint and the opposing limb portions; calculating by the processors a position of the wearable device, and instructions for the person to align the wearable device relative to the center of the joint of the patient; communicating by the processors to the personal communication device the instructions to be provided to the person for aligning the wearable device relative to the center of the joint of the user; and communicating to the person with the personal communication device.

(208) The method wherein the step of communicating to the person with the personal communication device further comprises providing audio instruction through a speaker to the

personal communication device.

(209) The method wherein the step of communication to the person with the communication device further comprises providing visual instruction through a display to the personal communication device.

(210) The above discussion is meant to be illustrative of the principles and various embodiments of the present invention. Numerous variations and modifications will become apparent to those skilled in the art once the above disclosure is fully appreciated. It is intended that the following claims be interpreted to embrace all such variations and modifications.

(211) The various aspects, embodiments, implementations or features of the described embodiments may be used separately or in any combination. The embodiments disclosed herein are modular in nature and may be used in conjunction with or coupled to other embodiments.

(212) Benefits, other advantages, and solutions to problems have been described above with regard to specific embodiments. However, the benefits, advantages, solutions to problems, and any feature(s) that can cause any benefit, advantage, or solution to occur or become more pronounced are not to be construed as a critical, required, sacrosanct or an essential feature of any or all of the claims.

(213) Consistent with the above disclosure, the examples of assemblies enumerated in the following clauses are specifically contemplated and are intended as a non-limiting set of examples.

Claims

1. A system for measuring an angle of a joint of a user, comprising: a center hub, the center hub having a first hub and a second hub; a first coupling apparatus and a second coupling apparatus external to the center hub, each of the first coupling apparatus and the second coupling apparatus having a first layer and a second layer disposed above the first layer, wherein the first layer defines an area larger than an area of the second layer, and wherein the first and second coupling apparatuses are configured to be adhesively attached to first and second limb portions proximal to the joint of the user, respectively; a first arm including a first outer end and a first inner end opposite the first outer end, wherein the first arm is attached to the second layer of the first coupling apparatus at the first outer end and the first arm is further attached to the first hub at the first inner end; a second arm including a second outer end and a second inner end opposite the second outer end, wherein the second arm is attached to the second layer of the second coupling apparatus at the second outer end and the second arm is further attached to the second hub at the second inner end, and, further, wherein the first hub is pivotally coupled to the second hub; a magnet coupled to the second hub; a sensor configured to detect a rotation of the magnet; and a transmitter configured to transmit an electrical signal based on the rotation of the magnet, wherein the electrical signal has data of the angle of the joint of the user.
2. The system of claim 1, further comprising a cover coupled to the center hub, wherein the cover has a snap mechanism configured to attach and detach the cover.
3. The system of claim 2, wherein the cover is detachably coupled to the first hub.
4. The system of claim 1, wherein the first and second arms have sections configured to rotate the first arm about the first inner end and the second arm about the second inner end each about ± 10 degrees.
5. The system of claim 1, wherein the first and second arms have sections configured to twist the first arm about the first inner end and the second arm about the second inner end each about ± 18 degrees.
6. The system of claim 1, further comprising a retaining ring configured to couple the magnet to the second hub.
7. The system of claim 6, wherein the retaining ring is coupled to a magnet housing, wherein the retaining ring is configured to secure the magnet within the magnet housing.

8. The system of claim 1, wherein sensor is configured to detect the rotation of the magnet at a sensitivity of a one-hundredth of a degree.
 9. The system of claim 1, wherein the first layer defines at least one notch in a peripheral edge thereof for marking a skin there beneath and to facilitate aligning a replacement coupling apparatus.
 10. The system of claim 9, wherein the at least one notch has a V-shape.
 11. The system of claim 9, wherein the at least one notch includes at least two notches spaced apart from one another.
 12. The system of claim 9, wherein the at least one notch includes four notches each spaced apart from one another.
 13. The system of claim 1, further comprising a pod attached one of the second layers, opposite from the first layer, and wherein the pod is configured to be releasably attached to one of the first arm or the second arm.
 14. The system of claim 13, wherein the pod is secured to the one of the first arm or the second arm with a magnet.
 15. The system of claim 13, wherein at least one of the pod, the first arm, or the second arm defines one or more recesses configured to receive a boss and to hold the pod in a fixed position when the pod is attached to the one of the first arm or the second arm.
 16. A system for measuring an angle of a joint of a user, comprising: a center hub, the center hub having a first hub and a second hub; a first coupling apparatus and a second coupling apparatus external to the center hub, each of the first coupling apparatus and the second coupling apparatus having a layer defining at least one notch, wherein the first coupling apparatus and second coupling apparatus are configured to be adhesively attached to first and second limb portions proximal to the joint of the user, respectively; a first arm including a first outer end and a first inner end opposite the first outer end, wherein the first arm is attached the first coupling apparatus at the first outer end and the first arm is further attached to the first hub at the first inner end; a second arm including a second outer end and a second inner end opposite the second outer end, wherein the second arm is attached to the second coupling apparatus at the second outer end and the second arm is further attached to the second hub at the second inner end, and, further, wherein the first hub is pivotally coupled to the second hub; and a sensor configured to detect a rotation of the second hub relative to the first hub.
 17. The system of claim 16, wherein the at least one notch has a V-shape.
 18. The system of claim 16, wherein the at least one notch includes at least two notches spaced apart from one another.
 19. The system of claim 16 further comprising a pod attached one of the first coupling apparatus or the second coupling apparatus, and wherein the pod is configured to be releasably attached to one of the first arm or the second arm.
 20. The system of claim 19, wherein the pod is secured to the one of the first arm or the second arm with a magnet.
-