

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402909
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Thommen; Daniel et al.

Multi-shield spinal access system

Abstract

An access device for accessing an intervertebral disc having an outer shield comprising an access shield with a larger diameter (~16-30 mm) that reaches from the skin down to the facet line, with an inner shield having a second smaller diameter (~5-12 mm) extending past the access shield and reaches down to the disc level. This combines the benefits of the direct visual microsurgical/mini open approaches and the percutaneous, “ultra-MIS” techniques.

Inventors: Thommen; Daniel (Liestal, CH), Richter; Joern (Kandern, DE), Wang; Michael (North Miami, FL), Assaker; Richard (Kain, BE), Fessler; Richard (Winnetka, IL), Mehren; Christoph (Munich, DE), Tan; Seang Beng (Clementi, SG), Taylor; William (Del Mar, CA), Buehlmann; Eric (Duxbury, MA), White; Michael (Liestal, CH)

Applicant: MEDOS INTERNATIONAL SARL (Le Locle, CH)

Family ID: 74198777

Assignee: Medos International Sàrl (Le Locle, CH)

Appl. No.: 18/401037

Filed: December 29, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240206909 A1	Jun. 27, 2024

Related U.S. Application Data

continuation parent-doc US 17214759 20210326 US 11883064 child-doc US 18401037
continuation parent-doc US 15254877 20160901 US 10987129 20210407 child-doc US 17214759
us-provisional-application US 62214297 20150904

Publication Classification

Int. Cl.: **A61B17/34** (20060101); **A61B1/00** (20060101); **A61B1/012** (20060101); **A61B1/018** (20060101); **A61B1/05** (20060101); **A61B1/055** (20060101); **A61B1/07** (20060101); **A61B1/12** (20060101); **A61B1/233** (20060101); **A61B1/267** (20060101); **A61B1/313** (20060101); **A61B1/317** (20060101); **A61B1/32** (20060101); **A61B5/00** (20060101); **A61B5/06** (20060101); **A61B5/24** (20210101); **A61B17/00** (20060101); **A61B17/02** (20060101); **A61B17/32** (20060101); **A61B17/60** (20060101); **A61B17/70** (20060101); **A61B18/18** (20060101); **A61B34/20** (20160101); **A61B90/00** (20160101); **A61B90/50** (20160101); **A61B90/57** (20160101); **A61F2/44** (20060101); **A61F2/46** (20060101); **A61M29/00** (20060101); **A61B17/16** (20060101); **A61B17/17** (20060101); **A61B17/56** (20060101); **A61B18/00** (20060101); **A61B34/00** (20160101); **A61B34/30** (20160101); **A61B90/30** (20160101)

U.S. Cl.:

CPC **A61B17/3421** (20130101); **A61B1/00045** (20130101); **A61B1/00089** (20130101); **A61B1/00091** (20130101); **A61B1/00094** (20130101); **A61B1/00096** (20130101); **A61B1/00103** (20130101); **A61B1/00128** (20130101); **A61B1/00133** (20130101); **A61B1/00135** (20130101); **A61B1/00154** (20130101); **A61B1/012** (20130101); **A61B1/018** (20130101); **A61B1/05** (20130101); **A61B1/051** (20130101); **A61B1/055** (20130101); **A61B1/07** (20130101); **A61B1/126** (20130101); **A61B1/233** (20130101); **A61B1/2676** (20130101); **A61B1/3132** (20130101); **A61B1/3135** (20130101); **A61B1/317** (20130101); **A61B1/32** (20130101); **A61B5/068** (20130101); **A61B5/24** (20210101); **A61B5/4041** (20130101); **A61B5/407** (20130101); **A61B17/00234** (20130101); **A61B17/0218** (20130101); **A61B17/025** (20130101); **A61B17/0293** (20130101); **A61B17/320068** (20130101); **A61B17/3423** (20130101); **A61B17/3462** (20130101); **A61B17/60** (20130101); **A61B17/7032** (20130101); **A61B17/7074** (20130101); **A61B17/708** (20130101); **A61B18/1815** (20130101); **A61B34/20** (20160201); **A61B90/03** (20160201); **A61B90/361** (20160201); **A61B90/50** (20160201); **A61B90/57** (20160201); **A61F2/4455** (20130101); **A61F2/4611** (20130101); **A61M29/00** (20130101); **A61B1/00149** (20130101); **A61B2017/00022** (20130101); **A61B2017/00053** (20130101); **A61B2017/00261** (20130101); **A61B2017/00296** (20130101); **A61B2017/00314** (20130101); **A61B2017/0034** (20130101); **A61B2017/00345** (20130101); **A61B2017/00407** (20130101); **A61B2017/00477** (20130101); **A61B2017/00557** (20130101); **A61B2017/00738** (20130101); **A61B2017/00831** (20130101); **A61B2017/00858** (20130101); **A61B2017/00871** (20130101); **A61B2017/00946** (20130101); **A61B2017/00991** (20130101); **A61B17/0206** (20130101); **A61B2017/0256** (20130101); **A61B2017/0262** (20130101); **A61B17/1637** (20130101); **A61B17/1671** (20130101); **A61B17/1703** (20130101); **A61B17/1757** (20130101); **A61B2017/320075** (20170801); **A61B17/3403** (20130101); **A61B17/3439** (20130101); **A61B2017/3443** (20130101); **A61B2017/3445** (20130101); **A61B2017/3447** (20130101); **A61B2017/345** (20130101); **A61B2017/3454** (20130101); **A61B2017/347** (20130101); **A61B2017/3484** (20130101); **A61B2017/564** (20130101); **A61B17/70** (20130101); **A61B17/7083** (20130101); **A61B2018/00339** (20130101); **A61B2018/00565** (20130101); **A61B2018/00577** (20130101); **A61B2018/00601** (20130101); **A61B2018/00839** (20130101); **A61B2018/1861** (20130101); **A61B2018/1869** (20130101); **A61B2034/2055** (20160201); **A61B34/30** (20160201); **A61B34/70** (20160201); **A61B2090/034** (20160201); **A61B2090/036** (20160201); **A61B2090/08021**

(20160201); A61B90/30 (20160201); A61B2090/306 (20160201); A61B2090/371 (20160201); A61B2090/3916 (20160201); A61B2090/3937 (20160201); A61B2090/3979 (20160201); A61B2090/3983 (20160201); A61B2218/002 (20130101); A61B2218/007 (20130101); A61F2002/4635 (20130101)

Field of Classification Search

CPC: A61B (1/100135); A61B (1/018); A61B (1/00142); A61B (2017/0256)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4132227	12/1978	Ibe	N/A	N/A
4318401	12/1981	Zimmerman	N/A	N/A
4573448	12/1985	Kambin	N/A	N/A
4646738	12/1986	Trott	N/A	N/A
4678459	12/1986	Onik et al.	N/A	N/A
4807593	12/1988	Ito	N/A	N/A
4863430	12/1988	Klyce et al.	N/A	N/A
4874375	12/1988	Ellison	N/A	N/A
4888146	12/1988	Dandeneau	N/A	N/A
5080662	12/1991	Paul	N/A	N/A
5195541	12/1992	Obenchain	N/A	N/A
5207213	12/1992	Auhll et al.	N/A	N/A
5285795	12/1993	Ryan et al.	N/A	N/A
5395317	12/1994	Kambin	N/A	N/A
5439464	12/1994	Shapiro	N/A	N/A
5529580	12/1995	Kusunoki et al.	N/A	N/A
5540706	12/1995	Aust et al.	N/A	N/A
5569290	12/1995	McAfee	N/A	N/A
5591187	12/1996	Dekel	N/A	N/A
5601569	12/1996	Pisharodi	N/A	N/A
5615690	12/1996	Giurtino et al.	N/A	N/A
5618293	12/1996	Sample et al.	N/A	N/A
5662300	12/1996	Michelson	N/A	N/A
5688222	12/1996	Hluchy et al.	N/A	N/A
5697888	12/1996	Kobayashi et al.	N/A	N/A
5730754	12/1997	Obenchain	N/A	N/A
5733242	12/1997	Rayburn et al.	N/A	N/A
5735792	12/1997	Vanden Hoek et al.	N/A	N/A
5749602	12/1997	Delaney et al.	N/A	N/A
5792044	12/1997	Foley et al.	N/A	N/A
5820623	12/1997	Ng	N/A	N/A
5885300	12/1998	Tokuhashi et al.	N/A	N/A
5894369	12/1998	Akiba et al.	N/A	N/A
5899425	12/1998	Corey Jr. et al.	N/A	N/A
5928137	12/1998	Green	N/A	N/A
5954635	12/1998	Foley et al.	N/A	N/A

5976075	12/1998	Beane et al.	N/A	N/A
5989183	12/1998	Reisdorf et al.	N/A	N/A
6017333	12/1999	Bailey	N/A	N/A
6033105	12/1999	Barker et al.	N/A	N/A
6053907	12/1999	Zirps	N/A	N/A
6063021	12/1999	Hossain et al.	N/A	N/A
6110182	12/1999	Mowlai-Ashtiani	N/A	N/A
6126592	12/1999	Proch et al.	N/A	N/A
6139563	12/1999	Cosgrove, III et al.	N/A	N/A
6200322	12/2000	Branch et al.	N/A	N/A
6217509	12/2000	Foley et al.	N/A	N/A
6234961	12/2000	Gray	N/A	N/A
6283966	12/2000	Houfburg	N/A	N/A
6286179	12/2000	Byrne	N/A	N/A
6296644	12/2000	Saurat et al.	N/A	N/A
6322498	12/2000	Gravenstein et al.	N/A	N/A
6354992	12/2001	Kato	N/A	N/A
6357710	12/2001	Fielden et al.	N/A	N/A
6371968	12/2001	Kogasaka et al.	N/A	N/A
6383191	12/2001	Zdeblick et al.	N/A	N/A
6447446	12/2001	Smith et al.	N/A	N/A
6468289	12/2001	Bonutti	N/A	N/A
6520495	12/2002	La Mendola	N/A	N/A
6558407	12/2002	Ivanko et al.	N/A	N/A
6575899	12/2002	Foley et al.	N/A	N/A
6579281	12/2002	Palmer et al.	N/A	N/A
6596008	12/2002	Kambin	N/A	N/A
6626830	12/2002	Califiore et al.	N/A	N/A
6648915	12/2002	Sazy	N/A	N/A
6663563	12/2002	Sharratt	N/A	N/A
6676597	12/2003	Guenst et al.	N/A	N/A
6679833	12/2003	Smith et al.	N/A	N/A
6685724	12/2003	Haluck	N/A	N/A
6688564	12/2003	Salvermoser et al.	N/A	N/A
6758809	12/2003	Briscoe et al.	N/A	N/A
6808505	12/2003	Kadan	N/A	N/A
6887198	12/2004	Phillips et al.	N/A	N/A
6983930	12/2005	La Mendola et al.	N/A	N/A
7001342	12/2005	Faciszewski	N/A	N/A
7087058	12/2005	Cragg	N/A	N/A
7104986	12/2005	Hovda et al.	N/A	N/A
7137949	12/2005	Scirica et al.	N/A	N/A
7179261	12/2006	Sicvol et al.	N/A	N/A
7182731	12/2006	Nguyen et al.	N/A	N/A
7226413	12/2006	McKinley	N/A	N/A
7341556	12/2007	Shalman	N/A	N/A
7434325	12/2007	Foley et al.	N/A	N/A
7491168	12/2008	Raymond et al.	N/A	N/A
7591790	12/2008	Pflueger	N/A	N/A
7594888	12/2008	Raymond et al.	N/A	N/A

7618431	12/2008	Roehm, III et al.	N/A	N/A
7636596	12/2008	Solar	N/A	N/A
7637905	12/2008	Saadat et al.	N/A	N/A
7641659	12/2009	Emstad et al.	N/A	N/A
7715925	12/2009	Hafer et al.	N/A	N/A
7766313	12/2009	Panosian	N/A	N/A
7771384	12/2009	Ravo	N/A	N/A
7794456	12/2009	Sharps et al.	N/A	N/A
7794469	12/2009	Kao et al.	N/A	N/A
7811303	12/2009	Fallin et al.	N/A	N/A
7931579	12/2010	Bertolero et al.	N/A	N/A
7946981	12/2010	Cubb	N/A	N/A
7951141	12/2010	Sharps et al.	N/A	N/A
7959564	12/2010	Ritland	N/A	N/A
7988623	12/2010	Pagliuca et al.	N/A	N/A
8007492	12/2010	DiPoto et al.	N/A	N/A
8038606	12/2010	Otawara	N/A	N/A
8043381	12/2010	Hestad et al.	N/A	N/A
8062218	12/2010	Sebastian et al.	N/A	N/A
8079952	12/2010	Fujimoto	N/A	N/A
8092464	12/2011	McKay	N/A	N/A
8096944	12/2011	Harrel	N/A	N/A
8202216	12/2011	Melkent et al.	N/A	N/A
8206357	12/2011	Bettuchi	N/A	N/A
8230863	12/2011	Ravikumar et al.	N/A	N/A
8236006	12/2011	Hamada	N/A	N/A
8267896	12/2011	Hartoumbekis et al.	N/A	N/A
8303492	12/2011	Ito	N/A	N/A
8333690	12/2011	Ikeda	N/A	N/A
8360970	12/2012	Mangiardi	N/A	N/A
8372131	12/2012	Hestad et al.	N/A	N/A
8382048	12/2012	Nesper et al.	N/A	N/A
8397335	12/2012	Gordin et al.	N/A	N/A
8419625	12/2012	Ito	N/A	N/A
8435174	12/2012	Cropper et al.	N/A	N/A
8460180	12/2012	Zarate et al.	N/A	N/A
8460186	12/2012	Ortiz et al.	N/A	N/A
8460310	12/2012	Stern	N/A	N/A
8518087	12/2012	Lopez et al.	N/A	N/A
8535220	12/2012	Mondschein	N/A	N/A
8556809	12/2012	Vijayanagar	N/A	N/A
8585726	12/2012	Yoon et al.	N/A	N/A
8602979	12/2012	Kitano	N/A	N/A
8622894	12/2013	Banik et al.	N/A	N/A
8636655	12/2013	Childs	N/A	N/A
8648932	12/2013	Talbert et al.	N/A	N/A
8688186	12/2013	Mao et al.	N/A	N/A
8690764	12/2013	Clark et al.	N/A	N/A
8721536	12/2013	Marino et al.	N/A	N/A
8740779	12/2013	Yoshida	N/A	N/A

8784421	12/2013	Carrison et al.	N/A	N/A
8821378	12/2013	Morgenstern Lopez et al.	N/A	N/A
8834507	12/2013	Mire et al.	N/A	N/A
8845734	12/2013	Weiman	N/A	N/A
8852242	12/2013	Morgenstern Lopez et al.	N/A	N/A
8870753	12/2013	Boulais et al.	N/A	N/A
8870756	12/2013	Maurice	N/A	N/A
8876712	12/2013	Yee et al.	N/A	N/A
8888689	12/2013	Poll et al.	N/A	N/A
8888813	12/2013	To	N/A	N/A
8894573	12/2013	Loftus et al.	N/A	N/A
8894653	12/2013	Solsberg et al.	N/A	N/A
8926502	12/2014	Levy et al.	N/A	N/A
8932207	12/2014	Greenburg et al.	N/A	N/A
8932360	12/2014	Womble et al.	N/A	N/A
8936545	12/2014	To	N/A	N/A
8936605	12/2014	Greenberg	N/A	N/A
8952312	12/2014	Blanquart et al.	N/A	N/A
8961404	12/2014	Ito	N/A	N/A
8972714	12/2014	Talbert et al.	N/A	N/A
8974381	12/2014	Lovell et al.	N/A	N/A
8986199	12/2014	Weisenburgh, II et al.	N/A	N/A
8992580	12/2014	Bar et al.	N/A	N/A
9028522	12/2014	Prado	N/A	N/A
9050036	12/2014	Poll et al.	N/A	N/A
9050037	12/2014	Poll et al.	N/A	N/A
9050146	12/2014	Woolley et al.	N/A	N/A
9055936	12/2014	Mire et al.	N/A	N/A
9072431	12/2014	Adams et al.	N/A	N/A
9078562	12/2014	Poll et al.	N/A	N/A
9123602	12/2014	Blanquart	N/A	N/A
9131948	12/2014	Fang et al.	N/A	N/A
9144374	12/2014	Maurice, Jr.	N/A	N/A
9153609	12/2014	Blanquart	N/A	N/A
9198674	12/2014	Benson et al.	N/A	N/A
9211059	12/2014	Drach et al.	N/A	N/A
9216016	12/2014	Fiechter et al.	N/A	N/A
9216125	12/2014	Sklar	N/A	N/A
9226647	12/2015	Sugawara	N/A	N/A
9232935	12/2015	Brand et al.	N/A	N/A
9247997	12/2015	Stefanchik et al.	N/A	N/A
9265491	12/2015	Lins et al.	N/A	N/A
9277928	12/2015	Morgenstern Lopez	N/A	N/A
9307972	12/2015	Lovell et al.	N/A	N/A
9320419	12/2015	Kirma et al.	N/A	N/A
RE46007	12/2015	Banik	N/A	N/A
RE46062	12/2015	James	N/A	N/A
9386971	12/2015	Casey et al.	N/A	N/A

9387313	12/2015	Culbert et al.	N/A	N/A
9414828	12/2015	Abidin et al.	N/A	N/A
9462234	12/2015	Blanquart et al.	N/A	N/A
9486296	12/2015	Mire et al.	N/A	N/A
9492194	12/2015	Morgenstern Lopez et al.	N/A	N/A
9509917	12/2015	Blanquart et al.	N/A	N/A
9510853	12/2015	Aljuri et al.	N/A	N/A
9516239	12/2015	Blanquart et al.	N/A	N/A
9522017	12/2015	Poll et al.	N/A	N/A
9526401	12/2015	Saadat et al.	N/A	N/A
9579012	12/2016	Vazales et al.	N/A	N/A
9603510	12/2016	Ammirati	N/A	N/A
9603610	12/2016	Richter et al.	N/A	N/A
9610007	12/2016	Kienzle et al.	N/A	N/A
9610095	12/2016	To	N/A	N/A
9622650	12/2016	Blanquart	N/A	N/A
9629521	12/2016	Ratnakar	N/A	N/A
9641815	12/2016	Richardson et al.	N/A	N/A
9655605	12/2016	Serowski et al.	N/A	N/A
9655639	12/2016	Mark	N/A	N/A
9668643	12/2016	Kennedy, II et al.	N/A	N/A
9675235	12/2016	Lieponis	N/A	N/A
9700378	12/2016	Mowlai-Ashtiani	N/A	N/A
9706905	12/2016	Levy	N/A	N/A
10111712	12/2017	Chegini et al.	N/A	N/A
10561427	12/2019	Weitzman et al.	N/A	N/A
10576231	12/2019	Gunday et al.	N/A	N/A
10682130	12/2019	White et al.	N/A	N/A
10758220	12/2019	White et al.	N/A	N/A
10869659	12/2019	Thommen et al.	N/A	N/A
10874425	12/2019	Thommen et al.	N/A	N/A
10987129	12/2020	Thommen et al.	N/A	N/A
11000312	12/2020	Thommen et al.	N/A	N/A
11331090	12/2021	Thommen et al.	N/A	N/A
11344190	12/2021	Thommen et al.	N/A	N/A
11439380	12/2021	Thommen et al.	N/A	N/A
11559328	12/2022	Richter et al.	N/A	N/A
11672562	12/2022	Thommen et al.	N/A	N/A
11712264	12/2022	Thommen et al.	N/A	N/A
11744447	12/2022	Thommen et al.	N/A	N/A
11793546	12/2022	Thommen et al.	N/A	N/A
11801070	12/2022	White et al.	N/A	N/A
11806043	12/2022	White et al.	N/A	N/A
11883064	12/2023	Thommen et al.	N/A	N/A
12150636	12/2023	Thommen et al.	N/A	N/A
12193704	12/2024	Richter et al.	N/A	N/A
2002/0022762	12/2001	Beane et al.	N/A	N/A
2002/0035313	12/2001	Scirica et al.	N/A	N/A
2002/0091390	12/2001	Michelson	N/A	N/A

2002/0138020	12/2001	Pflueger	N/A	N/A
2002/0165560	12/2001	Danitz et al.	N/A	N/A
2003/0083555	12/2002	Hunt et al.	N/A	N/A
2003/0083688	12/2002	Simonson	N/A	N/A
2003/0171744	12/2002	Leung et al.	N/A	N/A
2003/0191474	12/2002	Cragg et al.	N/A	N/A
2004/0092940	12/2003	Zwirnmann	N/A	N/A
2004/0122446	12/2003	Solar	N/A	N/A
2004/0127992	12/2003	Serhan et al.	N/A	N/A
2004/0143165	12/2003	Alleyne	N/A	N/A
2004/0158260	12/2003	Blau et al.	N/A	N/A
2004/0158286	12/2003	Roux et al.	N/A	N/A
2004/0249246	12/2003	Campos	N/A	N/A
2005/0021040	12/2004	Bertagnoli	N/A	N/A
2005/0075540	12/2004	Shluzas et al.	N/A	N/A
2005/0075644	12/2004	DiPoto et al.	N/A	N/A
2005/0080435	12/2004	Smith et al.	N/A	N/A
2005/0085692	12/2004	Kiehn et al.	N/A	N/A
2005/0090848	12/2004	Adams	N/A	N/A
2005/0107671	12/2004	McKinley	N/A	N/A
2005/0137461	12/2004	Marchek et al.	N/A	N/A
2005/0165420	12/2004	Cha	N/A	N/A
2005/0187570	12/2004	Nguyen et al.	N/A	N/A
2005/0192589	12/2004	Raymond et al.	N/A	N/A
2005/0256525	12/2004	Culbert et al.	N/A	N/A
2006/0020165	12/2005	Adams	N/A	N/A
2006/0041270	12/2005	Lenker et al.	N/A	N/A
2006/0052671	12/2005	McCarthy	N/A	N/A
2006/0074445	12/2005	Gerber et al.	N/A	N/A
2006/0142643	12/2005	Parker	N/A	N/A
2006/0161189	12/2005	Harp	N/A	N/A
2006/0173521	12/2005	Pond, Jr. et al.	N/A	N/A
2006/0200186	12/2005	Marchek et al.	N/A	N/A
2006/0206118	12/2005	Kim et al.	N/A	N/A
2006/0241350	12/2005	Nowitzke et al.	N/A	N/A
2006/0264895	12/2005	Flanders	N/A	N/A
2007/0016223	12/2006	Pagliuca et al.	N/A	N/A
2007/0049794	12/2006	Glassenberg et al.	N/A	N/A
2007/0055259	12/2006	Norton et al.	N/A	N/A
2007/0129634	12/2006	Hickey et al.	N/A	N/A
2007/0149975	12/2006	Oliver et al.	N/A	N/A
2007/0162223	12/2006	Clark	N/A	N/A
2007/0203396	12/2006	McCutcheon et al.	N/A	N/A
2007/0213716	12/2006	Lenke et al.	N/A	N/A
2007/0225556	12/2006	Ortiz et al.	N/A	N/A
2007/0249899	12/2006	Seifert	N/A	N/A
2007/0255100	12/2006	Barlow et al.	N/A	N/A
2007/0260113	12/2006	Otawara	N/A	N/A
2007/0260120	12/2006	Otawara	N/A	N/A
2007/0260184	12/2006	Justis et al.	N/A	N/A

2007/0270866	12/2006	von Jako	N/A	N/A
2008/0015621	12/2007	Emanuel	N/A	N/A
2008/0033251	12/2007	Araghi	N/A	N/A
2008/0064921	12/2007	Larkin et al.	N/A	N/A
2008/0064928	12/2007	Otawara	N/A	N/A
2008/0081951	12/2007	Frasier et al.	N/A	N/A
2008/0139879	12/2007	Olson et al.	N/A	N/A
2008/0147109	12/2007	Kambin et al.	N/A	N/A
2008/0183189	12/2007	Teichman et al.	N/A	N/A
2008/0188714	12/2007	McCaffrey	N/A	N/A
2008/0242930	12/2007	Hanypsiak et al.	N/A	N/A
2008/0260342	12/2007	Kuroiwa	N/A	N/A
2009/0012578	12/2008	Carrez et al.	N/A	N/A
2009/0018566	12/2008	Escudero et al.	N/A	N/A
2009/0024158	12/2008	Viker	N/A	N/A
2009/0062604	12/2008	Minosawa et al.	N/A	N/A
2009/0062871	12/2008	Chin et al.	N/A	N/A
2009/0105543	12/2008	Miller et al.	N/A	N/A
2009/0125032	12/2008	Gutierrez et al.	N/A	N/A
2009/0149857	12/2008	Culbert et al.	N/A	N/A
2009/0156898	12/2008	Ichimura	N/A	N/A
2009/0187080	12/2008	Seex	N/A	N/A
2009/0240111	12/2008	Kessler et al.	N/A	N/A
2009/0247831	12/2008	Miyamoto et al.	N/A	N/A
2009/0253965	12/2008	Miyamoto	N/A	N/A
2009/0259184	12/2008	Okoniewski	N/A	N/A
2009/0264895	12/2008	Gasperut et al.	N/A	N/A
2009/0287061	12/2008	Feigenbaum et al.	N/A	N/A
2009/0318765	12/2008	Torii	N/A	N/A
2010/0004651	12/2009	Biyani	N/A	N/A
2010/0022841	12/2009	Takahashi et al.	N/A	N/A
2010/0036384	12/2009	Gorek et al.	N/A	N/A
2010/0076476	12/2009	To et al.	N/A	N/A
2010/0081875	12/2009	Fowler et al.	N/A	N/A
2010/0114147	12/2009	Biyani	N/A	N/A
2010/0151161	12/2009	Da Rolo	N/A	N/A
2010/0161060	12/2009	Schaller et al.	N/A	N/A
2010/0240961	12/2009	Aferzon	N/A	N/A
2010/0256446	12/2009	Raju	N/A	N/A
2010/0268241	12/2009	Flom et al.	N/A	N/A
2010/0280325	12/2009	Ibrahim et al.	N/A	N/A
2010/0284580	12/2009	OuYang et al.	N/A	N/A
2010/0286477	12/2009	OuYang et al.	N/A	N/A
2010/0312053	12/2009	Larsen	N/A	N/A
2010/0312103	12/2009	Gorek et al.	N/A	N/A
2010/0317928	12/2009	Subramaniam	N/A	N/A
2010/0324506	12/2009	Pellegrino et al.	N/A	N/A
2011/0009905	12/2010	Shluzas	N/A	N/A
2011/0028791	12/2010	Marino et al.	N/A	N/A
2011/0040333	12/2010	Simonson et al.	N/A	N/A

2011/0054507	12/2010	Batten et al.	N/A	N/A
2011/0056500	12/2010	Shin et al.	N/A	N/A
2011/0073594	12/2010	Bonn	N/A	N/A
2011/0098628	12/2010	Yeung et al.	N/A	N/A
2011/0106261	12/2010	Chin et al.	N/A	N/A
2011/0112588	12/2010	Linderman et al.	N/A	N/A
2011/0125158	12/2010	Diwan et al.	N/A	N/A
2011/0130634	12/2010	Solitario, Jr. et al.	N/A	N/A
2011/0201888	12/2010	Verner	N/A	N/A
2011/0230965	12/2010	Schell et al.	N/A	N/A
2011/0251597	12/2010	Bharadwaj et al.	N/A	N/A
2011/0257478	12/2010	Kleiner et al.	N/A	N/A
2011/0295070	12/2010	Yasunaga	N/A	N/A
2011/0319941	12/2010	Bar et al.	N/A	N/A
2012/0016192	12/2011	Jansen et al.	N/A	N/A
2012/0029412	12/2011	Yeung et al.	N/A	N/A
2012/0095296	12/2011	Trieu et al.	N/A	N/A
2012/0101338	12/2011	Cormac	N/A	N/A
2012/0111682	12/2011	Andre	N/A	N/A
2012/0116170	12/2011	Vayser et al.	N/A	N/A
2012/0157788	12/2011	Serowski et al.	N/A	N/A
2012/0172664	12/2011	Hayman et al.	N/A	N/A
2012/0197320	12/2011	Bereczki	N/A	N/A
2012/0209273	12/2011	Zaretzka et al.	N/A	N/A
2012/0221007	12/2011	Batten et al.	N/A	N/A
2012/0232350	12/2011	Seex	N/A	N/A
2012/0232552	12/2011	Morgenstern Lopez et al.	N/A	N/A
2012/0259173	12/2011	Waldron et al.	N/A	N/A
2012/0265022	12/2011	Menn	N/A	N/A
2012/0296171	12/2011	Lovell et al.	N/A	N/A
2012/0298820	12/2011	Manolidis	N/A	N/A
2012/0316400	12/2011	Vijayanagar	N/A	N/A
2012/0323080	12/2011	DeRidder et al.	N/A	N/A
2013/0030535	12/2012	Foley et al.	N/A	N/A
2013/0103067	12/2012	Fabro et al.	N/A	N/A
2013/0103103	12/2012	Mire et al.	N/A	N/A
2013/0150670	12/2012	Cormac	N/A	N/A
2013/0150674	12/2012	Haig et al.	N/A	N/A
2013/0172674	12/2012	Kennedy, II et al.	N/A	N/A
2013/0172676	12/2012	Levy et al.	N/A	N/A
2013/0211202	12/2012	Perez-Cruet et al.	N/A	N/A
2013/0282022	12/2012	Yousef	N/A	N/A
2013/0289354	12/2012	Ainsworth et al.	N/A	N/A
2013/0289399	12/2012	Choi et al.	N/A	N/A
2013/0303846	12/2012	Cybulski et al.	N/A	N/A
2013/0304106	12/2012	Breznock	N/A	N/A
2013/0331730	12/2012	Femech et al.	N/A	N/A
2014/0025121	12/2013	Foley et al.	N/A	N/A
2014/0066940	12/2013	Fang et al.	N/A	N/A

2014/0074170	12/2013	Mertens et al.	N/A	N/A
2014/0088367	12/2013	DiMauro et al.	N/A	N/A
2014/0128979	12/2013	Womble et al.	N/A	N/A
2014/0142584	12/2013	Sweeney	N/A	N/A
2014/0148647	12/2013	Okazaki	N/A	N/A
2014/0163319	12/2013	Blanquart et al.	N/A	N/A
2014/0180321	12/2013	Dias et al.	N/A	N/A
2014/0194697	12/2013	Seex	N/A	N/A
2014/0215736	12/2013	Gomez et al.	N/A	N/A
2014/0221749	12/2013	Grant et al.	N/A	N/A
2014/0222092	12/2013	Anderson et al.	N/A	N/A
2014/0243604	12/2013	Vennard et al.	N/A	N/A
2014/0257296	12/2013	Morgenstern Lopez	N/A	N/A
2014/0257332	12/2013	Zastrozna	N/A	N/A
2014/0257489	12/2013	Warren et al.	N/A	N/A
2014/0261545	12/2013	Jenkins et al.	N/A	N/A
2014/0275793	12/2013	Song	N/A	N/A
2014/0275799	12/2013	Schuele	N/A	N/A
2014/0276840	12/2013	Richter et al.	N/A	N/A
2014/0276916	12/2013	Ahluwalia et al.	N/A	N/A
2014/0277204	12/2013	Sandhu	N/A	N/A
2014/0285644	12/2013	Richardson et al.	N/A	N/A
2014/0318582	12/2013	Mowlai-Ashtiani	N/A	N/A
2014/0336764	12/2013	Masson et al.	N/A	N/A
2014/0357945	12/2013	Duckworth	N/A	N/A
2014/0371763	12/2013	Poll et al.	N/A	N/A
2014/0378985	12/2013	Mafi	N/A	N/A
2015/0018623	12/2014	Friedrich et al.	N/A	N/A
2015/0065795	12/2014	Titus	N/A	N/A
2015/0073218	12/2014	Ito	N/A	N/A
2015/0087913	12/2014	Dang et al.	N/A	N/A
2015/0094610	12/2014	Morgenstern Lopez et al.	N/A	N/A
2015/0112398	12/2014	Morgenstern Lopez et al.	N/A	N/A
2015/0133727	12/2014	Bacich et al.	N/A	N/A
2015/0164496	12/2014	Karpowicz et al.	N/A	N/A
2015/0216593	12/2014	Biyani	N/A	N/A
2015/0223671	12/2014	Sung et al.	N/A	N/A
2015/0223676	12/2014	Bayer et al.	N/A	N/A
2015/0230697	12/2014	Phee et al.	N/A	N/A
2015/0238073	12/2014	Charles et al.	N/A	N/A
2015/0250377	12/2014	Iizuka	N/A	N/A
2015/0257746	12/2014	Seifert	N/A	N/A
2015/0272694	12/2014	Charles	N/A	N/A
2015/0313585	12/2014	Abidin et al.	N/A	N/A
2015/0313633	12/2014	Gross et al.	N/A	N/A
2015/0327757	12/2014	Rozenfeld et al.	N/A	N/A
2015/0335389	12/2014	Greenberg	N/A	N/A
2015/0342619	12/2014	Weitzman	N/A	N/A

2015/0342621	12/2014	Jackson, III	N/A	N/A
2015/0366552	12/2014	Sasaki et al.	N/A	N/A
2015/0374213	12/2014	Maurice, Jr.	N/A	N/A
2015/0374354	12/2014	Boyd et al.	N/A	N/A
2016/0007982	12/2015	Liu et al.	N/A	N/A
2016/0015467	12/2015	Vayser et al.	N/A	N/A
2016/0030061	12/2015	Thommen et al.	N/A	N/A
2016/0066965	12/2015	Chegini et al.	N/A	N/A
2016/0067003	12/2015	Chegini et al.	N/A	N/A
2016/0074029	12/2015	O'Connell et al.	N/A	N/A
2016/0095505	12/2015	Johnson et al.	N/A	N/A
2016/0106408	12/2015	Ponmudi et al.	N/A	N/A
2016/0166135	12/2015	Fiset	N/A	N/A
2016/0174814	12/2015	Igov	N/A	N/A
2016/0175004	12/2015	Dejima	N/A	N/A
2016/0192921	12/2015	Pimenta et al.	N/A	N/A
2016/0213500	12/2015	Beger et al.	N/A	N/A
2016/0228280	12/2015	Schuele et al.	N/A	N/A
2016/0235284	12/2015	Yoshida et al.	N/A	N/A
2016/0235427	12/2015	Rudser	N/A	N/A
2016/0256036	12/2015	Gomez et al.	N/A	N/A
2016/0287264	12/2015	Chegini et al.	N/A	N/A
2016/0296220	12/2015	Mast et al.	N/A	N/A
2016/0324541	12/2015	Pellegrino et al.	N/A	N/A
2016/0345952	12/2015	Kucharzyk et al.	N/A	N/A
2016/0353978	12/2015	Miller et al.	N/A	N/A
2016/0367294	12/2015	Boyd et al.	N/A	N/A
2017/0003493	12/2016	Zhao	N/A	N/A
2017/0007226	12/2016	Fehling	N/A	N/A
2017/0007294	12/2016	Iwasaka et al.	N/A	N/A
2017/0020627	12/2016	Tesar et al.	N/A	N/A
2017/0027606	12/2016	Cappelleri et al.	N/A	N/A
2017/0042408	12/2016	Washburn et al.	N/A	N/A
2017/0042411	12/2016	Kang et al.	N/A	N/A
2017/0065269	12/2016	Thommen et al.	N/A	N/A
2017/0065287	12/2016	Silva et al.	N/A	N/A
2017/0086878	12/2016	Geist	N/A	N/A
2017/0086939	12/2016	Vayser et al.	N/A	N/A
2017/0105770	12/2016	Woolley et al.	N/A	N/A
2017/0135699	12/2016	Wolf	N/A	N/A
2017/0156755	12/2016	Poll et al.	N/A	N/A
2017/0156814	12/2016	Thommen et al.	N/A	N/A
2017/0196549	12/2016	Piskun et al.	N/A	N/A
2017/0224391	12/2016	Biester et al.	N/A	N/A
2017/0245930	12/2016	Brannan et al.	N/A	N/A
2017/0280969	12/2016	Levy et al.	N/A	N/A
2017/0296038	12/2016	Gordon et al.	N/A	N/A
2017/0311789	12/2016	Mulcahey et al.	N/A	N/A
2018/0008138	12/2017	Thommen et al.	N/A	N/A
2018/0008253	12/2017	Thommen et al.	N/A	N/A

2018/0014858	12/2017	Biester et al.	N/A	N/A
2018/0014890	12/2017	Stanton et al.	N/A	N/A
2018/0098788	12/2017	White et al.	N/A	N/A
2018/0098789	12/2017	White et al.	N/A	N/A
2018/0110503	12/2017	Flock et al.	N/A	N/A
2018/0110506	12/2017	Thommen et al.	N/A	N/A
2018/0153592	12/2017	Larson	N/A	N/A
2018/0214016	12/2017	Thommen et al.	N/A	N/A
2018/0249992	12/2017	Truckey	N/A	N/A
2018/0311051	12/2017	Donaldson et al.	N/A	N/A
2018/0333061	12/2017	Pracyk et al.	N/A	N/A
2019/0105459	12/2018	Lajarín Barquero	N/A	N/A
2019/0209154	12/2018	Richter et al.	N/A	N/A
2019/0216454	12/2018	Thommen et al.	N/A	N/A
2019/0216486	12/2018	Weitzman	N/A	N/A
2019/0374236	12/2018	Weitzman et al.	N/A	N/A
2020/0268368	12/2019	White et al.	N/A	N/A
2020/0360048	12/2019	White et al.	N/A	N/A
2020/0367737	12/2019	Matsumoto et al.	N/A	N/A
2021/0052298	12/2020	Thommen et al.	N/A	N/A
2021/0186316	12/2020	Thommen et al.	N/A	N/A
2021/0204973	12/2020	Thommen et al.	N/A	N/A
2021/0282806	12/2020	Thommen et al.	N/A	N/A
2022/0192700	12/2021	Thommen et al.	N/A	N/A
2022/0249125	12/2021	Thommen et al.	N/A	N/A
2022/0265134	12/2021	Thommen et al.	N/A	N/A
2022/0378408	12/2021	Thommen et al.	N/A	N/A
2023/0135764	12/2022	Richter et al.	N/A	N/A
2024/0023987	12/2023	Thommen et al.	N/A	N/A
2024/0023989	12/2023	White et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2659368	12/2003	CN	N/A
1735380	12/2005	CN	N/A
1742685	12/2005	CN	N/A
101141928	12/2007	CN	N/A
101426437	12/2008	CN	N/A
201290744	12/2008	CN	N/A
101594830	12/2008	CN	N/A
101815476	12/2009	CN	N/A
102448380	12/2011	CN	N/A
202211669	12/2011	CN	N/A
102843984	12/2011	CN	N/A
202740102	12/2012	CN	N/A
102727309	12/2013	CN	N/A
102497828	12/2014	CN	N/A
102821673	12/2015	CN	N/A
103976779	12/2015	CN	N/A
106659375	12/2016	CN	N/A

106794032	12/2016	CN	N/A
103533904	12/2016	CN	N/A
105286776	12/2016	CN	N/A
107126254	12/2019	CN	N/A
111278365	12/2019	CN	N/A
9415039	12/1993	DE	N/A
29916026	12/1998	DE	N/A
20309079	12/2002	DE	N/A
0537116	12/1992	EP	N/A
0890341	12/1998	EP	N/A
0807415	12/2002	EP	N/A
0891156	12/2003	EP	N/A
2491848	12/2013	EP	N/A
2481727	12/2011	GB	N/A
H05207962	12/1992	JP	N/A
H0681501	12/1993	JP	N/A
H08126605	12/1995	JP	N/A
H08278456	12/1995	JP	N/A
H11313795	12/1998	JP	N/A
2000126190	12/1999	JP	N/A
2000511788	12/1999	JP	N/A
2001520906	12/2000	JP	N/A
2002519094	12/2001	JP	N/A
2002541901	12/2001	JP	N/A
2007007438	12/2006	JP	N/A
2007508050	12/2006	JP	N/A
2008508943	12/2007	JP	N/A
2009543612	12/2008	JP	N/A
2011512943	12/2010	JP	N/A
2012045325	12/2011	JP	N/A
2012527327	12/2011	JP	N/A
2012527930	12/2011	JP	N/A
2013059688	12/2012	JP	N/A
2013538624	12/2012	JP	N/A
2014054561	12/2013	JP	N/A
2014517710	12/2013	JP	N/A
2015500680	12/2014	JP	N/A
2015521913	12/2014	JP	N/A
2019505312	12/2018	JP	N/A
2022079758	12/2021	JP	N/A
1996029014	12/1995	WO	N/A
1997034536	12/1996	WO	N/A
2001056490	12/2000	WO	N/A
2001089371	12/2000	WO	N/A
2002002016	12/2001	WO	N/A
2004039235	12/2003	WO	N/A
2004103430	12/2003	WO	N/A
2006017507	12/2005	WO	N/A
2006096517	12/2005	WO	N/A
2007059068	12/2006	WO	N/A

2008121162	12/2007	WO	N/A
2009033207	12/2008	WO	N/A
2009108318	12/2008	WO	N/A
2010111629	12/2009	WO	N/A
2010135537	12/2009	WO	N/A
2010138083	12/2009	WO	N/A
2012004766	12/2011	WO	N/A
2012040239	12/2011	WO	N/A
2012122294	12/2011	WO	N/A
2013033426	12/2012	WO	N/A
2013059640	12/2012	WO	N/A
2013074396	12/2012	WO	N/A
2014041540	12/2013	WO	N/A
2014050236	12/2013	WO	N/A
2014100761	12/2013	WO	N/A
2014185334	12/2013	WO	N/A
2014188796	12/2013	WO	N/A
2015026793	12/2014	WO	N/A
2015033907	12/2014	WO	N/A
2015175635	12/2014	WO	N/A
2016111373	12/2015	WO	N/A
2016131077	12/2015	WO	N/A
2016168673	12/2015	WO	N/A
2016201292	12/2015	WO	N/A
2017006684	12/2016	WO	N/A
2017015480	12/2016	WO	N/A
2017040873	12/2016	WO	N/A
2017083648	12/2016	WO	N/A
2017162895	12/2016	WO	N/A
2018131039	12/2017	WO	N/A
2018147225	12/2017	WO	N/A
2018165365	12/2017	WO	N/A
2019026206	12/2018	WO	N/A
2021209987	12/2020	WO	N/A

OTHER PUBLICATIONS

Chinese Office Action issued for Application No. 2021100372023 dated Nov. 24, 2023 (14 pages).
cited by applicant

Australian Examination Report for Application No. 2018225113, issued Jul. 15, 2022 (4 pages).
cited by applicant

Chinese Office Action for Application No. 201880013056.7, dated Mar. 25, 2021 (15 pages). cited
by applicant

Chinese Office Action for Application No. 201880013056.7, dated Oct. 26, 2021 (6 pages). cited
by applicant

Chinese Office Action for Application No. 201880016688.9, dated Mar. 8, 2022, with Translation
(21 pages). cited by applicant

Chinese Decision of Reexamination issued for 201680051245.4, dated Aug. 23, 2022, (23 pages).
cited by applicant

Chinese Office Action and Search Report issued for Application No. 201880058099, dated Nov. 2,
2022 (14 pages). cited by applicant

Clinical Workbook of Neurosurgery in Xijing [M], edited by Fei Zhou, Xi'an: Fourth Military Medical University Press, Aug. 2012, pp. 431-432: an endoscope with a diameter of 3.7 mm is used for intramedullary examination). cited by applicant

Extended European Search Report for Application No. 16843037.9; issued Mar. 14, 2019 (8 pages). cited by applicant

Extended European Search Report for Application No. 18758290.3, issued Nov. 27, 2020 (7 pages). cited by applicant

Extended European Search Report for Application No. 20212396.4, issued Sep. 23, 2021 (9 pages). cited by applicant

Extended European Search Report for Application No. 18854503.2, issued Apr. 15, 2021 (10 pages). cited by applicant

Extended European Search Report for Application No. 19758283.6, issued Sep. 28, 2021 (8 pages). cited by applicant

Extended European Search Report for Application No. 18764249.1, issued Mar. 11, 2022 (8 pages). cited by applicant

Extended European Search Report for Application No. 18764504.9, issued Mar. 18, 2022 (7 pages). cited by applicant

Extended European Search Report for Application No. 18764370.5, issued Mar. 25, 2022 (8 pages). cited by applicant

Hott, J. S., et al., "A new table-fixed retractor for anterior odontoid screw fixation: technical note," J Neurosurg (Spine 3), 2003, v. 98, pp. 118-120. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2015/043554, mailed Nov. 19, 2015 (8 pages). cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2015/048485, mailed Feb. 9, 2016. (16 pages). cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2015/060978, mailed Feb. 15, 2016 (8 pages). cited by applicant

Invitation to Pay Additional Fees for Application No. PCT/US2016/050022, mailed Nov. 3, 2016 (2 pages). cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2016/050022, issued Feb. 1, 2017 (19 pages). cited by applicant

International Preliminary Report on Patentability issued for Application No. PCT/US2016/050022, mailed Mar. 15, 2018. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2018/018905, mailed May 7, 2018 (10 pages). cited by applicant

International Search Report for Application No. PCT/IB2018/057367, mailed Jan. 29, 2019, (4 pages). cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2018/021449, mailed Aug. 27, 2018 (13 pages) . cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2018/021454, mailed Jul. 3, 2018 (16 pages). cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2018/021466 mailed Jul. 3, 2018 (8 pages). cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2018/047136, mailed Jan. 23, 2019 (9 pages). cited by applicant

International Search Report and Written Opinion for Application No. PCT/EP2020/056706, mailed Jun. 9, 2020 (17 pages). cited by applicant

International Search Report and Written Opinion issued for Application No. PCT/US2018/021472, issued Jul. 19, 2018. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US19/18700, mailed

May 3, 2019 (7 pages). cited by applicant

Ipreburg, M, "Percutaneous Transforaminal Endoscopic Discectomy: The Thessys Method," in Lewandrowski, K., et al., Minimally Invasive Spinal Fusion Techniques, Summit Communications, 2008 pp. 65-81. cited by applicant

Japanese Office Action issued in Appln. No. JP 2018-511695, mailed May 26, 2020 (21 pages). cited by applicant

Japanese Office Action for Application No. JP 2019-548591, issued Oct. 5, 2021, (14 pages). cited by applicant

Japanese Office Action for Application No. JP 2019-545263, issued Jan. 4, 2022 (11 pages). cited by applicant

Japanese Office Action for Application No. JP 2019-545263, issued Aug. 9, 2022 (8 pages). cited by applicant

Japanese Office Action for Application No. JP 2020-513791, issued May 17, 2022 (8 pages). cited by applicant

Japanese Office Action for Application No. JP 2020-177880, issued May 31, 2022 (3 pages). cited by applicant

Japanese Decision to Grant a Patent for Application No. JP 2020-177880, issued Dec. 6, 2022 (2 pages). cited by applicant

Japanese Decision to Grant Patent for Application No. JP 2020-544278, issued Mar. 14, 2023. cited by applicant

Jung, K., et al., "A hands-free region-of-interest selection interface for solo surgery with a wide-angle endoscope: preclinical proof of concept," Surg Endosc, 2017, v. 31, pp. 974-980. cited by applicant

Regan, J. M. et al., "Burr Hole Washout versus Craniotomy for Chronic Subdural Hematoma: Patient Outcome and Cost Analysis," Plos One, Jan. 22, 2015, DOI: 10.1371/journal.pone.0115085. cited by applicant

Shalayev, S. G. et al., "Retrospective analysis and modifications of retractor systems for anterior odontoid screw fixation," Neurosurg Focus 16 (1): Article 14, 2004, pp. 1-4. cited by applicant

European Search Report for Application No. 24156567, issued Jun. 6, 2024 (8 pages). cited by applicant

Chinese First Search and Written Opinion for Application No. CN201980027429.0 dated Jan. 2, 2024 (10 pages). cited by applicant

Chinese First Search and Written Opinion for Application No. CN2020800035605 dated Jan. 8, 2024 (10 pages). cited by applicant

Japanese Notice of Reasons for Refusal for Application No. JP 2021-554717, dated Nov. 9, 2023 (4 pages). cited by applicant

U.S. Appl. No. 15/208,872, filed Jul. 13, 2016, Bone Anchor Assemblies and Related Instrumentation, Medos International Sarl. cited by applicant

U.S. Appl. No. 15/254,877, filed Sep. 1, 2016, Multi-Shield Spinal Access System, Medos International Sarl. cited by applicant

U.S. Appl. No. 15/437,792, filed Feb. 21, 2017, Multi-Shield Spinal Access System, Medos International Sarl. cited by applicant

U.S. Appl. No. 62/507,930, filed May 18, 2017, Neural Health Monitoring With Functional Near Infrared (fNIR) Spectroscopy, Medos International Sarl. cited by applicant

U.S. Appl. No. 15/692,845, filed Aug. 31, 2017, Surgical Visualization Systems and Related Methods, Medos International Sarl. cited by applicant

U.S. Appl. No. 15/697,494, filed Sep. 7, 2017, Multi-Shield Spinal Access System, Medos International Sarl. cited by applicant

U.S. Appl. No. 15/786,846, filed Oct. 18, 2017, Devices and Methods for Surgical Retraction, Medos International Sarl. cited by applicant

U.S. Appl. No. 15/786,858, filed Oct. 18, 2017, Devices and Methods for Providing Surgical Access, Medos International Sarl. cited by applicant

U.S. Appl. No. 15/786,891, filed Oct. 18, 2017, Surgical Access Port Stabilization, Medos International Sarl. cited by applicant

U.S. Appl. No. 15/786,923, filed Oct. 18, 2017, Surgical Instrument Connectors and Related Methods, Medos International Sarl. cited by applicant

U.S. Appl. No. 15/901,435, filed Feb. 21, 2018, Surgical Visualization Systems and Related Methods, Medos International Sarl. cited by applicant

U.S. Appl. No. 15/931,839, filed May 14, 2020, Surgical Access Port Stabilization, Medos International Sarl. cited by applicant

U.S. Appl. No. 15/966,293, filed Apr. 30, 2018, Neurel Monitoring Devices and Methods, Depuy Synthes Products, Inc. cited by applicant

U.S. Appl. No. 16/352,654, filed Mar. 13, 2019, Multi-Shield Spinal Access System, Medos International Sarl. cited by applicant

U.S. Appl. No. 16/362,497, filed Mar. 22, 2019, Surgical Instrument Connectors and Related Methods, Medos International Sarl. cited by applicant

U.S. Appl. No. 16/985,200, filed Aug. 4, 2020, Devices and Methods for Providing Surgical Access, Medos International Sarl. cited by applicant

U.S. Appl. No. 17/089,695, filed Nov. 4, 2020, Multi-Shield Spinal Access System, Medos International Sarl. cited by applicant

U.S. Appl. No. 17/159,129, filed Jan. 26, 2021, Multi-Shield Spinal Access System, Medos International Sarl. cited by applicant

U.S. Appl. No. 17/192,889, filed Mar. 5, 2021, Surgical Visualization Systems and Related Methods, Medos International Sarl. cited by applicant

U.S. Appl. No. 17/214,759, filed Mar. 26, 2021, Multi-Shield Spinal Access System, Medos International Sarl. cited by applicant

U.S. Appl. No. 17/692,942, filed Mar. 11, 2022, Multi-Shield Spinal Access System, Medos International Sarl. cited by applicant

U.S. Appl. No. 17/728,967, filed Apr. 25, 2022, Surgical Visualization Systems and Related Methods, Medos International Sarl. cited by applicant

U.S. Appl. No. 17/740,305, filed May 9, 2022, Surgical Visualization Systems and Related Methods, Medos International Sarl. cited by applicant

U.S. Appl. No. 17/884,523, filed Aug. 9, 2022, Surgical Instrument Connectors and Related Methods, Medos International Sarl. cited by applicant

U.S. Appl. No. 18/091,255, filed Dec. 29, 2022, Multi-Shield Spinal Access System, Medos International Sarl. cited by applicant

U.S. Appl. No. 18/479,058, filed Sep. 30, 2023, Surgical Access Port Stabilization, Medos International Sarl. cited by applicant

U.S. Appl. No. 18/479,048, filed Sep. 30, 2023, Surgical Visualization Systems and Related Methods, Medos International Sarl. cited by applicant

U.S. Appl. No. 18/479,059, filed Sep. 30, 2023, Devices and Methods for Providing Surgical Access, Medos International Sarl. cited by applicant

Chinese Second Office Action for Application No. CN 202080035605.8 dated May 23, 2024 (9 pages). cited by applicant

European Search Report for Application No. 24156567, issued Oct. 7, 2024 (11 pages). cited by applicant

U.S. Appl. No. 18/951,589, filed Nov. 18, 2024, Surgical Instrument Connectors and Related Methods, Medos International Sarl. cited by applicant

European Search Report for Application No. 24190243.6 issued Mar. 12, 2025 (9 pages). cited by applicant

Primary Examiner: Yang; Andrew

Attorney, Agent or Firm: Barnes & Thornburg LLP

Background/Summary

CONTINUING DATA (1) This application is a continuation of U.S. patent application Ser. No. 17/214,759, filed Mar. 26, 2021. U.S. patent application Ser. No. 17/214,759 is a continuation of U.S. patent application Ser. No. 15/254,877, filed Sep. 1, 2016, (now issued as 10,987,129). U.S. patent application Ser. No. 15/254,877 claims priority from U.S. Provisional Patent Application No. 62/214,297, entitled “Multi-Shield Spinal Access System” by Thommen et al., filed Sep. 4, 2015. The entire contents of each of these applications are incorporated herein by reference.

BACKGROUND OF THE INVENTION

(1) Today, microsurgical spinal bone resections and spinal decompressions which are performed under microscopic view through mini-open tubes and retractors are becoming the standard of spinal surgical care. These access tools normally have inner diameters between about 16 mm and 30 mm. Where, as here, the approach and decompression technique are familiar to spinal surgeons, and where standard equipment and instruments can be used, these known technologies should be considered as a base from which further innovation can be made.

(2) However, the anatomic window of Kambin's triangle, through which safe disc access is possible, has very limited dimensions. This access window can be enlarged by resecting at least a part of the superior articular process. But either way, the length of a working shield needed to safely introduce the implant to the intervertebral space via this approach must be in the region of about 8-12 mm in diameter, reaching from the facet joint line to the disc entry point.

SUMMARY OF THE INVENTION

(3) The present inventors envision introducing a second, inner shield through the above-mentioned first, outer shield. The second inner shield extends past the first outer shield to arrive next to nervous tissue, thereby shielding the nerves from instruments or devices passing through to the disc space. During this step, the outer shield allows the visual, safe placement of the inner shield.

(4) In one embodiment, there is provided an outer shield (which can be, for example, a tube or a blade) comprising an access shield with a larger diameter (~12-30 mm) that reaches from the skin down to the bone line, with an inner shield having a second smaller diameter (~5-12 mm) extending past the access shield and reaches down to the disc level. This combines the benefits of the direct visual from microsurgical/mini open approaches and percutaneous techniques (FIGS. 1a-1b and 2).

(5) The outer shield has a number of features and advantages. First, it enables separation and protection of surrounding of soft tissue and visualization during a standard microsurgical decompression/bone resection work under microscopic view based on a standard procedure that a surgeon who is familiar with MIS techniques is able to perform. Second, it enables separation and protection of surrounding of soft tissue and visualization during detection and removal of the facet joint, or parts of the facet joint based on a standard procedure that a surgeon who is familiar with MIS technique is able to perform. Third, it enables identification, preparation and protection of sensitive (e.g., neural) tissue (exiting nerve root, traversing nerve root, dura) under direct visual control underneath the border between retraction-sensitive and non-retraction sensitive tissues (e.g., the facet line) based on a standard procedure that a surgeon who is familiar with MIS technique is able to perform. Fourth, it enables insertion of the inner shield and potential docking of the inner

shield in the disc space or at the vertebrae under direct visual control.

(6) Likewise, the inner shield has a number of features and advantages. First, it enables protection of nervous tissue (exiting nerve root, transverse nerve root, dura) against instruments that are introduced into the intervertebral disc. Second, it enables guidance of intradiscal instrumentation (discectomy instruments, visualization instruments, discectomy verification instruments, implant insertion instruments, bone graft filling instruments). Third, because of its small size, the shield can be inserted with minimal damage or trauma to bone and soft tissue in the area of the posterior column of the spine, comparable to percutaneous access instruments.

(7) Therefore, in accordance with the present invention, there is provided a method of accessing an intervertebral disc in a patient, comprising the steps of: a) making an incision in a skin of the patient, b) percutaneously inserting through the incision an outer shield having a substantially tubular shape (such as a tube or a multi-slotted retractor), the outer shield having a length adapted to extend from the incision to a border between sensitive and insensitive tissue (e.g., a superior articular process (SAP), or a lamina), in the spine of the patient, c) stabilization of this outer shield to a pedicle anchor, d) insertion of an outer shield integrated optical visualization instrument, e) resecting a portion of the superior articular process, and/or performing a microsurgical decompression procedure f) inserting or deploying an inner shield through or from the outer shield so that a distal end portion of the inner shield extends to the disc, the inner shield having an outer surface, g) contacting the outer surface of the shield to a nerve root to shield the nerve root, h) microsurgical decompression of any tissue deemed to be causing nerve impingement, i) extraction of the intervertebral disc material including the removal of the cartilaginous material from the vertebral endplates, j) insertion of the interbody device, and k) deployment of a mechanism of stabilization to stabilize the intervertebral segment.

(8) Also in accordance with the present invention, there is provided a method of accessing an intervertebral disc in a patient, comprising the steps of: a) making an incision in a skin of the patient, b) percutaneously inserting through the incision an outer shield having a substantially tubular shape, c) stabilization of this outer shield to a pedicle anchor, d) inserting an inner shield through the outer shield so that a distal end portion of the inner shield extends to the disc, the inner shield having an outer surface, e) contacting the outer surface of the shield to a nerve root to shield the nerve root f) microsurgical decompression of any tissue deemed to be causing nerve impingement, g) extraction of the intervertebral disc material including the removal of the cartilaginous material from the vertebral endplates, h) insertion of the interbody device, and i) deployment of a mechanism of stabilization to stabilize the intervertebral segment.

(9) Also in accordance with the present invention, there is provided an access device for accessing an intervertebral disc, comprising: a) an outer shield having a substantially tubular portion, a length adapted to extend from an incision to a border between sensitive and insensitive tissue (e.g., an articular process or a lamina), a proximal end portion, a distal end portion, an outer surface, and a longitudinal throughbore defining an inner surface, b) an inner shield having i) a first substantially tubular portion having a proximal end portion, a distal end portion, a longitudinal through-bore defining an inner surface, and an outer surface defining a diameter, and ii) a longitudinal flange extending distally from the distal end portion of the substantially tubular portion, wherein the outer surface of the inner shield substantially nests within the inner surface of the outer shield so that the flange extends distally past the distal end portion of the outer shield.

Description

DESCRIPTION OF THE FIGURES

(1) FIG. 1a shows an interbody device delivered through the access device;

(2) FIG. 1b shows an end view of the access device;

(3) FIGS. **2a** and **2b** are different views of a tube-in-tube embodiment of the access device;

(4) FIGS. **3a-3d** show different axial cross sections of the inner shield;

(5) FIG. **4** shows a necked, funnel-shaped embodiment of the inner shield;

(6) FIGS. **5-6** show different longitudinal cross sections of concentric and nonconcentric inner shields;

(7) FIG. **7** shows a jointed access device;

(8) FIG. **8a** shows a flanged embodiment of the inner shield;

(9) FIG. **8b** shows an inner shield with a proximal stop;

(10) FIG. **9** shows an access device with two ports attached to the outer shield; one port is a connector to hold the outer tube, while the other is an interface for a light source;

(11) FIG. **10** discloses a cross-section of an outer tube wherein the outer tube wall has a first channel adapted for containing a visualization unit (such as a camera) and a second channel adapted for containing a cleaning system (such as a lens cleaning device);

(12) FIG. **11** discloses a cross-section of an outer tube wherein the outer tube wall contains a lens cleaning device and a camera;

(13) FIG. **12** discloses a chip-on-tip embodiment including a cross-section of an outer tube wherein the outer tube wall has a channel containing an endoscope having a video chip near its distal end;

(14) FIG. **13** discloses a distal end of an outer tube featuring a video chip near its distal end;

(15) FIG. **14** discloses a scope holder for an endoscope;

(16) FIGS. **15 a-15b** show inner shield having proximal elbows;

(17) FIG. **16** shows an access device with a distal sharpened tip on the inner shield within an outer shield;

(18) FIG. **17** shows an access device with a positioning ring between the inner and outer shields;

(19) FIG. **18** shows an access device with a depth adjustment means formed by the inner and outer shields;

(20) FIG. **19** discloses an integrated retractor having a flat inner face housed within a cutout of an outer tube **245**;

(21) FIG. **20** shows the embodiment of FIG. **48**;

(22) FIG. **21** discloses a retractor having a flat inner face housed within an outer tube;

(23) FIGS. **22-24b** show a distraction embodiment;

(24) FIGS. **25-30** show an access device with an extending shield;

(25) FIG. **31** shows an access device with an inner and outer shield;

(26) FIGS. **32-34** show in inner shield;

(27) FIG. **35** discloses a radial soft tissue retractor;

(28) FIG. **36** discloses an outer tube/inner retractor assembly wherein the first inner retractor and second inner retractor both tilt inwards to retract soft tissue;

(29) FIGS. **37-46** disclose a preferred method of surgery involving the access device;

(30) FIGS. **47a-47c** disclose a Navigation plug comprising a base having an array attached thereto, wherein the plug is adapted to fit within an outer tube;

(31) FIG. **48** discloses the cookie cutter-type distal end of an ultrasonic cutter extending from the end of an outer tube, wherein the distal end has a plurality of cutting teeth;

(32) FIGS. **49a-49b** disclose various cross-sections of the template for guiding a bone cutting device;

(33) FIG. **50** discloses a cookie cutter-type distal end of an ultrasonic cutter having a semicircular cutting piece cutter bone;

(34) FIG. **51** discloses a mini flex arm connecting an outer tube and a screw extension;

(35) FIG. **52** discloses an outer tube/inner retractor assembly wherein the inner retractor is tilted inwards to retract soft tissue;

(36) FIG. **53** discloses an outer tube/inner retractor assembly wherein the inner retractor runs parallel with the outer tube; and

(37) FIG. 54 discloses an endoscope housed within an outer tube, and an inner tube extending from the outer tube.

DETAILED DESCRIPTION OF THE INVENTION

(38) Fluoroscopic visualization is performed to define the incision site of the initial reference array placement, as well as the incision for access to the intervertebral disc.

(39) Generally, the shields of the present invention can be applied to any of the conventional approaches commonly used in spine surgery. However, given the clinical benefit of the access device and its underlying rationale, it is preferably suitable to use these shields in either interlaminar, extraforaminal or transforaminal approaches to the intervertebral disc.

(40) Now referring to FIGS. 1-7, there is provided an access device for accessing an intervertebral disc, comprising: a) an outer shield **1** having a substantially tubular portion, a length adapted to extend from an incision to a border between sensitive and insensitive tissue (e.g., an articular process), a proximal end portion **3**, a distal end portion **5**, an outer surface **7**, and a longitudinal through-bore **9** defining an inner surface **10**, b) an inner shield **11** having i) a first substantially tubular portion **13** having a proximal end portion **15**, a distal end portion **17**, a longitudinal through-bore **19** defining an inner surface **21**, and an outer surface **23** defining a diameter, and ii) a longitudinal flange **25** extending distally from the distal end portion of the substantially tubular portion, wherein the outer surface of the inner shield substantially nests within the inner surface of the outer shield so that the flange extends distally past the distal end portion of the outer shield, and the distal end portion of the substantially tubular portion of the inner shield extends distally past the distal end of the outer shield.

Outer Shield Embodiments

(41) In the design of the outer shield, traditional tube or split tube/retractor concepts can be used. Newer concepts such as a “flexible tube” could also be adopted. The outer shield can be a simple cylindrical tube. It may also be a split tube, in the manner that conventional retractors are considered to be split tubes. It can be a flexible tube. It can be a tube with a slot running from the proximal end to the distal end. Various shape embodiments could be: a) a cylindrical tube with an inner diameter D (FIG. 3a); b) an oval tube with a height a different than a length b (FIG. 3b); c) a “half moon” tube having a substantially circular or oval cross section of diameter D , with a section cut (or chord) “ a ” (FIG. 3c); and d) a rectangular tube with height a and width b (FIG. 3d).

(42) In some embodiments, the shape of the distal end portion **5** includes an unsymmetrical shape for better tissue retraction lateral to the SAP.

(43) The outer shield can be preferably used with a variety of access window sizes (i.e., widths) ranging from 6 mm to 25 mm and lengths ranging from 40 mm to 200 mm. Typically, the outer shield comprises a feature that allows for the attachment of a stabilization mechanism that allows for appropriate flexibility in attachment (e.g. a ball joint). In one embodiment, the outer shield has a customized feature adapted for the introduction of an endoscope or camera that allows the endoscope to be introduced to a predetermined depth where the working window at the distal portion of the outer shield can be visualized.

(44) Inner Shield Embodiments

(45) Now referring to FIGS. 3a-3d, the inner shield **11** may encompass various designs as well.

(46) In a first embodiment, the inner shield is a fully surrounding (i.e., extending for 360 degrees) stiff tube. It may possess various cross-sections, such as: e) a cylindrical tube with an inner diameter D (FIG. 3a); f) an oval tube with a height a different than a length b (FIG. 3b); g) a “half moon” tube having a circular cross section of diameter D , with a section cut (or chord) “ a ” (FIG. 3c); and h) a rectangular tube with height a and width b (FIG. 3d).

(47) The inner shield may possess different longitudinal shapes. For example, in a second embodiment, and now referring to FIGS. 4-7, the inner shield **11** is a funnel-shaped (e.g. necked) tube (as in FIG. 4). In this embodiment, it changes its cross sectional shape/area along the shield, with a bigger diameter/working zone at the proximal portion, and the length of this zone with a

bigger diameter is adjusted to be the part of the inner shield that will be nested within the outer shield, and a smaller diameter/working zone where the inner shield is extending the outer shield. This design increases the range of motion of intradiscal tools and enables better visualization. In FIG. 4, the flange is a second substantially tubular portion 25 having a diameter less than the diameter of the first substantially tubular portion 13 of the inner shield. A necked region 27 is disposed between the first and second substantially tubular portions.

(48) In some embodiments, the inner shield may be in the form of one of a plurality of retractor blades.

(49) In tubular embodiments, the smaller tube can be a concentric with the larger tube, or not concentric therewith. In FIG. 5, the first and second substantially tubular portions of the inner shield are concentric ($a=b$). In FIG. 6, the first and second substantially tubular portions of the inner shield are not concentric ($a>b$).

(50) In some embodiments, there is provided a spherical joint between the larger and the smaller tubes, allowing the angle to change between the two tubes (FIG. 7). In FIG. 7, the outer surface 23 of the inner shield substantially nests within the inner surface 10 of the outer shield so that the proximal end of the substantially tubular portion of the inner shield terminates within the outer shield. Also, the distal end portion of the inner shield narrows distally to define a first radius R1, and the proximal end portion of the inner shield narrows distally to define a second radius, and the proximal end portion of the inner shield nests within the distal end portion of the outer shield to allow polyaxial pivoting of the inner shield.

(51) In some embodiments, the inner shield is a partially surrounding tube/shield, or “flange,” designed only to protect the nerves. For some applications, the only purpose of the inner tube might be to shield/protect the exiting nerve root. In this case, the inner shield might be simplified to a cylinder with a flange 25 extending distally therefrom, so that the flange is only a shield of about a quarter of a full circle. See FIG. 8a, or FIG. 9 if mounted on the outer shield.

(52) Depth Adjustment of Nerve Protector

(53) The aforementioned outer shield can be positioned and fixed in its depth through a mechanism which relies on interference between the outer shield and the inner shield at any location along either the outer shield or inner shield.

(54) In FIG. 8b, the proximal end portion of the first substantially tubular portion 13 of the inner shield comprises a stop 31 adapted to abut the proximal end portion of the outer shield, the stop being adapted to prevent excessive distal movement of the inner shield. Preferably, the stop extends substantially radially about the proximal end portion of the substantially tubular portion of the inner shield. The stop may also further comprise a textured radial surface 33 adapted for gripping. It acts as both a stop and as a handle to twist the shield.

(55) In FIG. 9, the outer surface of the inner shield substantially nests within the inner surface of the outer shield so that the proximal end portion of the substantially tubular portion of the inner shield extends proximally past the proximal end of the outer shield. Also in FIG. 9, the outer surface of the outer shield further comprises a first port 41 adapted for connecting to a navigation instrument or a stabilization point, and a second port 43 adapted for connecting to a camera/light system.

(56) Navigation of Outer Shield

(57) The first port allows the outer shield to be navigated to determine its position (depth and orientation) in relation to the treatment site. In one embodiment, the outer surface of the outer shield has a feature that allows for the direct or indirect attachment of a navigation instrument. In another embodiment, the inner surface of the outer shield has a feature that allows for the direct or indirect attachment of a navigation instrument.

(58) Endoscope in the Outer Shield

(59) In some embodiments, the outer shield has an integrated endoscope that can be set in a fixed or variable (angle or circumferential) position relative to the anatomy. This endoscopic

visualization can be utilized in subsequent surgical steps, including bone removal, inner shield deployment, discectomy, and implant insertion. Preferably, the endoscope has an integrated lens cleaning mechanism for automated lens cleaning in situ.

(60) FIG. **10** discloses a cross-section of an outer tube wherein the outer tube wall **138** has a first channel **238** adapted for containing a camera and a second channel **338** adapted for containing a lens cleaning device.

(61) FIG. **11** discloses a cross-section of an outer tube wherein the outer tube wall contains a lens cleaning device **139** and a camera **239**.

(62) FIG. **12** discloses a chip-on-tip embodiment including a cross-section of an outer tube wherein the outer tube wall has a channel **140** containing an endoscope **240** having a video chip **340** near its distal end.

(63) FIG. **13** discloses a distal end of an outer tube featuring a video chip **141** near its distal end.

(64) Fixed Endoscope

(65) The endoscope can be a chip-on-tip type of endoscope having an outer diameter less than 5 mm and having an incremental length substantially matching the length of the outer shield. The benefits of an integrated chip-on-tip endoscope/outer shield embodiment include the relatively free space within the bore of the outer shield, thereby enhancing visualization.

(66) Preferably, the endoscope is angled within the port or has a built-in lens angle such that, at final positioning within the port, the circumference of the distal portion of the outer shield is visible and the area within the circumference is visible as well.

(67) In some embodiments, the endoscope can be removed from the wall of the outer shield and inserted independently into the outer shield bore to inspect the treatment site (e.g. into the disc space for confirmation of adequate discectomy).

(68) FIG. **14** discloses a scope holder **137** for an endoscope **237**.

(69) Still referring to FIG. **9**, in some embodiments, the flange **25** of the inner shield has an arcuate transverse cross-section. In some embodiments, the arcuate transverse cross-section of the flange defines an outer surface **47** of the flange having a curvature substantially similar to a curvature of the inner surface **10** of the outer shield. Preferably, the flange defines a second substantially tubular portion having a diameter less than or equal to the diameter of the first substantially tubular portion of the inner shield.

(70) Now referring to FIGS. **15a-15b** and **16**, the inner shield can be a single blade that can be mounted/hooked to the outer tube. In this case, elbow **51** functions as a stop and also as a connector to the outer tube. Also, the proximal end of the inner shield may form an anchoring spike **53**.

(71) There are a number of ways to fix or locate the inner shield onto the disc and/or onto the outer shield. In one embodiment, which provides safety of the inner shield against slippage/dislocation, involves mounting it distally (onto or within the vertebral endplates or disc annulus) and/or proximally (onto the outer shield).

(72) Distal fixation of the inner shield with the anatomy may include: a) fixation within disc annulus, b) fixation against vertebrae; c) fixation against other structures; d) K-Wires that are distally extending through the walls of the inner shield and anchored to the anatomy; and e) spikes extending the distal part (FIG. **15**) to be anchored to the anatomy.

(73) Proximal fixation of inner shield upon the outer shield may involve a positioning ring or a depth adjustment. Now referring to FIG. **17**, proximal fixation of inner shield upon the outer shield may involve a positioning ring **55**. Assuming the outer shield would be fixed relative to the anatomy, there would be the option of having positioning rings having the shape of the outer tube at the outside, and of the inner tube on the inside. When placed over the inner shield and into the outer shield, such a ring would stabilize the location or at least the orientation of the proximal inner shield against the outer shield, and—by considering the assumption above—also against the anatomy.

(74) Now referring to FIG. **18**, proximal fixation of inner shield upon the outer shield may involve

a depth adjustment means **57**. This would additionally stabilize or anchor the tip location of inner shield against the anatomy via anchoring or hooking the inner shield into the outer shield via ratchet system. The ratchet system can also be located between the inner surface of the outer shield, and the outer surface of the inner shield or within the wall of the outer shield. It may further include a spring system to increase friction between the inner and outer shields.

(75) Inner Shield Deployment (Circumferential)

(76) Embodiments having separate outer and inner shields allow for the independent positioning of the inner shield relative to the outer shield. Also, the use of a smaller inner shield (relative to the outer shield) allows for maximum visualization at the entrance where no retraction-sensitive tissues reside. This maximum visualization allows for accurate placement of the inner shield. Where retraction-sensitive tissues reside distal the outer shield, a relatively smaller inner shield allows for minimum retraction while providing an access through or past these tissues. Preferably, the inner diameter of the inner shield is no more than 40%-100% of the inner diameter of the outer shield.

(77) In some embodiments, the inner shield-outer shield configuration is replaced by a) a primary shield having a substantially tubular shape having a cutout, and b) a secondary shield having a shape that is substantially insertable into the cutout. Preferably, the primary shield has a substantially annular shape and the secondary shield has an arcuate cross-section that substantially matches the annular shape of the primary shield. This embodiment allows the secondary shield to be tilted with respect to the primary shield.

(78) Inner Shield Deployment (Radial)

(79) In another nerve protection embodiment, the motion of retraction of the shields is radial rather than rotational. In these embodiments, a straight or bayoneted inner shield may be used. The inner shield may be positioned over the area in which the protected tissue is to be located. The flange shield can then be angled into the center of the access window at the distal end of the outer shield e.g. towards the caudal pedicle. It can then be subsequently advanced longitudinally onto the medial side of the nerve root, into the "safe zone" as described by Kambin. It is subsequently angled such that the distal tip of the inner shield is angled laterally, wherein its outer distal surface gently pushes the existing nerve root away and/or shields it against the tools that are further introduced medially to the shield for intradiscal work. This embodiment may be constructed such that the inner shield substantially nests either a) within the wall of the outer shield (FIG. **19(a)**), b) inside the inner surface of the outer shield (FIG. **20(b)**), or c) outside the outer surface of the outer shield ((FIG. **21(c)**)). In some embodiments, the inner shield is built into the wall of the outer shield or even outside the outer shield.

(80) FIG. **19** discloses an integrated retractor having a flat inner face **145** housed within a cutout of an outer tube **245**.

(81) FIG. **20** discloses a retractor having a flat inner face **144** housed within an outer tube.

(82) FIG. **21** discloses an outer tube **150** having a retractor **250** nesting with the outer face **350** of the outer tube.

(83) Depth Control of Nerve Protector

(84) The aforementioned outer shield can be controlled in its depth through a mechanism that relies on interference between the outer shield and the inner shield at any location along either the outer shield or inner shield.

(85) There are a number of avenues by which the present device can be used to distract the disc space and/or provide nerve protection upon mounting.

(86) In one distraction embodiment, a revolution spreader is used. This is a conventional concept involves an ovoid or rectangular cross-sectional shaped rod that is inserted into the disc with its smaller dimension directed towards the vertebral endplates. After turning the spreader by 90° under force, the larger dimension is directed towards the vertebral endplates, which distracts the disc by the difference of the two cross sectional dimensions.

(87) In a second distraction embodiment, as now referring to FIGS. **22-24b**, the inner shield may

comprise a spreader, which includes a frame **60**, a cranial blade **61**, and a caudal blade **63**.

(88) The spreader with respective cranial **61** and caudal **63** distraction blades in cranial and caudal locations is introduced into the disc in a collapsed/tapered configuration (FIG. **22**). The spreader blades are then distracted with an inner core **65** (the core matching a counter geometry on the blade to not slip away sideways), elevating the intervertebral height from d1 to d2 (FIGS. **22-23**). The side walls **67** matching to the inner core height are then introduced medially/laterally (FIG. **24a**), to circumferentially close the four-wall shield. Once the inner core is removed, the stacked shield keeps the vertebral bodies separated in distracted condition (FIG. **24b**).

(89) Now referring to FIGS. **25-26**, the inner shield may further comprise a rotating flange **71** that moves laterally/medially upon rotation to shield the nerve root.

(90) In a nerve protection embodiment, and now referring to FIGS. **27-30**, a rotation funnel **70** is used. Preferably, the flange shield **71** can be smartly introduced to protect the exiting nerve root while being inserted. This shield can be directed towards the caudal pedicle if introduced through the outer shield. This location is a “safe zone.” Once the distal tip reaches the disc level, the inner shield can be turned clockwise by about 90° (i.e., rotated), so that the flange gently pushes the exiting nerve root away, and/or shields it against the tools that are further introduced medially to the shield, for intradiscal work.

(91) In a second nerve protection embodiment, and now referring to FIGS. **31-34**, a concentrically-arrayed multi-shield is used to gently move and/or shield nerves. The rotation funnel principle can also be applied for more than one rotating shield. A single shield may be suitable if the protection only has to be provided against a structure that lies on one single side. In other situations, however, the shield entry towards the disc would be bounded both medially and laterally by the traversing and the exiting nerves, so the inner shield needs to shield against two opposing structures. In this case, the two concentrically-arranged outer **81** and inner **83** rotating flanges are turned by 90° in respective clockwise and counterclockwise directions to reach an end configuration wherein the opposed shields protect the nerves from the tools that are further introduced for intradiscal work.

(92) In another nerve protection embodiment, a radially-retracting multi-shield is used to gently move and/or shield nerves. The radially-retracting principle can also be applied to more than one radially retracting shield.

(93) FIG. **35** discloses a radial soft tissue retractor **136**.

(94) FIG. **36** discloses an outer tube/inner retractor assembly wherein the first inner retractor **153** and second inner retractor **253** both tilt inwards to retract soft tissue.

(95) A single shield may be suitable if the protection only has to be provided against a structure that lies on one single side. In other situations, however, the shield entry into the disc would be bounded both medially and laterally by the traversing and the exiting nerves, so that the inner shield needs to shield against two opposing structures. In this case, the two opposing inner flanges are initially positioned towards the center of the outer tube access window and subsequently retracted outwards to shield the opposing nerves from the tools that are further introduced for intradiscal work.

(96) FIGS. **37-46** disclose a preferred method of surgery involving the tube-in-tube access device.

(97) In one embodiment, and now referring to FIG. **37**, the surgeon places a pedicle screw-based anchor, adds a navigation reference frame **101** to the anchor, and uses a commercial navigation system for navigation. In some embodiments, a navigation array is placed onto the anatomy with reference to an anatomical feature that is symmetrically substantially adjacent the treatment site (e.g. contralateral cranial or caudal pedicle).

(98) In some embodiments, there is navigation of the probe to a facet capsule or disc space through Kambin's triangle. Preferably, subsequent to fascia and muscle dissection, a probe enabled with navigation visualization is introduced to achieve an initial anchoring point. In one embodiment, the probe is inserted into the disc space by being indexed off the lateral border of the superior articulating process and may be optionally enabled with/supported by a nerve detection and/or visualization function. In another embodiment, the probe is introduced into the facet capsule.

(99) In some embodiments, there is dilation over a navigated probe. Subsequent to the initial anchoring point, dilation is performed to prepare the surgical site for the size of port required to perform the treatment. Sequential dilation up to the preferred size port window is then performed. The port is then introduced over the associated dilator. In one embodiment, the initial anchoring is in the disc space and concentric sequential dilation device(s) would be used in order to retract tissue concentrically around the initial anchoring point (exposing the lateral portion of the SAP on the lateral aspect and Kambin's triangle on the medial aspect). In another embodiment, the initial anchoring is in the facet capsule and eccentric sequential dilation device(s) could be used to focus tissue retraction laterally over the lateral portion of the SAP and Kambin's triangle.

(100) In some embodiments, the outer shield is stabilized onto an anatomical reference. The outer sleeve has a substantially tubular portion having a point or feature designed for attachment to a stabilization mechanism, which in turn is fixed to an anatomical feature on the vertebral body either cranial or caudal to the treatment site.

(101) FIG. 38 discloses an outer tube into which a plug containing a template for guiding a bone cutting device.

(102) In some embodiments, the outer sleeve is attached to a stabilization mechanism. In one embodiment, this stabilization device would be a device of sufficient length to reach an anatomical fixation point (e.g. pedicle screw) on the contralateral side of the treatment site. The mechanism (including its connection feature connecting to both the outer shield and the anatomical anchor) allows for sufficient flexibility of placement of the outer shield and sufficient stabilization to hold the outer shield in place until it is released by the user. The method of stabilization would be such that the user can dictate the degree of stiffness.

(103) In another embodiment, this device has sufficient length to reach an anatomical fixation point (e.g. pedicle screw) on the ipsilateral side of the treatment site. Likewise, the mechanism (including its connection feature to both outer shield and anatomical anchor) would allow for sufficient flexibility of placement of the outer shield and sufficient stabilization to hold the outer shield in place until released by the user. The method of stabilization would be such that the user can dictate the degree of stiffness.

(104) In another embodiment, this device would be a device of sufficient length to reach an anatomical fixation point (e.g. pedicle screw) on midline of the patient. Likewise, the mechanism (including its connection feature to both outer shield and anatomical anchor) would allow for sufficient flexibility of placement of the outer shield and sufficient stabilization to hold the outer shield in place unless released by the user. The method of stabilization would be such that the user can dictate the degree of stiffness.

(105) Now referring to FIGS. 39a-39b, the surgeon then dilates the tissue superior to the pedicle-based anchor, and inserts an outer shield 1, connected to the anchor, with its proximal end directed to the superior articular process. Blunt dissection up to the bone is carried out over the affected intervertebral disc, and muscle retraction over the affected intervertebral disc is then carried out. This retraction involves blunt dissection of the muscle and fascia to bone level under direct visualization.

(106) Now referring to FIG. 40, the surgeon then turns the outer shield 1 to the interlaminar space, performs a central, bilateral decompression as required by the pathology, and then turns the shield back to its original position.

(107) In some embodiments, an alternative to angling the access channel medially from the incision site could be the use of an alternative access site that would be more medial. In some embodiments, the initial anchoring point in the disc space will be medial to the inferior articulating process. For the embodiment having an initial anchoring point in the facet capsule, the dilation of the eccentric dilators will be medial from the capsule. Also, portions of the lamina and the inferior articulating process will be removed through the bone removal segment.

(108) Now referring to FIG. 41, the surgeon then inserts a bone removal tool (not shown) into the

outer shield tube and resects the lateral portion of the superior articular process to medially extend the traditional Kambin's triangle.

(109) Under either direct or endoscopic visualization, a bone removal device is introduced to the outer shield and utilized to remove at least the lateral portion of the SAP. Such a device is available in lengths and sizes allowing for its safe introduction and use through an access window from 40 mm to 200 mm and a window size from 10-25 mm.

(110) In one embodiment, this bone removal device is an ultrasonic cutting device. In another embodiment, this bone removal device is a reciprocating cutting surface. In yet another embodiment, this bone removal device is a revolving cutting tool. In another embodiment, this bone removal device is a mechanical punch with a stroke length between 10-30 mm. Removal of the bone can be performed in such a manner that sizes smaller than the access size will be excised and removed. The bone removal can be performed with the use of a template independently inserted into the outer shield and used to guide the direction of bone cutting and removal.

(111) A Negative Template is a plug-like device that is inserted in the outer Access Tube. It contains a longitudinal cut-out in different shapes, depending on the cross-sectional shape of the tissue that needs to be removed respective of the cross-sectional shape of the tissue that needs to be covered and therefore protected from any surgical interactions. By inserting a cutting device like, e.g., a Milling Bit, into the longitudinal cut-out the surgeon is able to remove the tissue without the risk of endangering the covered tissue/structures. In combination with a proximal stop-system (on proximal end of outer Access Tube and/or shaft of milling system) the surgeon can remove the tissue layer by layer. The layer thickness and therefore the progression of the cutting procedure can be controlled via the stop system supported by a scale. This system allows the surgeon to perform safe tissue removal with a controlled serial work flow: check anatomical situation.fwdarw.adjust stop system to define cross-sectional thickness of tissue that needs to be removed.fwdarw.insert milling system until the stop system is engaged.fwdarw.mill/cut tissue (also blindly) in plane (2D).fwdarw.remove milling system.fwdarw.check anatomical situation.fwdarw.adjust stop system.

(112) A serial workflow can be considered to be safer than a parallel workflow, since the surgeon only needs to take care of one parameter at a time (here: planar position of milling bit followed by its depth followed by planar position of milling bit . . .) whereas a parallel workflow requires the control of two or more parameters at a time (here: planar position of milling bit in parallel to its depth).

(113) Navigation of SAP Removal can be carried out with the aforementioned bone removal device adapted to be navigated through its mechanical or visual connection with a navigation system.

(114) Now referring to FIGS. **42-43**, the surgeon then inserts the inner shield tube into the outer shield tube, which acts to extend the outer tube anteriorly from the facet line until the tip of the inner shield reaches the level of the disc. The nerve root is protected by the inner shield.

(115) Now referring to FIG. **44**, the surgeon then identifies the disc, spreads the disc with a wedged osteotome; checks the mobilization, and removes the posterior rim, osteophytes and annulus until a minimum annular window is opened. The surgeon then inserts a disc removal tool **201** into the access device, removes the disc and prepares the endplates.

(116) An alternative embodiment to the prescribed disc clearing step in FIG. **44** would be to have the disc removal tool navigated through its mechanical or visual connection with a navigation system.

(117) Now referring to FIG. **45**, the surgeon then performs temporary disc space distraction, fills parts of the disc space with bone graft and inserts a fusion cage **203** into the remaining disc space.

(118) Now referring to FIG. **46**, the surgeon then adds posterior fixation **103**.

(119) Viewing Element

(120) In some embodiments, a visualization element based on the chip-on-tip technology and integrated into the wall of the port is used. This embodiment has a number of advantages over a standard rod-lens endoscope that is mounted at the tube wall:

(121) Manufacturing costs. The chip-on-tip technology allows a very cost efficient manufacturing, therefore can be marketed as a 'single use' instrument.

(122) Rigid portion only at distal tip. Whereas a standard rod-lens endoscope system has a stiff, cylindrical shape throughout the whole tube, the chip-on-top endoscope may have a non-cylindric configuration at the proximal outer tube end. Preferably, this shape is a flat cable shape. In some novel embodiments, in relation to a standard rod-lens-endoscope, the chip-on-tip endoscope has a relatively short "stiff" section (about 20 mm), where the proximal portion consists of a cable that can be flexible. In other embodiments, the stiff portion is shorter (producing a smaller chip-assembly) and actively articulating concepts are used to change the lens angle. Due to the cable's integration in the tube wall, the shape of the port window is maintained throughout the procedure. For example, a 5 mm chip on tip endoscope turns a 15 mm circular access window into a kidney shaped access window.

(123) Size/weight of camera unit. A standard rod-lens endoscope has a standard eyepiece that is a universal interface with a certain size. The camera that is connected to such a system has to be built in a certain dimension to be compatible with the eyepiece. This requirement produces a relatively bulky camera attachment (approx. 3-6 cm in diameter, approx. 5-10 cm in length) having a number of drawbacks. First, this large camera construct can be a physical obstacle to work, especially if the trajectory of the working port changes or interferes with the camera. Secondly, the dimension and weight of this conventional construct becomes significant enough to produce certain undesirable forces upon the rod-lens-endoscope, especially in bending. Thirdly, the relatively fragile conventional rod-lens-endoscope has to be embedded in stabilizing structures such as metal tubes, thereby further reducing the active working window.

(124) With the chip-on-tip embodiments disclosed herein having its chip cable embedded in the wall of the outer tube, the cable that exits at the proximal outer tube wall does not produce similar forces upon the working port. Also, respecting the attachment mechanisms that mount the chip-on-tip endoscope in the tube-wall, the lack of bending forces produced thereby raise the possibility of adopting relatively thin attachment options that mechanically do not need to be very stable.

(125) Working Environment. Conventionally, a constant fluid environment (permanent flow of saline solution) is used in spine endoscopy applications. However, in a mini-open and microsurgical environment, the fluid environment is not helpful, as the anatomical conditions are very different. Accordingly, in the preferred novel procedures described herein, the chip-on-tip endoscope works in a dry, open air environment. However, the open, dry air environment in which the chip-on-tip endoscope is used may produce an undesired condensation effect upon the lens component of the endoscope. For example, a colder lens in a humid body temperature environment may fog up. Moreover, drill debris, burr debris or smoke from monopolar scalpels or hemostatic tools can likewise affect the lens of the endoscope so as to reduce visibility. Accordingly, it may be desirable to periodically clean the lens of the chip-on-tip endoscope.

(126) Nerve Deflection (Tube in Tube)

(127) In minimally invasive spine surgery conducted through portals, a set of dilators is often used to prepare the site for reception of the portal. One such technology is shown in US Patent Publication US 2012-0232552 (Morgenstern). In this conventional technology (which has eccentric dilators), the outer diameter of any one of the dilators is identical to the inner diameter of the next successive (outer) dilator. This identity of diameters is necessary for fluoroscopy assisted, percutaneous muscle dilation.

(128) Since some embodiments of the present application describe a procedure between the level of the facet joint and the disc, the surgical site is dissected under direct visualization. Accordingly, the diameters of successive dilators used in these novel procedures do not have to match. Relaxation of the "exact diameter" requirement in these novel procedures allows the surgeon freedom in many tube design areas. For example, it allows the use of tubes that are tapered. It also allows the surgeon the freedom to use outer and inner ports that are not coaxial. It further allows the

trajectories of the inner port relative to the outer port to vary in angulation within certain treatment steps. Lastly, it allows the trajectories of the inner port relative to the outer port to vary in distance within certain treatment steps.

(129) Because fluoroscopy-assisted, percutaneous muscle dilation is carried out without direct visualization, it is a blind procedure whose use has limitations. These limitations include the inability to carry out surgical steps that require direct visualization out of safety considerations. One such treatment step requiring direct visualization is direct decompression of bony and ligamentous tissue that is directly adjacent to nerve structures. Since this decompression is a common step performed on degenerated spinal motion segments during a spinal fusion, the Morgenstern procedure severely limits the pathologies/indications that can be treated.

(130) Because some embodiments described herein allow for direct visualization of delicate anatomical structures, those embodiments further specifically allow direct decompression of bony and ligamentous tissue that is directly adjacent to nerve structures and more generally allow manipulation or removal of tissue adjacent the tubes through a very tissue-preserving “tube-in-tube” access port.

(131) Morgenstern further describes a method in which a guide wire is directly introduced through the disc space to Kambin's triangle, under fluoroscopy guidance (i.e., no direct visualization). This is a well-known approach, but still requires inserting a guidewire past nerve structures without direct visualization. Morgenstern further describes the possibility of using electrically-based nerve monitoring probes. Moreover Morgenstern describes a method of enlarging the spinous process by subsequently rasping away bone from the SAP and the pedicle. Such a procedure might weaken the base of the pedicle, which makes it risky to combine this method with pedicle screw constructs.

(132) The novel procedures described herein only perform non-visualized procedures (e.g., dilation) in a safe zone above the facet line. In the anatomically more critical zone between the level of the facet joint and the disc, the novel procedures dissect the surgical site under direct visualization, thereby allowing the surgeon to spare as much of the bone as is possible and as is meaningful.

(133) Navigation

(134) Navigation enhances static x-ray, CT, or MRI data by intra-operatively showing in real-time where the instruments used actually are in relation to the anatomy of the patient. Therefore it increases the safety of those instruments by showing their shape, trajectory and positioning and even more importantly it supports the surgeon to keep instrument orientation during the performed manipulations.

(135) Without wishing to be tied to a theory, it is believed that one reason why minimally invasive techniques are not often used is the significantly higher x-ray exposure needed to keep orientation in comparison to mini-open techniques, where the surgeon still has direct visualization and so can actually see the active site with a microscope or loupe. The x-ray exposure is an even greater for the surgeon who is exposed to the radiation on a frequent basis.

(136) This challenge is addressed by the implementation of navigation technology in the novel procedures described herein because they allow the reduction of x-ray exposure to an ideal minimal total of two x-rays for registration purposes. Once a single lateral shot and a single anterior-posterior shot have been registered, all used instruments (e.g. Jamshidi-Needle, Pointer, Dilators, Access Tube, Osteotome, Expandable Cage itself, Disc Removal Device . . .) can be projected in these static fluoro-images in real time. Another positive effect is a significant savings of time. Having the navigation system in place also helps the surgeon to understand the orientation (trajectory and depth) of the endoscope and therefore to understand what he or she actually sees with the camera. This can either be achieved by navigating the camera directly or indirectly by setting the camera in a fixed position integrated into a navigated Access Tube.

(137) The Jamshidi-Needle, Pointer, Dilators, and Access Tube Instruments can all be navigated with only one Instrument, the FOX-Navigation-Multi-Tool.

(138) FIGS. **47a-47c** disclose a Navigation plug comprising a base **147** having an array **247** attached thereto, wherein the plug is adapted to fit within an outer tube **347**.

(139) Bone Cutter

(140) In some embodiments, the novel procedures use an Ultrasonic Bone Cutting device for SAP removal, which specifically cuts bone only and will not cut soft tissue. Embodiments based on a conventional Expandable Cage Device for interbody fusion may require an access window at least as large as 12 mm. Such a large window can only be achieved by (partly) removing the Superior Articulation Process (SAP) to extend the Kambin's Triangle. The Ultrasonic Bone Cutting Device adds significantly to the safety of this procedure since it does not cut nerves if accidentally hit. If the cutting device blade is designed to be in the shape and diameter of the Inner Tube/Blade (i.e., a Cookie Cutter design) that approaches distally down to the level of the disc space, the SAP removal can be minimized (less trauma, less stress for patient, quicker recovery) and performed in a single step (faster than multiple step procedure).

(141) FIG. **48** discloses the cookie cutter-type distal end **143** of an ultrasonic cutter extending from the end of an outer tube **243**, wherein the distal end **143** has a plurality of cutting teeth **343**.

(142) Another option to increase the safety of bone cutting is a depth-controlled manual milling of the bone with a negative guide. The negative guide covers those areas that will not be removed (negative template). The depth control allows the milling of the bone layer by layer, under serial control of the surgeon. The reference for the depth control as well as the trajectory can be the outer Access Tube (also see paragraph navigation).

(143) FIGS. **49a-49b** disclose various cross-sections of the template for guiding a bone cutting device.

(144) Bone Cutter

(145) In some embodiments, the bone removal device is a harmonic scalpel having a cookie cutter design. The scalpel has a crescent-shaped cutting surface that interfaces with the outer tube. The scalpel is used as a single pass instrument, removing a predetermined amount of bone in a single pass. In some embodiments, the scalpel also has a tube that sprays water for irrigation, while the outer tube has a suction line for clearing the slurry of removed bone.

(146) In some embodiments, the scalpel can be navigated and ride down a slot provided in the inside wall of the outer tube. The slot depth can be predetermined to provide depth-controlled milling, and to control where cutter goes. This is advantageous because it is believed that freehand cutting hits the nerves too easily. The shape and size of the cutting surface can define the specific area of bone to be removed. The specificity of cut is advantageous because it minimizes the amount of bone removal, which is beneficial in the highly innervated facet. Thus, a quicker procedure, less trauma (less pain), and more stable construct is realized.

(147) Viewing Element (Olive)

(148) In some embodiments, the chip viewing element can be angulated so it can see around a corner of the tube.

(149) In a conventional endoscope, visualization is 2D (i.e., no depth perception), and so two nerves may look close together when they are actually 2 cm apart. Thus, in some embodiments, the endoscope is modified so that the chip acts like a range finder. In particular, the chip identifies and assesses a reference feature that is a known distance from chip, and then measures how far away a nerve is from chip (which is the tube end) based on that assessment.

(150) Nerve Deflection (Tube in Tube)

(151) In some embodiments, the outer shield has a pressure sensor thereon to measure the stress on the nerve. Using ultrasound techniques that can measure distance, the system can measure the elongation of nerve under retraction and define a maximum elongation limit (e.g., 20%), and then warn the surgeon if the elongation limit is exceeded. In some embodiments, the system integrates ultrasound into the port and thereby navigates the port.

(152) In some embodiments, the surgeon navigates the camera. This allows the surgeon to

understand orientation of the camera.

(153) In some embodiments, visualization provides an axial view of the disc, so the surgeon can understand the location of the disc removal tool.

(154) Neuromonitoring Analytics

(155) Currently, neuromonitoring devices can be used to obtain an indication of potential nerve health or nerve damage, which may be induced in a surgical setting. This indication of nerve health is achieved by measuring electrical impulses between a nerve near a surgical site and a far end of the nerve. For example, impulses may be measured between a nerve root at the spine and some point found on the legs.

(156) Nerve damage can be caused through direct manual contact with a nerve. Apart from gross damage such as severing or crushing the nerve, other lesser forces imparted on the nerve can also cause damage. For example, displacing the nerve, stretching it, or compressing it can cause significant damage. In some cases, extended application of such forces to the nerve can reduce blood flow through the nerve, again causing nerve damage. Often times, this exposure time is dependent on the amount of force applied. Accordingly, there appears to be no known steadfast rule as to how long the surgeon may be able to load a nerve.

(157) Alternate forms of evaluating potential nerve damage besides neuromonitoring may bring new insights into nerve protection during a procedure. In this regard, nerve manipulation measurement could yield an indication of risk to the nerve. If a nerve is displaced for the procedure, it may be elongated or it may be displaced laterally. These alterations in the nerve's physical features could be measured and used to predict potential nerve damage. Accordingly, other potential features could be measured and used to predict potential nerve damage include arc length and the diameter of the nerve itself etc. These features may be measured in quantifiable terms via techniques such as ultrasound. The resulting measurements are and then analyzed (via software or manually) in terms of absolute value, percent change or some other metric indicative of potential nerve risk/damage that can be obtained from a database or library. In some embodiments, these metrics can be used as predictors of the safe length of time that a nerve can have a given displacement or deformation without causing long term damage. Calculation or algorithms can also be used to determine a maximum safe deformation, or a maximum allowable time during which a nerve can have a given deformed feature.

(158) This measurement could be obtained in many ways. It can be measured manually, optically or through some other form of imaging. This could occur in an open procedure, subcutaneously in an MIS or other type of procedure. Direct visualization could be completed with the use of a camera. Before and after images could be interpreted to calculate the amount of absolute deformation or percent change. The measurements can be obtained through modalities such as ultrasound, or other forms of imaging that can “see” soft tissue or identify nerve tissue relative to the surrounding tissue (X-ray, CAT/PET scan, MRI, etc.).

(159) In some neuromonitoring embodiments, it may be possible to measure impedance within the nerve or impulses, wherein this may be done locally relative to the specific deformation area of the nerve. In particular, in some embodiments discussed herein, the nerve shield could have a sensor on opposite edges of the shield that would contact the same nerve in two different nerve locations. These sensors would allow the surgeon to read electrical values such as impulses or resistance, before nerve distention and then measure it again as distention occurs or is achieved. The difference in these measured values could be an indicator as to the level of deformation.

(160) FIG. 50 discloses a cookie cutter-type distal end **142** of an ultrasonic cutter having a semicircular cutting piece cutter bone.

(161) FIG. 51 discloses a mini flex arm **146** connecting an outer tube **246** and a screw extension **346**.

(162) FIG. 52 discloses an outer tube/inner retractor assembly wherein the inner retractor **151** is tilted inwards to retractor soft tissue.

(163) FIG. 53 discloses an outer tube/inner retractor assembly wherein the inner retractor 152 runs parallel with the outer tube 252.

(164) FIG. 54 discloses an endoscope 154 housed within an outer tube, and an inner tube 254 extending from the outer tube.

(165) In many embodiments disclosed above, an inner shield nests within an outer shield. In an alternative embodiment to all such embodiments, however, the inner shield is replaced with a removable blade that is integrated into a cutout formed within the wall of the outer shield. In such cases, the outer surface of the inner shield substantially nests within the outer surface of the outer shield so that the flange extends distally past the distal end portion of the outer shield.

(166) In many embodiments disclosed above, the proximal end portion of the substantially tubular portion of the inner shield comprises a stop adapted to abut the proximal end portion of the outer shield, the stop being adapted to prevent excessive distal movement of the inner shield. In other embodiments, the abutment occurs anywhere along the outer shield.

Claims

1. An access device for accessing an intervertebral disc, comprising: a) an outer shield having a length adapted to extend from an incision to an articular process, a proximal end portion, a distal end portion, an outer surface, and a longitudinal throughbore defining an inner surface, b) an inner shield having a proximal end portion and a distal end portion; and c) a video chip disposed in the distal end portion of the outer shield; wherein the inner shield is configured to be disposed within longitudinal throughbore of the outer shield such that the distal end portion of the inner shield extends distally past the distal end portion of the outer shield; and wherein the video chip is disposed in a channel of the outer shield and the channel opens into the inner surface of the outer shield at least at the distal end portion of the outer shield.
2. The device of claim 1, wherein the channel intersects with the longitudinal throughbore of the outer shield along the distal end portion of the outer shield proximal to a distal end of the outer shield.
3. The device of claim 1, further comprising a flat cable coupled to the video chip and extending from a proximal end portion of the outer shield.
4. The device of claim 1, wherein the proximal end portion of the inner shield comprises a stop adapted to abut the proximal end portion of the outer shield, the stop being adapted to prevent excessive distal movement of the inner shield.
5. The device of claim 4 wherein the stop extends substantially radially from the proximal end portion of the inner shield.
6. The device of claim 1, wherein the distal end portion of the inner shield has an arcuate transverse cross-section.
7. The device of claim 6, wherein the arcuate transverse cross-section of the distal end portion of the inner shield defines an outer surface having a curvature substantially similar to a curvature of the inner surface of the outer shield.
8. The device of claim 6, wherein the inner shield has a proximal elbow that functions as a stop.
9. The device of claim 6, comprising a camera disposed in the channel of the outer shield, the camera having the video chip.
10. A method of accessing an intervertebral disc in a patient, comprising: a) making an incision in a skin of the patient, b) percutaneously inserting through the incision an outer shield having longitudinal throughbore, the outer shield having a length adapted to extend from the incision to the spine of the patient, c) inserting an inner shield within the longitudinal throughbore of the outer shield so that a distal end portion of the inner shield extends distally past the distal end portion of the outer shield and to the disc, d) disposing a video chip in a distal end portion of a channel of the outer shield, wherein the channel opens into the inner surface of the outer shield at least at the

distal end portion of the outer shield.

11. The method of claim 10, further comprising resecting at least a lateral portion of the superior articular process.

12. The method of claim 10, wherein the channel intersects with the longitudinal throughbore of the outer shield along the distal end portion of the outer shield proximal to a distal end of the outer shield.

13. The method of claim 10, wherein the distal end portion of the inner shield has an arcuate transverse cross-section.

14. The method of claim 10, further comprising contacting the outer surface of the shield to a nerve root to shield the nerve root.

15. The method of claim 10, further comprising coupling a light source to the outer shield.

16. The method of claim 10, wherein the channel opens into the inner surface of the outer shield along the distal end portion of the outer shield proximal to a distal end of the outer shield.

17. The method of claim 10, further comprising contacting the outer surface of the shield to a nerve root to shield the nerve root.

18. The method of claim 10, wherein the inner shield is angled into a center of an access window at a distal end of the outer shield, and then is subsequently advanced longitudinally onto a medial side of a nerve root.

19. A method of accessing an intervertebral disc in a patient, comprising the steps of: a) making an incision in a skin of the patient, b) percutaneously inserting through the incision an outer shield having a substantially tubular shape, the outer shield having a length adapted to extend from the incision to the spine of the patient, c) stabilizing the outer shield to a pedicle anchor d) inserting an outer shield integrated optical visualization instrument, f) inserting an inner shield through the outer shield so that a distal end portion of the inner shield extends to the disc, the inner shield having an outer surface, g) contacting the outer surface of the inner shield to a nerve root to shield the nerve root, h) with the nerve root shielded, conducting a surgical operation through the access tube.
