

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403727
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Wada; Hironori

Pneumatic tire

Abstract

Provided is a pneumatic tire including: a plurality of main grooves each having a zigzag shape and extending in a tire circumferential direction; and a land portion defined by the main grooves adjacent to each other and having a rib structure that is continuous with the tire circumferential direction. The land portion includes first and second lug grooves having a semi-closed structure. A maximum length L21 of the first lug groove in a tire width direction has the relationship $1.30 \leq L21/L22 \leq 2.30$ with respect to a maximum length L22 of the second lug groove.

Inventors:	Wada; Hironori (Kanagawa, JP)
Applicant:	The Yokohama Rubber Co., LTD. (Tokyo, JP)
Family ID:	75156830
Assignee:	The Yokohama Rubber Co., LTD. (Tokyo, JP)
Appl. No.:	17/754007
Filed (or PCT Filed):	July 06, 2020
PCT No.:	PCT/JP2020/026442
PCT Pub. No.:	WO2021/059662
PCT Pub. Date:	April 01, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220348040 A1	Nov. 03, 2022

Foreign Application Priority Data

JP	2019-174665	Sep. 25, 2019
----	-------------	---------------

Publication Classification

Int. Cl.: B60C11/04 (20060101); B60C11/13 (20060101); B60C11/03 (20060101)

U.S. Cl.:

CPC B60C11/04 (20130101); B60C2011/0346 (20130101); B60C2011/0381 (20130101); B60C2011/0388 (20130101); B60C2200/04 (20130101); B60C2200/06 (20130101)

Field of Classification Search

CPC: B60C (2011/0381); B60C (2011/0383); B60C (2011/0346); B60C (11/04); B60C (11/042); B60C (11/045); B60C (11/047)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2012/0325386	12/2011	Dautrey	152/209.18	B60C 11/0309
2016/0375728	12/2015	Kuriyama	N/A	N/A
2017/0210176	12/2016	Ninomiya	N/A	B60C 11/0306
2019/0039418	12/2018	Arai	N/A	N/A
2019/0061430	12/2018	Kamigori	N/A	B60C 11/0304
2019/0351712	12/2018	Miyazaki	N/A	B60C 11/0304

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
11 2014 005 382	12/2022	DE	N/A
3 199 375	12/2016	EP	N/A
01204806	12/1986	JP	N/A
02114004	12/1989	JP	N/A
2001347811	12/2000	JP	B60C 11/0306
2012218652	12/2011	JP	N/A
2013-063701	12/2012	JP	N/A
2018-161944	12/2017	JP	N/A
2019026204	12/2018	JP	N/A

OTHER PUBLICATIONS

Machine Translation: JP-2012218652-A, Tamugi A, (Year: 2024). cited by examiner
Machine Translation: JP-2019026204-A, Suzuki T, (Year: 2024). cited by examiner
Machine Translation: JP-2001347811-A, Kuroki T, (Year: 2024). cited by examiner
Machine Translation: JP01204806A, Tsuda, Toru, (Year: 2025). cited by examiner
Machine Translation: JP-02114004-A, Takahashi O, (Year: 2025). cited by examiner

Primary Examiner: Ly; Kendra

Attorney, Agent or Firm: Thorpe North & Western

Background/Summary

TECHNICAL FIELD

(1) The technology relates to a pneumatic tire and particularly relates to a pneumatic tire that can provide snow traction performance and uneven wear resistance performance of the tire in a compatible manner.

BACKGROUND ART

(2) In a heavy duty tire that is mounted mainly on a drive shaft of a vehicle, the snow traction performance of the tire is enhanced by disposing semi-closed lug grooves in ribs while ensuring the uneven wear resistance performance of the tire based on a rib pattern.

(3) The technology described in Japan Unexamined Patent Publication No. 2019-026204 is a pneumatic tire in the related art that employs such a structure.

SUMMARY

(4) The technology provides a pneumatic tire that can provide both the snow traction performance and uneven wear resistance performance of the tire in a compatible manner.

(5) The pneumatic tire according to an embodiment of the technology includes a plurality of main grooves having a zigzag shape and extending in a tire circumferential direction, and land portions defined by the main grooves adjacent to each other and having a rib structure continuous in the tire circumferential direction. The land portions include first and second lug grooves having a semi-closed structure, and a maximum length L21 of the first lug groove in a tire width direction has the relationship $1.30 \leq L21/L22 \leq 2.30$ with respect to a maximum length L22 of the second lug groove.

(6) In a pneumatic tire according to an embodiment of the technology, the first and second lug grooves have maximum groove lengths L21, L22 that differ from each other, and thus, compared to a configuration in which the maximum groove lengths of the lug grooves are set to be uniform, there is an advantage that the uneven wear resistance performance and snow traction performance of the tire can be efficiently provided in a compatible manner.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a cross-sectional view in a tire meridian direction illustrating a pneumatic tire according to an embodiment of the technology.

(2) FIG. 2 is a plan view illustrating a tread surface of the pneumatic tire illustrated in FIG. 1.

(3) FIG. 3 is an enlarged view illustrating a shoulder land portion and a middle land portion of the pneumatic tire illustrated in FIG. 2.

(4) FIG. 4 is an enlarged view illustrating the middle land portion and a center land portion of the tire illustrated in FIG. 2.

(5) FIG. 5 is an enlarged view illustrating the shoulder land portion illustrated in FIG. 3.

(6) FIG. 6 is an enlarged view illustrating the middle land portion illustrated in FIG. 3.

(7) FIG. 7 is a cross-sectional view of the middle land portion illustrated in FIG. 6.

(8) FIG. 8 is an enlarged view illustrating the center land portion illustrated in FIG. 4.

(9) FIG. 9 is a cross-sectional view of the center land portion illustrated in FIG. 8.

(10) FIG. 10 is a table showing the results of performance tests of pneumatic tires according to embodiments of the technology.

(11) FIG. 11 is a table indicating the results of performance tests of pneumatic tires according to embodiments of the technology.

DETAILED DESCRIPTION

(12) Embodiments of the technology will be described in detail below with reference to the

drawings. Note that embodiments of the technology are not limited to the embodiments. Additionally, constituents of the embodiments include constituents that are substitutable and are obviously substitutes while maintaining consistency with the embodiments of the technology. Additionally, a plurality of modified examples described in the embodiments can be combined in a discretionary manner within the scope apparent to one skilled in the art.

Pneumatic Tire

(13) FIG. 1 is a cross-sectional view in a tire meridian direction illustrating a pneumatic tire according to an embodiment of the technology. The same drawing illustrates a cross-sectional view of a half region in a tire radial direction. As an example of a pneumatic tire, the same drawing illustrates a heavy duty radial tire mounted on a drive shaft of a vehicle for long-distance transport such as a truck or a bus.

(14) In the same drawing, a cross section in the tire meridian direction is defined as a cross section of the tire taken along a plane that includes a tire rotation axis (not illustrated). Further, a tire equatorial plane CL is defined as a plane perpendicular to the tire rotation axis through a midpoint between measurement points in a tire cross-sectional width defined by the Japan Automobile Tyre Manufacturers Association, Inc. (JATMA). Additionally, a tire width direction is defined as a direction parallel to the tire rotation axis, and the tire radial direction is defined as a direction perpendicular to the tire rotation axis.

(15) A pneumatic tire **1** has an annular structure with the tire rotation axis as its center and includes a pair of bead cores **11, 11**, a pair of bead fillers **12, 12**, a carcass layer **13**, a belt layer **14**, a tread rubber **15**, a pair of sidewall rubbers **16, 16**, and a pair of rim cushion rubbers **17, 17** (see FIG. 1).

(16) The pair of bead cores **11, 11** each include one or more of bead wires made of steel and made by being wound annularly multiple times, and the pair of bead cores **11, 11** are embedded in bead portions and constitute cores of the bead portions on the left and right. The pair of bead fillers **12, 12** are each made of a lower filler **121** and an upper filler **122**. The pair of bead fillers **12, 12** are disposed in outer circumferences in the tire radial direction of the pair of bead cores **11, 11**, respectively, and reinforce the bead portions.

(17) The carcass layer **13** includes a single layer structure made of one carcass ply, or a multilayer structure made of a plurality of carcass plies being layered, and the carcass layer **13** extends in a toroidal shape between the bead cores **11, 11** on the left and right, and constitutes the backbone of the tire. Additionally, both end portions of the carcass layer **13** are wound and turned back toward an outer side in the tire width direction to wrap the bead cores **11** and the bead fillers **12**, and are fixed. The carcass ply of the carcass layer **13** is formed by covering, with coating rubber, a plurality of carcass cords made of steel and by performing a rolling process on the carcass cords and has a cord angle (defined as an inclination angle in a longitudinal direction of the carcass cord with respect to the tire circumferential direction) being 80° or more and 90° or less as an absolute value.

(18) The belt layer **14** is made of a plurality of belt plies **141** to **144** being layered, and is disposed by being wound around an outer circumference of the carcass layer **13**. The belt plies **141** to **144** include a large-angle belt **141**, a pair of cross belts **142, 143**, and a belt cover **144**. The large-angle belt **141** is constituted by covering, with coating rubber, a plurality of belt cords made of steel and by performing a rolling process on the belt cords. The large-angle belt **141** has a cord angle (defined as an inclination angle in a longitudinal direction of the belt cords with respect to the tire circumferential direction) of 45 degrees or more and 70 degrees or less as an absolute value. The pair of cross belts **142, 143** are each constituted by covering, with coating rubber, a plurality of belt cords made of steel and by performing a rolling process on the belt cords. Each of the pair of cross belts **142, 143** has a cord angle of 10 degrees or more and 55 degrees or less as an absolute value. Additionally, the pair of cross belts **142, 143** have cord angles having mutually opposite signs, and the pair of cross belts **142, 143** are layered by making the belt cords mutually intersect in the longitudinal direction of the belt cords (a so-called crossply structure is formed). The belt cover **144** is constituted by covering, with coating rubber, a plurality of belt cover cords made of steel or

an organic fiber material and by performing a rolling process on the belt cover cords. The belt cover **144** has a cord angle of 10 degrees or more and 55 degrees or less as an absolute value. (19) The tread rubber **15** is disposed in the outer circumferences in the tire radial direction of the carcass layer **13** and the belt layer **14** and constitutes a tread portion of the tire. The pair of sidewall rubbers **16, 16** are disposed on an outer side in the tire width direction of the carcass layer **13** and constitute sidewall portions on the left and right, respectively. The pair of rim cushion rubbers **17, 17** extend from an inner side in the tire radial direction of the bead cores **11, 11** on the left and right and turned back portions of the carcass layer **13** toward the outer side in the tire width direction, and constitute rim fitting surfaces of the bead portions.

(20) Tread Surface

(21) FIG. **2** is a plan view illustrating a tread surface of the pneumatic tire illustrated in FIG. **1**. The same drawing illustrates a tread surface of an all-season tire. In the same drawing, “tire circumferential direction” refers to the direction about the tire rotation axis. Additionally, reference sign T denotes a tire ground contact edge, and dimension symbol TW denotes a tire ground contact width.

(22) As illustrated in FIG. **2**, the pneumatic tire **1** includes, in the tread surface, a plurality of main grooves **21, 22** extending in the tire circumferential direction and a plurality of land portions **31** to **33** defined by the main grooves **21, 22**.

(23) “Main groove” refers to a groove on which a wear indicator must be provided as specified by JATMA and has a groove width of 6.0 mm or more and a groove depth of 10 mm or more. Additionally, in the configuration of FIG. **2**, groove widths Wg1, Wg2 of the main grooves **21, 22**, respectively (see FIG. **2**), are in the range of 3% or more and 4% or less with respect to a tire ground contact width TW.

(24) The groove width is measured as a distance between groove walls opposed to each other in a groove opening portion when the tire is mounted on a specified rim, inflated to a specified internal pressure, and in an unloaded state. In a configuration in which the groove opening portion includes a notch portion or a chamfered portion, the groove width is measured with intersection points between an extension line of the tread contact surface and extension lines of the groove walls as measurement points, in a cross-sectional view parallel with the groove width direction and the groove depth direction.

(25) The groove depth is measured as a distance from the tread contact surface to a groove bottom when the tire is mounted on a specified rim, inflated to a specified internal pressure, and in an unloaded state. Additionally, in a configuration in which the groove bottom partially includes a raised bottom portion, a sipe, or a recess/protrusion portion, the groove depth is measured excluding the raised bottom portion, the sipe, or the recess/protrusion portion.

(26) “Specified rim” refers to a “standard rim” defined by JATMA, a “Design Rim” defined by the Tire and Rim Association, Inc. (TRA), or a “Measuring Rim” defined by the European Tyre and Rim Technical Organisation (ETRTO). Additionally, “specified internal pressure” refers to a “maximum air pressure” defined by JATMA, to the maximum value in “TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES” defined by TRA, or to “INFLATION PRESSURES” defined by ETRTO. Additionally, “specified load” refers to a “maximum load capacity” defined by JATMA, the maximum value in “TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES” defined by TRA, or “LOAD CAPACITY” defined by ETRTO.

However, in JATMA, in the case of a tire for a passenger vehicle, specified internal pressure is an air pressure of 180 kPa, and specified load is 88% of the maximum load capacity at the specified internal pressure.

(27) For example, in the configuration of FIG. **2**, four main grooves **21, 22** are disposed in a left-right symmetry about the tire equatorial plane CL. Five rows of land portions are defined by the main grooves **21, 22**. In addition, one land portion **33** is disposed on the tire equatorial plane CL.

(28) However, the configuration is not limited thereto, and three or five main grooves may be

disposed (not illustrated). Additionally, a land portion may be disposed at a distance from the tire equatorial plane CL (not illustrated).

(29) Additionally, of the main grooves **21, 22:21, 22** disposed in each of the regions being demarcated by the tire equatorial plane CL, the main grooves **21, 21** on outermost sides in the tire width direction are defined as shoulder main grooves, and the other main grooves **22, 22** are defined as center main grooves.

(30) In the configuration of FIG. 2, a distance (dimension symbol omitted in drawings) from the tire equatorial plane CL to a groove center line of each of the shoulder main grooves **21, 21** of left and right is in the range of 26% or more and 32% or less of the tire ground contact width TW. A distance from the tire equatorial plane CL to a groove center line of each of the center main grooves, **22, 22** of left and right is in the range of 8% or more and 12% or less of the tire ground contact width TW.

(31) The groove center line is defined as an imaginary line connecting midpoints of measurement points of a distance between groove walls opposed to each other.

(32) The tire ground contact width TW is measured as a maximum linear distance in the tire axial direction of a contact surface of the tire and a flat plate when the tire is mounted on a specified rim, inflated to a specified internal pressure, placed perpendicular to the flat plate in a static state, and loaded with a load corresponding to a specified load.

(33) A tire ground contact edge T is defined as a maximum width position in the tire axial direction of the contact surface between the tire and a flat plate when the tire is mounted on a specified rim, inflated to a specified internal pressure, placed perpendicular to the flat plate in a static state, and loaded with a load corresponding to a specified load.

(34) The land portions **31, 31** located on the outer side in the tire width direction, the outer side being defined by the shoulder main grooves **21, 21**, are defined as the shoulder land portions. The shoulder land portions **31, 31** are land portions on the outermost sides in the tire width direction and are located on the tire ground contact edges T. Additionally, the land portions **32, 32** located on an inner side in the tire width direction, the inner side being defined by the shoulder main groove **21, 21**, are defined as the middle land portions. The middle land portions **32, 32** are each adjacent to the shoulder land portion **31** across the shoulder main groove **21**. Furthermore, the land portion **33** located closer to a tire equatorial plane CL side than the middle land portions **32, 32** is defined as the center land portion. The center land portion **33** may be disposed on the tire equatorial plane CL (see FIG. 2) or may be arranged at a position away from the tire equatorial plane CL (not illustrated).

(35) In a configuration including four main grooves **21, 22** as illustrated in FIG. 2, a pair of the shoulder land portions **31, 31**, a pair of the middle land portions **32, 32**, and a single center land portion **33** are defined. Additionally, for example, in a configuration including five or more main grooves, two or more rows of the center land portions are defined (not illustrated), and in a configuration including three main grooves, the middle land portion also serves as the center land portion (not illustrated).

(36) In the configuration of FIG. 2, the shoulder land portion **31** is a block row defined by lug grooves **311** described below, and the middle land portion **32** and the center land portion **33** are ribs that are continuous in the tire circumferential direction.

(37) In the configuration described above, the land portions **32, 33** in the tread portion center region are ribs continuous in the tire circumferential direction, and the rigidity of the land portions **32, 33** is ensured while the wear resistance performance and uneven wear resistance performance of the tire are ensured. The land portions **32, 33** in the tread portion center region include a pair of middle lug grooves **321, 322** and another pair of lug grooves **331, 332**, the pairs of lug grooves having a semi-closed structure described below, and thus the snow traction performance of the tire is ensured.

(38) In FIG. 2, maximum ground contact widths Wb1, Wb2, Wb3 of the land portions **31, 32, 33**,

respectively, are in the range of 15% or more and 25% or less with respect to the tire ground contact width TW. In the configuration of FIG. 2, the maximum ground contact width Wb2 of the middle land portion 32 is the smallest. The maximum ground contact width Wb3 of the center land portion 33 preferably has the relationship $1.00 \leq Wb3/Wb2 \leq 1.20$ with respect to the maximum ground contact width Wb2 of the middle land portion 32, and more preferably has the relationship $1.05 \leq Wb3/Wb2 \leq 1.10$.

(39) The ground contact widths of the land portions are each measured as a linear distance in the tire axial direction in a contact surface of the land portion and a flat plate, when the tire is mounted on a specified rim, inflated to a specified internal pressure, placed perpendicular to the flat plate in a static state, and subjected to a load corresponding to a specified load.

(40) Zigzag Shape of Main Groove

(41) FIG. 3 is an enlarged view illustrating the shoulder land portion 31 and the middle land portion 32 of the pneumatic tire illustrated in FIG. 2. FIG. 4 is an enlarged view illustrating the middle land portion 32 and the center land portion 33 of the pneumatic tire illustrated in FIG. 2. In the drawings, a dot-dash line in a zigzag shape indicates a groove center line of each of the main grooves 21, 22.

(42) As illustrated in FIG. 2, the shoulder main groove 21 and the center main groove 22 have a zigzag shape having an amplitude in the tire width direction.

(43) Additionally, the shoulder main groove 21 has a zigzag shape formed by alternately connecting linear portions inclined in mutually different directions with respect to the tire circumferential direction. In FIG. 3, a circumferential length Lg1 of the linear portion preferably has the relationship $0.30 \leq Lg1/\lambda_1 \leq 0.70$ with respect to a wavelength λ_1 having a zigzag shape, and more preferably has the relationship $0.35 \leq Lg1/\lambda_1 \leq 0.65$. Accordingly, the shoulder main groove 21 preferably has a zigzag shape formed by connecting linear portions having a substantially identical length. Additionally, an amplitude A1 of the zigzag shape of the shoulder main groove 21 has the relationship $0.03 \leq A1/TW \leq 0.05$ with respect to the tire ground contact width TW.

(44) The center main groove 22 has a zigzag shape formed by alternately connecting long portions and short portions that are inclined in mutually different directions with respect to the tire circumferential direction. In FIG. 4, a circumferential length Lg2 of the long portion having a zigzag shape preferably has the relationship $0.70 \leq Lg2/\lambda_2 \leq 0.90$ with respect to a wavelength λ_2 having a zigzag shape, and more preferably has the relationship $0.75 \leq Lg2/\lambda_2 \leq 0.85$. Additionally, an amplitude A2 of the zigzag shape has the relationship $0.03 \leq A2/TW \leq 0.05$ with respect to the tire ground contact width TW.

(45) In the configuration described above, at least one of the main grooves 22 defining the land portions 32, 33 have the zigzag shape formed by alternately connecting the long portions and the short portions. Thus, compared to a configuration in which both of the main grooves have a straight shape, the snow traction performance of the tire can be improved while the rigidity of the land portions 32, 33 is ensured. Further, compared to a configuration in which both of the main grooves have a zigzag shape formed by linear portions having an approximately identical length, the rigidity of the land portions 32, 33 is ensured and the uneven wear resistance performance of the tire is improved.

(46) In FIG. 3, the wavelengths λ_1 , λ_2 of the zigzag shapes in the shoulder main groove 21 and the center main groove 22, respectively, have the relationship $1.50 \leq \lambda_2/\lambda_1 \leq 2.00$. Additionally, within the same pitch, the wavelength λ_2 in the center main groove 22 is preferably an integer multiple of the wavelength λ_1 in the shoulder main groove 21. For example, in the configuration of FIG. 3, a ratio λ_2/λ_1 of the wavelengths λ_1 , λ_2 within the same pitch is set to be twice.

(47) In FIG. 4, the center main grooves 22, 22 adjacent to each other have an identical wavelength λ_2 and an identical amplitude A2. However, when a ratio of wavelengths λ_2 and a ratio of amplitudes A2 of both of the main grooves are within $\pm 5\%$, the wavelengths and the amplitudes are considered to be identical. Additionally, a phase difference ϕ_2 in the zigzag shapes of the center

main grooves **22**, **22** adjacent to each other has the relationship $0 \leq \phi_2 / \lambda_2 \leq 0.10$ with respect to the wavelength λ_2 having the zigzag shape. Accordingly, the center main grooves **22**, **22** adjacent to each other are disposed with their zigzag phases aligned.

(48) In the configuration of FIG. 2, as described above, the shoulder main groove **21** has the zigzag shape formed by connecting the linear portions having the substantially identical length, and the center main groove **22** has the zigzag shape formed by alternately connecting the long portions and the short portions. In such a configuration, the traction characteristics of the shoulder region in the tread portion are improved, and the snow performance of the tire is effectively enhanced. On the other hand, the rigidity of an edge portion of the land portion **32** on the tire equatorial plane CL side is ensured, and the center wear of the land portion **32** is suppressed. Accordingly, the snow performance and uneven wear resistance performance of the tire are provided in a compatible manner.

(49) However, no such limitation is intended, and both the shoulder main groove **21** and the center main groove **22** may have the zigzag shape formed by alternately connecting the long portions and the short portions (not illustrated). Specifically, in FIG. 2, the shoulder main groove **21** has an identical structure to the center main groove **22**, and thus the edge portions of left and right of the middle land portion **32** may have an identical structure to the center land portion **33**.

(50) Also, in the configuration of FIG. 2, as described above, the shoulder main groove **21** having a shorter wavelength λ_1 ($< \lambda_2$) is disposed closer to a tire ground contact edge T side than the center main groove **22** having a longer wavelength λ_2 . In such a configuration, the traction characteristics of the shoulder region in the tread portion are improved, and the snow performance of the tire is effectively enhanced. On the other hand, the center main groove **22** on the tire equatorial plane CL side has a zigzag shape having the longer wavelength λ_2 , and thus the rigidity of the tread portion center region is ensured, and the uneven wear resistance performance of the tire is ensured. Thus, the snow performance and uneven wear resistance performance of the tire are preferably provided in a compatible manner.

(51) However, no such limitation is intended, and the shoulder main groove **21** may have a zigzag shape having a longer wavelength than the center main groove **22** (not illustrated), and the shoulder main groove **21** and the center main groove **22** may have an identical wavelength and amplitude (not illustrated).

(52) In the configuration of FIG. 2, as illustrated in FIG. 3, the zigzag shape of the shoulder main groove **21** has a see-through structure when viewed in the tire circumferential direction. Thus, an edge portion of the shoulder land portion **31** and an edge portion of the middle land portion **32** do not overlap each other when viewed in the tire circumferential direction. Accordingly, a groove volume of the shoulder main groove **21** is ensured and the drainage properties of the tire are enhanced.

(53) On the other hand, as illustrated in FIG. 4, the zigzag shape of the center main groove **22** has a see-through-less structure when viewed in the tire circumferential direction. Thus, the edge portion of the middle land portion **32** and an edge portion of the center land portion **33** overlap each other when viewed in the tire circumferential direction. Thus, the traction characteristics of the tire are improved.

(54) Shoulder Land Portion

(55) FIG. 5 is an enlarged view illustrating the shoulder land portion **31** illustrated in FIG. 3. The same drawing illustrates a single shoulder block **312**.

(56) As illustrated in FIG. 2 and FIG. 3, the shoulder land portion **31** includes the shoulder lug grooves **311**, the shoulder blocks **312**, circumferential narrow grooves **313**, and notch portions **314**.

(57) The shoulder lug groove **311** has a so-called open structure, extends through the shoulder land portion **31** in the tire width direction, and is open to the shoulder main groove **21** and the tire ground contact edge T. As illustrated in FIG. 5, the shoulder lug groove **311** is open to a maximum amplitude position, toward the tire ground contact edge T, of the zigzag shape of the shoulder main

grooves **21**. Additionally, a plurality of the shoulder lug grooves **311** are arrayed at a predetermined interval in the tire circumferential direction. A maximum groove width (dimension symbol omitted in drawings) of the shoulder lug groove **311** is in the range of 10 mm or more and 25 mm or less. A maximum groove depth (not illustrated) of the shoulder lug groove **311** is in the range of 30% or more and 80% or less with respect to a maximum groove depth of the shoulder main groove **21**. Note that in the configuration of FIG. 5, the shoulder lug groove **311** is shallower than the shoulder main groove **21**, and thus in a tread plan view, a boundary portion between the shoulder lug groove **311** and the shoulder main groove **21** appears as a ridge line.

(58) The shoulder block **312** is formed by the shoulder land portion **31** being defined by the shoulder lug grooves **311** in the tire circumferential direction. Also, a single block row is formed. As illustrated in FIG. 5, an edge portion of the shoulder block **312** on a shoulder main groove **21** side has a zigzag shape along the shoulder main groove **21**. Also, an edge portion of one shoulder block **312** includes two protrusion portions that project toward the shoulder main groove **21** and one recess portion that is recessed with respect to the shoulder main groove **21**. Additionally, a maximum circumferential length L_{12} of the shoulder block **312** has the relationship $0.40 \leq \lambda_1 / L_{12} \leq 0.70$ with respect to the wavelength λ_1 of the shoulder main groove **21**, the wavelength λ_1 having the zigzag shape. The maximum circumferential length L_{12} of the shoulder block **312** has the relationship $1.10 \leq L_{12} / W_{b1} \leq 1.40$ with respect to the maximum ground contact width W_{b1} of the shoulder land portion **31**.

(59) The circumferential narrow groove **313** extends through the shoulder block **312** in the tire circumferential direction and is open to the shoulder lug groove **311**. As illustrated in FIG. 5, the circumferential narrow groove **313** has a zigzag shape, and an amplitude (dimension symbol omitted in drawings) of the circumferential narrow groove **313** is smaller than the amplitude A_1 (see FIG. 3) of the shoulder main groove **21**. Additionally, a maximum groove width (dimension symbol omitted in drawings) of the circumferential narrow groove **313** is in the range of 2% or more and 10% or less with respect to the maximum ground contact width W_{b1} of the shoulder land portion **31**. The maximum groove depth (not illustrated) of the circumferential narrow groove **313** is in the range of 30% or more and 80% or less with respect to the maximum groove depth of the shoulder main groove **21**. A distance D_{13} from the tire ground contact edge T to the circumferential narrow groove **313** is in the range $0.30 \leq D_{13} / W_{b1} \leq 0.70$ with respect to the maximum ground contact width W_{b1} of the shoulder land portion **31**.

(60) The notch portion **314** is formed in the edge portion of the shoulder block **312** on the shoulder main groove **21** side. The notch portion **314** is disposed separated from the circumferential narrow groove **313**. The notch portion **314** is formed at the maximum amplitude position, toward the tire ground contact edge T , of the zigzag shape of the shoulder main groove **21**. Moreover, a single notch portion **314** is formed in the shoulder block **312**. An opening width (dimension symbol omitted in drawings) of the notch portion **314** with respect to the shoulder main groove **21** is in the range of 5.0 mm or more and 15 mm or less. A maximum depth (not illustrated) of the notch portion **314** is in the range of 30% or more and 80% or less with respect to the maximum groove depth of the shoulder main groove **21**.

(61) Additionally, as illustrated in FIG. 5, the shoulder block **312** has a plurality of sipes (reference sign omitted in drawings). Specifically, a single circumferential sipe is disposed in a region on the tire ground contact edge T side, the region being defined by the circumferential narrow groove **313**, and extends in the tire circumferential direction, and both end portions thereof terminate within the shoulder block **312**. Additionally, a plurality of sipes in the tire width direction are disposed in a region on the shoulder main groove **21** side, the region being defined by the circumferential narrow groove **313**, and extend in the tire width direction, connecting the circumferential narrow groove **313** and the shoulder main groove **21** or the notch portion **314**.

(62) "Sipe" refers to a cut formed in a tread contact surface and has a sipe width of less than 1.5 mm and a sipe depth of 2.0 mm or more, so that the sipe closes when the tire comes into contact

with the ground.

(63) The sipe width is measured as the maximum opening width of the sipe on the tread contact surface when the tire is mounted on a specified rim, inflated to a specified internal pressure, and in an unloaded state.

(64) The sipe depth is measured as a distance from the tread contact surface to a sipe bottom, when the tire is mounted on a specified rim, inflated to a specified internal pressure, and in an unloaded state. Additionally, in a configuration in which the sipe partially includes, in the sipe bottom, a raised bottom portion or a recess/protrusion portion, the sipe depth is measured excluding the portions.

Middle Land Portion

(65) FIG. 6 is an enlarged view illustrating the middle land portion 32 illustrated in FIG. 3. The same drawing is an extracted view of a single middle land portion 32. FIG. 7 is a cross-sectional view of the middle land portion 32 illustrated in FIG. 6. The same drawing illustrates a cross-sectional view along a first middle lug groove 321.

(66) As illustrated in FIG. 2 and FIG. 3, the middle land portion 32 includes the first middle lug groove 321 having a long length, and a second middle lug groove 322 having a short length.

(67) The first and second middle lug grooves 321, 322 have a so-called semi-closed structure, and are each open to the shoulder main groove 21 at one end portion, and terminate in the middle land portion 32 at the other end portion. Also, all of the middle lug grooves 321, 322 are open to an edge portion of the middle land portion 32 on the tire ground contact edge T side, and not open to an edge portion on the tire equatorial plane CL side. Accordingly, the edge portion of the middle land portion 32 on the tire equatorial plane CL side has a plain structure that is not divided by lug grooves. Additionally, both the first and second middle lug grooves 321, 322 are each open to a maximum amplitude position, toward the tire equatorial plane CL, of the zigzag shape of the shoulder main groove 21. In other words, both the first and second middle lug grooves 321, 322 are open at positions in the edge portion of the middle land portion 32, the positions being recessed with respect to the shoulder main groove 21. Additionally the first middle lug grooves 321 and the second middle lug grooves 322 are arrayed at a predetermined interval in the tire circumferential direction.

(68) In FIG. 6, a maximum length L21 of the first middle lug groove 321 in the tire width direction preferably has the relationship $1.30 \leq L21/L22 \leq 2.30$ with respect to a maximum length L22 of the second middle lug groove 322, and preferably has the relationship $1.40 \leq L21/L22 \leq 2.00$.

Accordingly, opening areas of the first and second middle lug grooves 321, 322 are made uniform. The maximum length L21 of the first middle lug groove 321 has the relationship $L21/Wb2 \leq 0.60$ with respect to the maximum ground contact width Wb2 of the middle land portion 32. The maximum length L22 of the second middle lug groove 322 has the relationship $0.20 \leq L22/Wb2$ with respect to the maximum ground contact width Wb2 of the middle land portion 32. A lower limit of a ratio L21/Wb2 and an upper limit of a ratio L22/Wb2 are not particularly limited, but is subject to restrictions by the numerical ranges set forth above by the ratio L21/L22.

(69) A maximum length of a lug groove is an extension length of a lug groove body, and is measured excluding a chamfered portion and a notch portion formed in the lug groove.

(70) In the configuration described above, the first and second middle lug grooves 321, 322 have maximum groove lengths L21, L22 that differ from each other, and thus, compared to a configuration in which maximum groove lengths of the lug grooves are set to be uniform, the uneven wear resistance performance and snow traction performance of the tire can be efficiently provided in a compatible manner.

(71) In the configuration of FIG. 6, the first middle lug groove 321 having a long length ($L21 > L22$) faces the long portion of the zigzag shape of the center main groove 22, and the second middle lug groove 322 having a short length faces the short portion of the zigzag shape of the center main groove 22. Specifically, an extension line of a groove center line (not illustrated) of the first middle

lug groove **321** intersects the long portion of the zigzag shape of the center main groove **22**, and an extension line of a groove center line of the second lug groove **322** intersects the short portion of the zigzag shape of the center main groove **22**.

(72) Additionally, in the configuration of FIG. **6**, groove widths of the first and second middle lug grooves **321**, **322** each monotonically decrease from an opening portion to the shoulder main groove **21** toward a terminating end portion in the middle land portion **32**. In addition, the terminating end portions of the first and second middle lug grooves **321**, **322** have a V-shape formed by connecting first and second edge portions having a linear shape or an arc shape. The first and second middle lug grooves **321**, **322** have a narrower groove width toward an identical direction in the tire circumferential direction (in FIG. **6**, upper side of drawing).

(73) The first and second middle lug grooves **321**, **322** are inclined in an identical direction with respect to the tire circumferential direction. The first and second middle lug grooves **321**, **322** and the long portion of the center main groove **22**, the long portion having a zigzag shape, are inclined in an identical direction with respect to the tire circumferential direction. Also, an inclination angle (not illustrated) of the groove center line of each of the first and second middle lug grooves **321**, **322** with respect to the tire circumferential direction is in the range of 45° or more and 90° or less.

(74) In FIG. **6**, a maximum groove width $W22$ of the second middle lug groove **322** having the short length preferably has the relationship $1.00 \leq W22/W21 \leq 1.50$ with respect to a maximum groove width $W21$ of the first middle lug groove **321** and more preferably has the relationship $1.05 \leq W22/W21 \leq 1.35$. Thus, the second middle lug groove **322** having the short length preferably has a wider structure than the first middle lug groove **321** having the long length. In such a configuration, groove volumes of the first and second middle lug grooves **321**, **322** are made uniform. Accordingly, the rigidity of the middle land portion **32** in the tire circumferential direction is made uniform, and the uneven wear of the middle land portion **32** is suppressed.

(75) Also, the maximum groove width $W21$ of the first middle lug groove **321** having the long length is in the range $5.0 \text{ mm} \leq W21$, and the maximum groove width $W22$ of the second middle lug groove **322** is in the range of $W22 \leq 15 \text{ mm}$. An upper limit of the maximum groove width $W21$ and a lower limit of the maximum groove width $W22$ are not particularly limited, but is subject to restrictions by the numerical ranges set forth above by the ratio $W22/W21$.

(76) In FIG. **7**, a maximum groove depth $H22$ of the second middle lug groove **322** having the short length preferably has the relationship $1.20 \leq H22/H21 \leq 1.60$ with respect to a maximum groove depth $H21$ of the first middle lug groove **321** having the long length, and preferably has the relationship $1.30 \leq H22/H21 \leq 1.50$. In such a configuration, the second middle lug groove **322** having the short length is deeper than the first middle lug groove **321** having the long length, and thus the groove volumes of the first and second middle lug grooves **321**, **322** are made uniform. Accordingly, the rigidity of the middle land portion **32** in the tire circumferential direction is made uniform, and the uneven wear of the middle land portion **32** is suppressed.

(77) Further, in FIG. **7**, the maximum groove depth $H21$ of the first middle lug groove **321** having the long length has the relationship $0.50 \leq H21/Hg1$ with respect to a maximum groove depth $Hg1$ of the shoulder main groove **21**, and the maximum groove depth $H22$ of the second middle lug groove **322** having the short length has the relationship of $H22/Hg1 \leq 0.95$ with respect to the maximum groove depth $Hg1$ of the shoulder main groove **21**. An upper limit of a ratio $H21/Hg1$ and a lower limit of a ratio $H22/Hg1$ are not particularly limited, but is subject to restrictions by the numerical ranges set forth above in the ratio $H22/H21$. Note that in FIG. **6**, the middle lug grooves **321**, **322** are shallower than the shoulder main groove **21**, and thus a ridge line appears in a boundary portion between each of the middle lug grooves **321**, **322** and the shoulder main groove **21** in a tread plan view.

(78) As illustrated in FIG. **6**, the middle land portion **32** includes a plurality of sipes **323**, **324**. Specifically, a first sipe **323** is open to the middle lug groove **321** or **322** at one end portion to extend the middle lug groove **321** or **322** and is open to the center main groove **22** at the other end

portion. Additionally, the first sipe **323** has a straight shape and is inclined in an identical direction with respect to the first and second middle lug grooves **321**, **322**. The second sipe **324** is disposed between the first and second middle lug grooves **321**, **322** adjacent to each other, and extends through the middle land portion **32** in the tire width direction to connect to the main grooves **21**, **22** of left and right. Additionally, the second sipe **324** is inclined in an identical direction with respect to the first and second middle lug grooves **321**, **322**. The second sipe **324** has a zigzag shape and is inclined in an identical direction with respect to the first and second middle lug grooves **321**, **322**. Also, as illustrated in FIG. 7, a maximum depth H23 of the first sipe **323** that connects to the first and second middle lug grooves **321**, **322** is shallower than the maximum groove depths H21, H22 of the first and second middle lug grooves **321**, **322**.

(79) Additionally, as illustrated in FIG. 3, the edge portions of the middle land portion **32** each have a zigzag shape that is parallel with the groove center line of the shoulder main groove **21** or the center main groove **22**. The middle land portion **32** is a rib that is continuous in the tire circumferential direction, and does not include a through lug groove that divides the middle land portion **32** in the tire width direction. This is a difference from the shoulder land portion **31**, which is a block row. Note that the sipes **323**, **324** are closed when the tire contacts the ground and do not inhibit a function of the land portion as a rib.

Center Land Portion

(80) FIG. 8 is an enlarged view illustrating the center land portion **33** illustrated in FIG. 4. The same drawing is an extracted view of a single center land portion **33**. FIG. 9 is a cross-sectional view of the center land portion **33** illustrated in FIG. 8. The same drawing is a cross-sectional view along the center lug groove **331** (**332**).

(81) As illustrated in FIG. 2 and FIG. 4, the center land portion **33** includes the first and second center lug grooves **331**, **332**.

(82) The first and second center lug grooves **331**, **332** have the so-called semi-closed structure, are open to the center main groove **22** at one end portion, and terminate at the other end portion in the center land portion **33**. The first center lug groove **331** is formed in one edge portion of the center land portion **33**, and the second center lug groove **332** is formed in the other edge portion of the center land portion **33**. The first and second center lug grooves **331**, **332** are each open to the maximum amplitude position, toward the tire equatorial plane CL, of the zigzag shape of the center main groove **22**. In other words, the first and second center lug grooves **331**, **332** are open at positions in the edge portion of the center land portion **33**, the positions being recessed with respect to a corresponding one of the center main grooves **22**, **22**. As illustrated in FIG. 8, opening positions of the first and second center lug grooves **331**, **332** are each preferably biased toward the side of the long portion of the zigzag shape of the center main grooves **22**, **22**. Additionally, the first and second center lug grooves **331**, **332** are disposed alternately in a staggered manner in the tire circumferential direction.

(83) In FIG. 8, maximum groove widths W31, W32 of the first and second center lug grooves **331**, **332** are in the range of 5.0 mm or more and 10 mm or less. Additionally, the maximum groove widths W31, W32 of the first and second center lug grooves **331**, **332** have the relationship $0.90 \leq W32/W31 \leq 1.10$, and preferably have the relationship $0.95 \leq W32/W31 \leq 1.05$. Thus, the first and second center lug grooves **331**, **332** have a substantially identical maximum groove width.

(84) Additionally, in FIG. 8, maximum lengths L31, L32 of the first and second center lug grooves **331**, **332** in the tire width direction have the relationships $0.20 \leq L31/Wb3 \leq 0.60$ and $0.20 \leq L32/Wb3 \leq 0.60$ with respect to the maximum ground contact width Wb3 of the center land portion **33**, and preferably have the relationships $0.35 \leq L31/Wb3 \leq 0.45$ and $0.35 \leq L32/Wb3 \leq 0.45$. The maximum lengths L31, L32 of the first and second center lug grooves **331**, **332** preferably have the relationship $0.90 \leq L32/L31 \leq 1.10$, and more preferably have the relationship $0.95 \leq L32/L31 \leq 1.05$. Thus, the first and second center lug grooves **331**, **332** have a substantially identical maximum groove length.

(85) In FIG. 8, an overlap W_r of the center lug grooves 331, 332 adjacent to each other when viewed in the tire circumferential direction has the relationship $0 \leq W_r/W_{b3} \leq 0.30$ with respect to the maximum ground contact width W_{b3} of the center land portion 33, and preferably has the relationship $0.10 \leq W_r/W_{b3} \leq 0.25$.

(86) Additionally, in FIG. 8, a pitch number each of the first and second center lug grooves 331, 332 is equal to a pitch number of the zigzag shape of the center main groove 22. Thus, a pair of the center lug grooves 331, 332 are disposed within one pitch of the center main groove 22. Also, a distance D_3 in the tire circumferential direction between the center lug grooves 331, 332 adjacent to each other has the relationship $0.20 \leq D_3/\lambda_2 \leq 0.50$ with respect to the wavelength λ_2 of the zigzag shape in the center main groove 22.

(87) In the configuration of FIG. 8, the first and second center lug grooves 331, 332 each face the long portion of the zigzag shape of the center main groove 22. Specifically, an extension line of a groove center line (not illustrated) each of the first and second center lug grooves 331, 332 intersects the long portion of the zigzag shape of the center main groove 22.

(88) Additionally, in the configuration of FIG. 8, the groove widths of the first and second center lug grooves 331, 332 each monotonically decrease from the opening portion to the center main groove 22 toward the terminating end portion in the center land portion 33. The opening portion each of the first and second center lug grooves 331, 332 is widened by partially having a chamfered portion or a notch portion (reference sign omitted in drawings) on one side thereof. The terminating end portion each of the first and second center lug grooves 331, 332 has a V-shape formed by connecting first and second edge portions having a linear shape or an arc shape. Additionally, the pair of the first and second center lug grooves 331, 332 are each disposed on one long portion of the zigzag shape of the center main groove 22, and the center lug grooves 331, 332 have curved shapes in mutually opposite directions.

(89) The first and second center lug grooves 331, 332 are inclined in an identical direction with respect to the tire circumferential direction. The first and second center lug grooves 331, 332 and the long portion of the zigzag shape of the center main groove 22 are inclined in mutually opposite directions with respect to the tire circumferential direction. Also, the inclination angle (not illustrated) of the groove center line of each of the first and second center lug grooves 331, 332 with respect to the tire circumferential direction is in the range of 45° or more and 90° or less.

(90) In FIG. 9, maximum groove depths H_{31} , H_{32} of the first and second center lug grooves 331, 332 have the relationships $0.70 \leq H_{31}/H_{g2} \leq 1.00$ and $0.70 \leq H_{32}/H_{g2} \leq 1.00$ with respect to a maximum groove depth H_{g2} of the center main groove 22. Also, the maximum groove depths H_{31} , H_{32} of the first and second center lug grooves 331, 332 preferably have the relationship $0.90 \leq H_{32}/H_{31} \leq 1.10$. Thus, the first and second center lug grooves 331, 332 have a substantially identical maximum groove depth. Note that in the configuration of FIG. 8, the center lug grooves 331, 332 are shallower than the center main groove 22, and thus a ridge line appears in a boundary portion between each of the center lug grooves 331, 332 and the center main groove 22 in a tread plan view.

(91) As illustrated in FIG. 8, the center land portion 33 includes a plurality of sipes 333, 334. Specifically, the first sipe 333 is open to the center lug groove 331 or 332 at one end portion to extend the center lug groove 331 or 332 and is open to the center main groove 22 at the other end portion. The first sipe 333 has a straight shape and is inclined in an identical direction with respect to the center lug grooves 331, 332. The second sipe 334 is disposed between the first and second center lug grooves 331, 332 adjacent to each other, and extends through the center land portion 33 in the tire width direction to connect to the center main grooves 22, 22 of left and right. The second sipe 334 is inclined in an identical direction with respect to the center lug grooves 331, 332. Also, the second sipe 334 has a zigzag shape and is inclined in an identical direction with respect to the center lug grooves 331, 332. As illustrated in FIG. 9, a maximum depth H_{33} of the first sipe 333 that connects to the center lug groove 331 or 332 is shallower than the maximum groove depths

H31, H32 of the center lug grooves **331**, **332**, respectively.

(92) Also, as illustrated in FIG. 4, edge portions of the center land portion **33** each have a zigzag shape that is parallel with the groove center line of the center main groove **22** of left and right. The center land portion **33** is a rib that is continuous in the tire circumferential direction, and does not include a through lug groove that divides the center land portion **33** in the tire width direction. This is a difference from the shoulder land portion **31**, which is a block row. Note that the sipes are closed when the tire contacts the ground and thus do not inhibit a function of the land portion as a rib.

(93) Effect

(94) As described above, the pneumatic tire **1** includes the plurality of main grooves **21**, **22** having the zigzag shape and extending in the tire circumferential direction, and the land portion **32** defined by the main grooves **21**, **22** adjacent to each other, the land portion **32** having the rib structure that is continuous in the tire circumferential direction (see FIG. 2). The land portion **32** includes the first and second middle lug grooves **321**, **322** having the semi-closed structure (see FIG. 3).

Additionally, the maximum length L21 of the first middle lug groove **321** in the tire width direction preferably has the relationship $1.30 \leq L21/L22 \leq 2.30$ with respect to the maximum length L22 of the second middle lug groove **322**.

(95) In such a configuration (1) the land portion **32** is the rib that is continuous in the tire circumferential direction, and this has the advantage of ensuring the rigidity of the land portion **32** while ensuring the wear resistance performance and uneven wear resistance performance of the tire. Also, (2) the land portion **32** includes the middle lug grooves **321**, **322** having the semi-closed structure, and this has the advantage of ensuring the snow traction performance of the tire. Further, (3) the first and second middle lug grooves **321**, **322** have the maximum groove lengths L21, L22 that differ from each other, and thus, compared to a configuration in which the maximum groove lengths of the lug grooves are set to be uniform, the uneven wear resistance performance and snow traction performance of the tire can be efficiently provided in a compatible manner.

(96) In the pneumatic tire **1** the maximum length L21 of the first middle lug groove **321** has the relationship $L21/Wb2 \leq 0.60$ with respect to the maximum ground contact width Wb2 of the land portion **32**. The maximum length L22 of the second middle lug groove **322** has the relationship $0.20 \leq L22/Wb2$ with respect to the maximum ground contact width Wb2 of the land portion **32**. This has the advantage of appropriately setting the maximum lengths L21, L22 of the first and second middle lug grooves **321**, **322**.

(97) In the pneumatic tire **1**, the first and second middle lug grooves **321**, **322** are open to the edge portion of the land portion **32** on the tire ground contact edge T side (see FIG. 2). This has the advantage of ensuring the rigidity of the edge portion of the land portion **32** on the tire equatorial plane CL side and ensuring the uneven wear resistance performance of the tire.

(98) Additionally, in the pneumatic tire **1** both the first and second middle lug grooves **321**, **322** each open to the maximum amplitude position, toward the tire equatorial plane CL, of the zigzag shape of the main groove **21** (see FIG. 3).

(99) Such a configuration has the advantage of increasing the maximum ground contact width Wb2 of the land portions **32** and effectively suppressing the uneven wear of the land portion **32**, compared to a configuration in which the lug grooves open to a maximum amplitude position, toward the tire ground contact edge, of the zigzag shape of the main groove.

(100) In the pneumatic tire **1** the maximum groove width W22 of the second middle lug groove **322** has the relationship $1.05 \leq W22/W21 \leq 1.50$ with respect to the maximum groove width W21 of the first middle lug groove **321** (see FIG. 6). In such a configuration, the maximum groove width W22 of the second middle lug groove **322** having the short length is wider than the maximum groove width W21 of the first middle lug groove **321** having the long length, and thus the groove volumes of the first and second middle lug grooves **321**, **322** are made uniform. This has the advantage of making the rigidity of the land portion **32** in the tire circumferential direction uniform and

suppressing the uneven wear of the land portion **32**

(101) Also, in the pneumatic tire **1**, the maximum groove width $W21$ of the first middle lug groove **321** is in the range $4.0 \text{ mm} \leq W21$, and the maximum groove width $W22$ of the second middle lug groove **322** is in the range of $W22 \leq 15 \text{ mm}$ (See FIG. 6). This has the advantage of appropriately setting the maximum groove widths $W21$, $W22$ of the first and second middle lug grooves **321**, **322**.

(102) Further, in the pneumatic tire **1** the maximum groove depth $H22$ of the second middle lug groove **322** has the relationship $1.20 \leq H22/H21 \leq 1.60$ with respect to the maximum groove depth $H21$ of the first middle lug groove **321**.

(103) In such a configuration the maximum groove depth $H22$ of the second middle lug groove **322** having the short length is larger than the maximum groove depth $H21$ of the first middle lug groove **321** having the long length, and thus the groove volumes of the first and second middle lug grooves **321**, **322** are made uniform. This has the advantage of making the rigidity of the land portion **32** in the tire circumferential direction uniform and suppressing the uneven wear of the land portion **32**.

(104) In the pneumatic tire **1**, the maximum groove depth $H21$ of the first middle lug groove **321** has the relationship $0.50 \leq H21/Hg1$ with respect to the maximum groove depth $Hg1$ of the main groove **21**, and the maximum groove depth $H22$ of the second middle lug groove **322** has the relationship $H22/Hg1 \leq 0.95$ with respect to the maximum groove depth $Hg1$ of the main groove **21**. This has the advantage of appropriately setting the maximum groove depths $H21$, $H22$ of the first and second middle lug grooves **321**, **322**.

(105) Further, in the pneumatic tire **1**, of the main grooves **21**, **22** defining the land portion **32**, the main groove **21** on the tire ground contact edge T side has the zigzag shape formed by connecting the linear portions having the approximately identical length, and the circumferential length $Lg1$ of the linear portion has the relationship $0.30 \leq Lg1/\lambda1 \leq 0.70$ with respect to the wavelength $\lambda1$ of the zigzag shape (see FIG. 3). Additionally, the main groove **22** on the tire equatorial plane CL side has the zigzag shape formed by connecting the long portions and the short portions, and the circumferential length $Lg2$ of the long portion has the relationship $0.70 \leq Lg2/\lambda2 \leq 0.90$ with respect to the wavelength $\lambda2$ of the zigzag shape. Such a configuration has the advantage of improving the traction characteristics of the tread portion shoulder region and effectively enhancing the snow performance of the tire. On the other hand, the rigidity of an edge portion of the land portion **32** on the tire equatorial plane CL side is ensured, and the center wear of the land portion **32** is suppressed. This has the advantage of providing the snow performance and uneven wear resistance performance of the tire in a compatible manner.

(106) Also, in the pneumatic tire **1** the wavelengths $\lambda1$, $\lambda2$ of the zigzag shapes of the main grooves **21**, **22**, respectively, have the relationship $1.50 \leq \lambda2/\lambda1 \leq 2.00$ (see FIG. 3). The lower limit described above provides the advantage of ensuring reinforcement of the rigidity of the edge portion of the land portion **32** on the tire equatorial plane CL side due to the longer wavelength $\lambda2$. The upper limit described above provides the advantage of alleviating a difference in rigidity between the edge portions of left and right of the land portion **32**.

(107) Further, in the pneumatic tire **1**, the first and second middle lug grooves **321**, **322** are open to the edge portion of the land portion **32** on the tire ground contact edge T side, and the first middle lug groove **321** is disposed opposite the long portion of the main groove **22** on the tire equatorial plane CL side (see FIG. 3). Such a configuration enhances the rigidity of the edge portion of the land portion **32** on the tire equatorial plane CL side, compared to a configuration in which the first middle lug groove **321** having the long length is disposed opposite the short portion of the main groove **22** on the tire equatorial plane CL side. This has the advantage of suppressing the center wear of the land portion **32**.

(108) Additionally, in the pneumatic tire **1**, the first and second middle lug grooves **321**, **322** are open to the edge portion of the land portion **32** on the tire ground contact edge T side, and the inclination direction of the first middle lug groove **321** with respect to the tire circumferential

direction is the same as the inclination direction of the long portion of the main groove **22** on the tire equatorial plane CL side (see FIG. **3**). Such a configuration enhances the rigidity of the edge portion of the land portion **32** on the tire equatorial plane CL side, compared to a configuration in which the inclination direction of the first middle lug groove **321** having the long length is opposite to the inclination direction of the long portion of the main groove **22** on the tire equatorial plane CL side. This has the advantage of suppressing the center wear of the land portion **32**.

(109) Additionally, in the pneumatic tire **1** the main groove **21** on the tire ground contact edge T side is the shoulder main groove on an outermost side in the tire width direction (see FIG. **2**). This has the advantage of effectively exhibiting the effects described above of the main grooves **21**, **22** of left and right, the main grooves defining the land portion **21**.

(110) Further, the pneumatic tire **1** includes the shoulder land portion **31** defined by the shoulder main grooves **21** (see FIG. **2**). Further, the shoulder land portion **21** includes the plurality of the lug grooves **311** extending through the shoulder land portion **31** and a plurality of the blocks **312** defined by the lug grooves **311**. This has the advantage of enhancing the snow traction properties of the tread portion shoulder region.

(111) Additionally, the pneumatic tire **1** is a heavy duty tire mounted on a drive shaft of a vehicle. By application to such a heavy duty tire, there is an advantage that a significant effect of improving the snow traction performance and uneven wear resistance performance of the tire can be obtained.

EXAMPLES

(112) FIG. **10** and FIG. **11** are tables showing the results of performance tests of pneumatic tires according to embodiments of the technology.

(113) In the performance tests, a plurality of types of test tires were evaluated in terms of (1) snow traction performance and (2) uneven wear resistance performance. Test tires having a tire size of 11R22.5 are assembled on rims specified by JATMA, and an internal pressure specified by JATMA and a load specified by JATMA are applied to the test tires. Additionally, the test tires were each mounted on a drive shaft of a tractor head of a 2-D (two-wheel vehicle), which is a test vehicle.

(114) (1) For evaluation of snow traction performance, the test vehicle is driven on a snowy road surface of a snowy road test site and the acceleration time until the travel speed reaches 20 km/h from 5 km/h is measured. The measurement results are expressed as index values and evaluated with Conventional Example being assigned as the reference (100). In this evaluation, larger values are preferable.

(115) (2) In the evaluation of uneven wear resistance performance, the test vehicle runs 30000 km on a predetermined paved road, and then degrees of heel and toe wear are measured and expressed as index values and evaluated. Results of the evaluation are expressed as index values and evaluated with the Conventional Example being assigned as the reference (100). In this evaluation, larger values are preferable.

(116) The test tires of Examples are provided with the configurations of FIG. **1** and FIG. **2**, and include four main grooves **21**, **22** having a zigzag shape and five rows of land portions **31** to **33** defined by the main grooves **21**, **22**. Also, the maximum groove widths $Wg1$, $Wg2$ of the main grooves **21**, **22**, respectively, are each 9.0 mm, and the maximum groove depths $Hg1$, $Hg2$ of the main grooves **21**, **22**, respectively, are each 21 mm. The wavelength $\lambda1$ of the zigzag shape of the shoulder main groove **21** is 40 mm, and the length $Lg1$ of the linear portion that is the long portion is 25 mm. A ratio of the maximum ground contact width $Wb2$ of the middle land portion **32** and the maximum ground contact width $Wb3$ of the center land portion **33** with respect to the tire ground contact width TW is 20%. The tire ground contact width TW is 240 mm.

(117) The test tire of Conventional Example includes, in the configuration of FIG. **1** and FIG. **2**, main grooves **21**, **22** that have a straight shape.

(118) As can be seen from the test results, the test tires of the Examples provide both snow traction performance and uneven wear resistance performance in a compatible manner.

Claims

1. A pneumatic tire comprising: a plurality of main grooves having a zigzag shape and extending in a tire circumferential direction; and, a land portion defined by the main grooves adjacent to each other, the land portion having a rib structure that is continuous in the tire circumferential direction, the land portion comprising first and second lug grooves having a semi-closed structure, a maximum length $L21$ of the first lug groove in a tire width direction having a relationship $1.30 \leq L21/L22 \leq 2.30$ with respect to a maximum length $L22$ of the second lug groove, the first and second lug grooves being open to an edge portion of the land portion on a tire ground contact edge side; and an edge portion of the land portion on the tire equatorial plane side having a plain structure that is not divided by lug grooves; wherein of the main grooves defining the land portion, the main groove on a tire ground contact edge side has a zigzag shape formed by alternately connecting linear portions having an approximately identical length, a circumferential length $Lg1$ of the linear portion has a relationship $0.30 \leq Lg1/\lambda_1 \leq 0.70$ with respect to a wavelength λ_1 of the zigzag shape, the main groove on a tire equatorial plane side has a zigzag shape formed by alternately connecting long portions and short portions, a circumferential length $Lg2$ of the long portion has a relationship $0.70 \leq Lg2/\lambda_2 < 0.90$ with respect to a wavelength λ_2 of the zigzag shape; and the first lug groove is disposed opposite the long portion of the main groove on the tire equatorial plane side.
2. A pneumatic tire according to claim 1, wherein the maximum length $L21$ of the first lug groove has a relationship $L21/Wb2 \leq 0.60$ with respect to a maximum ground contact width $Wb2$ of the land portion, and the maximum length $L22$ of the second lug groove has a relationship $0.20 \leq L22/Wb2$ with respect to the maximum ground contact width $Wb2$ of the land portion.
3. A pneumatic tire according to claim 1, wherein the first and second lug grooves are open to a maximum amplitude position, toward a tire equatorial plane, of the zigzag shape of the main groove.
4. A pneumatic tire according to claim 1, wherein the wavelengths λ_1 , λ_2 of the zigzag shapes of the main groove have a relationship $1.50 \leq \lambda_2/\lambda_1 \leq 2.00$.
5. A pneumatic tire according to claim 1, wherein the first lug groove has an inclination direction with respect to the tire circumferential direction, the inclination direction being identical with respect to an inclination direction of the long portion of the main groove on the tire equatorial plane side.
6. A pneumatic tire according to claim 1, wherein the main groove on the tire ground contact edge side is a shoulder main groove on an outermost side in the tire width direction.
7. A pneumatic tire according to claim 1, wherein the pneumatic tire comprises a shoulder land portion defined by the shoulder main groove, the shoulder land portion further comprises a plurality of lug grooves extending through the shoulder land portion and a plurality of blocks defined by the lug grooves.
8. A pneumatic tire according to claim 1, wherein the pneumatic tire is a heavy duty tire mounted on a drive shaft of a vehicle.
9. A pneumatic tire according to claim 1, wherein a maximum groove width $W22$ of the second lug groove has a relationship $1.05 \leq W22/W21 \leq 1.50$ with respect to a maximum groove width $W21$ of the first lug groove.
10. A pneumatic tire according to claim 9, wherein the maximum groove width $W21$ of the first lug groove is in a range of $4.0 \text{ mm} \leq W21$, and the maximum groove width $W22$ of the second lug groove is in a range of $W22 \leq 15 \text{ mm}$.
11. A pneumatic tire according to claim 1, wherein a maximum groove depth $H22$ of the second lug groove has a relationship $1.20 \leq H22/H21 \leq 1.60$ with respect to a maximum groove depth $H21$ of the first lug groove.

12. A pneumatic tire according to claim 11, wherein the maximum groove depth H21 of the first lug groove has a relationship $0.50 \leq H21/Hg1$ with respect to a maximum groove depth Hg1 of the main groove, and the maximum groove depth H22 of the second lug groove has a relationship $H22/Hg1 \leq 0.95$ with respect to the maximum groove depth Hg1 of the main groove.
13. A pneumatic tire comprising: a plurality of main grooves having a zigzag shape and extending in a tire circumferential direction; and, a land portion defined by the main grooves adjacent to each other, the land portion having a rib structure that is continuous in the tire circumferential direction, the land portion comprising first and second lug grooves having a semi-closed structure, a maximum length L21 of the first lug groove in a tire width direction having a relationship $1.30 \leq L21/L22 \leq 2.30$ with respect to a maximum length L22 of the second lug groove, and a maximum groove depth H22 of the second lug groove having a relationship $1.20 \leq H22/H21 \leq 1.60$ with respect to a maximum groove depth H21 of the first lug groove.
14. A pneumatic tire comprising: a plurality of main grooves having a zigzag shape and extending in a tire circumferential direction; and, a land portion defined by the main grooves adjacent to each other, the land portion having a rib structure that is continuous in the tire circumferential direction, the land portion comprising first and second lug grooves having a semi-closed structure, a maximum length L21 of the first lug groove in a tire width direction having a relationship $1.30 \leq L21/L22 \leq 2.30$ with respect to a maximum length L22 of the second lug groove, of the main grooves defining the land portion, the main groove on a tire ground contact edge side having a zigzag shape with a wavelength $\lambda 1$ formed by alternately connecting linear portions having an approximately identical length, the main groove on a tire equatorial plane side having a zigzag shape with a wavelength $\lambda 2$ formed by alternately connecting long portions and short portions, and the wavelengths $\lambda 1$, $\lambda 2$ having a relationship $1.50 \leq \lambda 2/\lambda 1 \leq 2.00$.
15. A pneumatic tire comprising: a plurality of main grooves having a zigzag shape and extending in a tire circumferential direction; and, a land portion defined by the main grooves adjacent to each other, the land portion having a rib structure that is continuous in the tire circumferential direction, the land portion comprising first and second lug grooves having a semi-closed structure, a maximum length L21 of the first lug groove in a tire width direction having a relationship $1.30 \leq L21/L22 \leq 2.30$ with respect to a maximum length L22 of the second lug groove, the first and second lug grooves being open to an edge portion of the land portion on a tire ground contact edge side; and an edge portion of the land portion on the tire equatorial plane side having a plain structure that is not divided by lug grooves; wherein of the main grooves defining the land portion, the main groove on a tire ground contact edge side has a zigzag shape formed by alternately connecting linear portions having an approximately identical length, a circumferential length Lg1 of the linear portion has a relationship $0.30 \leq Lg1/\lambda 1 \leq 0.70$ with respect to a wavelength $\lambda 1$ of the zigzag shape, the main groove on a tire equatorial plane side has a zigzag shape formed by alternately connecting long portions and short portions, a circumferential length Lg2 of the long portion has a relationship $0.70 \leq Lg2/\lambda 2 \leq 0.90$ with respect to a wavelength $\lambda 2$ of the zigzag shape; and the first lug groove has an inclination direction with respect to the tire circumferential direction, the inclination direction being identical with respect to an inclination direction of the long portion of the main groove on the tire equatorial plane side.
-