

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404172
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Sakai; Junya et al.

Hydrogen chloride dehydration method

Abstract

A dehydration method in accordance with an embodiment of the present invention includes: a first dehydration step of bringing hydrogen chloride gas (**21**) and concentrated sulfuric acid (**13A**) into contact with each other; and a second dehydration step of bringing hydrogen chloride gas (**21A**) that has been obtained through the first dehydration step into contact with concentrated sulfuric acid (**13B**). A concentration of the concentrated sulfuric acid used in the second dehydration step is higher than a concentration of the concentrated sulfuric acid used in the first dehydration step.

Inventors:	Sakai; Junya (Yamaguchi, JP), Iiyama; Shoji (Yamaguchi, JP)
Applicant:	TOKUYAMA CORPORATION (Yamaguchi, JP)
Family ID:	75158378
Assignee:	TOKUYAMA CORPORATION (Yamaguchi, JP)
Appl. No.:	17/771532
Filed (or PCT Filed):	September 04, 2020
PCT No.:	PCT/JP2020/033526
PCT Pub. No.:	WO2021/095329
PCT Pub. Date:	May 20, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220371886 A1	Nov. 24, 2022

Foreign Application Priority Data

JP	2019-205560	Nov. 13, 2019
----	-------------	---------------

Publication Classification

Int. Cl.: C01B7/07 (20060101); B01D53/26 (20060101); C01B33/107 (20060101)

U.S. Cl.:

CPC C01B7/0706 (20130101); B01D53/26 (20130101); C01B33/10763 (20130101); B01D2257/30 (20130101)

Field of Classification Search

CPC: C01B (7/0706); C01B (33/10763); C01B (33/10757); C01B (7/07); C01B (33/107); C01B (7/01); C01B (7/0718); C01B (17/90); C01B (7/0731); B01D (53/26); B01D (2257/30); B01D (2251/506); B01D (2252/10); B01D (2256/26); B01D (53/263); B01D (53/28); B01D (2257/80); B01D (2257/2045); B01D (53/261); B01D (2251/60); B01D (53/1493); B01D (2257/2025); B01D (53/78); B01D (2257/2064); C01P (2006/80)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4003723	12/1976	Schafer	423/240R	C01B 7/01
4227890	12/1979	Wood et al.	N/A	N/A
5378411	12/1994	Iwaki et al.	N/A	N/A
9533279	12/2016	Tachino	N/A	B01J 19/0053
2004/0059172	12/2003	Smith, Jr.	585/712	C07C 7/04
2008/0029404	12/2007	Weber et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
202265420	12/2011	CN	N/A
202265420	12/2011	CN	N/A
102530873	12/2011	CN	N/A
106955567	12/2016	CN	N/A
03-177301	12/1990	JP	N/A
6-24730	12/1993	JP	N/A
6-171907	12/1993	JP	N/A
2003-1048	12/2002	JP	N/A
2003-181235	12/2002	JP	N/A
2006-502282	12/2005	JP	N/A
2007-269679	12/2006	JP	N/A
2009-537430	12/2008	JP	N/A
2011-168443	12/2010	JP	N/A
2012-46363	12/2011	JP	N/A
1995-0011825	12/1994	KR	N/A

OTHER PUBLICATIONS

Machine translation of CN202265420U (Year: 2012). cited by examiner
Office Action for CN 202080071806.3. Aug. 30, 2023. 16 pages. cited by applicant

International Preliminary Report on Patentability for PCT/JP2020/033526, mailed Nov. 2, 2020, 5 pages. cited by applicant
International Search Report for PCT/JP2020/033526 and its English translation, mailed Nov. 2, 2020, 6 pages. cited by applicant
Office Action for KR Patent Application No. 10-2022-7012121, dated Jul. 3, 2025, 6 English pages. cited by applicant

Primary Examiner: Merkling; Sally A

Assistant Examiner: Laclair; Logan Edward

Attorney, Agent or Firm: Casimir Jones, S.C.

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to a method for dehydrating hydrogen chloride gas.

BACKGROUND ART

(2) Conventionally, an adsorption method, a cooling condensation method, a concentrated sulfuric acid method, and the like have been used as a method for removing water from hydrogen chloride gas. In the concentrated sulfuric acid method, among these methods, a concentration of concentrated sulfuric acid used for dehydration and a water concentration of hydrogen chloride after the dehydration are in a trade-off relationship. That is, in a case where hydrogen chloride gas having a high water concentration is treated or in a case where a large amount of hydrogen chloride gas having a high water concentration is treated, the concentration of water contained in the obtained hydrogen chloride gas increases with decrease in concentration of concentrated sulfuric acid. Thus, for example, Patent Literature 1 describes a method in which water in hydrogen chloride gas is condensed by a cooling condensation method, and then the hydrogen chloride gas having a decreased water concentration is further dehydrated by using a concentrated sulfuric acid drying column.

CITATION LIST

Patent Literature

(3) [Patent Literature 1]

(4) Chinese Utility Model Publication No. 202265420 (Registered on Jun. 6, 2012)

SUMMARY OF INVENTION

Technical Problem

(5) In a case where dehydration is carried out by a concentrated sulfuric acid method, a large amount of high-concentration concentrated sulfuric acid is often used to increase the certainty of dehydration of the obtained hydrogen chloride gas. Thus, improvement in efficiency in utilizing concentrated sulfuric acid is a very important problem from a cost and treatment efficiency point of view. Unfortunately, Patent Literature 1 does not disclose any configuration for increasing the efficiency in utilizing concentrated sulfuric acid.

(6) An object of an aspect of the present invention is to increase the efficiency in utilizing concentrated sulfuric acid in the entire dehydration process.

Solution to Problem

(7) In order to solve the above problem, a dehydration method in accordance with an aspect of the present invention is a hydrogen chloride gas dehydration method of dehydrating hydrogen chloride gas through a multi-step process, the method including: a first dehydration step of bringing

hydrogen chloride gas and concentrated sulfuric acid into contact with each other; and a second dehydration step of bringing hydrogen chloride gas that has been obtained through the first dehydration step into contact with concentrated sulfuric acid, wherein a concentration of the concentrated sulfuric acid used in the second dehydration step is higher than a concentration of the concentrated sulfuric acid used in the first dehydration step.

Advantageous Effects of Invention

(8) According to an aspect of the present invention, it is possible to increase the efficiency in utilizing concentrated sulfuric acid in the entire dehydration process.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a schematic diagram of a dehydration apparatus in accordance with Embodiment 1.
- (2) FIG. 2 is a schematic diagram of a dehydration apparatus in accordance with Embodiment 2.
- (3) FIG. 3 is a graph showing a relationship between a sulfuric acid concentration in a most downstream drying column and an outlet water concentration of hydrogen chloride gas in the most downstream drying column.
- (4) FIG. 4 is a schematic diagram of a device used for derivation of a relational expression of a water removal rate of hydrogen chloride gas, a concentrated sulfuric acid concentration, and a gas supply amount.

DESCRIPTION OF EMBODIMENTS

Embodiment 1

(5) (Hydrogen Chloride Gas Dehydration Apparatus)

(6) The following description will discuss an embodiment of the present invention in detail. First, an exemplary dehydration apparatus **100** used in a hydrogen chloride gas dehydration method in accordance with an embodiment of the present invention will be described with reference to FIG. 1.

(7) FIG. 1 is a schematic diagram illustrating the structure of the dehydration apparatus **100**. The dehydration apparatus **100** is an apparatus that removes water in hydrogen chloride gas through a multi-process step, that is, an apparatus that dehydrates hydrogen chloride gas. More specifically, the dehydration apparatus **100** is an apparatus that dehydrates hydrogen chloride gas by bringing hydrogen chloride gas into contact with concentrated sulfuric acid in a plurality of drying columns to take advantage of the dehydrating action of the concentrated sulfuric acid.

(8) The dehydration apparatus **100** includes a first drying column **1A** and a second drying column **1B**. The first drying column **1A** is a column for performing a first dehydration step of bringing pre-dehydration hydrogen chloride gas **21** and first concentrated sulfuric acid **13A**, which is concentrated sulfuric acid for the first dehydration step, into contact with each other. The second drying column **1B** is a column for performing a second dehydration step of bringing hydrogen chloride gas **21A**, which is obtained through the first dehydration step, into contact with second concentrated sulfuric acid **13B**, which is concentrated sulfuric acid for the second dehydration step. The hydrogen chloride gas **21A** that has been obtained through the first dehydration step is supplied from the first drying column **1A** to the second drying column **1B** through a pipe **41**. In contrast to the embodiment discussed later, in the dehydration apparatus **100**, the concentrated sulfuric acid that has been used in the second drying column **1B** is not reused in the first drying column **1A**.

(9) The first drying column **1A** includes a concentrated sulfuric acid supply tank **31A** for supplying concentrated sulfuric acid **11**, a pump **2A**, and a concentrated sulfuric acid collection tank **32A** for collecting concentrated sulfuric acid **14A** that has been used in the first dehydration step. Collected concentrated sulfuric acid is stored as collected concentrated sulfuric acid **12** in the concentrated sulfuric acid collection tank **32A**. To reuse the concentrated sulfuric acid in the first drying column **1A**, the pump **2A** delivers at least part of the concentrated sulfuric acid in the first drying column

1A from a discharge port (not illustrated) at a bottom part of the first drying column **1A** to a concentrated sulfuric acid supply port **6A** formed at an upper part of the first drying column **1A**.

(10) Similarly, the second drying column **1B** includes a concentrated sulfuric acid supply tank **31B**, a pump **2B**, and a concentrated sulfuric acid collection tank **32B** for collecting concentrated sulfuric acid **14B** that has been used in the second dehydration step. Collected concentrated sulfuric acid is stored as the collected concentrated sulfuric acid **12** in the concentrated sulfuric acid collection tank **32B**. The pump **2B** delivers the concentrated sulfuric acid to the inside of the second drying column **1B** via a concentrated sulfuric acid supply port **6B** of the second drying column **1B**.

(11) Provided in the middle of the first drying column **1A** is a packed bed **3A** that is packed with a packing material made of a resin. Provision of the packed bed **3A** increases an area of contact between the pre-dehydration hydrogen chloride gas **21** and the first concentrated sulfuric acid **13A**, and thus leads to efficient dehydration of the pre-dehydration hydrogen chloride gas **21**.

(12) Further, provided in the bottom part of the first drying column **1A** is a storage section **4A** for storing the concentrated sulfuric acid **14A** that has been used in the first dehydration step. Provided at a position of a predetermined height (vertically above the storage section **4A**) above the bottom of the first drying column **1A** is an overflow pipe **8A** for overflowing and discharging the concentrated sulfuric acid **14A** stored in the storage section **4A**. The overflow pipe **8A** is connected to the concentrated sulfuric acid collection tank **32A** such that a liquid can pass between the overflow pipe **8A** and the concentrated sulfuric acid collection tank **32A**.

(13) A hydrogen chloride gas supply port **5A** is provided so as to be continuous with a space under the packed bed **3A**, in order to supply the pre-dehydration hydrogen chloride gas **21**. The concentrated sulfuric acid supply port **6A** is provided so as to be continuous with a space above the packed bed **3A**, in order to supply the first concentrated sulfuric acid **13A**. The concentrated sulfuric acid supply port **6A** is connected to a spraying section **7A** such that a liquid can pass between the concentrated sulfuric acid supply port **6A** and the spraying section **7A**.

(14) The spraying section **7A** is a member for spraying a concentrated sulfuric acid liquid onto the packing material in the packed bed **3A**.

(15) The first drying column **1A** further includes a control device **60A** and a monitoring device **61A** for monitoring the concentration of the concentrated sulfuric acid **14A** that has been used in the first dehydration step. Upon receiving information on the concentration of the concentrated sulfuric acid **14A** from the monitoring device **61A**, the control device **60A** controls a supply amount of the concentrated sulfuric acid **11** to be supplied from the concentrated sulfuric acid supply tank **31A** in accordance with the concentration of the concentrated sulfuric acid **14A**.

(16) Similarly, the second drying column **1B** is provided with a packed bed **3B**, a storage section **4B**, a hydrogen chloride gas supply port **5B**, a concentrated sulfuric acid supply port **6B**, a spraying section **7B**, and an overflow pipe **8B**. A monitoring device **61B** and a control device **60B** also serve in the same manner.

(17) In controlling the supply amount of the concentrated sulfuric acid **11**, the control device **60A** and the control device **60B** each control the supply amount of the concentrated sulfuric acid **11** such that the concentration of the second concentrated sulfuric acid **13B** used in the second dehydration step is higher than the concentration of the first concentrated sulfuric acid **13A** used in the first dehydration step. The control of the supply amount is realized, for example, by the control device **60A** controlling a control valve **62A** and by the control device **60B** controlling a control valve **62B**. The control device **60A** and the control device **60B** are communicably connected to each other, so that such control of the supply amount of the concentrated sulfuric acid **11** can be performed.

(18) In FIG. **1**, ST means steam. LT and AT mean a level transmitter and an analyzer transmitter, respectively.

(19) (Flow of Hydrogen Chloride Gas)

(20) The pre-dehydration hydrogen chloride gas **21** is supplied to the inside of the first drying column **1A** through the hydrogen chloride gas supply port **5A**. Then, in the packed bed **3A**, the pre-dehydration hydrogen chloride gas **21** comes into contact with the first concentrated sulfuric acid **13A** and is dehydrated (first dehydration step). The hydrogen chloride gas **21A** that has been obtained through the first dehydration step is discharged from the top of the first drying column **1A**, and is supplied to the inside of the second drying column **1B** through the hydrogen chloride gas supply port **5B** of the second drying column **1B**. Then, in the packed bed **3B**, the hydrogen chloride gas **21A** comes into contact with the second concentrated sulfuric acid **13B** and is dehydrated (second dehydration step). Hydrogen chloride gas **21B** that has been obtained through the second dehydration step is discharged from the top of the second drying column **1B**.

(21) (Flow of Concentrated Sulfuric Acid)

(22) The concentrated sulfuric acid **11** stored in the concentrated sulfuric acid supply tank **31A** is usually concentrated sulfuric acid with a concentration of approximately 98 wt %. The concentrated sulfuric acid supply tank **31A** is connected to the first drying column **1A** via the control valve **62A**. The concentrated sulfuric acid **11** is supplied, as part of the first concentrated sulfuric acid **13A**, from the concentrated sulfuric acid supply tank **31A** to the first drying column **1A** via the concentrated sulfuric acid supply port **6A** of the first drying column **1A**. The supply amount of the concentrated sulfuric acid **11** to be supplied from the concentrated sulfuric acid supply tank **31A** is controlled by the control device **60A** as described above.

(23) The first concentrated sulfuric acid **13A** is sprayed toward the packed bed **3A** via the spraying section **7A**. The concentrated sulfuric acid **14A** that has been brought into contact with the pre-dehydration hydrogen chloride gas **21** in the packed bed **3A** (the concentrated sulfuric acid **14A** that has been used in the first dehydration step) is stored in the storage section **4A** for storing the concentrated sulfuric acid **14A**.

(24) At least part of the concentrated sulfuric acid **14A** stored in the storage section **4A** is delivered by the pump **2A** from the bottom part of the first drying column **1A** to the concentrated sulfuric acid supply port **6A** of the first drying column **1A**. The concentrated sulfuric acid **14A** is supplied, as at least part of the first concentrated sulfuric acid **13A** (in some cases, together with the concentrated sulfuric acid **11**), to the first drying column **1A**.

(25) The flow of the concentrated sulfuric acid is the same for the second drying column **1B**. The second concentrated sulfuric acid **13B** supplied through the concentrated sulfuric acid supply port **6B** is sprayed toward the packed bed **3B** via the spraying section **7B**. In the packed bed **3B**, the concentrated sulfuric acid **14B** that has been brought into contact with the hydrogen chloride gas **21A** obtained through the first dehydration step (the concentrated sulfuric acid **14B** that has been used in the second dehydration step) is stored in the storage section **4B**.

(26) At least part of the concentrated sulfuric acid **14B** stored in the storage section **4B** is delivered by the pump **2B** from the bottom part of the second drying column **1B** to the concentrated sulfuric acid supply port **6B**. The concentrated sulfuric acid **14B** is supplied, as at least part of the second concentrated sulfuric acid **13B** (in some cases, together with the concentrated sulfuric acid **11**), to the second drying column **1B**. The supply amount of the concentrated sulfuric acid **11** to be supplied from the concentrated sulfuric acid supply tank **31B** is controlled by the control device **60B** as described above.

(27) In Embodiment 1, the second concentrated sulfuric acid **13B** (concentrated sulfuric acid used in the second dehydration step) has a higher concentration than the first concentrated sulfuric acid **13A** (concentrated sulfuric acid used in the first dehydration step). As the second concentrated sulfuric acid **13B**, for example, concentrated sulfuric acid with a concentration of not lower than 96 wt % is used. As the first concentrated sulfuric acid **13A**, concentrated sulfuric acid with a concentration of not lower than 80 wt % and lower than 95 wt %, preferably not lower than 85 wt % and lower than 90 wt %, is used.

(28) Since the concentration of the first concentrated sulfuric acid **13A** is sufficiently lower than 98

wt %, the concentrated sulfuric acid **11** in the concentrated sulfuric acid supply tank **31A** does not have to be concentrated sulfuric acid with a concentration of 98 wt %.

(29) Further, as described above, there is a difference in concentration between the concentrated sulfuric acid used in the first dehydration step and the concentrated sulfuric acid used in the second dehydration step. Thus, as the first concentrated sulfuric acid **13A**, the concentrated sulfuric acid **14B** collected after having been used in the second dehydration step can also be used.

(30) Although the above description has discussed the case where there are two drying columns with reference to FIG. **1**, the number of drying columns is not limited to two and may be three or more.

(31) Further, the above description has discussed the embodiment in which the first dehydration step is performed in the first drying column **1A**, and the second dehydration step is performed in the second drying column **1B**. However, there may be an embodiment in which a plurality of dehydration steps including the first dehydration step and the second dehydration step are performed in one drying column.

Effect of Embodiment 1

(32) As described above, the dehydration method of Embodiment 1 is a hydrogen chloride gas dehydration method of dehydrating hydrogen chloride gas through a multi-step process, and is performed using the dehydration apparatus **100**. Further, the dehydration method of Embodiment 1 includes: a first dehydration step of bringing hydrogen chloride gas (pre-dehydration hydrogen chloride gas **21**) and concentrated sulfuric acid (first concentrated sulfuric acid **13A**) into contact with each other; and a second dehydration step of bringing hydrogen chloride gas (hydrogen chloride gas **21A**) that has been obtained through the first dehydration step into contact with concentrated sulfuric acid (second concentrated sulfuric acid **13B**). The concentration of the concentrated sulfuric acid (second concentrated sulfuric acid **13B**) used in the second dehydration step is higher than the concentration of the concentrated sulfuric acid (first concentrated sulfuric acid **13A**) used in the first dehydration step.

(33) According to this dehydration method, after dehydration of hydrogen chloride gas has been carried out in the first dehydration step, dehydration in the second dehydration step is carried out with use of concentrated sulfuric acid that has a concentration higher than that of concentrated sulfuric acid used in the first dehydration step. Even though a low concentration of concentrated sulfuric acid is used in the first dehydration step, a relatively high dehydration effect is obtained. Therefore, by efficiently utilizing a low concentration of concentrated sulfuric acid in the upstream first dehydration step, it is possible to increase the efficiency in utilizing concentrated sulfuric acid in the entire dehydration process of a plurality of steps.

Embodiment 2

(34) (Hydrogen Chloride Gas Dehydration Apparatus)

(35) The following description will discuss another embodiment of the present invention. Note that, for convenience, members having functions identical to those of the respective members of the foregoing embodiment are given respective identical reference numerals, and a description of those members is not repeated.

(36) FIG. **2** is a schematic diagram illustrating the structure of a dehydration apparatus **101**. The dehydration apparatus **101** is an example of an apparatus used in a hydrogen chloride gas dehydration method in accordance with Embodiment 2 of the present invention. The dehydration apparatus **101** includes a first drying column **1A**, a second drying column **1B**, a third drying column **1C**, and a mist separator **50**. The third drying column **1C** is a column for performing a third dehydration step of bringing hydrogen chloride gas **21B**, which is obtained through the second dehydration step, and third concentrated sulfuric acid **13C**, which is concentrated sulfuric acid for the third dehydration step, into contact with each other. The third drying column **1C** includes a pump **2C** for delivering the concentrated sulfuric acid to the inside of the third drying column **1C** via a concentrated sulfuric acid supply port **6C** of the third drying column **1C**. The concentrated

sulfuric acid supply tank **31** is connected via a control valve **62** to the third drying column **1C** such that a liquid can pass between the concentrated sulfuric acid supply tank **31** and the third drying column **1C**. The concentrated sulfuric acid collection tank **32** is connected to the overflow pipe **8A** of the first drying column **1A** such that a liquid can pass between the concentrated sulfuric acid collection tank **32** and the overflow pipe **8A**.

(37) The mist separator **50** is provided with a glass filter **51** for capturing sulfuric acid mist, and is a device for removing sulfuric acid mist from hydrogen chloride gas **22** that has been obtained through a multi-step process.

(38) In the first drying column **1A**, a packed bed **3A**, a storage section **4A**, a hydrogen chloride gas supply port **5A**, a concentrated sulfuric acid supply port **6A**, a spraying section **7A**, and an overflow pipe **8A** are the same as those in Embodiment 1.

(39) Similarly, the second drying column **1B** is provided with a packed bed **3B**, a storage section **4B**, a hydrogen chloride gas supply port **5B**, a concentrated sulfuric acid supply port **6B**, a spraying section **7B**, and an overflow pipe **8B**. Similarly, the third drying column **1C** is provided with a packed bed **3C**, a storage section **4C**, a hydrogen chloride gas supply port **5C**, a concentrated sulfuric acid supply port **6C**, a spraying section **7C**, and an overflow pipe **8C**.

(40) (Flow of Hydrogen Chloride Gas)

(41) Pre-dehydration hydrogen chloride gas **21** is supplied to the inside of the first drying column **1A** through the hydrogen chloride gas supply port **5A**. Then, in the packed bed **3A**, the pre-dehydration hydrogen chloride gas **21** comes into contact with the first concentrated sulfuric acid **13A** and is dehydrated (first dehydration step). Hydrogen chloride gas **21A** that has been obtained through the first dehydration step is discharged from the top of the first drying column **1A**, passes through a pipe **41**, and is supplied to the inside of the second drying column **1B** through the hydrogen chloride gas supply port **5B** of the second drying column **1B**. Then, in the packed bed **3B**, the hydrogen chloride gas **21A** comes into contact with the second concentrated sulfuric acid **13B** and is dehydrated (second dehydration step). Hydrogen chloride gas **21B** that has been obtained through the second dehydration step, is discharged from the top of the second drying column **1B**, passes through a pipe **42**, and is supplied to the inside of the third drying column **1C** through the hydrogen chloride gas supply port **5C** of the third drying column **1C**. Then, in the packed layer **3C**, the hydrogen chloride gas **21B** comes into contact with the third concentrated sulfuric acid **13C**, which is the concentrated sulfuric acid for the third dehydration step, and is dehydrated (third dehydration step). Hydrogen chloride gas **21C** that has been obtained through the third dehydration step is discharged from the top of the third drying column **1C**, passes through a pipe **43**, and is supplied to the mist separator **50**.

(42) By passage of the hydrogen chloride gas **22** supplied to the mist separator **50** after all of the dehydration steps through the glass filter **51** in the mist separator **50**, the sulfuric acid mist contained in the hydrogen chloride gas **22** is captured. The hydrogen chloride gas having passed through the glass filter **51** is discharged, as treated hydrogen chloride gas **23**, from the mist separator **50**, and is supplied to a storage tank or the like (not illustrated).

(43) Concentrated sulfuric acid **11M** collected by the mist separator **50** can be reused as, for example, concentrated sulfuric acid which is to be used for dehydration in the drying column.

(44) (Flow of Concentrated Sulfuric Acid)

(45) The concentrated sulfuric acid **11** stored in the concentrated sulfuric acid supply tank **31** is usually concentrated sulfuric acid with a concentration of approximately 98 wt %. The concentrated sulfuric acid **11** is supplied, as at least part of the third concentrated sulfuric acid **13C**, from the concentrated sulfuric acid supply tank **31** to the third drying column **1C** via the concentrated sulfuric acid supply port **6C** of the third drying column **1C**. The third concentrated sulfuric acid **13C** is sprayed toward the packed bed **3C** via the spraying section **7C**. Concentrated sulfuric acid **14C** that has been brought into contact with the hydrogen chloride gas **21C** in the packed bed **3C** (that has been used in the third dehydration step) is stored in the storage section **4C**.

The supply amount of the concentrated sulfuric acid **11** to be supplied from the concentrated sulfuric acid supply tank **31A** is controlled by the control device **60**. Details of a concentration control method performed by the control device **60** will be described later.

(46) At least part of the concentrated sulfuric acid **14C** that has been used in the third dehydration step and stored in the storage section **4C** is delivered by the pump **2C** from the bottom part of the third drying column **1C** to the concentrated sulfuric acid supply port **6C** of the third drying column **1C**. The concentrated sulfuric acid **14C** is supplied as at least part of the third concentrated sulfuric acid **13C** (in some cases, together with the concentrated sulfuric acid **11**) to the third drying column **1C**.

(47) In a case where the amount of the concentrated sulfuric acid **14C** stored in the storage section **4C** exceeds a predetermined amount, an excess amount of the concentrated sulfuric acid **14C** exceeding the predetermined amount is discharged from the third drying column **1C** via the overflow pipe **8C**, passes through a pipe **44**, and is supplied to the inside of the storage section **4B** of the second drying column **1B**. That is, at least part of the concentrated sulfuric acid **14C** that has been used in the third dehydration step is reused as the second concentrated sulfuric acid **13B** in the second dehydration step.

(48) At least part of concentrated sulfuric acid **15B** stored in the storage section **4B** of the second drying column is delivered by the pump **2B** from the bottom part of the second drying column **1B** to the concentrated sulfuric acid supply port **6B** of the second drying column **1B**. The concentrated sulfuric acid **15B** is supplied, as the second concentrated sulfuric acid **13B**, to the second drying column **1B**. The second concentrated sulfuric acid **13B** is sprayed toward the packed bed **3B** via the spraying section **7B**. Concentrated sulfuric acid **14B** that has been brought into contact with the hydrogen chloride gas **21A** in the packed bed **3B** (that has been used in the second dehydration step) is stored in the storage section **4B**.

(49) In a case where the amount of the concentrated sulfuric acid **15B** stored in the storage section **4B** exceeds a predetermined amount, an excess amount of the concentrated sulfuric acid **15B** exceeding the predetermined amount is discharged from the second drying column **1B** via the overflow pipe **8B**, passes through a pipe **45**, and is supplied to the inside of the storage section **4A** of the first drying column **1A**. That is, at least part of the concentrated sulfuric acid **14B** that has been used in the second dehydration step is reused as the first concentrated sulfuric acid **13A** in the first dehydration step.

(50) At least part of concentrated sulfuric acid **15A** stored in the storage section **4A** of the first drying column **1A** is delivered by the pump **2A** from the bottom part of the first drying column **1A** to the concentrated sulfuric acid supply port **6A** of the first drying column **1A**. The concentrated sulfuric acid **15A** is supplied, as the first concentrated sulfuric acid **13A**, to the first drying column **1A**. The first concentrated sulfuric acid **13A** is sprayed toward the packed bed **3A** via the spraying section **7A**. Concentrated sulfuric acid **14A** that has been brought into contact with the pre-dehydration hydrogen chloride gas **21** in the packed bed **3A** (that has been used in the first dehydration step) is stored in the storage section **4A**.

(51) In a case where the amount of the concentrated sulfuric acid (concentrated sulfuric acid **15A**) stored in the storage section **4A** exceeds a predetermined amount, an excess amount of the concentrated sulfuric acid **15A** exceeding the predetermined amount is discharged from the first drying column **1A** via the overflow pipe **8A** and is collected in the concentrated sulfuric acid collection tank **32**. The collected concentrated sulfuric acid is stored, as the collected concentrated sulfuric acid **12**, in the concentrated sulfuric acid collection tank **32**.

(52) As described above, by reusing, in the upstream dehydration step, the concentrated sulfuric acid that has been used in the downstream dehydration step, it is possible to increase the efficiency in utilizing the concentrated sulfuric acid in the entire multi-step dehydration process and further reduce the amount of concentrated sulfuric acid discarded.

(53) In Embodiment 2, the concentration of the concentrated sulfuric acid used in a most

downstream dehydration step (third dehydration step) is the highest concentration, as compared with the concentrations of the concentrated sulfuric acids used in the other dehydration steps. With this configuration, it is possible to increase the certainty of dehydration of the hydrogen chloride gas in the most downstream dehydration step.

(54) In the method in accordance with Embodiment 2 in which hydrogen chloride gas is dehydrated through a multi-step process, the multi-step process consists of the first dehydration step, the second dehydration step carried out after the first dehydration step, and the third dehydration step carried out after the second dehydration step. The concentration of the concentrated sulfuric acid (concentration of the concentrated sulfuric acid **14C**) reused in the second dehydration step after having been used in the third dehydration step is not lower than 96 wt %. Further, the concentration of the concentrated sulfuric acid (concentration of the concentrated sulfuric acid **15B**) reused in the first dehydration step after having been used in the second dehydration step is not lower than 85 wt % and lower than 96 wt %. Further, the concentration of the concentrated sulfuric acid (concentration of the concentrated sulfuric acid **15A**) after having been used in the first dehydration step is not lower than 75 wt % and lower than 85 wt %.

(55) In Embodiment 2, the case where there are three drying columns has been discussed. However, the number of drying columns is not limited to three and only needs to be two or more. In a case where there are two drying columns, the multi-step process consists of the first dehydration step and the second dehydration step. The concentration of the concentrated sulfuric acid (concentration of the concentrated sulfuric acid **15B**) reused in the first dehydration step after having been used in the second dehydration step is not lower than 96 wt %. Further, the concentration of the concentrated sulfuric acid (concentration of the concentrated sulfuric acid **15A**) after having been used in the first dehydration step is not lower than 85 wt % and lower than 90 wt %.

Effect of Embodiment 2

(56) FIG. 3 is a graph showing a relationship between a sulfuric acid concentration in the most downstream drying column and an outlet water concentration of hydrogen chloride gas in the most downstream drying column when hydrogen chloride gas having a water concentration of 200 ppm-mol is supplied at 5000 Nm.sup.3/hr. Here, the sulfuric acid concentration in the most downstream drying column is a concentrated sulfuric acid concentration (wt %) in the storage section of the most downstream drying column. The outlet water concentration of the hydrogen chloride gas is a water concentration (ppm-mol) of the hydrogen chloride gas **22** that has obtained through the multi-step process.

(57) In FIG. 3, a line A shows a case where there is one drying column (the first dehydration step alone). A line B shows a case where a double column operation (the multi-step process consists of the first dehydration step and the second dehydration step) is carried out by the method in Embodiment 2. A line C shows a case where a triple column operation (the multi-step process consists of the first dehydration step, the second dehydration step, and the third dehydration step) is carried out by the method in Embodiment 2.

(58) The results indicated by the lines A to C in FIG. 3 are respective calculated values. Details of a method for calculating the calculated values will be described later.

(59) In FIG. 3, for example, in a case where the outlet water concentration is 15 ppm-mol, the sulfuric acid concentration in the drying column is approximately 97 wt % in a single column operation. In contrast, it can be seen that in the case of the double column operation, the sulfuric acid concentration in the drying column is approximately 94 wt %, and in the case of the triple column operation, the sulfuric acid concentration in the drying column is approximately 92.5 wt %. This means that the concentrated sulfuric acid is more efficiently utilized by the dehydration with use of a plurality of drying columns (dehydration carried out by the method in Embodiment 2).

(60) Thus, in a case where the water concentration of hydrogen chloride gas is reduced to a specific water concentration, the dehydration with use of a plurality of columns (by the multi-step process)

makes it possible to more efficiently utilize concentrated sulfuric acid and reduce the amount of concentrated sulfuric acid used. This effect is more remarkable in the case of the triple column operation than in the case of the double column operation.

(61) (Relational Expression of Water Removal Rate of Hydrogen Chloride Gas, Concentrated Sulfuric Acid Concentration, and Gas Supply Amount)

(62) Here, derivation of a relational expression of a water removal rate of hydrogen chloride gas, a concentrated sulfuric acid concentration, and a gas supply amount will be described with reference to FIG. 4. FIG. 4 is a schematic diagram of a device used for derivation of the relational expression. Generally, in a case where the flow rate of concentrated sulfuric acid circulated through the drying column was constant, it was empirically clear that the water removal rate of hydrogen chloride gas is expressed as a function of the concentrated sulfuric acid concentration in the drying column and the supply amount of hydrogen chloride gas.

(63) Thus, the inventors measured, with use of a drying column 1 illustrated in FIG. 4, a water removal rate K in a case where hydrogen chloride gas in a predetermined supply amount F was supplied to the drying column 1 through which concentrated sulfuric acid having a predetermined sulfuric acid concentration C was circulated. Here, the sulfuric acid concentration C is a concentration (wt %) of the concentrated sulfuric acid circulating through the drying column 1. The hydrogen chloride gas supply amount F is a supply amount (Nm.sup.3/hr) of the hydrogen chloride gas supplied to the drying column 1. The water removal rate K is represented by the following expression (1):

$$K=(\alpha-\beta)/\alpha \quad (1)$$

(64) In the expression (1), α and β mean the following numerical values: α =(water concentration (C.sub.HCl-in) of hydrogen chloride gas supplied to the drying column 1) β =(water concentration (C.sub.HCl-out) of hydrogen chloride gas discharged from the drying column 1)

(65) Table 1 shows an example of the values of the water removal rate K when the hydrogen chloride gas supply amount F and the sulfuric acid concentration C were set to respectively predetermined values. Note that the amount of circulating sulfuric acid per unit cross-sectional area of the drying column 1 was 5 m.sup.3/m.sup.2/hr.

(66) TABLE-US-00001 TABLE 1 C (wt %) F (Nm.sup.3/hr) 80 94.5 97.8 1300 0.835 0.918 0.926 2600 0.764 0.889 0.912 3200 0.739 0.877 0.908 3900 0.715 0.864 0.903

(67) From the results in Table 1 above, it was found that the relationship of the water removal rate K, the concentrated sulfuric acid concentration C, and the hydrogen chloride gas supply amount F is expressed by the following expression (2):

$$K=0.024 \times \ln(C) \times \ln(F) \quad (2)$$

(Method for Calculating Hydrogen Chloride Gas Water Concentration and Concentrated Sulfuric Acid Concentration in Each Column)

(68) The hydrogen chloride gas water concentration and the concentrated sulfuric acid concentration in each column of Embodiment 2 can be calculated by using the expression (2) which has been derived as described above. The above relationship of the water removal rate K, the concentrated sulfuric acid concentration C, and the hydrogen chloride gas supply amount F can be similarly applied to each column.

(69) In this case, the sulfuric acid concentration C is a concentration (wt %) of concentrated sulfuric acid in the storage section (4A, 4B, 4C) of each column. The hydrogen chloride gas supply amount F is a supply amount (Nm.sup.3/hr) of hydrogen chloride gas to be supplied to each column. The water removal rate K in each drying column can be calculated by using the above expression (1).

(70) The above expressions (1) and (2) are stored in a storage device 64 that is communicably connected to the control device 60, and the control device 60 performs concentration control of the concentrated sulfuric acid in the dehydration apparatus 101 with use of a measured value (or a target value). A method for controlling the supply amount of concentrated sulfuric acid by the

control device **60** will be described below.

(71) (Control of Supply Amount of Concentrated Sulfuric Acid by Control Device)

(72) A method of controlling the supply amount of concentrated sulfuric acid by the control device **60** in the dehydration apparatus **101** includes a target value determination step and an operation control step.

(73) Target Value Determination Step

(74) The purpose of the control performed by the control device **60** is to achieve a target water concentration of hydrogen chloride gas by maintaining the sulfuric acid concentrations in the first to third drying columns within predetermined ranges through adjustment of the supply amount of concentrated sulfuric acid supplied from the concentrated sulfuric acid supply tank **31**. For that purpose, in the target value determination step, a target value C.sub.A of a concentration (C.sub.3) of the concentrated sulfuric acid **14C** that has been used in the third dehydration step, which target value C.sub.A is needed for adjustment of the supply amount of concentrated sulfuric acid, is determined.

(75) In determining the target value C.sub.A through steps (A2) to (A9) below, an initial value is used at the start of operation. After the start of operation, a measured value is used. In a case where the measured value is changed due to the operation control step described later, the target value C.sub.A is updated by repeating the steps (A1) to (A8) below.

(76) (A1) The control device **60** receives, from a hydrogen chloride gas monitoring device **63** provided in a hydrogen chloride gas supply path **46**, information indicative of a water concentration (C.sub.HCl-in(1)) of the pre-dehydration hydrogen chloride gas **21** to be supplied to the first drying column **1A** and information indicative of the supply amount (F.sub.HCl) of hydrogen chloride gas to be supplied to the first drying column **1A**.

(77) (A2) At the start of operation, the control device **60** receives, from an input device **65**, information indicative of a target concentration (C.sup.1) of waste concentrated sulfuric acid that has been inputted as an initial value to the input device **65** by a user. After the start of operation, the control device **60** receives, from the monitoring device **61A**, information indicative of the concentration (C.sub.1) of the concentrated sulfuric acid **15A** stored in the storage section **4A** of the first drying column **1A**.

(78) (A3) The control device **60** calculates a water concentration (C.sub.HCl-out(1)) of the hydrogen chloride gas **21A** to be discharged from the first drying column **1A**, by using (i) F.sub.HCl, (ii) C.sub.HCl-in(1) having been received in the step A1, (iii) C.sup.1' (or C.sub.1) having been received in the step A2, and (iv) the expressions (1) and (2). Here, C.sub.HCl-out(1) is equal to a water concentration (C.sub.HCl-in(2)) of the hydrogen chloride gas **21A** to be supplied to the second drying column **1B**.

(79) Specifically, the control device **60** performs the following operation:

$$C_{\text{sub.HCl-out}}(1) = C_{\text{sub.HCl-in}}(1) \{1 - 0.024 \times \ln(F_{\text{sub.HCl}})\}$$

(80) (A4) The control device **60** receives, from the input device **65**, information indicative of the concentration (C.sub.feed) of the concentrated sulfuric acid **11** that has been inputted to the input device **65**, as an initial value of information indicative of the concentration (C.sub.3) of the concentrated sulfuric acid **14C** stored in the storage section **4C** of the third drying column **1C**. The concentration (C.sub.feed) is usually 98 wt %.

(81) (A5) The control device **60** receives, from the input device **65**, as an initial value, information indicative of a target water concentration (C.sub.HCl-out(3)') that has been inputted to the input device **65**. After the start of operation, the control device **60** receives, from a hydrogen chloride gas monitoring device **66**, information indicative of the water concentration (C.sub.HCl-out(3)) of the hydrogen chloride gas **21C** obtained through the third dehydration step.

(82) (A6) The control device **60** calculates a water concentration (C.sub.HCl-in(3)) of the hydrogen chloride gas **21B** to be supplied to the third drying column **1C**, by using (i) F.sub.HCl, (ii) C.sub.feed that has been received in the step A4 and C.sub.HCl-out(3)' (or C.sub.HCl-out(3)) that

has been received in the A5 step, and (iii) the expressions (1) and (2). Here, C.sub.HCl-in (3) is equal to a water concentration (C.sub.HCl-out(2)) of the hydrogen chloride gas 21A to be discharged from the second drying column 1B.

(83) Specifically, the control device 60 performs the following operation:

$$C_{\text{sub.HCl-in}}(3) = C_{\text{sub.HCl-out}}(3) / \{1 - 0.024 \times \ln(C_{\text{sub.feed}}) \times \ln(F_{\text{sub.HCl}})\}.$$

(84) (A7) The control device 60 calculates the concentration (C.sub.2) of the concentrated sulfuric acid 15B in the second drying column 1B, by using (i) F.sub.HCl, (ii) C.sub.HCl-out(2) that has been calculated in the step A3, (iii) C.sub.HCl-out(2) that has been calculated in the step A6, and (iv) the expressions (1) and (2).

(85) Specifically, the control device 60 performs the following operation:

$$\ln(C_{\text{sub.2}}) = (C_{\text{sub.HCl-in}}(2) - C_{\text{sub.HCl-out}}(2)) / (C_{\text{sub.HCl-in}}(2) \times 0.024 \times \ln(F_{\text{sub.HCl}})),$$

that is, $C_{\text{sub.2}} = e^{\{(C_{\text{sub.HCl-in}}(2) - C_{\text{sub.HCl-out}}(2)) / (C_{\text{sub.HCl-in}}(2) \times 0.024 \times \ln(F_{\text{sub.HCl}}))\}}.$

(86) (A8) The control device 60 calculates the target value C.sub.A of the concentration of the concentrated sulfuric acid 14C in the third drying column 1C, by using (i) F.sub.HCl, (ii) C.sub.HCl-out(3) received in the step A5, (iii) C.sub.HCl-in(3) calculated in the step A5, and (iii) the expressions (1) and (2).

(87) Specifically, the control device 60 performs the following operation:

$$C_{\text{sub.A}} = e^{\{(C_{\text{sub.HCl-in}}(3) - C_{\text{sub.HCl-out}}(3)) / (C_{\text{sub.HCl-in}}(3) \times 0.024 \times \ln(F_{\text{sub.HCl}}))\}}.$$

(88) (A9) The control device 60 sets, as the target value C.sub.A, C.sub.A that has been calculated in the step A8.

(89) <Operation Control Step>

(90) Following the target value determination step, the operation control step is performed. In the operation control step, steps B1 to B4 below are performed by the control device 60.

(91) (B1) The control device 60 receives, from the monitoring device 61C, information indicative of the concentration (C.sub.3) of the concentrated sulfuric acid 14C that has been used in the third dehydration step.

(92) (B2) The control device 60 compares the information indicative of C.sub.3 that has been obtained in the step B1 with the target value C.sub.A.

(93) (B3) In a case where C.sub.3 is lower than the target value C.sub.A, the control device 60 increases the opening degree of the control valve 62 to increase the supply amount of the concentrated sulfuric acid 11 to be supplied from the concentrated sulfuric acid supply tank 31 to the third drying column 1C.

(94) (B4) In a case where C.sub.3 is higher than the target value C.sub.A, the control device 60 decrease the opening degree of the control valve 62 to decrease the supply amount of the concentrated sulfuric acid 11 to be supplied from the concentrated sulfuric acid supply tank 31 to the third drying column 1C.

(95) (B5) In a case where C.sub.3 is equal to the target value C.sub.A, the control device 60 maintains the opening degree of the control valve 62 and maintains the supply amount of the concentrated sulfuric acid 11 to be supplied from the concentrated sulfuric acid supply tank 31 to the third drying column 1C.

(96) (Operation Example)

(97) The conditions and results of the dehydration treatment performed by the dehydration apparatus 101 of Embodiment 2 under control of the concentration control method as described above are shown in Table 2 below.

(98) TABLE-US-00002 TABLE 2 Conditions Hydrogen chloride gas water concentration (inlet) ppm-mol 2000 Waste sulfuric acid target concentration (C.sub.1') wt % 80 First drying column sulfuric acid concentration wt % 80 Hydrogen chloride gas target water concentration ppm-mol 5 (outlet) Amount of circulating sulfuric acid m.sup.3/m.sup.2/hr 5 Hydrogen chloride gas supply

amount Nm.sup.3/hr 130 320 98 wt % concentrated sulfuric acid supply amount kg/hr 0.9 2.3
 Estimated Measured Estimated Measured values values values values Results First drying column
 sulfuric acid concentration wt % 80 81 80 82 Second drying column sulfuric acid concentration wt
 % 94.5 93.7 93 92 Third drying column sulfuric acid concentration wt % 97.8 97.8 97.4 97.8 First
 drying column outlet water concentration ppm-mol 330 280 520 470 Second drying column outlet
 water concentration ppm-mol 27 30 64 75 Third drying column outlet water concentration ppm-
 mol 5 4 5 2

(99) Table 2 shows that there is close agreement between estimated values calculated with use of the conditions shown in Table 2 and measured values of the sulfuric acid concentrations actually measured under control of the control device **60**. From this, it has been revealed that the above control method suitably controls the sulfuric acid concentration of each column in the dehydration apparatus of Embodiment 2, and achieves the target water concentration at the outlet. More specifically, regarding the control of the sulfuric acid concentrations, the following points were demonstrated: (i) a third drying column sulfuric acid concentration (the concentration of the concentrated sulfuric acid reused in the second dehydration step after having been used in the third dehydration step) is not lower than 96 wt %; (ii) a second drying column sulfuric acid concentration (the concentration of the concentrated sulfuric acid reused in the first dehydration step after having been used in the second dehydration step) falls within a range of not lower than 85 wt % and lower than 96 wt %; and (iii) a first drying column sulfuric acid concentration (the concentration of the concentrated sulfuric acid after having been used in the first dehydration step) falls within a range of not lower than 75 wt % and lower than 85 wt %.

(100) (Application in Trichlorosilane Synthesis)

(101) Hydrogen chloride gas with water content that has been reduced by the dehydration method of Embodiment 1 or 2 can be used for synthesis of trichlorosilane. That is, it is possible to provide a method for producing trichlorosilane by reacting hydrogen chloride gas with water content that has been reduced by the dehydration method of Embodiment 1 or 2 with metallic silicon.

(102) Trichlorosilane synthesis in which hydrogen chloride gas and metallic silicon are contained as raw materials is carried out in a synthesis column. Water contained in the hydrogen chloride gas which is the raw material can cause erosion of a dispersion plate in the synthesis column. Thus, it is preferable that the concentration of water contained in the hydrogen chloride gas for use in the reaction is lower.

(103) By using the hydrogen chloride gas with water content that has been reduced by the dehydration method of Embodiment 1 or 2, it is possible to reduce the erosion in the trichlorosilane synthesis column. This makes it possible to increase a useful life of the dispersion plate.

(104) The present invention is not limited to the embodiments, but can be altered by a skilled person in the art within the scope of the claims. The present invention also encompasses, in its technical scope, any embodiment derived by combining technical means disclosed in differing embodiments.

REFERENCE SIGNS LIST

(105) **1A, 1B, 1C**: first drying column, second drying column, third drying column **2A, 2B, 2C**: pump **3A, 3B, 3C**: packed bed **4A, 4B, 4C**: storage section **5A, 5B, 5C**: hydrogen chloride gas supply port **6A, 6B, 6C**: concentrated sulfuric acid supply port **7A, 7B, 7C**: spraying section **8A, 8B, 8C**: overflow pipe **11, 11M**: concentrated sulfuric acid **14A, 14B, 14C**: concentrated sulfuric acid that has been used in the first dehydration step, concentrated sulfuric acid that has been used in the second dehydration step, and concentrated sulfuric acid that has been used in the third dehydration step **13A, 13B, 13C**: first concentrated sulfuric acid, second concentrated sulfuric acid, and third concentrated sulfuric acid (concentrated sulfuric acid used in the first dehydration step, concentrated sulfuric acid used in the second dehydration step, and concentrated sulfuric acid used in the third dehydration step) **21**: pre-dehydration hydrogen chloride gas **21A, 21B, 21C**: hydrogen chloride gas that has been obtained through the first dehydration step, hydrogen chloride gas that

has been obtained through the second dehydration step, and hydrogen chloride gas that has been obtained through the third dehydration step **31, 31A, 31B**: concentrated sulfuric acid supply tank **32, 32A, 32B**: concentrated sulfuric acid collection tank **50**: mist separator **51**: glass filter **60, 60A, 60B**: control device **61A, 61B, 61C**: monitoring device **62, 62A, 62B**: control valve **63**: hydrogen chloride gas monitoring device **64**: storage device **65**: input device **100, 101**: dehydration apparatus

Claims

1. A method of dehydrating hydrogen chloride gas through a multi-step process, the method comprising: a first dehydration step of bringing hydrogen chloride gas and concentrated sulfuric acid into contact with each other; and a second dehydration step of bringing hydrogen chloride gas that has been obtained through the first dehydration step into contact with concentrated sulfuric acid, wherein a concentration of the concentrated sulfuric acid used in the second dehydration step is higher than a concentration of the concentrated sulfuric acid used in the first dehydration step, wherein at least part of the concentrated sulfuric acid that has been used in the second dehydration step is reused in the first dehydration step, wherein the multi-step process consists of the first dehydration step, the second dehydration step, and a third dehydration step carried out after the second dehydration step, wherein at least part of concentrated sulfuric acid that has been used in the third dehydration step is reused in the second dehydration step, a concentration of the concentrated sulfuric acid reused in the second dehydration step after having been used in the third dehydration step is not lower than 96 wt %, a concentration of the concentrated sulfuric acid reused in the first dehydration step after having been used in the second dehydration step is not lower than 85 wt % and lower than 96 wt %, and a concentration of the concentrated sulfuric acid after having been used in the first dehydration step is not lower than 75 wt % and lower than 85 wt %.
 2. The dehydration method according to claim 1, wherein in the multi-step process, a concentration of concentrated sulfuric acid used in a most downstream dehydration step is a highest concentration, as compared with the concentrations of the concentrated sulfuric acids used in dehydration steps upstream from the most downstream dehydration step.
 3. The dehydration method according to claim 1, further comprising: a step of removing sulfuric acid mist from hydrogen chloride gas that has been obtained through the multi-step process, by using a mist separator provided with a glass filter.
 4. A method for producing trichlorosilane by reacting hydrogen chloride gas with water content that has been reduced by a dehydration method according to claim 1 with metallic silicon.
-