

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405359
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Chaudhari; Pradip Girdhar et al.

Target measurement device and method for measuring a target

Abstract

A target measurement device is provided. The target measurement device includes a fixing ring, a main body, and a transceiver. The fixing ring has a first surface. The main body is over the first surface of the fixing ring. The transceiver is coupled to the main body. The transceiver is at least movable between a center of the fixing ring to an edge of the fixing ring from a top view perspective. A method for measuring a target is also provided.

Inventors: Chaudhari; Pradip Girdhar (Hsinchu, TW), Lee; Che-Hui (Taipei, TW), Wei; Chih-Cheng (Hsinchu, TW), Yang; Wen-Cheng (Hsinchu, TW), Ni; Chyi-Tsong (Hsin-Chu, TW)

Applicant: TAIWAN SEMICONDUCTOR MANUFACTURING COMPANY LTD. (Hsinchu, TW)

Family ID: 75120169

Assignee: TAIWAN SEMICONDUCTOR MANUFACTURING COMPANY LTD. (Hsinchu, TW)

Appl. No.: 18/359868

Filed: July 27, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230375684 A1	Nov. 23, 2023

Related U.S. Application Data

continuation parent-doc US 16906939 20200619 US 11754691 child-doc US 18359868
us-provisional-application US 62907521 20190927

Publication Classification

Int. Cl.: **G01C3/08** (20060101); **G01S7/481** (20060101); **G01S7/497** (20060101); **G01S17/06** (20060101)

U.S. Cl.:

CPC **G01S7/4972** (20130101); **G01S7/4812** (20130101); **G01S17/06** (20130101);

Field of Classification Search

CPC: G01S (7/4972); G01S (7/4812); G01S (17/06); G01B (11/30)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11754691	12/2022	Chaudhari	356/4.01	G01B 11/24

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
H1161403	12/1998	JP	H01L 21/203

Primary Examiner: Hellner; Mark

Attorney, Agent or Firm: WPAT LAW

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION (1) This application is a continuation application claims the benefit of prior-filed U.S. application Ser. No. 16/906,939, filed on Jun. 19, 2020, and prior-filed U.S. provisional application No. 62/907,521, filed on Sep. 27, 2019, which are incorporates its entirety herein.

FIELD

(1) The present disclosure relates to a target measurement device and a method for target measurement, particularly, the disclosed device can measure the erosion of the target used in a Physical Vapor Deposition (PVD) operation.

BACKGROUND

(2) PVD Coating refers to a variety of thin film deposition techniques where a solid material is vaporized in a vacuum environment and deposited on substrates as a pure material or alloy composition coating.

(3) Generally, the two most common PVD Coating processes are sputtering and thermal evaporation. Sputtering involves the bombardment of the coating material known as the target with a high energy electrical charge causing it to sputter off atoms or molecules that are deposited on a substrate like a silicon wafer or solar panel. Different from sputtering, thermal evaporation involves elevating a coating material to the boiling point in a high vacuum environment causing a vapor stream to rise in the vacuum chamber and then condense on the substrate.

(4) Currently, PVD is widely used in the technical field of semiconductor manufacturing. The two

important parts of PVD equipment are magnetron and target due to their impacts to tool availability and film performance. Thus, the accuracy of magnetron and target measurement data would directly influence to the judgement of parts replacement.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Aspects of the present disclosure are best understood from the following detailed description when read with the accompanying figures. It is noted that, in accordance with the standard practice in the industry, various structures are not drawn to scale. In fact, the dimensions of the various structures may be arbitrarily increased or reduced for clarity of discussion.

(2) FIG. 1 illustrates a cross-sectional view of a PVD chamber according to some embodiments of the present disclosure.

(3) FIG. 2 illustrates a stereogram of a target measurement device according to some embodiments of the present disclosure.

(4) FIG. 3A illustrates a stereogram of a fixing ring and a first baseplate according to some embodiments of the present disclosure.

(5) FIG. 3B illustrates a cross-sectional view of a target on a first baseplate according to some embodiments of the present disclosure.

(6) FIG. 3C illustrates a cross-sectional view of a target on a PVD chamber lid according to some embodiments of the present disclosure.

(7) FIG. 4 illustrates a schematic diagram of a main body and a transceiver according to some embodiments of the present disclosure.

(8) FIG. 5 illustrates a top perspective view of a fixing ring according to some embodiments of the present disclosure.

(9) FIG. 6 illustrates a cross-sectional view of a target according to some embodiments of the present disclosure.

(10) FIG. 7 illustrates a flow chart of measuring a target according to some embodiments of the present disclosure.

(11) FIG. 8 illustrates a cross-sectional view of a target and a fixing ring according to some embodiments of the present disclosure.

(12) FIG. 9 illustrates a cross-sectional view of a target and a fixing ring according to some embodiments of the present disclosure.

(13) FIG. 10 illustrates a chart of erosion depth of a target according to some embodiments of the present disclosure.

(14) FIG. 11 illustrates a flow chart of measuring a target according to some embodiments of the present disclosure.

DETAILED DESCRIPTION

(15) The following disclosure provides many different embodiments, or examples, for implementing different features of the provided subject matter. Specific examples of elements and arrangements are described below to simplify the present disclosure. These are, of course, merely examples and are not intended to be limiting. For example, the formation of a first feature over or on a second feature in the description that follows may include embodiments in which the first and second features are formed in direct contact, and may also include embodiments in which additional features may be formed between the first and second features, such that the first and second features may not be in direct contact. In addition, the present disclosure may repeat reference numerals and/or letters in the various examples. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship between the various embodiments and/or configurations discussed.

(16) Further, spatially relative terms, such as “beneath,” “below,” “lower,” “above,” “upper,” “on” and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. The spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. The apparatus may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein may likewise be interpreted accordingly.

(17) As used herein, the terms such as “first,” “second” and “third” describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms may be only used to distinguish one element, component, region, layer or section from another. The terms such as “first,” “second”, and “third” when used herein do not imply a sequence or order unless clearly indicated by the context.

(18) PVD is widely used for thin film deposition of the semiconductor manufacturing. As shown in FIG. 1, generally, a PVD equipment includes a magnetron **91** over a target **90**, and a plasma region **92** is existed between the target **90** and a substrate **93**, wherein the substrate **93** is supported by a pedestal **94**. The magnetron **91** is configured to control the directions of plasma ions in the plasma region **92**, and the target **90** is configured to provide a plurality of sputtered atoms through the collisions between the plasma ions and the target **90**. That is, the plasma ions are accelerated by potentials ranging from a few hundred to a few thousand electron volts and strike the negative electrode with sufficient force to dislodge and eject atoms from the target **90**. With the influence of the magnetron **91**, the target material may not be consumed, or bombarded, uniformly, instead, the target material may be eroded to different extents along the radial direction. The target **90** with uneven surface may impact the uniformity of the thin films deposited on the opposing substrate **93**. For instance, comparing a new target **90** to a target **90** after a 500 hours usage, the non-uniformity of a thin film formed by the target **90** after a 500 hours usage may be increased by one or more percentages, evidencing a deteriorated film thickness uniformity. Moreover, the erosion may reach to a target baseplate (e.g., the pedestal **94**) and thereby removing the baseplate material and inducing wafer scrap event.

(19) Without suitable portable tools to measure the surface profile of the target of PVD process, the evaluation of the consumption of the target would be a time-consuming work. For instance, in some circumstances, the target is removed from the PVD chamber and send to a target vender for erosion measurement. The process may take several weeks to few months and is highly inefficient.

(20) Accordingly, some embodiments of the present disclosure provide a device and a method for target measurement to measure the erosion of the target on-site. The device for target measurement may be mounted with an installed target in a PVD chamber so that the target is not required to be completely detached from a lid of the PVD chamber.

(21) FIG. 2 illustrates a target measurement device according to some embodiments of the present disclosure. The target measurement device includes a fixing ring **10**, a main body **20**, and a transceiver **30**. The fixing ring **10** has a first surface **10A**, the main body **20** is disposed over the first surface **10A** of the fixing ring **10**, and the transceiver **30** is coupled to the main body **20**. In some embodiments, the transceiver **30** is at least movable between a center **101** of the fixing ring **10** to an edge **102** of the fixing ring **10** (i.e., the dotted line in FIG. 2).

(22) The target measurement device of the present disclosure is utilized to measure the erosion of a target of PVD process. Referring to FIG. 2, the target **40** is disposed within the fixing ring **10** during the measurement, and the target surface **40A** with erosion is facing the main body **20** and the transceiver **30**. PVD process is the process which the material from a sputtering target may go from a condensed phase to a vapor phase and then back to a thin film condensed phase. To be more precisely, sputtering is a physical process whereby atoms in a solid target material are ejected into the gas phase due to bombardment of the material by energetic ions. Due to collisions, sputtering is largely driven by momentum exchange between the ions and atoms in the material. The process can

be thought of as atomic billiards, with the ion (i.e., cue ball) striking a large cluster of close-packed atoms (i.e., billiard balls). Although the first collision pushes atoms deeper into the cluster, subsequent collisions between the atoms can result in some of the atoms near the target surface being ejected away from the cluster. The number of atoms ejected from the target surface per incident ion is called the sputter yield and is an important measure of the efficiency of the sputtering process.

(23) The ejection of the atoms from the target surface **40A** may induce the erosion of the target **40**. Accordingly, the target **40** is disposed in the target measurement device, and the transceiver **30** thereover may scan the surface profile of the target **40**. In some embodiments, the erosion of the target **40** is measured outside of the PVD equipment. That is, the target **40** is taken out from a chamber of the PVD equipment prior to the scanning or measuring operation. In such embodiments, the PVD chamber lid is opened firstly, and next, the screws for fixing the target **40** are all removed to separate the target **40** from the PVD chamber.

(24) In some embodiments, the target **40** taken from the PVD chamber may be placed on an erosion setup baseplate under the fixing ring **10** for measurement. As shown in FIG. 3A, a space **10B** is enclosed by the fixing ring **10** for disposing the target. The fixing ring **10** is disposed on first baseplate **200**. The first baseplate **200** includes a flat top surface and a flat bottom surface, and it may be utilized to support the target and the fixing ring **10**. In some embodiments, the first baseplate **200** may include a plurality of through holes **200A** for reducing the weight of the first baseplate **200**, and it is also easier to take the scanned target out of the fixing ring **10** by pushing the target from the through holes **200A**.

(25) As shown in FIG. 3B, the target **40** may include an upper portion **403** for providing target material in PVD process, and a second baseplate **404** integrated with the upper portion **403** may be utilized to be installed on the first baseplate **200** out of the PVD chamber by screws; whereas in some other embodiments, as shown in FIG. 3C, the second baseplate **404** of the target **40** may be installed on an inner surface of a chamber lid **70** of the PVD chamber by screws.

(26) As shown in FIG. 4, in some embodiments, the main body **20** may include a motor **201** coupled to the transceiver **30**, wherein the transceiver **30** may include an optical sensor or a pressure sensor, which will be describe later. The motor **201** may be utilized to move of the transceiver **30** to scan the surface profile of the target. In some embodiments, the main body **20** may further include a controller **202** coupled to the motor **201**. The controller **202** may be a computer or the like, and the controller **202** is utilized to control the movement of the transceiver **30**. For instance, the controller **202** may control the transceiver **30** to move along a radius or a diameter of the target. In some embodiments, the main body **20** may further include a data collection unit **203** coupled to the transceiver **30**. The data collection unit **203** may collect the surface profile data of the target from the transceiver **30** for analysis. In some embodiments, the main body **20** may further include a motor driver **201A** coupled to the motor **201** and a motion controller **201B** coupled to the motor driver **201A** and the controller **202** to control the movement of the transceiver **30** further.

(27) Still referring to FIG. 2, in some embodiments, the main body **20** may include a pair of supporting legs **204** coupled to the fixing ring **10**. The pair of supporting legs **204** may be utilized to support the components described in FIG. 4 such as the motor **201**, the controller **202**, the data collection unit **203**, and the transceiver **30** over the fixing ring **10**. In some embodiments, the main body **20** may include a bracket rail **205** over the pair of supporting legs **204**. The bracket rail **205** may provide a scanning path for the transceiver **30** coupled to the main body **20**. In some embodiments, the bracket rail **205** may traverse the fixing ring **10**, and therefore the transceiver **30** may scan the target **40** from an edge of the fixing ring **10** to another edge thereof. In some embodiments, a measuring arm **206** may be disposed over the bracket rail **205**. The measuring arm **206** may be utilized to support the transceiver **30**, hence the transceiver **30** may be hung over the target **40**. In some embodiments, the measuring arm **206** is configured to slide along the bracket rail

205. In such embodiments, the transceiver **30** hung by the measuring arm **206** may scan the target **40** along a diameter of the target **40** because the bracket rail **205** is parallel to the diameter of the target **40**. In some embodiments, the transceiver **30** may be moved over the target **40** in x-axis and y-axis directions by the coordinate of the bracket rail **205** and the measuring arm **206**. In some embodiments, the main body **20** includes a control unit in-between the measuring arm **206** and the transceiver **30**, which is utilized to control the movement of the transceiver **30** in y-axis direction.

(28) The fixing ring **10** includes a second surface opposite to the first surface **10A**. Referring to FIG. 5, there are a plurality of holes at the first surface **10A** of the fixing ring **10** for different usages. In some embodiments, the plurality of holes penetrate through the fixing ring **10** and thus may be observed at the second surface. In some embodiments, the plurality of holes may have different diameters. In some embodiments, the fixing ring **10** may include a plurality of first mounting holes **104** distributed evenly at the first surface **10A** from a top view perspective. The fixing ring **10** may be screwed on the second baseplate **404** through the plurality of first mounting holes **104**. In some embodiments, the first baseplate **200** in previously shown FIG. 3A may include a plurality of mounting holes aligned with the first mounting holes **104** for installation. In some embodiments, there are 8 first mounting holes **104** at the first surface **10A**, such amount is identical to the screw holds in positioning the target in a common PVD chamber. In some embodiments, the amount of the first mounting holes **104** is identical to the screw holds in positioning the target in the PVD chamber.

(29) In some embodiments, the fixing ring **10** may include a plurality of second mounting holes **105** distributed proximity to a side of the fixing ring **10** from a top perspective. The main body **20** may be screwed on the fixing ring **10** through the plurality of second mounting holes **105**. In some embodiments, there are 4 second mounting holes **105** at the fixing ring **10**. In some embodiments, the pair of supporting legs **204** as shown in FIG. 2 are screwed on the fixing ring **10** through the plurality of second mounting holes **105**. Because the plurality of second mounting holes **105** are distributed proximity to the side of the fixing ring **10**, the transceiver **30** coupled on the main body **20** may scan the target therebelow along a diameter of the target without obstructing by the main body **20**. In other words, the positions of the plurality of second mounting holes **105** are away from the opposite edge of the fixing ring **10** to avoid obstructing the operation of scanning.

(30) In some embodiments, the fixing ring **10** may include a zeroing hole **103** at the first surface **10A**, and the plurality of the first and the second mounting holes **104**, **105** are adjacent to the zeroing hole **103**. The zeroing hole **103** is configured to be a zeroing point for scanning the target. In order to acquire the surface profile of the target, the transceiver **30** should scan the target along a radius or a diameter of the target instead of a secant line, this is because the erosion of the target may be as a circular symmetry. Referring to FIG. 6, in some circumstances, the erosion depth D.sub.E of the target **40** may be symmetric to the center **401** of the target **40**, and therefore the full scanning result may be rendered by a half-scanning data, for example, by scanning the target **40** along the radius of the target **40**, that is, conducting a half scan from a center to an edge of the target **40**. In some other embodiments, the erosion depth D.sub.E of the target **40** may not be symmetry to the center **401** of the target, and the transceiver **30** should scan the target **40** along the diameter of the target **40** to acquire the full scanning result.

(31) FIG. 7 illustrates a flow chart of measuring a target according to some embodiments of the present disclosure. In some embodiments, the measurement includes an operation **501**: receiving instruction to find a center of the target by moving a transceiver from an initial position to a calibration position where vertically aligning with a zeroing hole on a fixing ring surrounding the target along a linear trajectory; an operation **502**: receiving instruction to move the sensor from the calibration position toward an edge of the target; and an operation **503**: receiving instruction to scan the target to acquire an erosion profile by moving the transceiver from the edge to a center of the target or to another edge of the target.

(32) In order to scan the target along the radius or the diameter of the target, as mentioned on the

operation **501**, the center **401** of the target **40** needs to be confirmed prior to the operation of scanning. In some embodiments, the zeroing hole **103** at the fixing ring **10** is already lined up with the center **401** of the target **40**, and therefore the transceiver **30** may find the center **401** of the target **40** along a linear trajectory if priorly registered with the zeroing hole **103**. For example, before the measurement, the transceiver **30** may be located at any position above or near the target **40**, and therefore in some embodiments, the transceiver **30** is moved from its current location to the zeroing hole **103** for center-finding prior to the scanning. In some embodiment, the transceiver **30** may move to the zeroing hole **103** at a first attempt, the transceiver **30** may emit a laser beam toward the first surface **10A** of the fixing ring **10**. Once the laser beam passes through the zeroing hole **103**, the laser beam may be reflected back to the transceiver **30** by the underlying first baseplate **200** and being recognized by the controller according to a predetermine sensing mechanism, for example, the change of optical path or the property of reflected light. Center-finding operation may be confirmed if the transceiver **30** receives such recognizable sensing signal. In such embodiments, the transceiver **30** is ready to move toward the center **401** of the target **40** after the transceiver **30** is aligned and zeroed.

(33) In some other embodiments, the transceiver **30** may fail to hit the zeroing hole **103** at the first attempt. For instance, the transceiver **30** unexpectedly deviates from the zeroing hole **103** due to software error or the controller stop to find the zeroing hole **103** when a default searching time is running out. In such circumstances, it is available to adjust the transceiver **30** along a direction perpendicular to the primary direction of the bracket rail **205**, and then initiates a second attempt for the transceiver **30** to align with the zeroing hole **103**. In some embodiments, the aforesaid adjustment can be done manually or automatically. The laser beam passing through the zeroing hole **103** may be deemed as that the transceiver **30** has been registered with the zeroing hole **103**, therefore, the center-finding operation is completed. Subsequently, the measuring arm **206** is ready to initiate a target scan. In some embodiments, the transceiver **30** may include a pressure sensor and a gas jet (e.g., head air nozzle).

(34) In some embodiments, an optical sensor or a pressure sensor can be devised adjacent to the bottom of the zeroing hole **103** such that the transceiver **30** may function as an emitter (e.g., a laser diode or air nozzle), while the optical sensor or a pressure sensor function as the sensor, during the center-finding operation.

(35) In some embodiments, the transceiver **30** may include a laser beam emitter (e.g., laser diode) and an optical sensor for receiving the laser beam reflected from the target surface **40A**, and the surface profile of the target **40** may be acquired accordingly. In some other embodiments, the transceiver **30** may include a gas jet (e.g., head air nozzle) and a pressure sensor for sensing the pressure of the gas impact on the target surface **40A**, and the surface profile of the target **40** may be acquired accordingly.

(36) In performing the operation **502**, the transceiver **30** is moved from the calibration position (i.e., the zeroing hole **103**), which is in the fixing ring **10** instead of the target, and therefore the transceiver **30** will move toward the edge of the target. As shown in FIG. **8**, in some embodiment, there may be a gap **108** between the target surface **40A** and the first surface **10A** of the fixing ring **10**. In other words, the inner edge of the fixing ring **10** and the edge of the target **40** are discontinuous, and therefore in moving the transceiver **30** toward the edge of the target **40**, the gap **108** adjacent to the edge of the target **40** may be used to distinguish the surface profile of the fixing ring **10** and the target **40**. That is, it will be more easily to figure out the edge of the target **40**.

(37) In some embodiments, the second baseplate **404** may have a trench **404B** near the edge thereof. In some embodiments, the trench **404B** is utilized to place an O-ring **402**. In some embodiments, a portion of the O-ring **402** is protruded from a surface **404C** of the second baseplate **404**. In order to installing the fixing ring **10** around the target **40** without contacting the O-ring **402**, in some embodiments, the area of the first surface **10A** is larger than the second surface **10C** of the fixing ring **10**. That is, a lower portion **106** of the fixing ring **10** may be shrink to sidestep the O-

ring **402** protruded from the surface **404C** of the second baseplate **404**, and the O-ring **402** is vertically covered by an upper portion **107** of the fixing ring **10**. In such embodiments, the O-ring **402** need not to be removed from the trench **404B** for the fixing ring **10** installation, and therefore the time spend in setting up the target measurement device may be shortened.

(38) In some other embodiments, as shown in FIG. **9**, the second baseplate **404** may not include the trench or the O-ring, and the area of the first surface **10A** may be identical to the second surface **10C** of the fixing ring **10**, which means no portion of the fixing ring **10** is shrink to sidestep the structure on the second baseplate **404**.

(39) In performing the operation **503**, the transceiver **30** is moved from the edge to the center of the target **40**, wherein such scanning path is already aligned by the calibration position (i.e., the zeroing hole **103**), and therefore the transceiver **30** is substantially moved along the radius of the target **40**. In some embodiments, the transceiver **30** is moved from the edge to another edge of the target **40**, and therefore the transceiver **30** is substantially moved along the diameter of the target **40**. As aforementioned, the transceiver **30** may include the optical sensor or the pressure sensor, and therefore in some embodiments, the optical sensor may receive the laser beam reflected from the surface **40A** continuously to acquire the surface profile of the target **40**, based on the phase shift of the power modulation of the laser beams that was sent and reflected. In some other embodiments, the pressure sensor may be worked based on the principle of pneumatic measurement, that is, it is based on a pneumatic flow meter that directly reads the drop or increase in pressure corresponding to the variation of the flow rate corresponding to the surface profile of the target. To be more precisely, there may be air passes through the head air nozzle and impact the surface of the target, and the pressure variations between the head nozzle and the surface of the target are recorded by the micro-measurement pressure gauge.

(40) By moving the transceiver over the target, referring to FIG. **10**, the surface profile of the target may be scanned in several minutes, and the erosion of the target may be observed clearly. As shown in FIG. **10**, after the target is used for several hundred hours, in some embodiments, the uniformity of the surface of the target is changed, and the remaining life of the target may thus be evaluated.

(41) In some embodiments, the target may not be taken out from the PVD chamber. Referring to FIG. **11**, in such embodiments, the measurement includes an operation **601**: removing a plurality of screws from the edge of the target; an operation **602**: mounting a target measurement device in a chamber, the target measurement device comprises a transceiver; an operation **603**: enter instruction to move the transceiver from an initial position to a calibration position along an extension line passing a center of the target; and an operation **604**: enter instruction to scan the target to acquire an erosion profile by moving the transceiver from the calibration position to the center of the target.

(42) In such embodiment, the PVD chamber lid is opened and few of the screws are removed from the edge of the target. These screws are used to positioning the target, and the screw holes left by removing the screws may be used to install the fixing ring around the target prior to finding the center of the target. By mounting the target measurement device in the PVD chamber, the purpose of on-site target erosion measurement may be substantially achieved. Moreover, in such embodiments, the center of the target is also found in the operation of moving the transceiver from the initial position (i.e., any position) to the calibration position (i.e., the zeroing hole). In such operation, the transceiver may move along an extension line passing the center of the target, and the calibration position is at an end of the extension line. In some embodiments, the measuring arm may be disposed overlap the diameter of the fixing ring, and the transceiver couple to the measuring arm may be moved along the diameter of the target inside the fixing ring, wherein such path may be identical to the aforementioned extension line.

(43) According to the present disclosure, a target measurement device and a method for measuring a target of PVD process are disclosed. The target measurement device may achieve the goal of auto on-site target erosion measurement, and therefore it may help to save measurement time and

provide accurate data with a high repeatability (about 99%). The target measurement device includes a fixing ring which may mount around the target in the PVD chamber directly, without taking the target out of the chamber or removing the target O-ring. Moreover, the fixing ring include a zeroing hole as a calibration position to ensure the transceiver over the fixing ring may scan the target along a radius or a diameter correctly. By scanning the target along its radius or diameter, not only the surface profile, but the erosion depth of the target may be acquired thereby within a short time. Accordingly, a time-saving and convenient PVD target erosion measurement may be achieved.

(44) In one exemplary aspect, a target measurement device is provided. The target measurement device includes a fixing ring, a main body, and a transceiver. The fixing ring has a first surface. The main body is over the first surface of the fixing ring. The transceiver is coupled to the main body. The transceiver is at least movable between a center of the fixing ring to an edge of the fixing ring from a top view perspective.

(45) In another exemplary aspect, a method for measuring a target is provided. The method includes the operations as follows. An instruction to find a center of the target by moving a transceiver from an initial position to a calibration position where vertically aligning with a zeroing hole on a fixing ring surrounding the target along a linear trajectory is received. An instruction to move the transceiver from the calibration position toward an edge of the target is received. An instruction to scan the target to acquire an erosion profile by moving the transceiver from the edge to a center of the target is received.

(46) In yet another exemplary aspect, a method for measuring a target is provided. The method includes the operations as follows. A target measurement device is mounted in a chamber, and the target measurement device includes a transceiver. An instruction to move the transceiver from an initial position to a calibration position along an extension line passing a center of the target is entered. An instruction to scan the target to acquire an erosion profile by moving the transceiver from the calibration position to the center of the target is entered.

(47) The foregoing outlines structures of several embodiments so that those skilled in the art may better understand the aspects of the present disclosure. Those skilled in the art should appreciate that they may readily use the present disclosure as a basis for designing or modifying other processes and structures for carrying out the same purposes and/or achieving the same advantages of the embodiments introduced herein. Those skilled in the art should also realize that such equivalent constructions do not depart from the spirit and scope of the present disclosure, and that they may make various changes, substitutions, and alterations herein without departing from the spirit and scope of the present disclosure.

Claims

1. A target measurement device, comprising: a fixing ring having a first surface, wherein the fixing ring comprises: a zeroing hole at the first surface; and a plurality of mounting holes at the first surface and adjacent to the zeroing hole; and a transceiver disposed over the first surface of the fixing ring, wherein the transceiver is at least movable between a center of the fixing ring to an edge of the fixing ring from a top view perspective.
2. The target measurement device of claim 1, further comprising: a main body disposed over the first surface of the fixing ring and coupled to the transceiver.
3. The target measurement device of claim 2, wherein the main body comprises a motor coupled to the transceiver.
4. The target measurement device of claim 3, wherein the main body further comprises a controller coupled to the motor and a data collection unit.
5. The target measurement device of claim 2, wherein the main body comprises: a pair of supporting legs coupled to the fixing ring; a bracket rail over the pair of supporting legs and

- traversing the fixing ring; and a measuring arm over the bracket rail, and the measuring arm being configured to slide along the bracket rail.
6. The target measurement device of claim 1, further comprising a baseplate under the fixing ring.
7. The target measurement device of claim 1, wherein the transceiver comprises a pressure sensor.
8. A method for measuring a target, the method comprising: moving a transceiver to vertically align with a zeroing hole on a fixing ring surrounding the target; moving the transceiver toward an edge of the target along a linear trajectory; and scanning the target to acquire an erosion profile of the target by moving the transceiver from the edge to a center of the target.
9. The method of claim 8, wherein the zeroing hole is lined up with a center of the target along the linear trajectory.
10. The method of claim 9, wherein the fixing ring further comprises: a plurality of first mounting holes distributed evenly from a top view perspective; and a plurality of second mounting holes distributed in proximity to a side of the fixing ring from a top view perspective.
11. The method of claim 10, wherein the fixing ring is installed around the target through the plurality of first mounting holes.
12. The method of claim 10, wherein the transceiver is coupled to a main body, and the main body is coupled to the fixing ring through the plurality of second mounting holes.
13. The method of claim 8, wherein the fixing ring further comprises a first surface and a second surface opposite to the first surface, an area of the first surface is larger than that of the second surface.
14. The method of claim 8, further comprising: emitting a laser beam during the movement of the transceiver.
15. The method of claim 8, wherein the target is placed on a baseplate under the fixing ring.
16. A method for measuring a target, the method comprising: mounting a target measurement device in a chamber, the target measurement device comprises: a fixing ring; a bracket rail traversing over the fixing ring; and a transceiver connected to the bracket rail; moving the transceiver from an initial position to a calibration position along an extension line passing a center of the target; and scanning the target to acquire an erosion profile of the target by moving the transceiver from the calibration position to the center of the target.
17. The method of claim 16, wherein the target measurement device further comprises: a measuring arm, disposed over the bracket rail and bearing the transceiver, wherein the measuring arm slides along the bracket rail thereby moving the transceiver from the initial position to the calibration position; and a pair of support legs, supporting the bracket rail on the fixing ring.
18. The method of claim 16, wherein the operation of mounting the target measurement device in the chamber comprises installing the fixing ring around the target.
19. The method of claim 16, further comprising: removing a plurality of screws configured to fix the target prior to mounting the target measurement device in the chamber.
20. The method of claim 16, further comprising: moving the transceiver to align with the calibration position manually when the transceiver failed to move to the calibration position; wherein the calibration position is a zeroing hole at the fixing ring.
-