

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12406545
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Nakatake; Kazuo et al.

Paper sheet transport system and restoration method

Abstract

The present invention includes a configuration to move a transport body (500) in conjunction with movement of a moving body (200) due to repulsion applied between respective magnetic materials (213) and (523) when the moving body and the transport body are in a close location relation, and, when the moving body separates from a range of the close location relation due to halfway stop of the transport body, the transport body is moved in the opposite direction to stop at a predetermined end portion stop position, subsequently only the moving body is caused to travel in a direction further away from the transport body, and the moving body is returned into the range of the close location relation by causing the moving body to travel toward the transport body at a speed resistible against the repelling force.

Inventors:	Nakatake; Kazuo (Osaka, JP), Ichikawa; Masaaki (Osaka, JP), Arai; Hirokazu (Osaka, JP)
Applicant:	JAPAN CASH MACHINE CO., LTD. (Osaka, JP)
Family ID:	74673636
Assignee:	JAPAN CASH MACHINE CO., LTD. (Osaka, JP)
Appl. No.:	18/043957
Filed (or PCT Filed):	August 17, 2021
PCT No.:	PCT/JP2021/030055
PCT Pub. No.:	WO2022/054509
PCT Pub. Date:	March 17, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230316843 A1	Oct. 05, 2023

Foreign Application Priority Data

JP 2020-150572 Sep. 08, 2020

Publication Classification

Int. Cl.: G07D11/16 (20190101); A63F7/02 (20060101); B65G51/16 (20060101); B65G54/02 (20060101)

U.S. Cl.:

CPC G07D11/16 (20190101); B65G51/16 (20130101); B65G54/025 (20130101); A63F7/022 (20130101); G07D2211/00 (20130101)

Field of Classification Search

CPC: B65G (54/025)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1719231	12/1928	McLaren	104/156	B65G 54/02
4754691	12/1987	Rogerson	91/410	F15B 15/086
5388526	12/1994	Imai	104/138.1	B65G 54/025
6267058	12/2000	Schlienger	104/138.1	B60V 3/04
6279485	12/2000	Schlienger	104/138.1	B65G 54/025
6360670	12/2001	Schlienger	104/283	B61C 11/06
2019/0163123	12/2018	Kanemitsu et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2019-101172	12/2008	JP	N/A
2010-024058	12/2009	JP	N/A
2016-160038	12/2015	JP	N/A

OTHER PUBLICATIONS

WIPO, Japan International Search Authority, International Search Report (with English Translation) and Written Opinion mailed Sep. 21, 2021 in International Patent Application No. PCT/JP2021/030055, 10 pages. cited by applicant

Primary Examiner: Harp; William R

Attorney, Agent or Firm: MASUVALLEY & PARTNERS

Background/Summary

RELATED APPLICATIONS

(1) This application is the U.S. National Phase of and claims priority to International Patent Application No. PCT/JP2021/030055, International Filing Date Aug. 17, 2021, entitled Paper Sheet Transport System, And Restoration Method; which claims benefit of Japan Application No. 2020-150572 filed Sep. 8, 2020; both of which are incorporated herein by reference in their entireties.

FIELD

(2) The present invention relates to a transport system for paper sheets such as banknotes, and a restoration method thereof.

BACKGROUND

(3) In a game hall where various types of game machines such as pachinko machines or pachislot (pachinko-slot) machines are installed, game media dispensing devices for renting pachinko balls or tokens being game media to players according to a money amount of banknotes input through a banknote inlet are placed adjacent to the game machines. Various banknote transport devices are developed and proposed to enable the game media dispensing devices to safely and smoothly transport received banknotes to a safe.

(4) Patent Literature 1 discloses a paper sheet transport mechanism that causes a moving body to travel with an air flow and that causes a banknote transport body to travel with a magnetic force in conjunction with movement of the moving body. In the course of moving on a moving route along game media dispensing devices, the transport body transports banknotes received by each of the game media dispensing devices to a safe while sequentially collecting and retaining the banknotes. Since no mechanical driving means such as a motor, a gear, and a transport belt are required to cause the moving body and the transport body to travel, the durability of members constituting the transport mechanism can be increased and the running cost of the transport mechanism can be reduced.

CITATION LIST

Patent Literature

(5) Patent Literature 1: Japanese Patent Application Laid-open No. 2019-101172

SUMMARY

Technical Problem

(6) However, the paper sheet transport mechanism described in Patent Literature 1 has a configuration to move the transport body in conjunction with the moving body with a repelling force applied thereto only when a transport body magnetic material is in a predetermined close location relation with a moving body magnetic material. Therefore, when the transport body is prevented from moving due to a cause such as contact of banknotes on the transport body with an obstacle during a reciprocating operation and suddenly stops, a situation where the transport body cannot move from the stopped position while only the moving body that is not prevented from moving separates from the transport body and moves ahead occurs.

(7) FIG. 34(a) illustrates a state where a moving body **200** in an air blowing tube **100** and a transport body **500** in a transport body route **400** are in a normal close location relation in which these bodies can move in conjunction with each other, and FIG. 34(b) illustrates a state where only the moving body **200** moves ahead due to stop of the transport body **500**. In the example of FIG. 34(b), some banknotes P on the transport body have a deformed portion such as a creased portion, and this deformed portion interferes with an inner wall of the transport body route **400**, particularly, an inner wall of a curved route during movement of the transport body to cause jam of the whole banknotes and resists the travel of the transport body to stop the transport body.

(8) In this case, at the time when stop of the transport body that is supposed to be traveling is detected, the operation of the entire transport mechanism including the moving body is stopped to prevent damages of the banknotes. Thereafter, an operator removes the banknotes from the transport body and a restoration operation to return the moving body to a location proximate to the

transport body illustrated in FIG. 34(a) is subsequently performed.

(9) In the restoration operation, the moving body separated from the transport body as in FIG.

34(b) needs to be moved back to return to the normal close location as in FIG. 34(a). This return operation is an operation of moving the moving body back with an air flow or by human hands.

(10) However, when the moving body 200 is moved in a return direction as indicated by an arrow R in FIG. 34(b) to be brought close to the transport body 500 stopping halfway on the transport body route 400, the transport body recedes in the direction R due to repulsion based on a magnetic force before the moving body catches up with the transport body, and the moving body 200 can never crawl immediately under the transport body. Even when the moving body at the location illustrated in FIG. 34(b) is attempted to be brought close to the transport body and to enter the location immediately under the transport body in a state where the transport body is stopped in an unmovable manner, it is difficult to slip (dock) the moving body under the transport body because the repelling force of the magnet is strong.

(11) The present invention has been achieved in view of the circumstances described above, and has an object to provide a paper sheet transport system that moves a transport body including a magnetic material in conjunction with a moving body with a repelling force between the transport body and a magnetic material mounted on the moving body, and that can effectively return (restore) the moving body to a location proximate to the transport body when a situation in which only the moving body separates from the transport body and moves ahead because the transport body stops during traveling in a predetermined direction, and movement in conjunction with each other with a magnetic force is disabled occurs, and a restoration method thereof.

Solution to Problem

(12) In order to achieve the above object, the present invention comprises an air flow generating device, an air blowing tube that forms therein a flow path of an air flow generated by the air flow generating device, a switching unit that controls switching of directions of an air flow in the air blowing tube, a controlling unit that controls the air flow generating device and the switching unit a moving body that travels inside the air blowing tube while receiving an air flow flowing within the air blowing tube, a transport body route having at least a portion arranged along the air blowing tube to be adjacent to the air blowing tube and a transport body configured to be able to retain paper sheets and traveling inside the transport body route, wherein the moving body includes a moving body magnetic material, and the transport body includes a transport body magnetic material, a configuration to move the transport body in conjunction with movement of the moving body due to repulsion based on a magnetic force applied between the moving body magnetic material and the transport body magnetic material when the moving body magnetic material and the transport body magnetic material are in a close location relation is included, and when the moving body separates from a range of the close location relation due to halfway stop of the transport body in a process of the moving body moving the transport body in the close location relation in a predetermined direction, the controlling unit causes the moving body to move the transport body in an opposite direction to an original travel direction to stop the transport body at a predetermined end portion stop position, subsequently causes only the moving body to travel in a direction further away from the transport body to temporarily stop the moving body, and then returns the moving body into the range of the close location relation by causing the moving body to travel toward the transport body at a speed resistible against the repelling force.

Advantageous Effects of Invention

(13) According to the present invention, it is possible to effectively restore the moving body to a location proximate to the transport body when a situation in which only the moving body separates from the transport body and moves ahead because the transport body stops halfway during traveling in a predetermined direction, and movement in conjunction with each other with a magnetic force is disabled occurs.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a perspective view illustrating a schematic configuration of bank facilities including a plurality of game machines.
- (2) FIG. 2 is a plan view illustrating a schematic configuration of the bank facility including a plurality of the game machines.
- (3) FIG. 3 is a schematic diagram illustrating a schematic configuration of a banknote transport system according to a first invention.
- (4) FIG. 4 is a vertical sectional view of a moving body, an air blowing tube including the moving body, a transport body, and a transport tube including the transport body in a case in which the moving body and the transport body repel each other due to a magnetic force.
- (5) FIGS. 5(a) to 5(c) are schematic diagrams illustrating a relation between the air blowing tube and an air-blow control unit according to one embodiment of the first invention.
- (6) FIG. 6 is a perspective view illustrating a relation between the transport tube and the transport body.
- (7) FIG. 7 is a vertical sectional view of the moving body, the air blowing tube including the moving body, the transport body, and the transport tube including the transport body in a case in which the moving body and the transport body attract each other due to a magnetic force.
- (8) FIG. 8 is a vertical sectional view of the air blowing tube and the transport tube including the moving body and the transport body in a case in which the poles of each of moving body magnets are arranged to face in a travel direction.
- (9) FIG. 9 is a diagram illustrating a first modification of an air-blow control unit.
- (10) FIG. 10 is a diagram illustrating a second modification of the air-blow control unit.
- (11) FIG. 11 is a front view of a banknote transport system 10 including receiving units (banknote receiving devices) 600.
- (12) FIG. 12 is a plan view of the banknote transport system.
- (13) FIG. 13 is a front left perspective view of the banknote transport system.
- (14) FIG. 14 is a front right perspective view of the banknote transport system.
- (15) FIG. 15 is a perspective view illustrating a configuration of a coupling portion between the receiving unit and a transport tube 400.
- (16) FIG. 16 is a perspective view illustrating a portion of the transport tube in FIG. 15 in vertical cross section.
- (17) FIG. 17 is a horizontal sectional perspective view illustrating a configuration of the coupling portion between the receiving unit and the transport tube 400.
- (18) FIG. 18 is a horizontal sectional view of a portion of a banknote transport device C.
- (19) FIGS. 19(a), 19(b), 19(c), and 19(d) are an exterior perspective view, a front view, a plan view, and a sectional view along A-A in FIG. 19(a) of a transport body 500 in a state where collecting members (collecting pawls) are opened.
- (20) FIGS. 20(a) and 20(b) are an exterior perspective view and a plan view of the transport body 500 in a state where the collecting members (the collecting pawls) are closed.
- (21) FIG. 21 is a partial sectional view illustrating a location relation between the transport tube 400 and the transport body 500.
- (22) FIGS. 22(a), 22(b), 22(c), and 22(d) are plan horizontal sectional views illustrating a procedure in which the collecting members enter a keeping part to collect a kept banknote in a process of the transport body 500 moving forward.
- (23) FIG. 23 is a plan horizontal sectional view illustrating a state where one of the collecting pawls deforms in a process of the transport body moving backward.
- (24) FIG. 24 is a flowchart illustrating an example of a collecting procedure and an introducing

procedure for banknotes by the transport body.

(25) FIG. 25 is a flowchart illustrating another example of the collecting procedure and the introducing procedure for paper sheets by the transport body.

(26) FIG. 26 is a flowchart illustrating another example of the collecting procedure and the introducing procedure for paper sheets by the transport body.

(27) FIGS. 27(a) and 27(b) are a front vertical sectional view of portions of the air blowing tube and the transport body route on the side of an initial position in the banknote transport system according to a third invention, and a front vertical sectional view of portions thereof on the side of a safe system (a bank end unit).

(28) FIGS. 28(a) and 28(b) are a front view illustrating a state where the moving body causes the transport body to normally travel for collection of banknotes, and a front view illustrating a state where the moving body solely travels ahead because the transport body has stopped.

(29) FIGS. 29(a) and 29(b) are front views for explaining a control procedure for restoration.

(30) FIG. 30 is a flowchart illustrating a restoration method for the moving body and the transport body by a banknote transport system 10.

(31) FIGS. 31(a) and 31(b) are a front view illustrating a state where the moving body causes the transport body to normally travel to return to the initial position after collection of banknotes and transfer of banknotes to the safe unit are completed, and a front view illustrating a state where the moving body solely travels ahead because the transport body has stopped.

(32) FIGS. 32(a) and 32(b) are front views for explaining a control procedure for restoration.

(33) FIG. 33 is a perspective view illustrating another configuration example of the moving body.

(34) FIG. 34(a) is a diagram illustrating a state where the moving body in the air blowing tube and the transport body in a transport body route are in a normal close location relation, and FIG. 34(b) is a diagram illustrating a state where only the moving body moves ahead due to halfway stop of the transport body.

DESCRIPTION OF EMBODIMENTS

(35) The present invention will be described below in detail with embodiments illustrated in the drawings. Constituent elements, types, combinations, shapes, and relative arrangements described in the following embodiments are merely explanatory examples, and are not intended to limit the scope of the present invention solely thereto unless otherwise specified.

(36) Embodiments of the present invention are described below in detail.

(37) A. Paper Sheet Transport System According to First Invention

(38) A basic configuration of a paper sheet transport system according to a first invention, and an operation thereof are described below.

(39) The paper sheet transport system is installed on bank facilities in a game hall where various types of game machines such as pachinko machines or pachislot (pachinko-slot) machines are installed. While banknotes are mainly described as an example of paper sheets in the following embodiments, the present invention is also applicable to paper sheets (sheets) other than banknotes, including securities such as cash vouchers and gift certificates, and cards.

(40) [Schematic Configuration of Bank Facilities]

(41) FIG. 1 is a perspective view illustrating a schematic configuration of bank facilities including a plurality of game machines.

(42) Game machines 1 are installed on bank facilities L (L1, L2, . . .) and eight game machines 1 are arranged back to back on each of two opposing side surfaces of each of the bank facilities L, that is, a total of 16 game machines 1 are arranged back to back. An aisle on which players or clerks of the game hall walk is provided between the bank facilities L and a chair (not illustrated) is provided for each of the game machines 1 on the aisles.

(43) A sandwiched machine 2 is installed for each of the game machines 1 on the bank facilities L. The sandwiched machine 2 includes a banknote inlet (a banknote input part) that receives input banknotes, and a game media dispensing device that dispenses a number of pachinko balls

corresponding to the amount of input banknotes, and the like. A banknote transport system **10** that transports banknotes inserted through the sandwiched machines **2** to a safe unit **700** placed at one end portion of the associated bank facility **L** is installed in each of the illustrated bank facilities **L**. (44) FIG. **2** is a plan view illustrating a schematic configuration of the bank facility including a plurality of the game machines.

(45) The banknote transport system **10** installed in each of the bank facilities **L** includes receiving units (banknote receiving devices) **600** that each receive banknotes inserted from the banknote inlet of the associated sandwiched machine **2** therein, a transport tube **400** that extends in a longitudinal direction of the bank facility **L** (an array direction of the game machines **1**) and that transports the banknotes received by the receiving units **600**, the safe unit **700** that is arranged at one end of the transport tube **400**, and the like.

(46) [Schematic Configuration of Banknote Transport System]

(47) <Overall Outline>

(48) FIG. **3** is a schematic diagram illustrating a schematic configuration of the banknote transport system. The banknote transport system (a paper sheet transport mechanism) **10** according to one embodiment of the first invention is characterized in transporting banknotes using an air flow and a magnetic force.

(49) The banknote transport system **10** includes an air blowing tube **100** that forms a flow path (an air flow path **101**) of a gas, a moving body **200** that travels (moves) inside the air blowing tube **100** while receiving an air flow flowing in a predetermined direction within the air blowing tube **100**, an air-blow control unit **300** that controls the air flow flowing inside the air blowing tube **100**, the transport tube **400** (a transport path **401**) that has at least a portion arranged along the air blowing tube **100** to be adjacent to the air blowing tube **100**, and a transport body **500** that is configured to be able to retain banknotes (paper sheets) and that travels (moves) inside the transport tube **400**. The transport tube **400** forms the transport path **401** (a banknote (paper sheet) transport route and a transport space) for banknotes.

(50) The moving body **200** includes a moving body magnetic material (moving body magnets **213**), and the transport body **500** includes a transport body magnetic material (transport body magnets **523**). At least one of the moving body magnetic material and the transport body magnetic material is formed of a magnet.

(51) The banknote transport system **10** includes the receiving units **600** that receive banknotes input from outside and keep the banknotes at predetermined locations in the transport tube **400**, respectively, the safe unit **700** that includes a banknote accommodating part that accommodates therein banknotes transported by the transport body **500**, and a management unit (controlling unit) **800** that controls the components constituting the banknote transport system **10**.

(52) In the present example, the air-blow control unit **300** and the safe unit **700** are accommodated in a body **801** that has the management unit **800** accommodated therein.

(53) The banknote transport system **10** is characterized in moving in an advancing/retracting manner the moving body **200** arranged in the air blowing tube **100** in the longitudinal direction of the air blowing tube **100** with the air flow flowing inside the air blowing tube **100**, and in moving the transport body **500** arranged in the transport tube **400** along the longitudinal direction of the air blowing tube **100** with a magnetic force acting between the transport body **500** and the moving body **200**. That is, the banknote transport system **10** is characterized in moving the transport body **500** in conjunction with movement of the moving body **200** receiving the air flow due to attraction and/or repulsion based on a magnetic force acting between the moving body magnets **213** and the transport body magnets **523**.

(54) <Outline of Components>

(55) The air blowing tube **100** includes a moving route part **111** in at least a portion in the longitudinal direction, on which the moving body **200** travels along the longitudinal direction of the air blowing tube **100**. The moving route part **111** is arranged in parallel and adjacently to the

transport tube **400**.

(56) The moving body **200** moves inside the air blowing tube **100** while receiving an air flow flowing in a predetermined direction within the air blowing tube **100**. The moving body magnets **213** mounted on the moving body **200** provide a repelling action and/or an attracting action due to a magnetic force to the transport body **500**. The moving body **200** moves the moving body **200** in conjunction with its own movement due to the magnetic force.

(57) The air-blow control unit **300** includes a blower (an air flow generating device) **310** that generates (produces) an air flow in a predetermined direction inside the air blowing tube **100** and that can change the flow volume and the flow speed of the air flow. The air-blow control unit **300** alternately generates an air flow in a first direction (a banknote collecting direction and an arrow-B direction) and an air flow in a second direction (a transport body returning direction and an arrow-C direction) being an opposite direction to the first direction inside the air blowing tube **100** to reciprocate the moving body **200** inside the air blowing tube **100**.

(58) The transport tube **400** forms a space through which banknotes and the transport body **500** move.

(59) The transport body **500** receives the banknotes kept at predetermined locations in the transport path **401** to retain the banknotes in a standing manner, and moves inside the transport path **401** to transport the banknotes to the safe unit **700**. The transport body magnets **523** mounted on the transport body **500** are subjected to the attracting action and/or the repelling action due to the magnetic force from the moving body magnets **213** included in the moving body **200**. The transport body **500** moves inside the transport tube **400** in conjunction with the movement of the moving body **200** receiving the air flow.

(60) When only the attracting force is to be applied between the moving body **200** and the transport body **500**, both the magnetic materials mounted on the moving body **200** and the transport body **500** can be magnets, or one of the magnetic materials of the moving body **200** and the transport body **500** may be magnets and the other one may be a magnetic material such as iron. When only the repelling force is to be applied between the moving body **200** and the transport body **500**, both the magnetic materials mounted on the moving body **200** and the transport body **500** are formed of magnets.

(61) The receiving unit (the banknote receiving device) **600** receives banknotes inserted from the banknote inlet (a banknote inserting part) of the associated sandwiched machine **2** therein and keeps the banknotes at a predetermined location in the transport path **401**. The receiving unit **600** is provided for each of the sandwiched machines **2**. A plurality of the receiving units **600** are installed in the longitudinal direction of the transport tube **400** at a predetermined interval.

(62) The safe unit **700** includes a banknote accommodating part that accommodates therein banknotes transported by the transport body **500**, a drive mechanism that drives members related to accommodation of the banknotes in the banknote accommodating part, and the like.

(63) The management unit (controlling unit) **800** controls operations of the components constituting the banknote transport system **10**. The management unit **800** is configured to include a general computer device that includes a CPU (Central Processing Unit), a ROM (Read Only Memory), a RAM (Random Access Memory), and the like and in which these units are connected via a bus. The CPU is an arithmetic unit that controls the entire banknote transport system **10**. The ROM is a nonvolatile memory that has a control program to be executed by the CPU, data, and the like stored therein. The RAM is a volatile memory to be used as a work area for the CPU. The CPU reads the control program stored in the ROM to load the control program into the RAM and execute the control program, so that various functions are realized.

(64) [Detailed Configuration of Banknote Transport System]

(65) Detailed configurations of the components of the banknote transport system according to the embodiment of the first invention are explained.

(66) <Air Blowing Tube>

(67) The air blowing tube is explained with reference to FIGS. 3 and 4.

(68) FIG. 4 is a vertical sectional view of the moving body, the air blowing tube including the moving body, the transport body, and the transport tube including the transport body in a case in which the moving body and the transport body repel each other due to a magnetic force.

(69) The air blowing tube **100** illustrated in FIG. 3 includes a first air blowing tube **110** including the moving route part **111**, and a second air blowing tube **120** forming the air flow path **101** in an endless manner with the first air blowing tube **110** through a switching valve **325** (see FIG. 5), which will be described later.

(70) Since the banknote transport system **10** moves the transport body **500** using a magnetic force, the moving route part **111** of the air blowing tube **100** includes a configuration that does not affect the travel of the moving body **200** and the travel of the transport body **500** based on the magnetic force. While it is desirable that the moving route part **111** is entirely formed of a non-magnetic material, the moving route part **111** may include a magnetic material in a portion within a range that does not affect the travel of the moving body **200** and the transport body **500**.

(71) The moving route part **111** includes a configuration (the thicknesses of the tube, the spacing between tubes, the shape thereof, and the like) that can apply a magnetic force between the moving body **200** arranged inside the moving route part **111** and the transport body **500** arranged inside the transport tube **400**.

(72) With the configuration of the air blowing tube **100** separate from and independent of the transport tube **400**, an airtight flow path can be formed in the air blowing tube **100**. Reduction in the transport force of the moving body **200** due to air leakage to outside of the air blowing tube **100** can be prevented. Furthermore, the blower **310** being relatively inexpensive and outputting low power can be adopted as a blower to be used to generate an air flow and reduction in the cost of the banknote transport system **10** can be realized. The air flow inside the air blowing tube **100** can be reliably controlled even when the air blowing tube **100** is elongated with an increase in the banknote transport distance. Since the moving body **200** is caused to travel with the air flow, the need to arrange a mechanical configuration such as a gear or a transport belt, lines, or electrical contacts inside the air blowing tube **100** is eliminated and the durability of the air blowing tube **100** and the moving body **200** arranged therein is increased. Furthermore, external air does not flow in the air flow path **101** airtightly configured, so that grit and dust in the external air are not drawn therein and the inside of the air flow path **101** can be kept clean.

(73) <Moving Body>

(74) It suffices that the moving body **200** has a shape and a configuration that enables movement in the air blowing tube **100** by being subjected to an air pressure.

(75) As illustrated in FIG. 4, the moving body **200** has a configuration in which a plurality of divided pieces **210**, **210**, . . . are sequentially coupled to each other with hinge parts **211** along a travel direction of the moving body **200** (the longitudinal direction of the air blowing tube **100**). The divided pieces **210** illustrated in the present example have same configurations and each of the divided pieces **210** has the moving body magnet **213**.

(76) The moving body **200** includes the moving body magnets **213** respectively arranged at locations, in attitudes, and in shapes that enable to apply a magnetic force to the transport body **500**. In the present example, the moving body magnets **213** are arranged on a side of the moving body **200** nearer the transport tube **400**. The moving body magnets **213** included in the moving body **200** are arranged spaced apart from each other in the travel direction of the moving body **200**. In the present example, each of the moving body magnets **213** is attached to the associated divided piece **210** in such a manner that the N pole (one of the poles) faces the side of the transport tube **400** (the upper side in FIG. 4) and the S pole (the other pole) faces the lower side in FIG. 4.

(77) The moving body **200** illustrated in the present example is constituted of three divided pieces **210**. The divided pieces **210** are coupled to each other to be angularly displaceable within a predetermined range in the upper-lower direction in FIG. 4 and the depth direction of the plane of

the paper centering on the hinge parts **211**, respectively. With this configuration, the moving body **200** can smoothly move in the air blowing tube **100** while the divided pieces **210** are displaced even when the air blowing tube **100** forms the air flow path **101** curved in the upper-lower or right-left direction.

(78) <Relation Between Air Blowing Tube and Moving Body>

(79) The inner surface shape of the moving route part **111** and the outer surface shape (the configuration) of the moving body **200** are formed in such a manner that the moving body **200** does not relatively rotate on a virtual axis extending along the longitudinal direction of the moving route part **111** with respect to the moving route part **111**. For example, the horizontal sectional shape (the shape on a cross section orthogonal to the longitudinal direction) of the moving route part **111** and the horizontal sectional shape of the divided pieces **210** of the moving body **200** are respectively formed into rectangular shapes. With provision of the configuration described above, the attitude of the moving body **200** in the moving route part **111** can be maintained to cause the N pole (one of the poles) of each of the moving body magnets **213** to always face the side of the transport tube **400**.

(80) <Air-Blow Control Unit>

(81) FIGS. 5(a) to 5(c) are schematic diagrams illustrating a relation between the air blowing tube and the air-blow control unit according to one embodiment of the first invention.

(82) The air-blow control unit **300** according to the present embodiment includes a single blower **310** that generates an air flow flowing in a certain direction, and a switching unit **320** (the switching valve **325**) that controls the direction of the air flow in the air blowing tube **100**. The air-blow control unit **300** is characterized in switching the direction of the air flow in the air blowing tube **100** between the first direction (the banknote collecting direction and the arrow-B direction) and the second direction (the moving body returning direction and the arrow-C direction) opposite to the first direction using the switching unit **320**.

(83) The air-blow control unit (an air-flow control apparatus) **300** includes the switching unit (an air flow switching unit) **320** that controls the discharge direction of the air flow, a first circulation pipe **330** that forms an endless air flow path through the switching unit **320**, and the blower **310** that is arranged at an appropriate place in the first circulation pipe **330** to generate an air flow flowing in a certain direction inside the first circulation pipe.

(84) The switching unit **320** includes a casing **321** in which four flow paths **323** (a first flow path **323a** to a fourth flow path **323d**: ports) respectively connecting to external pipes are formed, and the switching valve **325** that is arranged in a joint portion (an intersecting portion) of the four flow paths **323** to switch the communication state among the flow paths **323** and/or the opening degrees at the time of communication. The flow paths **323** are communicated with and connected to an air discharge tube **331**, an air intake tube **333**, the first air blowing tube **110**, and the second air blowing tube **120** that are external pipes, respectively. In the present example, the flow paths **323** are arranged in a cross manner (a radial manner). The switching valve **325** illustrated in the present example is a rotary valve such as a ball valve and the switching valve **325** rotates in the casing **321** by a predetermined angle, whereby the communication states of the flow paths **323** and the opening degrees of the flow paths **323** are switched.

(85) The switching valve **325** is an electric-operated valve and is driven by a motor to control the rotation angle. For example, a stepping motor can be used as the motor. The switching valve **325** is, for example, controlled to have a desired rotation angle by the management unit **800** that controls the rotation angle of the stepping motor on the basis of a drive pulse. Of course, other methods may be used for driving means for rotating the switching valve **325** and control of the rotation angle of the switching valve **325**. For example, a configuration in which a rotary encoder that rotates in conjunction with the switching valve **325**, and a sensor that detects the rotation angle of the rotary encoder are mounted on the switching unit **320** and in which the management unit **800** executes feedback control of the rotation angle of the switching valve **325** may be adopted.

(86) The first circulation pipe **330** includes the air discharge tube **331** that has one end portion (one end portion **330a** of the first circulating pipe **330**) communicatively connected to the first flow path **323a** of the switching unit **320** and the other end portion communicatively connected to the outlet of the blower **310**, and the air intake tube **333** that has one end portion communicatively connected to the inlet of the blower **310** and the other end portion (the other end portion **330b** of the first circulation pipe **330**) communicatively connected to the second flow path **323b** of the switching unit **320**.

(87) The air blowing tube (the second circulation pipe) **100** has one end portion **100a** communicatively connected to the third flow path **323c** of the switching unit **320** and the other end portion **100b** communicatively connected to the fourth flow path **323d** of the switching unit **320**, and forms an endless air flow path through the switching unit **320**. The air blowing tube **100** reciprocates the moving body **200** placed therein in the arrow-B direction and the arrow-C direction in FIG. 5 with the air flow.

(88) The air blowing tube **100** according to the present example includes the first air blowing tube **110** forming the moving route part **111** of the moving body **200**, and the second air blowing tube **120** communicatively connected to the first air blowing tube **110**. The first air blowing tube **110** is communicatively connected to the third flow path **323c** and the second air blowing tube **120** is communicatively connected to the fourth flow path **323d**.

(89) <<Operation of Switching Unit: Neutral State>>

(90) FIG. 5(a) illustrates a neutral state.

(91) The switching valve **325** is at a neutral position for establishing communication between the first flow path **323a** and the second flow path **323b** while not establishing communication between the first and second flow paths **323a** and **323b** and the third and fourth flow paths **323c** and **323d**.

(92) Accordingly, the air flow circulates in the first circulation pipe **330** in an arrow-A (A1 and A2) direction and no air flow is generated inside the air blowing tube **100**. Therefore, the moving body **200** is in a state stopped in the air blowing tube **100**.

(93) <<Operation of Switching Unit: First Communication State>>

(94) FIG. 5(b) illustrates a first state in which an air flow flowing in the air blowing tube **100** in the first direction (an arrow-B1 or B2 direction) is generated inside the air blowing tube **100**. This state is, for example, a banknote collecting operation state for transporting banknotes collected by the transport body **500** to the safe unit **700**.

(95) The switching valve **325** is in a first communication position for establishing communication between the first flow path **323a** and the fourth flow path **323d** and establishing communication between the second flow path **323b** and the third flow path **323c**. At this time, the first flow path **323a** and the fourth flow path **323d** are not communicated with the second flow path **323b** and the third flow path **323c**.

(96) The air circulates in an endless manner between the first circulation pipe **330** and the air blowing tube **100**. That is, air (in the arrow-A1 direction) discharged from the discharge tube **331** to flow in the first flow path **323a** flows in the second air blowing tube **120** from the fourth flow path **323d** (in the arrow-B1 direction) due to the switching valve **325**. Air flowing in the arrow-B2 direction inside the first air blowing tube **110** to flow in the third flow path **323c** flows in the intake tube **333** from the second flow path **323b** (in the arrow-A2 direction) due to the switching valve **325**, returns to the blower **310**, and is discharged again from the discharge tube **331**.

(97) <<Operation of Switching Unit: Second Communication State>>

(98) FIG. 5(c) illustrates a second state in which an air flow flowing in the second direction (an arrow-C1 or C2 direction) is generated inside the air blowing tube **100**. This state is, for example, a return operation state for returning the transport body **500** from the side of the safe unit **700** (the side of the management unit **800**) to the distal end side of the transport tube **400**.

(99) The switching valve **325** is in a second communication position for establishing communication between the first flow path **323a** and the third flow path **323c** and establishing

communication between the second flow path **323b** and the fourth flow path **323d**. At this time, the first flow path **323a** and the third flow path **323c** are not communicated with the second flow path **323b** and the fourth flow path **323d**.

(100) The air circulates in an endless manner between the first circulation pipe **330** and the air blowing tube **100**. That is, air (in the arrow-A1 direction) discharged from the discharge tube **331** to flow in the first flow path **323a** flows in the first air blowing tube **110** from the third flow path **323c** (the arrow-C1 direction) due to the switching valve **325**. Air flowing in the arrow-C2 direction inside the second air blowing tube to flow in the fourth flow path **323d** flows in the intake tube **333** from the second flow path **323b** (in the arrow-A2 direction) due to the switching valve **325**, returns to the blower **310**, and is discharged again from the discharge tube **331**.

(101) <<Operation Of Switching Unit: Summary>>

(102) By connecting two endless pipes (the first circulation pipe **330** and the air blowing tube **100**) via the switching unit **320** as described above, three states including the neutral state in which no air flow is generated in the air blowing tube **100**, the first communication state in which an air flow flowing in the first direction (the arrow-B direction) is generated inside the air blowing tube **100**, and the second communication state in which an air flow flowing in the second direction (the arrow-C direction) is generated inside the air blowing tube **100** can be switched by changing the position of the switching valve **325** while an air flow in a certain direction (the arrow-A direction) is generated by the single blower **310**.

(103) In intermediate positions taken by the switching valve **325** among the three states described above, the communication state changes from those in the three states. That is, since the communication relation among the flow paths and the opening degrees of the flow paths can be adjusted according to the angle of the switching valve **325** in the casing **321** in the present embodiment, an air volume of the air flow according to the opening degrees of the flow paths can be generated inside the air blowing tube **100**. That is, the speed of the moving body **200** can be varied according to the wind speed in the air blowing tube **100**.

(104) The moving speed of the moving body **200** may be adjusted by control of the air volume of the blower **310**. For example, the air volume of the blower **310** may be adjusted by varying the rotational speed of blades of the blower **310** by PWM (Pulse Width Modulation) control. However, since the rotation responsiveness of the switching valve **325** is higher than the variation responsiveness of the rotational speed of the blower **310**, adjustment of the rotation angle of the switching valve **325** is more advantageous to rapidly adjust the speed of the moving body **200**.

(105) <Transport Tube>

(106) The transport tube (the transport route) **400** is explained with reference to FIGS. **4** and **6**.

(107) FIG. **6** is a perspective view illustrating a relation between the transport tube and the transport body. FIG. **6** illustrates a state in which the inner part of the transport tube **400** is partially exposed.

(108) Since the transport body **500** is transported with a magnetic force in the banknote transport system **10**, the transport tube **400** is formed of a material that does not affect the travel of the transport body **500** based on the magnetic force. Although it is desirable that the transport tube **400** is entirely formed of a non-magnetic material, the transport tube **400** may include a magnetic material in a part thereof without affecting the travel of the transport body **500**.

(109) The transport tube **400** includes a configuration (the thickness of the tube, the spacing between the tubes, the shape thereof, and the like) that can apply a magnetic force between the moving body **200** arranged inside the moving route part **111** and the transport body **500** arranged inside the transport tube **400**.

(110) Although the transport tube **400** is arranged above the air blowing tube **100** in the present example, the location relation between the air blowing tube **100** and the transport tube **400** is not limited thereto. The transport tube **400** may be arranged below the air blowing tube **100** or the transport tube **400** may be arranged on the lateral side of the air blowing tube **100**.

(111) While the transport tube **400** is illustrated as means for constituting the transport path **401**, the means for constituting the transport path **401** does not need to be tubular and the present invention can be achieved even with a configuration in which a part or the whole of the transport path **401** is open to outside. That is, the transport tube **400** may have any form as long as it can form therein an elongated space as the transport path **401**.

(112) <Transport Body>

(113) As illustrated in FIGS. **4** and **6**, the transport body **500** includes a transport base **510** that is arranged at a location nearer the air blowing tube **100** in the transport path **401** and that is subjected to a magnetic force from the moving body **200**, and a banknote collecting/retaining part **540** provided on the opposite side of the transport base **510** to the air blowing tube **100**.

(114) <<Transport Base>>

(115) The transport base **510** has a configuration in which a plurality of divided pieces **520**, **520**, . . . are sequentially coupled to each other with hinge parts **521** along the travel direction of the transport body **500** (the longitudinal direction of the transport tube **400**). Each of the divided pieces **520** illustrated in the present example includes the transport body magnet **523**.

(116) The transport base **510** includes the transport body magnets **523** arranged at locations, in attitudes, and in shapes that can be subjected to the effect of the magnetic force from the moving body **200**. In the present example, the transport body magnets **523** are arranged on the side of the transport base **510** nearer the air blowing tube **100**. The transport body magnets **523** included in the transport base **510** are arranged spaced apart from each other in the travel direction of the transport body **500**. In the present example, each of the transport body magnets **523** is attached to the associated divided piece **520** in such a manner that the N pole (one of the poles) faces the side of the air blowing tube **100** (the lower side in FIGS. **4** and **6**) and the S pole (the other pole) faces the upper side in FIGS. **4** and **6**. The transport base **510** magnetically levitates in the transport tube **400** under a repelling force due to the magnetic force from the moving body **200**.

(117) The transport base **510** illustrated in the present example is constituted of four divided pieces **520**. The divided pieces **520** are coupled to each other to be angularly displaceable within a predetermined range in the upper-lower direction in FIGS. **4** and **6** and the depth direction of the plane of paper on the hinge parts **521**, respectively. With the configuration described above, the transport body **500** can smoothly move in the transport tube **400** even when the transport tube **400** forms the transport path **401** curved in the upper-lower or right-left direction.

(118) <<Banknote Collecting/Retaining Part>>

(119) The banknote collecting/retaining part **540** is arranged on the transport base **510**. The banknote collecting/retaining part **540** includes a support member **541** that is upright in a direction away from the air blowing tube **100**, and collecting members (collecting pawls) **544** that are protruded from the support member **541** in the width direction at an end portion on the bank end side in the longitudinal direction of the transport tube **400** (on the distal end side with respect to the safe unit **700**). The support member **541** is protruded upward from a middle portion of the transport base **510** in the width direction.

(120) The banknote collecting/retaining part **540** retains banknotes **P** to cause the long edge direction of the banknotes **P** to follow the longitudinal direction of the transport tube **400** and in an upright attitude. One of long sides (a long side positioned on the lower side in FIG. **6**) of the banknote **P** is supported by the transport base **510**. The rear end edge (one of short sides) of the banknote is supported by the support member **541** or the collecting members **544**.

(121) <Relation Between Transport Tube and Transport Body>

(122) The transport tube **400** includes therein a base transport path **402** arranged on the side nearer the air blowing tube **100**, and a banknote transport path **403** arranged on the opposite side to the air blowing tube **100**. The base transport path **402** is a horizontally-long space where the transport base **510** of the transport body **500** travels, and the banknote transport path **403** is a vertically-long space where the banknote collecting/retaining part **540** of the transport body **500** and banknotes retained

by the banknote collecting/retaining part **540** travel.

(123) Since the transport body **500** illustrated in the present example travels while being subjected to a repelling force due to a magnetic force from the moving body **200**, the base transport path **402** and the transport base **510** are configured to inhibit separation (movement toward the banknote transport path **403**) of the transport base **510** from the base transport path **402** and maintain the transport base **510** at a location where the effect of the magnetic force can be received from the moving body **200**.

(124) The inner surface shape of the base transport path **402** and the outer surface shape of the transport base **510** are formed in such a manner that the transport base **510** does not relatively rotate on a virtual axis extending along the longitudinal direction of the base transport path **402** with respect to the base transport path **402**. For example, the horizontal sectional shape of the base transport path **402** and the horizontal sectional shape of the transport base **510** are formed in rectangular shapes. With provision of the configuration described above, the attitude of the moving body **200** in the base transport path **402** is maintained to cause the N pole (one of the poles) of each of the transport body magnets **523** to always face the side of the air blowing tube **100**.

(125) <Relation Between Moving Body and Transport Body>

(126) A relation between the moving body magnetic material and the transport body magnetic material is explained.

(127) <<Only Repulsion>>

(128) As illustrated in FIG. **4**, one or more magnets can be arranged in both the moving body **200** and the transport body **500** in directions repelling each other to apply only the repelling force between the moving body **200** and the transport body **500**. When only the repelling force is to be applied between the moving body **200** and the transport body **500**, it is desirable that a plurality of magnets are arranged on at least one of the moving body **200** and the transport body **500** at a predetermined interval in the travel direction. With arrangement of the magnets in the travel direction on at least one of the moving body **200** and the transport body **500**, the moving body magnets **213** and the transport body magnets **523** are alternately arrayed when the moving body **500** travels while being subjected to the repelling force from the moving body **200**. That is, when the transport body **500** travels, the transport body **500** is relatively positioned with respect to the moving body **200**. In this case, it is particularly preferable that the difference between the number of magnets included in the moving body **200** and the number of magnets included in the transport body **500** is one. In other words, when n is a natural number, it is preferable that n magnets are arranged on one of the moving body **200** and the transport body **500** and that $n+1$ magnets are arranged on the other one.

(129) When the transport tube **400** is placed above the air blowing tube **100** and a repelling force is applied between the transport body **500** and the moving body **200**, the transport body **500** levitates in the transport tube **400** and therefore the transport body **500** is less likely to be in contact with the transport tube **400**. Therefore, it is possible to prevent reduction in the transport force of the transport body **500** due to friction with the transport tube **400** and smoothly move the transport body **500**. Since the contact between the transport body **500** and the transport tube **400** is suppressed, generation of fine dust (powdery dust) due to contact between members can be prevented.

(130) When the repelling force is applied between the moving body **200** and the transport body **500**, the transport force can be increased by increasing the number of magnets included in the moving body **200** and the transport body **500**.

(131) <<Only Attraction>>

(132) FIG. **7** is a vertical sectional view of the air blowing tube and the transport tube including the moving body and the transport body in a case in which the moving body and the transport body attract each other due to a magnetic force.

(133) In an illustrated example, the moving body magnets **213** and the transport body magnets **523**

are respectively attached to the moving body **200** and the transport body **500** in attitudes attracting each other. Since the locations in the longitudinal direction of the moving body magnets **213** and the transport body magnets **523** match with walls of the air blowing tube **100** and the transport tube **400** interposed therebetween, positioning of the transport body **500** with respect to the moving body **200** is easy.

(134) When only the attracting force based on the magnetic force is to be applied between the moving body **200** and the transport body **500**, it suffices that at least either the magnetic material mounted on the moving body **200** or the magnetic material mounted on the transport body **500** is a magnet. For example, magnets may be arranged on one of the transport body **500** and the moving body **200** and a magnetic material (for example, iron plates), other than magnets, that is attracted by magnets may be arranged on the other one.

(135) When only the attracting force based on the magnetic force is to be applied between the moving body **200** and the transport body **500**, it suffices that at least one set of magnetic materials (for example, a set of a magnet and a magnet or a set of a magnet and an iron plate) is arranged on the transport body **500** and the moving body **200**.

(136) <<Repulsion and Attraction>>

(137) Both the repelling force and the attracting force may be applied between the moving body **200** and the transport body **500**. That is, a set of magnets that apply a repelling force to each other, and a set of magnets that apply an attracting force to each other may be mixed on the moving body **200** and the transport body **500**. An example in which both the repelling force and the attracting force are applied will be described later with reference to FIG. **8**.

(138) <<Orientation of Magnets>>

(139) While the poles of each of the magnets are arranged to face in the upper-lower direction (a staking direction of the air blowing tube **100** and the transport tube **400**) in the embodiment described above, the poles of each of the magnets may be arranged to face in the travel direction (for example, to cause the N pole to face toward the safe unit and the S pole to face toward the bank end side/the distal end side). Alternatively, the poles of each of the magnets may be arranged diagonally to the travel direction. The action of the magnetic force can be appropriately adjusted according to the orientation of the magnets.

(140) <<Orientation of Magnets: Arrangement in Tandem>>

(141) FIG. **8** is a vertical sectional view of the air blowing tube and the transport tube including the moving body and the transport body in a case in which the poles of each of the moving body magnets are arranged to face in the travel direction.

(142) In an illustrated example, each of the moving body magnets **213** is attached to the associated divided piece **210** in such a manner that the N pole (one of the poles) faces the side of the safe unit (the left side in FIG. **8**) and the S pole (the other pole) faces the distal end side (the right side in FIG. **8**). Each of the transport body magnets **523** is attached to the associated divided piece **520** in such a manner that the N pole faces the side of the air blowing tube **100** and the S pole faces the upper side in FIG. **8**.

(143) Since surfaces (the N poles) on the safe unit side of the moving body magnets **213** respectively repel the transport body magnets **523** (the N poles), and the surfaces (the S poles) on the distal end side of the moving body magnets **213** respectively attract the transport body magnets **523** (the N poles), both the repelling force and the attracting force can be applied between the moving body **200** and the transport body **500**.

(144) [First Modified Embodiment Related to Air Blow Control]

(145) FIG. **9** is a diagram illustrating a first modification of the air-blow control unit.

(146) An air-blow control unit **300B** may have a configuration including a blower **310a** having an outlet connected to one end portion **100a** of the air blowing tube **100**, a blower **310b** having an outlet connected to the other end portion **100b** of the air blowing tube **100**, and a connection pipe **340** that connects the inlets of the blowers **310a** and **310b** to each other. The air blowing tube **100**

(the first air blowing tube **110** and the second air blowing tube **120**) is configured in an endless manner through the two blowers **310a** and **310b** and the connection pipe **340**.

(147) Turning on/off of the blowers **310a** and **310b** and the air volume thereof are controlled by the management unit **800**.

(148) When an air flow flowing in a first direction (an arrow-B direction) is to be generated inside the air blowing tube **100** (the first state and the banknote collecting operation state), one blower **310b** is turned on to generate an air flow and the other blower **310a** is turned off. Air flowing inside the air blowing tube **100** flows in the outlet of the blower **310a** and is discharged from the inlet of the blower **310a**. The air further passes through the connection pipe **340** to return to the inlet of the blower **310b** and is discharged from the outlet of the blower **310b**.

(149) When an air flow flowing in a second direction (an arrow-C direction) is to be generated inside the air blowing tube **100** (the second state and the transport body returning state), it suffices to turn one blower **310b** off and turn the other blower **310a** on to generate the air flow.

(150) In this way, the use of two blowers also enables the air flow in the first direction and the air flow in the second direction to be generated inside the air blowing tube **100**.

(151) Since the inlets of the two blowers **310a** and **310b** are connected with the connection pipe **340** in the present example, air can be efficiently circulated inside the air flow path **101** airtightly configured.

(152) [Second Modified Embodiment Related to Air Blow Control]

(153) FIG. **10** is a diagram illustrating a second modification of the air-blow control unit.

(154) An air-blow control unit **300C** may have a configuration including the blowers **310a** and **310b** at one end portion **100a** and the other end portion **100b** of the air blowing tube **100**, respectively. Turning-on/off of the blowers **310a** and **310b** and the air volume thereof are controlled by the management unit **800**.

(155) When an air flow flowing in a first direction (an arrow-B direction) is to be generated inside the air blowing tube **100** (the first state and the banknote collecting operation state), one blower **310b** is turned on to generate an air flow and the other blower **310a** is turned off. The blower **310b** takes external air to the inside from the inlet and discharges the air, thereby generating the air flow in the arrow-B direction inside the air blowing tube **100**. This air flow is taken into the blower **310a** from the outlet of the blower **310a** and is discharged from the inlet.

(156) When an air flow flowing in a second direction (an arrow-C direction) is to be generated inside the air blowing tube **100** (the second state and the transport body returning state), it suffices to turn one blower **310b** off and turn the other blower **310a** on to generate the air flow.

(157) Since the present example does not require pipes for causing the air flow path **101** to be a circulation path, the configuration is simplified.

(158) B. Paper Sheet Transport System According to Second Invention

(159) <<Basic Configuration of Paper Sheet Transport System>>

(160) A paper sheet transport system according to a second invention is described next.

(161) The second invention has further embodied contents of the receiving units (paper sheet receiving devices) **600**, the transport tube **400**, the transport body **500**, and the like in the paper sheet transport system **10** according to the first invention, and like parts are denoted by like reference signs and are described with reference to FIGS. **1** to **10**.

(162) FIG. **11** is a front view of the banknote transport system **10** including the receiving units (the banknote receiving devices) **600**, FIG. **12** is a plan view of the banknote transport system, FIG. **13** is a front left perspective view of the banknote transport system, and FIG. **14** is a front right perspective view of the banknote transport system.

(163) FIG. **15** is a perspective view illustrating a configuration of a coupling portion between the receiving unit and the transport tube **400**, FIG. **16** is a perspective view illustrating a portion of the transport tube in FIG. **15** in vertical cross section, FIG. **17** is a horizontal sectional perspective view illustrating a configuration of the coupling portion between the receiving unit and the transport tube

400, and FIG. **18** is a horizontal sectional view of a portion of the banknote transport device C.

(164) The banknote transport system **10** according to the second invention schematically includes the banknote transport device C including the transport tube **400** (the transport path **401**) as a mainstream that has at least a portion arranged along the air blowing tube **100** to be adjacent to the air blowing tube **100**, the transport body (a banknote transport shuttle) **500** for transporting banknotes that move inside the transport tube **400**, and keeping parts **450** as tributaries that are provided at a plurality of places along the transport path **401** and that keep a banknote to be transferred onto the transport body **500**, the receiving units **600** that are each arranged at each of the keeping parts to receive a banknote P input one by one from outside and to move the received banknote P to the associated keeping part **450**, driving devices (such as a transport mechanism **620**) that drives driving targets such as the banknote transport device C and the receiving units **600**, the safe unit **700**, and the controlling unit (the management unit) **800** that controls these components, in addition to the air blowing tube **100** that forms a flow path of a gas, the moving body **200**, the air-blow control unit **300**, the blower **310**, and the like.

(165) The moving body **200** includes the moving body magnetic material **213**, and the transport body **500** includes the transport body magnetic material **523**. At least one of the moving body magnetic material and the transport body magnetic material is a magnet, and the transport body is moved in conjunction with movement of the moving body receiving the air flow due to attraction and/or repulsion based on a magnetic force acting between the moving body magnetic material and the transport body magnetic material.

(166) While the transport path **401** as the transport body route extends as a linear route in the present embodiment, this is an example and the transport path **401** may be configured to form a loop including rounded routes.

(167) While each of the receiving units **600** is included in the associated sandwiched machine **2** illustrated in FIG. **1** and the game machine **1** is arranged at a location adjacent to each of the sandwiched machines **2** on the bank facilities L in actual game holes, explanations of the game machines are omitted in the present embodiment.

(168) Each of the receiving units **600** includes a banknote receiving part (paper sheet receiving part) **605** that receives an input banknote, an introducing part **610** that sequentially transfers (guides) the banknote input to the banknote receiving part **605** to the associated keeping part **450**, the transport mechanism **620** (details are not illustrated) such as a roller, a belt, and a motor constituting the introducing part **610**, and the like.

(169) The transport body **500** moving in the transport path **401** includes the banknote collecting/retaining part (transfer unit) **540** that sequentially collects a banknote stopping at each of the keeping parts **450** in the process of passing the keeping parts with which the receiving units **600** are respectively communicated, transfers the banknote on the transport body in an upright state, and retains the banknotes in a stacked manner. The banknote collecting/retaining part has a configuration to retain banknotes with one face (a side surface) of a following banknote stacked on one face (a side surface) of preceding banknotes that have already been transferred thereon.

(170) The transport path **401** extends between a right end portion (an initial position) in FIGS. **11** to **14** and a banknote discharge position inside the safe system **700**, and transport body sensors (photosensors, not illustrated) are arranged at places in the transport path **401**, respectively, to check in real time the current location of the transport body **500** in the transport path **401**, whether the transport body has passed, and the timing of passage. For example, transport body detecting sensors are arranged at appropriate places such as the initial position, each of the keeping parts **450**, and the safe system **700**, respectively. Moving body sensors for detecting the location of the moving body **200**, whether the moving body has passed, and the timing of passage are also arranged at places in the longitudinal direction of the air blowing tube **100**, respectively.

(171) When the sensor in the keeping part **450** in a certain receiving unit **600** detects that there is no banknote in the keeping part, the controlling unit **800** drives the transport mechanism **620** of the

introducing part **610** to transfer the following banknote input to the banknote receiving part to the keeping part, and stops the transport mechanism when movement to the keeping part is detected and confirmed. When input of the following banknote to the banknote receiving part **605** is detected while a banknote kept in the keeping part **450** is detected, the controlling unit **800** drives the transport mechanism **620** of the introducing part **610** to receive the banknote and stops the banknote in the introducing part. Therefore, a user of the game machine can uninterruptedly input two paper sheets such as banknotes and the waiting time can be shortened.

(172) <<Receiving Unit **600**>>

(173) As illustrated in FIGS. **15** to **18**, each of the receiving units (the banknote receiving devices) **600** includes the banknote receiving part (banknote receiving port) **605** that is provided at the front of a body **601** of the receiving unit and that receives a banknote input one by one, and the introducing part **610** that is arranged from the banknote receiving part **605** to the inside of the body **601** and that introduces the received banknote into the associated keeping part **450**. The introducing part **610** schematically includes an introducing route **612** that is a space for sequentially transferring (guiding) a banknote input into the banknote receiving part **605** to the keeping part **450**, and the transport mechanism **620** constituted of a roller, a belt, a pulley, a gear, a motor, and the like arranged along the introducing route.

(174) A recognition unit **630** that recognizes and judges authentication of an input banknote, denomination thereof, and the like is provided in the introducing part **610** and the controlling unit **800** reverses the transport mechanism **620** to discharge a banknote from the banknote receiving part **605** when the banknote is not to be received. The banknote that is judged to be receivable by the recognition unit **630** is transported by the transport mechanism **620** in the introducing part **610** to the associated keeping part **450**.

(175) The introducing route **612** includes a first introducing route part **613** that extends from the banknote receiving part **605** to the transport path **401** to be orthogonal thereto, a second introducing route part **615** that is communicatively connected to the first introducing route part **613** to extend in the retracting direction R that is a direction substantially parallel to the transport path **401** and away from the safe unit **700**, and an inversion path (inversion part) **619** that is formed on an outer periphery side of an inversion roller **617** arranged at a termination portion of the second introducing route part **615** and that causes the second introducing route part **615** to be communicated with the keeping part **450** as illustrated in FIGS. **17** and **18**. The inversion path **619** is directly communicated with the keeping part **450** and a banknote passing through the inversion path enters the keeping part **450** and stops in the keeping part **450**. The inversion path **619** is latched between the outer periphery of the inversion roller **617** and a transport guide plate **619a** that is arranged to be opposed to the outer periphery with a predetermined transport space away therefrom.

(176) The keeping part **450** is a space formed in a body **455** to transport and keep a banknote, and is formed of a guide plate **460** on the side of the transport path **401** and another guide plate **465** arranged with a predetermined transport space away from the guide plate **460**. The keeping part **450** is designed to have a length and a shape that enable a longest banknote in the long edge direction to be kept therein while the extended attitude parallel to the transport path **401** is maintained in a state where the rear end edge of the longest banknote has passed through the inversion path **619**. The banknote kept in the keeping part needs to be positioned in such a manner that the banknote can be transferred from the keeping part onto the transport body (banknote carrier) **500** while the collecting pawls **544** press the rear end edge of the banknote in the forward direction P in contact therewith when the transport body passes the keeping part. The rear end of the banknote kept in the keeping part is configured to be sufficiently separated from inversion driving means such as the inversion roller **617**, so that the banknote can be continuously kept without influences of the inversion roller or the like even when the inversion roller is driven.

(177) As illustrated in FIG. **18**, a tracking sensor S1 that detects entry of a banknote is installed in

the banknote receiving part **605**, and other tracking sensors **S2** to **S5** are provided at appropriate places on the downstream side, for example, the entrance and the exit of the recognition unit **630**, the connection portion between the first introducing route part **613** and the second introducing route part **615**, and the inversion path **619**, respectively.

(178) A sensor **S6** that detects entry of a banknote from the inversion path **619** and sensors **S7** that detect collection of a banknote from the keeping part are arranged in the keeping part **450**.

(179) The first introducing route part **613** includes an entrance route part **613a** including the recognition unit **630**, and a keeping route part **613b** for the following banknote on the downstream side. A banknote that is judged to be receivable on the basis of recognition information obtained when the banknote passes the recognition unit **630** moves to the keeping route part **613b** and is transported into the keeping part **450** through the second introducing route part **615** and the inversion path **619** when the sensors **S6**, **S7**, and the like detect no preceding banknote kept in the keeping part **450**. The range of the keeping location for the following banknote may reach the inversion path **619** beyond the keeping route part **613b**.

(180) At the time when the sensors **S6**, **S7**, and the like detect that the banknote front end or the banknote rear end has reached the adequate keeping location after passage of the banknote rear end through the inversion path **619**, the banknote is stopped in transportation and shifts to a standby state. The location of the banknote rear end at the time when the banknote has shifted to the standby state is set to a location where the rear end is not in contact with a transport unit on the side of the introducing part **610**, such as the inversion roller **617** constituting the inversion path, whereby the banknote can maintain the stopped state without interference even when the transport mechanism on the upstream side, including the inversion roller, is driven to transport the following banknote. For example, even when the following banknote is judged to be unreceivable by the recognition unit **630** and the transport mechanism including the first introducing route part **613** and the second introducing route part **615** is accordingly inversely driven, the location of the banknote stopped in the keeping part, and the operation thereof are not affected.

(181) When a banknote **P1** in the keeping part is collected by the transport body **500** and it is detected that no banknote is in the keeping part, a following banknote **P2** having been kept in the route part **613b** or **615** on the upstream side of the inversion path **619** is sent into the keeping part **450** through the inversion path by redriving of the transport mechanism including the inversion roller **617**.

(182) <<Transport Body (Banknote Collecting Shuttle)>>

(183) FIGS. **19(a)**, **19(b)**, **19(c)**, and **19(d)** are an exterior perspective view, a front view, a plan view, and a sectional view along A-A in FIG. **19(a)** of the transport body **500** in a state where the collecting members (the collecting pawls) are opened. FIGS. **20(a)** and **20(b)** are an exterior perspective view and a plan view of the transport body **500** in a state where the collecting members (the collecting pawls) are closed. FIG. **21** is a partial sectional view illustrating the location relation between the transport tube **400** and the transport body **500**. FIGS. **22(a)**, **22(b)**, **22(c)**, and **22(d)** are plan horizontal sectional views illustrating a procedure in which the collecting members enter the keeping part to collect a kept banknote in the process of the transport body **500** moving forward. FIG. **23** is a plan horizontal sectional view illustrating a state where one of the collecting pawls deforms in the process of the transport body moving backward.

(184) The transport body **500** illustrated in FIGS. **19** to **21** are slightly different from the transport body illustrated in FIG. **6** in the configurations of the transport base **510** and the collecting members **544**.

(185) That is, the transport base **510** has a configuration in which the divided pieces **520** are coupled to each other with the hinges **521** to be displaceable in the upper-lower or right-left direction (or an oblique direction) and the transport body magnet (the transport body magnetic material) **523** is arranged in an internal space **520a** of each of the divided pieces illustrated in FIG. **19(d)**. A rotatable roller **525** is also arranged on both side surfaces of each of the divided pieces **520**

to enable smooth movement in the transport tube **400**. Rollers **545** are rotatably arranged on an upper portion of the support member **541** to reduce resistance with the inner wall of the transport tube.

(186) The banknote collecting/retaining part (transfer unit) **540** retains banknotes P to cause the long edge direction of the banknotes P to be in parallel to the longitudinal direction of the transport tube **400** and in an upright attitude. A long side on the lower side of the banknote P horizontally long and in the upright attitude is supported by the upper surface (the flat surface) of the transport base **510** (the divided pieces **520**). The rear end edge (one of short sides) of the banknote is supported by the support member **541** and the collecting members **544**.

(187) While projections **520b** preventing dropping of banknotes are provided on each of the divided pieces **520** on both end edges in the width direction, respectively, a region **520c** on the inner side of the projections **520b** is a flat surface and can stably support the long side on the lower side of the banknote. Since the regions **520c** on the inner sides of the divided pieces **520** are communicated with each other in the longitudinal direction, the banknote can be loaded across the inner regions **520c** of plural divided pieces.

(188) The banknote collecting/retaining part **540** erected on the transport base **510** includes, at an end portion on the bank end side in the longitudinal direction of the transport tube **400** (on the distal end side with respect to the safe unit **700**), the support member **541** that is upright in a direction away from the air blowing tube **100**, and the collecting members **544** including the two collecting pawls **544** that are protruded (spread) in the width direction from the support member **541** in a wing-like manner (at an acute angle or an obtuse angle) in plan view and that are pivotally supported by a pivotally support part **541a** on the side of the support member **541** to be openable/closable in the horizontal direction. Since the illustrated pivotally support part **541a** is in parallel to the support member **541**, that is, in a vertical attitude, the collecting pawls **544** rotating on the pivotally support part horizontally open and close. The rotation direction of the collecting pawls may be other directions.

(189) A pair of the collecting members **544** are arranged at a predetermined height location of the support member **541** unlike the configuration example of FIG. 6 in which upper and lower two pairs of the collecting members are arranged. The two collecting pawls **544** constituting the collecting members **544** are at the maximum open angle in the spread state illustrated in FIGS. 19 and cannot rotate in the opening direction any more while they can rotate in the closing direction from the spread state. FIG. 20 illustrate a state (closed state) in which the two collecting pawls **544** are at the minimum open angle. Each of the collecting pawls **544** is always elastically biased in the opening direction by a spring (an elastic member) **541b** provided on the pivotally support part **541a**. When the transport body **500** moves in the forward direction P toward the safe unit **700** on the transport path **401**, each of the collecting pawls **544** maintains the spread position with the spring **541b** and the collecting pawls can therefore catch the rear end edge of a banknote stopped in the upright state in each of the keeping parts **450** to transfer the banknote onto the transfer base **510** while moving the banknote in the forward direction P in the keeping part. Concave portions **405** (FIGS. 16 and 21) serving as collecting pawl passages are formed at places that are both inner walls of the transport tube **400** and that are passed by the collecting pawls to enable the collecting pawls **544** to maintain the spread position in the process of the transport base **510** moving in the transport path **401** in the forward direction P toward the safe unit **700**, respectively. The concave portions **405** in each of the keeping parts **450** are laid out to enable each of the collecting pawls to be brought into contact with the rear end edge of the banknote in the keeping part. It is preferable that the collecting pawls **544** are configured to independently perform the opening/closing operation. In such a case, each of the collecting pawls may be constituted of one coil spring (or a torsion spring) to individually rotate, or the spring **541b** may be provided for each of the collecting pawls.

(190) Each of the collecting pawls **544** in the spread state illustrated in FIG. 19 includes a base end piece **544a** on the inner side, which is pivotally supported by the pivotally support part **541a** to be

capable of rotating, an intermediate piece **544b** extending outward in the width direction of the transport body from the base end piece **544a**, and an end portion piece **544c** bent or curved to be protruded in a diagonally forward direction from the intermediate piece **544b**. When the collecting pawls **544** pass in the keeping part **450**, the intermediate piece **544b** and the end portion piece **544c** mainly enter the keeping part **450** and push the whole banknote in the forward direction while being in contact with the rear end edge of the kept banknote. If the banknote rear end edge being in contact with the intermediate piece **544b** is about to be deviated outward in the width direction along the face of the intermediate piece, the end portion piece **544c** can reliably block the deviation because the end portion piece **544c** is protruded obliquely from an end portion of the intermediate piece **544b**. After the kept banknote is transferred onto the transport base **510**, the end portion piece **544c** prevents the loaded banknotes from being deviated in the width direction or dropping.

(191) With the configuration of the intermediate piece **544b** to have an attitude parallel to the width direction of the transport path **401** or oblique to the forward direction P in the spread position of the collecting pawls **544** as illustrated in FIGS. **19**, the intermediate piece reliably seizes and presses the banknote rear end edge in the forward direction when being brought into contact with the rear end edge in each of the keeping parts.

(192) In this way, the collecting members **544** include a pair of collecting pawls pivotally supported by the support member to be openable and closable in a substantially horizontal direction, and each of the collecting pawls opens and closes between the spread position protruded outward in the width direction and the retracted position retracted inward in the width direction and is biased toward the spread position by the elastic member.

(193) Since each of the collecting pawls **544** has the configuration described above, only linearly moving the transport body at the time of collecting banknotes in the keeping parts that are alternately positioned at different locations in the longitudinal direction across the transport path **401**, enables the banknotes to be reliably collected by the associated collecting pawl and to be accumulated in a central portion of the transport body in the width direction.

(194) When the transport body **500** moves in the retracting direction R in the transport path, the collecting pawls interfere with banknotes in the keeping parts. However, the collecting pawls change the position in the closing direction against the biasing of the elastic member in the process of continuing to move in contact with the banknotes. Accordingly, the transport body **500** can smoothly continue to move in the return direction without providing impact such as damages on the kept banknotes.

(195) Since the method of sequentially loading a collected following banknote with one face of the following banknote stacked on one face (one side surface) of already loaded banknotes in a state where banknotes are already loaded on the transport base **510** in the upright state is adopted, a situation in which the front end edge of the following banknote hits the rear end edge of the already loaded banknotes to disable the loading does not occur.

(196) As illustrated in FIGS. **18**, **22**, **23**, and the like, the guide plate **460** is provided between each of the keeping parts **450** and the transport path **401** as a partition that separates these parts from each other, and an opening part **460a** for extracting a banknote to the transport path **401** is provided at an end portion of the guide plate **460** in the forward direction. A slit (not illustrated) through which the associated collecting pawl **544** can pass is formed on the guide plate **460** in parallel to the banknote transport direction, thereby preventing the guide plate **460** from blocking the collecting pawl during passage in the keeping part. A slit (not illustrated) through which the associated collecting pawl **544** can pass is also formed on the other guide plate **465** in parallel to the banknote transport direction, thereby preventing the guide plate **465** from blocking the collecting pawl during passage in the keeping part.

(197) In the process of the banknote in the keeping part being pushed at the rear end edge by the collecting pawl to move in the forward direction P, the front end of the banknote protrudes from the opening portion **460a** toward the transport path **401** and separates from the keeping part. An

inclined surface **460b** that guides the banknote toward the transport path at that time to enable the banknote front end edge to be reliably guided to the side of the transport path is provided on the opening portion (FIGS. **19**, **22**, and **23**).

(198) In this way, in the process of the banknote in each of the keeping parts **450** being pushed by the collecting pawl to move inside the keeping part toward the transport path **401**, the movement is always from the front end portion of the banknote and along the longitudinal direction. That is, due to the guide plate **460**, the banknote kept in the keeping part cannot move in a direction orthogonal to (approaching) the transport path **401** and moves from the opening portion **460a** onto the transport body while moving in the forward direction P along the longitudinal direction of the keeping part. Furthermore, the banknotes already loaded on the transport body and the banknotes kept in the keeping parts are previously set in the location relation to be at the same height location and in the same attitude with the guide plate **460** interposed therebetween, and are arranged in such a manner that the respective locations in the banknote thickness direction (the width direction of the transport path) are reliably displaced (to prevent the banknotes from interfering with each other). Accordingly, when transfer of the banknote pushed out from the opening portion **460a** onto the transport body is completed, the banknote is smoothly loaded on one side surface of the already loaded banknotes to be stacked thereon. Therefore, failure in the loading such as deviation or dropping due to hit of the end edges of the banknotes never occurs.

(199) As described above, the kept banknotes in the keeping parts and the loaded banknotes on the transport body are in the location relation not interfering with each other, and only the collecting pawls **544** on the transport body are in the location relation that can interfere with the kept banknotes. Therefore, when the collecting pawls enter the space of each of the keeping parts, the collecting pawls can catch the banknote rear end in the keeping part, push the banknote in the forward direction from the kept location to cause the front end edge of the banknote to be protruded from the opening part **460a**, and finally transfer the whole banknote onto the transfer body.

(200) The collecting pawls **544** are configured to be able to individually rotate (retract) in the closing direction against the spring **541b** when the collecting pawls **544** are brought into contact with an obstacle (banknotes in the keeping parts **450**) in the process of the transport base **510** moving in the transport path **401** in the retracting direction R away from the safe unit **700**, and to return to the original spread position after passing the obstacle. Accordingly, even when one of the collecting pawls **544** is brought into contact with a banknote P1 in one keeping part **450** located on the passage route in the process of the transport base **510** moving in the retracting direction R, this collecting pawl passes the banknote while retracting in the closing direction in the process of moving in contact with the banknote. Therefore, the transport base **510** can smoothly move (see FIG. **23**).

(201) As illustrated in FIG. **16**, the concave portions **405** are formed on two opposing inner walls of the transport path **401**, respectively, to enable the two collecting pawls **544** to smoothly pass through. The concave portions **405** are convex portions when seen from outside. While the concave portions **405** are formed on almost the entire length of the transport path **401** (almost the whole of the moving route of the transport body **500**), the concave portions **405** are not provided at places where the receiving units **600** are arranged, that is, in a range interfering with the keeping parts **450**. That is, convex wall portions of the transport path constituting the concave portions **405** are not provided in each of the exterior bodies **455** (FIGS. **16** and **18**) including the associated keeping part **450** therein. A banknote in the kept state is arranged in the space in the exterior body **455** forming each of the keeping parts **450**. Therefore, if the convex wall portion constituting each of the concave portions **405** extends to the inside of each of the keeping parts, the wall portion interferes with the space for keeping the banknote. In the exterior body **455** of the keeping part, the slits for avoiding the collecting pawls are formed on the guide plates **460** and **465** forming the keeping part. Accordingly, the collecting pawls entering the exterior body can be brought into contact with the kept banknote and transport the banknote.

(202) A procedure in which the transport body (the banknote collecting/retaining part **540**) collects banknotes stopping in the keeping parts **450** in the process of moving on the transport path **401** in the forward direction P toward the safe unit is explained next with reference to FIG. **22**.

(203) In a state illustrated in FIG. **22(a)**, while a portion of about two-thirds of the transport body **500** from the head of the transport base **510** reaches a location overlapping with the keeping part **450**, the support member **541** is located behind the keeping part and accordingly the collecting pawls **544** are also behind the keeping part. In FIGS. **22(b)** and **22(c)**, the support member **541** approaches more to the keeping part **450** than in FIG. **22(a)** while the collecting pawls **544** are still outside the keeping part. In FIG. **22(d)**, the support member **541** enters the keeping part and, when there is a banknote in the keeping part, the collecting pawl **544** on the side of the keeping part is in contact with the rear end edge of the banknote and moves the banknote in the width direction of the transport path **401** while pushing the banknote in the forward direction P. Therefore, the banknote P is transferred (collected) onto the transport base **510** while keeping the upright attitude. When there are banknotes already transferred on the transport base, the banknote P is loaded to be stacked on the lateral side of the already loaded banknotes.

(204) When the transport body **500** passes this keeping part **450** to collect a banknote in the subsequent keeping part located downstream in the moving direction, the collecting pawl **544** located on the side of the next keeping part collects the banknote.

(205) FIG. **23** illustrates a state where one of the collecting pawls **544** rotates in the closing direction to avoid the banknote P stopping in the keeping part **450** in the process of the transport body **500** moving in the transport path **401** in the retracting direction R away from the safe.

(206) With the banknote transport system according to the present invention, even when the transport body is moved at a high speed, a banknote retained in each of the game media dispensing devices (the receiving units) can be reliably and promptly collected and transferred onto the transport body and, at the same time, a plurality of banknotes can be stably transported without paper sheet jam while retained in an aligned manner.

(207) <<Collecting Procedure for Paper Sheets by Transport Body>>

(208) In the banknote transport system **10** having the configuration described above, various types of processing described below can be performed depending on the relation with the keeping parts **450** and whether there is a banknote in the introducing part **610**.

(209) FIG. **24** is a flowchart illustrating an example of a collecting procedure and an introducing procedure for banknotes by the transport body.

(210) When it is detected that a banknote is stopping in a certain keeping part **450** and there is no banknote in the associated introducing part **610** (YES at Step S1), and when it is detected that a following banknote has been newly input to the receiving unit (the banknote receiving device) **600** corresponding to the keeping part (YES at Step S3), the controlling unit **800** controls relevant components to receive the following banknote in the introducing part **610** and stop (keep) the banknote inside the introducing part (Steps S5, S7, and S9).

(211) This enables any place in the introducing part **610** on the upstream side of the keeping part **450** to be used as a keeping part for the following banknote, and the second banknote can be therefore input in a state where no banknote is in the keeping part.

(212) FIG. **25** is a flowchart illustrating another example of the collecting procedure and the introducing procedure for paper sheets by the transport body.

(213) When it is detected that different banknotes are simultaneously in the kept state in any one of the keeping parts **450** and in the introducing part **610** on the upstream side of this keeping part, respectively (YES at Steps S11 and S13), the controlling unit **800** controls relevant components to enable the banknote in the keeping part **450** to be collected by scanning the transport body **500** once from the initial position to the location of the safe system **700** using the moving body **200** (Step S15) and to enable the banknote in the introducing part **610** to move into the keeping part **450** (Step S17).

(214) When banknotes are kept in the keeping part **450** and the introducing part **610**, respectively, the third banknote cannot be input. However, the control described above enables the introducing part **610** to be emptied and the third banknote to be input therein.

(215) FIG. **26** is a flowchart illustrating another example of the collecting procedure and the introducing procedure for paper sheets by the transport body.

(216) When it is detected that banknotes are in the kept state in all the keeping parts **450** or when it is detected that banknotes are kept in a predetermined number of or more (for example, ten or more) keeping parts, respectively (YES at Step **S21**), the controlling unit **800** causes the transport body **500** to scan once from the initial position to a location near the safe system **700** using the moving body **200** (Step **S23**). Accordingly, the controlling unit **800** controls relevant components to collect the banknotes in the keeping parts **450** and, when there are banknotes in the introducing parts **610**, move these banknotes into the associated keeping parts, respectively (Steps **S25** and **S27**).

(217) This can reduce the waiting time in which banknotes cannot be input and can increase the convenience of users.

(218) C. Paper Sheet Transport System and Restoration Method According to Third Invention

(219) The banknote (paper sheet) transport system and the restoration method according to a third invention are explained next.

(220) FIGS. **27(a)** and **27(b)** are a front vertical sectional view of portions of the air blowing tube **100** and the transport body route **401** on the side of the initial position in the banknote transport system according to the third invention, and a front vertical sectional view of portions thereof on the side of the safe system (the bank end unit). FIGS. **28(a)** and **28(b)** are a front view illustrating a state where the moving body causes the transport body to normally travel for collection of banknotes, and a front view illustrating a state where the moving body solely travels ahead because the transport body has stopped. FIGS. **29(a)** and **29(b)** are front views for explaining a control procedure for restoration.

(221) The third invention is explained while referring also to FIGS. **1** to **26** related to the first and second inventions and parts equivalent to those in the first and second inventions are denoted by like reference signs.

(222) Illustrations of the wall portions (tube walls) respectively constituting the air blowing tube and the transport body route are omitted in FIGS. **28** and **29**.

(223) The banknote transport system **10** according to the third invention includes the air flow generating device (the blower) **310**, the air blowing tube **100** that forms therein a flow path of an air flow generated by the air flow generating device, the switching unit **320** that controls the direction of the air flow in the air blowing tube, the controlling unit **800** that controls the air flow generating device **310** and the switching unit **320**, the moving body **200** that travels inside the air blowing tube while receiving an air flow flowing in a predetermined direction within the air blowing tube **100**, the transport body route **400** (**401**) that has at least a portion arranged along the air blowing tube to be adjacent to the air blowing tube, and the transport body **500** that is configured to be able to retain banknotes and that travels inside the transport body route.

(224) The moving body **200** includes the moving body magnetic material **213**, and the transport body **500** includes the transport body magnetic material **523**. The system includes a configuration to, using repulsion based on a magnetic force acting between the moving body magnetic material and the transport body magnetic material when the moving body and the transport body are in a predetermined close location relation (docking location relation), move the transport body in conjunction with movement of the moving body while maintaining the close location relation.

(225) When the moving body **200** separates from the range of the close location relation with the transport body **500** due to stop of the transport body in the middle of the transport body route because of a failure such as jam, the controlling unit **800** causes the moving body to travel in a direction further away from the transport body and to temporarily stop while stopping the transport

body at a predetermined end portion stop position. Subsequently, the controlling unit **800** causes the moving body to travel toward the transport body (the end portion stop position) at a speed resistible against the repelling force between the magnetic materials, thereby returning the moving body into the range of the close location relation.

(226) More specifically, when the moving body **200** moves ahead and separates from the range of the close location relation due to suspension of the transport body **500** in the process of the moving body moving the transport body that is in the close location relation in a predetermined direction (the forward direction P or the retracting direction R), the controlling unit **800** causes the moving body to move the transport body in the opposite direction to the original travel direction to stop at the predetermined end portion stop position. The controlling unit **800** subsequently causes only the moving body to travel in the direction further away from the transport body, to temporarily stop, and then to travel toward the transport body at a speed resistible against the magnetic repelling force, thereby returning (restoring) the moving body into the range of the close location relation.

(227) In the banknote transport system **10** according to the present invention, there is a region in which the air blowing tube **100** and the transport tube **400** are arranged in parallel to each other in a close upper-lower location relation as illustrated in FIG. **27**. In this parallel arrangement region, the moving body **200** and the transport body **500** can have a proximate upper-lower location relation (the close location relation) as illustrated in FIG. **28** with the tube walls respectively constituting the air blowing tube and the transport tube interposed therebetween. When the moving body and the transport body are in the close location relation, the close location relation can be maintained (these bodies can be docked) with the repelling force (or the attracting force) between the magnetic materials **213** and **523** included in the moving body and the transport body, respectively, and the transport body can be synchronously moved in conjunction with the motion of the moving body.

(228) At the upstream end (the initial position) of the banknote transport system **10** illustrated in FIG. **27(a)**, the air blowing tube **100** and the transport tube **400** are docked in the proximate upper-lower location relation with the respective tube walls thereof interposed therebetween. In this docked state, the transport body **500** moves in the transport tube **400** to follow the moving body **200** in conjunction with the advancing/retracting motion thereof.

(229) A stopper **130** that stops and prevents the moving body from moving any more in the upstream direction (the retracting direction R) is arranged at an upstream end portion of the air blowing tube **100**. Similarly, a stopper **410** that stops and prevents the transport body **500** from moving any more in the upstream direction is arranged at an upstream end portion of the transport tube **400**.

(230) Also in the safe system (the bank end unit) illustrated in FIG. **27(b)**, a stopper **131** that stops and prevents the moving body from moving any more in the downstream direction is arranged at a downstream end portion of the air blowing tube **100** similarly at the upstream end portion.

Similarly, a stopper **411** that stops and prevents the transport body **500** from moving any more in the downstream direction is arranged at a downstream end portion of the transport tube **400**. When the transport body is stopped by the stopper **411** at the downstream end portion, the moving body stopped by the stopper **131** is positioned (docked) at a substantially central portion of the transport body in the longitudinal direction.

(231) A control procedure (a restoration method) for position adjustment between the moving body and the transport body, which is the characteristic of the third invention, is explained next with reference to FIGS. **28**, **29**, and **30**.

(232) FIG. **30** is a flowchart illustrating the restoration method for the moving body and the transport body by the banknote transport system **10**.

(233) In the docked state illustrated in FIG. **28(a)**, the moving body **200** travels in the forward direction P, whereby the transport body **500** located immediately thereabove moves in the same direction in conjunction therewith. At the time of banknote collection, the transport body **500** travels in the same direction while collecting a banknote in each of the keeping parts **450** at

locations where the receiving units **600** described in the second invention are respectively arranged (Step S1 in FIG. 30). However, if a banknote has a deformed portion such as a creased portion, the deformed portion may be caught by a curved route of the transport tube **400**, a joint of the tube wall constituting the transport tube, or the like, resulting in jam of the banknote. In this case, the transport body stops traveling due to resistance of the jammed banknote P. When the transport body suddenly stops, a situation occurs in which the transport body cannot move forward any more from the stopped position (halfway stop position) while the moving body rapidly traveling separates from the range of the close location relation against the repelling force based on the magnetic force, so that only the moving body moves ahead of the transport body (YES at Step S2 and YES at Step S3 in FIG. 30) as illustrated in FIG. 28(b).

(234) In this case, at the time when it is detected that only the transport body **500** that is supposed to travel with the moving body stops halfway, the controlling unit **800** stops air blowing by the air-flow control apparatus **300** (the blower **310**) to prevent damages of banknotes, so that the moving body **200** moving ahead is stopped. Thereafter, an operator performs jam processing such as removal of the banknotes from the transport body (Step S4) and the restoration operation to return the moving body to the proximity location to the transport body as illustrated in FIG. 28(a) is subsequently performed.

(235) A distance L1 illustrated in FIG. 28(b) indicates a distance with which the moving body that cannot crawl in a location (the close location) immediately below the transport body due to the repelling force applied between the magnetic materials **213** and **523** can most approach the transport body.

(236) The distance between the transport body and the moving body sometimes exceeds the distance L1 at a time when the moving body is stopped in association with halfway stop of the transport body **200**. Even when the moving body is moved from this separation location toward the transport body, the distance L1 cannot be reduced.

(237) In the restoration operation, the moving body separated from the transport body by at least the distance L1 as in FIG. 28(b) needs to be moved back toward the transport body to be returned to the normal location as illustrated in FIG. 28(a). However, since the repelling force between the magnetic materials is quite strong, the transport body moves away from the moving body when the moving body is attempted to be brought close to the transport body stopping halfway, and the distance L1 cannot be reduced, as explained in association with FIG. 34. Therefore, it is difficult to perform location relation restoration (docking) to the transport body stopping halfway by a usual method. Even when the transport body is moved by the moving body to the end portion stop position where the stopper **410** is installed and is stopped, and then the moving body is brought close to the transport body at a normal traveling speed to reduce the separation distance, it is impossible to enter the range of the close location against the strong magnetic repelling force.

(238) In contrast thereto, according to the present invention, when the moving body **200** (the moving body magnetic material **213**) and the transport body **500** (the transport body magnetic material **523**) separate from the range of the close location relation as illustrated in FIG. 28(b), control for restoration described below is executed. That is, banknotes on the transport body **500** halfway stopped are first removed (Step S4 in FIG. 30). Next, by moving the moving body **200** in the retracting direction R with power of wind from the blower **310**, the transport body **500** located in the middle of the transport body route, that is, at a halfway stop position is stopped at the predetermined end portion stop position, that is, the initial position illustrated in FIG. 29(a) to inhibit the movement in the retracting direction R with the stopper **410** (Step S5 and YES at Step S6). Subsequently, the moving body **200** at a location separated from the transport body by the distance L1 as in FIG. 28(b) is caused to travel in the direction P further away from the transport body **500** and is temporarily stopped at a predetermined location (a location of a distance L2) (FIG. 29(a), Step S7 and YES at Step S8 in FIG. 30). Meanwhile, the transport body stays at the end portion stop position. Subsequently, the moving body is caused to rapidly travel toward the

transport body at a speed resistible against the repelling force between the magnetic materials, so that the moving body can be returned into the range of the close location relation as illustrated in FIG. 29(b) (Step S9, and YES at Step S10). The moving body is stopped when reaching the range of the close location relation (Step S11).

(239) The motion states of the moving body and the transport body (whether these bodies are traveling or stopping, the timing thereof, and the travel directions), the current locations thereof, and the like are judged based on detection information from various sensors installed at appropriate places on the air blowing tube 100, the transport body route 400, and the like. The traveling speed of the moving body can be controlled by the air-flow control unit 300.

(240) The above processing is the restoration processing performed in a case in which a situation where the transport body stops in the process of the moving body causing the transport body to travel in the forward direction P, and where the moving body separates from the range of the close location relation occurs.

(241) The same situation and the same need for the restoration processing as described above may also occur in a process of the transport body traveling in the retracting direction R from the safe unit 700 to the initial position.

(242) That is, when reaching the safe unit 700, the transport body 500 transfers all loaded banknotes onto the safe unit with a banknote transfer device (not illustrated), and thereafter starts moving in the retracting direction R to return to the initial position. Also in the process of moving in the retracting direction, a situation in which the transport body stops due to some reason, and the moving body moving ahead separates from the range of the close location relation is envisaged.

(243) FIGS. 31(a) and 31(b) are a front view illustrating a state where the moving body causes the transport body to normally travel to return to the initial position after collection of banknotes and transfer of banknotes to the safe unit are completed, and a front view illustrating a state where the moving body solely travels ahead because the transport body has stopped. FIGS. 32(a) and 32(b) are front views for explaining a control procedure (a restoration method) for restoration.

(244) In this case, at the time when stop of the transport body that is supposed to travel is detected, the controlling unit 800 stops the moving body by stopping the air-flow control apparatus 300 (the blower 310) to prevent damages of banknotes. Subsequently, an operator removes or solves the cause that has stopped the transport body and then the restoration operation for returning the moving body to the proximity location to the transport body as illustrated in FIG. 31(a) is performed.

(245) In the restoration operation, control for restoration described below is executed. That is, by driving the blower 310 to move the moving body 200 in the retracting direction R with the air flow, the transport body 500 at the halfway stop position in the transport body route illustrated in FIG. 31(b) is stopped at the predetermined end portion stop position, that is, the end portion stop position on the side of the safe unit illustrated in FIG. 32(a) to inhibit movement in the forward direction P with the stopper 411. Next, the moving body 200 at a location away from the transport body is caused to travel in the direction R further away from the transport body 500 as in FIG. 32(a) and is temporarily stopped at a predetermined location (the distance L2). Meanwhile, the transport body stays at the end portion stop position. Subsequently, the moving body is caused to rapidly travel toward the transport body at a speed resistible against the repelling force between the magnetic materials, and the moving body is stopped at a time when returned into the range of the close location relation as illustrated in FIG. 32(b).

(246) The value of the speed during high-speed movement of the moving body at the locations illustrated in FIG. 29(a) and FIG. 32(a) toward the transport body, that is, the speed for returning to a location immediately below the transport body while resisting the repelling force between the magnetic materials can be experimentally derived depending on intensities of the magnetic force that produces the repelling force or weights of the moving body.

(247) The speed at the time when the transport body (the moving body) travels in the forward

direction P and the retracting direction R during normal transport of banknotes is 1.5 m/sec to 2.0 m/sec while the traveling speed in the retracting direction R at the time of the restoration operation illustrated in FIG. 29(b) or the traveling speed in the forward direction P at the time of restoration operation illustrated in FIG. 32(b) is 3.0 m/sec to 4.0 m/sec.

(248) This control for the restoration operation may be executed each time stop of the transport body is detected, or may be performed once each time the transport body performs a predetermined number of reciprocations (for example, one reciprocation) on the transport body route.

(249) With the control procedure for restoration described above, when a situation in which the transport body (the transport body magnetic material) stops due to jam or the like during traveling in the predetermined direction and only the moving body (the moving body magnetic material) therefore separates from the transport body to move ahead, whereby movement of the transport body in conjunction with the moving body with the magnetic force is disabled occurs, the moving body can be effectively restored to a location proximate to the transport body.

(250) The moving body **200** illustrated in FIGS. 28 to 32 has a different shape from the moving body illustrated in FIGS. 4, 7, 8, and the like. FIG. 33 is an exterior perspective view of the moving body **200** illustrated in FIGS. 28 to 32. The moving body **200** includes two divided pieces **210**, and a shaft **215** coupling these divided pieces **210**, and the divided pieces are pivotally supported by hinge parts (not illustrated) provided on both end portions of the shaft **215** to be rotatable in the horizontal direction, respectively. The moving body magnet **213** is arranged on the upper surface of each of the divided pieces **210**, and rollers **216** are arranged at four corners of each of the divided pieces to enable smooth movement in the air blowing tube **100**.

(251) [Summary of Configurations, Actions, and Effects of Present Invention]

(252) The paper sheet transport system **10** according to the present invention includes the paper sheet transport device C including the transport body route **401**, the transport body **500** for paper sheet transport, that moves on the transport body route, and a plurality of the keeping parts **450** that are installed along the transport body route and that keep paper sheets to be transferred onto the transport body, the paper sheet receiving devices (the receiving units) **600** that are each arranged for each of the keeping parts to receive paper sheets input one by one from outside and to move the paper sheets to the associated keeping parts, the driving device that drives the paper sheet receiving devices and the paper sheet transport device C, and the controlling unit **800** that controls these components, wherein each of the paper sheet receiving devices includes the introducing part **610** that sequentially transfers (guides) an input paper sheet to the associated keeping part, the transport body includes the paper sheet collecting/retaining part (pickup unit) **540** that collects paper sheets stopped at the keeping parts in the process of passing the keeping parts, transfers the paper sheets onto the transport body, and retains the paper sheets in an upright state, the paper sheet collecting/retaining part includes a configuration to retain the paper sheets with one face of the following paper sheet stacked on one face of the preceding paper sheets already transferred thereon, and the controlling unit causes, when a paper sheet is stopped at each of the keeping parts, the following paper sheet input to the paper sheet receiving device to be received by the introducing part and to be kept therein.

(253) According to the present invention, paper sheets kept in the keeping parts can be picked up and transferred onto the transport body without deceleration in the process of the transport body passing the keeping parts at a high speed. Accordingly, the paper sheet input from each of the receiving units and kept in the associated keeping part can be reliably and promptly collected and transferred onto the transport body. At the same time, a plurality of paper sheets can be stably transported without paper sheet jam while the paper sheets are aligned and retained.

(254) Since the method of loading a paper sheet onto the transport body is a method of stacking the paper sheet on a side surface of already loaded paper sheets on the transport body, a loading failure due to collision with the existing paper sheets, and the like can be prevented. Particularly, paper sheets on the transport body and paper sheets in the keeping parts are configured in such a manner

that the respective locations in the width direction are surely different and do not interfere with each other with the guide plate **460** interposed therebetween and accordingly collision of paper sheets can be reliably prevented. Even when either of the paper sheets has a deformed portion such as a creased portion, the risk of collision can be eliminated.

(255) In the paper sheet transport system **10** according to the present invention, the paper sheet collecting/retaining part **540** includes the support member **541** that is erected on the transport base **510** moving on the transport body route **401**, and the collecting members **544** installed on the support member, and the collecting members include a pair of collecting pawls pivotally supported by the support member to be openable and closable in a substantially horizontal direction. Each of the collecting pawls opens and closes between the spread position protruded outward in the width direction and the retracted position retracted inward in the width direction and is biased toward the spread position by the elastic member.

(256) Only the collecting members of the transport body can be brought into contact with the rear end edge of a paper sheet in each of the keeping parts from behind to push and transport the paper sheet forward in the keeping part, extract the paper sheet from the keeping part into the transport path, and finally stack the paper sheet on the side surface of the already loaded paper sheets. When the transport body returns inside the transport path, the collecting members interfere with the paper sheets in the keeping parts. However, the collecting members change the position in the retracting direction against the biasing of the elastic member in the process of continuously moving in contact with the paper sheets. Therefore, the transport body can smoothly continue to move in the return direction without being affected by the kept paper sheets or affecting the kept paper sheets.

(257) The paper sheet transport system (the transport mechanism) **10** according to the present invention includes the air blowing tube **100** that forms a flow path (the air flow path **101**) of a gas, the moving body **200** that travels inside the air blowing tube while receiving an air flow flowing in a predetermined direction (the arrow-B direction and the arrow-C direction) within the air blowing tube, the transport path **401** (the transport tube **400**) that has at least a portion arranged along the air blowing tube to be adjacent to the air blowing tube, and the transport body **3500** that is configured to be able to retain paper sheets (paper sheets P) and that travels inside the transport path. The moving body includes a moving body magnetic material (the moving body magnets **213**), and the transport body includes a transport body magnetic material (the transport body magnets **523**). At least one of the moving body magnetic material and the transport body magnetic material is formed of a magnet. The paper sheet transport mechanism is characterized in moving the transport body in conjunction with movement of the moving body receiving the air flow due to attraction and/or repulsion based on a magnetic force applied between the moving body magnetic material and the transport body magnetic material.

(258) The moving body is caused to travel with the air flow and the transport body is caused to travel with a magnetic force in conjunction with movement of the moving body. Since no mechanical driving means such as a motor, a gear, and a transport belt are required to cause the moving body and the transport body to travel, the durability of members constituting the transport mechanism can be increased and the running cost of the transport mechanism can be reduced.

(259) When a repelling force is to be applied between the transport body magnetic material and the moving body magnetic material, the transport body is less likely to be in contact with the transport path. As a result, reduction of the transport force due to generation of a frictional force or generation of dust due to contact of the members can be prevented.

(260) Since the air blowing tube and the transport path have separate and independent configurations, an airtight flow path can be formed in the air blowing tube. Air leakage to outside the air blowing tube can be prevented and reduction in the transport force can be therefore prevented. An air flow generating device (the blower **310**) that is relatively inexpensive and outputs low power can be adopted as a device that generates an air flow inside the air blowing tube and reduction in the cost of the transport mechanism is realized. Control of the air flow in the airtight

air blowing tube is easy even when the transport distance of paper sheets is increased.

(261) The air-flow control apparatus (the air-blow control unit **300**) according to the present invention includes the air flow switching unit **320** that includes the first to fourth flow paths (**323a** to **323d**) respectively connecting to external pipes, and the switching valve **325** arranged in a joint portion of the first to fourth flow paths and switching a communication state among the flow paths, the first circulation pipe **330** that has one end portion **330a** communicatively connected to the first flow path **323a** and the other end portion **330b** communicatively connected to the second flow path **323b** to form an air flow path in an endless manner through the air flow switching unit, the air flow generating device (the blower **310**) that is arranged at an appropriate place in the first circulation pipe and that generates an air flow flowing in a certain direction inside the first circulation pipe, and the second circulation pipe (the air blowing tube **100**) that has one end portion **100a** connected to the third flow path **323c** and the other end portion **100b** connected to the fourth flow path **323d** to form an air flow path in an endless manner through the air flow switching unit and that moves the moving body **200** arranged therein in a predetermined direction with the air flow.

(262) The switching valve is characterized in being configured to be able to switch among the neutral position (FIG. 5(a)) for establishing communication between the first and second flow paths, the first communication position (FIG. 5(b)) for generating an air flow flowing in the first direction inside the second circulation pipe by establishing communication between the first and fourth flow paths and communication between the second and third flow paths, and the second communication position (FIG. 5(c)) for generating an air flow flowing in the second direction inside the second circulation pipe by establishing communication between the first and third flow paths and communication between the second and fourth flow paths.

(263) According to the present aspect, while an air flow in a certain direction (the arrow-A direction) is generated by a single air flow generating device, three states including a state where no air flow is generated inside the air blowing tube, a state where an air flow flowing in the first direction (the arrow-B direction) is generated inside the air blowing tube, and a state where an air flow flowing in the second direction (the arrow-C direction) is generated inside the air blowing tube can be switched by changing the position of the switching valve.

(264) The paper sheet transport system (the transport mechanism) **10** according to the present invention includes the air flow generating device **310** that generates an air flow and that can adjust the flow speed and the flow volume of the generated air flow, the air blowing tube **100** that forms therein a flow path of the air flow generated by the air flow generating device, the switching unit **320** that controls the direction of the air flow in the air blowing tube, the controlling unit **800** that controls the air flow generating device and the switching unit, the moving body **200** that travels inside the air blowing tube while receiving the air flow flowing within the air blowing tube, the transport body routes **400** and **401** having at least a portion arranged along the air blowing tube to be adjacent to the air blowing tube, and the transport body **500** configured to be able to retain paper sheets and traveling inside the transport body route, the moving body **200** includes the moving body magnetic material **213**, the transport body includes the transport body magnetic material **523**, a configuration to move the transport body in conjunction with movement of the moving body due to repulsion based on a magnetic force applied between the moving body magnetic material and the transport body magnetic material when the moving body magnetic material and the transport body magnetic material are in a close location relation is included, and when the moving body separates from a range of the close location relation due to halfway stop of the transport body in a process of the moving body moving the transport body in the close location relation in a predetermined direction, the controlling unit causes the moving body to move the transport body in an opposite direction to an original travel direction to stop the transport body at a predetermined end portion stop position, subsequently causes only the moving body to travel in a direction further away from the transport body to temporarily stop the moving body, and then returns the moving body into the range of the close location relation by causing the moving body to travel toward the transport body

at a speed resistible against the repelling force.

(265) The transport body rapidly traveling in the narrow transport body route while having paper sheets loaded thereon is supposed to be stuck and stopped in the middle due to paper sheet jam or some other causes. In this case, the moving body traveling to move the transport body moves ahead beyond the range of magnetic repulsion from the transport body, and these bodies are in a separated state. In the present invention, after the cause of the stop of the transport body is removed, the transport body is moved to the end portion stop position and is stopped to return the moving body to a close location to the transport body. Subsequently, the moving body is moved to a location sufficiently away from the transport body and is then moved toward the transport body at a high speed, thereby being returned into the range of the close location.

(266) Since the work for restoration, which is performed after the cause of the stop of transport body stopped halfway is removed, can be automatically and quickly performed as a series of operations, the operation ratio of the paper sheet transport system is not greatly lowered.

(267) The restoration method in the paper sheet transport system **10** according to the present invention includes a step of causing the moving body to move the transport body in an opposite direction to an original travel direction to stop the transport body at a predetermined end portion stop position when the moving body moves ahead and separates from a range of the close location relation due to halfway stop of the transport body in a process of the moving body **200** moving the transport body in the close location relation in a predetermined direction, a step of subsequently causing only the moving body to travel in a direction further away from the transport body to temporarily stop the moving body, and a step of returning the moving body into the range of the close location relation by causing the moving body to travel from a location of the temporary stop toward the transport body at a speed resistible against the repelling force, in the paper sheet transport system including the configuration described above.

(268) According to this restoration method, the work for restoration, which is performed after the cause of the stop of the transport body stopped halfway is removed, can be automatically and quickly performed as a series of operations. Therefore, the operation ratio of the paper sheet transport system is not greatly lowered.

REFERENCE SIGNS LIST

(269) L bank facility, P banknote (paper sheet), **1** game machine, **2** sandwiched machine, **10** banknote transport system (paper sheet transport mechanism), **100** air blowing tube (second circulation pipe), **100a** one end portion, **100b** other end portion, **101** air flow path, **110** first air blowing tube, **111** moving route part, **120** second air blowing tube, **130**, **131** stopper, **200** moving body, **210** divided piece, **211** hinge part, **213** moving body magnet (moving body magnetic material), **300** air-blow control unit (air-flow control apparatus), **310** blower (air flow generating device), **320** switching unit, **321** casing, **323** flow path, **325** switching valve, **330** first circulation pipe, **330a** one end portion, **330b** other end portion, **331** discharge tube, **333** intake tube, **340** connection pipe, C banknote (paper sheet) transport device, **400** transport tube, **401** transport path (transport body route), **402** base transport path, **403** banknote (paper sheet) transport path, **405** concave portion, **410**, **411** stopper, **450** keeping part, **460**, **465** guide plate, **500** transport body, **510** transport base, **520** divided piece, **520a** internal space, **520b** projection, **520c** inner region, **521** hinge part, **523** transport body magnet (transport body magnetic material), **525** roller, **540** banknote collecting/retaining part, **541** support member, **541a** pivotally support part, **541b** spring (elastic member), **544** collecting pawl (collecting member), **545** roller, **600** receiving unit (paper sheet receiving device), **601** body, **605** paper sheet receiving part, **610** introducing part, **612** introducing route, **613** first introducing route part, **613a** entrance route part, **613b** keeping route part, **615** second introducing route part, **617** inversion roller, **619** inversion path (inversion part), **620** transport mechanism, **630** recognition unit, **700** safe unit, **800** management unit (controlling unit), **801** body

Claims

1. A paper sheet transport system comprising: an air flow generating device, an air blowing tube that forms therein a flow path of an air flow generated by the air flow generating device, a switching unit that controls switching of directions of an air flow in the air blowing tube, a controlling unit that controls the air flow generating device and the switching unit; a moving body that travels inside the air blowing tube while receiving an air flow flowing within the air blowing tube; a transport body route having at least a portion arranged along the air blowing tube to be adjacent to the air blowing tube; and a transport body configured to be able to retain paper sheets and traveling inside the transport body route, wherein the moving body includes a moving body magnetic material, and the transport body includes a transport body magnetic material, a configuration to move the transport body in conjunction with movement of the moving body due to repulsion based on a magnetic force applied between the moving body magnetic material and the transport body magnetic material when the moving body magnetic material and the transport body magnetic material are in a close location relation is included, and when the moving body moves ahead and separates from a range of the close location relation due to halfway stop of the transport body in a process of the moving body moving the transport body in the close location relation in a predetermined direction, the controlling unit causes the moving body to move the transport body in an opposite direction to an original travel direction to stop the transport body at a predetermined end portion stop position, subsequently causes only the moving body to travel in a direction further away from the transport body to temporarily stop the moving body, and then returns the moving body into the range of the close location relation by causing the moving body to travel toward the transport body at a speed resistible against a repelling force.
 2. A restoration method in a paper sheet transport system comprising: an air flow generating device, an air blowing tube that forms therein a flow path of an air flow generated by the air flow generating device, a switching unit that controls switching of directions of an air flow in the air blowing tube; a moving body that travels inside the air blowing tube while receiving an air flow flowing within the air blowing tube; a transport body route having at least a portion arranged along the air blowing tube to be adjacent to the air blowing tube; a transport body configured to be able to retain paper sheets and traveling inside the transport body route; and a moving body magnetic material included in the moving body, and a transport body magnetic material included in the transport body, and including a configuration to move the transport body in conjunction with movement of the moving body due to repulsion based on a magnetic force applied between the moving body magnetic material and the transport body magnetic material when the moving body magnetic material and the transport body magnetic material are in a close location relation, the method comprising: a step of causing the moving body to move the transport body in an opposite direction to an original travel direction to stop the transport body at a predetermined end portion stop position when the moving body moves ahead and separates from a range of the close location relation due to halfway stop of the transport body in a process of the moving body moving the transport body in the close location relation in a predetermined direction; a step of subsequently causing only the moving body to travel in a direction further away from the transport body to temporarily stop the moving body; and a step of returning the moving body into the range of the close location relation by causing the moving body to travel from a location of a temporary stop toward the transport body at a speed resistible against a repelling force.
-