

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12407511
B2
September 02, 2025
Dunjic; Milos et al.

Dynamic implementation and management of hash-based consent and permissioning protocols

Abstract

Computer-implemented systems, apparatuses, and processes that dynamically implement and manage hash-based consent and permissioning protocols. By way of example, an apparatus may obtain consent data that identifies one or more elements of data accessible to an application program executed by a device. The apparatus may generate a consent document for the application program based on at least a portion of the consent data, and may compute a consent hash value representative of the consent document. The apparatus may also generate and transmit permissioning data that includes at least the consent hash value to the device. The permissioning data may, for example, include information that instructs the executed application program to store the consent hash value within a local memory of the device and to associate the consent hash value with an access token of the executed application program.

Inventors: Dunjic; Milos (Oakville, CA), Chow; Arthur Carroll (Markham, CA), Tax; David Samuel (Toronto, CA), Rouhani; Armon (Toronto, CA), Ajmani; Keith Sanjay (Toronto, CA), Kliwer; Gregory Albert (Barrie, CA), Nguyen; Anthony Haituyen (Toronto, CA), Lozon; Martin Albert (London, CA), El-Onsi; Kareem (Toronto, CA), Alavi-Harati; Ashkan (Markham, CA), Jagga; Arun Victor (Mississauga, CA)

Applicant: The Toronto-Dominion Bank (Toronto, CA)

Family ID: 74259469

Assignee: The Toronto-Dominion Bank (Toronto, CA)

Appl. No.: 17/853080

Filed: June 29, 2022

Prior Publication Data

Document Identifier

US 20220360446 A1

Publication Date

Nov. 10, 2022

Related U.S. Application Data

continuation parent-doc US 16528164 20190731 US 11405207 child-doc US 17853080

Publication Classification

Int. Cl.: H04L9/32 (20060101); H04L9/06 (20060101)

U.S. Cl.:

CPC H04L9/3213 (20130101); H04L9/0637 (20130101); H04L9/3242 (20130101);

Field of Classification Search

CPC: H04L (63/0421); H04L (9/3228); H04L (9/3213); H04L (9/0637); H04L (9/3242); H04L (9/0825); H04L (9/3239); H04L (9/3247); G06Q (20/3678)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8505084	12/2012	Shukla et al.	N/A	N/A
9148429	12/2014	Caims et al.	N/A	N/A
9246887	12/2015	Satish et al.	N/A	N/A
9330280	12/2015	Rachalwar et al.	N/A	N/A
9473480	12/2015	Mason et al.	N/A	N/A
9552444	12/2016	Smith et al.	N/A	N/A
9603011	12/2016	Flowerday et al.	N/A	N/A
9621357	12/2016	Williams et al.	N/A	N/A
9699170	12/2016	Sondhi et al.	N/A	N/A
9754086	12/2016	Han	N/A	N/A
10038726	12/2017	Gaddam et al.	N/A	N/A
10163153	12/2017	Constantine et al.	N/A	N/A
10476862	12/2018	Kamal	N/A	H04L 9/3247
2003/0078880	12/2002	Alley et al.	N/A	N/A
2012/0254320	12/2011	Dove et al.	N/A	N/A
2013/0086645	12/2012	Srinivasan	726/4	H04L 9/3234
2013/0173642	12/2012	Oliver	N/A	N/A
2014/0020070	12/2013	Angal	726/5	H04L 63/10
2014/0189799	12/2013	Lu et al.	N/A	N/A
2014/0245417	12/2013	Hu et al.	N/A	N/A
2014/0258362	12/2013	Komatsu	709/201	G06Q 20/3263
2014/0351368	12/2013	Dudziak et al.	N/A	N/A

2016/0028737	12/2015	Srinivasan et al.	N/A	N/A
2016/0234209	12/2015	Kahol et al.	N/A	N/A
2018/0300307	12/2017	Oliver	N/A	N/A
2019/0014111	12/2018	Votaw	N/A	G06Q 20/3829
2019/0034602	12/2018	Votaw et al.	N/A	N/A
2019/0087893	12/2018	Pellew	N/A	N/A
2019/0097812	12/2018	Toth	N/A	H04L 9/0841
2019/0306128	12/2018	Kothavale	N/A	H04L 9/3247
2020/0389309	12/2019	Ricotta	N/A	H04L 9/3239
2020/0389317	12/2019	Dunjic	N/A	H04L 9/30
2021/0036854	12/2020	Dunjic	N/A	H04L 9/3213
2022/0263832	12/2021	Gupta	N/A	H04L 63/0838

OTHER PUBLICATIONS

Reis, “Securely Consume APIs on Mobile Devices—Part 2,” CA for Developers, May 4, 2018 (9 pages). cited by applicant

Jeyasudha et al., “MobiAuth: A new way for mobile authentication & authorization into third party websites,” Journal of Chemical and Pharmaceutical Sciences, vol. 8, Iss. 4, 2016, pp. 3204-3207. cited by applicant

Primary Examiner: Sholeman; Abu S

Attorney, Agent or Firm: Nixon Peabody LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation of, and claims the benefit of priority to, U.S. application Ser. No. 16/528,164, filed Jul. 31, 2019, the disclosure of which is expressly incorporated herein by reference to its entirety.

TECHNICAL FIELD

(1) The disclosed embodiments generally relate to computer-implemented systems and processes that dynamically implement and manage hash-based consent and permissioning protocols.

BACKGROUND

(2) Many computing environments include multiple, network-connected devices and systems that maintain, access, or distribute confidential data across various communications networks. For example, in an open banking environment, these computing systems may maintain programmatic interfaces capable of establishing communications, and exchanging data, with one or more third-party applications executed by additional network-connected devices and systems. For example, a third-party application, such as an executable financial management application, may access elements of confidential customer and account data maintained on behalf of a customer by computing systems of one or more financial institutions, and may perform operations to process, aggregate, or display portions of the obtained customer and account data on a digital interface, e.g., via the customer's mobile device.

SUMMARY

(3) In some examples, an apparatus includes a communications interface, a memory storing instructions, and at least one processor coupled to the communications interface and the memory. The at least one processor is configured to execute the instructions to obtain consent data that identifies one or more elements of data accessible to an application program executed by a device,

generate a consent document for the application program based on at least a portion of the consent data, and compute a consent hash value representative of the consent document. The at least one processor is further configured to generate and transmit, via the communications interface, permissioning data that includes the consent hash value to the device. The permissioning data includes information that instructs the executed application program to store the consent hash value within a local memory of the device and to associate the consent hash value with an access token of the executed application program.

(4) In other examples, a computer-implemented method, includes obtaining, using at least one processor, consent data that identifies one or more elements of data accessible to an application program executed by a device, and using the at least one processor, generating a consent document for the application program based on at least a portion of the consent data and computing a hash value representative of the consent document. The computer-implemented method also includes generating and transmitting, using the at least one processor, permissioning data that includes the consent hash value to the device. The permissioning data includes information that instructs the executed application program to store the consent hash value within a local memory of the device and to associate the consent hash value with an access token of the executed application program.

(5) Further, in some examples, an apparatus includes a communications interface, a memory storing instructions, and at least one processor coupled to the communications interface and to the memory. The at least one processor is configured to execute the instructions to receive, via the communications interface, a request for an element of data from a device. The request is generated by an application program executed at the device, and the request includes a first consent hash value. The at least one processor is further configured to obtain a consent document associated with the application program and a second consent hash value representative of the consent document, determine that the first consent hash value corresponds to the second consent hash value, and determine that requested data element is accessible to the application program based on the consent document. Further, the at least one processor is configured to load the requested data element from the memory, encrypt the requested data element, and transmit the encrypted data element to the device via the communications interface.

(6) It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the invention, as claimed. Further, the accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate aspects of the present disclosure and together with the description, serve to explain principles of the disclosed embodiments as set forth in the accompanying claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a block diagram of an exemplary computing environment, in accordance with some embodiments.

(2) FIG. 2A is a diagram illustrating a portion of an exemplary computing environment, in accordance with some embodiments.

(3) FIG. 2B is a diagram of an exemplary digital interface, in accordance with some embodiments.

(4) FIGS. 2C-2D, 3A-3B, and 4A-4B are diagrams illustrating portions of an exemplary computing environment, in accordance with some embodiments.

(5) FIGS. 4C-4D are diagrams of exemplary digital interfaces, in accordance with some embodiments.

(6) FIG. 4E is a diagram illustrating a portion of an exemplary computing environment, in accordance with some embodiments.

(7) FIGS. 5-7 are flowcharts of exemplary processes for dynamically implementing and managing

hash-based consent and permissioning processes, in accordance with some embodiments.

DETAILED DESCRIPTION

(8) Reference will now be made in detail to the disclosed embodiments, examples of which are illustrated in the accompanying drawings. The same reference numbers in the drawings and this disclosure are intended to refer to the same or like elements, components, and/or parts.

(9) In this application, the use of the singular includes the plural unless specifically stated otherwise. In this application, the use of “or” means “and/or” unless stated otherwise. Furthermore, the use of the term “including,” as well as other forms such as “includes” and “included,” is not limiting. In addition, terms such as “element” or “component” encompass both elements and components comprising one unit, and elements and components that comprise more than one subunit, unless specifically stated otherwise. Additionally, the section headings used herein are for organizational purposes only, and are not to be construed as limiting the described subject matter.

I. Exemplary Computing Environments

(10) FIG. 1 illustrates components of an exemplary computing environment **100**, in accordance with some exemplary embodiments. As illustrated in FIG. 1, environment **100** may include one or more computing devices, such as client device **102** operated by a user **101**, and one or more computing systems, such as computing system **130**. Environment **100** may also include one or more peer systems **180**, such as, but not limited to, peer system **182**. In some instances, each of client device **102**, computing system **130**, and peer systems **180** (including peer system **182**) may be interconnected across one or more wired or wireless communications networks, such as communications network **120**. Examples of network **120** include, but are not limited to, a wireless local area network (LAN), e.g., a “Wi-Fi” network, a network utilizing radio-frequency (RF) communication protocols, a Near Field Communication (NFC) network, a wireless Metropolitan Area Network (MAN) connecting multiple wireless LANs, and a wide area network (WAN), e.g., the Internet.

(11) Client device **102** may include a computing device having one or more tangible, non-transitory memories that store data and/or software instructions, such as memory **106**, and one or more processors, such as processor **104**, configured to execute the software instructions. As described herein, client device **102** may be associated with or operated by a user, such as user **101**, and examples of client device **102** include, but are not limited to, as a smart phone, tablet computer, a desktop computer, a gaming console, a wearable device, or another computing device, system, or apparatus associated with user **101**.

(12) The one or more tangible, non-transitory memories of client device **102** may store application programs, application modules, and other elements of code executable by the one or more processors. For example, as illustrated in FIG. 1, client device **102** may maintain, within memory **106**, an application repository **108** that includes, among other things, an executable mobile banking application **110** and one or more executable third-party applications, such as executable third-party applications **112** and **114**. In some instances, executable mobile banking application **110** may be provisioned to client device **102** by a computing system operated by, or associated with, a financial institution that provides financial services to user **101**, e.g., computing system **130**.

(13) Further, each of the executable third-party applications, including executable third-party applications **112** and **114**, may be developed by and provisioned to client device **102** by one or more computing systems operated by, or associated with, a corresponding third-party entity (not illustrated in FIG. 1). Examples of third-party applications **112** and **114** include, but are not limited to, a financial management application, an third-party financial aggregator application, and another application that, when executed by processor **104**, requests elements of confidential data maintained on behalf of user **101** by one or more computing systems operating within environment **100**, such as computing system **130**, and processes, aggregates, or displays portions of the requested elements of the confidential data within a corresponding digital interface.

(14) Client device **102** may include a display unit **116A** configured to present interface elements to

user **101**, and an input unit **116B** configured to receive input from a user of client device **102**, such as user **101**. Display unit **116A** may include, but is not limited to, an LCD display unit or other appropriate type of display unit, and input unit **116B** may include, but is not limited to, a keypad, keyboard, touchscreen, fingerprint scanner, voice activated control technologies, stylus, or any other appropriate type of input unit. Further, in some examples, the functionalities of display unit **116A** and input unit **116B** may be combined into a single device, such as a pressure-sensitive touchscreen display unit that can present elements (e.g., a graphical user interface) and can detect an input from user **101** via a physical touch. Client device **102** may also include a communications interface **118**, such as a transceiver device, coupled to processor **104** and configured to establish and maintain communications with communications network **120** via one or more appropriate communications protocols.

(15) Referring back to FIG. **1**, each of computing system **130** and peer systems **180** (including peer system **182**) may represent a computing system that includes one or more servers and one or more tangible, non-transitory memory devices storing executable code and application modules. The one or more servers may each include one or more processors, which may be configured to execute portions of the stored code or application modules to perform operations consistent with the disclosed embodiments. Further, in some examples, each of computing system **130** and peer systems **180** (including peer system **182**) may include a communications unit or interface coupled to the one or more processors for accommodating wired or wireless communication across network **120** with any of the additional network-connected systems or devices described herein, e.g., a transceiver device.

(16) In some instances, each of computing system **130** and peer systems **180** (including peer system **182**) may correspond to a discrete computing system, as described herein. In other instances, one or more of computing system **130** and peer systems **180** (including peer system **182**) may correspond to a distributed system that includes computing components distributed across one or more networks, such as communications network **120**, or other networks, such as those provided or maintained by cloud-service providers (e.g., Google Cloud™, Microsoft Azure™, etc.). The disclosed embodiments are, however, not limited to these exemplary distributed systems and, in other instances, computing system **130** and peer systems **180** (including peer system **182**) may include computing components disposed within any additional or alternate number or type of computing systems or across any appropriate network.

(17) In some instances, computing system **130** may maintain elements of confidential data within the one or more tangible, non-transitory memories, e.g., confidential data maintained on behalf of user **101**. For example, computing system **130** may be associated with, or may be operated by, a financial institution that provides financial services to user **101** and other customers, and the confidential data may include, among other things, confidential profile data that characterizes user **101**, account data identifying and characterizing one or more financial services accounts or payment instruments held by user **101**, or transaction data identifying and characterizing one or more transactions involving the financial services accounts or payment instruments.

(18) In some instances, computing system **130** may perform any of the exemplary processes described herein to provision one or more elements of confidential data requested by executed third-party applications **112** or **114** in accordance with a type or level of consent previously granted by user **101** (e.g., through the exemplary processes described herein). To facilitate a performance of these and other exemplary processes, such as those described herein, computing system **130** may maintain, within one or more tangible, non-transitory memories, a data repository **132** that includes a user database **134**, a confidential data store **136**, and a consent data store **138**.

(19) For example, user database **134** may include data records that identify and characterize one or more users of computing system **130**, e.g., user **101**. For example, and for each of the users, the data records of user database **134** may include a corresponding user identifier (e.g., an alphanumeric login credential assigned to user **101** by computing system **130**), and data that

uniquely identifies one or more devices (such as client device **102**) associated with or operated by that user (e.g., a unique device identifier, such as an IP address, a MAC address, a mobile telephone number, etc., that identifies client device **102**).

(20) Confidential data store **136** may maintain elements of confidential customer data on behalf of user **101** and other users of computing system **130**. For example, confidential data store **136** may include confidential account data and confidential transaction data that identify and characterize a balance or transaction history of one or more payment instruments, deposit accounts, brokerage accounts, or other financial services accounts issued to user **101** (e.g., by the financial institution that operates computing system **130**). Further, and by way of example, one or more data records of confidential data store **136** may also include customer profile data that identifies and characterizes user **101**, such as, but not limited to, a name or an address of user **101**, one or more governmental identifiers of user **101** (e.g., a driver's license number, a social security number, etc.), and demographic data that characterizes user **101** (e.g., an age, a gender, an income level, etc.). In some instances, each of the data records of confidential data store **136** may also include a corresponding user identifier (e.g., an alphanumeric login credential assigned to user **101** by computing system **130**) and/or a corresponding device identifier (e.g., the IP address, MAC address, or mobile telephone number of client device **102**), and as such, each of the data records confidential data store **136** may also be linked to, and associated with, one or more corresponding data records within user database **134**.

(21) Consent data store **138** may maintain, for one or more third-party applications, such as third-party application **112**, information indicative of a successful outcome of one or more of the exemplary decoupled consent and permissioning protocols described herein, which may be implemented collectively by client device **102** (e.g., though executed mobile banking application **110**, executed third-party application **112**, and additionally, or alternatively, executed third-party application **114**, etc.) and computing system **130** (e.g., through an executed consent and permissioning engine). By way of example, consent data store **138** may maintain, on behalf of mobile banking application **1110** and third-party applications **112** and **114**, a digital token, cryptogram, hash value, or other element of cryptographic data, e.g., an OAuth token, indicative of a permission of each of these executed applications programs to access programmatic interfaces established and maintained by computing system **130**.

(22) Further, consent data store **138** may also maintain elements of application-specific information that identifies and characterizes a level of access to confidential data (e.g., as maintained in confidential data store **136**) granted to third-party applications **112** and **114** by user **101**, e.g., via any of the exemplary decoupled consent and permissioning processes described herein. For example, and for each of third-party applications **112** and **114** (and any additional or alternate third-party application executed by client device **102**), the elements of application-specific information may include: (i) a consent document that, among other things, includes data identifying one or more accessible types, classes, or elements of confidential data maintained at computing system **130**, and data identifying one or more permissible operations on the accessible types, classes, or elements of confidential data; and (ii) a consent hash value representative of the consent document. In some instances, each of the elements of application-specific permissioning data (e.g., the consent document, the consent hash value, etc.) may be linked to or associated with a corresponding one of the application-specific OAuth tokens and a unique application identifier within the data records of consent data store **138**.

(23) The application-specific consent documents may, for example, be formatted in accordance with a data-interchange format, examples of which include, but are not limited to, a JavaScript Object Notation (JSON) format, a YAML format, an Internet-JSON (I-JSON) format, an XML format, or any additional or alternate language-independent, data serialization formats compatible with application programs executed by client device **102** and computing system **130**. Further, the application-specific consent hash values may represent a cryptographically secure, and tamper-

evident, attestation of the level of access currently granted to corresponding ones of third-party applications **112** and **114** (and other third-party applications executable at client device **102**).

(24) In some instances, one or more of the application-specific consent hash values may include a cryptographic hash value representative of the corresponding one of the application-specific consent documents, and computing system **130** may generate the cryptographic hash value based on an application of one or more cryptographic hash functions to the corresponding one of the application-specific consent documents, either alone or in combination with additional data. Examples of the cryptographic hash functions includes, but are not limited to, a secure hash algorithm (SHA), such as SHA-1, SHA-2, or SHA-256, and an MD5 algorithm. In other examples, one or more of the application-specific consent hash values may include a non-cryptographic hash value, and computing system **130** may generate the non-cryptographic hash value based on an application of one or more of a non-cryptographic hash function or a universal hash function to the corresponding one of the application-specific consent documents, either alone or in combination with additional data.

(25) Referring back to FIG. **1**, computing system **130** may also maintain, within the one or more tangible, non-transitory memories, one or more executable application programs **140**, such as, but not limited to a consent and permissioning engine **142**. When executed by the one or more processors of computing system **130**, consent and permissioning engine **142** may perform operations that, in conjunction with one or more application programs executed at client device **102** (e.g., executed mobile banking application **110**, executed third-party applications **112** or **114**, etc.), collectively implement one or more of the exemplary, decoupled consent and permissioning protocols described herein, which may decouple processes that establish permission of one or more executed third-party applications to access a programmatic interface established and maintained at computing system **130** from those processes that grant, and selectively modify or revoke, permission to each of the third-party applications to access elements of confidential data on an application-specific basis.

(26) Referring back to FIG. **1**, each of peer systems **180**, such as peer system **182**, may maintain, within one or more tangible, non-transitory memories, a data repository **184** that includes a local copy of a cryptographically secure distributed ledger **186**, which peer systems **180** (including peer system **182**) may establish and maintain using any of the exemplary consensus-based processes described herein. In some instances, as illustrated in FIG. **1**, distributed ledger **186** may include ledger blocks, such as consent ledger blocks **188**, that record OAuth tokens, consent documents, and additionally, or alternatively, hash values representative of the consent documents for one or more third-party applications provisioned to computing devices and systems operating within environment **100**, such as, but not limited to, third-party application **112** provisioned to client device **102**.

(27) For example, consent ledger blocks **188** may establish an immutable and cryptographically secure record of a temporal evolution in a type or level of consent granted to third-party application by user **101**. Further, in some instances, peer systems **180** may perform any of the exemplary, consensus-based processes described herein to broadcast distributed ledger **186** (and updates thereto) across network **120** to one or more computer systems or devices that participate in a corresponding distributed-ledger network, such as computing system **130**.

II. Exemplary Processes for Dynamically Implementing and Managing Hash-Based Consent and Permissioning Protocols

(28) FIG. **2A** illustrate a portion of computing environment **100**, in accordance with some exemplary embodiments. Referring to FIG. **2A**, user **101** may provide, to input unit **1168** of client device **102**, input **202** that requests an execution of a third-party application program provisioned to client device **102**, such as third-party application **112** (or alternatively, third-party application **114**). For example, and based on input **202**, client device **102** may execute third-party application **112**, and executed third-party application **112** may perform operations that establish a secure channel of

communications with one or more computing systems within environment **100** that maintain elements of confidential data on behalf of user **101**. As described herein, computing system **130** may maintain elements of confidential data on behalf of user **101** and other customers or users, and executed third-party application **112** may perform operations that establish the secure channel of communications with a programmatic interface established and maintained by computing system **130**, e.g., application programming interface (API) **204**.

(29) In some instances, and responsive to the establishment of the secure communications channel, executed third-party application **112** may generate one or more interface elements that, when rendered for presentation by display unit **116A**, collectively establish one or more display screens of a digital authentication interface (not illustrated in FIG. 2A). The digital authentication interface may prompt user **101** to provide, via input unit **116B**, one or more authentication credentials that uniquely identify user **101** at computing system **130**, such as, but not limited to, an alphanumeric login credential, an alphanumeric password, or one or more biometric credentials, such as a digital image of a face of user **101** or a digital scan of a thumbprint or fingerprint of user **101**. In some instances, executed third-party application **112** may receive the one or more authentication credentials, e.g., via input unit **116B**, and may package the one or more authentication credentials and a unique device identifier of client device **102** (e.g., an IP address, a MAC address, etc.) into corresponding portions of authentication data, which client device **102** may transmit across network **120** to computing system **130**.

(30) Although not illustrated in FIG. 2A, API **204** may receive and route the authentication data to consent and permissioning engine **142**, which upon execution by computing system **130**, may parse the authentication data to extract the one or more authentication credentials of user **101** and the device identifier of client device **102**. In some instances, executed consent and permissioning engine **142** may access one or more local authentication credentials maintained within an accessible data repository (e.g., within user database **134** of data repository **132**), and authenticate an identity of user **101** based on a comparison between the extracted authentication credentials and the accessed local authentication credentials.

(31) If, for example, executed consent and permissioning engine **142** were to establish an inconsistency between the extracted and local authentication credentials, executed consent and permissioning engine **142** may decline to authenticate the identity of user **101** and may decline to grant third-party application **112** access to computing system **130**. Although not illustrated in FIG. 2A, executed consent and permissioning engine **142** may generate an error message and may perform operations that cause computing system **130** to transmit the error message across network **120** to client device **102**, e.g., via a secure, programmatic interface established and maintained by executed third-party application **112**.

(32) In other instances, and based on an established consistency between the extracted and local authentication credentials, executed consent and permissioning engine **142** may authenticate an identity of user **101**. Responsive to the successful authentication, executed consent and permissioning engine **142** may generate and store confirmation data (e.g., a data flag, etc.) indicative of the successful authentication within an accessible data repository, such as user database **134**, in conjunction with the one or more of the authentication credentials of user **101** (e.g., as a user identifier) or the device identifier of client device **102**.

(33) Executed consent and permissioning engine **142** may also generate, and transmit, across network **120** to client device **102**, request data **206** that requests an initiation of one or more of the exemplary decoupled consent and permissioning protocols described herein, e.g., in conjunction within executed third-party application **112**. For example, request data **206** may include unique identifier of computing system **130** (e.g., an assigned internet protocol (IP) address, etc.) or of executed consent and permissioning engine **142** (e.g., a cryptogram, hash value, or other element of cryptographic data that uniquely identifies consent and permissioning engine **142** to executed third-party application **112**). Request data **206** may also include information that identifies certain types

or classes of confidential data maintained on behalf of user **101** by computing system **130** (e.g., confidential profile, account, or transaction data, etc.), along with certain data elements associated with each of the types or classes (e.g., elements of profile data that include governmental identifiers, elements of transaction data that include transaction times, transaction values, and identifiers of corresponding merchants or purchased products, elements of account data that include account identifiers, account balances, etc.).

(34) A secure programmatic interface established and maintained by executed third-party application **112**, such application programming interface (API) **208**, may receive request data **206** from computing system **130** and may route request data **206** to executed third-party application **112**. In some instances, a local authorization and consent module **210** of executed third-party application **112** may process request data **206** and generate interface elements **212** that, when rendered for presentation by display unit **116A**, collectively establish one or more display screens of a digital consent interface **214**. The one or more display screens of digital consent interface **214** may prompt user **101** to provide input to client device **102** that specifies whether user **101** grants third-party application **112** permission to access certain types, classes, or discrete elements of the confidential data maintained by computing system **130**, e.g., the confidential profile, account, or transaction data maintained on behalf of user **101** by computing system **130**.

(35) As illustrated in FIG. 2A, display screen **214A** of digital consent interface **214** may prompt user **101** to provide input to client device **102** that grants third-party application **112** access to the elements of confidential data maintained at computing system **130** on a global basis (e.g., to all available types or classes of confidential data), or that selectively grants third-party application **112** access to the elements of confidential data on a semi-global basis (e.g., to a selected subset of the available types or classes of confidential data). For example, display screen **214A** may include an interactive interface element, such as slider element **216**, that enables user **101** to grant, or deny, third-party application **112** access to each of the elements of the confidential customer data, account data, and transaction data on a global basis. Further, display screen **214A** may also include one or more additional interactive elements, such as slider elements **218**, **220**, and **222**, that enable user **101** to grant, or deny, third-party application **112** access to respective elements of the confidential customer data (e.g., slider element **218**), the confidential account data (e.g., slider element **220**), and the confidential transaction data (e.g., slider element **222**), on a semi-global bases, e.g., a class- or type-specific basis.

(36) For example, and based on the input provided to client device **102**, e.g., via input unit **116B**, user **101** may dispose slider element **218** at position **218A** within display screen **214A**, which indicates an intention to deny third-party application **112** access to any of the elements of confidential customer data maintained on behalf of user **101** at computing system **130**. Additionally, and based on the provided input, user **101** may dispose slider element **220** at position **220A** within display screen **214A**, and may dispose slider element **222** at position **222A** within display screen **214A**, which collectively indicate an intention to grant third-party application **112** access to each of the elements of confidential account and transaction maintained on behalf of user **101** at computing system **130**. Further, user **101** may elect to provide no input to slider element **216**, which indicates user **101**'s intention to selectively grant third-party application **112** access to the elements of confidential data on a semi-global, and not a global, basis.

(37) Display screen **214A** may also include additional interface elements, such as "SUBMIT" element **224**, that, when selected by user **101** through the additional provided input, confirm the level of access granted to third-party application **112**. In some instances, the selection of "SUBMIT" element **224** (e.g., based on the provided input) may cause executed third-party application **112** perform operations that submit consent data indicative of the granted level of access to computing system **130**, e.g., during the exemplary decoupled consent and permissioning protocols described herein.

(38) In other instances, one or more additional display screen of digital consent interface **214** may

prompt user **101** to grant, or deny, third-party application **112** access to one or more discrete elements of the types or classes of confidential data identified within display screen **214A**, e.g., the confidential customer data, account data, and transaction data maintained at computing system **130**. By way of example, as illustrated in FIG. 2A, display screen **214A** may include additional interface elements, such as interactive elements **226**, **228**, and **230**, that, when selected by user **101**, cause executed third-party application **112** generate and render for presentation additional interface screens facilitating a selective grant or denial of permission for third-party application **112** to access specific elements of the confidential customer data, account data, and transaction data.

(39) For example user **101** may elect to selectively grant, or deny, third-party application **112** access to one or more specific elements of the confidential transaction data maintained by computing system **130**, and may provide additional input to client device **102** (e.g., via input unit **116B**) that selects interface element **230** within display screen **214A**. Responsive to the additional input selecting interface element **230**, executed third-party application **112** may access request data **206**, e.g., as received from computing system **130**, and may generate one or more additional interface elements that, when rendered for presentation within an additional display screen of digital consent interface **214**, identify discrete elements of confidential transaction data maintained on behalf of user **101** at computing system **130** and prompt user **101** to selectively grant, or deny, executed third-party application **112** access to one or more of these discrete elements of confidential transaction data.

(40) Referring to FIG. 2B, and responsive to the additional input selecting interface element **230**, executed third-party application **112** may generate and render for presentation a data-specific display screen **214B**, which includes interactive interface elements, such as slider elements **232**, **234**, **236**, and **238**, that enable user **101** to selectively grant, or deny, third-party application **112** access to (i) a transaction type, value, and time for one or more transactions involving user **101** (e.g., slider element **232**); (ii) a product or service involved in the one or more transactions (e.g., slider element **234**); (iii) a counterparty or merchant involved in the one or more transactions; and (e.g., slider element **236**); and a payment instrument involved in the one or more transactions (e.g., slider element **240**). Display screen **214B** may also include further interface elements, such as “SUBMIT” element **240**, that, when selected by user **101** through the additional provided input, confirm the level of access granted to third-party application **112** (e.g., as described herein in reference to “SUBMIT” element **224**).

(41) For example, user **101** may elect to grant third-party application **112** access to the elements of confidential transaction data that identify a type, amount, and date of one or more transactions involving user **101**, and may provide further input to client device **102** (e.g., via input unit **116B**) that disposes slider element **232** at position **232A** within display screen **214B**, which indicates an intention to grant third-party application **112** access to the elements of confidential transaction data identifying the type, amount, and date of transactions involving user **101**. In other examples, user **101** may elect to deny third-party application **112** access to any elements of confidential transaction data that identify a product or service, a counterparty, or a payment instrument associated with transactions involving user **101**. As described herein, user **101** may provide further input to client device **102** (e.g., via input unit **116B**) that disposes that disposes slider elements **234**, **236**, and **238** and respective ones of positions **234A**, **236A**, and **238A** within display screen **214B**, which indicates an intention to deny third-party application **112** access to the elements of confidential transaction data identifying the involved product or service, counterparty, and payment instrument. The further provided input may also indicate a selection of “SUBMIT” element **240**, which confirms the level of access granted to executed third-party application **112**.

(42) In other instances, not illustrated in FIG. 2B, user **101** may also elect to selectively grant, or deny, executed third-party application access to one or more discrete elements of confidential customer profile data or confidential account data maintained at computing system **130**, and may provide further input to client device **102** (e.g., via input unit **116B**) that selects interactive

elements **226** or **228** of display screen **214A**, which causes executed third-party application **112** to generate and render for presentation additional interface screens facilitating a selective grant or denial of permission for executed third-party application **112** to access discrete elements of the confidential customer profile data or the confidential account data, e.g., using any of the exemplary processes described herein.

(43) The disclosed embodiments are however, not limited to these exemplary interface elements and display screens, and in other instances, digital consent interface **214** may include interface elements associated with any additional or alternate class or type of confidential data maintained on behalf of user **101** (e.g., the profile data or account data described herein) or any additional or alternate elements of these classes or types of confidential data, and may present these interface elements within an additional or alternate display screen of digital consent interface **214**, including a single display screen. Further, the disclosed digital interfaces and display screens are not limited to the exemplary types or functions of interface elements described herein (e.g., selectable elements, slider elements, etc.), and into other examples, the disclosed digital interfaces and display screens may include any additional or alternate type of interface element characterized by any additional or alternate functionality, such as, but not limited to, fillable text boxes or check boxes.

(44) Further, in some embodiments, one or more display screens of digital consent interface **214**, such as data-specific display screen **214B**, may include additional or alternate interface elements that, when selected by user **101** (e.g., based on additional input received via input unit **116B**), enable user **101** to permit a performance of one of more operations on selected classes or elements of confidential data by third-party application **112**. Examples of these operations can include, but are not limited to, processing or aggregating elements of raw confidential data, presenting the elements of raw, aggregated, or processed confidential data within one or more digital interfaces, and distributing the elements of raw, aggregated, or confidential data to additional computing systems operating within environment **100**, or to application programs executed by these additional computing systems (e.g., fourth- or fifth-party applications, etc.).

(45) Referring to FIG. 2C, local authorization and consent module **210** may receive the additional input, e.g., additional input **254**, via input unit **116B**. In some instances, local authorization and consent module **210** may parse additional input **254** perform operations that extract information identifying: (i) the selective disposition of slider element **218** at position **218A** of display screen **214A**, which indicates a denial of access to the elements of confidential customer data; (ii) the selective disposition of slider element **220** at position **220A** of display screen **214A**, which indicates a grant of access to the elements of confidential account data; (iii) the selective disposition of slider element **232** at position **232A** of display screen **214B**, which indicates a grant of access to the elements of confidential transaction data that specify the value, type, or date of the one or more transactions; (iv) the selective disposition of slider elements **234**, **236**, and **238** at respective ones of positions **234A**, **236A**, and **238A** of display screen **214B**, which indicates a denial of access to the elements of confidential transaction data that identify the product or service, counterparty, or payment instrument involved in the one or more transactions. In some instances, the extracted information may also identify the selection of “SUBMIT” element **240**, which confirms the level of access granted to executed third-party application **112** by user **101**.

(46) Local authorization and consent module **210** may perform operations that package the extracted information into corresponding portions of consent data **256**. As illustrated in FIG. 2B, local authorization and consent module **210** may generate response data **258**, which includes consent data **256**, and perform operations that cause client device **102** to transmit response data **258** across network **120** to API **204** of computing system **130**, e.g., as a response to request data **206**. Response data **258** may also include at least one of a unique user identifier **260A** of user **101** (e.g., an alphanumeric authentication credential, a biometric credential, etc.), a unique device identifier **260B** of client device **102** (e.g., an IP address, a MAC address etc.), and a unique application identifier **260C** of executed third-party application **112** (e.g., a unique cryptogram, hash value, or

other element of cryptographic data, etc.).

(47) API **204** may provide response data **258** as an input to consent and permissioning engine **142**, which upon execution, may perform any of the exemplary processes described herein to generate a digital token, cryptogram, hash value, or other element of cryptographic data, e.g., an OAuth token, indicative of the prior successful authentication of user **101**, and to generate application-specific elements of information, such as a consent document and a consent hash value, that identify, characterize, and represent the level of access to confidential data granted third-party application **112** by user **101**. In some instances, described herein, executed consent and permissioning engine **142** may perform operations that store the OAuth token, consent document, and consent hash value within an accessible data repository, such as consent data store **138**, in conjunction with one or more of identifiers **260A**, **260B**, and **260C**.

(48) As illustrated in FIG. **2C**, a validation module **262** of executed consent and permissioning engine **142** may receive response data **258** from API **204**, and may perform operations that associate response data **258** with a prior and successful authentication of the identity of user **101**, e.g., based on one or more of user identifier **260A** or device identifier **260B** and the confirmation data maintained within user database **134** (e.g., confirmation data **263**). Responsive to the association of response data **258** with the prior and successful authentication, executed validation module **262** may provide response data **258** as an input to a consent management module **266** of executed consent and permissioning engine **142**.

(49) In some instances, and based on portions of response data **258**, executed consent management module **242** may perform any of the exemplary processes described herein to generate a consent document that reflects a level of access granted by user **101** to third-party application **112**, e.g., as specified within consent data **256**, and to compute one or more hash values representative that consent document. Executed consent management module **242** may also perform any of the exemplary described herein processes to generate a digital access token, cryptogram, hash value, or other element of cryptographic data, such as an OAuth token, indicative of the prior successful authentication of the identity of user **101** and a permission of third-party application to access one or more programmatic interfaces established or maintained by computing system **130**.

(50) By way of example, consent data **256** may indicate that user **101** denied third-party application **112** access to elements of confidential customer data maintained at computing system **130**, and granted third-party application **112** access to any elements of confidential account data maintained at computing system **130**. Further, and as described herein, consent data **256** may also indicate that user **101** granted third-party application **112** access to elements of confidential transaction data characterizing a transaction type, value, and time for one or more transactions involving user **101**, while denying access to any elements of confidential transaction data characterizing a payment instrument, a product or service, or a counterparty involved in these transactions.

(51) In some instances, executed consent management module **266** may perform operations that package all or a portion of consent data **256** into corresponding portions of a consent document **268**, which as described herein, may be formatted in accordance with a data interchange format. Examples of the data-interchange format include, but are not limited to, a JavaScript Object Notation (JSON) format, a YAML format, an Internet-JSON (I-JSON) format, an XML format, or any additional or alternate language-independent, data serialization formats compatible with executed third-party application, consent and permissioning engine **142**, and other application programs executed by client device **102** and computing system **130**.

(52) Executed consent management module **266** may also generate a consent hash value **270** representative of consent document **268**, e.g., based on an application of any of the hash algorithms described herein to all or a selected portion of consent document **268**, either alone or in conjunction within additional data. In some instances, and as described herein, consent hash value **270** may correspond to a cryptographic hash value, e.g., computed using an SHA algorithm or an MD5 algorithm. In other instances, as described herein, consent hash value **270** may correspond to a

non-cryptographic hash value, e.g., computed based on an appropriate non-cryptographic hash algorithm or a universal hash algorithm).

(53) Executed consent management module **266** may perform further operations that generate a digital token, cryptogram, hash value, or other element of cryptographic data, e.g., an OAuth token **272**, indicative of the successful authentication of the identity of user **101** and of the permission of third-party application to access one or more programmatic interfaces established or maintained by computing system **130**. OAuth token **272** may, in some instances, be characterized by a predetermined structure or format recognizable by executed consent and permissioning engine **142** and further, by executed third-party application **112**. In some examples, executed consent management module **242** may generate OAuth token **272** (or any additional or alternate digital token, cryptogram, hash value, or cryptographic data element) based on an application of one or more tokenization processes to portions of consent data **256**, user identifier **260A**, device identifier **260B**, and/or application identifier **260C**.

(54) As illustrated in FIG. 2C, executed consent management module **266** may perform operations that store, within consent data store **138**, consent document **268**, consent hash value **270**, and OAuth token **272** in conjunction with user identifier **260A** (e.g., which uniquely identifies now-authenticated user **101**), device identifier **260B** (e.g., which identifies client device **102**), and application identifier **260C** (e.g., which identifies third-party application **112**). In some examples, the storage of consent document **268**, consent hash value **270**, OAuth token **272**, and identifiers **260A**, **260B**, and **260C** within consent data store **138** may associate consent document **268**, consent hash value **270**, and OAuth token **246** with user **101**, with client device **102**, and further, with executed third-party application **112**. Further, consent document **268** and consent hash value **270** may also establish, and be indicative of, a current attestation by computing system **130** of a level of type of access to confidential data granted third-party application by user **101**.

(55) In other examples, executed consent management module **266** may perform operations that package consent document **268**, consent hash value **270**, and application identifier **260C** (e.g., which identifies third-party application **112**) into corresponding portions of recordation data **274**. Executed consent management module **266** may further apply a digital signature **276** to recordation data **274**, e.g., using a private cryptographic key of computing system **130**, and may perform operations that cause computing system **130** to broadcast recordation data **274**, applied digital signature **276**, and a public key certificate **278** of computing system **130** (e.g., that includes a corresponding public cryptographic key) to one or more of peer systems **180**, including peer system **182**.

(56) A programmatic interface maintained by each of the one or more of peer systems **180**, including peer system **182**, may receive recordation data **274**, and may perform consensus-based operations that validate applied digital signature **276** (e.g., based on the public cryptographic key included within public key certificate **278**), that generate an additional ledger block **288** of distributed ledger **186** that includes consent document **268**, consent hash value **270**, and application identifier **260C** (along with an additional hash value representative of these elements of included data), and that compute competitively a proof-of-work or proof-of-stake associated with distributed ledger **186** (e.g., as established based on consensus among peer systems **180**). By way of example, peer system **182** may successfully compute the associated proof-of-work or proof-of-stake, may generate an updated distributed ledger **282** to which additional ledger block **288** is appended (e.g., a latest, longest version of the distributed ledger), and may broadcast updated distributed ledger **282** across network **120** to additional ones of peer systems **180** and further, to other participants in a distributed-ledger network, such as computing system **130**, for storage in one or more tangible, non-transitory memories.

(57) Referring back to FIG. 2C, executed consent management module **266** may perform operations that package OAuth token **272** and permissioning data **283** that identifies and characterizes a level of access granted to executed third-party application **112**, such as, but not

limited to, consent hash value **270**, into corresponding portions of attestation data **284**. Further, executed consent management module **266** also apply a digital signature **286** to all or a portion of attestation data **284** using any appropriate digital signature algorithm in conjunction with private cryptographic key of computing system **130** (e.g., to further verify an integrity of attestation data **284** during transmission across unsecured communications channels). Computing system **130** may, for example, perform operations that transmit attestation data **284**, digital signature **286**, and public key certificate **278** across network **120** to client device **102** using any appropriate communications protocol, e.g., via the corresponding communications interface, such as the transceiver device.

(58) Referring to FIG. 2D, API **208** of executed third-party application **112** may receive and route attestation data **284**, digital signature **286**, and public key certificate **278** to a local validation module **289** of executed third-party application **112**. In some instances, when executed by processor **104**, local validation module **289** may perform operations that validate digital signature **286**, e.g., based on the public cryptographic key of computing system **130** included within public key certificate **278**. Responsive to the successful validation of digital signature **286**, executed local validation module **289** may provide a portion of permissioning data **283** (e.g., consent hash value **270**) and OAuth token **272** as an input to local authorization and consent module **210**, which may store consent hash value **270** and OAuth token **272** within corresponding portions of a local credential data store **292** (e.g., as maintained in memory **106**), either alone or in conjunction with public key certificate **278**.

(59) As described herein, consent hash value **270** may be representative of consent document **268**, which identifies, specifies, and characterizes a level of access to confidential data granted executed third-party application **112** by user **101**. In some examples, when provisioned to third-party application **112** and stored within the one or more tangible, non-transitory memories (e.g., within local credential data store **292**), consent hash value **270** may correspond to an attestation, by third-party application **112**, of a type of access currently granted by user **101**. For example, when requesting access to one or more elements of confidential data maintained at computing system **130**, executed third-party application **112** may present not only OAuth token **272**, which confirms and authentication of an identity of user **101** and an authorization of executed third-party application **112** to access programmatic interfaces maintained at computing system **130**, but also consent hash value **270**, which enables computing system **130** to establish whether third-party application **112** (e.g., as executed by client device **102**) and consent and permissioning engine **142** (e.g., as executed by computing system **130**) each attest to a common level or type of granted consent.

(60) Further, and as described herein, attestation data **284** includes permissioning data **283**, such as consent hash value **270**, that, when provisioned to executed third-party application **112**, represents an attestation by third-party application **112** of a current level of access to confidential data granted by user **101** (e.g., using any of the exemplary processes described herein). The disclosed embodiments are, however, not limited to permissioning data that includes consent hash value **270** and in other examples, permissioning data **283** may also include all, or a selected portion, of consent document **268**, either alone or in addition to consent hash value **270**. In some instances, executed third-party application **112** may perform any of the exemplary processes described herein to validate the applied digital signature, and to store each of these additional elements of permissioning data **283** within corresponding portions of local consent data store **290**.

(61) In some instances, one or more of the exemplary consent and permissioning protocols described herein, when implemented collectively by executed third-party application **112** and executed dynamic consent and permissioning engine **142**, decouple an authorization of executed third-party application **112** to access computing system **130** through one or more programmatic interfaces (e.g., the generation of OAuth token **272**) from the selective grant or denial of access to elements of confidential data maintained by computing system **130** (e.g., the generation of consent document **268** and consent hash value **270**). By decoupling authorization from access and consent,

one or more of the exemplary processes described herein may enable user **101** to selectively grant, or deny, a third-party application access to elements of confidential data maintained at computing system **130**, on a global basis, on a semi-global basis (e.g., on a data-type- or data-class-specific basis), or an element-by-element basis. Certain of these exemplary processes may be implemented in addition to, or as an alternate to, many token-based consent and authorization processes that, in response to a request generated by a third-party application to access elements of confidential data maintained at computing system **130**, require user **101** to consent to the requested access to the elements of confidential data without condition, or alternatively, deny the requested access to not only the elements of confidential data, but also to computing system **130**.

(62) FIGS. **3A** and **3B** illustrate additional portions of computing environment **100**, in accordance with disclosed exemplary embodiments. Referring to FIG. **3A**, and upon execution by processor **104** of client device **102**, one or more application modules of third-party application **112**, such as request management module **302**, may generate a request **304** to access one or more elements of confidential data maintained on behalf of user **101** by one or more network-connected computing systems within environment **100**, such as the elements of confidential profile, account, and transaction data maintained by computing system **130**. By way of example, request **304** may correspond to a request, generated by executed third-party application **112**, to access a current account balance of a credit card account held by user **101** and data characterizing a specified number of recent purchase transactions involving that credit card account, e.g., the thirty most-recent purchase transactions involving the credit card account.

(63) In some instances, request **304** may include a data identifier **306** of each of the requested elements of confidential data e.g., unique identifiers of the requested elements of account data and transaction data maintained by computing system **130**. Further, although not illustrated in FIG. **3A**, request **304** may also include information that identifies and characterizes one or more operations involving the requested elements of confidential data, e.g., the presentation of the account balance and the transaction data within the digital interface by executed third-party application **112**.

(64) Request **304** may also include information that identifies, characterizes, or is representative of a level of access to confidential data granted third-party application **112**. By way of example, executed request management module **302** may access local credential data store **292** (e.g., as maintained within a portion of memory **106**), extract a consent hash value **308**, and package consent hash value **308** within a corresponding portion of request **304**. In some instances, consent hash value **308** may be provisioned to executed third-party application **112** by one or more applications executed by computing system **130** (e.g., executed consent and permissioning engine **142** of FIG. **1**) based on a successful outcome of any of the exemplary decoupled consent and authorization processes described herein.

(65) In some instances, consent hash value **308** may be representative of a corresponding consent document, which includes information that identifies one or more types, classes, or discrete elements of confidential data accessible to third-party application **112**, and may be generated by computing system **130** based on an application of any of the exemplary hash algorithms described herein to all or a selected portion of that corresponding consent document. Further, and as described herein, consent hash value **308** may also represent an attestation, by third-party application **112**, of the level of access to confidential data currently granted third-party application **112** by user **101**, e.g., using any of the exemplary decoupled consent and authorization processes described herein.

(66) Further, although not illustrated in FIG. **3A**, executed third-party application **112** may also maintain a local copy of the corresponding consent document within local credential data store **292**, e.g., as provisioned to client device **102** by computing system **130** using any of the exemplary processes described herein. In some exemplary embodiments, executed request management module **302** may package all, or a selected portion, of the local copy of the corresponding consent document into request **304**, e.g., either in addition to, or as an alternate to, consent hash value **308**.

(67) Further, and as illustrated in FIG. 3A, executed request management module **302** may also access and obtain an OAuth token **310** associated with third-party application **112** from local credential data store **292**, and may package OAuth token **310** within a corresponding portion of request **304**. OAuth token **310** may, for example, be indicative of an authentication of an identity of user **101** by computing system **130** and an authorization of third-party application **112** to access one or more programmatic interfaces established and maintained by computing system **130**. As described herein, OAuth token **310** may be generated by, and provisioned to client device **102** by computing system **130** based on a successful outcome of any of the exemplary decoupled authorization and consent processes described herein.

(68) In some instances, executed request management module **302** may also perform operations that that package, within corresponding portions of request **304**, a unique identifier **312A** of executed third-party application **112** (e.g., a unique cryptogram, hash value, or other element of cryptographic data, etc.) and a unique identifier **312B** of client device **102** (e.g., an IP address etc.). Executed request management module **302** may further apply a digital signature **314** to all or a portion of request **304**, e.g., using a private cryptographic key of third-party application **112**, and may perform operations that cause computing system **130** to broadcast request **304**, applied digital signature **314**, and a public key certificate **316** of third-party application **112** (e.g., that includes a corresponding public cryptographic key) across network **120** to computing system **130**.

(69) A secure, programmatic interface established and maintained by computing system **130**, such as application programming interface (API) **318**, may receive request **304**, and may route request **304**, applied digital signature **314**, and a public key certificate **316** to consent and permissioning engine **142**, e.g., as executed by computing system **130**. In some instances, and prior to routing request **304** to executed consent and permissioning engine **142**, API **318** may perform operations (not illustrated in FIG. 3A) that parse request **304**, extract OAuth token **310**, and perform an initial pre-validation process that determines whether a format or structure of OAuth token **310** conforms with an expected token format or structure, e.g., associated with the exemplary decoupled authentication and consent protocols described herein.

(70) If, for example, API **318** were to establish an inconsistency between the format or structure of OAuth token **310** and the expected token structure or format, API **318** may determine that OAuth token **310** is not valid for the requested access to the confidential data maintained at computing system **130**. Based on the established inconsistency, API **318** may discard request **304**, and computing system **130** may perform operations that generate and transmit an error message across network **120** to client device **102**, e.g., via API **208** (not illustrated in FIG. 3A).

(71) In other instances, if API **318** were to establish a consistency between the format or structure of OAuth token **310** and the expected token format or structure, API **318** may route request **304**, applied digital signature **314**, and a public key certificate **316** to executed consent and permissioning engine **142**. For example, an authorization module **320** of executed consent and permissioning engine **142** may receive request **304**, applied digital signature **314**, and a public key certificate **316**, and may perform operations that validate applied digital signature **314** based on a public cryptographic key of third-party application **112**, e.g., as extracted from public key certificate **316**. Responsive to an unsuccessful validation of digital signature **314**, executed authorization module **320** determine that request **304** was corrupted or modified during transmission (e.g., through an interception by one or more malicious parties, etc.), and may discard request **304**. Executed authorization module **320** may also generate and transmit an error message across network **120** to client device **102**, e.g., via API **208** (not illustrated in FIG. 3A).

(72) In other instances, and responsive to a successful validation of digital signature **314**, executed authorization module **320** may parse request **304** to extract OAuth token **310** and identifier **312A** of executed third-party application, and may perform operations that validate OAuth token **310**, e.g., as received from executed third-party application **112**. As illustrated in FIG. 3A, executed authorization module **320** may access consent data store **138** (e.g., as maintained within data

repository **132**), and obtain a reference version of the OAuth token, e.g., OAuth token **272**, that is associated with or linked to identifier **312A** within consent data store **138** and as such, is associated with third-party application **112**.

(73) Executed authorization module **320** may perform additional operations that validate OAuth token **310** based on a comparison with, and a determined consistency with, OAuth token **272**. For example, if executed authorization module **320** were to detect an inconsistency between OAuth token **310** (e.g., as received from executed third-party application **112**) and OAuth token **272** (e.g., as maintained within consent data store **138**), executed authorization module **320** may decline to validate OAuth token **310**, may reject request **304**, and may perform operations that generate and transmit an error message across network **120** to client device **102**, e.g., via API **208** (not illustrated in FIG. 3A).

(74) In other instances, if authorization module **320** were to determine that OAuth token **310** corresponds to or matches OAuth token **272**, executed authorization module **320** may validate OAuth token **310** and request **304**. As illustrated in FIG. 3A, authorization module **320** may route validated request **304** to a consent verification module **322** of executed consent and permissioning engine **142**, which may perform any of the exemplary processes described herein to determine whether executed third-party application **112** and executed consent and permissioning engine **142** each attest to a common level of access previously granted third-party application **112** by user **101**.

(75) For example, executed consent verification module **322** may parse request **304** and extract consent hash value **308** and identifier **312B** of executed third-party application **112**. In some instances, consent hash value **308** may correspond to, and be representative of, an attestation by third-party application **112** of the level of access previously granted third-party application **112** by user **101**. Further, in some examples, executed consent verification module **322** may also access consent data store **138**, and identify and extract a reference consent hash value, e.g., consent hash value **270**, associated with or linked to identifier **312A** (and OAuth token **272**) within consent data store **138**. As described herein, consent hash value **270**, which may be generated by executed consent management module **266** through any of the exemplary decoupled consent and authentication protocols described herein, may correspond to, and be representative of, an attestation by executed consent and permissioning engine **142** (and as such, of computing system **130**), of the level of access previously granted third-party application **112** by user **101**.

(76) In additional, or alternate, examples, executed consent management module **266** perform operations that obtain consent hash value **270** from within one or more elements of a distributed ledger maintained locally by, or available to, computing system **130**. For instance, computing system **130** may maintain, within data repository **132**, a local copy of distributed ledger, such as updated distributed ledger **282**, which establishes an immutable and cryptographically secure record of a temporal evolution in the level of access granted executed third-party application **112** by user **101**. In some examples, executed consent management module **266** may access one or more consent ledger blocks of updated distributed ledger **282**, such as ledger block **288**, that include or reference identifier **312A** of executed third-party application **112**. Executed consent management module **266** may perform operations that establish an association between identifier **312A** and consent hash value **270** within accessed ledger block **288**, and that extract consent hash value **270** from accessed ledger block **288**.

(77) Executed consent verification module **322** may perform additional operations that determine whether consent hash value **308** (e.g., as received from executed third-party application **112**) corresponds to, and matches, consent hash value **270** (e.g., as generated by executed consent management module **266** of computing system **130**). If, for example, consent verification module **322** were to determine an inconsistency between consent hash values **270** and **308**, executed consent verification module **322** may determine that third-party application **112** attests to a level of access to confidential data that differs from, and is inconsistent with, the level of access to which computing system **130** attests (e.g., through consent hash value **270**).

(78) Based on the determined inconsistency, consent verification module **322** may reject request **304**, and may perform operations that generate and transmit an error message across network **120** to client device **102**, e.g., via API **208** (not illustrated in FIG. 3A). In further instances, and based on the determined inconsistency, consent verification module **322** may also perform operations that provision, to executed third-party application **112**, additional information that confirms the level of access to confidential data currently granted to executed third-party application **112** by user **101**, such as, but not limited to, consent hash value **270** or portions of consent document **268**. By way of example, consent verification module **322** may package consent hash value **270** and/or the portions of consent document **268** within the generated error message, e.g., for transmission across network **120**.

(79) In some instances, not illustrated in FIG. 3A, client device **102** may receive the generated error message, e.g., via API **208**, and executed third-party application **112** parse the error message to extract consent hash value **270** (and additionally, or alternatively, the portions of consent document **268**), which may be stored in conjunction with OAuth token **310** within memory **106**, e.g., as a replacement for consent hash value **308** (and additionally, or alternatively, for the previously stored portions of consent document **268**). Certain of these exemplary processes, which facilitate a dynamic re-provisioning of the consent hash value (or other information characterizing the level of access currently granted to executed third-party application **112**) to client device **102** without invalidating a previously provisioned OAuth token, may be implemented by computing system **130** and by client device **102** in addition to, or as an alternate to, certain token-based authorization and consent process that, when implemented in response to the determined inconsistency, invalidate any existing OAuth token, and require an additional authentication of user **101** and a generation of an additional OAuth token.

(80) The disclosed exemplary embodiments are, however, not limited to processes that maintain a validity of a previously generated OAuth token in response to a detected inconsistency between consent hash values **308** and **270** and as such, between the attestations of the level of access previously granted to executed third-party application. By way of example, consent verification module **322** may establish that the inconsistency between consent hash values **270** and **308**, as determined using any of the exemplary processes, represents a latest one in a sequence or pattern of such determined inconsistencies, e.g., between consent hash values submitted by executed third-party application **112** and corresponding consent hash values locally maintained at computing system **130**. Responsive to the determined sequence or pattern of inconsistencies, consent verification module **322** may perform operations that invalidate OAuth token **272**, e.g., through a storage of revocation data (e.g., an invalidation flag) in conjunction with OAuth token **272** within consent data store **138** and additionally or alternatively, through a recordation of the revocation data within an additional one of consent ledger blocks **188** of distributed ledger **186**.

(81) Referring back to FIG. 3A, if executed consent verification module **322** were to determine that consent hash value **308** corresponds to, and matches, consent hash value **270**, executed consent verification module **322** may determine that third-party application **112** and computing system **130** attest to a common level of access granted to executed third-party application **112** by user **101**. Based on the attestation to the common level of granted access, executed consent verification module **322** may perform operations that route request **304** to a consent detection module **324** of executed consent and permissioning engine **142**, which may perform any of the exemplary processes described herein to determine whether the one or more elements of confidential data requested by executed third-party application are consistent with the type or level of access previously granted to executed third-party application by user **101**.

(82) For example, executed consent detection module **324** may parse request **304** to extract data identifiers **306**, which uniquely identify each of the elements of confidential data requested by third-party application **112**, and may perform operations that access consent data store **138** and extract all, or a selected portion, of consent document **268** associated with third-party application

112. In other examples, consent detection module **324**, may obtain all or a portion of consent document **268** from ledger block **288**, e.g., in association with application identifier **312A**. As described herein, consent document **268** may identify one or more types, classes, or discrete elements of data (e.g., as maintained by computing system **130**) that are accessible to executed third-party application **112**, and as illustrated in FIG. 3A, consent document **268** and consent hash value **270** (e.g., that represents consent document **268**) may each be associated with identifier **312A** of executed third-party application **112** within consent data store **138**.

(83) In some examples, and based on a comparison between consent document **268** and data identifiers **306**, executed consent detection module **324** may determine whether each of the requested elements of confidential data (e.g., as specified by identifiers **306**) is consistent with the level of access previously granted to third-party application **112** by user **101** (e.g., as specified within consent document **268**). If, for example, executed consent detection module **324** were to detect an inconsistency between the previously granted level of access (e.g., as specified within consent document **268**) and the requested elements of confidential data, executed consent detection module **324** may determine that the request **304** is inconsistent with the previously granted level of access. In some instances (not illustrated in FIG. 3A), executed consent detection module **324** may discard request **304**, and may perform operations that generate and transmit an error message to executed third-party application **112**, e.g., via API **208**.

(84) Alternatively, if executed consent detection module **324** were to establish a consistency between the previously granted level of access and each of the requested elements of confidential data, executed consent detection module **324** may perform operations that package each of data identifiers **306** into corresponding portions of accessible data identifiers **326**. By way of example, and as described herein, data identifiers **306** may identify requested elements of confidential data that include, but are not limited to, a current account balance of a credit card account held by user **101** and transaction dates and values characterizing a specified number of recent purchase transactions involving that credit card account, e.g., the thirty most-recent purchase transactions involving the credit card account.

(85) Additionally, and as described herein, information within consent document **268** may indicate that user **101** denied third-party application **112** access to elements of confidential customer profile data maintained at computing system **130**, granted third-party application **112** access to any elements of confidential account data maintained on behalf of user **101** by computing system **130**, and Further, the information within consent document **268** may also indicate that user **101** granted third-party application **112** access to elements of confidential transaction data characterizing a transaction type, value, and time for one or more transactions involving user **101**, while denying access to any elements of confidential transaction data characterizing a payment instrument, a product or service, or a counterparty involved in the one or more transactions.

(86) In some examples, executed consent detection module **324** may establish that the requested elements of confidential account and transaction data (e.g., as specified by data identifiers **306**) are each consistent with the accessible types, classes, or discrete elements of confidential data identified by consent document **268**. Executed consent detection module **324** may generate accessible data identifiers **326** that include each of data identifiers **306**, e.g., that identify the current account balance of the credit card account and the transaction dates and values characterizing the thirty most-recent purchase transactions involving the credit card account. Further, executed consent detection module **324** may also generate provisioning data **328** that includes accessible data identifiers **312** and the unique identifier **312B** of client device **102** (e.g., an IP address, a MAC address, etc.), and may provide provisioning data **328** as an input to a provisioning module **330** executed by computing system **130**.

(87) In other instances, executed consent detection module **324** may establish that the requested elements of confidential data associated are partially inconsistent with the previously granted type or level of access (e.g., as specified within consent document **268**). For example, executed consent

detection module **324** may determine that a first subset of the requested elements of the confidential data, as specified by data identifiers **306**, is consistent with the accessible types, classes, or discrete elements of confidential data identified by consent document **268**, which determining that a second subset of the requested elements of confidential data is inconsistent with the accessible types, classes, or discrete elements of confidential data identified by consent document **268**. Executed consent detection module **324** may, in some instances, perform operations that extract a portion of data identifiers **306** that correspond to the accessible first subset, and generate accessible data identifiers **326** that include the extracted portion of data identifiers **306**. Executed consent detection module **324** may further package accessible data identifiers **326** and device identifier **312B** into provisioning data **328**, which executed consent detection module **324** may provide as an input to a provisioning module **330** of computing system **130**.

(88) As illustrated in FIG. 3A, and upon execution by computing system **130**, provisioning module **330** may receive provisioning data **328**, which includes accessible data identifiers **326** and device identifier **312B**. Executed provisioning module **330** may access confidential data store **136**, and identify and perform operations that identify extract elements of confidential data **332** that correspond to accessible data identifiers **326**. For example, confidential data elements **332** may include, among other things, the current account balance of the credit card account held by user **101** (e.g., a balance of \$3,775.00), and the elements of transaction data that specify the transaction dates and values of the thirty, most-recent purchase transactions involving the credit card account. Further, executed provisioning module **330** may encrypt confidential data elements **332** using, for example, a public cryptographic key associated with or assigned to third-party application **112**, and may output elements of encrypted confidential data **334**. Further, executed provisioning module **330** may also apply a digital signature **336** to the elements of encrypted confidential data **334**, e.g., using any appropriate digital signature algorithm in conjunction with a private cryptographic key of computing system **130**.

(89) Executed provisioning module **330** may package the elements of encrypted confidential data **334** into corresponding portions of a response to request **304**, e.g., provisioning response **338**, along with digital signature **336** and a public key certificate **340** of computing system **130** (e.g., that includes a corresponding public cryptographic key). In some instances, executed provisioning module **330** may perform operations that cause computing system **130** to transmit provisioning response **338** across network **120** to client device **102** using any appropriate communications protocol, e.g., via the corresponding communications interface, such as the transceiver device.

(90) Referring to FIG. 3B, API **208** of executed third-party application **112** may receive provisioning response **338**, and may route provisioning response **338** to local validation module **289** of executed third-party application **112**. In some instances, executed local validation module **289** may parse provisioning response **338** to extract digital signature **336** and public key certificate **340**, and may perform operations that validate digital signature **336** based on the public cryptographic key of computing system **130** included within public key certificate **340**. If, for example, local validation module **289** were unable to validate digital signature **336**, local validation module **289** may determine that at least a portion of provisioning response **338** was corrupted or otherwise modified during transmission (e.g., through an interception by one or more malicious parties, etc.), and executed third-party application **112** may discard provisioning response **338** and await additional provisioning response generated and transmitted by computing system **130** (not illustrated in FIG. 3B).

(91) In other examples, and based on a successful validation of digital signature **336**, local validation module **289** may provide the elements of encrypted confidential data **334** as an input to a data processing module **342** of executed third-party application **112**. Executed data processing module **342** may, for instance, perform operations that store the elements of encrypted confidential data **334** within a corresponding portion of memory **106**. Executed data processing module **342** may also access a private cryptographic key of third-party application **112**, and may decrypt the

elements of encrypted confidential data **334**, e.g., to generate decrypted elements of confidential data **344**. Executed data processing module **342** may route the decrypted elements of confidential data **344** to an operations module **346** of executed third-party application **112**, which may perform one or more operations on the decrypted elements of confidential data **344**.

(92) The one or more operations may include, among other things, processes that aggregate, transform, or modify certain of the decrypted elements of confidential data **344**, or that present all or a portion of the decrypted elements of confidential data **344** within a corresponding digital interface. As illustrated in FIG. **3B**, executed operations module **346** may perform operations that generate one or more interface elements **348** that provide a graphical or textual representation of corresponding ones of the decrypted elements of confidential data **344**. Operations module **346** may route each of generated interface elements **348** to display unit **116A** of client device **102**, which may render generated interface elements **348** for presentation within digital interface **350**. For example, digital interface **350** may include interface element **352**, which when rendered for presentation, identifies a current account balance of \$3,775.00 for the credit card account held by user **101**. Further, digital interface **350** may also include additional interface elements **354**, which when rendered for presentation, identify the transaction dates and transaction values of at least a portion of the thirty, most-recent transactions involving the credit card account of user **101**.

(93) In some instances, one or more application programs, engines, or modules executed by client device **102** and computing system **130** (and in some instances, peer systems **180**) may perform one or more of the exemplary, decoupled consent and authorization processes described herein, which enable a user of client device **102**, such as user **101**, to provide permission for one or more third-party applications, e.g., third-party application **112**, to access elements of confidential maintained on behalf of user **101** at a custodian system operating within environment **100**, such as computing system **130**. By way of example, and based on authentication credentials (e.g., provided by user **101** in response to the exemplary digital authentication interfaces described herein) and consent data (e.g., provided by user **101** in response to the exemplary digital consent interfaces described herein) received from client device **102**, computing system **130** may perform any of the exemplary decoupled consent and authorization processes described herein to generate a digital token, e.g., an OAuth token, indicative of a successful authentication of an identity of user **101**, and one or more elements of information, such as the consent document and consent hash value described herein, indicative of a level of access granted by user **101** to executed third-party application.

(94) As described herein, computing system **130** may perform operations that store the generated OAuth token in conjunction with the consent hash value and the consent document, and provision the OAuth token, the consent hash value, and in some instances, all or a portion of the consent document to executed third-party application **112**. Certain of these exemplary processes, which decouple the generation and provisioning of the OAuth token from the generation and provisioning of the consent hash value and corresponding consent document, may be implemented in addition to, or as an alternate to, one or more existing token-based consent and authorization processes, such as the OAuth protocols described herein, which generate a single digital token (e.g., an OAuth token) representative and indicative of both the authorization of user **101** and the consent granted by user **101** to executed third-party application.

(95) In other instances, certain of the exemplary decoupled consent and authorization processes described herein, when implemented by the one or more application programs, engines, or modules executed by client device **102**, computing system **130**, and/or peer systems **180**, may enable user **101** to selectively modify a level of access to confidential data previously granted to a third-party application, while maintaining a validity and a pendency of the OAuth token previously generated and provisioned to that third-party application. By way of example, and referring to as described below, user **101** may provide input to client device **102** that triggers an execution of an application program, such as, but not limited to, mobile banking application **110** provisioned to client device **102** by computing system **130**, or a web browser application capable of accessing computing

system **130**, e.g., via a corresponding web server.

(96) When executed by client device **102**, mobile banking application **110** and/or the web browser application may obtain information from computing system **130** that identifies and characterizes a level of access granted to user **101** to one or more third-party applications executable at client device **102**, such as, but not limited to, third-party applications **112** and **114**. As described herein, executed mobile banking application **110** and/or the executed web browser application may perform operations that render the obtained information within one or more display screens of a corresponding digital interface, which may prompt user **101** to provide input that modifies or revokes a level of access granted to third-party application **112**, third-party application **114**, and additionally, or alternatively, to the one or more additional third-party applications executable at client device **102**. Based on data identifying the modified or revoked access for a particular one of the third-party applications, such as executed third-party application **112** or third-party application **114**, computing system **130** may perform any of the exemplary processes described herein to generate a modified consent document and corresponding consent hash value for that particular third-party application, and to provision the corresponding hash value to the particular third-party application (e.g., alone or in conjunction with the modified consent document), without invalidating a pending and previously generated OAuth token for that particular third-party application, as described in reference to FIGS. **4A-4E**.

(97) Referring to FIG. **4A**, user **101** may provide input **402** to client device **102** (e.g., via input unit **116B**) that requests an execution of an application program associated with and provisioned by computing system **130**, such as mobile banking application **110** or a web browsing application. For example, and upon execution by client device **102**, mobile banking application **110** may generate one or more interface elements that, when rendered for presentation by display unit **116A**, collectively establish one or more display screens of a digital authentication interface (not illustrated in FIG. **4A**). The digital authentication interface may prompt user **101** to provide, via input unit **116B**, one or more authentication credentials that uniquely identify user **101** at computing system **130**, such as, but not limited to, an alphanumeric login credential, an alphanumeric password, or one or more biometric credentials (e.g., a digital image of a face of user **101** or a digital scan of a thumbprint or fingerprint of user **101**).

(98) Executed mobile banking application **110** may receive the one or more authentication credentials, e.g., via input unit **116B**, and may perform operations that authenticate an identity of user **101**. For example, executed mobile banking application **110** may authenticate the identity of user **101** based on a comparison between the received authentication credentials and corresponding locally maintained authentication credentials, or based on interaction with computing system **130**, as described herein. In other examples (not illustrated in FIG. **4A**), as computing system **130** provisioned mobile banking application **110** to client device **102**, executed mobile banking application **110** may perform operations that, in conjunction with one or more application programs, engines, or modules executed by computing system **130**, implements a token-based consent and authorization processes (e.g., an OAuth protocol) to authenticate an identity of user **101** and generate an OAuth token indicative of the successful authentication of the identity of user **101** and a permission of executed mobile banking application **110** to access programmatic interfaces established and maintained by computing system **130**. Computing system **130** may, for instance, provision the OAuth token to executed mobile banking application **110** for storage within memory **106**.

(99) Responsive to a successful authentication of the identity of user **101**, executed mobile banking application **110** may perform operations that identify each of the third-party applications executed by client device **102**, and that generate data requesting, from computing system **130**, a level of access to confidential data currently granted to each of the identified third-party applications by user **101**. By way of example, application repository **108** may maintain third-party applications **112** and **114**, which may include, but are not limited to, a financial management application that tracks

balances of, and transactions involving, one or more accounts held by user **101** based on confidential data maintained at computing system **130** and other computing systems operating within environment **100**. In some instances, not illustrated in FIG. 4A, memory **106** of client device **102** may maintain, for each of third-party applications **112** and **114**, a unique application identifier in conjunction with a corresponding OAuth token and corresponding elements of elements of information, such as a consent hash value (or a corresponding consent document) indicative of the level of access granted to each of third-party applications **112** and **114** to access elements of confidential data maintained at computing system **130**.

(100) Referring back to FIG. 4A, executed mobile banking application **110** may access a portion of memory **106**, such as local credential data store **292**, and may perform operations that extract unique application identifier **406** of third-party application **112** and unique application identifier **408** of third-party application **114**. Examples of application identifiers **406** and **408** may include, but are not limited to, a unique cryptogram, hash value, or other element of cryptographic data that uniquely identify third-party applications **112** and **114** to one or more computing systems that operate within environment **100** and maintain confidential data on behalf of user **101**, such as computing system **130**. In some instances, executed mobile banking application **110** may perform operations that package applications identifiers **406** and **408** into corresponding portions of a request **410** for information that identifies the level of access to confidential data currently granted each of the third-party applications **112** and **114** by user **101**, e.g., through any of the exemplary decoupled consent and authorization processes described herein.

(101) Executed mobile banking application **110** may also perform operations that package, into a portion of request **410**, additional data that identifies executed mobile banking application **110** and further, indicates a successful confirmation of the identity of user **101**, e.g., based on the received authentication credentials using any of the exemplary processes described herein. For example, executed mobile banking application **110** may access local credential data store **292**, and obtain an OAuth token **412** associated with executed mobile banking application **110**, and further, package OAuth token **412** into a corresponding portion of request **410**. As described herein, OAuth token **412** may be indicative not only a successful authentication of the identity of user **101**, but also a permission of executed mobile banking application **110** to access the one or more programmatic interfaces established and maintained by computing system **130**.

(102) Referring back to FIG. 4A, executed mobile banking application **110** may perform additional operations that cause client device **102** to transmit request **410** across network **120** to computing system **130**. A programmatic interface established by and maintained at computing system **130**, such as application programming interface (API) **414**, may receive request **410**, and may route request **410** to consent and permissioning engine **142**, e.g., as executed by computing system **130**. In some instances, and prior to routing request **410** to executed consent and permissioning engine **142**, API **414** may perform a pre-validation process (not illustrated in FIG. 4A) that determines whether a format or structure of OAuth token **412** of executed mobile banking application **110** conforms with an expected token format or structure.

(103) Based on an established consistency between the format or structure of OAuth token **412** and the expected structure or format, API **414** may route request **410** to authorization module **320** of executed consent and permissioning engine **142**. In some instances, executed authorization module **320** may perform any of the exemplary processes described herein to validate OAuth token **412** based on a comparison with, and a determined consistency with, a reference OAuth token locally maintained within consent data store **138** on behalf of executed mobile banking application **110**, e.g., OAuth token **416** maintained within consent data store **138**.

(104) For example, if executed authorization module **320** were to detect an inconsistency between OAuth token **412** (e.g., as received from executed mobile banking application **110**) and OAuth token **416** (e.g., as maintained on behalf of executed mobile banking application **110** within consent data store **138**), executed authorization module **320** may decline to validate OAuth token **412** and

may reject request **410**. Executed authorization module **320** may perform any of the exemplary processes described herein that generate and transmit an error message across network **120** to client device **102**, e.g., via a programmatic interface (not illustrated in FIG. 3A).

(105) In other instances, if executed authorization module **320** were to determine that OAuth token **412** corresponds to or matches OAuth token **416**, executed authorization module **320** may validate OAuth token **412** and request **410**. Responsive to the successful validation, executed authorization module **320** may extract application identifiers **406** and **408** from now-validated request **410**, and may provide application identifiers **406** and **408** as an input to a management module of executed consent and permissioning engine **142**, e.g., consent management module **266**, which may perform any of the exemplary processes described herein to establish a level of access to confidential data previously granted by user **101** to each of third-party applications identified within request **410**, e.g., third-party applications **112** and **114**, and to provision information identifying and characterizing the previously granted level of access to executed mobile banking application **110**.

(106) For example, executed consent management module **266** may receive application identifiers **406** and **408**, which uniquely identify respective ones of third-party applications **112** and **114**. In some instances, executed consent management module **266** may perform operations that access consent data store **138**, and identify and obtain a current consent document associated with, and linked to, each of application identifiers **406** and **408** within consent data store **138**. For example, as illustrated in FIG. 4A, consent data store **138** may maintain, on behalf of third-party application **112**, consent document **268**, consent hash value **270**, and OAuth token **272**, each of which may be associated with application identifier **406**. Further, consent data store **138** may also maintain a consent document **418**, a corresponding consent hash value **420**, and an OAuth token **422** on behalf of third-party application **114**, and may associate each of consent document **418**, consent hash value **420**, and OAuth token **422** within application identifier **408** of third-party application **114**.

(107) As described herein, each of consent documents **268** and **418** may include data that identifies and characterizes a level of access currently granted, or denied, to respective ones of third-party applications **112** and **114** by user **101**. By way of example, consent documents **268** and **418** may, for respective ones of third-party applications **112** and **114**, identify a selective grant of access to specific types or classes of confidential data maintained within confidential data store **136**, such as, but not limited to, customer data, account data, or transaction data maintained on behalf of user **101** by computing system **130**. Additionally, or alternatively, and for respective ones of third-party applications **112** and **114**, consent documents **268** and **418** may also identify a selective grant of access to particular data elements within the specific types or classes of confidential customer data, account data, or transaction data.

(108) Further, and as described herein, consent documents **268** and **418** may identify, for respective ones of third-party applications **112** and **114**, a permission granted by user **101** to perform one or more operations on the accessed elements of confidential data, such as, but not limited to: presenting the accessed elements of confidential data within one or more digital interfaces; storing the accessed elements of confidential data within one or more locally or remotely accessible data repositories; further processing or aggregating the accessed elements of confidential data; or distributing the accessed elements of confidential data to additional related or unrelated computing systems or to application programs executed by these additional or unrelated systems (e.g., fourth- and fifth-party applications, etc.). Each of consent documents **268** and **418** may be formatted in accordance with one or more data-interchange formats, such as, but are not limited to, a JavaScript Object Notation (JSON) format, a YAML format, an Internet-JSON (I-JSON) format, an XML format, or any additional or alternate language-independent, data serialization formats.

(109) In some instances, each of consent documents **268** and **418**, consent hash values **270** and **420**, and OAuth tokens **272** and **422** may be generated through a collective implementation of any of the exemplary, decoupled consent and authentication processes described herein by computing system **130** (e.g., through executed consent and permissioning engine **142**) and client device **102** (e.g., via

an execution of respective ones of third-party applications **112** and **114**). For example, consent hash values **270** and **420** may be representative of consent documents **268** and **418**, respectively, and may be generated through an application of any of the exemplary cryptographic or non-cryptographic hash functions to respective ones of consent documents **268** and **418**. Further, and as described herein, OAuth tokens **272** and **422** may be indicative of a successful authentication of the identity of user **101** and of an authorization for respective ones of third-party application **112** and **142** to access the programmatic interfaces established or maintained by computing system **130**.

(110) Referring back to FIG. **4A**, executed consent management module **266** may access consent data store **138**, and may perform operations that extract consent document **268** associated with third-party application **112**, e.g., as associated with application identifier **406** within consent data store **138**. For example, and as described herein, consent document **268** may indicate that: (i) user **101** denied third-party application **112** access to elements of confidential customer profile data maintained at computing system **130**; (ii) user **101** granted third-party application **112** access to any elements of confidential account data maintained on behalf of user **101** by computing system **130**; and (iii) user **101** granted third-party application **112** access to elements of confidential transaction data characterizing a transaction type, value, and time for one or more transactions involving user **101**. In some instances, executed consent management module **266** may package application identifier **406** and all or a selected portion of consent document **268** within a corresponding portion of current consent data **424**.

(111) Executed consent management module **266** may also perform operations that extract, from consent data store **138**, consent document **418** associated with third-party application **114** (e.g., which may be associated with application identifier **408** within consent data store **138**). For example, and as described herein, consent document **418** may indicate that: (i) user **101** also denied third-party application **114** access to elements of confidential customer profile data maintained at computing system **130**; (ii) user **101** granted third-party application **114** access to elements of confidential account data that identify balances of one or more financial services accounts (e.g., deposit accounts, credit card accounts, etc.) issued to user **101** by the financial system associated with computing system **130**; and (iii) user **101** granted third-party application **114** access to elements of confidential transaction data characterizing a transaction type, value, and time for transactions involving the one or more financial services accounts. In some instances, executed consent management module **266** may package application identifier **408** and all or a selected portion of consent document **418** within a corresponding portion of current consent data **424**.

(112) Although not illustrated in FIG. **4A**, executed consent management module **266** may also extract, from consent data store **138**, consent hash values **270** and **420** associated with respective ones of third-party applications **112** and **114** (e.g., which are representative of respective ones of consent documents **268** and **418**), and may package consent hash values **270** and **420** into corresponding portions of current consent data **424**. In some instances, by incorporating consent hash values **270** and **420** into current consent data **424**, certain of the exemplary embodiments may enable client device **102** to verify an integrity of each of consent documents **268** and **418** through a calculation of respective local hash values and a comparison of the local hash values against corresponding ones of consent hash values **270** and **420**.

(113) Further, and in addition to consent documents (and representative hash values) that identify a level of access granted by user **101** to third-party applications **112** and **114**, current consent data **424** may also include additional information identifying certain types, classes, or elements of confidential data that are maintained on behalf by user **101** by computing system **130** and as such, that are potentially accessible to third-party applications **112** and **114**, when executed at client device **102**. For example, executed consent management module **266** may also perform operations that package, into current consent data **424**, additional information **425**, that identifies certain of the available types or classes of confidential data (e.g., confidential profile, account, or transaction data, etc.), along with certain data elements associated with each of the types or classes (e.g.,

elements of profile data that include governmental identifiers, elements of transaction data that include transaction times, transaction values, and identifiers of corresponding merchants or purchased products, elements of account data that include account identifiers, account balances, etc.).

(114) Executed consent management module **266** may also apply a digital signature **426** to all or a portion of current consent data **424**, e.g., using a private cryptographic key of executed mobile banking application **110**. Executed consent management module **266** may perform operations that cause computing system **130** to broadcast current consent data **424**, applied digital signature **426**, and a public key certificate **428** of executed mobile banking application **110** (e.g., that includes a corresponding public cryptographic key) across network **120** to client device **102**.

(115) Referring to FIG. **4B**, a secure programmatic interface established and maintained by executed mobile banking application **110**, such application programming interface (API) **428**, may receive current consent data **424** (and applied digital signature **426** and public key certificate **428**) from computing system **130**, and may route current consent data **424**, applied digital signature **426**, and public key certificate **428** to executed mobile banking application **110**. In some instances, a verification module **430** of executed mobile banking application **110** may perform operations that verify an integrity of current consent data **424** in response to a successful validation of applied digital signature **426**, e.g., based on the public cryptographic key extracted from public key certificate **428**. In other instances, as described herein, current consent data **424** may also include consent hash values **270** and **420** (e.g., representative of respective ones of consent documents **268** and **418**), and executed verification module **430** may perform additional operations that verify an integrity of each of consent documents **268** and **418** by computing corresponding local hash values (e.g., through an appropriate one of the exemplary hash functions described herein to consent documents **268** and **418**) and by comparing the local hash values against respective ones of consent hash values **270** and **420**.

(116) Based on the verified integrity of current consent data **424** (and additionally, or alternatively, the verified integrity of consent documents **268** and **418**), executed verification module **430** may provide current consent data **424** as an input to a local consent management module **432** of executed mobile banking application **110**. In some instances, executed local consent management module **432** may process current consent data **424** and generate interface elements **434** that, when rendered for presentation by display unit **116A**, collectively establish one or more display screens of a digital consent management interface **436**. In some instances, display screen **436A** of digital consent management interface **436** may prompt user **101** to provide additional input to client device **102** that modifies a level of access previously granted to third-party application **112**, third-party application **114**, and/or other third-party applications executed by client device **102** on a global basis (e.g., a revocation of the previously granted access to all third-party applications) or alternatively, on a semi-global basis (e.g., a revocation of the previously granted access to a selected subset of the third-party applications, such as one or more of third-party application **112** or third-party application **114**).

(117) For example, and as illustrated in FIG. **4B**, display screen **436A** may include an interactive interface element, such as slider element **437**, that enables user **101** to revoke, e.g., on a global basis, all access to confidential data previously to any third-party application executed at client device **102**, such as, but not limited to, executed third-party applications **112** and **114**. In other instances, display screen **436A** may include additional interface elements that identify and summarize a level of access previously granted to each of the third-party applications executed at client device **102**, such as interface elements **438**, which identify and summarize the level of access previously granted to third-party application **112** (e.g., “Third-Party Application A”), and interface elements **439**, which identify and summarize the level of access previously granted to third-party application **113** (e.g., “Third-Party Application B”).

(118) Display screen **436A** may also include one or more interactive interface elements, such as

slider elements **440** and **441**, that enable user **101** to revoke, on a semi-global basis, the level of access previously granted to respective ones of third-party application **112** (e.g., slider element **440**) and third-party application **114** (e.g., slider element **441**). In some instances, display screen **436A** may include additional interface elements, such as “SUBMIT” element **442**, that, when selected by user **101** through additional provided input, confirm an election by user **101** to revoke, or maintain, the level of access granted to third-party application **112**, third-party application **114**, or other third-party applications, either on a global or semi-global basis.

(119) In other examples, one or more display screens of digital consent management interface **436** may facilitate a selective modification of the level of access to specific classes, types, or discrete elements of confidential data previously granted by user **101** to third-party application **112**, third-party application **114**, or other third-party applications executed by client device **102** by user **101**. For instance, as illustrated in FIG. **4B**, display screen **436A** may include additional interactive elements, such as interactive elements **443** and **444** that, when selected by user **101** via input provided to client device **102** (e.g., via input unit **116B**), cause executed local consent management module **432** to further process current consent data **424** and generate additional ones of interface elements **434** that identify one or more types, classes, or discrete elements of confidential data available to the third-party applications (e.g., based on information **425** within current consent data **424**) and further, that identify the level of access to these types, classes, or discrete elements of confidential data granted previously to each of the third-party applications (e.g., based on consent documents **268** and **418** within current consent data **424**). When rendered for presentation within an additional display screen of digital consent management interface **436**, the additional ones of interface elements **434** may enable user **101** to review or modify the classes, types, or discrete elements of confidential data currently accessible to selected ones of the third-party applications, including third-party applications **112** and **114**.

(120) For example, user **101** may provide further input to client device **102** that selects interactive element **444** within display screen **436A**, which indicates an intention by user **101** to review and in some instances, selectively modify, the access previously granted by user **101** to third-party application **114**. Responsive to the further input, executed local consent management module **432** may further process current consent data **424** and generate the additional ones of interface elements **434**, which may rendered by display unit **116A** within an additional display screen **436B** of digital consent management interface **436**, described below in reference to FIG. **4C**.

(121) Referring to FIG. **4C**, display screen **436B** may include interactive interface elements associated with each of the available types or classes of confidential data maintained on behalf of user **101** at computing system **130**, such as slider elements **445**, **446**, and **447** associated with respective ones of the confidential customer profile data, account data, and transaction data maintained on behalf of user **101** at computing system **130**. In some instances, a position of each of slider elements **445**, **446**, and **447** within display screen **436B** may be indicative of an accessibility of the confidential customer profile data, account data, and transaction data to third-party application **114**. For example, when rendered for presentation, slider element **445** may be disposed initially at position **445A** within display screen **436B**, which indicates that user **101** currently denies third-party application **114** access to any elements of confidential customer data maintained at computing system **130**. Further, as illustrated in FIG. **4C**, slider elements **446** and **447** may be disposed initially at respective ones of positions **446A** and **447A**, which indicates that user **101** grants third-party application **114** access to at least a portion of the confidential account and transaction data maintained at computing system **130**.

(122) Display screen **436B** may also include additional interactive interface elements, such as slider elements **448** and **449**, associated with the discrete elements of confidential account data maintained at computing system **130**, such as account numbers, expiration dates, or other account identifiers (e.g., associated with slider element **448**) and corresponding account balances (e.g., associated with slider element **449**). Further, display screen **436B** may include interactive interface

elements, such as slider elements **450**, **451**, **452**, and **453**, associated with respective ones of the discrete elements of confidential transaction data maintained at computing system **130**, such as, but not limited to: (i) a transaction type, value, and time for one or more transactions involving user **101** (e.g., slider element **450**); (ii) a product or service involved in the one or more transactions (e.g., slider element **451**); (iii) a counterparty or merchant involved in the one or more transactions; and (e.g., slider element **452**); and a payment instrument involved in the one or more transactions (e.g., slider element **453**). Display screen **436B** may also include interface elements, such as “SUBMIT” element **454**, that, when selected by user **101** through provided input, confirms a modification to the level of access granted to third-party application **114**.

(123) In some instances, when rendered for presentation by display unit **116A**, an initial disposition of each of slider elements **448**, **449**, **450**, **451**, **453**, and **453** within display screen **436B** may be indicative of an accessibility of the corresponding elements of confidential account and transaction data to third-party application **114** (e.g., as specified within consent document **418**). For example, as illustrated in FIG. **4C**, slider element **448** may be disposed initially at position **448A** within display screen **436B**, which indicates that user **101** currently denies third-party application **114** access to the confidential account numbers, expiration dates, or other account identifiers, and slider element **449** may be disposed initially at position **449A** within display screen **436B**, which indicates that user **101** currently grants third-party application **114** access to the confidential account balances. Further, slider element **450** may be disposed initially at position **450A** within display screen **436B**, which indicates that user **101** currently grants third-party application **114** access to the confidential transaction type, value, and time for the one or more transactions involving user **101**, and slider elements **451**, **452**, and **453** may be disposed initially at respective ones of positions **451A**, **452A**, and **453A** within display screen **436B**, which indicates that user **101** currently denies third-party application **114** access to the confidential transaction data identifying the products or services, counterparties, and payment instruments associated with the one or more transactions involving user **101**.

(124) In some exemplary embodiments, may provide further input to client device **102** (e.g., via input unit **116B**) indicative of an intention to modify the level of access to the confidential customer profile, account, or transaction data currently granted to third-party application **114**. For example, as illustrated in FIG. **4D**, the provided further input may re-position slider elements **451** and **452** from positions **451A** and **452A** to positions **451B** and **452B** within display screen **436**, which collectively indicate an intention to grant third-party application **114** access to the confidential transaction data identifying the products or services and counterparties associated with the one or more transactions, e.g., as maintained on behalf of user **101** at computing system **130**. The further provided input may also indicate a selection of “SUBMIT” element **454**.

(125) Referring to FIG. **4E**, executed local consent management module **432** may receive the further provided input, e.g., additional input **456**, via input unit **116B**. In some instances, executed local consent management module **432** may parse additional input **456** to identify the selection of “SUBMIT” element **454**, which confirms the modification requested by user **101** to the level of access granted to executed third-party application **114**. Executed local consent management module **432** may further parse additional input **456** to extract modification information **458** that identifies: (i) the selective repositioning of slider element **451** from position **451A** to position **451B**, which indicates an intention by user **101** to grant third-party application **114** access to the elements of the confidential transaction data that specifies the products or services associated with the one or more transactions; and (ii) the selective repositioning of slider element **452** from position **452A** to position **452B**, which indicates an intention by user **101** to grant third-party application **114** access to the elements of the confidential transaction data that specify the counterparties associated with the one or more transactions. In some instances, executed local consent management module **432** may package modification information **458** into a corresponding portion of modified consent data **460**, along with application identifier **408** of third-party application **114**.

(126) Further, and as described herein, user **101** may intend to maintain the level of access to confidential data currently granted to third-party application **112**, e.g., the global denial of access to the elements of confidential customer profile data, the global grant of access to the elements of confidential account data, and the selective grant of access to the elements of confidential transaction data characterizing the transaction type, value, and time for the one or more transactions involving user **101**. In some instances, and based on the parsing of additional input **456**, executed local consent management module **432** may fail to detect any requested modification to the level of consent granted to third-party application **112**, and may generate a status information **462** (e.g., a flag, etc.) indicative of the intention of user **101** to maintain the level of access currently granted to third-party application **112**. As illustrated in FIG. **4E**, executed local consent management module **432** may package status information **462** into a corresponding portion of modified consent data **460**, along with application identifier **406** of third-party application **112**, and executed mobile banking application **110** may perform operations that cause client device **102** to transmit modified consent data **460** across network **120** to computing system **130** using any appropriate communications protocol, e.g., via a corresponding programmatic interface, such as API **318**.

(127) Modified consent data **460** may also include OAuth token **412** of executed mobile banking application **110** and in some instances, a unique device identifier **260B** of client device **102** (e.g., an IP address, a MAC address etc.). Further, although not illustrated in FIG. **4E**, executed local consent management module **432** may also perform any of the exemplary processes described herein to apply a digital signature to all or a portion of modified consent data **460**, and executed mobile banking application **110** may perform operations that cause client device **102** to transmit modified consent data **460**, the applied digital signature, and a public key certificate of mobile banking application **110** (which includes a corresponding public key) across network **120** to computing system **130**, e.g., via API **318** of executed consent and permissioning engine **142**.

(128) For example, API **414** may receive and route modified consent data **460** (e.g., either alone or in conjunction with the applied digital signature and the public key certificate) to authorization module **320** of executed consent and permissioning engine **142**. In some instances, and prior to routing modified consent data **460** to authorization module **320**, API **318** may perform operations (not illustrated in FIG. **4E**) that parse modified consent data **460**, extract OAuth token **412**, and perform any of the exemplary initial pre-validation processes described herein to determine that a format or structure of OAuth token **412** conforms with an expected token format or structure.

(129) Based on an established consistency between the format or structure of OAuth token **412** and the expected structure or format, API **414** may route modified consent data **460** (e.g., either alone or in conjunction with the applied digital signature and the public key certificate) to authorization module **320** of executed consent and permissioning engine **142**. Executed authorization module **320** may perform any of the exemplary processes described herein to validate OAuth token **412** based on a comparison, and a determined consistency, with a reference locally maintained within consent data store **138** on behalf of executed mobile banking application **110**, e.g., OAuth token **416**. In some instances, and prior to validating OAuth token **412**, executed authorization module **320** may establish an integrity of modified consent data **460** based on a validation of the applied digital signature using any of the exemplary processes described herein, e.g., based on the public cryptographic key included within the public key certificate.

(130) For example, if executed authorization module **320** were to detect an inconsistency between OAuth token **412** (e.g., as extracted from modified consent data **460**) and OAuth token **416** (e.g., as maintained within consent data store **138**), executed authorization module **320** may decline to validate OAuth token **412** and may reject modified consent data **460**. Executed authorization module **320** may perform any of the exemplary processes described herein that generate and transmit an error message across network **120** to client device **102**, e.g., via a programmatic interface (not illustrated in FIG. **4E**).

(131) In other instances, if executed authorization module **320** were to determine that OAuth token

412 corresponds to or matches OAuth token **416**, authorization module **320** may validate OAuth token **412** and modified consent data **460**. Responsive to the successful validation, executed authorization module **320** may provide modified consent data **460** as an input to consent management module **266** of executed consent and permissioning engine **142**, which may perform any of the exemplary processes described herein to identify the requested modification to, or revocation of, the level of consent previously granted to one or more third-party applications executable at client device **102** (e.g., based on modified consent data **460**), and to generate, for each of the one or more third-party applications, a modified consent document that reflects the requested modification without invalidating a currently pending OAuth token associated with each of the one or more third-party applications.

(132) By way of example, executed consent management module **266** may parse modified consent data **460** to identify application identifier **406** of third-party application **112**, and perform operations that may extract status information **462** associated with, or linked to, application identifier **406** within modified consent data **460**. In some instances, executed consent management module **266** may process status information **462**, and based on a format or structure of status information **462**, or based on a content of status information **462**, detect the intention of user **101** to maintain the level of access currently granted to third-party application **112**. Based on the detected intention, executed consent management module **266** may maintain the pendency and validity of consent document **268**, consent hash value **270**, and OAuth token **272** associated with, or linked to, application identifier **406** within consent data store **138**.

(133) Executed consent management module **266** may further parse modified consent data **460** to identify application identifier **408** of third-party application **114**, and perform operations that may extract modification information **458** associated with, or linked to, application identifier **408** within modified consent data **460**. Executed consent management module **266** may process modification information **458** to identify one or more requested modifications to the level of access previously granted to third-party application **114**, the intention of user **101** to grant third-party application **114** access to the elements of the confidential transaction data that specifies the products or services and the counterparties associated with the one or more transaction. Executed consent management module **266** may also access consent data store **138**, and perform additional operations that extract consent document **418**, which may be associated with application identifier **408** of third-party application **114**.

(134) In some instances, executed consent management module **266** may perform operations that modify portions of consent document **418** in accordance corresponding portions of modification information **458**, and that generate a modified consent document **464** that reflects the requested modifications to the level of access previously granted to third-party application (e.g., that includes both the modified portions of consent document **481**, and any unchanged portions of consent document **418**). Further, executed consent management module **266** may also generate a modified consent hash value **466** based on an application of any of the exemplary hash algorithms described herein to all or a selected portion of modified consent document **464**.

(135) For example, modified consent document **464** may indicate that: (i) user **101** continues to deny third-party application **114** access to elements of confidential customer data maintained at computing system **130**; (ii) user **101** continues to grant third-party application **114** access to elements of confidential account data that identify the account balances of the one or more financial services accounts issued to user **101** by the financial system associated with computing system **130**; and (iii) user **101** now grants third-party application **114** access to elements of confidential transaction data characterizing not only the transaction type, value, and time for the transactions involving the one or more financial services accounts, but also to the products or services and counterparties associated with these transactions. As described herein, modified consent document **464** may also be formatted in accordance with one or more data-interchange formats, such as, but are not limited to, a JavaScript Object Notation (JSON) format, a YAML

format, an Internet-JSON (I-JSON) format, an XML format, or any additional or alternate language-independent, data serialization formats.

(136) Executed consent management module **266** may perform operations that store, within consent data store **138**, modified consent document **464** and modified consent hash value **466** in conjunction with application identifier **408**, which identifies third-party application **114**, and previously generated OAuth token **422**, which confirms an authorization of third-party application **114** to access programmatic interfaces established and maintained by computing system **130**.

Certain of these exemplary decoupled consent and authorization processes, which enable a user to selectively modify a level of access granted previously to third-party application **114** (or other third-party applications executed by client device **102**) without invalidated a corresponding OAuth token, may be implemented in addition to, or as an alternate to, conventional token-based consent and authorization protocols, which couple together a global revocation of the level of access previously granted to third-party application **114** and a generation of a new OAuth token representative of a level of access newly granted to third-party application **114** by user **101**.

(137) In some examples, executed consent management module **266** may perform operations that replace, e.g., overwrite, consent document **418** and consent hash value **420** with corresponding ones of modified consent document **464** and modified consent hash value **466** in consent data store **138**. In other examples, executed consent management module **266** may store application identifier **408**, modified consent document **464**, modified consent hash value **466**, and OAuth token **422** within an additional portion of consent data store **138**, e.g., in conjunction with a corresponding time stamp or other data element that establishes a record of each consent document and consent hash value associated with third-party application **114**.

(138) In other examples (not illustrated in FIG. 4E), executed consent management module **266** may perform operations that package application identifier **408**, modified consent document **464**, and modified consent hash value **466** into corresponding portions of recordation data. Executed consent management module **266** may further apply a digital signature to the recordation data, e.g., using a private cryptographic key of computing system **130**, and may perform operations that cause computing system **130** to broadcast the recordation data, the applied digital signature, and a public key certificate of computing system **130** (e.g., that includes a corresponding public cryptographic key) to one or more of peer systems **180**, including peer system **182**, which may perform any of the exemplary processes described herein to validate the applied digital signature (e.g., based on the public cryptographic key included within the public key certificate) and generate an additional element of distributed ledger **186** that includes application identifier **408**, modified consent document **464**, and modified consent hash value **466**.

(139) By way of example, peer system **182** may successful compute a corresponding, consensus-based proof-of-work or proof-of-stake, may generate an updated distributed ledger to which the additional element is appended (e.g., a latest, longest version of the distributed ledger), and may broadcast the updated distributed ledger across network **120** to additional ones of peer systems **180** and further, to other participants in a distributed-ledger network, such as computing system **130**, for storage in one or more tangible, non-transitory memories. In some instances, the recordation of application identifier **408**, modified consent document **464**, and modified consent hash value **466** within the updated distributed ledger may establish an immutable, and cryptographically secure record of the temporal evolution in the level of consent granted to third-party application by user **101**.

(140) Referring back to FIG. 4E, executed consent management module **266** may generate modified attestation data **468** that includes modified consent hash value **466** and application identifier **408** of third-party application **114** (and in some instances, all or a portion of modified consent document **464**). In some instances, executed consent management module **266** may apply a digital signature **470** to modified attestation data **468** using any appropriate digital signature algorithm in conjunction with a private cryptographic key of computing system **130** (e.g., to further

verify an integrity of modified attestation data **468** during transmission across unsecured communications channels), and may perform operations that cause computing system **130** to transmit modified attestation data **468**, digital signature **470** and a public key certificate **472** of computing system **130** (e.g., that includes a corresponding public cryptographic key) across network **120** to client device **102** using any appropriate communications protocol, e.g., via the corresponding communications interface, such as the transceiver device.

(141) In some instances, API **427** of executed mobile banking application **110** may receive and route modified attestation data **468**, digital signature **470** and a public key certificate **472** to verification module **430** of executed mobile banking application **110**. In some instances, executed verification module **430** may perform any of the exemplary processes described herein to validate digital signature **470** based on the public cryptographic key of computing system **130** included within public key certificate **472**. Based on the successful validation of digital signature **470**, executed verification module **430** may provide modified attestation data **468** as an input to local consent management module **432** of executed mobile banking application **110**, which may perform operations that store modified consent hash value **466** (and in some instances, all or a portion of modified consent document **464**) within a portion of local credential data store **292** accessible to third-party application **114**, e.g., upon execution by processor **104**. As illustrated in FIG. 4E, modified consent hash value **466** (and in some instances, all or a portion of modified consent document **464**) may be stored in conjunction with previously generated, existing, and currently valid OAuth token **474** of third-party application **114**, which may be generated and provisioned to client device **102** by computing system **130** using any of the exemplary processes described herein.

(142) Certain of the exemplary embodiments, including those described herein in reference to FIGS. 4A-4E, are described in terms of one or more exemplary application programs executed at client device **102**, such as mobile banking application **110**. In other examples, the certain operations performed by executed mobile banking application, as described herein, may also be performed by other application programs executed by client device **102**, such as a web browser program that, upon execution of by client device **102**, performs processes that generate and display one or more of the exemplary digital consent management interfaces described herein.

(143) FIG. 5 is a flowchart of an exemplary process **500** for dynamically implementing hash-based consent and permissioning protocols, in accordance with disclosed exemplary embodiments. In some instances, a network-connected computing system operating within environment **100**, such as computing system **130**, may perform one or more of the steps of exemplary process **500**. Further, and as described herein, computing system **130** may perform one or more of the steps of exemplary process **500** based on data exchanged across a secure communications channel with a third-party application executed at a network-connected computing device or system, such as third-party application **112** or third-party application **114** executed at client device **102**.

(144) Referring to FIG. 5, computing system **130** may perform operations that establish a secure channel of communications across network **120** with third-party application **112** (or third-party application **114**) executed at client device **102** (e.g., in step **502**). In some instances, the secure communications channel may be established through one or more programmatic interfaces established or maintained by computing system **130**, such as, but not limited to application programming interface (API) **204**, as described herein.

(145) In some instances, computing system **130** may receive authentication data from client device **102** across network **120** (e.g., in step **504**). As described herein, the received authentication data may include one or more authentication credentials that uniquely identify user **101** of client device **102** at computing system **130** and a unique device identifier of client device **102** (e.g., an IP address, a MAC address, etc.). Computing system **130** may perform any of the exemplary processes described herein to extract the one or more authentication credentials from the authentication data, and to authenticate an identity of user **101** based on a comparison between the one or more extracted authentication credentials and the corresponding reference authentication

credentials maintained at computing system **130** (e.g., in step **506**).

(146) If, for example, computing system **130** were to establish an inconsistency between the extracted and local authentication credentials (e.g., step **506**; NO), computing system may decline to authenticate the identity of user **101** and may decline to grant the executed third-party application (e.g., third-party application **112** or **114**) access to computing system **130**. In step **508**, computing system **130** may perform operations that generate and transmit an error message across network **120** to client device **102**, and exemplary process **500** may then be complete in step **510**.

(147) In other instances, computing system **130** may establish a consistency between the extracted and local authentication credentials, and may authenticate an identity of user **101** (e.g., step **506**; YES). Responsive to the successful authentication, computing system **130** may generate and store confirmation data (e.g., a data flag, etc.) indicative of the successful authentication within an accessible data repository, such as user database **134**, in conjunction with the authentication credentials of user **101** (e.g., as a user identifier) or the device identifier of client device **102** (e.g., in step **512**).

(148) Computing system **130** may also perform operations that generate, and transmit data that requests an initiation of one or more of the exemplary decoupled consent and permissioning processes described herein across network **120** to client device **102** (e.g., in step **514**). By way of example, and as described herein, the generated and transmitted request data may include information that identifies certain types or classes of confidential data maintained on behalf of user **101** by computing system **130** (e.g., confidential profile, account, or transaction data, etc.), along with certain data elements associated with each of the types or classes.

(149) Client device **102** may receive the request data through a corresponding programmatic interface. In some instances, the third-party application executed at client device **102** (e.g., executed third-party applications **112** or **114**) may perform any of the exemplary processes described herein to generate one or more display screens of a digital consent interface, which prompt user **101** to provide input to client device specifying a level of access to the confidential customer, account, or transaction data maintained on behalf of user **101** by computing system **130** granted the executed third-party application by user **101**, e.g., on a global basis, on a semi-global basis (e.g., on a class- or type-specific basis), or on an element-by-element basis.

(150) Referring back to FIG. 5, computing system **130** may receive a response to the transmitted request from client device **102** across network **120** via the secure communications channel (e.g., in step **516**). In some instances, the received response may include consent data that identifies and characterizes the level of access granted to the executed third-party application (e.g., third-party application **112** or **114** executed at client device **102**) by user **101**. The consent data may, for example, include information that identifies one or more classes, types, or discrete elements of the confidential customer, account, and transaction data that are accessible to, or inaccessible to, the executed third-party application. Further, the received response may also include a unique user identifier of user **101**, a unique device identifier of client device **102**, and a unique application identifier of the executed third-party application.

(151) In step **518**, computing system **130** may perform operations that associate the received response with a prior and successful authentication of the identity of user **101**, e.g., based on one or more of the user or device identifiers and the confirmation data. Responsive to the association of the received response with the prior and successful authentication, computing system **130** may perform any of the exemplary processes described herein to generate an application-specific consent document that reflects a level of access granted by user **101** to the executed third-party application (e.g., in step **520**). In some instances, and as described herein, computing system **130** may package all or a portion of the consent data (e.g., as extracted from the received response) into corresponding portions of the application-specific consent document, which may be formatted in accordance with a data interchange format.

(152) Further, in step **520**, computing system **130** may also perform any of the exemplary processes

described herein to compute an application-specific consent hash value representative of the application-specific consent document, e.g., based on an application of any of the hash algorithms described herein to all or a selected portion of the application-specific consent document, either alone or in conjunction within additional data. In some instances, computing system **130** may perform any of the exemplary processes described herein to generate an access token, e.g., an OAuth token, indicative of the successful authentication of the identity of user **101** and of the permission of the third-party application to access one or more programmatic interfaces established or maintained by computing system **130** (e.g., in step **522**).

(153) Computing system **130** may also perform any of the exemplary processes described herein to store, within a locally or remotely accessible data repository, the application-specific consent document, the application-specific consent hash value, and the OAuth token in conjunction with the user, device, and application identifiers, and additionally, or alternatively, to record the application-specific consent document, the application-specific consent hash value, and the application identifier within an additional ledger block of a distributed ledger (e.g., in step **524**). In step **526**, computing system **130** may perform any of the exemplary processes described herein to provision the application-specific consent hash value, the OAuth token, and in some instances, all or a portion of the application-specific consent document, to the third-party application executed at client device **102**. Exemplary process **500** may then pass back to step **510**, and exemplary process **500** is complete.

(154) FIG. **6** is a flowchart of an exemplary process **600** for dynamically managing hash-based consent and permissioning protocols, in accordance with disclosed exemplary embodiments. In some instances, a network-connected computing system operating within environment **100**, such as computing system **130**, may perform one or more of the steps of exemplary process **600**. Further, and as described herein, computing system **130** may perform one or more of the steps of exemplary process **500** based on data exchanged across a secure communications channel with a third-party application executed at a network-connected computing device or system, such as third-party application **112** or third-party application **114** executed at client device **102**.

(155) Referring to FIG. **6**, computing system **130** may receive, from client device **102** across network **120**, a request for to access one or more elements of confidential data (e.g., in step **602**). In some instances, the request may be generated by the third-party application executed at client device **102**, such as third-party application **112** or third-party application **114**, and the requested elements of confidential data may include one or more of the elements of confidential profile, account, and transaction data maintained by computing system **130** on behalf of user **101** of client device **102**. The received request may, for example, include an identifier of each of the requested elements of confidential data, and may further include information that identifies and characterizes one or more operations involving the requested elements of confidential profile, account, and transaction data.

(156) Further, in some instances, the received request may include information that identifies, characterizes, or is representative of a level of access to the elements of confidential profile, account, and transaction data granted to the executed third-party application by user **101**. For example, the received request may include an application-specific consent hash value representative of a corresponding application-specific consent document, which includes information that identifies one or more types, classes, or discrete elements of confidential data accessible to the executed third-party application program. As described herein, the application-specific consent hash value may also represent an attestation, by the executed third-party application, of the level of access to confidential data currently granted to the third-party application by user **101**, e.g., using any of the exemplary decoupled consent and authorization processes described herein. In other examples, the received request may include all or a portion of the corresponding, application-specific consent document, either in addition to, or as an alternate to, the application-specific consent hash value.

(157) The received request may also include an OAuth token associated with the executed third-party application. The OAuth token may, for example, be indicative of an authentication of an identity of user **101** by computing system **130** and an authorization of the executed third-party application to access one or more programmatic interfaces established and maintained by computing system **130**. As described herein, the OAuth token may be generated by, and provisioned to client device **102**, by computing system **130** based on a successful outcome of any of the exemplary decoupled authorization and consent processes described herein.

(158) In some instances, computing system **130** may parse the request to extract the OAuth token associated with the executed third-party application, and may perform any of the exemplary processes described herein to validate the extracted OAuth token based on a determined consistency with a locally accessible reference OAuth token associated with the executed third-party application (e.g., in step **604**). For example, if computing system **130** were to detect an inconsistency between the extracted and reference OAuth tokens, computing system **130** may decline to validate the extracted OAuth token (step **604**; NO), and computing system **130** may decline to grant the third-party application access to the requested elements of confidential data and may discard the request (e.g., in step **606**). Computing system **130** may also perform operations that generate and transmit an error message across network **120** to client device **102** (e.g., also in step **606**). Exemplary process **600** is then complete in step **608**.

(159) If, however, computing system **130** were to establish a consistency between the extracted and reference OAuth tokens (step **604**; YES), computing system **130** may validate the extracted OAuth token, and may perform operations that determine whether the executed third-party application and computing system **130** each attest to a common level of access previously granted third-party application **112** by user **101** (e.g., in step **610**). For example, in step **610**, computing system **130** may extract the consent hash value associated with the executed third-party application from the now-validated request, and may perform any of the exemplary processes described herein to obtain, from an accessible data repository, a reference consent hash value associated with the executed third-party application. In other examples, in step **610**, computing system **130** may obtain the reference consent hash value from one or more elements of a distributed ledger maintained locally by, or available to, computing system **130**, e.g., using any of the exemplary processes described herein.

(160) By way of example, if computing system **130** were to establish an inconsistency between the extracted and reference consent hash values associated with the executed third-party application, computing system **130** may determine that the executed third-party application attests to a level of access to confidential data that differs from, and is inconsistent with, the level of access to which computing system **130** attests (step **610**; NO). Exemplary process **600** may pass back to step **606**, and computing system **130** may decline to granted the executed third-party application access to the requested elements of confidential data, and may discard the request. Computing system **130** may also perform operations that generate and transmit an error message across network **120** to client device **102** (e.g., in also in step **606**).

(161) In some instances, and based on the established inconsistency, computing system **130** may also perform operations any of the exemplary processes described herein to provision, to the executed third-party application, additional information that confirms the level of access to confidential data currently granted to the executed third-party application by user **101**, such as, but not limited to, the reference consent hash value or portions of a corresponding consent document. For example, computing system **130** may package the reference consent hash value and/or the portions of the corresponding consent document within the generated error message (e.g., in step **606**). Exemplary process **600** is then complete in step **608**.

(162) In other examples, if computing system **130** were to determine that extracted consent hash value corresponds to, and matches, the reference consent hash value, computing system **130** may determine that the executed third-party application and computing system **130** attest to a common

level of granted access (step **610**; YES). Based on the attestation to the common level of granted access, computing system **130** may parse the now-validated request to extract the identifiers of the requested elements of confidential data (e.g., in step **612**), and may perform operations that extract, from an accessible data repository, all or a selected portion of a reference consent document **268** associated with the executed third-party application (e.g., in step **614**).

(163) In some instances, and based on the extracted data identifiers and the reference consent document, computing system **130** may perform any of the exemplary processes described herein to determine whether the one or more elements of confidential data requested by third-party application are consistent with the type or level of access previously granted to executed third-party application by user **101** (e.g., in step **616**). For example, in step **612**, and based on a comparison between the reference consent document and the data identifiers, computing system **130**, may determine whether each of the requested elements of confidential data (e.g., as specified by the data identifiers) is consistent with the level of access previously granted to the executed third-party application by user **101** (e.g., as specified within the reference consent document).

(164) If, for example, computing system **130** were to detect an inconsistency between the previously granted level of access and the requested elements of confidential data, computing system **130** may determine that the now-validated request is inconsistent with the previously granted level of access (step **616**; NO). Exemplary process **600** may pass back to step **606**, and may decline to granted the executed third-party application access to the requested elements of confidential data, and may discard the request. In some instances, computing system **130** may perform operations that generate and transmit an error message across network **120** to client device **102** (e.g., also in step **606**). Exemplary process **600** is then complete in step **608**.

(165) Alternatively, if computing system **130** were to establish a consistency between the previously granted level of access and at least the subset of the requested elements of confidential data (e.g., step **616**; YES), computing system **130** may perform any of the exemplary processes described herein to extract least the subset of the requested elements of confidential data from an accessible data repository (e.g., in step **618**). Further, and as described herein, computing system **130** may encrypt the extracted elements of confidential data using a public cryptographic key associated with or assigned to the executed third-party application and in some instances, may apply a digital signature to the encrypted elements of confidential data using any appropriate digital signature algorithm in conjunction with a private cryptographic key of computing system **130** (e.g., in step **620**). Computing system **130** may transmit the encrypted and digitally signed elements of confidential data across network **120** to client device **102** using any appropriate communications protocol (e.g., in step **622**). Exemplary process **600** is then complete in step **608**.

(166) FIG. 7 is a flowchart of an exemplary process **700** for dynamically managing hash-based consent and perm issioning protocols, in accordance with disclosed exemplary embodiments. In some instances, a network-connected computing system operating within environment **100**, such as computing system **130**, may perform one or more of the steps of exemplary process **700**. Further, and as described herein, computing system **130** may perform one or more of the steps of exemplary process **700** based on data exchanged across a secure communications channel with one or more application programs executed at a network-connected computing device or system, such as, but not limited to, a mobile banking application **110** or a web browser executed at client device **102**.

(167) Referring to FIG. 7, computing system **130** may receive a request, from client device **102**, for consent data identifying and characterizing a level of access to confidential data previously granted by user **101** to one or more third-party applications executable at client device **102**, such as, but not limited to, executable third-party applications **112** and **114** described herein (e.g., in step **702**). The received request may include a unique application identifier of each of the executable third-party applications, and in some instances, may be generated by executed mobile banking application **110** or by the executed web browser in response to a successful authentication of an identity of user **101**, e.g., using any of the exemplary processes described herein.

(168) The received request may also include an OAuth token indicative of the successful authentication of the identity of user **101** and of an authorization of the one or more executed application programs, such as executed mobile banking application **110**, to access programmatic interfaces established or maintained by computing system **130**. In some instances (not illustrated in FIG. 7), computing system **130** may perform any of the exemplary processes described herein to verify the OAuth token included within the received request based on a comparison with a reference OAuth token locally maintained within an accessible data repository.

(169) In some examples, computing system **130** may extract the application identifiers of each of the executable third-party applications, and based on the may perform any of the exemplary processes described herein to identify and obtain a current consent document and a current consent hash value associated with each extracted application identifier and as such, each executable third-party application (e.g., in step **704**). Further, computing system **130** may perform any of the exemplary processes described herein to obtain additional information identifying certain types, classes, or elements of confidential customer, account, and transaction data that are maintained on behalf by user **101** by computing system **130** and as such, that are potentially accessible to each of the one or more third-party applications, when executed at client device **102** (e.g., in step **706**).

(170) Additionally, computing system **130** may perform any of the exemplary processes described herein to generate current consent data that associates each consent document with a corresponding identifier of a third-party application program executed at client device **102** (e.g., third-party applications **112** or **114**, etc.) and further, that includes the additional information identifying the potentially available classes, types, or discrete elements of confidential customer, account, and transaction data (e.g., in step **708**). Further, in step **708**, computing system **130** may perform operations that digitally sign to the current consent data, and that transmit the digitally signed current consent data across network **120** to client device **102**.

(171) As described herein, client device **102** may receive the digitally signed current consent data through a corresponding programmatic interface. In some instances, the one or more application programs executed by client device **102**, e.g., executed mobile banking application **110** or the executed web browser, may validate the digital signature applied to the current consent data, and may perform any of the exemplary processes described herein to process the current consent data and generate one or more display screens of a digital consent management interface, which prompts user **101** to provide input to client device modifying a level of access to the confidential customer, account, or transaction data previously granted to one or more of the executed third-party applications, e.g., on a global basis, on a semi-global basis (e.g., on an application-specific basis, or on a class- or type-specific basis), or on an element-by-element basis.

(172) In step **710**, computing system **130** may receive modified consent data from client device **102**, e.g., across network **120** through a corresponding programmatic interface. In some instances, the modified consent data may be generated by the one or more application programs executed by client device **102** (e.g., executed mobile banking application **110** or the executed web browser) based on input provided by user **101** (e.g., to client device **102** via input unit **1166**) in response to the one or more display screens of the digital consent management interface.

(173) As described herein, the modified consent data may associate the unique application identifier of each of the one or more executable third-party applications (e.g., third-party applications **112** or **114**) with either: (i) elements of modification information that identify a requested modification to the level of access to confidential data previously granted by user **101** to an executable third-party application associated with the unique application identifier; or (ii) elements of status information indicative of an intention to maintain the level of access to confidential data previously granted by user **101** to the that executable third-party application. In some instances, a digital signature may be applied to the modified consent data, and although not illustrated in FIG. 7, computing system **130** may perform any of the exemplary processes described herein to validate the applied digital signature and as such, to validate an integrity of the modified

consent data received from client device **102**.

(174) Further, the modified consent data may also include an additional OAuth token indicative of the successful authentication of the identity of user **101** and of an authorization of the one or more executed application programs, such as executed mobile banking application **110**, to access programmatic interfaces established or maintained by computing system **130**. In some instances (not illustrated in FIG. 7), computing system **130** may perform any of the exemplary processes described herein to verify the additional OAuth token included within the received request based on a comparison with a reference OAuth token locally maintained within an accessible data repository.

(175) In some instances, computing system **130** may parse the modified consent data and access the unique application identifier of a corresponding third-party application executable at client device **102**, such as, but not limited to, third-party applications **112** or **114** (e.g., in step **712**). Based on the accessed unique application identifier, computing system **130** may perform further operations that determine whether the modified consent data specifies a requested modification to the level of access to confidential data previously granted by user **101** to the corresponding executable third-party application (e.g., in step **714**).

(176) For example, and based on portions of the modified consent data, computing system **130** may establish an association between the accessed application identifier and one or more elements of modification information, which specify the requested modification to the corresponding third-party application. Responsive to the established association between the accessed application identifier and the modification information, computing system **130** may determine that modified consent data specifies a requested modification (e.g., step **714**; YES), and computing system **130** may perform operations that extract the modification information associated with the accessed application identifier from the modified consent data (e.g., in step **716**). Computing system **130** may also obtain, from an accessible data repository (e.g., consent data store **138** of FIG. 1), an existing consent document associated with the accessed application identifier and as such, the corresponding executable third-party application (e.g., also in step **716**). As described herein, the existing consent document may identify and characterize the level of access to confidential data previously granted to the corresponding executable third-party application by user **101**.

(177) In some examples, computing system **130** may perform any of the exemplary processes described herein to generate a modified consent document for the corresponding executable third-party application based on the extracted modification information and the existing consent document, and to generate a modified consent hash value that represents all or a portion of the modified consent document (e.g., in step **718**). The modified consent document may, for example, reflect the requested modification to the level of access to confidential data previously granted by user **101** to the corresponding executable third-party application, and computing system **130** may generate the modified consent document and the modified consent hash value without invalidating an existing OAuth token associated with the corresponding executable third-party application.

(178) Computing system **130** may also perform any of the exemplary processes described herein to store, within the accessible data repository (e.g., consent data store **138**), the modified consent document and the modified consent hash value in conjunction with the accessed application identifier, which identifies the corresponding executable third-party application, and the existing OAuth token, which confirms an authorization of the corresponding executable third-party application to access programmatic interfaces established and maintained by computing system **130** (e.g., in step **720**). Additionally, or alternatively, in step **720**, computing system **130** may also perform any of the exemplary processes described herein to record the modified consent document, the modified consent hash value, and the accessed application identifier within an additional ledger block of a distributed ledger. Exemplary process **700** may then pass to step **722**, and computing system **130** may perform further operations that parse the modified consent data to identify a presence of one or more additional application identifiers.

(179) Referring back to step **174**, and based on portions of the modified consent data, computing

system **130** may establish an association between the accessed application identifier and one or more elements of status information, which specify the intention of user **101** to maintain the level of access to confidential data previously granted by user **101** to the corresponding executable third-party application. Responsive to the established association between the accessed application identifier and the status information, computing system **130** may determine that modified consent data fails to specify a requested modification (e.g., step **174**; NO), and computing system **130** may decline to modify the consent document associated with the corresponding executable third-party application (e.g., in step **724**). Exemplary process **700** may then pass back to step **722**, and computing system **130** may perform further operations that parse the modified consent data to identify a presence of one or more additional application identifiers.

(180) If, for example, computing system **130** were to identify an additional application identifier within the modified consent data (step **722**; YES), exemplary process **700** may pass back to step **714**, and computing system **130** may perform any of the exemplary processes described herein to determine whether the modified consent data specifies a requested modification to the level of access to confidential data previously granted by user **101** to an executable third-party application associated with the additional application identifier. Alternatively, if computing system **130** were unable to identify any additional application identifiers within the modified consent data (e.g., step **722**; NO), computing system **130** may perform any of the exemplary processes described herein to provision each of the modified consent hash values, and in some instances, all or a portion of corresponding ones of the modified consent document, to client device **102**, for storage in local data repository in conjunction with corresponding ones of the existing, and previously stored, OAuth tokens (e.g., in step **726**). Exemplary process **700** is then complete in step **728**.

III. Exemplary Hardware and Software Implementations

(181) Embodiments of the subject matter and the functional operations described in this specification can be implemented in digital electronic circuitry, in tangibly-embodied computer software or firmware, in computer hardware, including the structures disclosed in this specification and their structural equivalents, or in combinations of one or more of them. Exemplary embodiments of the subject matter described in this specification, such as, but not limited to, mobile banking application **110**, third-party applications **112** and **114**, consent and permissioning engine **142**, local authorization and consent module **210**, APIs **204**, **208**, **318**, validation module **262**, consent management module **266**, local validation module **289**, request management module **302**, authorization module **320**, consent verification module **322**, consent detection module **324**, provisioning module **330**, data processing module **342**, operations module **346**, verification module **430**, local consent management module **432**, can be implemented as one or more computer programs, i.e., one or more modules of computer program instructions encoded on a tangible non-transitory program carrier for execution by, or to control the operation of, a data processing apparatus (or a computer system).

(182) Additionally, or alternatively, the program instructions can be encoded on an artificially generated propagated signal, such as a machine-generated electrical, optical, or electromagnetic signal that is generated to encode information for transmission to suitable receiver apparatus for execution by a data processing apparatus. The computer storage medium can be a machine-readable storage device, a machine-readable storage substrate, a random or serial access memory device, or a combination of one or more of them.

(183) The terms “apparatus,” “device,” and “system” refer to data processing hardware and encompass all kinds of apparatus, devices, and machines for processing data, including, by way of example, a programmable processor such as a graphical processing unit (GPU) or central processing unit (CPU), a computer, or multiple processors or computers. The apparatus, device, or system can also be or further include special purpose logic circuitry, such as an FPGA (field programmable gate array) or an ASIC (application-specific integrated circuit). The apparatus, device, or system can optionally include, in addition to hardware, code that creates an execution

environment for computer programs, such as code that constitutes processor firmware, a protocol stack, a database management system, an operating system, or a combination of one or more of them.

(184) A computer program, which may also be referred to or described as a program, software, a software application, a module, a software module, a script, or code, can be written in any form of programming language, including compiled or interpreted languages, or declarative or procedural languages, and it can be deployed in any form, including as a stand-alone program or as a module, component, subroutine, or other unit suitable for use in a computing environment. A computer program may, but need not, correspond to a file in a file system. A program can be stored in a portion of a file that holds other programs or data, such as one or more scripts stored in a markup language document, in a single file dedicated to the program in question, or in multiple coordinated files, such as files that store one or more modules, sub-programs, or portions of code. A computer program can be deployed to be executed on one computer or on multiple computers that are located at one site or distributed across multiple sites and interconnected by a communication network.

(185) The processes and logic flows described in this specification can be performed by one or more programmable computers executing one or more computer programs to perform functions by operating on input data and generating output. The processes and logic flows can also be performed by, and apparatus can also be implemented as, special purpose logic circuitry, such as an FPGA (field programmable gate array), an ASIC (application-specific integrated circuit), one or more processors, or any other suitable logic.

(186) Computers suitable for the execution of a computer program include, by way of example, general or special purpose microprocessors or both, or any other kind of central processing unit. Generally, a CPU will receive instructions and data from a read-only memory or a random-access memory or both. Computers consistent with the disclosed exemplary embodiments may include a CPU for performing or executing instructions and one or more memory devices for storing instructions and data. Generally, a computer will also include, or be operatively coupled to receive data from or transfer data to, or both, one or more mass storage devices for storing data, such as magnetic, magneto-optical disks, or optical disks. However, a computer need not have such devices. Moreover, a computer can be embedded in another device, such as a mobile telephone, a personal digital assistant (PDA), a mobile audio or video player, a game console, a Global Positioning System (GPS) receiver, or a portable storage device, such as a universal serial bus (USB) flash drive.

(187) Computer-readable media suitable for storing computer program instructions and data include all forms of non-volatile memory, media and memory devices, including by way of example semiconductor memory devices, such as EPROM, EEPROM, and flash memory devices; magnetic disks, such as internal hard disks or removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks. The processor and the memory can be supplemented by, or incorporated in, special purpose logic circuitry.

(188) To provide for interaction with a user, embodiments of the subject matter described in this specification can be implemented on a computer having a display unit, such as a CRT (cathode ray tube) or LCD (liquid crystal display) monitor, for displaying information to the user and a keyboard and a pointing device, such as a mouse or a trackball, by which the user can provide input to the computer. Other kinds of devices can be used to provide for interaction with a user as well; for example, feedback provided to the user can be any form of sensory feedback, such as visual feedback, auditory feedback, or tactile feedback; and input from the user can be received in any form, including acoustic, speech, or tactile input. In addition, a computer can interact with a user by sending documents to and receiving documents from a device that is used by the user; for example, by sending web pages to a web browser on a user's device in response to requests received from the web browser.

(189) Implementations of the subject matter described in this specification can be implemented in a

computing system that includes a back-end component, such as a data server, or that includes a middleware component, such as an application server, or that includes a front-end component, such as a computer having a graphical user interface or a Web browser through which a user can interact with an implementation of the subject matter described in this specification, or any combination of one or more such back-end, middleware, or front-end components. The components of the system can be interconnected by any form or medium of digital data communication, such as a communication network. Examples of communication networks include a local area network (LAN) and a wide area network (WAN), such as the Internet.

(190) The computing system can include clients and servers. A client and server may be disposed remote from each other and may interact through a communication network. The relationship of client and server arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other. In some implementations, a server transmits data, such as an HTML page, to a user device, such as for purposes of displaying data to and receiving user input from a user interacting with the user device, which acts as a client. Data generated at the user device, such as a result of the user interaction, can be received from the user device at the server.

(191) Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve certain results. In certain circumstances, multitasking and parallel processing may be advantageous. Moreover, the separation of various system components in the embodiments described above should not be understood as requiring such separation in all embodiments, and it should be understood that the described program components and systems may generally be integrated together in a single software product or packaged into multiple software products.

(192) Various embodiments have been described herein with reference to the accompanying drawings. It will, however, be evident that various modifications and changes may be made thereto, and additional embodiments may be implemented, without departing from the broader scope of the disclosed embodiments as set forth in the claims that follow.

(193) Further, other embodiments will be apparent to those skilled in the art from consideration of the specification and practice of one or more embodiments of the present disclosure. It is intended, therefore, that this disclosure and the examples herein be considered as exemplary only, with a true scope and spirit of the disclosed embodiments being indicated by the following listing of exemplary claims.

Claims

1. An apparatus, comprising: a communications interface; a memory storing instructions; and at least one processor coupled to the communications interface and the memory, the at least one processor being configured to execute the instructions to: receive, via the communications interface, consent data from a device, the consent data comprising an identifier of at least one of a data class or data type, information indicating an accessibility of one or more elements of data associated with the at least one of the data class or data type to an application program that is executed by the device and indicating a permission of the application program to perform one or more operations on the one or more elements of data, data identifiers of the one or more elements of data associated with at least one of the data class or data type, and an application identifier of the application program; generate a consent document for the application program based on at least a portion of the consent data; generate a consent hash value representative of the consent document, the consent document comprising status data that confirms an accessibility of corresponding ones of the one or more elements of data associated with the at least one data class or data type to the application program, and that confirms the permission of the of the application program to perform

the one or more operations on the one or more elements of data; obtain an access token of the application program and the consent document from a portion of the memory based on at least the application identifier; and transmit, to the device via the communications interface, the access token and permissioning data that includes at least the consent hash value, the permissioning data comprising information that instructs the application program to store the access token and the consent hash value within a local memory of the device and to associate the consent hash value and the access token within the local memory.

2. The apparatus of claim 1, wherein the at least one processor is further configured to execute the instructions to transmit the access token and the permissioning data to the device through a programmatic interface associated with the application program.

3. The apparatus of claim 1, wherein: the access token comprises an OAuth token; the at least one processor is further configured to execute the instructions to store the OAuth token, the consent document, the consent hash value, and the application identifier of the application program within the portion of the memory.

4. The apparatus of claim 1, wherein the at least one processor is further configured to execute the instructions to: generate a recordation request that includes the consent document, the consent hash value, and the application identifier of the application program; transmit the generated recordation request to one or more peer systems via the communications interface, the recordation request comprising additional information that causes the one or more peer systems to perform operations that record the consent document, the consent hash value, and the application identifier within an element of a distributed ledger; and receive at least a portion of the distributed ledger via the communications interface and store the received portion of the distributed ledger within the memory.

5. The apparatus of claim 1, wherein the at least one processor is further configured to execute the instructions to store the consent document, the consent hash value, and the application identifier within a portion of the memory.

6. The apparatus of claim 5, wherein the at least one processor is further configured to execute the instructions to: receive modified consent data from the device via the communications interface, the modified consent data comprising modification information that identifies a requested modification to an accessibility of at least one of the data elements to the application program; generate a modified consent document based on the modification information and the consent document, and generate a modified consent hash value representative of the modified consent document, the modified consent document reflecting the requested modification to the accessibility of the at least one of the data elements; and transmit, via the communications interface, modified permissioning data that includes the modified consent hash value to the device, the modified permissioning data comprising additional information that instructs the application program to store the modified consent hash value within the local memory of the device and to associate the modified consent hash value with the access token of the application program.

7. The apparatus of claim 6, wherein the requested modification comprises at least one of (i) a modification to a level of access to the at least one of the data elements or (ii) a revocation of the access to the at least one of the data elements.

8. The apparatus of claim 5, wherein the at least one processor is further configured to: receive, via the communications interface, a request for an element of data from the device, the request being generated by the application program executed at the device, and the request comprising a local consent hash value, the access token, and the application identifier; validate the access token, and based on the validated access token, obtain the consent document and the consent hash value from the portion of the memory; determine that the local consent hash value corresponds to the consent hash value associated with the application program, and determine that the requested data element is accessible to the application program based on a corresponding one of the elements of status data associated with the requested data element; based on the determination that the local consent hash

value corresponds to the consent hash value and that the data element is accessible to the application program, load the requested data element from the memory and encrypt the requested data element using a public cryptographic key associated of the application program; and transmit the encrypted data element to the device via the communications interface.

9. The apparatus of claim 1, wherein the at least one processor is further configured to execute the instructions to generate the permissioning data based on at least a portion of the consent document.

10. The apparatus of claim 9, wherein: the permissioning data further comprises at least the portion of the consent document; and the information further instructs the application program to store the portion of the consent document and the consent hash value within the local memory of the device and to associate the portion of the consent document and the consent hash value with the access token of the application program.

11. The apparatus of claim 1, wherein the at least one processor is further configured to execute the instructions to: receive, from the device via the communications interface, modified consent data that characterizes a modification to an accessibility of at least one of the data elements to the application program; generate a modified consent document for the application program based on the modified consent data and on the consent document, and generate a modified consent hash value representative of the modified consent document, the modified consent document reflecting the modification to the accessibility of the at least one of the data elements; and transmit, via the communications interface, modified permissioning data that includes the modified consent hash value to the device, the modified permissioning data comprising additional information that instructs the application program to store the modified consent hash value within the local memory of the device and to associate the modified consent hash value with the access token of the application program.

12. A computer-implemented method, comprising: receiving, using at least one processor, consent data from a device, the consent data comprising an identifier of at least one of a data class or data type, information indicating an accessibility of one or more elements of data associated with the at least one of the data class or data type to an application program that is executed by the device and indicating a permission of the application program to perform one or more operations on the one or more elements of data, data identifiers of the one or more elements of data associated with at least one of the data class or data type, and an application identifier of the application program; generating, using the at least one processor, a consent document for the application program based on at least a portion of the consent data; generating, using the at least one processor, a consent hash value representative of the consent document, the consent document comprising status data that confirms an accessibility of corresponding ones of the one or more elements of data associated with the at least one data class or data type to the application program and that confirms the permission of the of the application program to perform the one or more operations on the one or more elements of data; obtaining, using the at least one processor, an access token of the application program and the consent document from a portion of a memory based on at least the application identifier; and transmitting, using the at least one processor, the access token and permissioning data that includes at least the consent hash value to the device, the permissioning data comprising information that instructs the application program to store the access token and the consent hash value within a local memory of the device and to associate the consent hash value and the access token within the local memory.

13. An apparatus, comprising: a communications interface; a memory storing instructions; and at least one processor coupled to the communications interface and to the memory, the at least one processor being configured to execute the instructions to: receive, via the communications interface, a request for an element of data, the request being generated by an application program that is executed at a device, the data element is associated with the at least one of a data type or data class, and the request comprising a first consent hash value, a first access token, data identifiers of the data element associated with at least one of the data class or data type, and an

application identifier of the application program; based on the application identifier, obtain a consent document, a second consent hash value representative of the consent document, and a second access token associated with the application program from a portion of the memory, the consent document comprising status data that confirms an accessibility of a plurality of data elements associated with the at least one of the data class or data type to the application program and that confirms a permission of the application program to perform one or more operations on the plurality of data elements; based on a determination that the first consent hash value corresponds to the second consent hash value, and based on an established consistency between the first access token and the second access token, determine that data element is accessible to the application program and that the application program is permitted to perform the one or more operations on the data element based on the consent document; and obtain the data element, encrypt the data element, and transmit the encrypted data element to the device via the communications interface.

14. The apparatus of claim 13, wherein the at least one processor is further configured to execute the instructions to determine that the plurality of data elements include the data element and to determine that the data element is accessible to the application program based on a corresponding one of the elements of status data associated with the data element.

15. The apparatus of claim 13, wherein the at least one processor is further configured to execute the instructions to: load the data element from the memory based on the determination that the that the first consent hash value corresponds to the second consent hash value, based on the established consistency between the first access token and the second access token, and based on the determination that the data element is accessible to the application program; encrypt the data element using a public cryptographic key associated with the application program; and transmit, via the communications interface, the encrypted data element to the device through a programmatic interface associated with the application program.

16. The apparatus of claim 13, wherein the at least one processor is further configured to execute the instructions to: based on the application identifier, access a portion of the memory that includes the consent document, the second consent hash value, and the second access token; and obtain the consent document, the second consent hash value, and the second access token from the portion of the memory.

17. The apparatus of claim 13, wherein the at least one processor is further configured to execute the instructions to load the data element from the memory the based on the established consistency between the first and second access tokens, based on the determination that the first consent hash value corresponds to the second consent hash value, and based on the determination that data element is accessible to the application program.

18. The apparatus of claim 13, wherein the at least one processor is further configured to execute the instructions to: determine an inconsistency between the first consent hash value and the second consent hash value; and based on the determined inconsistency, perform operations that invalidate the second access token.

19. The apparatus of claim 13, wherein the at least one processor is further configured to: determine an inconsistency between the first consent hash value and the second consent hash value; based on the determined inconsistency, generate a message that includes the second consent hash value; and transmit, via the communications interface, the message to the device via a programmatic interface associated with the application program.

20. The apparatus of claim 13, wherein the at least one processor is further configured to execute the instructions to: load at least one ledger block of a distributed ledger from the memory; based on the application identifier, access a portion of the at least one ledger block that includes the consent document and the second consent hash value associated with the application program; and obtain the consent document and the second consent hash value from the portion of the at least one ledger block.

21. The apparatus of claim 13, wherein the at least one processor is further configured to execute

the instructions to: receive consent data from the device via the communications interface, the consent data identifying one or more additional elements of data accessible to a third-party application program executed by the device, the consent data comprising an additional application identifier associated with the third-party application program; generate a third consent document for the third-party application program based on at least a portion of the consent data and compute a third consent hash value representative of the third consent document; and obtain a third access token associated with the third-party application program based on at least the additional application identifier, and transmit, via the communications interface, the third access token and permissioning data that includes the third consent hash value to the device, the permissioning data comprising information that instructs the third-party application program to store the third access token and the third consent hash value within a local memory of the device and to associate the third consent hash value and the third access token within the local memory.
