

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250276232

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

PETERSON; JACK W. et al.

INTERACTIVE ARTIFICIAL INTELLIGENCE GOLF ASSISTANT SYSTEM

Abstract

The embodiments disclose a system for interactively providing golf swing guidance to a user on a golf course including a database coupled to a remote server to collect, store and maintain updated topography of golf courses based on LIDAR, a club sensor configured to removably attach to one or more portions of the golf club and further configured to collect the club sensor golf club swing data as the user operates the golf club in a practice swing, a remote server configured to interactively identify a location of a user on the LIDAR topography when positioned at a golf course using a real-time kinematics device, a user audio device wirelessly coupled to the remote server configured to interactively communicate feedback guidance to and from the user of golf club selection and golf club swing adjustments.

Inventors: PETERSON; JACK W. (Elk Ridge, UT), ELLINS; CRAIG (Las Vegas, NV), DEFRANK; EDMOND (Northridge, CA)

Applicant: PETERSON; JACK W. (Elk Ridge, UT); ELLINS; CRAIG (Las Vegas, NV); DEFRANK; EDMOND (Northridge, CA)

Family ID: 92898819

Appl. No.: 19/206029

Filed: May 12, 2025

Related U.S. Application Data

parent US continuation 18737987 20240608 parent-grant-document US 12296246 child US 19206029

parent US continuation-in-part 18224483 20230720 parent-grant-document US 12011653 child US 18737987

us-provisional-application US 63393193 20220728

Publication Classification

Int. Cl.: **A63B69/36** (20060101); **A63B24/00** (20060101); **A63B71/06** (20060101)

U.S. Cl.:

CPC **A63B69/3635** (20130101); **A63B24/0006** (20130101); **A63B24/0062** (20130101);
 A63B71/0622 (20130101); A63B2024/0009 (20130101); A63B2071/0655 (20130101);
 A63B2220/12 (20130101); A63B2220/40 (20130101); A63B2220/56 (20130101);
 A63B2220/808 (20130101); A63B2220/833 (20130101); A63B2220/89 (20130101);
 A63B2225/20 (20130101); A63B2225/50 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This Patent Application is a Continuation and claims priority to the United States patent application entitled “INTERACTIVE ARTIFICIAL INTELLIGENCE GOLF ASSISTANT SYSTEM”, U.S. Ser. No. 18/737,987 filed on Jun. 8, 2024, by Jack W. Peterson, which is a Continuation-in-part of the United States patent application entitled “SYSTEM FOR PROVIDING PUTTING SPEED AND DIRECTION”, U.S. Ser. No. 18/224,483 filed on Jul. 20, 2023, by Jack W. Peterson,” which claims priority to U.S. Provisional Patent Application No. 63/393,193, filed Jul. 28, 2022, and entitled “Digital Compass”, all being incorporated herein by reference.

BACKGROUND

[0002] Golf courses vary from one to another. A golfer faces challenges to score an acceptable completion of play on each course. The golfer is tasked with judging numerous distances, avoiding physical hazards and obstacles, and avoiding errant shots that can cost penalty strokes. Each hole on a course has a distinct set of characteristics that confront the golfer, some of which can be seen and others that are out of view. Even professional golfers can get frustrated when their golf shots are not going well. What is required is some assistance in conducting the myriad of tasks required to make good golf shots on the variances of golf courses and holes.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- [0003] FIG. 1 shows for illustrative purposes only an example of an AI module application of one embodiment.
- [0004] FIG. 2A shows for illustrative purposes only an example of a glasses display of one embodiment.
- [0005] FIG. 2B shows for illustrative purposes only an example of the satellite topography of one embodiment.
- [0006] FIG. 3 shows for illustrative purposes only an example of satellite golf course contours of one embodiment.
- [0007] FIG. 4 shows for illustrative purposes only an example of lidar real-time kinematics golf course terrain details of one embodiment.
- [0008] FIG. 5 shows a block diagram of an overview flow chart of a golf ball recognition device of one embodiment.
- [0009] FIG. 6 shows a block diagram of an overview flow chart of calibrating the AI assistant

module of one embodiment.

[0010] FIG. 7 shows a block diagram of an overview flow chart of calibrating AI assistant module continuation of one embodiment.

[0011] FIG. 8 shows a block diagram of an overview flow chart of determining the type of shot with user confirmation of one embodiment.

[0012] FIG. 9 shows a block diagram of an overview flow chart of interacting with the user on the club selection of one embodiment.

[0013] FIG. 10 shows for illustrative purposes only an example of recording swing sensor data and shot sensor data of one embodiment.

[0014] FIG. 11 shows a block diagram of an overview of using shot sensor data to automatically set up the next shot of one embodiment.

[0015] FIG. 12 shows a block diagram of an overview of a tee shot of one embodiment.

[0016] FIG. 13A shows a block diagram of an overview of a tee shot visual suggestion of one embodiment.

[0017] FIG. 13B shows for illustrative purposes only an example of driver golf club distance and dispersion of one embodiment.

[0018] FIG. 13C shows for illustrative purposes only an example of a 2-iron golf club distance and dispersion of one embodiment.

[0019] FIG. 14 shows for illustrative purposes only an example of a RTK golf course hole plan view of one embodiment.

[0020] FIG. 15 shows for illustrative purposes only an example of the real-time kinematics of one embodiment.

[0021] FIG. 16 shows for illustrative purposes only an example of artificial intelligence (AI) suggestions of one embodiment.

[0022] FIG. 17 shows a block diagram of an overview of the AI module application of one embodiment.

[0023] FIG. 18 shows for illustrative purposes only an example of vital signs wearable of one embodiment.

[0024] FIG. 19 shows for illustrative purposes only an example of an approach shot of one embodiment.

[0025] FIG. 20A shows for illustrative purposes only an example of a bunker shot of one embodiment.

[0026] FIG. 20B shows for illustrative purposes only an example of a geometric calculated approach shot over a tree of one embodiment.

[0027] FIG. 21 shows for illustrative purposes only an example of a schematic view of a ball marker sensor system of one embodiment.

[0028] FIG. 22 shows a block diagram of an overview of the AI module application display screen of a text message of one embodiment.

[0029] FIG. 23 shows a block diagram of an overview of the AI module application display screen of a graphic putt path of one embodiment.

[0030] FIG. 24 shows a block diagram of an overview of a golfer on a putting green of one embodiment.

[0031] FIG. 25 shows for illustrative purposes only an example of a plan view of a putting green of one embodiment.

[0032] FIG. 26 shows for illustrative purposes only an example of putt path determination of one embodiment.

[0033] FIG. 27 shows for illustrative purposes only an example of interactive putt path selection of one embodiment.

[0034] FIG. 28 shows for illustrative purposes only an example of user AI golf assistant interaction of one embodiment.

[0035] FIG. **29** shows a block diagram of an overview flow chart of the ball marker placement of one embodiment.

[0036] FIG. **30** shows a block diagram of an overview flow chart of the estimated distance input of one embodiment.

[0037] FIG. **31** shows for illustrative purposes only an example of recommended force and direction information of one embodiment.

[0038] FIG. **32** shows for illustrative purposes only an example of recommended swing parameters for multiple distances of one embodiment.

[0039] FIG. **33** shows for illustrative purposes only an example of generating recommended putt stroke parameters of one embodiment.

GENERAL OVERVIEW

[0040] It should be noted that the descriptions that follow, for example, in terms of an artificial intelligence golf assistant system are described for illustrative purposes and the underlying system can apply to any number and multiple types of golf courses. In one embodiment of the present invention, the artificial intelligence golf assistant system can be configured using an AI module application. The artificial intelligence golf assistant system can be configured to include an artificial intelligence and machine learning processor and can be configured to include an input using the present invention.

[0041] The present invention is an interactive artificial intelligence (AI) golf assistant that allows a user to interact with an AI golf assistant module with voice commands, hand gestures, eye movements, or selections on a touch screen of a mobile device to request advice from the AI golf assistant module. The AI golf assistant module can interact with the user to advise the user during a golf round as the user prepares to play a golf course and when the user prepares to hit a golf shot. The AI golf assistant module has information stored in a database that includes information about the user's golf swing and the user's golf tendencies for different shots, with different golf clubs, during course play and at the practice driving range. The AI golf assistant module also has information stored in a database about other similar amateur golfers' tendencies when playing the same shot as well as how professional golfers play the same shot to increase success for each shot for the user.

[0042] The terms “AI caddy,” “AI caddie,” “AI assistant,” and “AI virtual assistant” are used interchangeably herein and have the same meaning of a human interactive artificial intelligence (AI) module and AI system. The AI golf module, AI golf assistant, and/or AI module or system can include several ways for a human user to interact with the AI module and system, including as one example, audible user voice commands and audible feedback from the system. The audible feedback can include interactive announcement recommendations and suggestions to a user and responses to a user's questions generated from the AI golf assistant module of the AI golf application.

[0043] FIG. **1** shows for illustrative purposes only an example of an AI module application of one embodiment. FIG. **1** shows an artificial intelligence remote server platform **100**. The artificial intelligence remote server platform **100** includes an artificial intelligence server **110**, databases **115**, at least one static database **120**, an artificial intelligence and machine learning processor **122**, at least one dynamic database **124**, and at least one wireless communication device **125**.

[0044] A user's mobile device **130** has an AI golf application **132** installed. The AI golf application **132** includes a location module **140** having a Real-Time Kinematic (RTK) **142** module and a Global Positioning System (GPS) **144** module. The user's mobile device **130** includes a camera **146**, a graphical user interface (GUI) **148**, and an AI golf assistant module **150**. The AI golf assistant module **150** includes a range finder module **152**, and an input module **154**. The AI golf application **132** utilizes the user's mobile device **130** GPS coordinates to identify the golf course the user has arrived at and will be playing on at that time. The AI golf application **132** can be used to replay a prior round of play to refresh the user's memory of especially difficult holes. The replay

could be statistical or even the prior shots overlaid on a course RTK map, club use, or suggestive corrections that the user should consider for this next round of play.

[0045] Upon arriving at a specific golf course and launching the AI golf application **132**, the user's location triggers detection at that precise golf course. Subsequently, the AI golf application **132** retrieves pertinent data from the server **110** through linked databases **115** dedicated to the specific golf course. This data encompasses the RTK topographic map, historical records of amateur and professional play, and the user's personal play history for each hole on the course. By acquiring this data, the AI golf application **132** can review the user's previous rounds, with a focused analysis on golf shots that needlessly inflated the score.

[0046] If the user is unfamiliar with a particular course, the AI assistant will begin to familiarize the user with the course based on the RTK topography map and the previous amateur and professional play history. The hole-by-hole information the AI assistant provides will alert the user to areas on a hole that frequently negatively impact the score of those who have previously played the hole. The AI caddie will provide suggestions to avoid the pitfalls of others who have previously played the hole and how to avoid the same results.

[0047] Moreover, the AI golf assistant module **150** is capable of replaying those shots and offering suggestions on how to avoid repeating previous poor shots. These suggestions may include recommendations for club selection and target shot locations to avoid hazards.

[0048] The AI golf assistant module **150** tracks its recommendations and how often the user has used it after a round to learn and predict how well the AI golf assistant module **150** performed and if the user would have done better with its recommendations. This information is stored in a database and compared with how other users use the AI golf assistant module **150**. The golf rounds are analyzed at the end of each golf round to teach the AI how to get better with custom recommendations for the user and other similar users based on how the user played with the recommendations and added or reduced strokes on the course through the round. This also allows the AI golf assistant module **150** to be taught and to learn how and what recommendations are the most useful for future recommendations for the current users and other uses.

[0049] The golf ball tracking statistics provide insights into the shot's distance, flight profile, and landing location. The club utilized in a prior shot may have influenced a slice or hook, prompting the AI assistant module, in certain instances, to propose an alternative club that sacrifices some distance for improved control. Users can selectively replay the details for each hole, and as they approach a particular hole, the AI golf assistant module **150** can recap the specifics pertinent to that specific hole. The replay feature includes wearable camera images and videos displaying the user's stance and club face orientation as they addressed the golf ball in previous shots.

[0050] The AI golf assistant module **150** can be coupled, such as wirelessly, to the user's mobile device, such as a mobile phone, mobile special purpose electronic device, mobile launch monitor, or a mobile electronic tablet. The user's mobile device **130** can include various motion, audible and visual sensors, a camera, a speaker **162**, and a microphone **160**. FIG. **1** also shows a user **170** holding a golf club **172** having a club sensor **178** coupled to the golf club **172**. The user **170** is addressing a golf ball **174** in preparation for making a practice swing.

[0051] In one embodiment, the user **170** can wear a wearable golf environment detector **176**. In one embodiment, the wearable is a pair of glasses or a body camera with a video camera that picks features from the hole to further identify the location and provide related suggestions. The wearable camera includes zoom module selections the user picks to get a closer look at the area. In one embodiment, the zoom module selections can be an automatic zoom that is coupled to a wearable rangefinder to provide the user a closer view based on the distance to a particular hazard and to a golf ball landing location to assist the user in finding the golf ball as they get closer to the golf ball landing site. The user uses the automatic zoom module when approaching a green to begin to determine the topography of the green and RTK recorded slopes. This feature allows more time to assess a potential putting circumstance and potential landing target areas on the green for a chip

shot. In all the embodiments of the present invention, an audible system with voice commands coupled to the AI golf assistant module **150** can be used to control, adjust, access, monitor, learn and track all features of the present invention.

[0052] For example, the area of rough is different and narrows the fairway from the user's previous round. The camera could be in a hat belt or another type of clothing. The finite green topography may have changes and the suggestions can be adjusted accordingly on approach shots, chip shots, and sand shots including where the ideal landing spot should be targeted, not necessarily the pin. A new pin location may be located by another user earlier. Regarding the green conditions a green grass grow algorithm stores recent weather conditions that may affect the growth of the green grasses and how fast various green grasses grow. This may affect the green topography and the topography data can be updated using RTK and photogrammetry.

[0053] In another embodiment, the user can wear augmented reality (AR) glasses that include light detection and ranging (LIDAR) features to read the contours, slopes, green speed, and other green characteristics that will affect a putt on a projected screen in front of their eyes. The projected images can be displayed on a clear prism in front of the user's eyes with an optical waveguide that projects the desired images on the prism in front of their eyes. Alternatively, the projected images can be an optical system that projects light and the images on the retina of their eyes. Other suitable projection methods can be used to project and superimpose the images on the user's vision to create an augmented reality experience with eyewear, such as glasses or contact lenses.

[0054] In one embodiment, the user can wear the AR glasses and walk up from the cup location on the golf hole to the position of the user's golf ball on the green or just off the green for a chip shot. The LIDAR system, integrated into the AR glasses, detects the contours and other data, and processes the data to display the contours and other green data superimposing the contours onto the real-time images of the green.

[0055] The AR glasses process the data and additionally display the path the ball will follow to the cup and the aiming direction the user will use to strike the golf ball for the putt to follow the contoured path of the golf ball to the cup. The AR glasses LIDAR is contained within memory devices, display programming, camera, sensors, and processors for receiving the visual and sensor data of the green and processing the data to overlay the contours and calculated putt path and aiming direction to assist the user in making the putt to drop into the cup. The AR glasses also include rechargeable batteries to power the LIDAR and other devices and systems. The AR glasses can have automatic or manual electrochromic dimming levels to assist the user to see the projected images and the real-world view at the same time during varying ambient and outdoor lighting conditions.

[0056] In one embodiment, the ball marker includes a stimp meter integrated into the bottom of the ball marker. A stimp rating is a numerical value that represents the speed or how fast the golf ball rolls on the putting surface.

[0057] Should a golfer not be able to physically join at least one other player on a golf course, one or more of the other player users could share camera views of the hole to allow other absent players to virtually join the group on the golf course. Golfers on the course could use augmented reality to superimpose the camera views with the RTK topography allowing comments on hazards and shots made by the other golfers. Where the particular golf course topography is accessible, the absent player may be able to play along using a golf simulator app or game. Each of the players could create an Avatar to include in a replay of the round being played in the Metaverse. Where legal the players could make wagers, for example, on whether a player sinks a putt or successfully chips out of a sand trap. In one embodiment, the RTK and photogrammetry golf course data could be supplied to a golf simulator game partner. This would allow users to practice on golf courses near to them with the simulator to improve their play.

[0058] In one embodiment, "smart" golf balls are used for user practice. The smart golf balls can have sensors on the surface of the golf ball or embedded within the golf ball. The AI golf

application **132** can track and record the “smart” golf ball practice shots to allow analysis of the user's practice to improve suggestions to assist the user in perfecting the play on the course. [0059] When practicing putting, use a home tracking device to record swing or stroke speed, tempo, and the open/close movement of the putter. This helps in tracking putting practice sessions away from the golf course, enhancing the AI caddy's suggestions for putting techniques. The additional data can be put to use on a practice green at a given golf course. Identifying the areas of improvement resulting from increased putting practice, these suggested enhancements will allow the user to focus on those specific areas while practicing on the greens at a designated golf course. The AI assistant can explain the types of putts to work on.

[0060] The cups/pins in practice greens change even daily, and the user may use the ball marker to locate the current cup locations before the user begins putting practice. The AI assistant can then give guidance on what putts to practice, pictorially where the user should place the ball marker and which cup to putt to. Part of practicing putting on an enabled green is to ask the user the line, read it without being aided with the ball marker, and then give the putt parameters to follow (line, aim point, speed, etc.). Gathering additional putting practice will be recorded along with fairway swing data, $\frac{3}{4}$ swing data, etc.

[0061] During a practice golf swing, the artificial intelligence and machine learning processor **122** will predict how far your golf ball **174** will carry, finish, and where it will most likely end up. The AI golf assistant module **150** can interact with the user **170** to keep analyzing practice swings until a desired probabilistic outcome is achieved. The AI golf assistant module **150** can keep making suggestions until the user **170** is comfortable with the shot.

[0062] The AI golf assistant module **150** can interact with the user **170** as the user **170** is lining up for the shot and help point out an optimal direction or line of where the user **170** should be aiming at the golf shot. For example, when the user **170** addresses the golf ball **174**, the AI golf assistant module **150** can detect where the user **170** is aiming or lined up for the shot and interact with the user **170** using audible messages to correct or confirm the correct line.

[0063] Wearable sensors **176**, camera sensors **146**, and sensors on the equipment **178** can also be used to make the optimal determinations in trying to achieve the perfect swing. Also, instructional multimedia videos can be used during the golf round to help the user **170** with his golf shot. These instructional videos can be from professional golfers, previous users, amateurs, or coaches.

[0064] The AI golf assistant module **150** allows the user **170** to interact with the AI golf assistant module **150** with voice commands, hand gestures, eye movements, or selections on a touch screen of a mobile device **130** to request advice from the AI golf assistant module **150**. Also, the user **170** may use voice commands to control features of the assistant module **150** before, during or after a round of golf. For example, voice commands can be used during a round of golf to enter, add or edit data into the AI golf assistant module **150** relating to a golf shot. In another example, voice commands can be used after a round of golf to enter, add or edit data into the AI golf assistant module **150** relating to previous golf shots.

[0065] In another example, voice commands can be used before a round of golf to access data, simulate a future round or create notes about the future round into the AI golf assistant module **150** relating to proposed golf shots, reminders or tips on certain golf holes or golf shots before the round to allow this data to be available during the round. Also, voice commands can be used to control and review all aspects of the AI golf assistant module **150** before, during or after a round of golf. The AI golf assistant module **150** can also accept and use self-reported information and assessment data about the user to further teach the AI golf assistant module **150** about the user. After an actual round, the AI golf assistant module **150** can compare the before the round data to the actual round to determine the effectiveness of the before the round analysis and make adjustments based on what worked and what did not for modifications to future rounds and future recommendations as part of the artificial intelligence learning process.

[0066] In one example embodiment, the AI golf assistant module **150** can advise the user **170**

during a golf round as the user **170** prepares to hit a tee shot. The AI golf assistant module **150** has information stored in a database **115** that includes information about the user's **170** golf swing and the user's **170** golf tendencies for different shots with different golf clubs **172** during course play and at the practice driving range. The AI golf assistant module **150** has information stored in a database **115** about other amateur golfers' tendencies when playing the same shot. The other amateur's information includes tendencies for different shots with different golf clubs **172** during course play on the same course being played by the current user **170**. Additional stored information includes how professional golfers play the same shot, on the same hole, on the same course that the current user **170** is playing currently.

[0067] The golf tendencies include technical data and information for each golf club and the golf ball before, at, and after impact with each golf club. This data can be captured by radar, doppler, photo, video sensors, and can include data such as target alignment, backswing takeaway, path, downswing path, location of impact of the golf ball on the golf club, golf ball carry distance, golf ball total distance, golf ball back and side spin rates, golf ball launch angle, golf club swing speed, golf ball speed, golf club angle of attack, golf club face angle, golf club swing path before, at and after impact and other relevant swing characteristics and analytics.

[0068] The AI golf assistant module **150** uses at least one artificial intelligence and machine learning processor **122** to analyze the other amateurs of the same skill level and professional golfers with the same tee shot on the same hole. The analysis calculates the success percentage of those shots leading to better scoring against par on the hole. The analyzed information determined the shot placement, golf club **172** selected, and at least the result of the tee shot in setting up the next shot that follows.

[0069] The AI golf assistant module **150** factors into the analysis weather conditions, humidity, wind speed, and direction, type of shot from a straight shot, a fade, and a draw, avoidance of hazards, out-of-bounds, tree contacts, and whether the results of the tee shot avoided the obstacles and the final tee shot resting place in relation to the hole mapped high-resolution LIDAR Real-Time Kinematic (RTK) topography of the course and particular hole.

[0070] The AI golf assistant module **150**, based on the shots analysis and the current user's **170** tendencies, provides the location of where the user **170** should hit the tee shot with the highest chance of success with the next shot. Which golf club **172** the user **170** should use based on the known distances of the user **170** for each golf club **172**; known data about the golf course; the current weather conditions; the elevation, topography, and terrain of the current hole; and the type of shot the user **170** usually has the most success with.

[0071] For example, the golf hole in play has a dogleg right, that prevents the user **170** from seeing the target golf hole and what obstacles are present in the fairway of the dogleg. The AI golf assistant module **150** considers the dogleg when analyzing the best tee shot placement for the user **170**. When the user **170** verbally questions the AI golf assistant module **150**, "Where should I aim this tee shot?"; based on the user's **170** tendencies and the highest-ranking successful shots on this golf hole by other amateurs and professional golfers; the AI golf assistant module **150** may suggest a long iron versus using the driver due to the distance to the dogleg turning point fairway and predictable resulting fairway position viewable for the second shot.

[0072] Additionally, the AI golf assistant module **150** has determined, based on the tendencies of the user **170**, that the user **170** has consistently hit better-controlled long iron shots than wood shots. The targeted shot position would be 20 yards left of the dogleg right turning point. The user **170** better controlled long iron shot would have a better opportunity to avoid the turning point trees on the right and have a clear second shot.

[0073] In one embodiment, the user **170** can use hand gestures to indicate a corner of the dogleg where there are tall trees, indicating the direction to aim to clear the trees and have the ball land around the corner of the dogleg. The AI golf assistant module **150** may also respond verbally with an alert to the user **170** to avoid trying to cut across the turning point of the dogleg because of 50-

foot-high trees that would be encountered on the downward portion of the ball flight and be nearly impossible to avoid hitting a tree or the shot falling short and be blocked from a clear second shot by the trees.

[0074] Also, the user **170** can verbally interact with the AI golf assistant module **150** and verbally ask, "Which long iron should I use?". The AI golf assistant module **150** will use the tendencies of the user and make a suggestion. In this example scenario, the AI golf assistant module **150** has stored in its system the average distances and shapes of each club of the user **170** to suggest an ideal targeted shot placement position, including the calculated roll after the golf ball is carried.

[0075] This ideal location takes into consideration the likelihood of making it to that location and setting up the user **170** for success with the next shot based on the tendencies of the user **170** with golf shots closer to the hole. The likelihood of success of the ideal ball position for the current shot and subsequent shots is based on other similar golfers, coaches, professionals, and course suggestions. The AI golf assistant module **150** also evaluates the current weather conditions, course conditions, and time of day to calculate and predict the carry and roll of each golf shot. This would provide the user **170** with an advantageous position for the next shot on the hole and be consistent with the highest-ranking successful scoring shots of others.

[0076] The AI golf assistant module **150** can be powered by Bayesian networks for its probabilistic reasoning. Other artificial intelligence systems include deep learning neural networks that use convolutional neural networks (CNNs) for image recognition and recurrent neural networks (RNNs) for sequence data. Decision trees and random forests can be used with a set of conditions for classification. Random forests can be used with an ensemble of decision trees to improve accuracy.

[0077] Support vector machines (SVM) can be used for classification and regression tasks. The SVM can be used with the high-dimensional spaces of the AI golf assistant module **150** when tasks with clear boundaries between classes are needed. Generic Algorithms can be used when algorithms with optimization that evolve solutions to complex problems over multiple generations are needed. Reinforcement learning AI can be used, including Q-learning and deep reinforcement learning methods for training models to make sequential decisions.

[0078] In one embodiment, the AI golf assistant module **150** has numerous data points about the user's **170** golf swing stored in the learning database **115**. The AI golf assistant module **150** utilizes the user's **170** golf tendencies, including the user's **170** patterns and behaviors that have been observed in the user's **170** previous rounds, to determine the user's **170** strengths and weaknesses, and understand the familiar challenges the user **170** faces during a particular tee shot. This analysis enables the AI golf assistant module **150** to recommend adjustments that align with the user's **170** playing style, maximizing the user's **170** chances of success.

[0079] In addition, the AI golf assistant module **150** uses insights from a vast database **115** of amateur golfers, to suggest common strategies and pitfalls associated with tee shots at the user's **170** similar skill levels. By analyzing trends among other amateur players, the AI golf assistant module **150** can provide context-specific advice, helping the user **170** navigate challenges that are commonly encountered by golfers with similar capabilities.

[0080] In parallel, the AI golf assistant module **150** can delve into the techniques employed by professional golfers during a particular tee shot. The database **115** of strategies of elite players allows the AI golf assistant module **150** to offer expert insight to the user **170** about club selection, shot trajectory, and ball placement. This understanding of how the best golfers in the world approach similar situations allows the user **170** to gain valuable knowledge to elevate the user's **170** performance based on the advice from the AI golf assistant module **150**.

[0081] Also, the AI golf assistant module **150** leverages data about the golf course and recommends a target location for the tee shot with the highest chance of success for other shots for the golf hole being played. Global Positioning System (GPS), Real-Time Kinematic (RTK), and course mapping technology are used to provide advice about how to reach optimal landing zones while avoiding

potential hazards. This is used in combination with the AI golf assistant module's **150** knowledge of the user's **170** historical data to recommend the most suitable golf club **172** for the shot. The AI golf assistant module **150** takes into consideration the user's **170** known distances for each golf club **172**, ensuring that the user **170** makes informed choices aligned with the user's capabilities.

[0082] In addition, external factors are used, such as real-time weather data to provide additional guidance. Whether it is wind speed, direction, or temperature, the AI golf assistant module **150** offers suggestions to account for these variables, enhancing the accuracy of your tee shot. The AI golf assistant module **150** also analyzes the terrain of the current hole, elevation changes, bunkers, and other features that may impact the user's **170** shot. This comprehensive understanding of the golf course's topography allows the AI golf assistant module **150** to tailor its advice to the specific challenges posed by the terrain.

[0083] Lastly, recognizing the user's **170** most successful and preferred shot types, the AI golf assistant module **150** uses this information when recommending strategies that align with the user's **170** past successes. Whether it is a draw, fade, or straight shot, the AI golf assistant module **150** leverages the user's **170** historical performance data to guide the user **170** with the shot selection, optimizing the user's **170** chances of achieving the desired outcome.

[0084] In essence, the AI golf assistant module **150** serves as a multifaceted interactive AI assistant, integrating information from various sources to deliver precise, personalized advice at every step of the user's tee shot, enhancing the user's overall golfing experience, performance, and success.

DETAILED DESCRIPTION

[0085] FIG. 2A shows for illustrative purposes only an example of a glasses display of one embodiment. FIG. 2A shows the AI golf assistant module **150** of FIG. 1 projecting information to the user on the lenses of a pair of AI golf assistant glasses **210** superimposed on a view of a golf course hole **200**. The AI golf assistant glasses **210** AI caddy projected messages include data in response to the user's questions about how to play the hole. The glasses use AI caddy projected messages **215**.

[0086] In one embodiment, the AI golf assistant glasses **210** includes a laser device to measure the distance to an object the user is looking at through the AI golf assistant glasses **210**. The laser device can also have a triangulation feature that allows the laser to track different objects and use a triangulation processor to determine the distance between each object. In one embodiment, the triangulation can be used to determine the width of a fairway or the distance between distant objects on the golf course, such as hazards, landmarks, and flagsticks, etc.

[0087] The AI golf assistant glasses **210** has an Augmented Reality (AR) device feature that projects crosshair a crosshair onto each lens and an AR-depicted laser beam positioned relative to the crosshairs to assist the user in aiming the laser at the object or point of interest to the user. The user's bifocal vision combines the crosshairs, and the user gives the AI golf assistant glasses **210**, for example, an audible voice command "distance" that triggers the laser to measure the distance to the object or point in the crosshairs. The AI golf assistant glasses **210** answers the user's "distance" command with an audible of the number of yards to the object or point.

[0088] In another embodiment, a combination laser GPS rangefinder is coupled to the AI golf assistant glasses **210** having an Augmented Reality (AR) device feature. The Augmented Reality (AR) device feature projects a crosshair onto each lens to overlay the RTK topographic map to identify the object or point to calculate the distance based on the user AI golf assistant glasses **210** GPS location. The RTK topographic map overlay identifies an object or point on the RTK topographic map overlay the user selected. The user gives a verbal audible command of 'distance' and the AI golf assistant module **150** of FIG. 1 responds with an audible broadcast of the distance in yards to the object or point chosen by the user with the crosshairs.

[0089] In yet another embodiment, the AI golf assistant includes a mobile app for installation on a user's mobile device having a camera. The mobile app includes a camera laser rangefinder that displays crosshairs and a simulated laser beam. The camera laser rangefinder display allows the

user to aim the mobile device camera laser rangefinder at an object or area and use the display to place, for example, the object in the crosshairs. The user then taps a laser icon on the display to actuate the laser. The laser determines the distance to the object and displays the yardage on the display. A laser processor calculates the distance adjusting for up or down elevation height differences between the user location and the object location.

[0090] In addition, the user's mobile device acquires the user's GPS coordinates and the camera laser rangefinder processor calculates the GPS location coordinates of the object taking into account the angle from true north. The image of the object can be viewed using the AI golf assistant glasses **210**. The camera laser rangefinder mirrors the distance to the object and object GPS coordinates on the lenses of the AI golf assistant glasses **210**. The object GPS coordinate may be used to display superimposed RTK topography on the glasses and the camera laser rangefinder display.

[0091] The camera laser rangefinder display makes it easier for the user to get the accurate distance to a chosen target than binoculars or a viewfinder scope. The user can quickly scan the course for the shot and receive multiple laser distances to assist the user in deciding on a preferred target and a club selection to either reach the object, or area, or in cases of hazards avoid reaching the hazard or safely dealing the hazard and potential penalty shots.

[0092] The user may pan the area of interest and select multiple targets. The camera laser rangefinder can record the laser beam results for each of the multiple targets and display a list of distances for each selected target in the order in which they were selected. The camera laser rangefinder, in one embodiment, includes a user voice-activated "laser" command to avoid the user having to move fingers to tap the laser icon to select the targets.

[0093] For example, how far did the user drive using a club driver **220** yds **220**, what is the distance to a bunker on the left, how should the driver shot be performed, any wind to be concerned with on the shot, what is my chance of success and how have others done on this hole. The AI golf assistant responses include a distance of 190 yards to a bunker **222**, a golf stance adjustment to perform a suggested slight draw left **224**, an impact of a wind 5 mph left to right **230** aiming 5 yards to aim more to the right to compensate. Following the suggestion the AI golf assistant predicts the player est. success rate 58% **232** and have the following results other players ranked success pro-95%, HC-scratch 80%, HC-mid 70%, HC-high 60% **234**. In one embodiment, the AI golf assistant glasses **210** include a microphone and speakers to allow the user to verbally communicate with the AI golf assistant. The AI golf assistant tracks and knows which club the user used for each golf shot because the AI caddy questions the user after and before each shot with audible questions and also based on the AI's recommendations the user acted upon and those dismissed by the user.

[0094] FIG. 2B shows for illustrative purposes only an example of a portion of an RTK map approaching the green of one embodiment. FIG. 2B shows an RTK map of a portion of a hole to the green **240**. The RTK map shows **142** yards to the green **250** from the current location of a user ball. Also showing are a left bunker **252**, the green **260** including the cup **262** and flag **264**. The fairway **270** has rough **272** on both sides, one area of out-of-bounds **280**, and a tree **282** among the many trees along the course for this hole of one embodiment.

[0095] FIG. 3 shows for illustrative purposes only an example of satellite golf course contours of one embodiment. FIG. 3 shows 2D satellite views showing elevations of ground, trees, course holes area, and calculated distances for downhill and uphill lies of the ball to assist in club selection **300**. The 2D satellite view data is stored in the static database **120** for uses including, for example, distance measurements between features of a golf course hole map. The 2D satellite views show a green **310**, trees **320**, topographic contours **330**, elevations **340**, a tee **350**, a bunker **360**, and a hole number **370**. Also shown is the scale **380** of the 2D satellite images used for measurements. A course hole yardage card **390** also provides a check on the measurement accuracy of one embodiment.

[0096] FIG. 4 shows for illustrative purposes only an example of satellite golf course contours of one embodiment. FIG. 4 shows a golf course **400** being flown over with an RTK drone **405**. The RTK drone **405** includes Real-Time Kinematic sensor devices and camera **410** to collect topographic data of the golf course including elevation contour lines **420**, scalable distances, features including bunkers, water hazards, trees including heights, cart paths, and other features with 1-2-centimeter accuracy. The RTK drone sensor data is transmitted for storage to the static database **120** of one embodiment.

[0097] FIG. 5 shows a block diagram of an overview flow chart of a golf ball recognition device of one embodiment. FIG. 5 shows a golf ball recognition device **500** used to track a golf ball from tee, ground, or sand **510**. The tracking detects the direction, and flight path including draws and fades, height of the flight arc, landing distance, and amount of roll distance **515**. The information collected from a wireless golf ball tracking sensor **520** including a wearable **522**, integrated in a golf hat **524** or an integrated inside a golf ball **526** also assists in determining where the ball lands and rolls. This allows the user to find the ball in a shorter time and reduces lost balls. The tracking data is transmitted to the user's mobile device **130** and displayed by the AI golf application **132** with the AI golf assistant module **150**.

[0098] In one embodiment, the AI golf assistant module **150** tracks and knows which club the user used for each golf shot because the AI caddy questions you after and before each shot with audible questions and also based on AI's recommendations. AI tracks its recommendations and how often a golfer used it after a round to learn and predict how well AI performed and if a golfer would have done better with its recommendations, for example, the user used the AI recommendations 50% of the time and was right on those 90% of the shots, but the user was wrong on 30% of the user's 50% to not use the recommendations-so the user would have scored X shots better if they used the recommendations and vice versa.

[0099] The golf rounds are analyzed at the end of each golf round to teach the AI how to get better with custom recommendations for the user and other similar users based on how the user played with the recommendations. The AI tracks each shot, so it calculates penalties and scores for each hole and the total scores of the user and other players. Since AI tracks each shot from above, it can analyze the round and determine strategies for how to play better and avoid penalties and focus on what worked best for the user during the round to help with future rounds on that course and other courses with similar holes and determine the strengths and weaknesses of the golf user.

[0100] The analysis allows AI determination of how many strokes per type of shot are added or reduced strokes. For example, always using a driver off a tee. Instances of instead using an iron off the tee produces a better landing position for the next shot than a user's tendencies with a driver. Risking adding a stroke is a difficult decision due to erratic control of the driver as seen in the user's tendencies versus gaining control of the shot to save a stroke. A similar circumstance comes when hazards are present. Placement versus distance is recommended by the AI assistant module **600** based on the user's tendencies. Considerations of placement to avoid a hazard are a sure way to avoid penalty strokes.

[0101] In one embodiment, the AI golf application **132** of FIG. 1 also includes a range finder module **152** of FIG. 1 and an input module **154** of FIG. 1. In another embodiment, laser technology is coupled to the range finder module **152** in the glasses. In yet another embodiment, a laser plus GPS receivers are coupled to the range finder module **152** in the glasses. A rangefinder heads-up display that calculates the distance to an object or point selected by the user enables adjustments for selecting a different club. The range finder module **152** can include lasers and timing devices, GPS devices, optical sensors and cameras. LIDAR devices, landscape database object recognition information and triangulation devices to accurately detect distances from the user to an object, heights of objects, contours of landscape, distances between objects and angles between objects.

[0102] Audible commands, questions, and responses are used by the user and the AI golf application **132** of FIG. 1 to control the laser rangefinder and cameras to scan objects at a distance

through the glasses with AR and GPS. A GPS rangefinder on a mobile device that is replicated as a heads-up display of an overlay of the RTK topographic on the AR glasses while on the golf course to determine distances and to track shots. The heads-up display will highlight hazards along the user's next shot. This will assist in making recommendations to the user of club selection and shot placement targeting.

[0103] The collected data is used to increase the predictability of a user shot with a determination of speed, path, and flight arc projection of landing based on 3D LIDAR golf course data. The predictability of a user shot is based on user tendencies when making a shot and this additional data increases the accuracy of the predictions of one embodiment.

[0104] FIG. 6 shows a block diagram of an overview flow chart of an AI golf assistant of one embodiment. FIG. 6 shows the calibrating AI assistant module **600**. Several sources are used for calibrating the AI assistant module as shown in FIG. 7. The AI golf assistant provides the user with course and hole information and recorded data with interaction by the user for determining a type of shot with user confirmation **610**. This is further described in FIG. 8.

[0105] The type of shot, location along the fairway, and user tendencies are combined with interacting with the user on a club selection **620**. Descriptions continue on FIG. 9. The dynamic database **124** of FIG. 1 stores historical data on the user's golf club swings and stroke performance tendencies data that the AI golf assistant uses in analyzing predictions on current user club selections and adjustments for a user swing to increase the success rate of each shot. This data is collected for each shot including practice swings.

[0106] Updating the tendencies is accomplished by recording swing sensor data and shot sensor data **630**. The use of the tendencies is described in FIG. 10. Using shot sensor data to automatically set up the next shot **640** that will follow the current shot is taken into account for the current shot placement using the user tendencies, RTK mapping of the course hole, avoidance of obstacles and hazards in route to the current shot placement and avoidance of obstacles and hazards confronting the next shot. The AI golf application **132** of FIG. 1 uses the collected data for analyzing the user's tendencies for the next type of shot **670** by the user **170**. The next shot assessment is described further in FIG. 11 of one embodiment.

[0107] FIG. 7 shows a block diagram of an overview flow chart of calibrating AI assistant module continuation of one embodiment. FIG. 7 shows calibrating AI assistant module **600** by comparing GPS coordinates detected with golf courses stored RTK data GPS coordinates on the static database **700**. Confirming with the user the name and location of the golf course to be played **710** and interacting with the user to confirm the golf hole on the golf course is being played at times during play. Interacting with the user to suggest taking some practice swings and some putts on the practice putting green before starting the round of golf **720**.

[0108] Testing the club swing and putter stroke sensor detection features **730**. Using the sensor detection features while the user is practicing swings and putter strokes before beginning play **740**. Confirming the sensor detection features are working correctly **750**. Recording test swing data in the dynamic database to confirm the recordation component is working correctly **760**. Analyzing the current practice swings with previous practice and shot swings to determine any changes in the user swings, particularly noting any improvements of one embodiment.

[0109] FIG. 8 shows a block diagram of an overview flow chart of calibrating AI assistant module continuation of one embodiment. FIG. 8 shows the determining type of shot with user confirmation **610**. Determining the type of shot with user confirmation **610** includes confirming the par for the hole by interacting with the user **805**. Confirming the hole yardage with the user from the published course hole by hole yardage card **810**. Checking the user course location for the hole including a back, mid, and front tee box **820**. Categorizing types of shots based on RTK map distances from the user location to the green **830**. Confirming with the user a type of shot including a tee shot, an approach shot, a bunker shot, a putt, and a recovery shot from a hazard, behind a tree, and a difficult lie in heavy rough **840**. Analyzing user's tendencies for the next type of shot **670** of FIG. 6

of one embodiment.

[0110] FIG. 9 shows a block diagram of an overview flow chart of determining the type of shot with user confirmation of one embodiment. FIG. 9 shows interacting with the user on the club selection **620**. The interaction with the user includes determining the distance of the shot to the location of the next shot using the RTK map **905**. Comparing the determined distance to the user shot distance tendencies for each of the user's clubs to find a match **910**. Evaluating current conditions that may affect the club distance prediction **920**. Ask the user about any physical conditions that may impede a viable swing with any club **930**. Analyzing ball location for any course conditions that may affect the club distance including tall grass, and reduced roll due to ground conditions **940**. Confirming interactively the club selection for the shot with the user **672** of one embodiment.

[0111] FIG. 10 shows a block diagram of an overview flow chart of interacting with the user on the club selection of one embodiment. FIG. 10 shows recording swing sensor data and shot sensor data **630**. Collecting swing data, the user attaches a club sensor to a selected club **1005**. The user proceeds to perform a practice swing by the user and recording the club sensor data **1010**. Interacting with the user to try different adjustments to the practice swing to confirm the sensors are detecting the adjustments **1020**. Analyzing the sensor detected swing adjustments to determine correct predictions in the results of the adjustments **1030**. Comparing the current practice swings with real shot swings and noting the tracking data results **1040**. Recording practice swings and shot sensor data on the dynamic database **680** of one embodiment.

[0112] FIG. 11 shows for illustrative purposes only an example of recording swing sensor data and shot sensor data of one embodiment. FIG. 11 shows using shot sensor data to automatically set up the next shot **640**. The AI golf assistant module suggests that the user interacts with the club selection of the next shot **1105**. Determining the next shot distance to a shot placement avoiding bunkers and other hazards **1110**. Confirm with the user the club selection will reach the distance and that the user believes a draw could be made based on the user tendencies **1120** of one embodiment.

[0113] FIG. 12 shows a block diagram of an overview of a tee shot of one embodiment. FIG. 12 shows the user's mobile device **130** having the AI golf application **132** and its AI golf assistant module **150**. The AI golf assistant module **150** uses at least one artificial intelligence and machine learning processor **122** to generate golf shot recommendations and suggestions based on the user course location and user tendencies and high-success shots of other amateurs and professional golfers on the same hole. The AI golf assistant module **150** interacts with the user with the AI caddy on the user's mobile device **130** to offer audible golf shot recommendations and suggestions and receive user verbal questions and two-way responses to the recommendations, suggestions, and user questions.

[0114] For example, the user asks, "What club should I use and where should I aim the shot?" **1210**. FIG. 12 shows the user **170** having the club sensor receiver **176**. The user is holding the driver **172** with the club sensor **178** attached. The user **170** is addressing the golf ball **174**. The AI caddy: "Suggestion uses the driver, tee ball high to hit with the center of the driver. Aim 10 yards right of the center of the fairway. Move the lead foot 3 inches forward to make a slight draw. Wind 8 mph right to left. Avoid the left bunker and right out of bounds. A 57% success rate to make shot placement location" **1240** is the AI golf assistant module **150** verbal response **1260** of one embodiment.

[0115] The club sensor **178** includes a launch monitor to advise the user **170** with reasons for the recommendations. For example, the club sensor **178** launch monitor provides recommendations for club speed and explains audibly "Club speed is the velocity that the club head travels measured just before ball contact". The angle of attack is the angle at which the clubhead approaches the ball during impact, influencing ball flight, spin, and distance, and the path of the clubhead is measured in degrees. The angle of attack during impact influences the ball's flight, spin, and distance.

[0116] The ball speed is a measurement of the golf ball's velocity measured just after impact. The ball speed is the main component in generating distance. The launch angle is the initial vertical angle of the ascent relative to the ground plane measured in degrees. The launch angle, combined with ball spin and speed, will determine the ball's carry and total distance. The azimuth is also known as the side angle or deviation angle. The initial horizontal angle relative to the target line. The azimuth, combined with side spin, will determine the final ball position down range relative to the target line.

[0117] A side spin is a component of total spin that defines ball curvature or shot shape. Also related to the spin-tilt axis. The side spin includes negative side spin and positive side related to a draw and slice. Backspin is a component of total spin that defines ball lift and trajectory. Total spin is the total amount of spin around the tilt axis that creates curvature and lift. The spin-tilt axis is the axis that the golf ball rotates around to create shot curvature and lift. When the spin-tilt axis is positioned to the left, looking down range, the ball's trajectory will move from right to left. When the spin-tilt axis is positioned to the right, looking down range, the ball's trajectory will move from left to right.

[0118] Trees are hazards confronting the user **170** on a hole. The RTK topography shows the height of the trees on the course. The user tendencies show a peak height achieved by the user **170** for each club. The peak height is the apex of the trajectory measured from the ground plane. The AI golf assistant module **150** verbal recommendation will list the clubs with sufficient peak height to allow the user **170** to make a shot over the tree hazard. The user **170** may question the AI golf assistant module **150** whether it would be more advisable to make a shot around the tree rather than attempt to go over the tree. At least one artificial intelligence and machine learning processor **122** and at least one artificial intelligence and machine learning processor **122** analyses the user tendencies and the previous results of other amateurs and professional golfers and determines the user **170** has a higher percentage of gaining a stroke if the user **170** makes a shot around the tree. The user **170** agrees with the AI golf assistant module **150** verbal response to the user's question and proceeds to play around the tree.

[0119] Offline is the end position distance right or left measured from the target line. Carry is the total distance of flight produced by the initial launch condition. Total distance is the combined ball flight with bounce and roll the golf ball will travel for the shot. The AI golf assistant module **150** interactive verbal responses and explanations of the specific issue related to a recommendation allows the user **170** to better understand the reasons for the recommendations and to make adjustments to correct the swing to fit the circumstances encountered on the course.

[0120] The launch monitor may be integrated into the club sensor, integrated into the club grip, club shaft, or club head. The launch monitor may also be a separate device that can be positioned near the golf ball before the swing. In one embodiment, the launch monitor may transmit and display the data on a user's mobile device and audibly broadcast the data through the AI golf application **132** installed on the user's mobile device. In another embodiment, the launch monitor may transmit and display the data on a user's AI golf assistant glasses **210** of FIG. 2 lenses and broadcast the data audibly on micro speakers **1580** of FIG. 15.

[0121] A launch monitor may use various technologies including Doppler radar technology, high-speed cameras, photometrics, and other technologies. Launch monitors may use wireless communication devices compatible with mobile device operating systems, may have displays, and may be portable or integrated into golf club structures including grips, shafts, and club heads. A launch monitor analyzes a user's swing, tracks user progress in gaining strokes, and is used during practice sessions, indoors with golf simulators, or outside while playing a round of golf. The launch monitor gathers data and analyzes the data to generate data-driven improvements for a golfer. Launch Monitor Data are parameters including the flight of the ball, the movement of the golf club head, speeds, spins, distances, angles, impact characteristics, and performance measures such as dispersion. The analysis calculates user skill levels in tee shots, approach shots, chipping, and

putting and compares the skill levels for each type of shot.

[0122] In one embodiment, the golf shot is tracked using a sensor coupled to the head of a club. The club head sensor detects the first impact of the club head with the golf ball. The club head sensor records the GPS coordinates of the first impact. In the next shot, the club head sensor records the GPS coordinates of a second club head golf ball impact and records the GPS coordinates of the second impact. The club head sensor records the GPS coordinates of each subsequent club head golf ball impact until the hole is completed on the green.

[0123] In another embodiment, the golf shot can be tracked with a sensor coupled to the golf equipment or the user's mobile device **130** to determine when the golf ball is struck indicating a shot has occurred. In addition, subsequent shots can determine distances and locations of previous ones, as each shot is linked with the next.

[0124] Also, other types of sensors, including audible sensors, optical sensors, motion sensors, location sensors, pressure sensors, magnetic sensors, and other sensors capable to reliably detect a golf shot can be used. In addition, self-reporting voice commands can be used to alert the AI golf assistant module **150** that a golf shot was made at a certain location that needs to be tracked. In another embodiment, the AI golf assistant module **150** tracks extra golf shots, such as provisional golf shots or “mulligan” or secondary golf shots that the user desires to hit again either with or without adding golf scoring penalties to the user's statistics and/or scoring. In another embodiment, the AI golf assistant module **150** can be used to allow multiple users to in competitive rounds of golf by disabling certain features of the AI golf assistant module **150** to comply with local rules and governing body rules of golf.

[0125] In another embodiment, the AI golf assistant module **150** can be used by multiple users to allow the users to compete against each other either while they are playing together or playing virtually in golf competitions. In this embodiment, the AI golf assistant module **150** collects data about each user and automatically records each shot and scores for each user that is local, remote, or virtual. In one embodiment, competitive golf rounds can be organized amateur and/or professional leagues, including in-person physical leagues and virtual leagues, where the AI golf assistant module **150** can be used to automatically organize, control, track, monitor, judge and keep score of golf rounds for the competitive leagues.

[0126] The AI golf assistant module includes a processor that superimposes each in order of the recorded club head golf ball impacts using the GPS coordinates on an overlay of the RTK topography and calculates the distance between the impacts. The superimposed tracked impacts are connected linearly to show the tracked route of the golf ball in relationship to the hole topography. The user **170** reviews after the hole completion or after the last hole played to see the tracked data to assess the outcomes of the shots. The displayed impact data includes the club used for the shot, the trajectory of the golf ball, and the distance achieved with the shot of one embodiment.

[0127] FIG. **13A** shows a block diagram of an overview of the tee shot visual suggestion of one embodiment. FIG. **13A** shows the user's mobile device **130** having the AI golf application **132** and it's AI golf assistant module **150** feature. The AI golf assistant module **150** is displayed on the user's mobile device **130** RTK course hole layout **1300**. Also shown is the wind **1305**, a fairway **1310**, bunker **1312**, a bunker near green **1314**, rough **1320**, and a green and flag **1330**.

[0128] FIG. **13A** shows the distance of an average amateur tee shot **1332** from the tee that other players reach with a tee shot. Players at the user's skill level hit past 225 yards from tee **1332** and reach 250 yards from tee **1334**. The poor shot placement lands the golf ball in the rough. Players at a more advanced skill level hit past the 275 yards from tee **1336** and reach near the 300 yards from tee **1338** in the center of the fairway **1310**.

[0129] The average amateur tee shot **1332** from the amateur tee **1342** has a 34% birdie % **1344**. The advanced scoring tee shot **1345** from the mid tee **1346** has a 62% better decision **1347**. One major improvement of the advanced scoring tee shot **1345** is the shot placement. Landing in the rough **1320** creates a more difficult next shot. The tee shot visual suggestion based on the decision

of pro golfers' data **1350** produces a tee shot visual suggestion **1352** to aim the user tee shot to the center of the fairway **1310**. The AI caddy can alert the user of a shot that will be affected by the user's stored average golf shot distance and dispersion and successful shots that overcame dispersion by other amateurs and professionals of one embodiment.

[0130] FIG. **13B** shows for illustrative purposes only an example of driver golf club distance and dispersion of one embodiment. FIG. **13B** shows the user's mobile device **130** having the AI golf application **132** of FIG. **1** displaying the current hole the user is beginning to play. In one embodiment, the user is at the tee **1362** at the start of the fairway **1310**. The RTK topography map shows the nearest tree **282**. The RTK topography map also shows a bunker **360** to the right.

[0131] The AI assistant can alert the user of a shot that will be affected by the user's stored average golf shot distance and dispersion and successful shots that overcame dispersion by other amateurs and professionals. A hook or slice will vary in the amount of curvature imparted on the golf ball flight. Dispersion is the spread of the landing of the shot that will vary due to the curve of the flight trajectory. For example, the user may have an intended landing in the middle of the fairway but selects, for example, a driver.

[0132] Further from the tee **1362** is a water hazard **1382**. The AI golf application **132** of FIG. **1** shows the driver golf club the user normally selects. The AI golf application **132** of FIG. **1** superimposes the user tendency of the user's driver shots. The user's tendency is the golfer's common slight hook with a driver **1388**. The driver shot tendency has an average greater hook curve **1384** and an average lesser hook curve **1386**. The spread of the golf ball landings between the average greater hook curve **1384** and the average lesser hook curve **1386** is referred to as dispersion. The user selects the driver to get a long distance. However, in this hole, the dispersion distance **1381** can lead to the golf ball ending up in the water hazard **1382**. The driver golf club distance and dispersion **1380** may cause the hook to land the golf ball in the water hazard **1382** or roll into the water hazard **1382** of one embodiment.

[0133] FIG. **13C** shows for illustrative purposes only an example of a 2-iron golf club distance and dispersion of one embodiment. FIG. **13C** shows the user's mobile device **130** having the AI golf application **132** of FIG. **1** displaying the current hole. The dispersion will spread in an ever-increasing width the further the ball travels. This can result in an unintended course to a hazard. The AI caddy may suggest a shorter club to minimize the dispersion and shorten the distance to prevent reaching the hazard.

[0134] The user at the tee is beginning to play at the start of the fairway **1310**. The RTK topography map shows the nearest tree **282**. The RTK topography map also shows a bunker **360** to the right and further from the tee **1362** is the water hazard **1382**.

[0135] The user's mobile device **130** also displays an AI assistant suggestion for a 2-iron golf club distance and dispersion **1385**. The AI assistant shows the user's tendency with the 2-iron golf club. The golfer's common slight hook with 2-iron **1387** shows a short shot distance and reduced dispersion. The shorter distance and 2-iron average dispersion **1383** demonstrates the user has more shot control with the 2-iron versus the driver. In this instance, the water hazard poses a multi-stroke penalty opportunity as compared with eliminating the risk of a penalty versus a well-placed shot near the center of the fairway for the next shot of one embodiment.

[0136] FIG. **14** shows for illustrative purposes only an example of a RTK golf course hole plan view of one embodiment. FIG. **14** shows an RTK golf course hole plan view **1400**. Starting at the handicap tee **1444** and the non-handicap tee **1446** a tree **1440** with a tree height of 24 ft. **1442**. The distance shown is 82 yards to Fairway **1450**. The shot placement is important to an entry tee shot to the hole because of the proximity of the trees to the fairway **1415** and penalty out of bounds **1430** on both sides in the rough.

[0137] The fairway widens to a 33-yard fairway width **1462** then narrows to a 29-yard fairway width **1460**. It is 170 yards from non-handicap tee **1463** nearing the dogleg right **1410**. The AI golf assistant module **150** of FIG. **1** suggests to the user to, "Use a 3 or 4-wood to the left side of the

fairway **1415** to avoid the trees on the right side at the dogleg right **1410**. A slight fade to avoid the rough **1420**. This will better position the next shot through the dogleg right” **1410**.

[0138] The user responds, “The 2 or 3-iron might be better as the user has better control of the long irons and I can usually get 180 to 190 yards which will be close to the shot placement you suggested”. The RTK golf course hole plan view **1400** shows it is 213 yards from a non-handicap tee **1464** past the dogleg right **1410**. The AI golf assistant module **150** of FIG. **1** interacts with the user with a reply that, “The distance between the 170 yards from non-handicap tee **1463** and the 213 yards from non-handicap tee **1464** is approximately 191 yards and the user response of a 2 or 3-iron would work perhaps better with the 2-iron to get closer to the **190** distance for setting up the next shot”.

[0139] The user selects the 2-iron and prepares to hit the tee shot aiming to the left side of the fairway with a slight fade. The AI golf assistant module **150** of FIG. **1** interacts with the user to, “Suggest one or two practice swings with the 2-iron to check the predictable result”. The user responds with an agreement. The prediction of the two practice swings shows a result for both landing at or near the shot placement position. The AI golf assistant module **150** of FIG. **1** displays on the RTK golf course hole plan view **1400** displayed on the user's mobile device **130** of FIG. **1** the landing positions of the two practice swings predicted landing positions. The user makes the shot and as predicted the golf ball lands near the shot placement.

[0140] The 34-yard fairway width **1412** at the dogleg right **1410** provides a clear path to the first 17-yard fairway width **1414** narrowing. The user asks, “What is the distance between the first narrowing of the fairway and the second narrowing?” The AI golf assistant module **150** of FIG. **1** responds to the user, “Approximately 125 yards to the first and 165 yards to the second narrowing”. The user then asks, “What about a 5-iron to reach the second narrowing to get closer to the green for a shorter approach shot?”. The AI golf assistant module **150** of FIG. **1** responds to the user, “You tend to hit a straight 5-iron but only an average of 150 yards, the 4-iron averages 160 to 165 yards but tends to have a slight hook”. The AI golf assistant module **150** of FIG. **1** responds to the user, “Are you confident about countering the hook with a fade similar to the 2-iron first tee shot?”.

[0141] The user asks, “How do I adjust to not under or over-correct with the fade shot?” The AI golf assistant module **150** of FIG. **1** responds, “The average slight hook would be equivalent to a 3-inch draw shot, so an adjustment of a 4 to 5-inch movement of the lead foot back would counter the hook and produce a slight fade”. The RTK course hole map **1400** indicates this next shot will pass the 142 yards from green **1465** and approach or pass the second 17-yard fairway width **1414**. This may also pass the 110 yards to green **1466** to 90 yards to green **1470**. The AI golf assistant module **150** of FIG. **1** suggests, “Try at least one practice swing with the 4-iron”. The user agrees. The predictions of the user's three 4-iron practice swings show the stance adjustment will correct the hook and make a fade that will keep the landing point clear of the trees and near the center of the second narrowing. The user proceeds to make the next second shot. The prediction was correct except the golf ball rolled further than anticipated and left about 83 yards to the green.

[0142] The RTK golf course hole plan view **1400** shows at that landing point it passed the 29-yard fairway width **1460** and is left of the center of the second 17-yard fairway width **1414**. The user queries the AI golf assistant module **150** of FIG. **1** about using an 8-iron to the front of the green on the left side towards the flag **1490**. The AI golf assistant module **150** of FIG. **1** points out bunker **1472** on the left and bunker **1472** on the right in front of the green **1470** at the 32-yard fairway width **1468**. The AI golf assistant module **150** of FIG. **1** adds that the flag **1490** is about 10 yards from the front of the left side of the green **1470**. The AI golf assistant module **150** of FIG. **1** responds to the user question, “Your 8-iron tendency is 115 yards which would land towards the back of the green. Your 9-iron tendency is 102 yards. The distance to the flag is 93 yards. The green slopes to the left and front on the left front side. The slopes with the added backspin of the 9-iron should roll the golf ball towards the flag shortening the putt”.

[0143] The user agrees and will try some practice swings to try and reduce the 9-iron yardage to get

closer to the flag **1490**. The predictions for the 2 practice swings show the user would cut 5 yards off the **102** average tendency and hit a straight shot. The user proceeds with the 9-iron approach shot to the green. The golf ball lands 7 yards past the flag and rolls back 4.5 yards. The three shots to get on the green are superimposed on the RTK course hole map **1400** using the tracking data results **1040** of FIG. **10**. The approach shot past the 36 yards to green **1467** and 17 yards to green **1471** yardages. The green details **1474** section of the map indicates the golf ball position on the green **1470**. The green details **1474** show the 16 yards green width **1484** and 31-yard green length **1486** general dimensions of the green and the back downhill slope **1480** and right to left downhill slope **1482** on the left front portion of the green **1470** where the user hit the green.

[0144] The user has a 7.5-foot downhill putt to the cup **1492**. The user places a ball marker **2202** of FIG. **22** behind the golf ball and reviews the ball marker user interface **2222** of FIG. **22** to see the angle and force of the putt to sink the golf ball in the cup **1492**. The user takes 2 practice putts and sees the results that the putt should be turned 1 inch to the left to follow the target path **2342** of FIG. **23** to the cup. The user makes the putt and lands the golf ball in the cup. The user has made par for the hole.

[0145] While waiting for the next hole to clear for the tee shot, the user and the AI golf assistant module **150** of FIG. **1** review the previous hole. The AI golf assistant module **150** of FIG. **1** points out the improvements the user has made on the fade shots and well-thought-out adjustments suggested during the interaction that led to the user scoring a par for a difficult hole of one embodiment.

[0146] FIG. **15** shows for illustrative purposes only an example of the real-time kinematics of one embodiment. FIG. **15** shows real-time kinematics location of the course, golfer, ball, and cup with 1-2-centimeter accuracy **1520**. In one embodiment, the accurate, current course topography with drone collected lidar/photogrammetry having 1-2-centimeter accuracy **1530**. A physics engine to determine, for example, an ideal green landing area, and putting line/speed calculations **1540**. A virtual assistant-artificial intelligence assistant (AI-assistant) advice (conversational) for golfer club use, golfer historical tendencies with audio interaction with ear buds and microphone **1550**.

[0147] For example, golfer: "Hey AI-assistant: how far is the green trap on the right, and what club should I use, and where should I land my shot?" **1560**. The response from the AI assistant: "Trap is 175 yards, wind left to right, aim left of the trap, you shot 180 yards the last time you used your 3-wood" **1570**. The user may also use AI golf application **132** of FIG. **1** eyeglasses-visual and audio interaction textual and image projections on the lens and verbal data with micro speakers **1580** to see and hear suggestions and data related to the personalized user tendencies and predictions of shot success from practice swings and putting strokes analysis of one embodiment.

[0148] FIG. **16** shows for illustrative purposes only an example of artificial intelligence (AI) suggestions of one embodiment. FIG. **16** shows artificial intelligence (AI) suggestions **1600** based on the user's stored tendencies and stored results of other amateur and professional golfers. The AI golf assistant module **150** of FIG. **1** responds to user questions and offers suggestions on several topics, for example, shot placement **1610**, club selection **1612**, windage **1614**, green speeds based on humidity **1616**, and green contours based on high-resolution lidar topography **1618**.

[0149] Other topics include the distance and location of bunkers **1620**, out-of-bounds **1622**, water hazards **1624**, trees and heights **1626**, and cart paths **1628**. Some topics, for example, relate to the course condition including high turf rough **1630**, down slopes on sides of fairway **1632**, cup location on green **1634**, last mowing affecting roll **1636**, and recent heavy rain soggy spots in fairway **1638** of one embodiment.

[0150] FIG. **17** shows a block diagram of an overview of the AI module application of one embodiment. FIG. **17** shows the AI golf application **132** and server **110** that receives data from the club sensor **178** attached to a golf club **1710** during a practice swing **1712** and a putter **1720** during a practice putter stroke **1722**. An AI assistant analyses user course performance tendencies **1730** from dynamic database user stored tendencies **1732**. This allows the AI golf application **132** to

generate information that responds to user inquiries with personalized suggestions based on user shot tendencies and how others have played the hole **1740**.

[0151] For example, a user may ask what club to use, and the AI golf assistant module **150** of FIG. **1** may respond with, "Use 7-iron to get loft and less roll" **1742** and point out current conditions for wind, bunker locations, out of bounds and other obstacles to avoid **1750**, and, "Aim shot 20 feet right of center of green and to the uphill back of green" **1753**. The AI golf application **132**, for example, collects current wind data for wind speed and direction detection **1752** from devices wirelessly coupled to the AI golf assistant module **150** of FIG. **1**, including an anemometer **1754**, wind sound sensor coupled to a microphone **1756**, and a wind gauge **1758**.

[0152] The AI golf assistant module **150** of FIG. **1** may respond to the user's request to suggest areas to aim the shot free of obstacles **1760**. The responses may include, "Aim shot 20 feet right of the center of green and to the uphill back of green" **1762**. The AI golf assistant module **150** of FIG. **1** may respond to suggest better-scoring percentages based on other amateurs and pro shot selection **1770** with, "A 65% success rate to make par" **1772** of one embodiment.

[0153] The AI golf assistant module **150** includes a processor that superimposes each shot in the order of the recorded club head golf ball impacts using the GPS coordinates on an overlay of the RTK topography and calculates the distance between the impacts. The superimposed tracked impacts are connected linearly to show the tracked route of the golf ball in relationship to the hole topography. The user reviews after the hole completion or after the last hole played to see the tracked data to assess the outcomes of the shots. The displayed impact data includes the club used for the shot, the trajectory of the golf ball, and the distance achieved with the shot of one embodiment.

[0154] The sensor data is recorded for each club selected for different types of shots. The data includes shot distances for each club. The data enables an analysis of shot distances across various shot types for each club, facilitating comparisons between clubs for different shot types. The strokes gained is a golf stats methodology that measures a golfer's skill by each part of their game. Strokes gained is a golf statistic made up of four main components strokes gained off the tee, strokes gained on approach shots, strokes gained around the green chipping, and strokes gained putting. The strokes gained track the user's shot results for each club and type of shot and measure a golfer's skill by each part of their game.

[0155] The strokes gained analysis is to measure the overall skill of a golfer. It can assess a golfer's putting skill, chipping skill, approach shot skill, driving skill, or all of these combined into one statistic. It is a relative statistic based on average "benchmarks" for each type of shot. Total strokes gained combines all non-aggregated metrics which include off the tee, approach, around the green, and putting. The aggregated strokes gained metric is an overall measurement of a golfer's skill. The strokes gained analysis data of the user shot distances analysis provides real data for the AI golf assistant module **150** to suggest a club selection to the user **170** that has the highest percentage of resulting in a stroke gained improvement.

[0156] FIG. **18** shows for illustrative purposes only an example of vital signs wearable of one embodiment. FIG. **18** shows in one embodiment, the user's mobile device **130** having the AI golf application **132** with the AI golf assistant module **150**. The AI golf assistant module **150** detects measured player swing speed, ball impact, and vital signs to determine if the player is tiring **1800**. A player user has a vital sign wearable **1810** used to determine if the user is tired.

[0157] The club sensor **178** detects and measures a practice swing **1805** to determine swing speed and ball impact. Should the swing speed and ball impact force show decreasing levels the AI golf assistant module **150** is suggesting a club change to increase distance **1820** without as much effort **1830**. The user's mobile device **130** having the AI golf application **132** with the AI golf assistant module **150** receives the current vital signs wearable vital signs of the golfer **1812**. For example, should the vital signs show signs of reduced physical strength confirmed by reduced swing speed and ball impact force in the practice swing it would indicate the player user is tiring.

[0158] The AI golf assistant module **150** may interact with the user by suggesting: “Change your 4-wood to a 2-wood to increase distance with your normal swing **1822**”. This may also be an AI golf assistant module verbal suggestion **1880** of one embodiment.

[0159] FIG. **19** shows for illustrative purposes only an example of an approach shot of one embodiment. FIG. **19** shows the user after the approach shot swing **1900**. Before the actual approach shot the user questions on the user's mobile device **130** having the AI golf application **132** and AI golf assistant module **150** feature, “What club should I use and where should I aim the shot?” **1910**. The response is an “AI caddy: suggestion to use the 7-iron to get more loft and less roll, small green, cup in the left center of the green.” **1920**. The user selects the 7-iron **1940** from the golf bag with clubs **1930** as indicated in the AI golf assistant module verbal suggestion **1950**. After the shot swing the golf ball flight tracked **1960** shows the golf ball lands on the green **1990** near the flag **264** and avoided any bunker **1980** of one embodiment.

[0160] FIG. **20A** shows for illustrative purposes only an example of a bunker shot of one embodiment. FIG. **20A** shows the user **2000** asking the AI golf assistant module **150**, “What club should I use and where should I aim the shot?” **2010** on the user's mobile device **130** having the AI golf application **132**. The AI assistant: suggestion, “Use the pitching wedge to get more backspin to reduce roll, cup downhill from the edge of the green.” **2042**. The AI golf assistant module is a verbal suggestion **2045**. The user is in the sand bunker **2020** and selects the suggested club **2025**. The user aims for the flag **264**. FIG. **20A** shows the golf ball in flight **2060** with the flight path of the ball **2062** to the green **2050** and towards the cup **2052** of one embodiment.

[0161] In another embodiment, a sensor detects the movements of a club the user selected for a shot. The sensor includes a high-speed camera optical sensor to record and track the movements of the club head. The detected sensor data includes the movements of the club including back swing, striking of the golf ball, and follow through.

[0162] The sensor detection further includes the club face orientation relative to the golf ball. The detected and tracked club movements are used to calculate the club speed, the golf ball speed from impact to final landing, the force imparted to the ball, the club head travel path to contact the golf ball, distance of the shot, and record elapsed time of club head travel to determine speed.

[0163] The data is processed using at least one processor to calculate speeds and angles along the travel path of the club head and golf ball after impact. The high-speed optical calculated data is used to determine club speed, ball speed, swing speed, and golf ball strike angles to determine predictable loft, and poor contact with the golf ball that affects distance, trajectory, draws, and slices. The club used for each shot, distance achieved, and swing impact data are used to display the user performance with golf ball trajectory, distance, and the calculated data displayed on an overlay of the RTK topography. A review by the user after each hole and at the end of the round provides the AI golf assistant module **150** to offer recommendations on corrective measures to allow the user to improve shots and reduce the number of strokes of one embodiment.

[0164] FIG. **20B** shows for illustrative purposes only an example of a geometric calculated approach shot over a tree of one embodiment. FIG. **20B** shows the user **170** has a wearable golf environment detector **176**. The golf club **172** has a club sensor **178** attached to the shaft. The club sensor **178** includes an accelerometer, a gyroscope, a pressure sensor, a force sensor, a light sensor, and a transmitter. A processor coupled to the club sensor is used to analyze measured golf club swing data to predict a golf ball trajectory based on practice swing data including club head speed, club path direction, club face orientation, and swing path contact position.

[0165] The user **170** addressing the golf ball **174**. While addressing the golf ball **174** the user sees a first tree **2074** a short distance away that has a first tree branch **2076** low on the trunk. The user also sees a taller second tree **2080** further away but in the path to the green and flag **1330**. The user's mobile device **130** having the AI golf application **132** is aware of the user's position and the two trees based on the RTK course hole map **1400** of FIG. **14**. The height of both trees is indicated on the RTK course hole map **1400** of FIG. **14**. The AI golf application **132** using a processor and

the user's tendencies with different clubs calculates a predicted path of the golf ball **174** with an average of the user's club shots.

[0166] The predicted paths are calculated using geometry to predict adequate height to clear the second tree **2080** while starting the shot low enough to miss the first tree branch **2076**. Based on the user's tendencies the AI golf assistant module **150** displays interactively on the user's mobile device **130** the following message: "AI golf assistant: suggestion use the 7-iron to get more height to go over the 2nd tree. Your 5-Iron will get more distance but not clear the 2nd tree height." **2090**. The AI golf assistant module **150** will also display the geometric predicted shot paths to show the user the geometric paths. The AI golf assistant module **150** additionally broadcasts a verbal suggestion **2072** to alert the user of the suggestion of one embodiment.

[0167] FIG. **21** shows for illustrative purposes only an example of a schematic view of a ball marker sensor system of one embodiment. FIG. **21** shows a schematic of the sensor system **2102** of the base station **2127** of the ball marker and its unit components **2114**. The components include a positioning system **2126**, processor **2116**, sensor(s) **2124**, transceiver **2120**, memory **2118**, and a user interface **2122** of one embodiment.

[0168] The sensor system **2102** can include a housing configured to house and support the components of the sensor system **2102**. The sensor system **2102** can include a processor **2116**, memory **2118**, one or more transceivers **2120**, one or more user interfaces **2122**, one or more sensor(s) **2124**, and a positioning system **2126**.

[0169] The processor **2116** can be any circuit or virtual circuit (e.g., a physical circuit emulated by logic executing on an actual processor) that manipulates data values according to control signals (e.g., "commands," "opcodes," "machine code," etc.) and that can produce corresponding output signals that can be applied to operate a machine. A processor can be one or more of a central processing unit (CPU), a reduced instruction set computing (RISC) processor, a complex instruction set computing (CISC) processor, a graphics processing unit (GPU), a digital signal processor (DSP), an ASIC, a radio-frequency integrated circuit (RFIC), or the like. A processor can further be a multi-core processor having two or more independent processors (sometimes referred to as "cores") that may execute instructions contemporaneously.

[0170] The memory **2118** can be connected to the processor **2116** and can be a machine-readable medium, which can be a component, device, or other tangible medium able to store instructions and data temporarily or permanently and can include random-access memory (RAM), read-only memory (ROM), buffer memory, flash memory, optical media, magnetic media, cache memory, other types of storage (e.g., erasable programmable read-only memory (EPROM)), or any suitable combination thereof. The term "machine-readable medium" should be taken to include a single medium or multiple media (e.g., a centralized or distributed database, or associated caches and servers) able to store instructions.

[0171] The term "machine-readable medium" shall also be taken to include any medium, or combination of multiple media, that is capable of storing instructions (e.g., code) for execution by a machine, such that the instructions when executed by one or more processors of the machine, cause the machine to perform any one or more of the methodologies described herein. Accordingly, a "machine-readable medium" refers to a single storage apparatus or device, as well as "cloud-based" storage systems or storage networks that include multiple storage apparatus or devices.

[0172] The transceiver **2120** can be any antenna or device configured to send or receive signals, such as using one or more communication protocols such as Bluetooth™, cellular, NFC, Ethernet, Wi-Fi, or the like. Further examples are discussed in FIG. **7**. The transceiver **2120** can be connected to the processor **2116** such as to receive data therefrom and to transfer data thereto. One or more transceivers **2120** can be configured to transmit data to or receive data from external devices (through any protocol or medium discussed above or below) such as the AI golf application **132** of FIG. **1**, the user audio device, the club sensor **178** of FIG. **1**, or the user device.

[0173] The user interface **2122** can be any display and/or input device. For example, the user

interface **2122** can be a touchscreen monitor or display, or any combination of buttons, lights, switches, speakers, or the like. The user interface **2122** can be connected to the processor **2116** and can be configured to display information for receipt by the golfer. Optionally, the processor **2116** can be configured to receive information from the user, such as via selectable indications or buttons, which can be transmitted by the user interface **2122** to the processor **2116**. The user interface **2122** can optionally be connected to an outer portion of the housing to allow user interaction with the user interface **2122**. The user interface **2122** can optionally extend at least partially through the housing.

[0174] One or more sensors **2124** can be any sensors configured to collect location or swing information. For example, as noted above, one or more sensors **2124** can include one or more of a radar sensor, a lidar sensor, an image capture device (e.g., camera), an optical sensor, or the like. One or more sensors **2124** can produce one or more signals based on observed or monitored swings of the golfer that can be transmitted to the AI golf application **132** of FIG. **1**, the user device, or other devices. One or more sensors **2124** can be connected to the processor **2116** such as to transmit data collected from one or more sensors **2124**. The one or more sensors **2124** can optionally extend at least partially through the one or more sensors **2124** such as to enable collection of swing data.

[0175] The positioning system **2126** can include one or more positioning receivers (such as a GPS receiver, i.e., L-band radio receiver) and a processor for communicating with satellites and resolving a position of the sensor system **2102** based on the resolution or calculation. The positioning system **2126** can optionally be or can include an RTK system including a receiver and processor for using a corrective stream to more accurately resolve or determine a location of the positioning system **2126** and the sensor system **2102**.

[0176] The correcting stream can be received from one or more base stations **2127**. The base station **2127** can be located at the golf course or can be located within a radius of several golf courses. The positioning system **2126** can receive a correcting stream from the base station **2127** and can (optionally with the GPS-determined location) resolve the location of the sensor system **2102** more accurately. For example, the positioning system **2126** including the RTK system can determine the location of the sensor system **2102** with an accuracy of up to ± 1 centimeter.

[0177] In operation of some examples, the user can power on the sensor system **2102**, such as using the user interface **2122**. Once powered on, the sensor system **2102** can be positioned at or near the ball on the green of the golf course or any golf course. The positioning system **2126** can determine the location of the sensor system **2102**, which can be transmitted to the AI golf application **132** of FIG. **1** or the user device for comparing to a database or table of courses and holes for identifying the hole and the golf course on which the sensor system **2102** is placed.

[0178] New hole placement on a green is updated based on recent golfers playing on the course using the AI golf application **132** of FIG. **1**. The ball marker data while putting will upload to the server and be used to update the stored RTK data on the new hole location. A user may plan on a drone fly-over of the course following the GPS coordinates of each from the RTK mapping to quickly determine any changes in the hole locations.

[0179] As discussed above, the location of the sensor system **2102** can also be used by the sensor system **2102**, the AI golf application **132** of FIG. **1**, or the user device to determine the relative position of the sensor system **2102** and the ball to the hole, such as by referring to a table of hole placements for the identified putting green and the identified golf course. Once the ball and hole locations are determined, a green topography can be determined, and a desired ball trajectory can be selected. Once selected, required swing characteristics can be determined, as discussed above, and the user can indicate, such as through the user interface **2122** or the user device that the user wants to perform a practice swing to be observed or monitored by the sensor system **2102**.

[0180] When the sensor system **2102** receives an input or instruction from the golfer that a practice swing is to be observed, the sensor system **2102** can activate one or more sensors **2124**, and one or

more sensors **2124** can observe or monitor the practice swing of the user, such as via an image capture device or radar. One or more sensors **2124** can produce a signal including data from the observed practice swing, which can be transmitted to the processor **2116**. The processor **2116** can determine one or more practice swing characteristics based on the received signals from one or more sensors **2124**. The processor **2116** can then compare the practice swing characteristics to the required characteristics to put the ball on the selected trajectory. Optionally, the processor **2116** can instruct one or more transceivers **2120** to transmit the sensor data and the calculations can be performed at the AI golf application **132** of FIG. 1 or the user device.

[0181] The processor **2116** (or other processor of the AI golf application **132** of FIG. 1 or the user device) can determine whether the practice swing characteristics are likely to put the ball on the selected trajectory and the results of the determination can be transmitted to the user, such as via the transceiver one or more transceivers **2120** to the user audio device **2206** of FIG. 22. Optionally the results can be transmitted to the user through the user interface **2122** or the user device. The devices of the sensor system **2102** can be used to perform additional steps, as discussed below concerning FIGS. 26 and 27.

[0182] FIG. 22 shows a block diagram of an overview of the AI module application display screen of a text message of one embodiment. FIG. 22 shows the user's mobile device **130** of FIG. 1 having the AI golf application **132** of FIG. 1 with the AI golf assistant module **150** of FIG. 1 feature. The AI golf assistant module **150** of FIG. 1 informs the user that the "Practice swing speed: too fast, reduce by 3 feet in distance" **2210**. A ball marker **2202** includes a ball marker user interface **2222** that allows the user to see the results of the ball marker sensor system **2208** detections of the putter stroke. The ball marker sensor system **2208** detections are transmitted to an AI golf application **132** via cloud **2204** for recordation in the dynamic database **124** of FIG. 1. The user may also receive the sensor data using a user audio device **2206** for a verbal message interaction with the AI golf assistant module **150** of FIG. 1 of one embodiment.

[0183] The user's mobile device **130** of FIG. 1 can be a tablet, smartphone, computer, laptop computer, or other device including a processor and a transceiver. The user audio device **2206** can be an audio device, such as headphones or earbuds configured to output audio via a speaker. Optionally, the user audio device **2206** can include a microphone configured to receive audio input, such as from a user. The user audio device **2206** can be connected to one or more devices of the golf swing system such as the user's mobile device **130** of FIG. 1 and the ball marker sensor system **2208** of one embodiment.

[0184] FIG. 23 shows a block diagram of an overview of the AI module application display screen of a text message of one embodiment. FIG. 23 shows the user's mobile device **130**, AI golf application **132**, and AI golf assistant module **150**. The AI golf application **132** provides bidirectional communication **2332** with the artificial intelligence remote server platform **100**. The artificial intelligence remote server platform **100** includes the artificial intelligence server **110**, databases **115** including at least one static database **120**, and dynamic database **124**. The artificial intelligence remote server platform **100** includes the artificial intelligence and machine learning processor **122**.

[0185] FIG. 23 shows the actual golf ball **174** as it is positioned relative to the actual hole **2370**. These actual relative positions are displayed on the user's mobile device **130**. FIG. 23 shows the AI golf assistant module **150** displaying the golf ball **2340** and a target path **2342** to aim the putt to follow a slope curve **2350** to the cup **2344**.

[0186] The AI golf assistant module audio suggestion **2380** broadcasts the audio suggestion to the user **2360**, in this example, where the user audio device may include earbuds **2381**. The target path **2342** is based on the user practice strokes, transmissions from club sensor **2368**, stored static database golf course terrain, elevations, water hazards, etc., and greens flag placements **2390**, other players of the hole stored in the dynamic database **124**, and green slope contours measured accurately up to ± 1 centimeter. The club sensor **178** is attached to the putter **2362** to detect,

measure, and transmit the movements, speed, direction, and force level of the putter during the user's **2360** practice strokes.

[0187] The contours and other physical and conditional characteristics of the golf course and each hole are recorded from the RTK golf course hole plan view **1400** of FIG. **14** collected in the real-time kinematic flyover measurement detection observations. The RTK golf course hole plan view **1400** of FIG. **14** is updated from other members playing the course and monthly reanalysis of the conditions **2392**. The updates and monthly reanalysis of the conditions are stored static database of golf course terrain, elevations, water hazards, etc., and greens flag placements **2390** of one embodiment.

[0188] FIG. **24** shows a block diagram of an overview of a golfer on a putting green of one embodiment. FIG. **24** shows a ball marker **2202** and a user **2460** on a putting green of a golf course. More specifically, user **2460** is illustrated holding a putter **2362** and addressing a golf ball **174** on a green uphill slope **2420** of the putting surface **2410** of the green. The user **2460** is aligned toward a cup **2370** indicated by a flag **264** and flagstick **2430**. The ball marker **2202** of FIG. **22** can be placed or located on or near the green uphill slope **2420**, such as behind the golf ball **174** relative to the cup **2370**. The ball marker **2202** can include one or more sensors for observing a swing of the user **2460**, such as a practice swing or a stroke of the putter **2362** as it contacts the golf ball **174**. The ball marker **2202** can produce swing data based on the observed or monitored swing, to provide swing guidance to the user.

[0189] The ball marker **2202** can also include one or more sensors to determine or transmit a location of the ball marker **2202**. The location of the ball marker **2202** can be used to identify the course and hole of the course on which the ball marker **2202** is placed. The AI golf application **132** of FIG. **1** can determine, based on the hole location, one or more required swing characteristics to put the golf ball **174** on the selected path to make the putt or stroke.

[0190] The AI golf application **132** of FIG. **1** can then compare the practice swing characteristics of the putt, as observed by the ball marker **2202**, to the required swing characteristics to make the putt and provide feedback or guidance to the user **2460**. For example, the AI golf assistant module **150** of FIG. **1** can inform the user **2460** whether the stroke is likely to result in a made putt, helping to improve a user's score, help the user learn their golf course, and help improve the user's green reading skills.

[0191] A computing environment includes a ball marker **2202** that is connected to a user's mobile device **130** of FIG. **1** (e.g., a smartphone) via the connection. Connection can typically be a Bluetooth™ connection; however, any other type of connection over which two computing devices can communicate could be used. The user's mobile device **130** of FIG. **1** is connected to an artificial intelligence server **110** of FIG. **1** via a wireless connection. Connection can typically be a mobile network data connection; however, any other type of connection can also be used.

[0192] The user's mobile device **130** of FIG. **1** can be any type of computing device that can be carried by the golfer. For example, the user's mobile device **130** of FIG. **1** can be the user's smartphone having an AI golf application **132** of FIG. **1** for communicating with the ball marker **2202** and artificial intelligence server **110** of FIG. **1**.

[0193] In typical usage, a user **2460** will carry the ball marker **2202** and user's mobile device **130** of FIG. **1** onto the green and use the ball marker **2202** to mark the golf ball **174** of FIG. **1**. The ball marker **2202** communicates information to the user's mobile device **130** of FIG. **1** which is routed to the artificial intelligence server **110** of FIG. **1**. The artificial intelligence server **110** uses the information to calculate the force and direction information for the shot and routes this information back to ball marker **2202** via user's mobile device **130** of FIG. **1**. The ball marker **2202** can then display the force and direction information to the golfer to assist the golfer in playing the shot of one embodiment.

[0194] FIG. **25** shows for illustrative purposes only an example of a plan view of a putting green of one embodiment. FIG. **25** shows a putting green **2551** of a golf course **2552**. The ball marker **2202**

is shown on the putting green **2551** putting surface **2558** positioned behind the golf ball **174** aligned toward cup **2370** indicated by a flag **264** of FIG. 2. Based on the alignment with the ball marker **2202** FIG. 25 shows directions Left, Right, Past, and Short. The ball marker **2202** can include a transceiver configured to connect to an external system, such as the AI golf application **132** of FIG. 1 through one or more local or remote antennas. The ball marker **2202** and the AI golf application **132** of FIG. 1 can, together, use the global positioning system (GPS) along with a real-time kinematics (RTK) system to determine the location of the ball marker **2202** and therefore the location of the golf ball **174**. The determined location can be used to identify the golf course and the putting green of the hole of the ball marker **2202** and the user **170** of FIG. 1.

[0195] The ball marker **2202**, or the user's mobile device **130** of FIG. 1 can include access to the static database **120** of FIG. 1 of golf courses and holes where a topography of each green is stored and maintained. The database can also store recent golf hole locations on each green, which can be input by previous users (e.g., golfers or workers). Optionally, if the location of the hole is shown incorrectly, user **170** of FIG. 1 can place the ball marker **2202** at the location of the hole to correct (such as using GPS and RTK) the location of the hole on the green. The hole location can then be updated in the database, such as in the static database **120** of FIG. 1. For example, the ball marker **2202** can be used to determine the location of the cup **2370** on the putting green.

[0196] Because the system e.g., the ball marker **2202** knows the location of cup **2370** and golf ball **174**, the ball marker **2202** can determine a distance D between golf ball **174** and cup **2370**. Further, because the system knows the topography of the putting green, the ball marker **2202** can determine, using a physics engine, a plurality of trajectories of the ball to be holed or made by a putt. The trajectories can be presented to the user **170** of FIG. 1 for selection of a desired trajectory, i.e., a putt with a desired speed and path to the hole.

[0197] The ball marker **2202** can determine, based on the hole location, one or more required swing characteristics to put the ball on the selected path. The selected path can be communicated to the user **170** of FIG. 1 such as via the user's mobile device **130** of FIG. 1 or the ball marker **2202** and can be used by the ball marker **2202** or AI golf application **132** of FIG. 1 on the user's mobile device **130** of FIG. 1 to determine putting stroke instructions. For example, though the distance between the golf ball **174** and the hole is D , the ball marker **2202** can provide instructions to make a stroke at a force that normally falls short of the hole, such as by a distance of one foot (or about 0.3 meters).

[0198] Similarly, the ball marker **2202** can provide directional aiming instructions relative to the cup **2370**. For example, though the shortest path to the hole is shown by the line indicating distance D , the system can show an aiming path A (e.g., graphically) such as on the user's mobile device **130** of FIG. 1 or the ball marker **2202**. The aiming path A can also be communicated to the user **170** of FIG. 1 in relative directional instructions. For example, directions can be sent (e.g., via the user audio device **2206** of FIG. 22) to aim left of the hole by 3.3 feet (or about 1 meter). The user can optionally use this information of an aim point and an aiming distance to make a stroke or to make a practice stroke.

[0199] If the user so decides, the user can select, such as via the user's mobile device **130** of FIG. 1, to have the ball marker **2202** observe a practice swing or practice stroke. The ball marker **2202** can observe, such as via one or more sensors, the practice swing of the golfer. The ball marker **2202** can produce data based on the observed or monitored practice swing. The data can be transmitted to the AI golf assistant module **150** of FIG. 1 on the user's mobile device **130** of FIG. 1 or can be stored at the ball marker **2202**. The data of the practice swing can be used to determine one or more practice swing characteristics, which any of the ball marker **2202** or the AI golf assistant module **150** of FIG. 1 on the user's mobile device **130** of FIG. 1 can compare to the one or more required swing characteristics to put the golf ball **174** on the selected path.

[0200] Based on this comparison, the AI golf application **132** of FIG. 1 (any of the ball marker **2202** or AI golf assistant module **150** of FIG. 1 on the user's mobile device **130** of FIG. 1) can

determine a probable stroke result or outcome of the putt and can transmit the probable stroke result to the user's mobile device **130** of FIG. **1**, or can transmit such information through the ball marker **2202** or the user audio device **2206** of FIG. **22**. For example, the AI golf assistant module **150** of FIG. **1** can inform the user **170** of FIG. **1** whether or not the stroke is likely to result in a made putt. This information (or feedback) can be provided to the user in several ways, such as through audio feedback (e.g., through the user audio device **2206** of FIG. **22**, the ball marker **2202**, or the user's mobile device **130** of FIG. **1**).

[0201] The feedback or information can also be provided to the user **170** of FIG. **1** via visible feedback such as a display of images on the GUI **148** of FIG. **1** screen of the user's mobile device **130** of FIG. **1** or through one or more lights on the ball marker **2202**. The feedback or information can also be provided to user **170** of FIG. **1** in other ways, such as the vibration of the user's mobile device **130** of FIG. **1**, such as when it is in the pocket of the user **170** of FIG. **1**. For example, a first vibration characteristic (e.g., quick vibrations) can indicate a bad practice stroke and a second vibration characteristic (e.g., slow vibrations) can indicate a good practice stroke.

[0202] The user **170** of FIG. **1** can receive this information and modify their swing and can optionally repeat the practice swing process until the user receives a notification that the practice swing is likely to result in a holed putt. In this way, user **170** of FIG. **1** can use feedback provided by the ball marker **2202** (or the AI golf application **132** of FIG. **1** or the user's mobile device **130** of FIG. **1**) to select a putting trajectory or line and can further use the golf swing ball marker **2202** to determine whether a practice stroke of user **170** of FIG. **1** is likely to result in a ball trajectory on the selected line. These AI golf applications **132** of FIG. **1** and methods can help to lower a golfer's score while helping a golfer learn green reading and putting distance control.

[0203] Optionally, user **170** of FIG. **1** can select an indication on the user's mobile device **130** of FIG. **1** or ball marker **2202** that user **170** of FIG. **1** is going to deliver a stroke to the golf ball **174**. The ball marker **2202** can observe or monitor the delivered stroke and can produce stroke data which can be used to determine one or more stroke characteristics. The stroke characteristics can be compared to the required characteristics and the practice swing characteristics and feedback or guidance for use on future putts can be provided to the user **170** of FIG. **1** of one embodiment.

[0204] FIG. **26** shows for illustrative purposes only an example of putt path determination of one embodiment. FIG. **26** shows the process to determine the location of sensor **2602** and determine the location of the hole relative to sensor **2604**. Upon the determinations, the AI golf application **132** of FIG. **1** will calculate reverse paths from hole **2606**. The select path **2608** calculations will factor in the contours of the green and other factors affecting the roll of the golf ball **174** of FIG. **1**. The determinations are providing golf swing information, guidance, or feedback to a user and can be performed using one or more of the devices discussed above or below. The feedback to the user is produced using the AI golf application **132** of FIG. **1**.

[0205] The determinations include the location of the ball marker **2202** of FIG. **22** positioned on the ground surface. For example, the ball marker **2202** of FIG. **22** (e.g., the positioning system of the ball marker **2202** of FIG. **22**) can communicate with a GPS network (and optionally an RTK network) to determine the location of the ball marker **2202** of FIG. **22**. The ball marker **2202** of FIG. **22** can transmit the location to the AI golf application **132** of FIG. **1** on the user's mobile device **130** of FIG. **1** where either device can use the location to identify the golf course (e.g., the golf course) and the putting green (e.g., the putting green) such as by referencing the static database **120** of FIG. **1** of stored locations of the golf course and putting greens.

[0206] The golf swing ball marker **2202** of FIG. **22** (e.g., the AI golf application **132** of FIG. **1**) can also include a stored database of recent hole locations and can use the location of the ball marker **2202** of FIG. **22** to determine the location of the nearest and most recent hole. Once the golf hole location is determined, the AI golf application **132** of FIG. **1** on the user's mobile device **130** of FIG. **1** can transmit the location to the user, which can be displayed on the display screen of the user's mobile device **130** of FIG. **1**, the ball marker **2202** of FIG. **22** user interface, or can be

transmitted via another device, such as the user audio device **2206** of FIG. **22**. Upon receipt of the identifying information, the user can be presented with a confirmation indication on the display screen or the user interface, to confirm the location.

[0207] A location of the hole relative to the ball marker **2202** of FIG. **22** can be determined. For example, once the hole location is confirmed or updated, the golf swing ball marker **2202** of FIG. **22** (e.g., the AI golf application **132** of FIG. **1**) can use the location of cup **2370** and the location of the golf ball **174** of FIG. **1** to determine a relative location of the ball marker **2202** of FIG. **22** (located at the golf ball **174** of FIG. **1**) to the cup **2370** of FIG. **23**.

[0208] Then the AI golf application **132** of FIG. **1** can determine paths or trajectories, such as reverse paths, from the hole to the ball. Because the golf swing ball marker **2202** of FIG. **22** knows the identity of the putting green of the golf course, the golf swing ball marker **2202** of FIG. **22** can look up or find a stored green topography for the putting green. The ball marker **2202** of FIG. **22** (e.g., the AI golf application **132** of FIG. **1**) can then determine, such as using a physics engine to determine one or more reverse paths or trajectories from the cup **2370** of FIG. **23** to the golf ball **174** of FIG. **1**.

[0209] A path can be selected. For example, the ball marker **2202** of FIG. **22** (e.g., through the user's mobile device **130** of FIG. **1** GUI **148** or the ball marker **2202** of FIG. **22** user interface) can present to the user **170** of FIG. **1** one or more paths or trajectories of which the user **170** of FIG. **1** can select a trajectory or path to the hole, such as based on required putting speed or velocity. Optionally, the golf swing ball marker **2202** of FIG. **22** can select an optimal path. The selected path can also be used by the ball marker **2202** of FIG. **22**, AI golf application **132** of FIG. **1**, or the user's mobile device **130** of FIG. **1** to determine putting stroke instructions. For example, the ball marker **2202** of FIG. **22** can determine or produce instructions to make a stroke at a particular distance and a particular aiming point relative to the hole, as discussed above in one embodiment.

[0210] FIG. **27** shows for illustrative purposes only an example of interactive putt path selection of one embodiment. FIG. **27** shows feedback to transmit instructions to user **2702** and receive user confirmation **2704**. The feedback will display the results to determine the required swing **2706**. The ball marker **2202** of FIG. **22** will monitor user practice swing **2708** and then compare user swing to required swing **2710**. The user and systems interaction will provide user feedback **2712** on the viability of the practice swing and ask if the user accepts. **2714**. A user NO response will send the process back to an additional monitor user practice swing **2708**. A user's YES response will prompt the ball marker **2202** of FIG. **22** to monitor stroke **2716** and provide user feedback **2718** on the stroke and either the success of the golf ball **174** of FIG. **1** falling into the cup or the cause of a miss of the cup.

[0211] FIG. **28** shows for illustrative purposes only an example of user AI golf assistant interaction of one embodiment. FIG. **28** shows a machine **2800** that may include or may operate by, logic or several components, or mechanisms in the machine **2800** where the machine **2800** can be one or more of the devices or systems discussed above, such as the golf swing ball marker **2202** of FIG. **22**, the AI golf application **132** of FIG. **1**, or the user's mobile device **130** of FIG. **1**. The machine **2800** may include a processor **2802** with instructions **2824**, main memory **2804** with instructions **2824**, and a static memory **2806** with instructions **2824**. The machine **2800** may also include human input sensor(s) **2828**, a network interface device **2820**, a connection to a network **2826**, a display device **2810**, an input device **2812**, a UI navigation device **2814**, mass storage **2816**, machine-readable medium **2822** with instructions **2824**, a signal generation device **2818**, an output controller **2830**, and at least one link **2808** between the components.

[0212] The machine **2800** may include circuitry (e.g., processing circuitry) of a collection of circuits implemented in tangible entities of the machine **2800** that include hardware (e.g., simple circuits, gates, logic, etc.). Circuitry membership may be flexible over time. Circuitries include members that may, alone or in combination, perform specified operations when operating. For example, the hardware of the circuitry may be immutably designed to carry out a specific operation

(e.g., hardwired).

[0213] For example, the hardware of the circuitry may include variably connected physical components (e.g., execution units, transistors, simple circuits, etc.) including a machine-readable medium physically modified (e.g., magnetically, electrically, moveable placement of invariant massed particles, etc.) to encode instructions of the specific operation. In connecting the physical components, the underlying electrical properties of a hardware constituent are changed, for example, from an insulator to a conductor or vice versa.

[0214] The instructions enable embedded hardware (e.g., the execution units or a loading mechanism) to create members of the circuitry in hardware via the variable connections to carry out portions of the specific operation when in operation. Accordingly, in an example, the machine-readable medium elements are part of the circuitry or are communicatively coupled to the other components of the circuitry when the device is operating. For example, any of the physical components may be used in more than one member of more than one circuitry. For example, under operation, execution units may be used in a first circuit of a first circuitry at one point in time and reused by a second circuit in the first circuitry, or by a third circuit in a second circuitry at a different time. Additional examples of these components concerning the machine **2800** follow.

[0215] In alternative embodiments, the machine **2800** may operate as a standalone device or may be connected (e.g., networked) to other machines. In a networked deployment, machine **2800** may operate in the capacity of a server machine, a client machine, or both in server-client network environments. For example, machine **2800** may act as a peer machine in a peer-to-peer (P2P) (or other distributed) network environment. The machine **2800** may be a personal computer (PC), a tablet PC, a set-top box (STB), a personal digital assistant (PDA), a mobile telephone, a web appliance, a network router, switch or bridge, or any machine capable of executing instructions (sequential or otherwise) that specify actions to be taken by that machine. Further, while only a single machine is illustrated, the term “machine” shall also be taken to include any collection of machines that individually or jointly execute a set (or multiple sets) of instructions to perform any one or more of the methodologies discussed herein, such as cloud computing, software as a service (SaaS), other computer cluster configurations.

[0216] The machine (e.g., computer system) **2800** may include a hardware processor **2802** (e.g., a central processing unit (CPU), a graphics processing unit (GPU), a hardware processor core, or any combination thereof), a main memory **2804**, a static memory (e.g., memory or storage for firmware, microcode, a basic-input-output (BIOS), unified extensible firmware interface (UEFI), etc.) **2806**, and mass storage **2808** (e.g., hard drive, tape drive, flash storage, or other block devices) some or all of which may communicate with each other via an interlink (e.g., bus) link **2808**.

[0217] The machine **2800** may further include a display unit **2810**, an alphanumeric input device **2812** (e.g., a keyboard), and a user interface (UI) navigation device **2814** (e.g., a mouse). For example, the display unit **2810**, input device **2812**, and UI navigation device **2814** may be a touch screen display. The machine **2800** may additionally include a storage device (e.g., drive unit), a signal generation device **2818** (e.g., a speaker), a network interface device **2820**, and one or more sensors, such as a global positioning system (GPS) sensor, compass, accelerometer, or another sensor.

[0218] The machine **2800** may include an output controller **2830**, such as a serial (e.g., universal serial bus (USB), parallel, or other wired or wireless (e.g., infrared (IR), near field communication (NFC), etc.) connection to communicate or control one or more peripheral devices (e.g., a printer, card reader, etc.). Registers of the processor **2802**, the main memory **2804**, the static memory **2806**, or the mass storage **2816** may be, or include, a machine-readable medium **2822** on which is stored one or more sets of data structures or instructions **2824** (e.g., software) embodying or utilized by any one or more of the techniques or functions described herein.

[0219] The instructions **2824** may also reside, completely or at least partially, within any of the registers of the processor **2802**, the main memory **2804**, the static memory **2806**, or the mass

storage **2816** during execution thereof by the machine **2800**. For example, one or any combination of the hardware processor **2802**, the main memory **2804**, the static memory **2806**, or the mass storage **2816** may constitute the machine-readable media **2822**. While the machine-readable medium **2822** is illustrated as a single medium, the term “machine-readable medium” may include a single medium or multiple media (e.g., a centralized or distributed database, and/or associated caches and servers) configured to store one or more instructions **2824**.

[0220] The term “machine-readable medium” may include any medium that is capable of storing, encoding, or carrying instructions for execution by the machine **2800** and that causes the machine **2800** to perform any one or more of the techniques of the present disclosure, or that is capable of storing, encoding or carrying data structures used by or associated with such instructions. Non-limiting machine-readable medium examples may include solid-state memories, optical media, magnetic media, and signals (e.g., radio frequency signals, other photon-based signals, sound signals, etc.). In an example, a non-transitory machine-readable medium comprises a machine-readable medium with a plurality of particles having invariant (e.g., rest) mass, and thus are compositions of matter.

[0221] Accordingly, non-transitory machine-readable media are machine-readable media that do not include transitory propagating signals. Specific examples of non-transitory machine-readable media may include non-volatile memory, such as semiconductor memory devices (e.g., Electrically Programmable Read-Only Memory (EPROM), Electrically Erasable Programmable Read-Only Memory (EEPROM)) and flash memory devices; magnetic disks, such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks.

[0222] The instructions **2824** may be further transmitted or received over a communications network **2826** using a transmission medium via the network interface device **2820** utilizing any one of several transfer protocols (e.g., frame relay, internet protocol (IP), transmission control protocol (TCP), user datagram protocol (UDP), hypertext transfer protocol (HTTP), etc.). Example communication networks may include a local area network (LAN), a wide area network (WAN), a packet data network (e.g., the Internet), mobile telephone networks (e.g., cellular networks), Plain Old Telephone (POTS) networks, and wireless data networks (e.g., Institute of Electrical and Electronics Engineers (IEEE) 802.11 family of standards known as Wi-Fi®, IEEE 802.16 family of standards known as WiMax®, IEEE 802.15.4 family of standards, peer-to-peer (P2P) networks, among others.

[0223] For example, the network interface device **2820** may include one or more physical jacks (e.g., Ethernet, coaxial, or phone jacks) or one or more antennas to connect to the communications network **2826**. For example, the network interface device **2820** may include a plurality of antennas to wirelessly communicate using at least one of single-input multiple-output (SIMO), multiple-input multiple-output (MIMO), or multiple-input single-output (MISO) techniques. The term “transmission medium” shall be taken to include any intangible medium that can store, encode, or carry instructions for execution by the machine **2800**, and includes digital or analog communications signals or other intangible medium to facilitate communication of such software. A transmission medium is a machine-readable medium.

[0224] FIG. **29** shows for illustrative purposes only an example of ball marker placement of one embodiment. FIG. **29** shows a green **2900** with an indication of true north **2902**. Also shown is a cup **2370** with a line from cup to ball **2920**. Also shown is an angle from true north **2910** to the line from cup to ball **2920**. Next to the golf ball **174** is the ball marker **2202** whose arrow **2960** is oriented to be in line with the line from cup to ball **2920**. The green **2900** comprises a putting surface **2903** having a hole **2370** marked by a flagstick or pin.

[0225] The putting surface **2903** comprises grass that is cut very short so that a golf ball **174** may roll for a long distance. The putting surface **2903** may further include various physical contours, such as slopes or grades which are designed to challenge the player in putting the golf ball **174** into hole **2370**. Accordingly, a player must account for the physical contours of putting surface **2903**

when putting golf ball **174** into the hole **2370**.

[0226] To accurately provide swing parameters (e.g. force and direction information) for putting the golf ball **174** into the hole **2370**, three general pieces of information must be known: (1) the position of golf ball **174** on green **2900**; (2) the position of the hole **2370** on green **2900**; and (3) the topography of the green **2900** (e.g. the slope of putting surface **2903** between golf ball **174** and hole **2370**). The present invention enables the quick determination of the required information and the calculation of recommended swing parameters in an accurate manner without slowing play.

[0227] Specifically, the topography of the green **2900** and the position of the hole **2370** can be preprogrammed into artificial intelligence server **110** of FIG. **1** (because the topography should remain constant and the position of the hole **2370** is changed infrequently and can be updated accordingly). However, the position of golf ball **174** is different for each golfer. Accordingly, the ball marker **2202** can be used to determine the position of the golf ball **174** on the green **2900**. The determination of the position of the golf ball **174** can use two types of data: (1) the angle from true north formed by a line between ball **174** and the hole **2370**; and (2) the distance between golf ball **174** and the hole **2370**.

[0228] FIG. **30** shows a block diagram of an overview flow chart of the estimated distance input of one embodiment. FIG. **30** shows three input buttons **3005-3020** of the ball marker **2202**. Button **3005** can be pressed to switch between modes for entering distance and requesting an angle. Button **3010** can be used to change the value of the most significant digit of distance **59 3040**, for example, 5 in this case. Button **3020** can be used to change the value of the least significant digit of distance **59 3040**, for example, 9 in this case. The display **3030** can be a touch display, displaying a distance which is shown as being 59 ft.

[0229] The ball marker **2202** can be used to receive user **170** of FIG. **1** input of an estimated distance. Buttons **3005-3020** can be pressed to input or modify distance **3040**. For example, button **3005** can be pressed to switch between modes for entering distance and requesting an angle. Before placing ball marker **2202** behind the golf ball **174** of FIG. **1**, the estimated distance can be input such as by using buttons **3010** and **3020**. For example, button **3010** can be used to change the value of the most significant digit of distance **3040**, and button **3020** can be used to change the value of the least significant digit of distance **3040**.

[0230] As described above, buttons **3005-3020** are the only way in which input can be provided to ball marker **2202**, and any other type of input device or means can also be used. For example, display **3030** can be a touch display so that no buttons or other input controls are required. In other cases, a combination of buttons or other input controls and a touchscreen call also be provided. Similarly, ball marker **2202** can be configured to accept speech input in some embodiments. Accordingly, ball marker **2202** can receive user input of an estimated distance in any appropriate manner.

[0231] Once a distance is input, ball marker **2202** can be placed behind the golf ball **174** of FIG. **1**, as shown in FIG. **4**, after which the ball is typically removed from the green. Referring specifically to the example in FIG. **30**, after a distance is input, button **3005** can be pressed to switch to the mode for acquiring an angle. In this mode, ball marker **2202** can use a compass module to determine an angle from true north and submit the angle and the distance input by the user **170** of FIG. **1** to artificial intelligence server **110** of FIG. **1** via the user's mobile device **130** of FIG. **1**.

[0232] In some embodiments, the compass module can be configured to detect the angle once ball marker **2202** has been at rest for a specified duration of time or in response to input from user **170** of FIG. **1**, which would allow the user **170** of FIG. **1** to align the indication with the hole before the angle determination being made. Once the angle is determined by the compass module, ball marker **2202** can be picked up or otherwise removed from the putting surface.

[0233] In this manner, ball marker **2202** only requires the user **170** of FIG. **1** to input an estimated distance and then place the ball marker behind the golf ball. Typically, a golfer is required to mark his ball on the green with some type of ball marker, and therefore, placing ball marker **2202** behind

golf ball **174** of FIG. **1** does not require any additional time than would otherwise be taken by the user **170** of FIG. **1**.

[0234] Using the present invention, the only additional step required of the user **170** is the input of an estimated distance. However, because ball marker **2202** can provide recommended force and direction information for putting the ball, which the typical golfer would otherwise spend a significant amount of time determining mentally, the use of ball marker **2202** may not slow play, and in many cases may even speed play.

[0235] For example, as will be more fully described below, ball marker **2202** can inform the golfer how hard the putt should be hit and the approximate direction to aim. This information can be determined and returned immediately by artificial intelligence server **110** of FIG. **1** for display on ball marker **2202** thereby relieving the golfer from having to spend the time to figure out this information on his own. The golfer only needs to view the information on the ball marker **2202** and play the shot accordingly.

[0236] Using the estimated distance input by the golfer and the angle calculated by the compass module, artificial intelligence server **110** of FIG. **1** can accurately determine the position of the ball on the green. Using this position in combination with the known position of the hole and the topography of the green, artificial intelligence server **110** of FIG. **1** can calculate the approximate amount of force with which the ball should be hit, and the approximate direction to hit the ball. For example, based on the topography of the green between the position of the ball and the hole, artificial intelligence server **110** of FIG. **1** can determine that the hole is four feet uphill from the ball and that there is a rightward slope of 10 degrees. Artificial intelligence server **110** of FIG. **1** can therefore recommend hitting the ball x feet to the left of the hole (to account for the break to the right) and with a force Y (to account for the uphill slope).

[0237] FIG. **31** shows for illustrative purposes only an example of recommended force and direction information of one embodiment. FIG. **31** shows the ball marker **2202**. The ball marker **2202** display **3030** can be a touch display. In this instance, display **3030** shows a distance: of 59 feet, a force: of 65 feet, and an angle of left: of 3 feet.

[0238] The display of recommended force and direction information on ball marker **2202** uses the example numbers from FIG. **30**. As shown, given an estimated distance of 59 feet and the other known parameters, artificial intelligence server **110** of FIG. **1** has recommended that the putt be hit with a force of 65 feet (i.e. with a force that would result in the ball moving 65 feet over a flat green) and at 3 feet to the left of the hole.

[0239] FIG. **32** shows for illustrative purposes only an example of recommended swing parameters for multiple distances of one embodiment. FIG. **32** shows the ball marker **2202** with the display **3030**. The display **3030** is showing recommended swing parameters for multiple distances. Each recommendation includes distance, putt like, and aim factors as described in FIG. **31**. The recommendations include for example 56', 60', 30" left; 57', 61', 30" left; 58', 61', 30" left; 59', 65', 36" left; 60', 68', 43" left; 61', 68.5", 43" left; and 62', 69', 43" left.

[0240] The number of distances for which swing parameters are recommended can be a user **170** of FIG. **1** configurable parameter or may vary based on the topography of the green. In this way, user **170** of FIG. **1** can easily see if a change in the estimated distance will result in a significant change in the recommended shot. For example, if a significant break existed at 60 feet from the hole but not at 58 feet from the hole (as shown in FIG. **32** by the 11" difference between the recommended aim for 58' and 60'), the golfer could see the significant difference between recommended force/distance information and adjust his shot accordingly.

[0241] However, if the force/distance information changes linearly with the estimated distance, the user **170** of FIG. **1** need not be too concerned that following recommended information for the wrong distance will give undesirable results. In some embodiments, artificial intelligence server **110** of FIG. **1** can also provide recommended force and direction information for other distances around the estimated distance. For example, because the estimate is likely not to be perfectly

accurate, artificial intelligence server **110** of FIG. **1** can calculate recommended force and direction information for distances of 56, 57, 58, 60, 61, and 62 feet using the same determined angle. [0242] FIG. **33** shows for illustrative purposes only an example of generating recommended putt stroke parameters of one embodiment. FIG. **33** shows the machine **2800** receives, from a ball marker that is placed on a green, proximate to a ball lying on the green, in an orientation that defines a line between the ball marker and a hole in the green, an angle between the line defined by the orientation and true north **3310**. Receiving an indication of a distance between the ball and the hole **3320**. Submitting the angle and the indication of the distance to server system **3330**. Receiving, from the server system, recommended swing parameters for putting the ball into the hole, the recommended swing parameters being based on the angle, the distance, a known position of the hole, and the known topography of the green **3340** of one embodiment. [0243] The foregoing has described the principles, embodiments, and modes of operation of the present invention. However, the invention should not be construed as being limited to the particular embodiments discussed. The above-described embodiments should be regarded as illustrative rather than restrictive, and it should be appreciated that variations may be made in those embodiments by workers skilled in the art without departing from the scope of the present invention as defined by the following claims.

Claims

1. A system for providing interactive golf shot guidance of a golf ball to a user on a golf course, the system comprising: a remote server including a processor and a database, the database being configured to store golf course data comprising historical golf shot data of the user, shot data of other golfers, and data describing landmark features of the golf course; a location module configured to determine the current position of the user on the golf course; an interface with a microphone and speaker wirelessly coupled to the remote server configured to enable natural language dialogues with the user to receive user-reported environmental and experiential inputs, wherein the inputs are used by the remote server to create adaptive golf club selection and shot recommendation guidance customized to the user's situational context on the golf course; wherein the processor is configured to generate shot recommendations based on analytical golf data comprising the user's current location, the user's prior playing history, verbal feedback from the user, and situational context including landmark features of the golf course and golf shot likelihoods derived from the golf data; and wherein the processor is further configured to adaptively learn over multiple golf rounds by analyzing the user's verbal responses, golf shot outcomes, and deviations from prior suggestions in order to improve the accuracy of future shot recommendations.
2. The system for providing interactive golf shot guidance of a golf ball to a user on a golf course of claim 1, further comprising at least one of current ball lie conditions, wind presence imperceptible to mechanical sensors, ground irregularities, the user's personal shot history or physical limitations.
3. The system for providing interactive golf shot guidance of a golf ball to a user on a golf course of claim 1, wherein the processor is further configured to calculate a success probability for a given golf shot of the user based on the analytical golf data and the golf course data.
4. The system for providing interactive golf shot guidance of a golf ball to a user on a golf course of claim 1, wherein the shot recommendations include suggested club selection, aiming direction, and swing adjustment instructions based on the user's verbal description of a prior shot result.
5. The system for providing interactive golf shot guidance of a golf ball to a user on a golf course of claim 1, wherein the processor is further configured to use a reinforcement learning algorithm to refine shot recommendations over time based on the user's actual shot outcomes compared to predicted outcomes.

6. The system for providing interactive golf shot guidance of a golf ball to a user on a golf course of claim 1, wherein the user audio device includes a microphone and speaker integrated into augmented reality (AR) glasses.
7. The system for providing interactive golf shot guidance of a golf ball to a user on a golf course of claim 1, wherein the user audio device is further configured to provide audible prompts after a shot to obtain verbal self-assessment feedback from the user.
8. A system for providing interactive golf shot guidance of a golf ball to a user on a golf course, the system comprising: a remote server comprising a processor and a database, the database configured to store golf course data including historical golf shot data of the user, shot data associated with other amateur and professional golfers, and data characterizing physical and strategic features of the golf course; a location module communicatively coupled to the remote server and configured to determine the current geolocation of the user on the golf course; an interface with a microphone and speaker wirelessly coupled to the remote server configured to enable natural language dialogues with the user to receive user-reported environmental and experiential inputs, wherein the inputs are used by the remote server to create adaptive golf club selection and shot recommendation guidance customized to the user's situational context on the golf course; wherein the processor is configured to generate golf shot recommendations based on analytical golf data that includes the user's current geolocation, the user's prior golf shot history, verbal feedback received from the user, and contextual information derived from golf course features and shot outcome probabilities; and wherein the processor is further configured to adaptively improve future recommendations over multiple rounds of golf by analyzing the user's verbal responses, golf shot outcomes, and deviations from prior recommendations to iteratively refine predictive models associated with the user.
9. The system for providing interactive golf shot guidance of a golf ball to a user on a golf course of claim 8, further comprising at least one of current ball lie conditions, wind presence imperceptible to mechanical sensors, ground irregularities, the user's personal shot history or physical limitations.
10. The system for providing interactive golf shot guidance of a golf ball to a user on a golf course of claim 8, further comprising a wearable camera integrated into AR glasses including an augmented reality visual display that overlays suggested shot trajectories, hazards, and target areas in a field of view of the user.
11. The system for providing interactive golf shot guidance of a golf ball to a user on a golf course of claim 8, wherein the AR glasses include an optical rangefinder and project laser-calculated distances and hazard information onto a heads-up display visible to the user.
12. The system for providing interactive golf shot guidance of a golf ball to a user on a golf course of claim 8, further comprising wearable sensors configured to track vital signs of the user, wherein the user's vital signs are used to make the shot recommendations.
13. The system for providing interactive golf shot guidance of a golf ball to a user on a golf course of claim 8, further comprising at least one of current ball lie conditions, wind presence imperceptible to mechanical sensors, ground irregularities, the user's personal shot history or physical limitations.
14. The system for providing interactive golf shot guidance of a golf ball to a user on a golf course of claim 8, wherein the processor is further configured to generate a predicted ball trajectory and landing area based on the user's swing data and compare it to optimal target zones on the golf course.
15. A system for providing interactive, conversational golf shot guidance across an entire golf course hole, from tee to golf hole, the system comprising: a remote server comprising a processor and a database, the database configured to store user-specific golf shot history, contextual golf course data, and outcome-based shot analytics from prior amateur and professional play; a location module configured to continuously determine a current geolocation of a user throughout

progression on the golf course hole; an interface with a microphone and speaker wirelessly coupled to the remote server configured to enable natural language dialogues with the user to receive user-reported environmental and experiential inputs, wherein the inputs are used by the remote server to create adaptive golf club selection and shot recommendation guidance customized to the user's situational context on the golf course; wherein the processor is configured to conduct interactive natural language dialogue with the user throughout play of the golf hole, including receiving verbal user input regarding prior shot feedback and future shot intention, and providing predictive verbal guidance on shot selection, club choice, aiming strategy, and risk assessment based on golf course topology, user shot tendencies, and learned outcome data; and wherein the system is further configured to dynamically update and apply one or more machine learning models that correlate user verbal feedback, shot execution results, and deviations from recommended strategy, and to use those updated models to improve the quality and personalization of verbal guidance on subsequent holes and future rounds.

16. The system for providing interactive golf shot guidance of a golf ball to a user on a golf course of claim 15, further comprising at least one of current ball lie conditions, wind presence imperceptible to mechanical sensors, ground irregularities, the user's personal shot history or physical limitations.

17. The system for providing interactive golf shot guidance of a golf ball to a user on a golf course of claim 15, wherein the processor is further configured to calculate a success probability for a given golf shot of the user based on the analytical golf data and the golf course data.

18. The system for providing interactive golf shot guidance of a golf ball to a user on a golf course of claim 11, wherein the shot recommendations include suggested club selection, aiming direction, and swing adjustment instructions based on the user's verbal description of a prior shot result.

19. The system for providing interactive golf shot guidance of a golf ball to a user on a golf course of claim 11, wherein the processor is further configured to use a reinforcement learning algorithm to refine shot recommendations over time based on the user's actual shot outcomes compared to predicted outcomes.

20. The system for providing interactive golf shot guidance of a golf ball to a user on a golf course of claim 10, wherein the user audio device is further configured to provide audible prompts after a shot to obtain verbal self-assessment feedback from the user.
