

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250276455

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

ZHANG; Dongsheng et al.

ROBOT HIP JOINT, CONTROL METHOD AND APPARATUS, AND ROBOT

Abstract

A robot hip joint apparatus, method, and control apparatus providing enhanced mobility and control. The robot hip joint includes a support assembly, a drive assembly comprising first, second, and third drivers, and an execution assembly comprising first and second movable leg members and a movable waist member. The first and second movable leg members are separately and rotatably connected to the support assembly, with the first and second drivers configured to drive their respective leg members to rotate around a first axis. The method and control apparatus determine a motion mode of the robot hip joint, generate a control signal based on the motion mode, and transmit the control signal to the drive assembly to control the movement of the leg and waist members for coordinated robotic motion.

Inventors: ZHANG; Dongsheng (Shenzhen, CN), LI; Xiong (Shenzhen, CN), ZHANG; Yufeng (Shenzhen, CN), SHENG; Minhua (Shenzhen, CN), LI; Jingchen (Shenzhen, CN), ZHANG; Zhengyou (Shenzhen, CN)

Applicant: TENCENT TECHNOLOGY (SHENZHEN) COMPANY LIMITED (Shenzhen, CN)

Family ID: 93170553

Assignee: TENCENT TECHNOLOGY (SHENZHEN) COMPANY LIMITED (Shenzhen, CN)

Appl. No.: 19/208677

Filed: May 15, 2025

Foreign Application Priority Data

CN

202310478135.8

Apr. 26, 2023

Related U.S. Application Data

Publication Classification

Int. Cl.: B25J17/00 (20060101); B25J9/16 (20060101); B62D57/032 (20060101)

U.S. Cl.:

CPC B25J17/00 (20130101); B25J9/1664 (20130101); B62D57/032 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation application of International Application No. PCT/CN2023/131736 filed on Nov. 15, 2023 which claims priority to Chinese Patent Application No. 202310478135.8, filed with the China National Intellectual Property Administration on Apr. 26, 2023, the disclosures of each being incorporated by reference herein in their entireties.

FIELD

[0002] The disclosure relates to the field of robot technologies, a robot hip joint apparatus, a control method, and apparatus.

BACKGROUND

[0003] In the related art, a hip joint is one of key parts of a leg mechanism of a robot, is a connecting component of a leg component of the robot, and is also a support component of an upper body of the robot. In addition, driving elements with a plurality of degrees of freedom need to be integrated. The mechanical efficiency and the driving efficiency of the hip joint directly affect overall control and energy consumption of the robot.

[0004] Most of hip joints in the related art have a human-like degree-of-freedom deployment, mainly using a serial or parallel $\frac{3}{2}$ degree-of-freedom implementation form.

SUMMARY

[0005] Provided are a robot hip joint apparatus, a control method, and a control apparatus, which facilitate efficient and coordinated movement of robotic leg and waist components. These embodiments enable improved mobility, balance, and motion control in robotic systems through parallel axis configuration and integrated driver assemblies.

[0006] Some embodiments provide a robot hip joint apparatus, the apparatus comprising: a support assembly, a drive assembly comprising a first driver, a second driver, and a third driver; and an execution assembly comprising a first movable leg member, a second movable leg member, and a movable waist member; wherein the first movable leg member and the second movable leg member are separately and rotatably connected to the support assembly, the first driver is in a transmission connection to the first movable leg member and is configured to drive the first movable leg member to rotate around a first axis, and the second driver is configured to drive the second movable leg member to rotate around the first axis, wherein the movable waist member is rotatably connected to the support assembly, the third driver is in a transmission connection to the movable waist member, and the third driver is configured to drive the movable waist member to rotate about a second axis, and wherein the first axis is parallel to the second axis.

[0007] Some embodiments provide a control method, performed by a computer device, the method comprising: determining a motion mode of a robot hip joint; generating a control signal based on the motion mode; transmitting the control signal to a drive assembly of the robot hip joint; wherein the robot hip joint comprises: a support assembly, a drive assembly comprising a first driver, a

second driver, and a third driver; and an execution assembly comprising a first movable leg member, a second movable leg member, and a movable waist member; wherein the first movable leg member and the second movable leg member are separately and rotatably connected to the support assembly, the first driver is in a transmission connection to the first movable leg member and is configured to drive the first movable leg member to rotate around a first axis, and the second driver is configured to drive the second movable leg member to rotate around the first axis, wherein the movable waist member is rotatably connected to the support assembly, the third driver is in a transmission connection to the movable waist member, and the third driver is configured to drive the movable waist member to rotate about a second axis, and wherein the first axis is parallel to the second axis.

[0008] Some embodiments provide a control apparatus, comprising: at least one memory configured to store program code; and at least one processor configured to read the program code and operate as instructed by the program code, the program code comprising: determining code configured to cause at least one of the at least one processor to determine a motion mode of a robot hip joint; signal generation code configured to cause at least one of the at least one processor to generate a control signal based on the motion mode; and transmitting code configured to cause at least one of the at least one processor to transmit the control signal to a drive assembly of the robot hip joint, wherein the robot hip joint comprises: a support assembly, a drive assembly comprising a first driver, a second driver, and a third driver; and an execution assembly comprising a first movable leg member, a second movable leg member, and a movable waist member; wherein the first movable leg member and the second movable leg member are separately and rotatably connected to the support assembly, the first driver is in a transmission connection to the first movable leg member and is configured to drive the first movable leg member to rotate around a first axis, and the second driver is configured to drive the second movable leg member to rotate around the first axis, wherein the movable waist member is rotatably connected to the support assembly, the third driver is in a transmission connection to the movable waist member, and the third driver is configured to drive the movable waist member to rotate about a second axis, and wherein the first axis is parallel to the second axis.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] To describe the technical solutions of some embodiments of this disclosure more clearly, the following briefly introduces the accompanying drawings for describing some embodiments. The accompanying drawings in the following description show only some embodiments of the disclosure, and a person of ordinary skill in the art may still derive other drawings from these accompanying drawings without creative efforts. In addition, one of ordinary skill would understand that aspects of some embodiments may be combined together or implemented alone.

[0010] FIG. 1 is a schematic structural diagram of a robot hip joint according to some embodiments.

[0011] FIG. 2 is a front view of a structure of a robot hip joint according to some embodiments.

[0012] FIG. 3 is a schematic structural diagram of a robot hip joint according to some embodiments.

[0013] FIG. 4 is a diagram of a status of a connection between a robot hip joint and a leg component according to some embodiments.

[0014] FIG. 5 is an exploded view of a structure of a robot hip joint according to some embodiments.

[0015] FIG. 6 is a schematic structural diagram of a support assembly according to some embodiments.

[0016] FIG. 7 is an exploded view of a structure of a support assembly according to some embodiments.

[0017] FIG. 8 is a schematic structural diagram of a support assembly from another perspective according to some embodiments.

[0018] FIG. 9 is a schematic flowchart of a control method according to some embodiments.

[0019] FIG. 10 is a schematic structural diagram of a control apparatus according to some embodiments.

[0020] FIG. 11 is a block diagram of a computer device according to some embodiments.

DESCRIPTION OF EMBODIMENTS

[0021] To make the objectives, technical solutions, and advantages of the present disclosure clearer, the following further describes the present disclosure in detail with reference to the accompanying drawings. The described embodiments are not to be construed as a limitation to the present disclosure. All other embodiments obtained by a person of ordinary skill in the art without creative efforts shall fall within the protection scope of the present disclosure.

[0022] In the following descriptions, related “some embodiments” describe a subset of all possible embodiments. However, it may be understood that the “some embodiments” may be the same subset or different subsets of all the possible embodiments, and may be combined with each other without conflict. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include all possible combinations of the items enumerated together in a corresponding one of the phrases. For example, the phrase “at least one of A, B, and C” includes within its scope “only A”, “only B”, “only C”, “A and B”, “B and C”, “A and C” and “all of A, B, and C.”

[0023] In some embodiments, an orientation or positional relationship indicated by the term “center”, “longitudinal”, “transverse”, “length”, “width”, “thickness”, “above”, “beneath”, “front”, “back”, “left”, “right”, “vertical”, “horizontal”, “top”, “bottom”, “internal”, “external”, “clockwise”, “counterclockwise”, “axial direction”, “radial direction”, “circumferential direction”, or the like is based on an orientation or positional relationship shown in FIG. 1, and is merely for ease of describing some embodiments and simplifying the descriptions, but does not indicate or imply that an apparatus or an element referred to have an orientation or be constructed and operated in a orientation, and therefore cannot be understood as a limitation on some embodiments.

[0024] Unless otherwise indicated, all technical terms used herein have the same meaning as those commonly understood by a person of ordinary skill in the art.

[0025] With continuous development and evolution of robots, types and functions of the robots continuously expand, and the robot and a leg structure of the robot also develop in various manners. A degree-of-freedom deployment and a transmission manner of a human-like hip cannot be completely applicable to a use scenario, for example, climbing stairs.

[0026] Therefore, some embodiments provides a robot hip joint, so that a leg action and a waist action of a robot can be driven. A structure is more compact, and can be applicable to a use scenario, for example, climbing stairs.

[0027] The robot hip joint provided in some embodiments may be applied to a robot scenario in fields such as cloud technologies, artificial intelligence, and intelligent transportation, and may be implemented in a scenario, such as performing a human-computer interaction and serving people's daily life by using a robot.

[0028] Artificial intelligence (AI) is a theory, a method, a technology, and an application system that use a digital computer or a machine controlled by a digital computer to simulate, extend, and expand human intelligence, perceive an environment, obtain knowledge, and use the knowledge to obtain an optimal result. In other words, the artificial intelligence is a comprehensive technology in computer science and attempts to understand the essence of intelligence and produce a new intelligent machine that can react in a manner similar to human intelligence. The artificial intelligence is to study the design principles and implementation methods of various intelligent

machines, to enable the machines to have the functions of perception, reasoning, and decision-making.

[0029] The artificial intelligence technology is a comprehensive discipline, and relates to a wide range of fields including both hardware-level technologies and software-level technologies. Basic artificial intelligence technologies generally include a sensor, a dedicated artificial intelligence chip, cloud computing, distributed storage, a big data processing technology, a pre-trained model technology, an operating/interaction system, electromechanical integration, and the like. The pre-trained model is also referred to as a large model or a basic model, and may be widely applied to downstream tasks in various directions of the artificial intelligence after being fine-tuned. Artificial intelligence software technologies mainly include several major directions such as a computer vision (CV) technology, a speech processing technology, a natural language processing technology, and machine learning/deep learning.

[0030] An intelligent traffic system (ITS) applied to the intelligent transportation field is also referred to as an intelligent transportation system, and is a comprehensive transportation system that effectively and comprehensively applies advanced science and technologies (an information technology, a computer technology, a data communication technology, a sensor technology, an electronic control technology, an automatic control theory, operations research, artificial intelligence, and the like) to transportation, service control, and vehicle manufacturing, and that enhances a connection between a vehicle, a road, and a user, to ensure safety, increase the efficiency, improve an environment, and save energy.

[0031] In an aspect, with reference to FIG. 1 and FIG. 2, this embodiment provides a robot hip joint, the robot hip joint including: a support assembly **1**, a drive assembly **2**, and an execution assembly **3**, the drive assembly **2** including a first driver **21**, a second driver **22**, and a third driver **23**, and the execution assembly **3** including a first movable leg member **31**, a second movable leg member **32**, and a movable waist member **33**; the first movable leg member **31** and the second movable leg member **32** being separately and rotatably connected to the support assembly **1**, the first driver **21** being in a transmission connection to the first movable leg member **31**, the first driver **21** being configured to drive the first movable leg member **31** to rotate around a first axis **001**, and the second driver **22** being configured to drive the second movable leg member **32** to rotate around the first axis **001**; the movable waist member **33** being rotatably connected to the support assembly **1**, the third driver **23** being in a transmission connection to the movable waist member **33**, and the third driver **23** being configured to drive the movable waist member **33** to rotate about a second axis **002**; and the first axis **001** being parallel to the second axis **002**.

[0032] Based on the robot hip joint in this embodiment, the first movable leg member **31** and the second movable leg member **32** can be respectively driven by the first driver **21** and the second driver **22** to rotate about the first axis **001**, to drive a leg action of a robot. A rotation degree of freedom of the first movable leg member **31** and a rotation degree of freedom of the second movable leg member **32** are coaxially set. The movable waist member **33** is driven by the third driver **23** to rotate about the second axis **002**, to drive a waist action of the robot. The first axis **001** and the second axis **002** are disposed in parallel. The structure of the robot hip joint is more compact, and is more applicable to a use scenario, for example, climbing stairs.

[0033] Rotation axes of the first movable leg member **31** and the second movable leg member **32** are disposed in a coinciding manner, so that the compactness of the structure of the robot hip joint can be improved. When the first movable leg member **31** and the second movable leg member **32** rotate, the robot has better balance and flexibility, thereby facilitating saving layout space of the support assembly **1**, reducing an entire size of the support assembly **1**, and further reducing a volume of the entire robot hip joint.

[0034] Besides meeting respective rotation degrees of freedom of the first movable leg member **31**, the second movable leg member **32**, and the movable waist member **33** in this embodiment, a degree of freedom in another direction may further be set depending on an actual requirement. For

example, a degree of freedom in another rotation direction is set in series, to implement a degree of freedom in which the movable waist member **33** has a universal secondary form, so that the robot hip joint not only has a capability to pitch forward and backward, but also has a capability to swing left and right. Similarly, a degree of freedom in a vertical direction may continue to be set in series above the robot hip joint, so that an upper body of the robot has at least three degrees of freedom on the movable waist member **33**.

[0035] For example, each of the first driver **21**, the second driver **22**, and the third driver **23** is a motor, is driven by electric power, has a built-in decelerator module, and can output driving torque that meets predetermined torque or a predetermined rotation speed.

[0036] In one embodiment, a rated power of the first driver **21** is the same as that of the second driver **22**, so that the first movable leg member **31** and the second movable leg member **32** have the same dynamic feature, and can perform independent and coordinated rotational motion, thereby driving the entire robot to perform actions such as going forward, going backward, climbing upward, and climbing downward.

[0037] In some possible implementations, when the robot hip joint in some embodiments is applied to a robot scenario, the second axis **002** is located above the first axis **001** (with reference to an orientation shown in FIG. 1), for example, the movable waist member **33** is located above the first movable leg member **31** or the second movable leg member **32**, so that a structure in a front-rear direction of the robot hip joint is compact. When the first movable leg member **31** and the second movable leg member **32** are located below the movable waist member **33** for support, there is a better force-bearing layout, thereby facilitating improving the force-bearing stability of the robot.

[0038] With reference to FIG. 3, in some embodiments, one of the first movable leg member **31** and the second movable leg member **32** includes a rotating shaft member **311**, the rotating shaft member **311** is rotatably located on the support assembly **1** along the first axis **001**, and an axis of the rotating shaft member **311** coincides with the first axis **001**.

[0039] The other one of the first movable leg member **31** and the second movable leg member **32** includes a shaft sleeve member **321**, the shaft sleeve member **321** is sleeved on the rotating shaft member **311**, an inner axis surface of the shaft sleeve member **321** is connected to an outer peripheral surface of the rotating shaft member **311**, and an axis of the shaft sleeve member **321** coincides with both the rotating shaft member **311** and the first axis **001**. The rotating shaft member **311** and the shaft sleeve member **321** can separately rotate about the first axis **001**.

[0040] The first movable leg member **31** and the second movable leg member **32** in this embodiment are rotatably connected to the support assembly **1** along the same axis by using the rotating shaft member **311** and the shaft sleeve member **321**. The rotating shaft member **311** is directly and rotatably connected to the support assembly **1**, and the shaft sleeve member **321** is indirectly and rotatably connected to the support assembly **1**. When a status of a connection between the shaft sleeve member **321** and the support assembly **1** is analyzed, the rotating shaft member **311** may be considered as a part of the support assembly **1**.

[0041] For example, the rotating shaft member **311** is a part of the first movable leg member **31**, and the shaft sleeve member **321** is a part of the second movable leg member **32**. The rotating shaft member **311** is a part of the second movable leg member **32**, and the shaft sleeve member **321** is a part of the first movable leg member **31**.

[0042] In some possible implementations, the rotating shaft member **311** is rotatably connected to the support assembly **1** by using a bearing member. The shaft sleeve member **321** is rotatably connected to the rotating shaft member **311** by using the bearing member.

[0043] With reference to FIG. 2, FIG. 3, and FIG. 4, in some embodiments, the first movable leg member **31** further includes a first connecting plate **312**, the first connecting plate **312** is connected to the rotating shaft member **311**, and the first connecting plate **312** rotates with the rotating shaft member **311** about the first axis **001**.

[0044] The second movable leg member **32** further includes a second connecting plate **322**, the

second connecting plate **322** is connected to the shaft sleeve member **321**, and the second connecting plate **322** rotates with the shaft sleeve member **321** about the first axis **001**.

[0045] The first connecting plate **312** and the second connecting plate **322** are respectively used for connecting different leg components **4**, and are used for respectively driving the different leg components **4** to rotate about the first axis **001**.

[0046] Based on that a coaxial rotational connection between the first movable leg member **31** and the second movable leg member **32** is implemented by using the rotating shaft member **311** and the shaft sleeve member **321**, the first connecting plate **312** is connected to the rotating shaft member **311**, so that the leg component **4** can be connected to the rotating shaft member **311**. When the rotating shaft member **311** rotates about the first axis **001**, the leg component **4** can be driven to act, to implement an action such as taking a step or raising a leg. The second connecting plate **322** is connected to the shaft sleeve member **321**, to connect the another leg component **4** to the shaft sleeve member **321**. When the shaft sleeve member **321** rotates about the first axis **001**, the leg component **4** can be driven to act, to implement an action such as taking a step or raising a leg.

[0047] In some possible implementations, with reference to FIG. **4**, the leg component **4** includes a first leg component **41** and a second leg component **42**. The first leg component **41** is connected to the first connecting plate **312**. When the rotating shaft member **311** rotates about the first axis **001**, the first leg component **41** can be driven to implement an action such as taking a step or raising a leg. The second leg component **42** is connected to the second connecting plate **322**. When the shaft sleeve member **321** rotates about the first axis **001**, the second leg component **42** can be driven to implement an action such as taking a step or raising a leg.

[0048] With reference to FIG. **3**, in some embodiments, the rotating shaft member **311** is in a transmission connection to the first driver **21**, and the shaft sleeve member **321** is in a transmission connection to the second driver **22**.

[0049] In this embodiment, the rotating shaft member **311** is in a transmission connection to the first driver **21**, and the first driver **21** can be configured to drive the rotating shaft member **311** to rotate about the first axis **001** relative to the support assembly **1**. The shaft sleeve member **321** is in a transmission connection to the second driver **22**, and the second driver **22** can be configured to drive the shaft sleeve member **321** to rotate about the first axis **001** relative to at least one of the support assembly **1** and the rotating shaft member **311**, thereby implementing independent actions of the first movable leg member **31** and the second movable leg member **32**. For example, when the first driver **21** and the second driver **22** alternately drive the rotating shaft member **311** and the shaft sleeve member **321**, the first movable leg member **31** and the second movable leg member **32** can perform an action such as alternately taking a step or alternately raising a leg.

[0050] With reference to FIG. **5**, in some embodiments, a quantity of first connecting plates **312** is two, and a quantity of shaft sleeve members **321** is two. Two ends of the rotating shaft member **311** respectively protrude to an outer side of the support assembly **1**, the two first connecting plates **312** are respectively located at the two ends of the rotating shaft member **311**, and the two shaft sleeve members **321** are respectively located at positions of the rotating shaft member **311** that are close to the two ends.

[0051] The second connecting plate **322** extends along a direction of the first axis **001**, and is separately connected to the two shaft sleeve members **321**.

[0052] The first movable leg member **31** can be connected to at least two leg components **4** by using the two first connecting plates **312** disposed at the two ends of the rotating shaft member **311**. The at least two leg components **4** are disposed at an interval, thereby facilitating providing stable support for the robot.

[0053] The second movable leg member **32** can be rotatably connected to the rotating shaft member **311** stably and reliably by using the two shaft sleeve members **321** disposed close to the two ends of the rotating shaft member **311**. The second connecting plate **322** extends in the direction of the first axis **001** and is connected to the two shaft sleeve members **321**, so that it may

be ensured that the second connecting plate **322** can reliably and stably rotate about the first axis **001**, thereby driving the leg component **4** connected to the second connecting plate **322** to stably and reliably act.

[0054] In some possible implementations, with reference to FIG. 4, a quantity of first leg components **41** is two. The two first leg components **41** are respectively located at the two ends of the rotating shaft member **311**, and are connected to the rotating shaft member **311** by using the first connecting plate **312**, so that the rotating shaft member **311** can be driven by using the first driver **21** to rotate. The rotating shaft member **311** drives the first connecting plate **312** to rotate, and the first connecting plate **312** drives the first leg component **41** to rotate about the first axis **001**.

[0055] In some other possible implementations, with reference to FIG. 4, a quantity of second leg components **42** is two. The two second leg components **42** are respectively located at two ends of the second connecting plate **322**, and are connected to the two shaft sleeve members **321** by using the second connecting plate **322**, so that the shaft sleeve members **321** can be driven by using the second driver **22** to rotate. The shaft sleeve members **321** drive the second connecting plate **322** to rotate, and the second connecting plate **322** drives the second leg component **42** to rotate about the first axis **001**.

[0056] For example, the two first leg components **41** and the two second leg components **42** are disposed in a sequence of the first leg component **41**-the second leg component **42**-the second leg component **42**-the first leg component **41** along the direction of the first axis **001**, to form a reliable and stable four-leg support structure, thereby implementing stable support for the robot hip joint and the robot.

[0057] When the first driver **21** and the second driver **22** are alternately started, the two first leg components **41** on an outer side and the two second leg components **42** on an inner side alternately act, thereby implementing an action of the robot, for example, going forward, going backward, or climbing.

[0058] Another degree-of-freedom driving mechanism may be further disposed between the first connecting plate and the first leg component **41**, for example, driving autorotation of the first leg component **41**.

[0059] Another degree-of-freedom driving mechanism may be disposed between the second connection plate and the second leg component **42**, for example, driving autorotation of the second leg component **42**.

[0060] In some possible implementations, a structure, for example, a jacket, is disposed on an axis segment of the rotating shaft member **311** that is not covered by the shaft sleeve member **321**. In this way, the structure has a function of preventing the rotating shaft member **311** from moving axially. In addition, the structure has an internal and external protection function, thereby improving the working reliability of the robot hip joint in this embodiment.

[0061] With reference to FIG. 2, in some embodiments, the first driver **21** and the second driver **22** are located on the support assembly **1** along a third axis **003**, and the third axis **003** is parallel to the first axis **001**. The third driver **23** is located on the support assembly **1** along the second axis **002**.

[0062] The first driver **21** and the second driver **22** are disposed along the third axis **003** parallel to the first axis **001**, thereby facilitating improving the compactness and balance of the structure of the robot hip joint in this embodiment. The first driver **21** and the second driver **22** perform power transmission on the rotating shaft member **311** and the shaft sleeve member **321** at a position parallel to the first axis **001**, thereby facilitating simplifying a transmission mechanism **5**, increasing the transmission efficiency, and improving the working reliability of the first movable leg member **31** and the second movable leg member **32**.

[0063] The third driver **23** and the movable waist member **33** are coaxially disposed, so that the compactness of an upper structure of the robot hip joint can be improved.

[0064] In some possible implementations, the first driver **21** and the second driver **22** are

symmetrically disposed along a central plane of the support assembly **1**. The central plane of the support assembly **1** is a plane that is separately perpendicular to the first axis **001**, the second axis **002**, and the third axis **003**, and that passes through midpoints of the first axis **001**, the second axis **002**, and the third axis **003**, and may be considered as a plane in which a center of gravity of the robot hip joint is located. The first driver **21** and the second driver **22** are symmetrically disposed along the plane, so that balance of the robot hip joint can be greatly improved, and working performance of the robot hip joint can be improved.

[0065] With reference to FIG. 3, in some embodiments, a transmission mechanism **5** is disposed between the first driver **21** and the first movable leg member **31**, and a transmission mechanism **5** is disposed between the second driver **22** and the second movable leg member **32**.

[0066] The transmission mechanism **5** is at least one of a meshing transmission mechanism, a belt transmission mechanism, and a chain transmission mechanism.

[0067] By means of the transmission mechanism **5**, power transmission between the first driver **21** and the first movable leg member **31** (for example, the rotating shaft member **311**) can be implemented, and power transmission between the second driver **22** and the second movable leg member **32** (for example, the shaft sleeve member **321**) can be implemented. Actions of the two movable leg members are independently driven and independently transmitted, thereby presenting better reliability and stability.

[0068] In some possible implementations, with reference to FIG. 3, output shafts of the first driver **21** and the second driver **22** respectively face an outer side of the support assembly **1**, for example, the first driver **21** and the second driver **22** are disposed back to back. The output shaft of the first driver **21** extends in a direction away from the second driver **22**, and the output shaft of the second driver **22** extends in a direction away from the first driver **21**. Therefore, the output shaft of the first driver **21** and the output shaft of the second driver **22** are respectively located on two opposite sides of the support assembly **1** along the third axis **003**.

[0069] The output shaft of the first driver **21** is in a transmission connection to the rotating shaft member **311** on one side of the support assembly **1**. The output shaft of the second driver **22** is in a transmission connection to the rotating shaft member **311** on the other side of the support assembly **1**. The two transmission mechanisms **5** are respectively located on the two sides of the support assembly **1** and can perform power transmission without interfering with each other, thereby facilitating simplifying a design and assembly difficulty of the transmission mechanism **5**. In addition, the two transmission mechanisms **5** are respectively located on the two sides of the support assembly **1**, thereby further facilitating improving balance of the robot hip joint.

[0070] With reference to FIG. 3 and FIG. 5, in some embodiments, the transmission mechanism **5** includes a first gear member **51** and a second gear member **52**, the first gear member **51** is connected to the output shaft of the first driver **21** or the second driver **22**, the second gear member **52** is connected to the first movable leg member **31** and the second movable leg member **32**, and the first gear member **51** is in a meshing connection to the second gear member **52**.

[0071] By means of a meshing connection between the first gear member **51** and the second gear member **52**, a transmission connection between the first driver **21** and the rotating shaft member **311** or the shaft sleeve member **321**, and a transmission connection between the second driver **22** and the rotating shaft member **311** or the shaft sleeve member **321** are implemented, which has advantages such as a compact structure, high transmission precision, high transmission efficiency, and high reliability.

[0072] With reference to FIG. 6, FIG. 7, and FIG. 8, in some embodiments, the support assembly **1** includes a first mechanical part **11**, a second mechanical part **12**, and a third mechanical part **13**.

[0073] The first mechanical part **11** and the second mechanical part **12** are disposed at an interval along an axis direction of the first axis **001** or the second axis **002**, and are respectively located on two sides of the third mechanical part **13**.

[0074] A first shaft sleeve portion **111** is disposed at a position at which the first mechanical part **11**

intersects the first axis **001**, a second shaft sleeve portion **121** is disposed at a position at which the second mechanical part **12** intersects the first axis **001**, and the first shaft sleeve portion **111** and the second shaft sleeve portion **121** are used for being rotatably connected to at least one of the first movable leg member **31** and the second movable leg member **32**.

[0075] A third shaft sleeve portion **112** is disposed at a position at which the first mechanical part **11** intersects the second axis **002**, a fourth shaft sleeve portion **122** is disposed at a position at which the second mechanical part **12** intersects the second axis **002**, and the third shaft sleeve portion **112** and the fourth shaft sleeve portion **122** are used for being rotatably connected to the movable waist member **33**.

[0076] In the support assembly **1** in this embodiment, the first mechanical part **11** and the second mechanical part **12** are respectively symmetrically disposed on the two sides of the third mechanical part **13**, so that the support assembly **1** has better structural balance.

[0077] The first shaft sleeve portion **111** and the second shaft sleeve portion **121** can provide stable and reliable double-point support for at least one of the first movable leg member **31** and the second movable leg member **32**, to ensure that the first movable leg member **31** and the second movable leg member **32** can stably and reliably rotate about the first axis **001**.

[0078] The third shaft sleeve portion **112** and the fourth shaft sleeve portion **122** can provide stable and reliable double-point support for the movable waist member **33**, to ensure that the movable waist member **33** can stably and reliably rotate about the first axis **001**.

[0079] For example, the first shaft sleeve portion **111** and the second shaft sleeve portion **121** are used for supporting the rotating shaft member **311**, and the two ends of the rotating shaft member **311** respectively extend and protrude to an outer side of the first shaft sleeve portion **111** and an outer side of the second shaft sleeve portion **121**. One of the two shaft sleeve members **321** is located on the outer side of the first shaft sleeve portion **111**, and the other shaft sleeve member **321** is located on the outer side of the second shaft sleeve portion **121**. After the two shaft sleeve members **321** are connected by using the second connecting plate **322**, the first shaft sleeve portion **111** and the second shaft sleeve portion **121** can provide an axial limit, to ensure that the second movable leg member **32** does not move axially.

[0080] In some other possible implementations, with reference to FIG. 5, a second gear used as a follower in the transmission mechanism **5** is sleeved on an inner side of an end portion of the rotating shaft member **311**, to implement a power connection between the rotating shaft member **311** and the first driver **21** or the second driver **22**. The second gear is located on an axial side of the shaft sleeve member **321**, to implement a power connection between the shaft sleeve member **321** and the first driver **21** or the second driver **22**.

[0081] In some other possible implementations, the first mechanical part **11**, the second mechanical part **12**, and the third mechanical part **13** are of assembled structures. For example, after being separately manufactured, the three mechanical parts are detachably or undetachably combined together in a manner such as a soldering connection or a fastener connection, to form a stable and reliable integral structure. In this way, it is beneficial to reducing processing difficulty of the support assembly **1**, reducing production costs of the support assembly **1**, reducing the mass of the support assembly **1**, and improving the portability of the robot hip joint.

[0082] With reference to FIG. 6 and FIG. 7, in some embodiments, a first assembly portion **113** is disposed at a position at which the first mechanical part **11** intersects the third axis **003**, and a second assembly portion **123** is disposed at a position at which the second mechanical part **12** intersects the third axis **003**. The first assembly portion **113** is configured to be connected to the second driver **22**, and the second assembly portion **123** is configured to be connected to the first driver **21**.

[0083] The first driver **21** and the second driver **22** can be stably and reliably connected to the support assembly **1** by using the first assembly portion **113** and the second assembly portion **123**.

[0084] With reference to FIG. 6 and FIG. 7, in some embodiments, the first shaft sleeve portion

111, the third shaft sleeve portion **112**, and the first assembly portion **113** are triangularly located on the first mechanical part **11**. The second shaft sleeve portion **121**, the fourth shaft sleeve portion **122**, and the second assembly portion **123** are triangularly located on the second mechanical part **12**.

[0085] Therefore, the support assembly **1** in this embodiment has advantages such as a compact layout, good stability, and high structural strength, so that the reliability of the robot hip joint may be ensured.

[0086] With reference to FIG. **6**, FIG. **7**, and FIG. **8**, in some embodiments, the third mechanical part **13** includes at least one frame body **131**. The at least one frame body **131** is connected between the first mechanical part **11** and the second mechanical part **12**, and the at least one frame body **131** avoids the first axis **001**, the second axis **002**, and the third axis **003**.

[0087] The at least one frame body **131** is used as the third mechanical part **13**. In this way, it is beneficial to avoid the first axis **001**, the second axis **002**, and the third axis **003**, to further avoid the structures such as the rotating shaft member **311**, the movable waist member **33**, and the driver that are disposed along the three axes, thereby improving utilization of internal space of the support assembly **1**. In addition, it is beneficial to reduce the mass of the support assembly **1**.

[0088] With reference to FIG. **6**, FIG. **7**, and FIG. **8**, in some embodiments, the at least one frame body **131** includes an arc-shaped frame body **1311** and a cylindrical frame body **1312**, and the arc-shaped frame body **1311** and the cylindrical frame body **1312** are separately connected between the first mechanical part **11** and the second mechanical part **12**. The arc-shaped frame body **1311** is disposed in an edge region of the support assembly **1**, and the cylindrical frame body **1312** is disposed in a middle portion of the support assembly **1**. The arc-shaped frame body **1311** can not only perform a support function, but also serve as isolation protection for an internal structure of the support assembly **1**. The cylindrical frame body **1312** is disposed inside and performs reliable support along a direction parallel to the first axis **001**.

[0089] For example, shapes of the cylindrical frame body **1312** include, but are not limited to, a cylindrical shape, a prismatic shape, and the like. Further, the cylindrical frame body **1312** is prism-shaped, and may properly be selected according to the inner space of the support assembly **1**, for example, is triangular prism-shaped or quadrangular prism-shaped.

[0090] In some embodiments, the robot hip joint further includes at least one rotary encoder. The at least one rotary encoder is connected to the first movable leg member **31**, the second movable leg member **32**, or the movable waist member **33**, and is configured to detect and feed back a rotation angle of the first movable leg member **31**, the second movable leg member **32**, or the movable waist member **33**.

[0091] The rotary encoder can measure a rotation speed of a rotating shaft of the movable leg member, and by means of photoelectric conversion, can convert mechanical quantities such as an angular displacement and an angular velocity of the rotating shaft into corresponding electric impulses that are outputted as digital quantities.

[0092] For example, the rotary encoder includes, but is not limited to, a voltage output, an open collector output, a push-pull complementary output, a long-line driver output, and the like.

[0093] In the robot hip joint in this embodiment, the rotary encoder is disposed at the first movable leg member **31**, the second movable leg member **32**, or the movable waist member **33**, so that the rotation angle of the first movable leg member **31**, the second movable leg member **32**, or the movable waist member **33** can be detected and fed back in real time, to ensure that the first movable leg member **31**, the second movable leg member **32**, or the movable waist member **33** of the robot hip joint accurately and reliably rotate to a target position, thereby improving working precision of the robot hip joint.

[0094] In some embodiments, the robot hip joint further includes at least one torque sensor. The at least one torque sensor is connected to the first movable leg member **31**, the second movable leg member **32**, or the movable waist member **33**, and is configured to detect and feed back torque of

the first movable leg member **31**, the second movable leg member **32**, or the movable waist member **33**.

[0095] In the robot hip joint in this embodiment, the torque sensor is disposed at the first movable leg member **31**, the second movable leg member **32**, or the movable waist member **33**, so that working torque of the first movable leg member **31**, the second movable leg member **32**, or the movable waist member **33** can be detected and fed back in real time, to ensure that the first movable leg member **31**, the second movable leg member **32**, or the movable waist member **33** of the robot hip joint accurately and reliably outputs the corresponding working torque, thereby improving working safety and reliability of the robot hip joint.

[0096] According to another aspect, with reference to FIG. **4**, some embodiments provides a robot, the robot including: the robot hip joint provided herein.

[0097] The robot in this embodiment uses the robot hip joint provided herein, and has all beneficial technical effects of all the embodiments in this specification.

[0098] According to another aspect, with reference to FIG. **9**, some embodiments provides a control method, the control method being used for controlling the robot hip joint herein, and the control method including the following operations:

[0099] Operation **S1**: Determine a motion mode of the robot hip joint.

[0100] The motion mode of the robot hip joint includes, but is not limited to: a mode in which a first movable leg member **31** and a second movable leg member **32** stand close, a mode in which the first movable leg member **31** and the second movable leg member **32** stand crosswise, a mode in which the first movable leg member **31** and the second movable leg member **32** travel in a crossed gait, a mode in which a movable waist member **33** pitches and moves, and the like.

[0101] For example, when the motion mode is a mode of travelling in a crossed gait, when moving on a non-flat ground, the robot to which the robot hip joint is applied may travel in a crossed gait by using two movable leg members, and the two movable leg members alternately travel.

[0102] Operation **S2**: Generate a control signal based on the motion mode.

[0103] In some possible implementations, the control signal includes a first control signal corresponding to a first driver **21**, a second control signal corresponding to a second driver **22**, and a third control signal corresponding to a third driver **23**.

[0104] The first control signal is used for controlling the first driver **21**, the second control signal is used for controlling the second driver **22**, and the third control signal is used for controlling the third driver **23**. The first control signal, the second control signal, and the third control signal respectively include, but are not limited to, a rotation angle instruction, a rotation speed instruction, a rotation torque instruction, and the like.

[0105] Operation **S3**: Transmit the control signal to a drive assembly **2** of the robot hip joint.

[0106] For example, when the motion mode is the mode of travelling in a crossed gait, in an initial state, the first movable leg member **31** and the second movable leg member **32** stand crosswise or close. The second movable leg member **32** is used as support, and a bottom-layer drive board of the first driver **21** first controls, based on the received first control signal, the first driver **21** to rotate, to drive the first movable leg member **31** to rotate about a first axis **001** to move to a next position. After that, the first movable leg member **31** is then used as support, and a bottom-layer drive board of the second driver **22** controls, based on the received second control signal, the second driver **22** to rotate, to drive the second movable leg member **32** to rotate about the first axis **001** to move to a next position. The first driver **21** and the second driver **22** alternately receive the control signal, and the first movable leg member **31** and the second movable leg member **32** alternately move, so that the robot to which the robot hip joint is applied implements travelling in a crossed gait.

[0107] For another example, when the motion mode is a pitch mode, a bottom-layer drive board of the third driver **23** controls, based on the received third control signal, the third driver **23** to rotate, to drive the movable waist member **33** to rotate about a second axis **001**, so that a pitch angle of the robot to which the robot hip joint is applied is adjusted.

[0108] According to another aspect, with reference to FIG. **10**, some embodiments provides a control apparatus, the control apparatus being configured to control the robot hip joint herein, and the control apparatus including: a determining module **6**, configured to determine a motion mode of the robot hip joint; a signal generation module **7**, configured to generate a control signal based on the motion mode; and a transmit module **8**, configured to transmit the control signal to a drive assembly **2** of the robot hip joint.

[0109] The control apparatus in this embodiment can generate different control signals based on different motion modes, to control the drive assembly to work based on different control parameters, to drive an execution assembly to complete different motions, so that the robot to which the robot hip joint is applied implements different motions.

[0110] FIG. **11** is a structural block diagram of a computer device according to some embodiments.

[0111] The computer device may be a portable mobile terminal, such as a computer device, a smartphone, a tablet computer, an Moving Picture Experts Group Audio Layer 3 (MP3) player, a Moving Picture Experts Group Audio Layer 4 (MP4) player, a notebook computer, or a desktop computer that are configured to control a robot hip joint or a robot to which a robot hip joint is applied. The computer device may further be referred to as another name such as user equipment, a portable terminal, a laptop terminal, or a desktop terminal. In some embodiments, the computer device may be implemented as a control device part in the robot.

[0112] Generally, the computer device includes a processor **901** and a memory **902**.

[0113] The processor **901** may include one or more processing cores, such as a four-core processor or an eight-core processor. The processor **901** may be implemented in at least one hardware form of a digital signal processor (DSP), a field-programmable gate array (FPGA), and a programmable logic array (PLA). The processor **901** may include a main processor and a coprocessor. The main processor is configured to process data in an active state, and is referred to as a central processing unit (CPU). The coprocessor is a low-power processor configured to process data in a standby state.

[0114] The memory **902** may include one or more computer-readable storage media. The computer-readable storage medium may be non-transient. The memory **902** may further include a high-speed random access memory and a non-volatile memory, for example, one or more disk storage devices or flash storage devices. In some embodiments, a non-transitory computer-readable storage medium in the memory **902** is configured to store at least one instruction, and the at least one instruction is used for being executed by the processor **901**, to implement the control method provided herein.

[0115] In some embodiments, the computer device further includes: a peripheral device interface **903** and at least one peripheral device. The processor **901**, the memory **902**, and the peripheral device interface **903** may be connected by using a bus or a signal cable. Each peripheral device may be connected to the peripheral device interface **903** by using a bus, a signal cable, or a circuit board. Specifically, the peripheral device includes at least one of a radio frequency circuit **904**, a camera assembly **906**, an audio circuit **907**, a positioning assembly **908**, and a power supply **909**.

[0116] The peripheral device interface **903** may be configured to connect the at least one peripheral device related to input/output (I/O) to the processor **901** and the memory **902**. In some embodiments, the processor **901**, the memory **902**, and the peripheral device interface **903** are integrated on the same chip or circuit board. In some other embodiments, any or both of the processor **901**, the memory **902**, and the peripheral device interface **903** may be implemented on an independent chip or circuit board. This is not limited in the embodiments.

[0117] The radio frequency circuit **904** is configured to receive and transmit a radio frequency signal, also referred to as an electromagnetic signal. The radio frequency circuit **904** communicates with a communication network and other communication devices by using the electromagnetic signal. The radio frequency circuit **904** converts an electrical signal into an electromagnetic signal for transmission, or converts a received electromagnetic signal into an electrical signal. In one

embodiments, the radio frequency circuit **904** includes: an antenna system, a radio frequency transceiver, one or more amplifiers, a tuner, an oscillator, a digital signal processor, a codec chipset, a user identity module card, and the like. The radio frequency circuit **904** may communicate with other terminals through at least one wireless communication protocol. The wireless communication protocol includes, but is not limited to, at least one of a worldwide web, a metropolitan area network, an intranet, generations of mobile communication networks (2G, 3G, 4G, and 5G), a wireless local area network, and/or a wireless fidelity (Wi-Fi) network. In some embodiments, the radio frequency circuit **904** may further include a circuit related to near field communication (NFC). This is not limited in some embodiments.

[0118] The camera assembly **906** is configured to collect images or videos. In one embodiment, the camera assembly **906** includes a main camera, a depth of field camera, a wide-angle camera, a long-focus camera, and the like, and may implement visual detection on an external environment, so that the robot can perform visual detection by using a computer vision technology.

[0119] The audio circuit **907** may include a microphone and a speaker. The microphone is configured to collect sound waves of a user and an environment, convert the sound waves into an electrical signal, and input the electrical signal into the processor **901** for processing or into the radio frequency circuit **904** for implementing voice communication. For the purpose of stereo collection or noise reduction, there may be a plurality of microphones, respectively disposed at different portions of the computer device. The microphone may further be an array microphone or an omni-directional collection microphone. The speaker is configured to convert the electrical signal from the processor **901** or the radio frequency circuit **904** into sound waves. The speaker may be a film speaker, or may be a piezoelectric ceramic speaker. When the speaker is the piezoelectric ceramic speaker, the speaker not only can convert an electrical signal into an acoustic wave audible to a human being, but also can convert an electrical signal into an acoustic wave inaudible to a human being, for ranging and other purposes. The positioning assembly **908** is configured to determine a current geographic position of the computer device, to implement navigation or a location based service (LBS). The positioning assembly **908** may be a positioning assembly based on the Global Positioning System (GPS), the BeiDou system, or the Galileo system.

[0120] The power supply **909** is configured to supply power to assemblies in the computer device. The power supply **909** may be an alternating current, a direct current, a disposable battery, or a rechargeable battery. When the power supply **909** includes a rechargeable battery, the rechargeable battery may be a wired rechargeable battery or a wireless rechargeable battery. The wired rechargeable battery is a battery charged through a wired line, and the wireless rechargeable battery is a battery charged through a wireless coil. The rechargeable battery may further be configured to support a fast charging technology.

[0121] In some embodiments, the computer device further includes one or more sensors **910**. The one or more sensors **910** include, but are not limited to: an acceleration sensor **911** and a gyroscope sensor **912**.

[0122] The acceleration sensor **911** may detect magnitude of acceleration on three coordinate axes of a coordinate system established with the computer device. For example, the acceleration sensor **911** may be configured to detect components of gravity acceleration on the three coordinate axes. The processor **901** may send control information to the robot based on a gravity acceleration signal collected by the acceleration sensor **911**, to control motion of the robot.

[0123] The gyroscope sensor **912** may detect a body direction and a rotation angle of the computer device. The gyroscope sensor **912** may cooperate with the acceleration sensor **911** to collect an action of the robot. The processor **901** may implement the following functions according to the data collected by the gyroscope sensor **912**: action sensing.

[0124] A person skilled in the art may understand that the structure shown in FIG. **11** does not constitute any limitation on the computer device, and the computer device may include more or

fewer components than those shown in the figure, or some components may be combined, or a different component deployment may be used.

[0125] Some embodiments further provides a computer device, the computer device including a memory and a processor, the memory having at least one piece of program code stored therein, and the program code being loaded and executed by the processor, to implement the above control method.

[0126] According to some embodiments, this embodiment provides a non-volatile computer-readable storage medium, the non-volatile computer-readable storage medium having a computer program stored therein, the computer program being configured to be executed by a processor, to implement the above control method.

[0127] According to some embodiments, this embodiment provides a chip, the chip including at least one of a programmable logic circuit and program instructions, and during running of an electronic device on which the chip is installed, being configured to implement the above control method.

[0128] According to some embodiments, a computer program product is provided, the computer program product including computer instructions, the computer instructions being stored in a computer-readable storage medium, and a processor reading the computer instructions from the computer-readable storage medium and executing the computer instructions, to implement the above control method.

[0129] “Several” and “at least one” mentioned in the specification means one or more, and “a plurality of” and “at least two” means two or more.

[0130] In some embodiments, unless otherwise explicitly specified or defined, the terms such as “install”, “connect”, and “connection” are to be understood in a broad sense. For example, the connection may be a fixed connection, a detachable connection, or an integral connection; or the connection may be a mechanical connection; or the connection may be a direct connection, an indirect connection through an intermediate medium, internal communication between two components, or an interaction relationship between two components. A person of ordinary skill in the art may understand the meanings of the foregoing terms herein.

[0131] In addition, terms “first” and “second” are used merely for the purpose of description, and shall not be construed as indicating or implying relative importance or implying a quantity of indicated technical features. Therefore, a feature limited by “first” or “second” may explicitly or implicitly include one or more features. In some embodiments, “a plurality of” means two or more, unless otherwise definitely and specifically limited.

[0132] Unless otherwise explicitly stipulated and restricted, that a first feature is “on” or “under” a second feature may include that the first feature and the second feature are in direct contact, or may include that the first feature and the second feature are not in direct contact but in contact by using other features between the first feature and the second feature. Moreover, the first feature being “on” or “above” or “over” the second feature includes the first feature being directly above and obliquely above the second feature, or simply means that the level of the first feature is higher than that of the second feature. That the first feature is “below”, “under”, or “beneath” the second feature includes that the first feature is right below and at the inclined bottom of the second feature or merely indicates that a level of the first feature is lower than that of the second feature.

[0133] In the descriptions of this specification, descriptions using reference terms “some implementations”, “an implementation”, “some implementations”, “an exemplary implementation”, “an example”, “a specific example”, or “some examples” mean that specific features, structures, materials, or characteristics described with reference to the implementation or example are included in at least one implementation or example of some embodiments.

[0134] According to some embodiments, each module or unit may exist respectively or be combined into one or more units. Some units may be further split into multiple smaller function subunits, thereby implementing the same operations without affecting the technical effects of some

embodiments. The units are divided based on logical functions. In actual applications, a function of one unit may be realized by multiple units, or functions of multiple units may be realized by one unit. In some embodiments, the apparatus may further include other units. These functions may also be realized cooperatively by the other units, and may be realized cooperatively by multiple units.

[0135] A person skilled in the art would understand that these “modules” could be implemented by hardware logic, a processor or processors executing computer software code, or a combination of both. The “modules” may also be implemented in software stored in a memory of a computer or a non-transitory computer-readable medium, where the instructions of each module are executable by a processor to thereby cause the processor to perform the respective operations of the corresponding module.

[0136] The foregoing embodiments are used for describing, instead of limiting the technical solutions of the disclosure. A person of ordinary skill in the art shall understand that although the disclosure has been described in detail with reference to the foregoing embodiments, modifications can be made to the technical solutions described in the foregoing embodiments, or equivalent replacements can be made to some technical features in the technical solutions, provided that such modifications or replacements do not cause the essence of corresponding technical solutions to depart from the spirit and scope of the technical solutions of the embodiments of the disclosure and the appended claims.

Claims

1. A robot hip joint apparatus, the apparatus comprising: a support assembly, a drive assembly comprising a first driver, a second driver, and a third driver; and an execution assembly comprising a first movable leg member, a second movable leg member, and a movable waist member; wherein the first movable leg member and the second movable leg member are separately and rotatably connected to the support assembly, the first driver is in a transmission connection to the first movable leg member and is configured to drive the first movable leg member to rotate around a first axis, and the second driver is configured to drive the second movable leg member to rotate around the first axis, wherein the movable waist member is rotatably connected to the support assembly, the third driver is in a transmission connection to the movable waist member, and the third driver is configured to drive the movable waist member to rotate about a second axis, and wherein the first axis is parallel to the second axis.
2. The apparatus according to claim 1, wherein at least one of the first movable leg member or the second movable leg member comprises at least one shaft sleeve member, and the shaft sleeve member is sleeved on the rotating shaft member, and wherein the rotating shaft member and the shaft sleeve member are configured to separately rotate about the first axis.
3. The apparatus according to claim 2, wherein the first movable leg member further comprises at least one first connecting plate, and the first connecting plate is connected to the rotating shaft member and is configured to rotate with the rotating shaft member about the first axis, wherein the second movable leg member further comprises at least one second connecting plate, and the second connecting plate is connected to the shaft sleeve member and is configured to rotate with the shaft sleeve member about the first axis, and wherein the first connecting plate and the second connecting plate are configured to connect different leg components, and drive the leg components to rotate about the first axis.
4. The apparatus according to claim 2, wherein the rotating shaft member is in a transmission connection to the first driver, and the shaft sleeve member is in a transmission connection to the second driver.
5. The apparatus according to claim 3, wherein the first movable leg member further comprises two first connecting plate, and at least one of the first movable leg member or the second movable leg

member comprises two shaft sleeve members, wherein two ends of the rotating shaft member is configured to protrude to an outer side of the support assembly, the two first connecting plates are located at the two ends of the rotating shaft member, and the two shaft sleeve members are located near the two ends of the rotating shaft, and wherein the second connecting plate is configured to extend along a direction of the first axis, and separately connect to the two shaft sleeve members.

6. The apparatus according to claim 1, wherein the first driver and the second driver are located on the support assembly along a third axis, the third axis is parallel to the first axis; and the third driver is located on the support assembly along the second axis.

7. The apparatus according to claim 1, wherein at least one first transmission mechanism is disposed between the first driver and the first movable leg member, and at least one second transmission mechanism is disposed between the second driver and the second movable leg member, and wherein the first and second transmission mechanism are at least one of a meshing transmission mechanism, a belt transmission mechanism, or a chain transmission mechanism.

8. The apparatus according to claim 7, wherein at least one of the first and the second transmission mechanism comprises: a first gear member that is configured to connect to an output shaft of the first driver or the second driver, and a second gear member that is configured to connect to the first movable leg member and the second movable leg member, wherein the first gear member is in a meshing connection to the second gear member.

9. The apparatus according to claim 1, wherein the support assembly comprises a first mechanical part, a second mechanical part, and a third mechanical part, wherein the first mechanical part and the second mechanical part are disposed at an interval along at least one of the first axis or the second axis, and are located on two sides of the third mechanical part, the apparatus further comprising: a first shaft sleeve portion that is disposed at a position where the first mechanical part intersects the first axis, a second shaft sleeve portion that is disposed at a position where the second mechanical part intersects the first axis, wherein the first shaft sleeve portion and the second shaft sleeve portion are configured to rotatably connect to at least one of the first movable leg member and the second movable leg member; and a third shaft sleeve portion that is disposed at a position where the first mechanical part intersects the second axis, a fourth shaft sleeve portion that is disposed at a position where the second mechanical part intersects the second axis, wherein the third shaft sleeve portion and the fourth shaft sleeve portion are configured to rotatably connect to the movable waist member.

10. The apparatus according to claim 9, further comprising: a first assembly portion that is disposed at a position where the first mechanical part intersects the third axis; a second assembly portion that is disposed at a position where the second mechanical part intersects the third axis, wherein the first assembly portion is configured to connect to the second driver, and the second assembly portion is configured to connect to the first driver.

11. The apparatus according to claim 10, wherein the first shaft sleeve portion, the third shaft sleeve portion, and the first assembly portion are triangularly located on the first mechanical part, and wherein the second shaft sleeve portion, the fourth shaft sleeve portion, and the second assembly portion are triangularly located on the second mechanical part.

12. The apparatus according to claim 9, wherein the third mechanical part comprises at least one frame body, wherein the at least one frame body is configured to be connected between the first mechanical part and the second mechanical part, wherein the at least one frame body is positioned away from the first axis and the second axis.

13. The apparatus according to claim 12, wherein the at least one frame body comprises an arc-shaped frame body and a cylindrical frame body, wherein the arc-shaped frame body and the cylindrical frame body are separately connected between the first mechanical part and the second mechanical part.

14. A control method, performed by a computer device, the method comprising: determining a motion mode of a robot hip joint; generating a control signal based on the motion mode;

transmitting the control signal to a drive assembly of the robot hip joint; wherein the robot hip joint comprises: a support assembly, a drive assembly comprising a first driver, a second driver, and a third driver; and an execution assembly comprising a first movable leg member, a second movable leg member, and a movable waist member; wherein the first movable leg member and the second movable leg member are separately and rotatably connected to the support assembly, the first driver is in a transmission connection to the first movable leg member and is configured to drive the first movable leg member to rotate around a first axis, and the second driver is configured to drive the second movable leg member to rotate around the first axis, wherein the movable waist member is rotatably connected to the support assembly, the third driver is in a transmission connection to the movable waist member, and the third driver is configured to drive the movable waist member to rotate about a second axis, and wherein the first axis is parallel to the second axis.

15. The method according to claim 14, wherein at least one of the first movable leg member or the second movable leg member comprises at least one shaft sleeve member, and the shaft sleeve member is sleeved on the rotating shaft member, and wherein the rotating shaft member and the shaft sleeve member are configured to separately rotate about the first axis.

16. The method according to claim 15, wherein the first movable leg member further comprises at least one first connecting plate, and the first connecting plate is connected to the rotating shaft member and is configured to rotate with the rotating shaft member about the first axis, wherein the second movable leg member further comprises at least one second connecting plate, and the second connecting plate is connected to the shaft sleeve member and is configured to rotate with the shaft sleeve member about the first axis, and wherein the first connecting plate and the second connecting plate are configured to connect different leg components, and drive the leg components to rotate about the first axis.

17. The method according to claim 15, wherein the rotating shaft member is in a transmission connection to the first driver, and the shaft sleeve member is in a transmission connection to the second driver.

18. The method according to claim 16, wherein the first movable leg member further comprises two first connecting plate, and at least one of the first movable leg member or the second movable leg member comprises two shaft sleeve members, wherein two ends of the rotating shaft member is configured to protrude to an outer side of the support assembly, the two first connecting plates are located at the two ends of the rotating shaft member, and the two shaft sleeve members are located near the two ends of the rotating shaft, and wherein the second connecting plate is configured to extend along a direction of the first axis, and separately connect to the two shaft sleeve members.

19. The method according to claim 16, wherein the first driver and the second driver are located on the support assembly along a third axis, the third axis is parallel to the first axis; and the third driver is located on the support assembly along the second axis.

20. A control apparatus, comprising: at least one memory configured to store program code; and at least one processor configured to read the program code and operate as instructed by the program code, the program code comprising: determining code configured to cause at least one of the at least one processor to determine a motion mode of a robot hip joint; signal generation code configured to cause at least one of the at least one processor to generate a control signal based on the motion mode; and transmitting code configured to cause at least one of the at least one processor to transmit the control signal to a drive assembly of the robot hip joint, wherein the robot hip joint comprises: a support assembly, a drive assembly comprising a first driver, a second driver, and a third driver; and an execution assembly comprising a first movable leg member, a second movable leg member, and a movable waist member; wherein the first movable leg member and the second movable leg member are separately and rotatably connected to the support assembly, the first driver is in a transmission connection to the first movable leg member and is configured to drive the first movable leg member to rotate around a first axis, and the second driver is configured to drive the second movable leg member to rotate around the first axis, wherein the movable waist

member is rotatably connected to the support assembly, the third driver is in a transmission connection to the movable waist member, and the third driver is configured to drive the movable waist member to rotate about a second axis, and wherein the first axis is parallel to the second axis.
