

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250279510

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Lin; Denghua et al.

BATTERY CELL, BATTERY, AND ELECTRIC APPARATUS

Abstract

A battery cell is disclosed, including a housing, electrode terminals, and a protective member. The housing includes a wall portion and a fastener, where the fastener comprises a connecting portion and a pressing portion that together define a cavity. At least part of the electrode terminals is positioned within the cavity. The protective member includes a first protective portion covering the connecting portion and a second protective portion covering the pressing portion. The second protective portion extends beyond the pressing portion in a first direction. The structure reduces the likelihood of short circuits by shielding the pressing portion, thereby enhancing battery cell reliability.

Inventors: Lin; Denghua (Ningde, CN), Chen; Xinxiang (Ningde, CN), Huang; Shoujun (Ningde, CN), Luo; Yan (Ningde, CN), Zheng; Yulian (Ningde, CN), Wang; Peng (Ningde, CN), Jin; Haizu (Ningde, CN)

Applicant: CONTEMPORARY AMPEREX TECHNOLOGY CO., LIMITED (Ningde, CN)

Family ID: 93032371

Appl. No.: 19/212735

Filed: May 20, 2025

Foreign Application Priority Data

CN

202310395020.2

Apr. 13, 2023

Related U.S. Application Data

parent WO continuation PCT/CN2024/074735 20240130 PENDING child US 19212735

Publication Classification

**Int. Cl.: H01M50/103 (20210101); H01M50/15 (20210101); H01M50/176 (20210101);
H01M50/186 (20210101)**

U.S. Cl.:

**CPC H01M50/103 (20210101); H01M50/15 (20210101); H01M50/176 (20210101);
H01M50/186 (20210101);**

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of PCT Application No. PCT/CN2024/074735, filed on Jan. 30, 2024, which claims priority to Chinese Patent Application No. 202310395020.2, filed on Apr. 13, 2023 and entitled “BATTERY CELL, BATTERY, AND ELECTRIC APPARATUS”, which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

[0002] This application relates to the field of battery technology, and in particular to, a battery cell, a battery, and an electric apparatus.

BACKGROUND

[0003] As the smallest unit constituting a battery, a battery cell typically includes an electrode assembly, a housing, and electrode terminals, where the electrode assembly is disposed within the housing and electrically connected to the electrode terminals for electric energy output or input of the battery cell. A wall portion of the housing is usually provided with a fastener, and the electrode terminals are fixed on the wall portion of the housing under the pressing action of a pressing portion of the fastener. However, in practical use, a distance between the pressing portion and exposed portions of the electrode terminals is small and metal burrs on the pressing portion or external metal wires are likely to bridge between the pressing portion and the exposed portions of the electrode terminals. Therefore, a short-circuit fault may be caused in the battery cell, reducing the reliability of the battery cell.

SUMMARY

[0004] One objective of the embodiments of this application is to provide a battery cell, a battery, and an electric apparatus, so as to solve the technical problem of low reliability of the battery cell caused by metal burrs on the pressing portion or external metal wires that tend to bridge between the pressing portion and exposed portions of the electrode terminals.

[0005] To solve the foregoing technical problem, the embodiments of this application propose the following technical solution.

[0006] According to a first aspect, a battery cell is provided, including an electrode assembly, a housing, electrode terminals, an insulator, and a protective member. The housing is configured to accommodate the electrode assembly, where the housing includes a wall portion and a fastener, the fastener includes a connecting portion connected to the wall portion and a pressing portion connected to the connecting portion, and the connecting portion and the pressing portion jointly define a cavity. The electrode terminals are electrically connected to the electrode assembly, and at least a portion of the electrode terminals is accommodated in the cavity. The insulator is disposed between the fastener and the electrode terminals, where the pressing portion presses against the electrode terminals through the insulator to fix the electrode terminals on the wall portion. The protective member includes a first protective portion and a second protective portion connected to each other, where the first protective portion covers the connecting portion, the second protective portion covers the pressing portion, the second protective portion protrudes beyond the pressing

portion along a first direction, and the first direction is a direction pointing from the pressing portion to the electrode terminals and perpendicular to a thickness direction of the wall portion. [0007] A beneficial effect of the battery cell provided in the embodiments of this application is that: the battery cell provided in the embodiments of this application effectively shields the pressing portion by means of having the second protective portion protrude beyond the pressing portion along the first direction. This reduces the risk that metal burrs on the pressing portion extend outward or external metal wires have contact with the pressing portion, so that metal burrs on the pressing portion or external metal wires are less likely to bridge between the pressing portion and exposed portions of the electrode terminals, reducing the risk of a short-circuit fault in the battery cell and effectively enhancing the reliability of the battery cell.

[0008] In some embodiments of this application, the insulator includes a first insulating portion, and along the first direction, the first insulating portion is disposed between the pressing portion and the electrode terminals.

[0009] In this technical solution, the first insulating portion insulates and separates the pressing portion and the electrode terminals along the first direction, further reducing the risk that metal burrs on the pressing portion or external metal wires bridge between the pressing portion and exposed portions of the electrode terminals. This further reduces the risk of a short-circuit fault in the battery cell and further enhances the reliability of the battery cell.

[0010] In some embodiments of this application, at least a portion of a projection of the second protective portion in the thickness direction of the wall portion overlaps with a projection of the first insulating portion in the thickness direction of the wall portion.

[0011] In this technical solution, at least a portion of the second protective portion covers the first insulating portion. In this way, the pressing portion and the electrode terminals are insulated and separated more reliably, further reducing the risk that metal burrs on the pressing portion or external metal wires bridge between the pressing portion and exposed portions of the electrode terminals. This further reduces the risk of a short-circuit fault in the battery cell and enhances the reliability of the battery cell.

[0012] In some embodiments of this application, the second protective portion is fixedly connected to the first insulating portion.

[0013] In this technical solution, under the cooperative action of the second protective portion and the first insulating portion, the pressing portion and the electrode terminals are fully separated, further reducing the risk that metal burrs on the pressing portion or external metal wires bridge between the pressing portion and exposed portions of the electrode terminals. This further reduces the risk of a short-circuit fault in the battery cell and enhances the reliability of the battery cell.

[0014] In some embodiments of this application, in the thickness direction of the wall portion, an end surface of the first insulating portion facing away from the electrode assembly is flush with a surface of the pressing portion facing away from the electrode assembly, and the second protective portion is fixedly connected to the end surface of the first insulating portion.

[0015] In this technical solution, the second protective portion and the first insulating portion can be easily connected and connection stress between the second protective portion and the first insulating portion is reduced, so that the second protective portion is less likely to detach from the first insulating portion.

[0016] In some embodiments of this application, in the thickness direction of the wall portion, at least a portion of the first insulating portion protrudes beyond the surface of the pressing portion facing away from the electrode assembly.

[0017] In this technical solution, the first insulating portion insulates and separates the pressing portion and the electrode terminals more reliably, further reducing the risk that metal burrs on the pressing portion or external metal wires bridge between the pressing portion and exposed portions of the electrode terminals. This further reduces the risk of a short-circuit fault in the battery cell and enhances the reliability of the battery cell.

[0018] In some embodiments of this application, the insulator further includes a second insulating portion connected to an end of the first insulating portion facing the electrode assembly, and along the first direction, the second insulating portion is disposed between the connecting portion and the electrode terminals.

[0019] In this technical solution, the second insulating portion insulates and separates the connecting portion and the electrode terminals, thereby further reducing the risk of a short-circuit fault in the battery cell and enhancing the reliability of the battery cell.

[0020] In some embodiments of this application, the second insulating portion includes a first insulating segment, a second insulating segment, and a third insulating segment, where the first insulating segment is connected to the first insulating portion, the first insulating segment, the second insulating segment, and the third insulating segment enclose a cladding cavity, and at least a portion of the electrode terminals is disposed within the cladding cavity.

[0021] In this technical solution, the connecting portion and the electrode terminals are effectively insulated and separated, thereby further reducing the risk of a short-circuit fault in the battery cell and enhancing the reliability of the battery cell.

[0022] In some embodiments of this application, the second protective portion includes a cover body and a flange, where one side of the cover body along the first direction is connected to the first protective portion, the other side of the cover body along the first direction is connected to the flange, and in the thickness direction of the wall portion, the cover body covers the pressing portion and the flange covers a side of the pressing portion facing the electrode terminals along the first direction.

[0023] In this technical solution, the flange separates the pressing portion and the electrode terminals along the first direction, further reducing the risk that metal burrs on the pressing portion or external metal wires bridge between the pressing portion and exposed portions of the electrode terminals. This further reduces the risk of a short-circuit fault in the battery cell and enhances the reliability of the battery cell.

[0024] In some embodiments of this application, the insulator includes a first insulating portion, where the first insulating portion is disposed between the pressing portion and the electrode terminals along the first direction, a gap is formed between the first insulating portion and the pressing portion, and at least a portion of the flange is accommodated in the gap.

[0025] In this technical solution, the flange and the first insulating portion jointly insulate and separate the pressing portion and the electrode terminals along the first direction, further reducing the risk that metal burrs on the pressing portion or external metal wires bridge between the pressing portion and exposed portions of the electrode terminals. In addition, the flange is restricted within the gap to reduce the risk of the flange detaching from a position between the pressing portion and the electrode terminals, thereby further reducing the risk of a short-circuit fault in the battery cell and enhancing the reliability of the battery cell.

[0026] In some embodiments of this application, a length of the portion of the flange accommodated in the gap is greater than a minimum width of the gap.

[0027] In this technical solution, the flipping range of the flange within the gap is restricted to a certain extent, thereby reducing the risk of the flange flipping out of the gap.

[0028] In some embodiments of this application, a thickness of the flange is less than a width of the gap.

[0029] In this technical solution, the flange can be easily inserted into the gap.

[0030] In some embodiments of this application, the flange is fixedly connected to the side of the pressing portion facing the electrode terminals along the first direction.

[0031] In this technical solution, the relative positions of the flange and the pressing portion are kept unchanged, so that the flange separates the pressing portion and the electrode terminals along the first direction, further reducing the risk that metal burrs on the pressing portion or external metal wires bridge between the pressing portion and exposed portions of the electrode terminals.

This further reduces the risk of a short-circuit fault in the battery cell and enhances the reliability of the battery cell.

[0032] In some embodiments of this application, a cross-section of the side of the pressing portion facing the electrode terminals along the first direction is an arcuate structure in the thickness direction of the wall portion.

[0033] In this technical solution, an area of connection between the flange and the pressing portion is effectively increased to enhance connection strength between the flange and the pressing portion and control the lifting of the flange, thereby maintaining the relative positions of the flange and the pressing portion more effectively.

[0034] In some embodiments of this application, a side of a joint between the first protective portion and the second protective portion facing the fastener has a first fillet structure.

[0035] In this technical solution, connection stress between the first protective portion and the second protective portion is effectively reduced so that the second protective portion is less likely to detach from the pressing portion due to lifting, thereby further reducing the risk of a short-circuit fault in the battery cell and enhancing the reliability of the battery cell.

[0036] In some embodiments of this application, a side of a joint between the connecting portion and the pressing portion facing the first fillet structure has a second fillet structure.

[0037] In this technical solution, connection stress between the connecting portion and the pressing portion is effectively reduced to control the risk of fracture of the connecting portion and the pressing portion, further enhancing the reliability of the battery cell.

[0038] In some embodiments of this application, a radius of the first fillet structure is less than or equal to a radius of the second fillet structure.

[0039] In this technical solution, the joint between the first protective portion and the second protective portion less interferes with the joint between the connecting portion and the pressing portion, so that the second protective portion is less likely to detach from the pressing portion due to lifting. This further reduces the risk of a short-circuit fault in the battery cell and enhances the reliability of the battery cell.

[0040] In some embodiments of this application, a side of a joint between the connecting portion and the pressing portion facing the first fillet structure has a first chamfered structure.

[0041] In this technical solution, the fastener can be easily bent and processed. After the first chamfered structure is formed, part of the material of the pressing portion displaces toward the electrode terminals, effectively increasing a downward pressure exerted by the pressing portion on the insulator. In this way, the electrode terminals can be fixed more firmly on the wall portion of the housing.

[0042] In some embodiments of this application, a projection of the first chamfered structure in the thickness direction of the wall portion has a first width, and a projection of the first chamfered structure in the first direction has a second width; where the radius of the first fillet structure is less than or equal to the first width, and the radius of the first fillet structure is less than or equal to the second width.

[0043] In this technical solution, the joint between the first protective portion and the second protective portion less interferes with the joint between the connecting portion and the pressing portion, so that the second protective portion less likely to detach from the pressing portion due to lifting. This further reduces the risk of a short-circuit fault in the battery cell and enhances the reliability of the battery cell.

[0044] In some embodiments of this application, a side of a joint between the connecting portion and the pressing portion facing the protective member has a first chamfered structure, and a side of a joint between the first protective portion and the second protective portion facing the first chamfered structure has a second chamfered structure; where a projection of the first chamfered structure in the thickness direction of the wall portion has a first width, a projection of the first chamfered structure in the first direction has a second width; a projection of the second chamfered

structure in the thickness direction of the wall portion has a third width, a projection of the second chamfered structure in the first direction has a fourth width; and the third width is less than or equal to the first width, and the fourth width is less than or equal to the second width.

[0045] In this technical solution, the joint between the first protective portion and the second protective portion less interferes with the joint between the connecting portion and the pressing portion, so that the second protective portion less likely to detach from the pressing portion due to lifting. This further reduces the risk of a short-circuit fault in the battery cell and enhances the reliability of the battery cell.

[0046] In some embodiments of this application, the wall portion is provided with a first through hole, the electrode terminals are disposed in the first through hole and electrically connected to the electrode assembly, the first protective portion and the connecting portion each have an annular structure, the connecting portion is annularly disposed around the first through hole, the first protective portion is annularly disposed around the connecting portion, and an inner diameter of the first protective portion is greater than or equal to an outer diameter of the connecting portion.

[0047] In this technical solution, interference between the first protective portion and the connecting portion is reduced to lower the possibility of the second protective portion being lifted due to lifting of the first protective portion. This effectively reduces the risk of the second protective portion detaching from the pressing portion, thereby further reducing the risk of a short-circuit fault in the battery cell and enhancing the reliability of the battery cell.

[0048] In some embodiments of this application, the protective member further includes a third protective portion covering the wall portion, the third protective portion is connected to the first protective portion, and a side of a joint between the third protective portion and the first protective portion facing the fastener has a third fillet structure.

[0049] In this technical solution, connection stress between the third protective portion and the first protective portion is effectively reduced to lower the possibility of the second protective portion being lifted due to lifting of the first protective portion. This effectively reduces the risk of the second protective portion detaching from the pressing portion, thereby further reducing the risk of a short-circuit fault in the battery cell and enhancing the reliability of the battery cell.

[0050] In some embodiments of this application, a side of a joint between the connecting portion and the wall portion facing the third fillet structure has a fourth fillet structure.

[0051] In this technical solution, connection stress between the connecting portion and the wall portion is effectively reduced to control the risk of fracture of the connecting portion and the wall portion, further enhancing the reliability of the battery cell.

[0052] In some embodiments of this application, a radius of the third fillet structure is greater than or equal to a radius of the fourth fillet structure.

[0053] In this technical solution, the joint between the first protective portion and the third protective portion less interferes with the joint between the connecting portion and the wall portion, lowering the possibility of the second protective portion being lifted due to lifting of the first protective portion. This effectively reduces the risk of the second protective portion detaching from the pressing portion, thereby further reducing the risk of a short-circuit fault in the battery cell and enhancing the reliability of the battery cell.

[0054] In some embodiments of this application, the first protective portion, the second protective portion, and the third protective portion are integrally formed.

[0055] In this technical solution, the manufacturing process of the protective member is effectively simplified, thereby improving manufacturing efficiency of the protective member and reducing manufacturing costs of the protective member.

[0056] In some embodiments of this application, the pressing portion has an annular structure and is annularly disposed around the electrode terminals.

[0057] In this technical solution, the pressing portion is less likely to flip outward, so that the electrode terminals can be fixed more firmly on the wall portion of the housing.

[0058] In some embodiments of this application, the battery cell further includes a sealing member, and at least a portion of the sealing member is located between the wall portion and the electrode terminals.

[0059] In this technical solution, the sealing member seals a gap between the wall portion and the electrode terminals, reducing the risk of electrolyte leakage from between the electrode terminals and the body within the housing. This helps enhance the reliability of the battery cell.

[0060] In some embodiments of this application, the housing includes a housing body and an end cap, where one end of the housing body has an opening, the end cap covers the opening, the housing body includes a side wall and a bottom wall, the side wall is annularly disposed outside the electrode assembly, the bottom wall is disposed opposite the opening, and the wall portion is the end cap, the bottom wall, or the side wall.

[0061] In this technical solution, the electrode terminals can be installed on the end cap, the bottom wall, or the side wall.

[0062] According to a second aspect, an embodiment of this application further provides a battery, including the foregoing battery cell.

[0063] A beneficial effect of the battery provided in the embodiment of this application is that: with the foregoing battery cell adopted, the battery provided in the embodiment of this application has higher reliability.

[0064] According to a third aspect, an embodiment of this application further provides an electric apparatus, including the foregoing battery.

[0065] A beneficial effect of the electric apparatus provided in the embodiment of this application is that: with the foregoing battery adopted, the electric apparatus provided in the embodiment of this application has higher reliability.

Description

DESCRIPTION OF DRAWINGS

[0066] To illustrate the technical solutions in the embodiments of this application more clearly, the drawings required in the description of the embodiments or the prior art are briefly described below. Obviously, the drawings described below are merely some embodiments of this application, and for those of ordinary skill in the art, other drawings may be obtained based on these drawings without creative effort.

[0067] FIG. 1 is a schematic structural diagram of a vehicle according to an embodiment of this application;

[0068] FIG. 2 is a schematic exploded view of a battery according to an embodiment of this application;

[0069] FIG. 3 is a schematic structural diagram of a battery cell according to an embodiment of this application;

[0070] FIG. 4 is a schematic exploded view of the battery cell shown in FIG. 3;

[0071] FIG. 5 is a top view of the battery cell shown in FIG. 4;

[0072] FIG. 6 is a cross-sectional view of the battery cell shown in FIG. 5 along the A-A line direction;

[0073] FIG. 7 is a first enlarged view of position B of the battery cell shown in FIG. 6;

[0074] FIG. 8 is a second enlarged view of position B of the battery cell shown in FIG. 6;

[0075] FIG. 9 is a third enlarged view of position B of the battery cell shown in FIG. 6;

[0076] FIG. 10 is a fourth enlarged view of position B of the battery cell shown in FIG. 6; and

[0077] FIG. 11 is an enlarged view of position C of the battery cell shown in FIG. 6.

REFERENCE SIGNS

[0078] **1000.** vehicle; [0079] **100.** battery; [0080] **10.** box; **11.** first portion; **12.** second portion; **13.**

accommodating space; [0081] **20.** battery cell; **21.** protective member; **211.** first protective portion; **212.** second protective portion; **2121.** cover body; **2122.** flange; **2123.** second through hole; **213.** third protective portion; **214.** first fillet structure; **215.** second chamfered structure; **216.** third fillet structure; **22.** housing; **221.** housing body; **222.** end cap; **2221.** first through hole; **223.** fastener; **2231.** connecting portion; **2232.** pressing portion; **2233.** second fillet structure; **2234.** first chamfered structure; **224.** fourth fillet structure; **23.** electrode terminal; **231.** first connecting segment; **232.** second connecting segment; **233.** flange portion; **24.** electrode assembly; **25.** insulator; **251.** first insulating portion; **252.** second insulating portion; **2521.** first insulating segment; **2522.** second insulating segment; **2523.** third insulating segment; **26.** sealing member; **27.** gap; **28.** pressure relief mechanism; [0082] **200.** controller; and [0083] **300.** motor.

DESCRIPTION OF EMBODIMENTS

[0084] To make the technical problems, technical solutions, and beneficial effects to be solved by this application clearer, this application is further described in detail below in conjunction with the drawings and embodiments. It should be understood that the specific embodiments described herein are merely used to explain this application but are not intended to limit this application.

[0085] It should be noted that when an element is referred to as being “fixed to” or “disposed on” another element, the element may be directly on the other element or indirectly on the other element. When an element is referred to as being “connected to” another element, the element may be directly connected to the another element or indirectly connected to the another element.

[0086] It should be understood that the terms “length”, “width”, “upper”, “lower”, “front”, “rear”, “left”, “right”, “vertical”, “horizontal”, “top”, “bottom”, “inner”, “outer”, and similar terms indicating orientation or positional relationships are based on the orientation or positional relationships shown in the drawings, and are merely for convenience of describing this application and simplifying the description, rather than indicating or implying that the device or element referred to must have a specific orientation, be constructed and operated in a specific orientation, and thus should not be construed as limiting this application.

[0087] In addition, the terms “first” and “second” are used for description purposes only and should not be understood as indicating or implying relative importance or implicitly specifying the number of technical features indicated. Therefore, a feature defined with “first” or “second” may explicitly or implicitly include one or more of that feature. In the description of this application, “a plurality” means two or at least two unless otherwise specifically stated.

[0088] As the smallest unit constituting a battery, a battery cell typically includes an electrode assembly, a housing, and electrode terminals. The housing is a component configured to provide an internal environment of the battery cell, the electrode assembly is accommodated in the internal environment of the battery cell, and the electrode terminals are fixed on a wall portion of the housing and electrically connected to the electrode assembly for electric energy output or input of the battery cell. In practical use, to ensure that the electrode terminals are mounted stably, a fastener is usually provided on the wall portion of the housing to fix the electrode terminals. Specifically, a connecting portion of the fastener is connected to the wall portion of the housing, and a pressing portion of the fastener is connected to the connecting portion and provides a downward pressure to the electrode terminals, so that the electrode terminals is fixed on the wall portion of the housing.

[0089] In related technologies, for ease of connection between the electrode terminals and external electrical connectors, at least a portion of the electrode terminals needs to be exposed to an external environment of the battery cell. Due to the small distance between the pressing portion and exposed portions of the electrode terminals, a short-circuit easily occurs between the pressing portion and the electrode terminals. For example, when metal burrs are present on the pressing portion, the metal burrs is likely to extend toward the exposed portions of the electrode terminals and bridge between the pressing portion and the exposed portions of the electrode terminals, short-circuiting the pressing portion and the electrode terminals. Alternatively, when an external metal wire falls

between the pressing portion and the electrode terminals, the metal wire bridges between the pressing portion and the exposed portions of the electrode terminals, short-circuiting the pressing portion and the electrode terminals. In these cases, a short-circuit fault occurs in the battery cell, reducing the reliability of the battery cell.

[0090] To reduce the risk of a short-circuit fault in the battery cell, an embodiment of this application provides a battery cell, where the battery cell includes a housing, electrode terminals, and a protective member. A wall portion of the housing is provided with a fastener, the electrode terminals are accommodated in a cavity of the fastener, a pressing portion of the fastener provides a downward pressure to the electrode terminals to fix the electrode terminals on the wall portion of the housing, and along a direction pointing from the pressing portion to the electrode terminals and perpendicular to a thickness direction of the wall portion, a second protective body of the protective member protrudes beyond a side of the pressing portion facing the electrode terminals to shield the pressing portion, reducing the risk that metal burrs on the pressing portion extend outward or external metal wires have contact with the pressing portion. In this way, metal burrs on the pressing portion or external metal wires are less likely to bridge between the pressing portion and exposed portions of the electrode terminals, thereby effectively reducing the risk of a short-circuit fault in the battery cell and effectively enhancing the reliability of the battery cell.

[0091] The embodiments of this application disclose a battery cell, a battery, and an electric apparatus using the battery as a power source. The electric apparatus may include, but is not limited to, a vehicle, a mobile phone, a portable device, a laptop computer, a ship, a spacecraft, an electric toy, an electric tool, and the like. The vehicle may be a fuel vehicle, a gas vehicle, or a new energy vehicle, where the new energy vehicle may be a pure electric vehicle, a hybrid vehicle, an extended-range vehicle, or the like. The spacecraft includes an airplane, a rocket, a space shuttle, a spaceship, and the like. The electric toy includes a stationary or mobile electric toy, such as a gaming console, an electric car toy, an electric ship toy, an electric airplane toy, and the like. The electric tool includes a metal cutting electric tool, a grinding electric tool, an assembly electric tool, and a railway electric tool, such as an electric drill, an electric grinder, an electric wrench, an electric screwdriver, an electric hammer, an impact drill, a concrete vibrator, an electric planer, and the like.

[0092] For ease of description, the electric apparatus according to an embodiment of this application being a vehicle is used as an example for description of the following embodiments.

[0093] Referring to FIG. 1, FIG. 1 is a schematic structural diagram of a vehicle **1000** according to an embodiment of this application. The vehicle **1000** may be a fuel vehicle, a gas vehicle, or a new energy vehicle, where the new energy vehicle may be a pure electric vehicle, a hybrid vehicle, an extended-range vehicle, or the like. A battery **100** is provided inside the vehicle **1000**, and the battery **100** may be disposed at the bottom, front, or rear of the vehicle **1000**. The battery **100** may be used for power supply of the vehicle **1000**, for example, the battery **100** may serve as an operational power source of the vehicle **1000**. The vehicle **1000** may further include a controller **200** and a motor **300**, where the controller **200** is configured to control the battery **100** to supply power to the motor **300**, for example, for operational power requirements during starting, navigation, and driving of the vehicle **1000**.

[0094] In some embodiments of this application, the battery **100** may be used not only as the operational power source for the vehicle **1000** but also a driving power source for the vehicle **1000**, replacing or partially replacing fossil fuel or natural gas to provide driving traction for the vehicle **1000**.

[0095] Referring to FIG. 2, FIG. 2 is a schematic exploded view of a battery **100** according to an embodiment of this application. The battery **100** includes a box **10** and a battery cell **20**, where the battery cell **20** is accommodated in the box **10**. The box **10** is configured to provide an accommodating space **13** for the battery cell **20**. The box **10** may have various structures. In some embodiments, the box **10** may include a first portion **11** and a second portion **12**. The first portion

11 and the second portion **12** fit together so that the first portion **11** and the second portion **12** jointly define an accommodating space **13** for accommodating the battery cells **20**. The second portion **12** may be a hollow structure with an opening at one end, the first portion **11** may be a plate-shaped structure, and the first portion **11** covers the opening side of the second portion **12** so that the first portion **11** and the second portion **12** jointly define the accommodating space **13**. Alternatively, both the first portion **11** and the second portion **12** may be hollow structures with an opening at one side, and the opening side of the first portion **11** is engaged with the opening side of the second portion **12**. Certainly, the box **10** formed by the first portion **11** and the second portion **12** may be of various shapes, for example, cylinder or cuboid.

[0096] In some embodiments, the box **10** may be a part of a chassis structure of the vehicle **1000**. For example, a portion of the box **10** may be at least a part of a floor of the vehicle **1000**, or a portion of the box **10** may be at least a part of cross beams and longitudinal beams of the vehicle **1000**.

[0097] In the battery **100**, the battery cell **20** may be provided in plurality, and the plurality of battery cells **20** may be connected in series, in parallel, or in series-parallel, where a series-parallel connection refers to a combination of series and parallel connections among the plurality of battery cells **20**. The plurality of battery cells **20** may be directly connected in series, in parallel, or in series-parallel, and then an entirety of the plurality of battery cells **20** is accommodated in the box **10**. Alternatively, the battery **100** may also be formed by first connecting a plurality of battery cells **20** in series, in parallel, or in series-parallel to form battery modules, and then connecting a plurality of battery modules in series, in parallel, or in series-parallel to form an entirety, which is accommodated in the box **10**. The battery **100** may also include other functional components, for example, the battery **100** may further include a busbar component configured to achieve electrical connection between the plurality of battery cells **20**.

[0098] Each battery cell **20** may be a secondary battery or a primary battery, where the secondary battery refers to a battery cell **20** that can be recharged to activate active materials for continued use after discharge, and the primary battery refers to a battery cell **20** that cannot be recharged to activate active materials for continued use after its electric energy is depleted; the battery cell **20** may also be a lithium-ion battery, a sodium-ion battery, a sodium-lithium-ion battery, a lithium metal battery, a sodium metal battery, a lithium-sulfur battery, a magnesium-ion battery, a nickel-hydrogen battery, a nickel-cadmium battery, a lead-acid battery, or the like, but is not limited thereto. The battery cell **20** may be a cylindrical battery cell, a prismatic battery cell, a pouch battery cell, or a battery cell of other shapes, where the prismatic battery cell includes a square-housing body battery cell, a blade-shaped battery cell, a polygonal prismatic battery, such as a hexagonal prismatic battery, and the like, with no particular limitation in this application.

[0099] Alternatively, in some embodiments, the battery **100** may not include the box **10**, but instead, a plurality of battery cells **20** are electrically connected and assembled into an entirety through necessary fixing structures before being mounted into the vehicle **1000**.

[0100] Referring to FIG. 3 and FIG. 4, FIG. 3 is a schematic structural diagram of a battery cell **20** according to an embodiment of this application, and FIG. 4 is a schematic exploded view of the battery cell **20** shown in FIG. 3. The battery cell **20** refers to the smallest unit constituting the battery **100**. The battery cell **20** provided in the embodiments of this application includes a housing **22**, an electrode assembly **24**, electrode terminals **23**, an insulator **25**, and other functional components.

[0101] The housing **22** includes a housing body **221** and an end cap **222**, where the housing body **221** is a component configured to provide an internal environment of the battery cell **20**, and the internal environment can be used to accommodate the electrode assembly **24** and other functional components. The housing body **221** may be an independent component, and an opening may be provided on the housing body **221**, where the end cap **222** is disposed over the opening to form the internal environment of the battery cell **20**, and components such as the electrode assembly **24** are

accommodated in the internal environment. Specifically, the housing body **221** and the end cap **222** may form a common connection surface before other components are placed into the housing body, and when the interior of the housing body **221** needs to be encapsulated, the end cap **222** is disposed over the opening of the housing body **221**. Optionally, the housing body **221** may have various shapes and sizes, such as a cuboid shape, a cylindrical shape, and a hexagonal prism shape. Specifically, the shape of the housing body **221** may be determined based on the specific shape and size of the electrode assembly **24**. The housing body **221** may be made of various materials, such as copper, iron, aluminum, stainless steel, aluminum alloy, or the like, with no specific limitation herein.

[0102] The end cap **222** refers to a component that covers the opening of the housing body **221** to isolate the internal environment of the battery cell **20** from an external environment. The shape of the end cap **222** may be adapted to the shape of the housing body **221** to fit with the housing body **221**. In some embodiments, the end cap **222** may be made of a material with certain hardness and strength, so that the end cap **222** is not easily deformed when subjected to compression or collision, enabling the battery cell **20** to have higher structural strength and improved safety performance. Certainly, the material of the end cap **222** is not uniquely limited in this embodiment, and the end cap **222** may be made of materials such as copper, iron, aluminum, stainless steel, aluminum alloy, plastic, or the like. In some embodiments, the end cap **222** may also be provided with a pressure relief mechanism **28** configured to release internal pressure when the internal pressure or temperature of the battery cell **20** reaches a threshold. In some embodiments, an insulating separator may also be provided on the end cap **222**, where the insulating separator can be used to isolate electrical connection components within the housing body **221** from the end cap **222** to reduce the risk of a short circuit. Optionally, the material of the insulating separator may include, but is not limited to, plastic, rubber, or the like.

[0103] The electrode assembly **24** is a component in the battery cell **20** where an electrochemical reaction occurs. The battery cell **20** may include one or more electrode assemblies **24**. The electrode assembly **24** is primarily formed by winding or stacking a positive electrode plate, a negative electrode plate, and a separator.

[0104] In some embodiments, the electrode assembly **24** has a wound structure. The positive electrode plate and the negative electrode plate are formed into a wound structure.

[0105] In some embodiments, the electrode assembly **24** has a laminated structure.

[0106] As an example, a plurality of positive electrode plates and a plurality of negative electrode plates may be provided, where the plurality of positive electrode plates and the plurality of negative electrode plates are alternately stacked.

[0107] As an example, a plurality of positive electrode plates may be provided, and the negative electrode plate is folded to form a plurality of stacked folding segments, with one positive electrode plate sandwiched between adjacent folding segments.

[0108] As an example, both the positive electrode plate and the negative electrode plate are folded to form a plurality of stacked folding segments.

[0109] As an example, a plurality of separators may be provided, each disposed between any adjacent positive electrode plates or negative electrode plates.

[0110] As an example, the separator may be continuously provided, and disposed between any adjacent positive electrode plates or negative electrode plates by means of folding or winding.

[0111] During charging and discharging of the battery cell **20**, active ions (for example, lithium ions) intercalate and deintercalate back and forth between the positive electrode plate and the negative electrode plate. The separator is disposed between the positive electrode plate and the negative electrode plate to prevent a short circuit between the positive and negative electrodes while allowing the active ions to pass through.

[0112] The positive electrode plate may include a positive electrode current collector and a positive electrode active material disposed on at least one surface of the positive electrode current collector.

[0113] As an example, the positive electrode current collector has two opposite surfaces in a thickness direction of the positive electrode current collector, and the positive electrode active material is disposed on either or both of the two opposite surfaces of the positive electrode current collector.

[0114] As an example, the positive electrode current collector may be a metal foil current collector or a composite current collector. For example, the metal foil may use silver surface-treated aluminum or stainless steel, stainless steel, copper, aluminum, nickel, baked carbon, carbon, nickel, or titanium. The composite current collector may include a polymer material matrix and a metal layer. The composite current collector may be formed by forming a metal material (aluminum, aluminum alloy, nickel, nickel alloy, titanium, titanium alloy, silver, silver alloy, or the like) on a polymer material matrix (for example, a matrix of polypropylene, polyethylene terephthalate, polybutylene terephthalate, polystyrene, or polyethylene).

[0115] As an example, the positive electrode active material may include at least one of the following materials: lithium-containing phosphate, lithium transition metal oxide, and respective modified compounds thereof. However, this application is not limited to these materials, and other conventional materials that can be used as the positive electrode active material of the battery cell **20** may also be used. These positive electrode active materials may be used alone or in combination. Examples of the lithium-containing phosphate may include, but are not limited to, at least one of lithium iron phosphate (for example, LiFePO_4 (LFP for short)), a composite material of lithium iron phosphate and carbon, lithium manganese phosphate (for example, LiMnPO_4), a composite material of lithium manganese phosphate and carbon, lithium iron manganese phosphate, and a composite material of lithium iron manganese phosphate and carbon. Examples of the lithium transition metal oxide may include, but are not limited to, at least one of lithium cobalt oxide (for example, LiCoO_2), lithium nickel oxide (for example, LiNiO_2), lithium manganese oxide (for example, LiMnO_2 , LiMn_2O_4), lithium nickel cobalt oxide, lithium manganese cobalt oxide, lithium nickel manganese oxide, lithium nickel cobalt manganese oxide (for example, $\text{LiNi}_{1/3}\text{Co}_{1/3}\text{Mn}_{1/3}\text{O}_2$ (NCM333 for short), $\text{LiNi}_{0.5}\text{Co}_{0.2}\text{Mn}_{0.3}\text{O}_2$ (NCM523 for short), $\text{LiNi}_{0.5}\text{Co}_{0.25}\text{Mn}_{0.25}\text{O}_2$ (NCM211 for short), $\text{LiNi}_{0.6}\text{Co}_{0.2}\text{Mn}_{0.2}\text{O}_2$ (NCM622 for short), $\text{LiNi}_{0.8}\text{Co}_{0.1}\text{Mn}_{0.1}\text{O}_2$ (NCM811 for short)), lithium nickel cobalt aluminum oxide (for example, $\text{LiNi}_{0.85}\text{Co}_{0.15}\text{Al}_{0.05}\text{O}_2$), and modified compounds thereof.

[0116] In some embodiments, the positive electrode may use a foam metal. The foam metal may be foam nickel, foam copper, foam aluminum, foam alloy, or foam carbon, or the like. When the foam metal is used as the positive electrode, the surface of the foam metal may or may not be provided with the positive electrode active material. As an example, a lithium source material, potassium metal, or sodium metal may also be filled or deposited within the foam metal, where the lithium source material is lithium metal and/or a lithium-rich material.

[0117] The negative electrode plate may include a negative electrode current collector.

[0118] As an example, the negative electrode current collector may use a metal foil, a foam metal, or a composite current collector. For example, the metal foil may use silver surface-treated aluminum or stainless steel, stainless steel, copper, aluminum, nickel, baked carbon, carbon, nickel, or titanium. The foam metal may be foam nickel, foam copper, foam aluminum, foam alloy, or foam carbon, or the like. The composite current collector may include a polymer material matrix and a metal layer. The composite current collector may be formed by forming a metal material (copper, copper alloy, nickel, nickel alloy, titanium, titanium alloy, silver, silver alloy, or the like) on a polymer material matrix (for example, a matrix of polypropylene, polyethylene terephthalate, polybutylene terephthalate, polystyrene, polyethylene, or the like).

[0119] As an example, the negative electrode plate may include a negative electrode current

collector and a negative electrode active material disposed on at least one surface of the negative electrode current collector.

[0120] As an example, the negative electrode current collector has two opposite surfaces in a thickness direction of the negative electrode current collector, and the negative electrode active material is disposed on either or both of the two opposite surfaces of the negative electrode current collector.

[0121] As an example, the negative electrode active material may use a negative electrode active material known in the art for the battery cell **20**. For example, the negative electrode active material may include at least one of the following materials: artificial graphite, natural graphite, soft carbon, hard carbon, silicon-based material, tin-based material, and lithium titanate. The silicon-based material may be selected from at least one of elemental silicon, silicon-oxygen compound, silicon-carbon composite, silicon-nitrogen composite, or silicon alloy. The tin-based material may be selected from at least one of elemental tin, tin-oxygen compound, or tin alloy. However, this application is not limited to these materials, and other conventional materials that can be used as the negative electrode active material of the battery cell **20** may also be used. These negative electrode active materials may be used alone or in combination.

[0122] In some embodiments, the material of the positive electrode current collector may be aluminum, and the material of the negative electrode current collector may be copper.

[0123] In some embodiments, the separator is an isolating film. The separator is not limited to any particular type in this application, and may be any well-known porous separator with good chemical stability and mechanical stability.

[0124] As an example, a major material of the isolating film may be selected from at least one of glass fiber, non-woven fabric, polyethylene, polypropylene, polyvinylidene fluoride, or ceramics. The separator may be a single-layer film or a multi-layer composite film, which is not particularly limited. When the separator is a multi-layer composite film, materials of layers may be the same or different, with no particular limitation. The separator may be a single component located between the positive electrode plate and the negative electrode plate, or may be attached to the surface of the positive electrode plate and the surface of the negative electrode plate.

[0125] In some embodiments, the separator is a solid electrolyte. The solid electrolyte is disposed between the positive electrode plate and the negative electrode plate, for transmitting ions and isolating the positive and negative electrodes.

[0126] In some embodiments, the battery cell **20** further includes an electrolyte, where the electrolyte serves to conduct ions between the positive electrode plate and the negative electrode plate. The type of the electrolyte is not specifically limited in this application and may be selected according to needs. The electrolyte may be liquid, gel, or solid.

[0127] The liquid electrolyte includes an electrolyte salt and a solvent.

[0128] In some embodiments, the electrolyte salt may be selected from at least one of lithium hexafluorophosphate, lithium tetrafluoroborate, lithium perchlorate, lithium hexafluoroarsenate, lithium bis(fluorosulfonyl)imide, lithium bis(trifluoromethanesulfonyl)imide, lithium trifluoromethanesulfonate, lithium difluorophosphate, lithium difluoro(oxalato)borate, lithium bis(oxalato) borate, lithium difluoro-bis(oxalato)phosphate, and lithium tetrafluoro(oxalato)phosphate.

[0129] In some embodiments, the solvent may be selected from at least one of ethylene carbonate, propylene carbonate, ethyl methyl carbonate, diethyl carbonate, dimethyl carbonate, dipropyl carbonate, methyl propyl carbonate, ethyl propyl carbonate, butylene carbonate, fluoroethylene carbonate, methyl formate, methyl acetate, ethyl acetate, propyl acetate, methyl propionate, ethyl propionate, propyl propionate, methyl butyrate, ethyl butyrate, 1,4-butyrolactone, sulfolane, methyl sulfonyl methane, ethyl methanesulfonate, and diethyl sulfone. The solvent may also be selected from ether solvents. The ether solvents may include one or more of ethylene glycol dimethyl ether, ethylene glycol diethyl ether, diethylene glycol dimethyl ether, triethylene glycol dimethyl ether,

tetraethylene glycol dimethyl ether, 1,3-dioxolane, tetrahydrofuran, methyl tetrahydrofuran, diphenyl ether, and crown ether.

[0130] The gel electrolyte includes a skeleton network with a polymer as the electrolyte, together with an ionic liquid-lithium salt.

[0131] The solid electrolyte includes a polymer solid electrolyte, an inorganic solid electrolyte, and a composite solid electrolyte.

[0132] As an example, the polymer solid electrolyte may be polyether (polyethylene oxide), polysiloxane, polycarbonate, polyacrylonitrile, polyvinylidene fluoride, polymethyl methacrylate, single-ion polymer, polyionic liquid-lithium salt, cellulose, or the like.

[0133] As an example, the inorganic solid electrolyte may be one or more of an oxide solid electrolyte (crystalline perovskite, sodium superionic conductor, garnet, or amorphous LiPON film), a sulfide solid electrolyte (crystalline lithium superionic conductor (lithium germanium phosphorus sulfide, or argyrodite), or amorphous sulfide), a halide solid electrolyte, a nitride solid electrolyte, and a hydride solid electrolyte.

[0134] As an example, the composite solid electrolyte is formed by adding inorganic solid electrolyte fillers to the polymer solid electrolyte.

[0135] In some embodiments, the electrode assembly **24** may be cylindrical, flat, polygonal prismatic, or in other shapes.

[0136] In some embodiments, the electrode assembly **24** is provided with tabs, where the tabs can conduct current from the electrode assembly **24**. The tabs include a positive tab and a negative tab.

[0137] The electrode terminals **23** are components electrically connected to the electrode assembly **24** to output electric energy from the battery cell **20** or input electric energy to the battery cell **20**. The electrode terminals **23** may be disposed on the end cap **222**, where a portion of the electrode terminals **23** extends into the internal environment of the battery cell **20** and is directly or indirectly connected to the tabs of the electrode assembly **24**, and another portion of the electrode terminals **23** is exposed to the external environment of the battery cell **20** and connected to components such as a busbar or a sampling device. Optionally, the electrode terminals **23** may have a columnar structure, such as a cylindrical structure, a prismatic structure, or the like, or the electrode terminals **23** may have a plate-like structure, such as a circular plate, a square plate, or the like, or the electrode terminals **23** may have other irregular three-dimensional structures, with no specific limitation herein. The electrode terminals **23** may be made of a single metal material or multiple metal materials, where the metal materials may include, but are not limited to, copper, aluminum, nickel, zinc, iron, or the like, with no specific limitation herein.

[0138] The insulator **25** refers to a component made of an insulating material, where the insulator **25** is located between the housing **22** and the electrode terminals **23** to insulate and separate the housing **22** and the electrode terminals **23**, reducing the risk of a short circuit. The insulating material may include, but is not limited to, plastic, rubber, or the like.

[0139] The following describes in detail the technical solutions provided in this application with reference to specific accompanying drawings and embodiments.

[0140] According to a first aspect, referring to FIG. **4** to FIG. **11**, the battery cell **20** provided in an embodiment of this application further includes a protective member **21**. The housing **22** is configured to accommodate the electrode assembly **24**, where the housing **22** includes a wall portion and a fastener **223**, the fastener **223** includes a connecting portion **2231** connected to the wall portion and a pressing portion **2232** connected to the connecting portion **2231**, and the connecting portion **2231** and the pressing portion **2232** jointly define a cavity. The electrode terminals **23** are electrically connected to the electrode assembly **24**, and at least a portion of the electrode terminals **23** is accommodated in the cavity. The insulator **25** is disposed between the fastener **223** and the electrode terminals **23**, where the pressing portion **2232** presses against the electrode terminals **23** through the insulator **25** to fix the electrode terminals **23** on the wall portion. The protective member **21** includes a first protective portion **211** and a second protective portion

212 connected to each other, where the first protective portion **211** covers the connecting portion **2231**, the second protective portion **212** covers the pressing portion **2232**, the second protective portion **212** protrudes beyond the pressing portion **2232** along a first direction, and the first direction is a direction pointing from the pressing portion **2232** to the electrode terminals **23** and perpendicular to a thickness direction of the wall portion.

[0141] For convenience of description below, the thickness direction of the wall portion of the housing **22** is referred to as a second direction, namely the Y direction in FIG. 7 to FIG. 11.

[0142] The wall portion of the housing **22** may be any wall of the housing body **221**, for example, a side wall of the housing body **221**, a bottom wall of the housing body **221**, or a cover plate of the end cap **222**, with no specific limitation herein.

[0143] The fastener **223** refers to a component of the housing **22** that protrudes from the wall portion and is configured to fix the electrode terminals **23**. The fastener **223** and the wall portion of the housing **22** may be an integrated structure, for example, the fastener **223** and the wall portion of the housing **22** are manufactured and formed using an integration process such as extrusion, injection molding, or die casting. The fastener **223** and the wall portion of the housing **22** may also be a separate structure, that is, the fastener **223** and the wall portion of the housing **22** are separately formed and then connected together. Referring to FIG. 11, the wall portion of the housing **22** is provided with a first through hole **2221**, and the fastener **223** is annularly disposed around the first through hole **2221** and encloses a cavity for accommodating the electrode terminals **23**.

[0144] Specifically, the fastener **223** includes a connecting portion **2231** and a pressing portion **2232**.

[0145] The connecting portion **2231** refers to a portion of the fastener **223** located between the pressing portion **2232** and the wall portion of the housing **22**, where the connecting portion **2231** serves to connect the pressing portion **2232** and the wall portion of the housing **22**, and may also support the pressing portion **2232**. The connecting portion **2231** is annularly disposed around the first through hole **2221**, where the connecting portion **2231** may be an annular integral structure disposed around the first through hole **2221**, or the connecting portion **2231** may be a segmented structure annularly arranged along a circumferential direction of the first through hole **2221**.

[0146] The pressing portion **2232** refers to a portion of the fastener **223** configured to press against the insulator **25**. The pressing portion **2232** may be parallel to the wall portion of the housing **22** and spaced apart from the wall portion of the housing **22**, or may be inclined relative to the wall portion of the housing **22**. The specific design may depend on actual structures, with no limitation herein. The pressing portion **2232** may be an annular integral structure annularly disposed outside the electrode terminals **23**, or the pressing portion **2232** may be a segmented structure annularly arranged along a circumferential direction of the electrode terminals **23**. Referring to FIG. 11, the pressing portion **2232** encloses a second through hole **2123**, where the first through hole **2221**, the cavity, and the second through hole **2123** are sequentially connected along the second direction.

[0147] The electrode terminals **23** may be partially or entirely located within the cavity enclosed by the fastener **223**. The electrode terminals **23** may be electrically connected to an electrical connector through the first through hole **2221** and then electrically connected to the electrode assembly **24**. The electrode terminals **23** may alternatively be exposed to an external environment of the battery cell **20** through the second through hole **2123** and then electrically connected to a busbar to achieve electric energy output and input of the battery cell **20**.

[0148] In some embodiments, referring to FIG. 11, the electrode terminals **23** include a first connecting segment **231** and a second connecting segment **232**, where the first connecting segment **231** and the second connecting segment **232** are distributed along the second direction and connected to each other to form a main body of the electrode terminals **23**. At least a portion of the first connecting segment **231** is disposed within the first through hole **2221** and extends into the internal environment of the battery cell **20** for electrical connection with an electrical connector and

then electrical connection with the electrode assembly **24**. At least a portion of the second connecting segment **232** is exposed to the external environment of the battery cell **20** through the second through hole **2123**, and then electrically connected to a busbar. The electrode terminals **23** may further include a flange portion **233**, where the flange portion **233** is annularly disposed around the main body of the electrode terminals **23** and located within the cavity enclosed by the fastener **223**, and the insulator **25** is at least partially located between the pressing portion **2232** and the flange portion **233**, so that the pressing portion **2232** presses against the insulator **25**, and the insulator **25** presses against the flange portion **233**, thereby fixing the electrode terminals **23** on the wall portion of the housing **22**.

[0149] The protective member **21** covers the fastener **223**. This can insulate the fastener **223** from other components to prevent a short circuit between the housing **22** and external circuits, and protect the fastener **223** against scratches. The protective member **21** is made of an insulating material, where the insulating material may include, but is not limited to, polyimide, polyethylene, polyvinylidene fluoride, polytetrafluoroethylene, or the like, with no specific limitation herein. The protective member **21** includes a first protective portion **211** and a second protective portion **212**. The first protective portion **211** covers the connecting portion **2231**. Specifically, the first protective portion **211** covers a wall surface of the connecting portion **2231** facing away from the electrode terminals **23**. The shape of the first protective portion **211** is adapted to the shape of the connecting portion **2231**. For example, when the connecting portion **2231** has an annular structure, the first protective portion **211** also has an annular structure. The second protective portion **212** covers the pressing portion **2232**. Specifically, the second protective portion **212** covers a surface of the pressing portion **2232** facing away from the electrode assembly **24**. The shape of the second protective portion **212** is adapted to the shape of the pressing portion **2232**. For example, when the pressing portion **2232** has an annular structure, the second protective portion **212** also has an annular structure.

[0150] One side of the second protective portion **212** along the first direction is connected to the first protective portion **211**, and another side of the second protective portion **212** along the first direction protrudes beyond the pressing portion **2232**. In other words, along the first direction, a distance between the second protective portion **212** and the second connecting segment **232** of the electrode terminals **23** is less than a distance between the pressing portion **2232** and the second connecting segment **232** of the electrode terminals **23**. The first direction may be any direction pointing from the pressing portion **2232** to the electrode terminals **23** and perpendicular to the second direction, for example, the X direction shown in FIG. 7 to FIG. 11.

[0151] The battery cell **20** provided in the embodiments of this application effectively shields the pressing portion **2232** by means of having the second protective portion **212** protrude beyond the pressing portion **2232** along the first direction. This reduces the risk that metal burrs on the pressing portion **2232** extend outward or external metal wires have contact with the pressing portion **2232**, lowering the possibility of metal burrs on the pressing portion **2232** or external metal wires bridging between the pressing portion **2232** and exposed portions of the electrode terminals **23**, and thereby effectively reduces the risk of a short-circuit fault in the battery cell **20** and enhances the reliability of the battery cell **20**.

[0152] In some embodiments of this application, referring to FIG. 7, the insulator **25** includes a first insulating portion **251**. Along the first direction, the first insulating portion **251** is disposed between the pressing portion **2232** and the electrode terminals **23**.

[0153] Along the first direction, the first insulating portion **251** is disposed between the pressing portion **2232** and the electrode terminals **23**. In other words, the first insulating portion **251** is disposed between a hole wall of the second through hole **2123** and the second connecting segment **232** of the electrode terminals **23**, so that along the first direction, the first insulating portion **251** separates the second connecting segment **232** and the pressing portion **2232** to achieve insulation and separation between the fastener **223** and the electrode terminals **23**.

[0154] In this technical solution, the first insulating portion **251** insulates and separates the pressing portion **2232** and the electrode terminals **23** along the first direction, further reducing the risk that metal burrs on the pressing portion **2232** or external metal wires bridge between the pressing portion **2232** and exposed portions of the electrode terminals **23**. This further reduces the risk of a short-circuit fault in the battery cell **20** and enhances the reliability of the battery cell **20**.

[0155] In some embodiments of this application, referring to FIG. 7, at least a portion of a projection of the second protective portion **212** in the second direction overlaps with a projection of the first insulating portion **251** in the second direction.

[0156] A plane perpendicular to the Y direction shown in FIG. 7 is defined as a first projection plane, and the projection of the second protective portion **212** on the first projection plane at least partially overlaps with the projection of the first insulating portion **251** on the first projection plane. In other words, in the second direction, at least a portion of the second protective portion **212** protruding beyond the pressing portion **2232** is located above the first insulating portion **251**. The portion of the second protective portion **212** protruding beyond the pressing portion **2232** may be fixedly connected to the first insulating portion **251**, may abut against the first insulating portion **251**, or may be spaced apart from the first insulating portion **251** along the second direction.

[0157] In this technical solution, at least a portion of the second protective portion **212** covers the first insulating portion **251**. In this way, the pressing portion **2232** and the electrode terminals **23** are insulated and separated more reliably, further reducing the risk that metal burrs on the pressing portion **2232** or external metal wires bridge between the pressing portion **2232** and exposed portions of the electrode terminals **23**. This further reduces the risk of a short-circuit fault in the battery cell **20** and enhances the reliability of the battery cell **20**.

[0158] In some embodiments of this application, the second protective portion **212** is fixedly connected to the first insulating portion **251**.

[0159] It can be understood that at least a portion of the second protective portion **212** protruding beyond the pressing portion **2232** is fixedly connected to an end surface of the first insulating portion **251** facing away from the electrode assembly **24**. The manner in which the second protective portion **212** is fixedly connected to the first insulating portion **251** may include, but is not limited to, adhesion, welding, or the like, with no specific limitation herein.

[0160] With the second protective portion **212** fixedly connected to the first insulating portion **251**, under the cooperative action of the second protective portion **212** and the first insulating portion **251**, the pressing portion **2232** and the electrode terminals **23** are fully separated, further reducing the risk that metal burrs on the pressing portion **2232** or external metal wires bridge between the pressing portion **2232** and exposed portions of the electrode terminals **23**. This further reduces the risk of a short-circuit fault in the battery cell **20** and enhances the reliability of the battery cell **20**.

[0161] In some embodiments of this application, referring to FIG. 7, in the second direction, an end surface of the first insulating portion **251** facing away from the electrode assembly **24** is flush with a surface of the pressing portion **2232** facing away from the electrode assembly **24**, and the second protective portion **212** is fixedly connected to the end surface of the first insulating portion **251**.

[0162] In other words, in the second direction, the height position of the end surface of the first insulating portion **251** facing away from the electrode assembly **24** is the same as the height position of the surface of the pressing portion **2232** facing away from the electrode assembly **24**. With the second protective portion **212** fixedly connected to the end surface of the first insulating portion **251**, the second protective portion **212** and the first insulating portion **251** can be easily connected, while the second protective portion **212** is hardly bent, reducing the connection stress between the second protective portion **212** and the first insulating portion **251**. This reduces the risk of the second protective portion **212** detaching from the first insulating portion **251**.

[0163] In some other embodiments of this application, in the second direction, at least a portion of the first insulating portion **251** protrudes beyond the surface of the pressing portion **2232** facing away from the electrode assembly **24**.

[0164] In other words, in the second direction, the height of the end surface of the first insulating portion **251** facing away from the electrode assembly **24** is greater than the height of the surface of the pressing portion **2232** facing away from the electrode assembly **24**. As such, in the first direction, the first insulating portion **251** can better insulate and separate the pressing portion **2232** and the electrode terminals **23**, further reducing the risk that metal burrs on the pressing portion **2232** or external metal wires bridge between the pressing portion **2232** and exposed portions of the electrode terminals **23**. This further reduces the risk of a short-circuit fault in the battery cell **20** and enhances the reliability of the battery cell **20**.

[0165] In some embodiments of this application, referring to FIG. 7, the insulator **25** further includes a second insulating portion **252** connected to an end of the first insulating portion **251** facing the electrode assembly **24**, where along the first direction, the second insulating portion **252** is disposed between the connecting portion **2231** and the electrode terminals **23**.

[0166] Specifically, the second insulating portion **252** covers at least a portion of the foregoing flange portion **233**. For example, the second insulating portion **252** covers a surface of the flange portion **233** facing away from the electrode assembly **24**, the second insulating portion **252** covers a surface of the flange portion **233** facing away from the main body of the electrode terminals **23**, the second insulating portion **252** covers a surface of the flange portion **233** facing away from the pressing portion **2232**, or the second insulating portion **252** covers the surface of the flange portion **233** facing away from the electrode assembly **24**, the surface of the flange portion **233** facing away from the main body of the electrode terminals **23**, and the surface of the flange portion **233** facing away from the pressing portion **2232**. The pressing portion **2232** presses against the surface of the second insulating portion **252** facing away from the electrode assembly **24**. It can be understood that the pressing portion **2232** presses the second insulating portion **252** toward the electrode assembly **24**, and the second insulating portion **252** pushes against the flange portion **233**, thereby fixing the electrode terminals **23** on the wall portion of the housing **22**.

[0167] In this technical solution, the second insulating portion **252** insulates and separates the connecting portion **2231** and the electrode terminals **23**, thereby further reducing the risk of a short-circuit fault in the battery cell **20** and enhancing the reliability of the battery cell **20**.

[0168] In some embodiments of this application, referring to FIG. 11, the second insulating portion **252** includes a first insulating segment **2521**, a second insulating segment **2522**, and a third insulating segment **2523**, where the first insulating segment **2521** is connected to the first insulating portion **251**, the first insulating segment **2521**, the second insulating segment **2522**, and the third insulating segment **2523** enclose a cladding cavity, and at least a portion of the electrode terminals **23** is disposed within the cladding cavity. For example, the foregoing flange portion **233** is disposed within the cladding cavity, so that the second insulating portion **252** covers the surface of the flange portion **233** facing away from the electrode assembly **24**, the surface of the flange portion **233** facing away from the main body of the electrode terminals **23**, and the surface of the flange portion **233** facing away from the pressing portion **2232**.

[0169] In this technical solution, the connecting portion **2231** and the electrode terminals **23** are effectively insulated and separated, thereby further reducing the risk of a short-circuit fault in the battery cell **20** and enhancing the reliability of the battery cell **20**.

[0170] In some other embodiments of this application, referring to FIG. 8, the second protective portion **212** includes a cover body **2121** and a flange **2122**, where one side of the cover body **2121** along the first direction is connected to the first protective portion **211**, the other side of the cover body **2121** along the first direction is connected to the flange **2122**, and in the second direction, the cover body **2121** covers the surface of the pressing portion **2232** facing away from the electrode assembly **24** and the flange **2122** covers a side of the pressing portion **2232** facing the electrode terminals **23** along the first direction.

[0171] The cover body **2121** is a portion of the second protective portion **212** used to cover the surface of the pressing portion **2232** facing away from the electrode assembly **24**. The cover body

2121 may be fixedly connected to the surface of the pressing portion **2232** facing away from the electrode assembly **24**. For example, the cover body **2121** is adhered to the surface of the pressing portion **2232** facing away from the electrode assembly **24**. Alternatively, the cover body **2121** may simply abut against the surface of the pressing portion **2232** facing away from the electrode assembly **24**.

[0172] The flange **2122** is a portion of the second protective portion **212** used to cover the side of the pressing portion **2232** facing the electrode terminals **23** along the first direction. One side of the cover body **2121** along the first direction is connected to the first protective portion **211**, and the other side of the cover body **2121** along the first direction is connected to the flange **2122**. In other words, in the first direction, the flange **2122** is located on the side of the cover body **2121** facing away from the first protective portion **211**. The flange **2122** may be inclined relative to the cover body **2121**, or the flange **2122** may be perpendicular to the cover body **2121**. The flange **2122** may be fixedly connected to the side of the pressing portion **2232** facing the electrode terminals **23** along the first direction. For example, the cover body **2121** is adhered to the side of the pressing portion **2232** facing the electrode terminals **23** along the first direction. Alternatively, the flange **2122** may abut against the side of the pressing portion **2232** facing the electrode terminals **23** along the first direction, or the flange **2122** may be spaced apart from the side of the pressing portion **2232** facing the electrode terminals **23** along the first direction.

[0173] It can be understood that the pressing portion **2232** and the second connecting segment **232** of the electrode terminals **23** are spaced apart along the first direction, and at least a portion of the flange **2122** is disposed in the space between the pressing portion **2232** and the electrode terminals **23** along the first direction, thereby insulating and separating the pressing portion **2232** and the electrode terminals **23**.

[0174] In this technical solution, the flange **2122** separates the pressing portion **2232** and the electrode terminals **23** along the first direction, further reducing the risk that metal burrs on the pressing portion **2232** or external metal wires bridge between the pressing portion **2232** and exposed portions of the electrode terminals **23**. This further reduces the risk of a short-circuit fault in the battery cell **20** and enhances the reliability of the battery cell **20**.

[0175] In some embodiments of this application, referring to FIG. 8, when the insulator **25** includes the first insulating portion **251** and the first insulating portion **251** is disposed between the pressing portion **2232** and the electrode terminals **23** along the first direction, a gap **27** is formed between the first insulating portion **251** and the pressing portion **2232** along the first direction, and at least a portion of the flange **2122** is accommodated in the gap **27**.

[0176] In other words, the pressing portion **2232**, the flange **2122**, the first insulating portion **251**, and the second connecting segment **232** of the electrode terminals **23** are sequentially arranged along the first direction, where the first insulating portion **251** is spaced apart from the pressing portion **2232** along the first direction. It can be understood that the first insulating portion **251** may be spaced apart from the second connecting segment **232** along the first direction, or the first insulating portion **251** may abut against the second connecting segment **232** along the first direction.

[0177] In this technical solution, the flange **2122** and the first insulating portion **251** jointly insulate and separate the pressing portion **2232** and the electrode terminals **23** along the first direction, further reducing the risk that metal burrs on the pressing portion **2232** or external metal wires bridge between the pressing portion **2232** and exposed portions of the electrode terminals **23**. In addition, the flange **2122** is restricted within the gap **27** to reduce the risk of the flange **2122** detaching from the position between the pressing portion **2232** and the electrode terminals **23**, thereby further reducing the risk of a short-circuit fault in the battery cell **20** and enhancing the reliability of the battery cell **20**.

[0178] In some embodiments of this application, referring to FIG. 8, a length **L1** of the portion of the flange **2122** accommodated in the gap **27** is greater than a minimum width of the gap **27**.

[0179] The length **L1** of the portion of the flange **2122** accommodated in the gap **27** refers to the dimension of the portion of the flange **2122** accommodated in the gap **27** along the second direction. The minimum width of the gap **27** refers to the smallest dimension of the gap **27** along the first direction.

[0180] When the portion of the flange **2122** accommodated in the gap **27** abuts against the side of the pressing portion **2232** facing the electrode terminals **23** along the first direction, the length **L1** of the portion of the flange **2122** accommodated in the gap **27** is greater than the minimum width of the gap **27**. Therefore, after the flange **2122** flips toward the first insulating portion **251** to a certain extent, the first insulating portion **251** hinders further flipping of the flange **2122**, thereby restricting the flipping range of the flange **2122** within the gap **27** to a certain extent. This reduces the risk of the flange **2122** flipping out of the gap **27**.

[0181] It can be understood that, since the first insulating portion **251** hinders the flipping of the flange **2122** when the portion of the flange **2122** accommodated in the gap **27** abuts against the side of the pressing portion **2232** facing the electrode terminals **23** along the first direction. Similarly, when the portion of the flange **2122** accommodated in the gap **27** is spaced apart from the side of the pressing portion **2232** facing the electrode terminals **23** along the first direction, the first insulating portion **251** also hinders the flipping of the flange **2122** toward the first insulating portion **251**.

[0182] In some embodiments of this application, referring to FIG. **8**, a thickness of the flange **2122** is less than a width **W1** of the gap **27**.

[0183] The thickness of the flange **2122** refers to the dimension of the flange **2122** along the first direction when the flange **2122** is parallel to the second direction.

[0184] In this technical solution, the flange **2122** can be easily inserted into the gap **27**.

[0185] In some embodiments of this application, the flange **2122** is fixedly connected to the side of the pressing portion **2232** facing the electrode terminals **23** along the first direction.

[0186] The manner in which the flange **2122** is fixedly connected to the side of the pressing portion **2232** facing the electrode terminals **23** along the first direction may include, but is not limited to, adhesion, welding, or the like, with no specific limitation herein.

[0187] In this technical solution, the relative positions of the flange **2122** and the pressing portion **2232** are kept unchanged, so that the flange **2122** separates the pressing portion **2232** and the electrode terminals **23** along the first direction, further reducing the risk that metal burrs on the pressing portion **2232** or external metal wires bridge between the pressing portion **2232** and exposed portions of the electrode terminals **23**. This further reduces the risk of a short-circuit fault in the battery cell **20** and enhances the reliability of the battery cell **20**.

[0188] In some embodiments of this application, referring to FIG. **8**, a cross-section of the side of the pressing portion **2232** facing the electrode terminals **23** along the first direction is an arcuate structure in the second direction.

[0189] In other words, in the second direction, the surface of the side of the pressing portion **2232** facing the electrode terminals **23** along the first direction is an arcuate surface. Compared to a flat surface of the side of the pressing portion **2232** facing the electrode terminals **23** along the first direction, an arcuate surface effectively increases the area of connection between the flange **2122** and the pressing portion **2232**. This enhances the connection strength between the flange **2122** and the pressing portion **2232** and controls the lifting of the flange **2122**, thereby maintaining the relative positions of the flange **2122** and the pressing portion **2232** more effectively.

[0190] In some embodiments of this application, referring to FIG. **7**, a side of a joint between the first protective portion **211** and the second protective portion **212** facing the fastener **223** has a first fillet structure **214**.

[0191] The first fillet structure **214** refers to that the surface of the connection between the first protective portion **211** and the second protective portion **212** facing the fastener **223** is an arcuate surface, where the arcuate surface is recessed in a direction away from the fastener **223**. A radius

R1 of the first fillet structure **214** may be determined based on actual application needs. In some embodiments, the radius R1 of the first fillet structure **214** may include, but is not limited to, 0.4 mm, 0.5 mm, 0.6 mm, 0.7 mm, 0.8 mm, 0.9 mm, 1 mm, 1.1 mm, 1.2 mm, or 1.3 mm, with no specific limitation herein.

[0192] In this technical solution, the connection stress between the first protective portion **211** and the second protective portion **212** is effectively reduced, so that the second protective portion **212** is less likely to detach from the pressing portion **2232** due to lifting, thereby further reducing the risk of a short-circuit fault in the battery cell **20** and enhancing the reliability of the battery cell **20**.

[0193] In some embodiments of this application, referring to FIG. 7, a side of a joint between the connecting portion **2231** and the pressing portion **2232** facing the first fillet structure **214** has a second fillet structure **2233**.

[0194] The second fillet structure **2233** refers to that the surface of the connection between the connecting portion **2231** and the pressing portion **2232** facing the first fillet structure **214** is an arcuate surface, where the arcuate surface protrudes toward the protective member **21**. A radius R2 of the second fillet structure **2233** may be determined based on actual application needs. In some embodiments, the radius R2 of the second fillet structure **2233** may include, but is not limited to, 0.4 mm, 0.5 mm, 0.6 mm, 0.7 mm, 0.8 mm, 0.9 mm, 1 mm, 1.1 mm, 1.2 mm, or 1.3 mm, with no specific limitation herein.

[0195] In this technical solution, the connection stress between the connecting portion **2231** and the pressing portion **2232** is effectively reduced to control the risk of fracture of the connecting portion **2231** and the pressing portion **2232**, further enhancing the reliability of the battery cell **20**.

[0196] In some embodiments of this application, the radius R1 of the first fillet structure **214** is less than or equal to the radius R2 of the second fillet structure **2233**.

[0197] In this technical solution, the joint between the first protective portion **211** and the second protective portion **212** less interferes with the joint between the connecting portion **2231** and the pressing portion **2232**, so that the second protective portion **212** is less likely to detach from the pressing portion **2232** due to lifting. This further reduces the risk of a short-circuit fault in the battery cell **20** and enhances the reliability of the battery cell **20**.

[0198] In some other embodiments of this application, referring to FIG. 9, a side of a joint between the connecting portion **2231** and the pressing portion **2232** facing the first fillet structure **214** has a first chamfered structure **2234**.

[0199] The first chamfered structure **2234** refers to that the surface of the connection between the connecting portion **2231** and the pressing portion **2232** facing the first fillet structure **214** is an inclined surface, where the first chamfered structure **2234** is inclined relative to the first direction. The angle of inclination of the first chamfered structure **2234** relative to the first direction may include, but is not limited to, 30°, 45°, 60°, or the like, with no specific limitation herein. As shown in FIG. 9, the first chamfered structure **2234** extends obliquely upward from the surface of the connecting portion **2231** facing away from the electrode terminals **23** to the surface of the pressing portion **2232** facing away from the electrode assembly **24**. During the process of bending the fastener **223** using a tool to form the pressing portion **2232**, the tool is provided with an inclined surface adapted to the first chamfered structure **2234**, and the fastener **223** is pressed by this inclined surface to form the first chamfered structure **2234**. When the inclined surface presses the fastener **223**, the inclined surface on the fastener **223** applies a force toward the fastener **223** in a direction perpendicular to the first chamfered structure **2234**. The component of this force along the X direction facilitates the bending process of the fastener **223**, and the tool is easy to control due to the counterforce, so that the fastener **223** can be bent conveniently.

[0200] In this technical solution, the fastener **223** can be easily bent. After the first chamfered structure **2234** is formed, a portion of the material of the pressing portion **2232** displaces toward the electrode terminals **23**, effectively increasing the downward pressure exerted by the pressing portion **2232** on the insulator **25**. In this way, the electrode terminals **23** can be fixed more firmly

on the wall portion of the housing **22**.

[0201] In some embodiments of this application, referring to FIG. **9**, a projection of the first chamfered structure **2234** in the second direction has a first width **W2**, and a projection of the first chamfered structure **2234** in the first direction has a second width **W3**; where the radius **R1** of the first fillet structure **214** is less than or equal to the first width **W2**, and the radius **R1** of the first fillet structure **214** is less than or equal to the second width **W3**.

[0202] A plane perpendicular to the Y direction shown in FIG. **9** is defined as a first projection plane, and the projection of the first chamfered structure **2234** on the first projection plane has a first width **W2**. The size of the first width **W2** of the projection of the first chamfered structure **2234** on the first projection plane may be determined based on actual application needs. In some embodiments, the first width **W2** may include, but is not limited to, 0.4 mm, 0.5 mm, 0.6 mm, 0.7 mm, 0.8 mm, 0.9 mm, 1 mm, 1.1 mm, 1.2 mm, or 1.3 mm, with no specific limitation herein. It should be noted that the radius **R1** of the first fillet structure **214** is less than or equal to the first width **W2**.

[0203] A plane perpendicular to the X direction shown in FIG. **9** is defined as a second projection plane, and the projection of the first chamfered structure **2234** on the second projection plane has a second width **W3**. The size of the second width **W3** of the projection of the first chamfered structure **2234** on the second projection plane may be determined based on actual application needs. In some embodiments, the second width **W3** may include, but is not limited to, 0.4 mm, 0.5 mm, 0.6 mm, 0.7 mm, 0.8 mm, 0.9 mm, 1 mm, 1.1 mm, 1.2 mm, or 1.3 mm, with no specific limitation herein. It should be noted that the radius **R1** of the first fillet structure **214** is less than or equal to the second width **W3**.

[0204] In this technical solution, the joint between the first protective portion **211** and the second protective portion **212** less interferes with the joint between the connecting portion **2231** and the pressing portion **2232**, so that the second protective portion **212** is less likely to detach from the pressing portion **2232** due to lifting, thereby further reducing the risk of a short-circuit fault in the battery cell **20** and enhancing the reliability of the battery cell **20**.

[0205] In some other embodiments of this application, referring to FIG. **10**, a side of the joint between the connecting portion **2231** and the pressing portion **2232** facing the protective member **21** has a first chamfered structure **2234**, a side of the joint between the first protective portion **211** and the second protective portion **212** facing the first chamfered structure **2234** has a second chamfered structure **215**; the projection of the first chamfered structure **2234** in the second direction has a first width **W2**, the projection of the first chamfered structure **2234** in the first direction has a second width **W3**; a projection of the second chamfered structure **215** in the second direction has a third width **W4**, a projection of the second chamfered structure **215** in the first direction has a fourth width **W5**; the third width **W4** is less than or equal to the first width **W2**, and the fourth width **W5** is less than or equal to the second width **W3**.

[0206] The second chamfered structure **215** refers to the surface of the connection between the first protective portion **211** and the second protective portion **212** facing the first chamfered structure **2234** being an inclined surface, where the second chamfered structure **215** is inclined relative to the first direction. The angle of inclination of the second chamfered structure **215** relative to the first direction may include, but is not limited to, 30°, 45°, 60°, or the like, with no specific limitation herein. For example, as shown in FIG. **10**, the second chamfered structure **215** extends obliquely upward from the surface of the first protective portion **211** facing the fastener **223** to the surface of the second protective portion **212** facing the fastener **223**.

[0207] A plane perpendicular to the Y direction shown in FIG. **10** is defined as a first projection plane, the projection of the first chamfered structure **2234** on the first projection plane has a first width **W2**, and the projection of the second chamfered structure **215** on the first projection plane has a third width **W4**. The size of the first width **W2** of the projection of the first chamfered structure **2234** on the first projection plane may be determined based on actual application needs. In

some embodiments, the first width **W2** may include, but is not limited to, 0.4 mm, 0.5 mm, 0.6 mm, 0.7 mm, 0.8 mm, 0.9 mm, 1 mm, 1.1 mm, 1.2 mm, or 1.3 mm, with no specific limitation herein. Similarly, the size of the third width **W4** of the projection of the second chamfered structure **215** on the first projection plane may be determined based on actual application needs. In some embodiments, the third width **W4** may include, but is not limited to, 0.4 mm, 0.5 mm, 0.6 mm, 0.7 mm, 0.8 mm, 0.9 mm, 1 mm, 1.1 mm, 1.2 mm, or 1.3 mm, with no specific limitation herein. It should be noted that the third width **W4** is less than or equal to the first width **W2**.

[0208] A plane perpendicular to the X direction shown in FIG. **10** is defined as a second projection plane, the projection of the first chamfered structure **2234** on the second projection plane has a second width **W3**, and the projection of the second chamfered structure **215** on the second projection plane has a fourth width **W5**. The size of the second width **W3** of the projection of the first chamfered structure **2234** on the second projection plane may be determined based on actual application needs. In some embodiments, the second width **W3** may include, but is not limited to, 0.4 mm, 0.5 mm, 0.6 mm, 0.7 mm, 0.8 mm, 0.9 mm, 1 mm, 1.1 mm, 1.2 mm, or 1.3 mm, with no specific limitation herein. Similarly, the size of the fourth width **W5** of the projection of the second chamfered structure **215** on the second projection plane may be determined based on actual application needs. In some embodiments, the fourth width **W5** may include, but is not limited to, 0.4 mm, 0.5 mm, 0.6 mm, 0.7 mm, 0.8 mm, 0.9 mm, 1 mm, 1.1 mm, 1.2 mm, or 1.3 mm, with no specific limitation herein. It should be noted that the fourth width **W5** is less than or equal to the second width **W3**.

[0209] In this technical solution, the joint between the first protective portion **211** and the second protective portion **212** less interferes with the joint between the connecting portion **2231** and the pressing portion **2232**, reducing the risk of the second protective portion **212** detaching from the pressing portion **2232** due to lifting. This further reduces the risk of a short-circuit fault in the battery cell **20** and enhances the reliability of the battery cell **20**.

[0210] In some embodiments of this application, referring to FIG. **11**, the first protective portion **211** and the connecting portion **2231** each have an annular structure, the connecting portion **2231** is annularly disposed around the first through hole **2221**, the first protective portion **211** is annularly disposed around the connecting portion **2231**, and an inner diameter **L2** of the first protective portion **211** is greater than or equal to an outer diameter **L3** of the connecting portion **2231**.

[0211] The size of the inner diameter **L2** of the first protective portion **211** may be determined based on actual application needs. In some embodiments, the inner diameter **L2** of the first protective portion **211** may include, but is not limited to, 10 mm, 15 mm, 20 mm, 25 mm, or 30 mm, with no specific limitation herein. Similarly, the size of the outer diameter **L3** of the connecting portion **2231** may be determined based on actual application needs. In some embodiments, the outer diameter **L3** of the connecting portion **2231** may include, but is not limited to, 10 mm, 15 mm, 20 mm, 25 mm, or 30 mm, with no specific limitation herein. It should be noted that the inner diameter **L2** of the first protective portion **211** is greater than or equal to the outer diameter **L3** of the connecting portion **2231**.

[0212] In this technical solution, interference between the first protective portion **211** and the connecting portion **2231** is reduced, lowering the possibility of the second protective portion **212** being lifted due to lifting of the first protective portion **211**. This effectively reduces the risk of the second protective portion **212** detaching from the pressing portion **2232**, thereby further reducing the risk of a short-circuit fault in the battery cell **20** and further enhancing the reliability of the battery cell **20**.

[0213] In some embodiments of this application, referring to FIG. **7**, the protective member **21** further includes a third protective portion **213** covering the wall portion of the housing **22**, the third protective portion **213** is connected to the first protective portion **211**, and a side of a joint between the third protective portion **213** and the first protective portion **211** facing the fastener **223** has a third fillet structure **216**.

[0214] The third fillet structure **216** refers to that the surface of the connection between the third protective portion **213** and the first protective portion **211** facing the fastener **223** is an arcuate surface, where the arcuate surface protrudes toward the fastener **223**. The radius **R3** of the third fillet structure **216** may be determined based on actual application needs. In some embodiments, the radius **R3** of the third fillet structure **216** may include, but is not limited to, 0.4 mm, 0.5 mm, 0.6 mm, 0.7 mm, 0.8 mm, 0.9 mm, 1 mm, 1.1 mm, 1.2 mm, or 1.3 mm, with no specific limitation herein.

[0215] In this technical solution, the connection stress between the third protective portion **213** and the first protective portion **211** is effectively reduced, lowering the possibility of the second protective portion **212** being lifted due to lifting of the first protective portion **211**. This effectively reduces the risk of the second protective portion **212** detaching from the pressing portion **2232**, thereby further reducing the risk of a short-circuit fault in the battery cell **20** and enhancing the reliability of the battery cell **20**.

[0216] In some embodiments of this application, referring to FIG. 7, a side of a joint between the connecting portion **2231** and the wall portion of the housing **22** facing the third fillet structure **216** has a fourth fillet structure **224**.

[0217] The fourth fillet structure **224** refers to that the surface of the connection between the connecting portion **2231** and the wall portion of the housing **22** facing the third fillet structure **216** is an arcuate surface, where the arcuate surface is recessed in a direction away from the protective member **21**. The radius **R4** of the fourth fillet structure **224** may be determined based on actual application needs. In some embodiments, the radius **R4** of the fourth fillet structure **224** may include, but is not limited to, 0.4 mm, 0.5 mm, 0.6 mm, 0.7 mm, 0.8 mm, 0.9 mm, 1 mm, 1.1 mm, 1.2 mm, or 1.3 mm, with no specific limitation herein.

[0218] In this technical solution, the connection stress between the connecting portion **2231** and the wall portion is effectively reduced to control the risk of fracture of the connecting portion **2231** and the wall portion, further enhancing the reliability of the battery cell **20**.

[0219] In some embodiments of this application, the radius **R3** of the third fillet structure **216** is greater than or equal to the radius **R4** of the fourth fillet structure **224**.

[0220] In this technical solution, the joint between the first protective portion **211** and the third protective portion **213** less interferes with the joint between the connecting portion **2231** and the wall portion, lowering the possibility of the second protective portion **212** being lifted due to lifting of the first protective portion **211**. This effectively reduces the risk of the second protective portion **212** detaching from the pressing portion **2232**, thereby further reducing the risk of a short-circuit fault in the battery cell **20** and enhancing the reliability of the battery cell **20**.

[0221] In some embodiments of this application, the first protective portion **211**, the second protective portion **212**, and the third protective portion **213** are integrally formed. For example, the first protective portion **211**, the second protective portion **212**, and the third protective portion **213** are integrally formed through an injection molding process.

[0222] In this technical solution, the manufacturing process of the protective member **21** is effectively simplified, thereby improving the manufacturing efficiency of the protective member **21** and reducing the manufacturing costs of the protective member **21**.

[0223] In some embodiments of this application, the pressing portion **2232** has an annular structure and is annularly disposed around the electrode terminals **23**.

[0224] The pressing portion **2232** extends along the circumferential direction of the electrode terminals **23** and forms an annular structure. It can be understood that the pressing portion **2232** is annular, and the pressing portion **2232** may be circular, elliptical, polygonal, or in other shapes, with no specific limitation herein.

[0225] In this technical solution, the pressing portion **2232** is less likely to flip outward, so that the electrode terminals **23** can be fixed more firmly on the wall portion of the housing **22**.

[0226] In some embodiments of this application, referring to FIG. 7, the battery cell **20** further

includes a sealing member **26**, where at least a portion of the sealing member **26** is located between the wall portion and the electrode terminals **23**.

[0227] The sealing member **26** is used to seal a gap between the wall portion of the housing **22** and the electrode terminals **23**. The sealing member **26** may be entirely clamped between the electrode terminals **23** and the wall portion of the housing **22**, or a portion of the sealing member **26** may be clamped between the electrode terminals **23** and the wall portion of the housing **22** while another portion is clamped between the electrode terminals **23** and the connecting portion **2231**. Optionally, the sealing member **26** may include, but is not limited to, a sealing ring, a sealing gasket, or the like, with no specific limitation herein.

[0228] Specifically, when the insulator **25** includes the second insulating portion **252** and the electrode terminals **23** include the flange portion **233**, the second insulating portion **252** covers the flange portion **233**, the pressing portion **2232** presses against the second insulating portion **252**, and the pressing portion **2232** applies a pressure to the second insulating portion **252**. This pressure is transmitted through the second insulating portion **252** to the flange portion **233** of the electrode terminals **23**, and the electrode terminals **23** press the sealing member **26** toward the wall portion of the housing **22**, so that the sealing member **26** is clamped between the electrode terminals **23** and the wall portion of the housing **22**. The sealing member **26** compresses and deforms under pressure, sealing the gap between the wall portion of the housing **22** and the electrode terminals **23**.

[0229] In this technical solution, the sealing member **26** seals the gap between the wall portion and the electrode terminals **23**, reducing the risk of electrolyte leakage from between the electrode terminals **23** and the body within the housing **22**. This helps enhance the reliability of the battery cell **20**.

[0230] In some embodiments of this application, referring to FIG. **4**, the housing **22** includes a housing body **221** and an end cap **222**, one end of the housing body **221** has an opening, the end cap **222** covers the opening, the housing body **221** includes a side wall and a bottom wall, the side wall is annularly disposed outside the electrode assembly **24**, the bottom wall is disposed opposite the opening, and the wall portion is the end cap **222**, the bottom wall, or the side wall.

[0231] The side wall of the housing body **221** encloses the internal environment of the housing **22**, both ends of the side wall have openings, the bottom wall of the housing body **221** covers one opening of the side wall, and the end cap **222** covers the other opening of the side wall. The electrode terminals **23** may be disposed on the end cap **222**, the side wall of the housing body **221**, or the bottom wall of the housing body **221**, depending on actual needs.

[0232] According to a second aspect, an embodiment of this application further provides a battery **100**, including the foregoing battery cell **20**.

[0233] A beneficial effect of the battery **100** provided in the embodiment of this application is that: with the foregoing battery cell **20**, the battery **100** provided in the embodiment of this application has higher reliability.

[0234] According to a third aspect, an embodiment of this application further provides an electric apparatus, including the foregoing battery **100**.

[0235] A beneficial effect of the electric apparatus provided in the embodiment of this application is that: with the foregoing battery **100** adopted, the electric apparatus provided in the embodiment of this application has higher reliability.

[0236] The foregoing descriptions are merely preferable embodiments of this application, but are not intended to limit this application. Any modification, equivalent replacement, or improvement made without departing from the spirit and principle of this application shall fall within the protection scope of this application.

Claims

- 1.** A battery cell, wherein the battery cell comprises: an electrode assembly; a housing configured to accommodate the electrode assembly, wherein the housing comprises a wall portion and a fastener, the fastener comprising a connecting portion connected to the wall portion and a pressing portion connected to the connecting portion, the connecting portion and the pressing portion jointly defining a cavity; electrode terminals electrically connected to the electrode assembly, wherein at least a portion of the electrode terminals is accommodated in the cavity; an insulator disposed between the fastener and the electrode terminals, wherein the pressing portion presses against the electrode terminals through the insulator to fix the electrode terminals on the wall portion; and a protective member comprising a first protective portion and a second protective portion connected to each other, wherein the first protective portion covers the connecting portion, the second protective portion covers the pressing portion, the second protective portion protrudes beyond the pressing portion along a first direction, and the first direction is a direction pointing from the pressing portion to the electrode terminals and perpendicular to a thickness direction of the wall portion.
- 2.** The battery cell according to claim 1, wherein the insulator comprises a first insulating portion, wherein along the first direction, the first insulating portion is disposed between the pressing portion and the electrode terminals.
- 3.** The battery cell according to claim 2, wherein at least a portion of a projection of the second protective portion in the thickness direction of the wall portion overlaps with a projection of the first insulating portion in the thickness direction of the wall portion.
- 4.** The battery cell according to claim 3, wherein the second protective portion is fixedly connected to the first insulating portion.
- 5.** The battery cell according to claim 4, wherein in the thickness direction of the wall portion, an end surface of the first insulating portion facing away from the electrode assembly is flush with a surface of the pressing portion facing away from the electrode assembly, and the second protective portion is fixedly connected to the end surface of the first insulating portion.
- 6.** The battery cell according to claim 2, wherein in the thickness direction of the wall portion, at least a portion of the first insulating portion protrudes beyond the surface of the pressing portion facing away from the electrode assembly.
- 7.** The battery cell according to claim 2, wherein the insulator further comprises a second insulating portion connected to an end of the first insulating portion facing the electrode assembly, and along the first direction, the second insulating portion is disposed between the connecting portion and the electrode terminals.
- 8.** The battery cell according to claim 7, wherein the second insulating portion comprises a first insulating segment, a second insulating segment, and a third insulating segment, wherein the first insulating segment is connected to the first insulating portion, the first insulating segment, the second insulating segment, and the third insulating segment enclose a cladding cavity, and at least a portion of the electrode terminals is disposed within the cladding cavity.
- 9.** The battery cell according to claim 1, wherein the second protective portion comprises a cover body and a flange, wherein one side of the cover body along the first direction is connected to the first protective portion, the other side of the cover body along the first direction is connected to the flange, and in the thickness direction of the wall portion, the cover body covers the pressing portion and the flange covers a side of the pressing portion facing the electrode terminals along the first direction.
- 10.** The battery cell according to claim 9, wherein the insulator comprises a first insulating portion, wherein the first insulating portion is disposed between the pressing portion and the electrode terminals along the first direction, a gap is formed between the first insulating portion and the pressing portion, and at least a portion of the flange is accommodated in the gap.
- 11.** The battery cell according to claim 10, wherein a length of the portion of the flange

accommodated in the gap is greater than a minimum width of the gap.

- 12.** The battery cell according to claim 10, wherein a thickness of the flange is less than a width of the gap.
 - 13.** The battery cell according to claim 9, wherein the flange is fixedly connected to the side of the pressing portion facing the electrode terminals along the first direction.
 - 14.** The battery cell according to claim 13, wherein a cross-section of the side of the pressing portion facing the electrode terminals along the first direction is an arcuate structure in the thickness direction of the wall portion.
 - 15.** The battery cell according to claim 1, wherein a side of a joint between the first protective portion and the second protective portion facing the fastener has a first fillet structure.
 - 16.** The battery cell according to claim 15, wherein a side of a joint between the connecting portion and the pressing portion facing the first fillet structure has a second fillet structure.
 - 17.** The battery cell according to claim 16, wherein a radius of the first fillet structure is less than or equal to a radius of the second fillet structure.
 - 18.** The battery cell according to claim 15, wherein a side of a joint between the connecting portion and the pressing portion facing the first fillet structure has a first chamfered structure.
 - 19.** The battery cell according to claim 18, wherein a projection of the first chamfered structure in the thickness direction of the wall portion has a first width, and a projection of the first chamfered structure in the first direction has a second width; wherein the radius of the first fillet structure is less than or equal to the first width, and the radius of the first fillet structure is less than or equal to the second width.
 - 20.** The battery cell according to claim 1, wherein the pressing portion has an annular structure and is annularly disposed around the electrode terminals.
 - 21.** The battery cell according to claim 1, wherein the battery cell further comprises a sealing member, and at least a portion of the sealing member is located between the wall portion and the electrode terminals.
 - 22.** The battery cell according to claim 1, wherein the housing comprises a housing body and an end cap, wherein one end of the housing body has an opening, the end cap covers the opening, the housing body comprises a side wall and a bottom wall, the side wall is annularly disposed outside the electrode assembly, the bottom wall is disposed opposite the opening, and the wall portion is the end cap, the bottom wall, or the side wall.
 - 23.** A battery, wherein the battery comprises the battery cell according to claim 1.
-