

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250279927

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Sarath; Arjun et al.

System And Method To Reduce Database Interruptions In A Service-Based Architecture

Abstract

An apparatus is communicatively coupled to a plurality of databases in a service-based architecture and comprises a memory and a processor. The memory stores multiple configuration commands. The processor is configured to generate a request to establish a communication session in which a network component accesses a first database and a second database based at least in part upon a configuration command of the configuration commands. The network component exchanges connectivity signals with the first database and the second database. The first database provides database operations in response to the connectivity signals exchanged with the network component. The first database reports to the second database that the database operations are provided. The processor is further configured to, in response to determining that the communication session between the network component and the first database is lost, maintain the communication session to access the second database.

Inventors: Sarath; Arjun (Littleton, CO), Shahdad; Mohammad Dawood (Aurora, CO)

Applicant: DISH Wireless L.L.C. (Englewood, CO)

Family ID: 93651789

Appl. No.: 19/209488

Filed: May 15, 2025

Related U.S. Application Data

parent US continuation 18326858 20230531 parent-grant-document US 12348355 child US 19209488

Publication Classification

Int. Cl.: H04L41/0654 (20220101); H04L67/1097 (20220101); H04L67/141 (20220101)

Background/Summary

RELATED APPLICATION AND CLAIM TO PRIORITY [0001] This present application is a continuation that claims priority to U.S. Non-Provisional application Ser. No. 18/326,858 filed May 31, 2023, entitled “SYSTEM AND METHOD TO REDUCE DATABASE INTERRUPTIONS IN A SERVICE-BASED ARCHITECTURE,” which is incorporated herein by reference.

TECHNICAL FIELD

[0002] The present disclosure relates generally to operation of a communication system in a service-based architecture, and more specifically to a system and a method to reduce or to prevent database interruptions in the service-based architecture.

BACKGROUND

[0003] In some wireless communications systems, groups of network components may be configured to perform specific Network Functions (NFs) in a network. Further, each network component may be configured to perform multiple communication transmissions across the network in accordance with routing and configuration information provided by a repository. The repository is connected to a database that stores the routing and configuration information for the groups of network components.

[0004] In the event of a repository interruption in which the repository loses at least partial connection to the network, the group of network components is cut off from the routing and configuration information provided by the repository. In this regard, the group of network components is unable to perform any communication transmissions across the network because the repository is unable to communicate the routing and configuration information to the group of network components. Previous technologies fail to provide reliable solutions to reduce or to prevent repository interruptions when the repository is unable to communicate with the network. As a result, repository interruptions currently lead to large periods of downtime for the entire network.

[0005] In the event of a database interruption in which the database loses at least partial connection to the network, the group of network components is cut off from the routing and configuration information stored in the database. In this regard, the group of network components is unable to perform any communication transmissions across the network because the repository is unable to access the routing and configuration information from the database. Previous technologies fail to provide reliable solutions to reduce or to prevent database interruptions when the database is unable to communicate with the network. As a result, database interruptions currently lead to large periods of downtime for the entire network.

SUMMARY OF THE DISCLOSURE

[0006] In one or more embodiments, a system and a method described herein provide several practical applications and technical advantages that overcome current technical problems in wireless communication technology. In particular, the system and the method are integrated into multiple practical applications improving speed, quality, and reliability of wireless communications systems. In some embodiments, wireless communication systems comprise one or more network components configured to perform specific Network Functions (NFs) in a network. The network may comprise a Service-Based Architecture (SBA). Further, each network component may be configured to perform multiple communication transmissions across the network in accordance with routing and configuration information provided by a specific network component performing

a Network Repository Function (NRF). The specific network component may be communicatively coupled to a specific database that stores the routing and configuration information for the one or more of network components.

[0007] In some embodiments, the system and the method provide reliable solutions to reduce or to prevent communication interruptions to the NRF when one or more specific network functions attempt to reach the NRF or when the specific network component performing the NRF is unable to communicate with the network (hereinafter referred to as NRF interruptions). As a result, the speed, quality, and reliability of wireless communications systems are improved by reducing, preventing, or eliminating periods of downtime for the entire network. For example, in the event of an NRF interruption in which the specific network component loses at least partial connection to the network, the system and the method reduce, prevent, or eliminate any additional network components to be cut off from the routing and configuration information stored in the database the group of network components is cut off from the routing and configuration information provided by the specific network. In this regard, the system and the method enable the additional network components to perform any communication transmissions across the network because the specific network component or a backup network component is able to communicate the routing and configuration information to the group of network components with no or little downtime despite any NRF interruptions.

[0008] In other embodiments, the system and the method provide reliable solutions to reduce or to prevent database interruptions when the specific database associated with the specific network component performing the NRF is unable to communicate with the network. As a result, the speed, quality, and reliability of wireless communications systems are improved by reducing, preventing, or eliminating periods of downtime for the entire network. For example, in the event of a database interruption in which the database loses at least partial connection to the network, the system and the method reduce, prevent, or eliminate any additional network components to be cut off from the routing and configuration information stored in the database. In this regard, the system and the method enable the additional network components to perform any communication transmissions across the network because the specific network component is able to access the routing and configuration information from a backup database with no or little downtime despite any database interruptions.

[0009] Reducing Network Function Interruptions In one or more embodiments, the system and the method disclosed herein reduce network function interruptions in the network comprising the SBA. In particular, the system and the method provide a specific network component performing the NRF as part of the SBA. In performing the NRF, the specific network component maintains NF profiles and corresponding configuration operations in the network. In some embodiments, the specific network component is communicatively coupled with a specific database that comprises routing and connections associated with every NF in the SBA. In this regard, the specific network component may be configured to provide routing and configuring information for other network components to establish initial communication sessions between two or more network components. Further, the specific network component may be configured to provide backup routing and configuring information for the other network components to establish backup communication sessions between the two or more network components.

[0010] In one or more embodiments, the system and the method are configured to reduce NRF interruptions by establishing backup communication sessions in the event that an initial communication session is lost. In some embodiments, the NRF interruptions are events in which the NRF cannot be performed in relation to the network. For example, the NRF interruptions may comprise that the specific network component is disconnected from the SBA or that the specific network component is unable to continue performing the NRF. To identify an NRF interruption in the network, the system and the method may be configured to identify that certain connectivity signals are not received from the specific network component. If the certain connectivity signals

are not received, then the system and the method may be configured to determine that the NRF interruption occurred. Upon identifying the NRF interruption in the network, the system and the method may be configured to execute a script that automatically establishes backup communication sessions where initial communication sessions are lost. The backup communication sessions may be established using local provisioning parameters that are backup copies of configuration commands used to establish the initial communication sessions. In some embodiments, the system and the method may dynamically update the local provisioning parameters any time a new configuration command is generated via the NRF. In other embodiments, the system and the method may dynamically or periodically update the local provisioning parameters over time.

[0011] In one or more embodiments, the system and the method described herein are integrated into a practical application to reduce NRF interruptions in the SBA. In this regard, the system and the method are integrated into a practical application of providing local provisioning parameters to establish backup communication sessions that replace initial communication sessions that are determined to be lost in an NRF interruption. In particular, the system and the method provide a script that automatically replaces lost communication sessions with new communication sessions such that downtime is severely reduced in the SBA upon determining NRF interruptions.

[0012] In addition, the system and method described herein are integrated into a technical advantage of increasing processing speeds in a computer system in the SBA, because processors associated with the system and the method comprise scripts that automatically reestablish communication sessions in between network components. In the scripts, the system and the method may provide local provisioning parameters that replace configuration commands for routing and configuring communications of the network components. As a result, processing speed is increased because the system and the method may be automatically configured with the local provisioning instead of waiting for initial communication sessions to be reestablished using the configuration commands or estimating possible alternative configuration commands to reestablish the initial communication sessions. Under these improvements, the system and the method provide a practical application of maintaining operations in the network for longer periods of time by reducing downtime caused by NRF interruptions.

[0013] In one or more embodiments, the system and the method may be performed by an apparatus, such as a server, communicatively coupled to multiple network components in the SBA. Further, the system may be a wireless communication system, that comprises the apparatus. In addition, the system and the method may be performed as part of a process performed by the apparatus communicatively coupled to the network components in the SBA. As a non-limiting example, the apparatus may comprise a memory and a processor. The memory is configured to store multiple configuration commands, multiple local provisioning parameters, and a configuration scripts. The configuration commands may be configured to establish one or more initial communication sessions between two or more network components of the network components. The local provisioning parameters may be configured to establish one or more backup communication sessions. Each local provisioning parameter may be a backup copy of a corresponding configuration command. The configuration script may be configured to instruct the network components to establish the one or more initial communication sessions based at least in part upon the local provisioning parameters. The processor may be communicatively coupled to the memory and configured to generate a first request to establish an initial communication session between a first network component of the plurality of network components and a second network component of the plurality of network components. The processor may be configured to establish the initial communication session between the first network component and the second network component based at least in part upon a first configuration command of the configuration commands; determine that the initial communication session is lost based at least in part upon identifying an interruption in the initial communication session; and in response to determining that the initial communication session is lost, execute the configuration script to instruct the first

network component to establish a backup communication session based at least in part upon a first local provisioning parameter of the local provisioning parameters.

Further Reducing Network Function Interruptions

[0014] In one or more embodiments, the system and the method disclosed herein reduce, prevent, or eliminate network function interruptions in the network comprising the SBA. In particular, the system and the method provide a primary network component or a secondary (e.g., backup) network component performing the NRF as part of the SBA. In performing the NRF, the primary network component maintains NF profiles and corresponding configuration operations in the network. In some embodiments, the primary network component provides a copy of operations related to maintaining the NF profiles to the secondary network component. The primary network component and the backup network component may be communicatively coupled with a specific database that comprises routing and connections associated with every NF in the SBA. In this regard, the primary network component may be configured to provide routing and configuring information for other network components to establish communication sessions between two or more network components. Further, the secondary network component may be configured to provide backed up routing and configuring information for other network components to establish communication sessions between two or more network components if the primary network component is not available due to an NRF interruption. As a result, the secondary network component may be configured to provide backup routing and configuring information to establish communication sessions between the two or more network components.

[0015] In one or more embodiments, the system and the method are configured to reduce, prevent, or eliminate NRF interruptions by controlling backup network components to reestablish or maintain communication sessions in the event that a given communication session is lost. In some embodiments, the NRF interruptions are events in which the NRF cannot be performed in relation to the network. For example, the NRF interruptions may comprise that the primary network component is disconnected from the SBA or that the primary network component is unable to continue performing the NRF. To identify an NRF interruption in the network, the system and the method may be configured to identify that certain connectivity signals are not received from the primary network component. If the certain connectivity signals are not received, then the system and the method may be configured to determine that the NRF interruption occurred. Upon identifying the NRF interruption in the network, the system and the method may be configured to maintain a communication session with the secondary network component even if the communication session with the primary network component is lost.

[0016] The secondary network component may be a backup network component that establishes a communication session with other network components at a same time the primary network component establishes a corresponding communication session. In this regard, the primary network component and the secondary network component may establish individual communication sessions with a given network component. Further, the primary network component and the secondary network component may establish a communication link to copy operations from the primary network component to the secondary network component. In the event that the communication session is lost between the primary network component and the given network component, the secondary network component maintains the corresponding communication session with the given network component. As a result, the given network component may not experience any effects caused by the NRF interruptions. In some embodiments, the primary network component may dynamically update the NRF operations to the secondary network component. In other embodiments, the primary network component may periodically update the NRF operations to the secondary network component.

[0017] In one or more embodiments, the system and the method described herein are integrated into a practical application to reduce, prevent, or to eliminate NRF interruptions in the SBA. In this regard, the system and the method are integrated into a practical application of providing a backup

network component configured to perform any or all operations associated with the primary network component when communications with the primary network component are determined to be lost in an NRF interruption. In particular, the system and the method provide backup routing and configurations via the secondary network component in response to losing connectivity with the primary network component such that downtime is severely reduced in the SBA upon determining NRF interruptions associated with the primary network component.

[0018] In addition, the system and method described herein are integrated into a technical advantage of increasing processing speeds in a computer system in the SBA, because processors associated with the system and the method comprise automatically transitioning from the primary network component to the secondary network component when connectivity to the primary network component is lost. In some embodiments, the system and the method comprise the secondary network component to provide backup routing and configuring information of the network components. As a result, processing speed is increased because the system and the method may automatically provide the routing and configuring information to any network components in the network instead of awaiting to reestablish new communication sessions or estimating possible alternative configuration commands to reestablish the communication sessions. Under these improvements, the system and the method provide a practical application of maintaining operations in the network for longer periods of time by reducing, preventing, or eliminating downtime caused by NRF interruptions.

[0019] In one or more embodiments, the system and the method may be performed by an apparatus, such as a server, communicatively coupled to multiple network components in the SBA. Further, the system may be a wireless communication system, that comprises the apparatus. In addition, the system and the method may be performed as part of a process performed by the apparatus communicatively coupled to the network components in the SBA. As a non-limiting example, the apparatus may comprise a memory and a processor. The memory is configured to store multiple configuration commands configured to establish one or more communication sessions between two or more network components of the network components. The processor may be communicatively coupled to the memory and configured to generate a request to establish a communication session between a first network component, a second network component, and a third network component. The processor may be configured to establish the communication session between the first network component, the second network component, and the third network component based at least in part upon a first configuration command of the configuration commands. Concurrently with the communication session, the first network component may exchange first connectivity signals with the second network component and the third network component; the second network component may perform first session operations in response to the first plurality of connectivity signals exchanged with the first network component; and the second network component may report to the third network component that the first session operations are performed. In addition, the processor may be configured to determine whether the communication session is lost between the first network component and the second network component based at least in part upon identifying an interruption in the communication session; and in response to determining that the communication session between the first network component and the second network component is lost, maintain the communication session between the first network component and the third network component.

Reducing Database Interruptions

[0020] In one or more embodiments, the system and the method disclosed herein reduce, prevent, or eliminate database interruptions in the network comprising the SBA. In particular, the system and the method provide a primary database or a secondary (e.g., backup) database performing database operations as part of the SBA. In performing the database operations, the primary database stores and provides NF profiles and corresponding configuration commands in the network. In some embodiments, the primary database provides a copy of operations related to

storing the NF profiles to the secondary database. The primary database and the backup database may be communicatively coupled with a specific network component that performs the NRF in the SBA. In this regard, the primary database may be configured to store or provide routing and configuring information for other network components to establish communication sessions between two or more network components. Further, the secondary database may be configured to store or provide backed up routing and configuring information for other network components to establish communication sessions between two or more network components if the primary database is not available due to a database interruption. As a result, the secondary database may be configured to store or provide backup routing and configuring information to establish communication sessions between the two or more network components.

[0021] In one or more embodiments, the system and the method are configured to reduce, prevent, or eliminate database interruptions by controlling backup databases to maintain information associated with communication sessions in the event that a given communication session is lost. In some embodiments, the database interruptions are events in which the database operations cannot be performed in relation to the network. For example, the database interruptions may comprise that the primary database is disconnected from the SBA or that the primary database is unable to continue storing information associated with the NRF. To identify a database interruption in the network, the system and the method may be configured to identify that certain database operations are not received from the primary database. If the certain database operations are not received, then the system and the method may be configured to determine that the database interruption occurred. Upon identifying the database interruption in the network, the system and the method may be configured to maintain a communication session with the secondary database even if the communication session with the primary database is lost.

[0022] The secondary database may be a backup database accessed via a communication session with a network component at a same time the primary database is accessed via a corresponding communication session. In this regard, the primary database and the secondary database may be accessed via individual communication sessions with a given network component. Further, the primary database and the secondary database may establish a communication link to copy operations from the primary database to the secondary database. In the event that the access is lost between the primary database and the given network component, the secondary database maintains the corresponding communication session with the given network component. As a result, the given network component may not experience any effects caused by the database interruptions. In some embodiments, the primary database may dynamically update the database operations to the secondary database. In other embodiments, the primary database may periodically update the database operations to the secondary database.

[0023] In one or more embodiments, the system and the method described herein are integrated into a practical application to reduce, prevent, or to eliminate database interruptions in the SBA. In this regard, the system and the method are integrated into a practical application of providing a backup database configured to perform any or all operations associated with the primary database when access to the primary database is determined to be lost in a database interruption. In particular, the system and the method provide storage of backup routing and configurations via the secondary database in response to losing connectivity with the primary database such that downtime is severely reduced in the SBA upon determining database interruptions associated with the primary database.

[0024] In addition, the system and method described herein are integrated into a technical advantage of increasing processing speeds in a computer system in the SBA, because processors associated with the system and the method comprise automatically transitioning from the primary database to the secondary database when access to the primary database is lost. In some embodiments, the system and the method comprise the secondary database to provide backup routing and configuring information of the network components. As a result, processing speed is

increased because the system and the method may be immediately store or provide the routing and configuring information to any network components in the network instead of awaiting to reestablish new communication sessions for access or estimating possible alternative configuration commands to reestablish access to routing and configuration information. Under these improvements, the system and the method provide a practical application of maintaining operations in the network for longer periods of time by reducing, preventing, or eliminating downtime caused by database interruptions.

[0025] In one or more embodiments, the system and the method may be performed by an apparatus, such as a server, communicatively coupled to multiple network components in the SBA. Further, the system may be a wireless communication system, that comprises the apparatus. In addition, the system and the method may be performed as part of a process performed by the apparatus communicatively coupled to the network components in the SBA. As a non-limiting example, the apparatus may comprise a memory and a processor. The memory is configured to store multiple configuration commands configured to establish one or more communication sessions to access two or more databases of the plurality of databases. The processor may be communicatively coupled to the memory and configured to generate a request to establish a communication session in which a network component accesses a first database of the databases and a second database of the databases. The processor may be configured to establish the communication session to access the first database and the second database based at least in part upon a first configuration command of the configuration commands. Concurrently with the communication session, the network component exchanges first connectivity signals with the first database and the second database; the first database provides first database operations in response to the first connectivity signals exchanged with the network component; and the first database reports to the second database that the first database operations are provided. In addition, the processor may be configured to determine that the communication session is lost between the network component and the first database based at least in part upon identifying an interruption in the communication session; and in response to determining that the communication session between the network component and the first database is lost, maintain the communication session to access the second database.

[0026] Certain embodiments of this disclosure may comprise some, all, or none of these advantages. These advantages and other features will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings and claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0027] For a more complete understanding of this disclosure, reference is now made to the following brief description, taken in connection with the accompanying drawings and detailed description, wherein like reference numerals represent like parts.

[0028] FIG. 1 illustrates an example communication system in accordance with one or more embodiments;

[0029] FIG. 2 illustrates examples of one or more core network communication operations performed in conjunction with the example communication system of FIG. 1;

[0030] FIG. 3 illustrates an example communication structure to perform the one or more core network communication operations of FIG. 2;

[0031] FIG. 4 illustrates an example operational flow to reduce network function interruptions in conjunction with the example communication system of FIG. 1 and the example communication architecture of FIG. 3;

[0032] FIG. 5 illustrates an example flowchart of a method to reduce network function

interruptions in conjunction with the operational flow of FIG. 4;

[0033] FIG. 6 illustrates an example operational flow to reduce network function interruptions in conjunction with the example communication system of FIG. 1;

[0034] FIG. 7 illustrates an example flowchart of a method to reduce network function interruptions in conjunction with the operational flow of FIG. 6;

[0035] FIG. 8 illustrates an example operational flow to reduce database interruptions in conjunction with the example communication system of FIG. 1; and

[0036] FIG. 9 illustrates an example flowchart of a method to reduce database interruptions in conjunction with the operational flow of FIG. 8.

DETAILED DESCRIPTION

[0037] Previous technologies fail to provide reliable solutions to reduce or to prevent Network Repository Function (NRF) interruptions when a network component performing NRF operations is unable to communicate with one or more network components in a network comprising a service-based architecture (SBA). In this regard, this disclosure provides various systems and methods to reduce or to prevent network function interruptions in the SBA. Further, as described above, previous technologies fail to provide reliable solutions to reduce or to prevent database interruptions when a database associated with the network component performing the NRF is unable to communicate with the network. In this regard, this disclosure provides various systems and methods to reduce or to prevent database interruptions in the SBA. These are solutions shown and described in reference to FIGS. 1-9.

[0038] In one or more embodiments, FIG. 1 illustrates a communication system **100** in which a server **102** configures communication operations between one or more data networks **104**, a core network **106**, a Radio Access Network (RAN) **108**, and one or more user equipment **110A-110G**. FIG. 2 illustrates one or more core network communication operations **200** in which one or more core network components **202** communicate with at least one base station **111X** and the server **102** of FIG. 1.

[0039] FIG. 3 illustrates a communication structure **300** between the server **102** of FIG. 1 and electronic devices in one or more communication regions **302A-302C**. FIG. 4 illustrates an operational flow **400** in which NRF interruptions **402** are reduced when a given network component **101A** performing NRF operations (e.g., one of the primary NRFs **112**) is unable to communicate with one or more network components **101B-101E** in the core network **106**. FIG. 5 illustrates a first process **500** to perform one or more of operations associated with the server **102** of FIG. 1.

[0040] FIG. 6 illustrates an operational flow **600** in which NRF interruptions **602** are reduced when a given network component (e.g., any of the network components **101A-101E**) performing NRF operations (e.g., primary NRF **112A**) is unable to communicate with one or more network components **101A-101E** in the core network **106**. FIG. 7 illustrates a second process **700** to perform one or more operations associated with the server **102** of FIG. 1.

[0041] FIG. 8 illustrates an operational flow **800** in which database interruptions **802** are reduced or prevented when a given database (e.g., primary database **116A**) associated with a specific network component **101A** performing the NRF (e.g., one of the primary NRFs **112**) is unable to communicate with one or more network components (e.g., any of the network components **101A-101E**) in the core network **106**. FIG. 9 illustrates a third process **900** to perform one or more operations associated with the server **102** of FIG. 1.

Communication System Overview

[0042] FIG. 1 illustrates a diagram of a communication system **100** (e.g., a wireless communication system) comprises a server **102** configured to reduce network function interruptions, prevent network interruptions, reduce database interruptions, or prevent database interruptions in core network **106** comprising an SBA, in accordance with one or more embodiments. In the communication system **100** of FIG. 1, the server **102** may provision the core network **106** to

respond to NRF (e.g., one of the primary NRFs **112**) interruptions and database interruptions. In FIG. **1**, the server **102** is communicatively coupled to multiple devices in the communication system **100**. While FIG. **1** shows the server **102** connected directly to the one or more data networks **104**, the server **102** may be located inside the core network **106** as part of one or more of the network components (e.g., any of the network components **101A-101E**) in the core network **106**.

[0043] In one or more embodiments, the communication system **100** comprises the user equipment **110A-110G** (collectively referred as “user equipment **110**”), the RAN **108**, the core network **106**, the one or more data networks **104**, and the server **102**. In some embodiments, the communication system **100** may comprise a Fifth Generation (5G) mobile network or wireless communication system, utilizing high frequency bands (e.g., 24 Gigahertz (GHz), 39 GHz, and the like) or lower frequency bands such (e.g., Sub 6 GHz). In this regard, the communication system **100** may comprise a large number of antennas. In some embodiments, the communication system may perform one or more communication operations associated with the 5G New Radio (NR) protocols described in reference to the Third Generation Partnership Project (3GPP). As part of the 5G NR protocols, the communication system **100** may perform one or more millimeter (mm) wave technology operations to improve bandwidth or latency in wireless communications.

[0044] In some embodiments, the communication system **100** may be configured to partially or completely enable communications via one or more various radio access technologies (RATs), wireless communication technologies, or telecommunication standards, such as Global System for Mobiles (GSM) (e.g., Second Generation (2G) mobile networks), Universal Mobile Telecommunications System (UMTS) (e.g., Third Generation (3G) mobile networks), Long Term Evolution (LTE) of mobile networks, LTE-Advanced (LTE-A) mobile networks, 5G NR mobile networks, or Sixth Generation (6G) mobile networks.

Service-Based Architecture

[0045] As described above, the communication system **100** may comprise the SBA. The SBA may be an organization scheme in the core network **106** that comprises authentication, security, session management, and aggregation of traffic from end devices (e.g., the user equipment **110A-110G**). In the SBA, the core network **106** may be representative of the 5G Core network and comprises multiple network components **101A-101E** (collectively, the core network components **202** of FIG. **2**). In the SBA, the network components **101A-101E** are hardware (e.g., electronic circuitry with antennas or communication ports, a processor, and a memory) configured to perform one or more specific Network Functions (NFs). Herein, network components **101A-101E** configured to perform one or more NFs may be referenced using an NF-associated name. For example, a network component **101A** configured to perform a Network Repository Function (NRF) may be referred to as an NRF (e.g., one of the primary NRFs **112**) or a NRF network component. In another example, one of the network components **101A-101E** may comprise a version of the server **102** with a server processor **122** configured to perform one or more specific NFs.

[0046] In some embodiments, individual network components **101A-101E** provide services or resources to other network components **101A-101E** performing different NFs. In other embodiments, each NF is a service provider that allocates one or more resources in communications inside or outside the network components **101A-101E** to provide one or more services. The services may be specific for each of the network components **101A-101E** and their respective NFs instead of each of the network components **101A-101E** providing and consuming processing resources and memory resources to perform multiple NFs in the core network **106**. In 5G NR mobile networks, the SBA is defined by 3GPP to comprise one or more network components **101A-101E** configured to perform specific NFs to provide control plane operations and user plane operations. In the 5G NR, the control plane comprises any part of the communication system **100** that controls operations and routing associated with data packets and forwarding operations. Further, in the 5G NR, the user plane comprises any part of the

communication system **100** that carries user traffic operations.

[0047] In one or more embodiments, the SBA may be configured to provide slices in accordance with specific application scenarios. A slice may be portions of a collection of NFs that are combined into providing specific application resources. The application resources may be provided to one or more user equipment **110A-110G** simultaneously via the RAN **108** via web-based Application Programming Interfaces (APIs). The APIs may enable flexible and agile deployment of innovative services. An API may be a set of instructions that, when executed by a processor, perform modular or cloud-native functions and procedures allowing creation of applications that access features or data of an operating system, application, or other service in the communication system **100**.

Communication System Components

Server

[0048] The server **102** is generally any device that is configured to process data, communicate with the data networks **104**, one or more network components **101A-101E** in the core network **106**, the RAN **108**, and the user equipment **110A-110G**. The server **102** may be configured to monitor, track data, control routing of signal, and control operations of certain electronic components in the communication system **100**, associated databases, associated systems, and the like, via one or more interfaces. The server **102** is generally configured to oversee operations of the server processing engine **120**. The operations of the server processing engine **120** are described further below. In some embodiments, the server **102** comprises a server processor **122**, one or more displays **124**, one or more server Input (I)/Output (O) interfaces **126**, a hardware accelerator **128**, a server network interface **130**, one or more administrator interfaces **132**, and a server memory **134** communicatively coupled to one another. The server **102** may be configured as shown, or in any other configuration. As described above, the server **102** may be located in one of the network components **101A-101E** located in the core network **106** and may be configured to perform one or more NFs associated with communication operations of the core network **106**.

[0049] In one or more embodiments, the server processor **122**, the one or more displays **124**, the one or more server I/O interfaces **126**, the hardware accelerator **128**, the server network interface **130**, the one or more administrator interfaces **132**, and the server memory **134** may be located at a same location or distributed over multiple remote locations separate from one another.

[0050] The server processor **122** may comprise one or more processors operably coupled to and in signal communication with the one or more displays **124**, the one or more server I/O interfaces **126**, the hardware accelerator **128**, the server network interface **130**, the one or more administrator interfaces **132**, and the server memory **134**. The server processor **122** is any electronic circuitry, including, but not limited to, state machines, one or more central processing unit (CPU) chips, logic units, cores (e.g., a multi-core processor), field-programmable gate arrays (FPGAs), application-specific integrated circuits (ASICs), or digital signal processors (DSPs). The server processor **122** may be a programmable logic device, a microcontroller, a microprocessor, or any suitable combination of the preceding. The one or more processors in the server processor **122** are configured to process data and may be implemented in hardware or software executed by hardware. For example, the server processor **122** may be an 8-bit, a 16-bit, a 32-bit, a 64-bit, or any other suitable architecture. The server processor **122** may comprise an arithmetic logic unit (ALU) to perform arithmetic and logic operations, processor registers that supply operands to the ALU, and store the results of ALU operations, and a control unit that fetches software instructions such as server instructions **136** from the server memory **134** and executes the server instructions **136** by directing the coordinated operations of the ALU, registers and other components via the server processing engine **120**. The server processor **122** may be configured to execute various instructions. For example, the server processor **122** may be configured to execute the server instructions **136** to perform functions or perform operations disclosed herein, such as some or all of those described with respect to FIGS. 1-9. In some embodiments, the functions described herein are

implemented using logic units, FPGAs, ASICs, DSPs, or any other suitable hardware or electronic circuitry.

[0051] In the example of FIG. 1, the one or more displays **124** may be configured to display a two-dimensional (2D) or three-dimensional (3D) representation of a service. Examples of the representations may comprise, but are not limited to, a graphical or simulated representation of an application, diagram, tables, or any other suitable type of data information or representation. In some embodiments, the one or more displays **124** may be configured to present visual information to one or more users (not shown). The one or more displays **124** may be configured to present visual information to the one or more users updated in real-time. The one or more displays **124** may be a wearable optical display (e.g., glasses or a head-mounted display (HMD)) configured to reflect projected images and enable user to see through the one or more displays **124**. For example, the one or more displays **124** may comprise display units, one or more lenses, one or more semi-transparent mirrors embedded in an eye glass structure, a visor structure, or a helmet structure. Examples of display units comprise, but are not limited to, a cathode ray tube (CRT) display, a liquid crystal display (LCD), a liquid crystal on silicon (LCOS) display, a light emitting diode (LED) display, an organic LED (OLED) display, an active-matrix OLED (AMOLED) display, a projector display, or any other suitable type of display. In another embodiment, the one or more displays **124** are a graphical display on the server **102**. For example, the graphical display may be a tablet display or a smartphone display configured to display the data representations.

[0052] In one or more embodiments, the server I/O interfaces **126** may be hardware configured to perform one or more communication operations. The server I/O interfaces **126** may comprise one or more antennas as part of a transceiver, a receiver, or a transmitter for communicating using one or more wireless communication protocols or technologies. In some embodiments, the server I/O interfaces **126** may be configured to communicate using, for example, NR or LTE using at least some shared radio components. In other embodiments, the server I/O interfaces **126** may be configured to communicate using single or shared radio frequency (RF) bands. The RF bands may be coupled to a single antenna, or may be coupled to multiple antennas (e.g., for a multiple-input multiple output (MIMO) configuration) to perform wireless communications.

[0053] In some embodiments, the hardware accelerator **128** may be any combination of a baseband processor, analog RF signal processing circuitry (e.g., including filters, mixers, oscillators, amplifiers, and the like), or digital processing circuitry (e.g., for digital modulation as well as other digital processing). For example, the hardware accelerator **128** may be configured to allocate power, frequency, and sensing resources during wireless communication operations.

[0054] The server network interface **130** may be any suitable hardware or software (e.g., executed by hardware) to facilitate any suitable type of communication in wireless or wired connections. These connections may comprise, but not be limited to, all or a portion of network connections coupled to additional network components **101A-101E** in the core network **106**, the RAN **108**, the user equipment **110A-110G**, the Internet, an Intranet, a private network, a public network, a peer-to-peer network, the public switched telephone network, a cellular network, a local area network (LAN), a metropolitan area network (MAN), a wide area network (WAN), and a satellite network. The server network interface **130** may be configured to support any suitable type of communication protocol.

[0055] The one or more administrator interfaces **132** may be user interfaces configured to provide access and control to of the server **102** to one or more users (not shown) or electronic devices. The one or more users may access the server memory **134** upon confirming one or more access credentials to demonstrate that access or control to the server **102** may be modified. In some embodiments, the one or more administrator interfaces **132** may be configured to provide hardware and software resources to the one or more users. Examples of user devices comprise, but are not limited to, a laptop, a computer, a smartphone, a tablet, a smart device, an Internet-of-Things (IoT) device, a simulated reality device, an augmented reality device, or any other suitable type of

device. The administrator interfaces **132** may enable access to one or more graphical user interfaces (GUIs) via an image generator display (e.g., the one or more displays **124**), a touchscreen, a touchpad, multiple keys, multiple buttons, a mouse, or any other suitable type of hardware that allow users to view data or to provide inputs into the server **102**. The server **102** may be configured to allow users to send requests to one or more network components **101A-101E** or network.

[0056] The server memory **134** may be volatile or non-volatile and may comprise a read-only memory (ROM), random-access memory (RAM), ternary content-addressable memory (TCAM), dynamic random-access memory (DRAM), and static random-access memory (SRAM). The server memory **134** may be implemented using one or more disks, tape drives, solid-state drives, and/or the like. The server memory **134** is operable to store the server instructions **136**, one or more configuration scripts **138**, local provisioning parameters **140**, configuration commands **142**, a user-specific directory **144**, and a provider-specific directory **146**. In the server memory **134**, the server instructions **136** may comprise commands and controls for operating one or more specific NFs in the core network **106** when executed by the server processing engine **120** of the server processor **122**.

[0057] In one or more embodiments, the configuration commands **142** are configured to establish one or more initial communication sessions between two or more network components **101A-101E** in the core network **106**. Each configuration command of the configuration commands **142** may establish an initial communication session between a first network component of the network components **101A-101E** comprising the server **102** and a second network component of the network components **101A-101E** based at least in part upon a first configuration command of the configuration commands **142**. The configuration commands **142** may be routing and configuration information (e.g., shown as routing and configuration information **314** in FIG. **3**) for reinstating or reestablishing initial communication sessions when a change is detected in the operations of the core network **106**. For example, in response to losing a specific initial communication session established with the first configuration command, the server **102** may attempt to reinstate the specific initial communication session based at least in part upon a second configuration command. The configuration commands **142** may be dynamically or periodically updated from another of the network components **101A-101E** in the core network **106**. Herein, initial communication sessions refer to communication signals exchanged between the server **102** and additional network components **101A-101E** in the core network **106**. In some embodiments, the configuration commands **142** are provided to the server **102** from another of the network components **101A-101E** performing the NRF.

[0058] In one or more embodiments, the local provisioning parameters **140** are configured to establish one or more backup communication sessions between two or more network components **101A-101E** in the core network **106**. Each local provisioning parameter of the local provisioning parameters **140** may establish a backup communication session between a first network component of the network components **101A-101E** comprising the server **102** and a second network component of the network components **101A-101E** based at least in part upon a first local provisioning parameter of the local provisioning parameters **140**. The local provisioning parameters **140** may be backup routing and configuration information for reinstating or reestablishing communication sessions when a access to the configuration commands **142** is lost or interrupted as it will be described in reference to FIGS. **4** and **5**. For example, in response to losing a specific initial communication session established with the first configuration command and in response to failing an attempt to reinstate the specific initial communication session, the server **102** may transition to establish a backup communication session based at least in part upon a local provisioning parameter. The configuration commands **142** may be dynamically or periodically updated from the configuration commands **142**. Herein, the configuration commands **142** are copied into the server memory **134** as the local provisioning parameters **140**.

[0059] In one or more embodiments, the one or more configuration scripts **138** are configured to

instruct one or more network components **101A-101E** in the core network **106** to establish the one or more backup communication sessions based at least in part upon one or more of the local provisioning parameters **138**. In some embodiments, the server processor **122** may implement the server processing engine **120** to execute a configuration script to instruct a specific network component of the network components **101A-101E** to establish a backup communication session based at least in part upon a specific local provisioning parameter of the local provisioning parameters **140**. The one or more configuration scripts **138** enable automation of the routing and configuration of network components **101A-101E** in the core network **106**. In this regard, the one or more configuration scripts **138** may reconfigure multiple cloud-NFs (CNFs) **150** that establish initial communication sessions with at least one NRF (e.g., one of the primary NRFs **112** or one of the secondary NRFs **114**) in a communication path comprising one or more additional network components **101A-101E**, such as those to be described in reference to the core network components **202** of FIG. 2. In other embodiments, the one or more configuration scripts **138** may be configured to reduce or remove discovery-based mechanisms to locate new target CNF to reestablish initial communication sessions once a connection with the NRF is lost. In this regard, the one or more configuration scripts **138** instruct routing and configuration of communication procedures based on static routing commands to restore restores services in the core network **106**. Once the NRF is back online, the one or more configuration scripts **138** may be configured to transition connections in the core network **106** from relying on the local provisioning parameters **140** to the configuration commands **142** provided by the NRF.

[0060] The user-specific directory **144** may be configured to store user-specific information. The user-specific directory **144** may enable the server **102** to confirm user credentials to access one or more network components (e.g., one of the network components **101A-101E** configured to perform the CNFs **150**, a Session Management Function (SMF) **152**, an access and management function (AMF) **154**, one or more Service Communication Proxys (SCPs) **156**, or the like) in the core network **106**. The provider-specific directory **146** may be configured to store provider-specific information. The provider-specific directory **146** may enable the server **102** to validate credentials associated with a specific provider (e.g., one of the CNFs **150**) against corresponding user-specific information in the user-specific directory **144**.

User Equipment

[0061] In one or more embodiments, each of the user equipment (collectively, user equipment **110**) (e.g., the user equipment **110A-110G**) may be any computing device configured to communicate with other devices, such as the server **102**, other network components **101A-101E** in the core network **106**, databases, and the like in the communication system **100**. Each of the user equipment **110** may be configured to perform specific functions described herein and interact with one or more network components **101A-101E** in the core network **106** via one or more base stations (collectively, base stations **111**) (e.g., the base stations **111A-111G**). Examples of user equipment **110** comprise, but are not limited to, a laptop, a computer, a smartphone, a tablet, a smart device, an IoT device, a simulated reality device, an augmented reality device, or any other suitable type of device.

[0062] In one or more embodiments, referring to the user equipment **110A** as a non-limiting example of the user equipment **110**, the user equipment **110A** may comprise a user equipment (UE) network interface **160**, a UE I/O interface **162**, a UE processor **164**, and a UE memory **166**. The UE network interface **160** may be any suitable hardware or software (e.g., executed by hardware) to facilitate any suitable type of communication in wireless or wired connections. These connections may comprise, but not be limited to, all or a portion of network connections coupled to additional network components **101A-101E** in the core network **106**, the RAN **108**, the Internet, an Intranet, a private network, a public network, a peer-to-peer network, the public switched telephone network, a cellular network, a local area network (LAN), a metropolitan area network (MAN), a wide area network (WAN), and a satellite network. The UE network interface **160** may be configured to

support any suitable type of communication protocol.

[0063] The UE I/O interface **162** may be hardware configured to perform one or more communication operations. The UE I/O interface **162** may comprise one or more antennas as part of a transceiver, a receiver, or a transmitter for communicating using one or more wireless communication protocols or technologies. In some embodiments, the UE I/O interface **162** may be configured to communicate using, for example, 5G NR or LTE using at least some shared radio components. In other embodiments, the UE I/O interface **162** may be configured to communicate using single or shared RF bands. The RF bands may be coupled to a single antenna, or may be coupled to multiple antennas (e.g., for a MIMO configuration) to perform wireless communications. In some embodiments, the user equipment **110A** may comprise capabilities for voice communication, mobile broadband services (e.g., video streaming, navigation, and the like), or other types of applications. In this regard, the UE I/O interface **162** of the user equipment **110A** may communicate using machine-to-machine (M2M) communication, such as machine-type communication (MTC), or another type of M2M communication.

[0064] In some embodiments, the user equipment **110A** is communicatively coupled to one or more of the base stations **111** via one or more communication links **190A-190G** (e.g., collectively, communication link **190**). The user equipment **110** may be a device with cellular communication capability such as a mobile phone, a hand-held device, a computer, a laptop, a tablet, a smart watch or other wearable device, or virtually any type of wireless device. In some applications, the user device **110** may be referred to as a UE, UE device, or terminal.

[0065] The UE processor **164** may comprise one or more processors operably coupled to and in signal communication with the UE network interface **160**, the UE I/O interface **162**, and the UE memory **166**. The UE processor **164** is any electronic circuitry, including, but not limited to, state machines, one or more CPU chips, logic units, cores (e.g., a multi-core processor), FPGAs, ASICs, or DSPs. The UE processor **164** may be a programmable logic device, a microcontroller, a microprocessor, or any suitable combination of the preceding. The one or more processors in the UE processor **164** are configured to process data and may be implemented in hardware or software executed by hardware. For example, the UE processor **164** may be an 8-bit, a 16-bit, a 32-bit, a 64-bit, or any other suitable architecture. The UE processor **164** comprises an ALU to perform arithmetic and logic operations, processor registers that supply operands to the ALU, and store the results of ALU operations, and a control unit that fetches software instructions such as UE instructions **168** from the UE memory **166** and executes the UE instructions **168** by directing the coordinated operations of the ALU, registers, and other components via a UE processing engine **170**. The UE processor **164** may be configured to execute various instructions. For example, the UE processor **164** may be configured to execute the UE instructions **168** to implement functions or perform operations disclosed herein, such as some or all of those described with respect to FIGS. **1-9**. In some embodiments, the functions described herein are implemented using logic units, FPGAs, ASICs, DSPs, or any other suitable hardware or electronic circuitry.

Radio Access Network

[0066] In one or more embodiments, the RAN **108** enables the user equipment **110** to access one or more services in the core network **106**. The one or more services may be a mobile telephone service, a Short Message Service (SMS) message service, a Multimedia Message Service (MMS) message service, an Internet access, cloud computing, or other types of data services. The RAN **108** may comprise the base stations **111** in signal communication with the user equipment **110** via the one or more communication links **190A-190G**. Each of the base stations **111** may service the user equipment **110A-110G**. In some embodiments, while multiple base stations **111** are shown connected to multiple user equipment **110** via the communication link **190**, one or more additional base stations **111** may be connected to one or more additional user equipment **110** via one or more additional communication links **190**. For example, the base stations **111A-111G** may exchange connectivity signals with the user equipment **110A** via the communication link **190A**. In another

example, the base station **111G** may exchange connectivity signals with the user equipment **110G** via the communication link **190G**. In yet another example, the base stations **111** may service some user equipment **110** when the user equipment **110** are located within a geographic area serviced by one of the base

[0067] In one or more embodiments, referring to the base station **111A** as a non-limiting example of the base station **111**, the base station **111A** may comprise a base station (BS) network interface **182**, a BS I/O interface **184**, a BS processor **186**, and a BS memory **188**. The BS network interface **182** may be any suitable hardware or software (e.g., executed by hardware) to facilitate any suitable type of communication in wireless or wired connections between the core network **106** and the user equipment **110**. These connections may comprise, but not be limited to, all or a portion of network connections coupled to additional network components **101A-101E** in the core network **106**, other base stations **111**, the user equipment **110**, the Internet, an Intranet, a private network, a public network, a peer-to-peer network, the public switched telephone network, a cellular network, a LAN, a MAN, a WAN, and a satellite network. The BS network interface **182** may be configured to support any suitable type of communication protocol.

[0068] The BS I/O interface **184** may be hardware configured to perform one or more communication operations. The BS I/O interface **184** may comprise one or more antennas as part of a transceiver, a receiver, or a transmitter for communicating using one or more wireless communication protocols or technologies. In some embodiments, the BS I/O interface **184** may be configured to communicate using, for example, 5G NR or LTE using at least some shared radio components. In other embodiments, the BS I/O interface **184** may be configured to communicate using single or shared RF bands. The RF bands may be coupled to a single antenna, or may be coupled to multiple antennas (e.g., for a MIMO configuration) to perform wireless communications. In some embodiments, the base station **111A** may allocate resources in accordance with one or more routing and configuration operations obtained from the core network **106**. In some embodiments, resources may be allocated to enable capabilities in the user equipment **110** for voice communication, mobile broadband services (e.g., video streaming, navigation, and the like), or other types of applications.

[0069] In some embodiments, the base station **111A** is communicatively coupled to one or more of the user equipment **110** via the one or more communication links **190**. In some applications, the base station **111** may be referred to as a BS, evolved Node B (eNodeB or eNB), a next generation Node B, gNodeB, gNB, or terminal.

[0070] The BS processor **186** may comprise one or more processors operably coupled to and in signal communication with the BS network interface **182**, the BS I/O interface **184**, and the BS memory **188**. The BS processor **186** is any electronic circuitry, including, but not limited to, state machines, one or more CPU chips, logic units, cores (e.g., a multi-core processor), FPGAs, ASICs, or DSPs. The BS processor **186** may be a programmable logic device, a microcontroller, a microprocessor, or any suitable combination of the preceding. The one or more processors in the BS processor **186** are configured to process data and may be implemented in hardware or software executed by hardware. For example, the BS processor **186** may be an 8-bit, a 16-bit, a 32-bit, a 64-bit, or any other suitable architecture. The BS processor **186** comprises an ALU to perform arithmetic and logic operations, processor registers that supply operands to the ALU, and store the results of ALU operations, and a control unit that fetches software instructions (not shown) from the BS memory **188** and executes the software instructions by directing the coordinated operations of the ALU, registers, and other components via a processing engine (not shown) in the BS processor **186**. The BS processor **186** may be configured to execute various instructions. For example, the BS processor **186** may be configured to execute the software instructions to implement functions or perform operations disclosed herein, such as some or all of those described with respect to FIGS. **1-9**. In some embodiments, the functions described herein are implemented using logic units, FPGAs, ASICs, DSPs, or any other suitable hardware or electronic circuitry.

Core Network

[0071] The core network **106** may be a network configured to manage communication sessions for the user equipment **110**. In one or more embodiments, the core network **106** may establish connections between user equipment **110** and a particular data network **104** in accordance with one or more communication protocols. In the example of FIG. 1, the core network **106** comprises one or more primary NRFs **112**, one or more secondary NRFs **114**, one or more primary databases **116**, one or more secondary databases **118**, one or more CNFs **150**, the SMF **152**, the AMF **154**, and one or more SCPs **156**. Herein, while multiple NRFs are shown, the core network **106** may comprise a single network component **101A** performing the NRF as shown in FIG. 1. Further, while multiple databases are shown, the core network **106** may comprise a single database in a single network component **101B** as shown in FIG. 1.

[0072] In some embodiments, any one of the network components **101A-101E** performing the one or more primary NRFs **112** or the one or more secondary NRFs **114** (collectively, NRF **112/114**) may be configured to register any services offered by the core network **106**. The NRF **112/114** may comprise a service registration procedure that accesses the one or more primary databases **116** and the one or more secondary databases **118** (collectively, databases **116/118**) to store or retrieve routing and configuration information associated with one or more network components **101A-101E** in the core network **106**. The NRF **112/114** may access the database to discover services offered by other networks or other network components **101A-101E** with service discovery procedures and service authorization procedures. The NRF **112/114** may maintain a list of available NFs operations available in the core network **106** and any network components **101A-101E** associated with performing a given NF. The NRF **112/114** may also performs registration and discovery of service such that different NFs may find each other via APIs. As an example, when the SMF **152** is registered to the NRF **112/114**, the SMF **152** is discoverable by the AMF **154** when the user equipment **110** attempts to access a given service type via the SMF **152**. In other embodiments, the NFs may be connected via a communication bus **210** (shown in FIG. 2) to all other additional network elements in the core network **106**. In the SBA, the NRF may enable access between user equipment **110** and the services offered via the NFs.

[0073] In one or more embodiments, the network components **101C** performing the one or more CNFs **150** may be configured to operate multiple services associated with one or more applications, while dynamically directing network traffic within the core network **106**. In some embodiments, the network component **101E** performing the SMF **152** may be configured to manage one or more communication sessions established between network components **101A-101E** of the core network **106**, allocate and manage resource allocation routing for the user equipment **110**, user plane selection, QoS and configuration enforcements for the control plane, service registration, discovery, establishment, and the like. In other embodiments, the network component **101C** performing the AMF **154** may be configured to manage mobility, registration, connections, and overall access for the other network components **101A-101E** in the core network **106**. The AMF **154** may act as an entry point for connections between the user equipment **110** and a given service. In yet other embodiments, the network component **101E** performing the one or more SCPs **156** may be configured to provide a point of entry for a cluster of NFs in the core network **106** to the user equipment **110** once the user equipment **110** are discovered by the NRF **112/114**. This allows the SCPs **156** to be delegated discovery points in the core network **106**.

[0074] In some embodiments, the core network **106** enables the user equipment to communicate with the server **104**, or another type of device, located in a particular data network **104** or in signal communication with a particular data network **104**. The core network **106** may implement a communication method that does not require the establishment of a specific communication protocol connection between the user equipment **110** and one or more of the data networks **104**. The core network **106** may include one or more types of network devices (not shown), which may perform different NFs.

[0075] In some embodiments, the core network **106** may include a 5G NR or an LTE access network (e.g., an evolved packet core (EPC) network) among others. In this regards, the core network **106** may comprise one or more logical networks implemented via wireless connections or wired connections. Each logical network may comprise an end-to-end virtual network with dedicated power, storage, or computation resources. Each logical network may be configured to perform a specific application comprising individual policies, rules, or priorities. Further, each logical network may be associated with a particular Quality of Service (QoS) class, type of service, or particular user associated with one or more of the user equipment **110**. For example, a logical network may be a Mobile Private Network (MPN) configured for a particular organization. In this example, when the user equipment **110A** is configured and activated by a wireless network associated with the RAN **108**, the user equipment **110A** may be configured to connect to one or more particular network slices (i.e., logical networks) in the core network **106**. Any logical networks or slices that may be configured for the user equipment **110A** may be configured using a network component (e.g., one of the network components **101A-101E** of FIG. **1** or the core network components **202** of FIG. **2**) performing a Network Slice Selection Function (NSSF) **204** (as shown in FIG. **2**) that may store a subscription profile associated with the user equipment **110A**, in a network component operating as a Unified Data Management (UDM) **206** (as shown in FIG. **2**). Further, when the user equipment **110A** may request a connection to a particular logical network or slice, the user equipment **110A** may send a request to the network component performing the AMF **154**. The AMF **154** may provide a list of allowed logical networks or slices to the user equipment **110A**. The user equipment **110A** may then request a Packet Data Unit (PDU) connection with one or more of the provided logical networks or slices.

Data Networks

[0076] In the example system **100** of FIG. **1**, the data networks **104** may facilitate communication within the communication system **100**. This disclosure contemplates that the data networks **104** may be any suitable network operable to facilitate communication between the server **102**, the core network **106**, the RAN **108**, and the user devices **110**. The data networks **104** may include any interconnecting system capable of transmitting audio, video, signals, data, messages, or any combination of the preceding. The data networks **104** may include all or a portion of a LAN, a WAN, an overlay network, a software-defined network (SDN), a virtual private network (VPN), a packet data network (e.g., the Internet), a mobile telephone network (e.g., cellular networks, such as 4G or 5G), a Plain Old Telephone (POT) network, a wireless data network (e.g., WiFi, WiGig, WiMax, and the like), a Long Term Evolution (LTE) network, a Universal Mobile Telecommunications System (UMTS) network, a peer-to-peer (P2P) network, a Bluetooth network, a Near Field Communication network, a Zigbee network, or any other suitable network, operable to facilitate communication between the components of the communication system **100**. In other embodiments, the communication system **100** may not have all of these components or may comprise other elements instead of, or in addition to, those above.

Core Network Communication Operations

[0077] FIG. **2** illustrates one or more core network communication operations **200** in accordance with one or more embodiments. The core network communication operations **200** may be performed by one or more core network components **202** performing dedicated NFs in the core network **106**. In the non-limiting example of FIG. **2**, the core network components **202** are shown solely with the labels of one or more NFs performed for ease of reference. As described above, the NFs may be performed by one of the core network components **202** such as those network components **101A-101E** described in reference to FIG. **1**. The core network components **202** may comprise the NRF **112/114**, the database **116/118**, the one or more CNFs **150**, the AMF **154**, the SMF **152**, the one or more SCPs **156**, the NSSF **204**, and the UDM **206** described or mentioned in reference to the core network **106** of FIG. **1**. Further, the core network components **202** may comprise network components (e.g., similar to those network components **101A-101E** of FIG. **1**)

configured to perform a Network Exposure Function (NEF) **220**, a User Plane Function (UPF) **222**, an Authentication Server Function (AUSF) **224**, a Policy Control Function (PCF) **226**, a Unified Data Repository (UDR) **228**, and an Equipment Identity Register (EIR) **230**. In some embodiments, the multiple network components performing the different NFs of the core network components **202** may be interconnected to one another and additional SBA APIs **240** via the communication bus **210**. The interconnections, operations, and procedures performed by the core network components **202** may follow the guidelines (such as reference information elements to establish communication among the network components) for the SBA described in TS 23.501, TS 29.510, and TS 29.511 of the 3GPP standard.

[0078] In one or more embodiments, instead of a single NRF **112/114**, the core network **106** comprises multiple primary NRFs **112** and multiple secondary NRFs **114**. The multiple primary NRFs **112** may be one or more of the core network components **202** configured to establish initial communication sessions between any other of the core network components **202** of the core network **106**. The multiple secondary NRFs **114** may referred to the core network components **202** configured to establish backup communication sessions between the core network components **202** in the communication system **100** when initial communication sessions established via a corresponding primary NRF **112** are lost. In particular, the core network components **202** of FIG. 2 show a primary NRF **112A** and a corresponding secondary NRF **114A**, a primary NRF **112B** and a corresponding secondary NRF **114B**, and a primary NRF **112C** and a corresponding secondary NRF **114C**. In some embodiments, each of the core network components **202** performing one of the NRFs **112/114** may comprise a version of the server **102** of FIG. 1. In other embodiments, one or more servers operating as the server **102** may be configured to perform one or more of the NRFs **112/114**.

[0079] In one or more embodiments, the primary NRF **112A**, the primary NRF **112B**, and the primary NRF **112C** may be communicatively coupled to one another to provide feedback regarding each other's NRF operations. In some embodiments, the secondary NRF **114A**, the secondary NRF **114B**, and the secondary NRF **114C** may be communicatively coupled to one another to provide feedback regarding each other's NRF operations. In other embodiments, the primary database **116A**, the primary database **116B**, and the primary database **116C** may be communicatively coupled to one another to provide feedback regarding each other's database operations. In yet other embodiments, the secondary database **118A**, the secondary database **118B**, and the secondary database **118C** may be communicatively coupled to one another to provide feedback regarding each other's database operations.

[0080] In one or more embodiments, instead of a single database **116/118**, the core network **106** comprises multiple primary databases **116** and multiple secondary databases **118**. The multiple primary databases **116** may refer to one of the network components **101A-101E** configured to enable initial access between any other network components **101A-101E** of the core network **106** and the database associated with a given NRF of the NRFs **112/114** of FIG. 1. The multiple secondary databases **118** may refer to the network components **101A-101E** configured to enable backup access between any network components **101A-101E** in the communication system **100** and the database associated with a given NRF of the NRFs **112/114** of FIG. 1 when the initial access to a corresponding database **116** is lost. In particular, the core network components **202** of FIG. 2 show a primary database **116A** and a corresponding secondary database **118A**, a primary database **116B** and a corresponding secondary database **118B**, and a primary database **116C** and a corresponding secondary database **118C**. In some embodiments, each of the core network components **202** enabling access to one of the databases **116/118** may comprise a version of the server **102** of FIG. 1. In other embodiments, one or more servers operating as the server **102** may be configured to enable access to one or more of the databases **116/118**.

[0081] In one or more embodiments, a given base station **111X** and the server **102** may be connected to the core network components **202** via a connection **250** and a connection **260**,

respectively. The base station **111X** may be configured to enable any one of the user equipment **110** of FIG. **1** to access the core network components **202** in the core network **106** using one or more RATs and one or more communication protocols. In some embodiments, the core network components **202** may include additional NFs (not shown) that may be part of the SBA, such as a Unified Data Management (UDM), a Charging Function (CHF), a Network Data Analytics Function (NWDAF), an Application Function (AF), and a Short Message Service Function (SMSF) among others.

[0082] In one or more embodiments, similar to the one or more CNFs **150**, the one or more SCPs **156**, the NRFs **112/114**, and the databases **116/118**, while FIG. **2** shows a single AMF **154**, SMF **152**, NSSF **204**, UDM **206**, NEF **220**, UPF **222**, the AUSF **224**, PCF **226**, UDR **228**, and EIR **230** for illustration purposes, the core network **106** may comprise multiple AMFs **154**, SMFs **152**, NSSFs **204**, UDMs **206**, NEFs **220**, UPFs **222**, AUSFs **224**, PCFs **226**, UDRs **228**, and EIRs **230**. In some embodiments, the NFs shown in the core network components **202** may be performed in a dedicated network component (e.g., in the server **102** located in one of the network components **101A-101E** in FIG. **1** or communicatively connected with the core network components **202** of FIG. **2**) or a simulated NF implemented on a common shared physical infrastructure across multiple network elements. For example, the server **102** may be configured to implement one or more of the NFs of FIG. **2** in collaboration with other of the core network components **202** using a Virtual Network Function (VNF) virtual machine, a CNF container, an event driven serverless architecture interface, or a specific type of SDN architecture.

[0083] In one or more embodiments, the NRFs **112/114**, the databases **116/118**, the one or more CNFs **150**, the SMF **152**, the AMF **154**, and the one or more SCPs **156** may comprise the operations described in FIG. **1**. The NSSF **204**, the UDM **206**, the NEF **220**, the UPF **222**, the AUSF **224**, the PCF **226**, the UDR **228**, and the EIR **230** may perform one or more of the operations described below.

[0084] The NSSF **204** may be implemented in one of the core network components **202** configured to maintain a list of authorization operations in the core network **106**. As an example, in an event in which the AMF **154** authorizes uses of network slices and applications based at least in part upon subscription information stored in the UDM **206** or queries the NSSF **204** to authorize access to a network slice or application based at least in part upon one or more service requirements. The NSSF **204** may redirect traffic to a specific one of the core network components **202** performing an intended network slice or application.

[0085] The UDM **206** may be implemented in one of the core network components **202** configured to perform management data of functions or services. In some embodiments, the UDM **206** is configured to perform operations such as handling of user identification, management of subscriptions, authentication of users, authorization to access network components to perform operations (e.g., such as roaming, and the like). In some embodiments, the UDM **206** and the AUSF **224** may share performing of some of the aforementioned operations. In this regard, the AUSF **224** may be for authentication processes while the UDM **206** may manage user data for any other processes in the core network **106**. In other embodiments, the UDM **206** may receive requests for subscriber data from the SMF **152**, the AMF **154**, the AUSF **224**, and the SMSF before providing any services. The AUSF **224** may be implemented in one of the core network components **202** configured to enable the AMF **154** to authenticate the user equipment **110**.

[0086] The NEF **220** may be implemented in one of the core network components **202** configured to provide services and resources over APIs within and outside the core network **106**. In one or more embodiments, one or more 5G services may be provided via the NEF **220** based at least in part upon API identifiers or indicators. In some embodiments, the NEF **220** may enable third-party (e.g., outside the core network **106** or unrelated to a network component performing a specific NF or providing a specific service).

[0087] The UPF **222** may be implemented in one of the core network components **202** configured

to connect data coming over the RAN **108** to the data networks **104**. In some embodiments, the UPF **222** may be able to route data packets to correct destinations on the data networks **104**.

[0088] The PCF **226** may be implemented in one of the core network components **202** configured to provide a policy control framework in which rules and policies are implemented in accordance with one or more application guidelines. In some embodiments, the PCF **226** may apply policy decisions to services provided, accessing subscription information, and the like. to control behavior associated with the core network **106**.

[0089] The UDR **228** may be implemented in one of the core network components **202** configured to operate as a centralized data repository for subscription data, subscriber policy data, session information, context information, and application states. In some embodiments, the UDR **228** may be configured to provide API integrations with other NFs (e.g., the one or more core network components **202**) to retrieve subscriber subscription and policy data. The UDR **228** may notify other NFs of changes in subscriber data, supports real-time or batch (e.g., bulk) data access provisioning and subscriber data provisioning, and manages service parameters and application data for advanced applications.

[0090] The EIR **230** may be implemented in one of the core network components **202** configured to determine whether a given user equipment **110** is allowed onto the core network **106**. In some embodiments, when a subscriber (e.g., user **180** via the user equipment **110G**) connects to the core network **106**, the EIR **230** may be configured to obtain user data or user profiles may be provided to the core network **106** to confirm service information and availability to the user **180**.

[0091] In one or more embodiments, the server **102** may be located in the network component **101C** configured to perform the AMF **154**. The server **102** may be configured to provide reliable solutions to reduce and to prevent NRF interruptions when the network component **101A** performing the NRFs **112/114** is unable to communicate with the rest of the core network **106**. To reduce periods of downtime for at least a portion of the core network **106**, the server **102** may execute one of the configuration scripts **138** to provide backup routing and configuration information to network components (e.g., one of the network components **101A-101E** as shown in FIG. **1** or communicatively connected with the core network components **202** as shown in FIG. **2**) in the core network **106**. In some embodiments, to reduce or eliminate periods of downtime for at least a portion of the core network **106**, the server **102** may replace session operations performed by one of the primary NRFs **112** with session operations performed by one of the secondary NRFs **114**.

[0092] In other embodiments, the server **102** may be configured to provide reliable solutions to reduce and to prevent database interruptions when a specific network component of the core network components **202** providing access to the databases **116/118** is unable to communicate with the rest of the core network **106**. To reduce periods of downtime for at least a portion of the core network **106**, the server **102** may execute one of the configuration scripts **138** to provide backup routing and configuration information to other of the core network components **202** in the core network **106**. In some embodiments, to reduce or eliminate periods of downtime for at least a portion of the core network **106**, the server **102** may replace database operations performed by one of the primary databases **116** with database operations performed by one of the secondary databases **118**.

Communication Structure

[0093] FIG. **3** illustrates a communication structure **300** in accordance with one or more embodiments. The communication structure **300** comprises connections from the server **102** to multiple electronic components located in multiple communication regions **302A-302C** (collectively, communication region **302**) via a communication connection **320** and via a communication connection **330**. The communication structure **300** may comprise the one or more core network components **202** and the one or more availability zones (collectively, availability zones **340**). Each of the availability zones **340** may comprise one or more of the user equipment

110. In FIG. 3, the communication structure **300** shows an operation flow in which routing and configuration information **314** is provided from the server **102** to the one or more user equipment **110**. Each communication region **302** is shown to comprise a couple of availability zones. For example, a communication region **302A** comprises an availability zone **340A** and an availability zone **340B**; a communication region **302B** comprises an availability zone **340C** and an availability zone **340D**; and a communication region **302C** comprises an availability zone **340E** and an availability zone **340F**. Each of the availability zone **340** may comprise multiple base stations **111** and user equipment **110**.

[0094] In one or more embodiments, each of the primary NRFs **112**, each of the secondary NRFs **114**, each of the primary database **116**, and each of the secondary database **118** may be configured to be performed in association with a specific communication region **302** or a specific availability zone **340**. For example, the primary NRF **112A**, the secondary NRF **112A**, the primary database **116A**, and the secondary database **118A** may be configured to be performed in association with the communication region **302A** and the availability zone **340A** or the availability zone **340B**. In another example, the primary NRF **112B**, the secondary NRF **112B**, the primary database **116B**, and the secondary database **118B** may be configured to be performed in association with the communication region **302B** and the availability zone **340C** or the availability zone **340D**. In yet another example, the primary NRF **112C**, the secondary NRF **112C**, the primary database **116C**, and the secondary database **118C** may be configured to be performed in association with the communication region **302C** and the availability zone **340E** or the availability zone **340F**.

[0095] In one or more embodiments, the server **102** and the core network components **202** may be located in the core network **106** while the communication regions **302** may include a combination of the RAN **108** and the user equipment **110**. In some embodiments, the server **102** may execute one or more configuration scripts **138** while provisioning routing and configuration information **314** changes to all network components. In some embodiments, the server **102** may be a jump server configured to provide a master network data map **312** on the core network components **202** via the communication connection **320**. The server **102** may be configured to instruct one or more of the core network components **202** in the core network **106** to establish one or more initial communication sessions in accordance with one or more configuration commands **142**. Further, the server **102** may be configured to instruct one or more core network components **202** in the core network **106** to establish one or more backup communication sessions in accordance with one or more local provisioning parameters **140**. In some embodiments, the server **102** is configured to establish a backup communication session between any two specific network components when an initial connection is determined to be lost between the two specific network components.

[0096] In the core network **106**, the server **102** may execute one of the configuration scripts **138** as part of a process to reduce NRF interruptions. In particular, the server **102** may be configured to determine that a specific initial communication session is lost and, upon determining that the specific initial communication session is lost, the server **102** may execute one of the configuration scripts **138** to instruct reestablishment of connections via a specific backup communication session. In the example of FIG. 3, the server **102** may provide a backup of the master network data map **312** to the core network components **202** via the communication connection **320**. In turn, the core network components **202** may provide static routing and configuration information **314** to any electronic components or devices (e.g., the base stations **111** and the user equipment **110**) until the NRF interruption is resolved. In this regard, the routing and configuration information **314** provided to the availability zones **340** in the communication regions **302** may comprise static configuration, static connections, and one or more connectivity checks.

[0097] In some embodiments, the communication connection **320** may be any wired or wireless communication connections between the server **102** and other additional network components of the core network components **202** in the core network **106**. Further, the communication connection **330** may be any wired or wireless communication connections between the core network **106**, the

RAN **108**, the one or more base stations **111** and the one or more user equipment **110** distributed within the multiple availability zones **340**.

Operational Flow To Reduce Network Repository Function Interruptions

[0098] FIG. **4** illustrates an operation flow **400** performed to reduce NRF interruptions in the SBA, in accordance with one or more embodiments. As a non-limiting example, the operation flow **400** is performed via the server **102** operating as part of the network element **101E** performing the AMF **154** and in communicatively coupling with at least one of the user equipment **110A**, at least one network component performing one or more NRFs **112/114** (e.g., the network component **101A**), and at least one network component performing the SMF **152** (e.g., the network component **101E**). In some embodiments, the operation flow **400** comprises reducing NRF interruptions by establishing backup communication sessions in the event that corresponding initial communication sessions are lost. In some embodiments, the NRF interruptions are events in which the NRF **112/114** cannot be performed in relation to the core network **106**.

Establish Initial Communication Session

[0099] In one or more embodiments, the operation flow **400** starts when the user equipment **110A** transmits a request to establish an initial communication session (e.g., shown as the initial session request **402**). At this stage, the server **102** in the AMF **154** may be configured to request routing and configuration information from the NRFs **112/114** to route and configure access to one or more services in the core network **106** for the user equipment **110A**. Concurrently, the SMF **152** may exchange connectivity signals with the NRFs **112/114** providing connection registration data via a connection registration **404**. In this process, the NRFs may establish session requests **406** in which one or more of the configuration commands **142** are generated and saved in the server memory **134**. At this stage, a backup copy of the configuration commands **142** is generated and stored in the server memory **134** as the local provisioning parameters **140**. A registration entry is created in a registration creation **408** and transmitted to the SMF **152** such that the SMF **152** may provide resources and routing for one of the user equipment **110**.

[0100] Concurrently with receiving the initial session request **402**, the AMF **154** may transmit a connection discovery **410** to the NRFs **112/114** to request to access services or resources in the core network **106**. The NRFs **112/114** may perform a service discovery **412** in which the NRFs **112/114** evaluate user profiles or user credentials from the user equipment **110A** against the user-specific directory **144** and service profile or resources from the core network **106** against the provider-specific directory **146**. In response to verifying and associating information from the user equipment **110A** and the NRFs **112/114**, the NRFs **112/114** provide multiple SMF lists **414** to the AMF **154**. The SMF lists **414** enable the user equipment **110A** to establish the initial communication session. The AMF **154** may transmit may respond by creating a PDU session **420** to access resources in the core network **106** and one or more data networks **104**. As the PDU session **420** is created, the registration access **422** provides information regarding resource allocation commands to service the user equipment **110A**. At this stage, the user equipment **110A**, the AMF **154**, the NRFs **112/114**, and the SMF **152** are considered to have established an initial session **424** and the SMF **152** is allowed to provide a registration access **424** to the AMF **154**. During the initial communication session **420**, the NRFs **112/114** may be configured to perform the NRF and dynamically update the configuration commands **142** at the server **102**. Further, the local provisioning parameters may be updated dynamically any time one of the configuration commands **142** is updated or modified. In some embodiments, the local provisioning parameters **140** may be updated periodically after a predefined time period.

Loss of Initial Communication Session

[0101] In one or more embodiments, the initial communication session **420** to the NRFs **112/114** may be lost due to an NRF interruption **430**. The NRF interruption **430** may be caused by a disconnection of the NRFs **112/114** from the core network **106**. In this regard, the network element **101A** performing the NRF **112/114** may be unable to connect to the communication bus **210** in the

core network **106**. In some embodiments, the NRF interruption **430** may comprise that the network component **101A** is disconnected from the SBA or that the network component **101A** is unable to continue performing the NRFs **112/114**. To identify or confirm that the NRF interruption **430** occurred in the core network **106**, the server **102** may be configured to identify or confirm that certain connectivity signals are not received from the network component **101A**. The certain connectivity signals may comprise periodic connection feedback received from the NRFs **112/114** or expected periodic signaling (e.g., to update the configuration commands **142**).

[0102] If the certain connectivity signals are not received from the NRFs **112/114**, then the server **102** may be configured to perform one or more reestablishment attempts **450** in which the AMF **154** and one or more additional core network components **202** request one or more connectivity signals from the NRFs **112/114** to check for a connection. If a response is not received and the reestablishment attempts **450** fail as a result, the server **102** may be configured to determine or confirm that the NRF interruption **430** occurred. Upon identifying or confirming that the NRF interruption **430** occurred in the network, the server **102** may be configured to execute one of the configuration scripts **138** that automatically establishes backup communication sessions where initial communication sessions are lost **440**. In some embodiments, the configuration script **138** may be configured to instruct the SMF **152** and any other core network components **202** to transition to the local provisioning parameters **140** instead of the configuration commands **142**. The server **102** may then establish one or more backup communication sessions to restore operations in the core network **106** by statically providing routing and configuration information that would otherwise be provided by the NRFs.

[0103] In one or more embodiments, to transition from the configuration commands **142** to the local provisioning parameters **140**, the AMF selects subsequent or ongoing SMF lists **414** for the backup communication sessions by modifying multiple information elements as part of the operations of the core network **106**. The configuration script **138** may be configured to automatically replace information elements from relying on the NRFs **112/114** to relying on locally provisioned parameters. As a non-limiting example, the information elements that select one or more routing or configuration information for services associated with the SMF **152**, the UDM **206**, the AUSF **224**, the PCF **226**, the SMSF (not shown), and the EIR **230**. The information parameters may be modified from an NRF setting command to a LocalProvisioning setting command or a NRFLocalProvisioning setting command. These information parameters may comprise smfSelection, udmSelection, ausfSelection, pcfSelection, smsfSelection, and eirSelection to change the respective settings for the SMF **152**, the UDM **206**, the AUSF **224**, the PCF **226**, the SMSF (not shown), and the EIR **230**. In some embodiments, the LocalProvisioning setting command causes the AMF **152** to use locally provisioned NFs for the selection of any given NF. In other embodiments, the NRFLocalProvisioning setting command causes the AMF **152** to check any locally provisioned selection rules before relying on the NRFs **112/114**. If there is a match, then the AMF **152** selects the NF matching the rule. If there is no match, then the AMF **152** selects the NRFs **112/114**.

Transition To Backup Communication Session

[0104] In one or more embodiments, the server **102** transitions to a static implementation of the NRFs **112/114** by using the local provisioning parameters **140**. In this regard, the server **102** may be configured to transition to the local provisioning and backup communication sessions **460**. The backup communication sessions may be established using the local provisioning parameters **140** that are backup copies of configuration commands **142** used to establish the initial communication sessions **420**. In some embodiments, the server **102** may periodically check for the return of the NRFs **112/114**. The server **102** may reestablish the communication session **420** upon determining that the network component **101A** performing the NRFs **112/114** is reconnected to the core network **106**.

Example Process to Reduce Network Repository Function Interruptions

[0105] FIG. 5 illustrates an example flowchart of a process **500** to reduce NRF interruptions (e.g., the NRF interruption **430**) in the SBA, in accordance with one or more embodiments. In one or more embodiments, the process **500** comprises reducing NRF interruptions by establishing backup communication sessions in the event that an initial communication session is lost. In some embodiments, the NRF interruptions are events in which the NRF **112/114** cannot be performed in relation to the core network **106**.

[0106] The process **500** starts at operation **502**, where the server **102** receives a request for establishing a communication session between a first network component and a second network component. The first network component may be the network component **101C** performing the AMF **154**. The second component may be the network component **101E** performing the SMF. In this regard, the network component **101C** may include the server **102** that attempts to establish a communication session between the AMF **154** and the SMF **152**. The process **500** continues at operation **504**, where the server **102** establishes an initial communication session between the first network component and the second network component based at least in part upon a configuration command. As described in reference to FIG. 4, the initial communication session is established to obtain routing or configuration information using one or more of the configuration commands **142** previously obtained from a third network component (e.g., the network component **101A** performing the NRFs **112/114**). At operation **506**, the server **102** may exchange multiple connectivity signals between the first network and the second network. The connectivity signals may be performed over predetermined time periods such that the AMF **154** and the SMF **152** may determine when a correspondence connectivity signal is not received at either network component within a given time period.

[0107] At operation **510**, the server **102** may determine whether the initial communication session is lost. As described in reference to FIG. 4, the network component **101C** may determine that a specific connectivity signal is not received from the network component **101E** in a predetermined time period. The AMF **154** may determine that the initial communication connection is lost if a reestablishment procedure fails in which the AMF **154** attempts to reconnect the initial communication session with the SMF **152**. If the initial communication session is not lost (i.e., NO), the process **500** returns to operation **506**. In this case, at operation **510**, the AMF **154** may receive the specific connectivity signal within the predetermined time period. In response, the AMF **154** may confirm that the NRF **112/114** is connected to the core network **106** or that the initial communication is not lost. If the initial communication session is lost (i.e., YES), the process **500** proceeds to operation **512**. In this case, at operation **510**, the AMF **154** may not receive the specific connectivity signal within the predetermined time period. In response, the AMF **154** may confirm, assume, or determine that the NRF **112/114** is not connected to the core network **106** or that the initial communication is lost.

[0108] The process **500** ends at operation **512**, where the server **102** executes a configuration script instructing the first network component to establish a backup communication session based at least in part upon a local provisioning parameter. The configuration script may be one of the configuration scripts **138** instructing to reconnect the network component **101C** and the network component **101E**. The configuration script may instruct the network component **101C** to establish a reconnection by establishing the backup communication session using one or more local provisioning parameters **140** instead of the configuration commands **142**.

Operational Flow To Reduce Network Repository Function Interruptions

[0109] FIG. 6 illustrates an operation flow **600** performed to reduce, to prevent, or to eliminate NRF interruptions in the SBA, in accordance with one or more embodiments. As a non-limiting example, the operation flow **600** is performed via the server **102** operating as part of the network element **101C** performing the AMF **154** and in communicatively coupling with at least one of the core network components **202** performing one or more of the CNFs **150** and the one or more SCPs **156**, at least one network component performing the primary NRF **112A** (e.g., the network

component **101A**), at least one network component performing the secondary NRF **114A** (e.g., the network component **101A**), at least one network component performing one or more additional primary NRFs **602** (e.g., the primary NRF **112B** and the primary NRF **112C**), and at least one network component performing one or more additional secondary NRFs **604** (e.g., the secondary NRF **114B** and the secondary NRF **114C**). In some embodiments, the operation flow **600** comprises reducing, preventing, or eliminating NRF interruptions by maintaining communication sessions with the secondary NRF **114A** when in the event that the primary NRF **112A** is lost due to an NRF interruption. In some embodiments, the NRF interruptions are events in which any one of the NRF **112/114** cannot be performed in relation to the core network **106**.

[0110] In some embodiments, while the primary NRF **112A** is used as a reference for the operation flow **600**, the primary NRF **112B** or the NRF **112C** may perform any of the operations described in reference to the primary NRF **112A**. In other embodiments, while the secondary NRF **114A** is used as a reference for the operation flow **600**, the secondary NRF **114B** or the secondary NRF **114C** may perform any of the operations described in reference to the secondary NRF **114A**.

Establish Communication Session With A Primary NRF And A Secondary NRF

[0111] In one or more embodiments, the operation flow **600** starts when the network component **101D** performing one of the CNFs **150** communicates with the network component **101E** performing the SCP **156** and the network component **101C** performing the AMF **154** to access the primary NRF **112A** and the secondary NRF **114A** performed by the network component **101A**. The CNFs **150** may establish a communication session (e.g., shown as session establishment **610**) with both the primary NRF **112A** and the secondary NRF **114A**. In this communication session, the AMF **154** may receive SMF lists and other correspondence from the primary NRF **112A** while maintaining an active (e.g., open) communication link with both the primary NRF **112A** and the secondary NRF **114A**. In the communication link, the AMF **154** may perform one or more session operations **612** with the primary NRF **112A** where the primary NRF **112A** establishes routing and configuration information for NFs in the core network **106** and any user equipment **110** attempting to access services from the core network **106**. At this stage, the server **102** in the AMF **154** may be configured to request routing and configuration information from the primary NRFs **112A** to route and configure access to one or more services in the core network **106**. Concurrently, the SMF **152** may exchange connectivity signals with the primary NRF **112A** providing connection registration data via a connection registration and eventually establish a PDU with one or more of the data networks **104**. The routing and configuration commands from the primary NRF **112A** may be saved as the configuration commands **142** in the server **102**. During the communication session, the primary NRF **112A** may be configured to perform the NRF and dynamically update the configuration commands **142** at the server **102**.

[0112] In one or more embodiments, the primary NRF **112A** may provide the secondary NRF **114A** with a report in which the session operations **612** are copied. The report may be a string of data, a sequence of data packets, or a confirmation signal acknowledging that a service is provided to the rest of the core network **106**. The server **102** may assume that all session operations **612** performed with the primary NRF **112A** are reported to the secondary NRF **114A**. In some embodiments, the primary NRF **112A** and the secondary NRF **114A** may not be performed by the same network component **101A**. In some embodiments, the session operations **614** are further reported as copied operations **616** between the primary NRF **112A** and the additional primary NRFs **602**. In other embodiments, the session operations **614** are further reported as copied operations **618** between the secondary NRF **114A** and the additional secondary NRFs **604**. Similar to the report of operations **614**, the copied operations **616-618** may be data strings, sequences of data packets, or signal confirmations acknowledging that one or more services are provided to the rest of the core network **106**.

Loss Of Communication Session With The Primary NRF

[0113] In one or more embodiments, the communication session to the primary NRF **112A** may be

lost due to an NRF interruption **620**. Similar to the NRF interruption **430**, the NRF interruption **620** may be caused by a disconnection of the primary NRF **112A** from the core network **106**. In this regard, the network element **101A** performing the primary NRF **112A** may be unable to connect to the communication bus **210** in the core network **106**. In some embodiments, the NRF interruption **620** may comprise that the network component **101A** is disconnected from the SBA or that the network component **101A** is unable to continue performing the primary NRF **112A** causing a session to be lost (e.g., session lost **630**). To identify or confirm that the NRF interruption **620** occurred in the core network **106**, the server **102** may be configured to identify or confirm that certain connectivity signals are not received from the network component **101A**. The certain connectivity signals may comprise periodic connection feedback received from the primary NRF **112A** or expected periodic signaling (e.g., to update the configuration commands **142**).

[0114] If the certain connectivity signals are not received from the primary NRF **112A**, then the server **102** may be configured to perform one or more reestablishment attempts in which the AMF **154** and one or more additional core network components **202** request one or more connectivity signals from the primary NRF **112A** to check for a connection. If a response is not received and there are failed reestablishments **640** as a result, the server **102** may be configured to determine or confirm that the NRF interruption **620** occurred. Concurrently, and similar to the failed reestablishments **640**, the secondary NRF **114A** may identify that the primary NRF **112A** has undergone the interruption **620** if the report operations **614** are not received and one or more reported operations are missing (e.g., one or more missing reported operations **650**).

Maintain Communication Session With The Secondary NRF

[0115] In one or more embodiments, upon identifying that the primary NRF **112A** is disconnected or unresponsive due to the NRF interruption **620**, the server **102** may be configured to maintain a communication session with the secondary network component even if the communication session with the primary NRF **112A** is lost. At this stage, the core network **106** relies on the secondary NRF **114A** until a connection with the primary NRF **112A** is restored. The secondary NRF **114A** may perform one or more session operations **660** with the core network **106**. After the session operations **660** are performed, the secondary NRF **114A** may transmit a copy of the session operations to the additional primary NRFs **602** (e.g., copy operations **662**) and the additional secondary NRFs **604** (e.g., copy operations **664**).

Example Process To Reduce Network Function Interruptions

[0116] FIG. 7 illustrates an example flowchart of a process **700** to reduce, to prevent, or to eliminate NRF interruptions (e.g., the NRF interruption **620** of FIG. 6) in the SBA, in accordance with one or more embodiments. In one or more embodiments, the process **700** comprises reducing, preventing, or eliminating NRF interruptions by controlling backup network components (e.g., the network component **101A** performing the secondary NRFs **114**) to establish or maintain secondary communication sessions in the event that a corresponding primary communication session is lost. In some embodiments, the NRF interruptions are events in which the primary NRFs **112** cannot be performed in association with the core network **106**.

[0117] The process **700** starts at operation **702**, where the server **102** generates a request to establish a communication session between a first network component, a second network component, and a third network component. The first network component may be the network component **101C** performing the AMF **154**. The second network component may be the network component **101A** performing the primary NRFs **112**. The third network component may be the network component **101A** performing the secondary NRFs **114**. In some embodiments, two or more different network components of the core network components **202** may be configured to individually perform the primary NRFs **112** and the secondary NRFs **114**.

[0118] The process **700** continues at operation **710**, where the server **102** establishes the communication session between the first network component, the second network component, and the third network component. Herein, the server **102** establish individual or shared communication

sessions with the primary NRFs **112** and the secondary NRFs **114**. At operation **712**, the first network component exchanges multiple connectivity signals with the second network component and the third network component. In this case, the connectivity signals include establishing communication links to perform multiple operation sessions such as those discussed in reference to session operation **612** of FIG. **6**. At operation **714**, the second network component performs multiple session operations in response to the connectivity signals received from the first network component. The session operations may comprise providing and receiving communications associated with routing and configuring information for the one or more core network components **202**. At operation **716**, the second network component reports to the third network component that the session operations are performed. At this stage, the primary NRF **112A** provides one or more reports to the secondary NRF **114A** that the session operations were performed between the AMF **154** and the primary NRF **112A**.

[0119] At operation **720**, the server **102** may determine whether the communication session is lost between the first network component and the second network component. The server **102** determines that that an interruption (e.g., the NRF interruption **620** of FIG. **6**) caused the communication session between the AMF **154** and the primary NRF **112A** were lost. If the communication session is not lost (i.e., NO), the process **700** returns to operation **712**. If the communication session is lost (i.e., YES), the process **700** proceeds to operation **722**.

[0120] The process **700** ends at operation **722**, where the server **102** maintains the communication session between the first network component and the third network component. As a result, downtime in the core network **106** is reduced, prevented, or eliminated because the AMF **154** may pick up session operations with the secondary NRF **114A** after a communication session with the primary NRF **112A** is lost.

Operational Flow To Reduce Database Interruptions

[0121] FIG. **8** illustrates an operation flow **800** performed to reduce, to prevent, or to eliminate database interruptions in the SBA, in accordance with one or more embodiments. As a non-limiting example, the operation flow **800** is performed via the server **102** operating as part of the network element **101C** performing the AMF **154** and in communicatively coupling with at least one of the core network components **202** performing one or more of the CNFs **150**, the one or more SCPs **156**, and the one or more primary NRFs **112**, at least one network component providing the primary database **116A** (e.g., the network component **101B**), at least one network component performing the secondary database **118A** (e.g., the network component **101B**), at least one network component performing one or more additional primary databases **802** (e.g., the primary database **116B** and the primary database **116C**), and at least one network component performing one or more additional secondary databases **804** (e.g., the secondary database **118B** and the secondary database **118C**). In some embodiments, the operation flow **800** comprises reducing, preventing, or eliminating database interruptions by maintaining communication sessions with the secondary database **118A** when in the event that the primary database **116A** is lost due to a database interruption. In some embodiments, the database interruptions are events in which any one of the databases **116/118** cannot be accessed in relation to the core network **106**.

[0122] In some embodiments, while the primary database **116A** is used as a reference for the operation flow **800**, the primary database **116B** or the database **116C** may perform any of the operations described herein in association with the primary database **116A**. In other embodiments, while the secondary database **118A** is used as a reference for the operation flow **800**, the secondary database **118B** or the secondary database **118C** may perform any of the operations described herein in association with the secondary database **118A**.

Establish Access To A Primary Database And A Secondary Database

[0123] In one or more embodiments, the operation flow **800** starts when the network component **101D** performing one of the CNFs **150** communicates with the network component **101E** performing the SCP **156** and the network component **101C** performing the AMF **154** to access the

primary database **116A** and the database NRF **114A** hosted by the network component **101B**. The CNFs **150** may establish a communication session (e.g., shown as session establishment **810**) with both the primary database **116A** and the secondary database **118A**. In this communication session, the AMF **154** may receive information and data components stored in the primary database **116A** while maintaining an active (e.g., open) communication link with both the primary database **116A** and the secondary database **118A**. In the communication link, the AMF **154** may perform one or more database operations **812** with the primary database **116A** where the primary database **116A** establishes routing and configuration information for NFs in the core network **106** and any user equipment **110** attempting to access services from the core network **106**. At this stage, the server **102** in the AMF **154** may be configured to request access to routing and configuration information stored in the primary database **116A** to route and configure access to one or more services in the core network **106**. Concurrently, the SMF **152** may exchange connectivity signals with the primary database **116A** to provide connection registration data via a connection registration and eventually establish a PDU with one or more of the data networks **104**. The routing and configuration commands from the primary database **116A** may be saved as the configuration commands **142** in the server **102**. During the communication session, the primary database **116A** may be configured to store information associated with one or more of the primary NRFs **112** and dynamically update the configuration commands **142** at the server **102**.

[0124] In one or more embodiments, the primary database **116A** may provide the secondary database **118A** with a report in which the database operations **812** are copied. The report may be a string of data, a sequence of data packets, or a confirmation signal acknowledging that a service is provided to the rest of the core network **106**. The server **102** may assume that all database operations **812** performed via the primary database **116A** are reported to the secondary database **118A**. In some embodiments, the primary database **116A** and the secondary database **118A** may not be performed by the same network component **101B**. In some embodiments, the database operations **814** are further reported as copied operations **816** between the primary database **116A** and the additional primary databases **802**. In other embodiments, the database operations **814** are further reported as copied operations **818** between the secondary database **118A** and the additional secondary databases **804**. Similar to the report of operations **814**, the copied operations **816-818** may be data strings, sequences of data packets, or signal confirmations acknowledging that one or more services are provided to the rest of the core network **106**.

Loss Of Access To The Primary Database

[0125] In one or more embodiments, the communication session to the primary database **116A** may be lost due to a database interruption **820**. The database interruption **820** may be caused by a disconnection of the primary database **116A** from the core network **106**. In this regard, the network element **101B** performing the primary database **116A** may be unable to connect to the communication bus **210** in the core network **106**. In some embodiments, the database interruption **820** may comprise that the network component **101B** is disconnected from the SBA or that the network component **101B** is unable to continue providing access to the primary database **116A** causing a database to be lost (e.g., session lost **830**). To identify or confirm that the database interruption **820** occurred in the core network **106**, the server **102** may be configured to identify or confirm that certain connectivity signals are not received from the network component **101B**. The certain connectivity signals may comprise periodic connection feedback received from the primary database **114A** or expected periodic signaling (e.g., to update the configuration commands **142**).

[0126] If the certain connectivity signals are not received from the primary database **116A**, then the server **102** may be configured to perform one or more reconnection attempts in which the AMF **154** and one or more additional core network components **202** request one or more connectivity signals from the primary database **116A** to check for a connection. If a response is not received and there are failed reconnections **840** as a result, the server **102** may be configured to determine or confirm that the database interruption **820** occurred. Concurrently, and similar to the failed reconnections

840, the secondary database **118A** may identify that the primary database **116A** has undergone the interruption **820** if the report operations **814** are not received and one or more reported operations are missing (e.g., one or more missing report operations **850**).

Maintain Access To The Secondary Database

[0127] In one or more embodiments, upon identifying that the primary database **116A** is disconnected or unresponsive due to the database interruption **820**, the server **102** may be configured to maintain a communication session with the secondary network component even if the communication session with the primary database **116A** is lost. At this stage, the core network **106** relies on the secondary database **118A** until a connection with the primary database **116A** is restored. The secondary database **118A** may perform one or more database operations **860** with the core network **106**. After the database operations **860** are performed, the secondary database **118A** may transmit a copy of the database operations to the additional primary databases **802** (e.g., copy operations **862**) and the additional secondary databases **804** (e.g., copy operations **864**).

Example Process To Reduce Database Interruptions

[0128] FIG. **9** illustrates an example flowchart of a process **900** to reduce, to prevent, or to eliminate database interruptions (e.g., the database interruption **820** of FIG. **8**) in the SBA, in accordance with one or more embodiments. In one or more embodiments, the process **900** comprises reducing, preventing, or eliminating database interruptions by controlling backup databases (e.g., e.g., the network component **101B** operating the secondary databases **118**) to maintain information associated with communication sessions in the event that an initial communication session is lost. In some embodiments, the database interruptions are events in which the database operations cannot be performed in relation to the network.

[0129] The process **900** starts at operation **902**, where the server **102** generates a request to establish a communication session in which a network component accesses a first database and a second database. The network component may be the network component **101C** performing the AMF **154**. The first database may be the primary database **116A** in the network component **101B**. The second database may be the secondary database **118A** in the network component **101B**. In some embodiments, two or more different network components of the core network components **202** may be configured to individually contain the primary databases **116** and the secondary databases **118**. Herein, the server **102** establish individual or shared communication sessions with the primary databases **116** and the secondary databases **118**.

[0130] The process **900** continues at operation **910**, where the server **102** establishes the communication session to access the first database and the second database. Herein, the server **102** establish individual or shared communication sessions to access the primary databases **116** and the secondary databases **118**. At operation **912**, the network component exchanges multiple connectivity signals with the first database and the second database. In this case, the connectivity signals include establishing communication links to access database information and perform database operations such as those discussed in reference to database operation **812** of FIG. **6**. At operation **914**, the first database provides multiple database operations in response to the connectivity signals exchanged with the first database. The database operations may comprise providing and receiving communications associated with obtaining database information including routing and configuring information for the one or more core network components **202**. At operation **916**, the first database reports to the second database that the database operations are provided. At this stage, the primary database **116A** provides one or more reports to the secondary database **118A** that the database operations were performed between the AMF **154** and the primary database **116A**.

[0131] At operation **920**, the server **102** may determine whether the access is lost between the network component and the first database. The server **102** determines that that an interruption (e.g., the database interruption **820** of FIG. **8**) caused the communication session between the AMF **154** and the primary database **116A** were lost. If the access is not lost (i.e., NO), the process **900** returns

to operation **912**. If the access is lost (i.e., YES), the process **900** proceeds to operation **922**.

[0132] The process **900** ends at operation **922**, where the server **102** maintains the access between the network component and the second database. As a result, downtime in the core network **106** is reduced, prevented, or eliminated because the AMF **154** may pick up database operations with the secondary database **118A** after a communication session with the primary database **116A** is lost.

Example Processes

[0133] FIGS. **5**, **7**, and **9** illustrate respective example flowcharts of the process **500**, the process **700**, or the process **900**, in accordance with one or more embodiments. Modifications, additions, or omissions may be made to the process **500**, the process **700**, or the process **900**. The process **500**, the process **700**, or the process **900** may include more, fewer, or other operations than those shown above. For example, operations may be performed in parallel or in any suitable order. While at times discussed as the server **102**, one or more of the network components **101A-101E**, one or more of the core network components **202**, or components of any of thereof performing operations described in the operations, any suitable system or components of the security system **100** may perform one or more operations of the process **500**, the process **700**, or the process **900**. For example, one or more operations of the process **500**, the process **700**, or the process **600** may be implemented, at least in part, in the form of server instructions **136** of FIG. **1**, stored on non-transitory, tangible, machine-readable media (e.g., server memory **134** of FIG. **1**) that when run by one or more processors (e.g., the server processor **122** of FIG. **1**) may cause the one or more processors to perform operations described in operations **502-512**, operations **702-722**, or operations **902-922**.

Scope Of The Disclosure

[0134] While several embodiments have been provided in the present disclosure, it should be understood that the disclosed systems and methods might be embodied in many other specific forms without departing from the spirit or scope of the present disclosure. The present examples are to be considered as illustrative and not restrictive, and the intention is not to be limited to the details given herein. For example, the various elements or components may be combined or integrated with another system or certain features may be omitted, or not implemented.

[0135] In addition, techniques, systems, subsystems, and methods described and illustrated in the various embodiments as discrete or separate may be combined or integrated with other systems, modules, techniques, or methods without departing from the scope of the present disclosure. Other items shown or discussed as coupled or directly coupled or communicating with each other may be indirectly coupled or communicating through some interface, device, or intermediate component whether electrically, mechanically, or otherwise. Other examples of changes, substitutions, and alterations are ascertainable by one skilled in the art and could be made without departing from the spirit and scope disclosed herein.

[0136] To aid the Patent Office, and any readers of any patent issued on this application in interpreting the claims appended hereto, applicants note that they do not intend any of the appended claims to invoke 35 U.S.C. § 112 (f) as it exists on the date of filing hereof unless the words “means for” or “step for” are explicitly used in the particular claim.

Claims

1. A system, comprising: a plurality of databases comprising a first database and a second database; and an apparatus communicatively coupled to the plurality of databases and configured to: establish a communication session to access the first database and the second database; concurrently with the communication session: exchange a first plurality of connectivity signals with the first database and the second database; provide a first plurality of database operations in response to the first plurality of connectivity signals exchanged with the apparatus; and report to the second database that the first plurality of database operations is provided; determine that the

communication session is lost between the apparatus and the first database; and in response to determining that the communication session between the apparatus and the first database is lost, maintain the communication session to access the second database.

2. The system of claim 1, wherein, concurrently with maintaining the communication session to access the second database, the apparatus is further configured to: exchange a second plurality of connectivity signals with the second database; and provide a second plurality of database operations in response to the second plurality of connectivity signals received from the second database.

3. The system of claim 1, wherein the apparatus is further configured to: determine a first database operation of the first plurality of database operations to be received by the apparatus from the first database; in response to determining that the first plurality of database operations is interrupted from being received by the apparatus, attempt to reestablish the communication session to access the first database; and in response to a failed attempt to reestablish the communication session, determine that the communication session is lost.

4. The system of claim 1, wherein, concurrently with the communication session: the first database transmits a first copy of the first plurality of database operations provided to a third database and a fourth database; and the second database transmits a second copy of the first plurality of database operations provided to a fifth database and a sixth database.

5. The system of claim 4, wherein: the first database and the second database are associated with a first plurality of service providers communicating to a first plurality of users in a first availability zone; the third database and the fourth database are associated with a second plurality of service providers communicating to a second plurality of users in a second availability zone; and the fifth database and the sixth database are associated with a third plurality of service providers communicating to a third plurality of users in a third availability zone.

6. The system of claim 4, wherein: the apparatus is located within a first electronic component configured to perform an Access and Mobility Function (AMF); the first database is first primary database; the second database is first secondary database; the third database is second primary database; the fourth database is second secondary database; the fifth database is third primary database; and the sixth database is third secondary database.

7. The system of claim 6, wherein: the communication session between the apparatus and the first database is lost due to an interruption; and the interruption indicates that the first database is disconnected from a service-based architecture.

8. A method, comprising: establishing a communication session to access a first database and a second database; concurrently with the communication session: exchange a first plurality of connectivity signals with the first database and the second database; provide a first plurality of database operations in response to the first plurality of connectivity signals exchanged with an apparatus; and report to the second database that the first plurality of database operations is provided; determining that the communication session is lost between the apparatus and the first database; and in response to determining that the communication session between the apparatus and the first database is lost, maintaining the communication session to access the second database.

9. The method of claim 8, further comprising, in conjunction with maintaining the communication session to access the second database: exchanging a second plurality of connectivity signals with the second database; and providing a second plurality of database operations in response to the second plurality of connectivity signals received from the second database.

10. The method of claim 8, further comprising: determining a first database operation of the first plurality of database operations to be received by the apparatus from the first database; in response to determining that the first plurality of database operations are interrupted from being received by the apparatus, attempting to reestablish the communication session to access the first database; and in response to a failed attempt to reestablish the communication session, determining that the communication session is lost.

- 11.** The method of claim 8, wherein, concurrently with the communication session: the first database transmits a first copy of the first plurality of database operations provided to a third database and a fourth database; and the second database transmits a second copy of the first plurality of database operations provided to a fifth database and a sixth database.
- 12.** The method of claim 11, wherein: the first database and the second database are associated with a first plurality of service providers communicating to a first plurality of users in a first availability zone; the third database and the fourth database are associated with a second plurality of service providers communicating to a second plurality of users in a second availability zone; and the fifth database and the sixth database are associated with a third plurality of service providers communicating to a third plurality of users in a third availability zone.
- 13.** The method of claim 11, wherein: the method is performed by an apparatus located within a first electronic component configured to perform an Access and Mobility Function (AMF); the first database is first primary database; the second database is first secondary database; the third database is second primary database; the fourth database is second secondary database; the fifth database is third primary database; and the sixth database is third secondary database.
- 14.** The method of claim 13, wherein: the communication session between the apparatus and the first database is lost due to an interruption; and the interruption indicates that the first database is disconnected from a service-based architecture.
- 15.** A non-transitory computer-readable medium storing instructions that when executed by a processor cause the processor to: establish a communication session to access a first database and a second database; concurrently with the communication session: exchange a first plurality of connectivity signals with the first database and the second database; provide a first plurality of database operations in response to the first plurality of connectivity signals exchanged with an apparatus; and report to the second database that the first plurality of database operations is provided; determine that the communication session is lost between the apparatus and the first database; and in response to determining that the communication session between the apparatus and the first database is lost, maintain the communication session to access the second database.
- 16.** The non-transitory computer-readable medium of claim 15, wherein, when executed by the processor, the instructions further cause the processor to: in conjunction with maintaining the communication session to access the second database, exchange a second plurality of connectivity signals with the second database; and provide a second plurality of database operations in response to the second plurality of connectivity signals received from the second database.
- 17.** The non-transitory computer-readable medium of claim 15, wherein, when executed by the processor, the instructions further cause the processor to: determine a first database operation of the first plurality of database operations to be received by the apparatus from the first database; in response to determining that the first plurality of database operations is interrupted from being received by the apparatus, attempt to reestablish the communication session to access the first database; and in response to a failed attempt to reestablish the communication session, determine that the communication session is lost.
- 18.** The non-transitory computer-readable medium of claim 15, wherein, concurrently with the communication session: the first database transmits a first copy of the first plurality of database operations provided to a third database and a fourth database; and the second database transmits a second copy of the first plurality of database operations provided to a fifth database and a sixth database.
- 19.** The non-transitory computer-readable medium of claim 18, wherein: the first database and the second database are associated with a first plurality of service providers communicating to a first plurality of users in a first availability zone; the third database and the fourth database are associated with a second plurality of service providers communicating to a second plurality of users in a second availability zone; and the fifth database and the sixth database are associated with a third plurality of service providers communicating to a third plurality of users in a third availability

zone.

20. The non-transitory computer-readable medium of claim 19, wherein: the communication session between the apparatus and the first database is lost due to an interruption; and the interruption indicates that the first database is disconnected from a service-based architecture.
