

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396578
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Holtschlag; Deborah

Display clips

Abstract

Display clips are disclosed that may include a front plant-receiving upper hoop and a lower support base for supporting the plant or other article. The display clips also include rear first and second opposing spring clamps that allow the display clips to be removably mounted on railings between adjacent spindles. The first and second opposing spring clamps and at least one of the upper hoop and the lower support base may be made of a single piece of rod. For installation, the first and second opposing spring clamps may be drawn together to elastically deform the display clip to allow the opposing spring clamps to fit between the adjacent spindles. Once between the spindles, the opposed spring clamps can be released to spring back to engage the spindles in order to secure the display clip on the railing. The opposing spring clamps may have resilient bumpers mounted thereon to cushion and help hold the display clip on the railing spindles.

Inventors:	Holtschlag; Deborah (Pittsburgh, PA)
Applicant:	D Squared Plant Traps LLC (Pittsburgh, PA)
Family ID:	1000008781676
Assignee:	D Squared Plant Traps LLC (Pittsburgh, PA)
Appl. No.:	18/406719
Filed:	January 08, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240138598 A1	May. 02, 2024

Related U.S. Application Data

continuation parent-doc US 18369166 20230916 US 11864679 child-doc US 18406719
us-provisional-application US 63450605 20230307

Publication Classification

Int. Cl.: A47G7/04 (20060101)

U.S. Cl.:

CPC A47G7/044 (20130101);

Field of Classification Search

CPC: A47G (7/02); A47G (7/044)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
D28589	12/1897	Wedmore	N/A	N/A
1220717	12/1916	Bennett	N/A	N/A
1913587	12/1932	Edwards	N/A	N/A
1930673	12/1932	Consolazio	N/A	N/A
2747825	12/1955	Lachenmayer	N/A	N/A
3414311	12/1967	Trimboli	N/A	N/A
3502294	12/1969	Kalbow et al.	N/A	N/A
3516801	12/1969	Shah	N/A	N/A
D231296	12/1973	Morris et al.	N/A	N/A
D242314	12/1975	Arnett	N/A	N/A
D251579	12/1978	Calgaro	N/A	N/A
D262678	12/1981	DeBoer	N/A	N/A
D266382	12/1981	Hutchinson	N/A	N/A
D285510	12/1985	Douglas et al.	N/A	N/A
4623113	12/1985	Studebaker	N/A	N/A
4882875	12/1988	Green	N/A	N/A
D316058	12/1990	Mitchell et al.	N/A	N/A
5127188	12/1991	Shaw et al.	N/A	N/A
D332212	12/1992	Mitchell et al.	N/A	N/A
D337938	12/1992	Shaw et al.	N/A	N/A
D338122	12/1992	Emalfarb et al.	N/A	N/A
5269095	12/1992	Helfman et al.	N/A	N/A
D344876	12/1993	Vandergon	N/A	N/A
5320319	12/1993	Winger et al.	N/A	N/A
D350081	12/1993	May	N/A	N/A
5368267	12/1993	Howard	N/A	N/A
5390443	12/1994	Emalfarb et al.	N/A	N/A
5405116	12/1994	Shepherd et al.	N/A	N/A
5577699	12/1995	Gardner	N/A	N/A
D383916	12/1996	Richards et al.	N/A	N/A
5711433	12/1997	Smith	N/A	N/A

D393159	12/1997	Richards et al.	N/A	N/A
D406978	12/1998	Cox	N/A	N/A
D409854	12/1998	Rehmert et al.	N/A	N/A
D415366	12/1998	Walters-Dowding et al.	N/A	N/A
D419812	12/1999	Robichaud	N/A	N/A
6050532	12/1999	Paul	N/A	N/A
D425326	12/1999	Rehmert et al.	N/A	N/A
6079686	12/1999	Reed	N/A	N/A
D428848	12/1999	Wurst	N/A	N/A
D433958	12/1999	Rosenberg	N/A	N/A
D554927	12/2006	Smith	N/A	N/A
D555462	12/2006	Moffitt et al.	N/A	N/A
D573011	12/2007	Decker et al.	N/A	N/A
D628835	12/2009	Valentine, Jr.	N/A	N/A
D660102	12/2011	Allred	N/A	N/A
D678043	12/2012	Lu	N/A	N/A
8561345	12/2012	Armas	N/A	N/A
8596473	12/2012	Newbould et al.	N/A	N/A
8979043	12/2014	Florman	N/A	N/A
D885082	12/2019	Frolich	N/A	N/A
D916511	12/2020	Padgett	N/A	N/A
D1003076	12/2022	Holtschlag	N/A	N/A
D1005008	12/2022	Holtschlag	N/A	N/A
11864679	12/2023	Holtschlag	N/A	N/A
2005/0167551	12/2004	Leroux	N/A	N/A
2009/0224118	12/2008	Meyers	N/A	N/A
2011/0303809	12/2010	Tincher	N/A	N/A
2013/0264443	12/2012	Armas	N/A	N/A
2022/0087450	12/2021	Holtschlag	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
621935	12/1980	CH	N/A
924284	12/1954	DE	N/A
19643941	12/1997	DE	N/A
19643941	12/1997	DE	A47G 7/044
29821437	12/1999	DE	N/A
20014817	12/2001	DE	N/A
1025781	12/1999	EP	N/A
2014204	12/2008	EP	N/A
2520218	12/1982	FR	N/A
2617030	12/1987	FR	N/A
2859091	12/2004	FR	N/A

OTHER PUBLICATIONS

Holtschlag, U.S. Design U.S. Appl. No. 29/903,665, filed Sep. 26, 2023. cited by applicant
Holtschlag, U.S. Design U.S. Appl. No. 29/903,669, filed Sep. 26, 2023. cited by applicant
Plant traps website, Railscapes Vertical Garden Clip, Apr. 2, 2023,
<https://www.planttraps.com/products/railscaping-clip> (Year 2023). cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 18/369,166 filed Sep. 16, 2023, now U.S. Pat. No. 11,864,679, which claims the benefit of U.S. Provisional Patent Application No. 63/407,538 filed Sep. 16, 2022, and U.S. Provisional Patent Application No. 63/450,605 filed Mar. 7, 2023, all of which are incorporated herein by reference.

FIELD OF THE INVENTION

(1) The present invention relates to display clips that may be used to support and display plants and other articles on various types of railings.

BACKGROUND INFORMATION

(2) There are many devices for displaying plants on balconies and deck railings. Traditionally, plants are often displayed on the top railing.

SUMMARY OF THE INVENTION

(3) Display clips are provided that may include a front plant-receiving upper hoop and a lower support base for supporting the plant or other article. The display clips also include a rear railing support bracket with opposing spring clamps that allow the display clips to be removably mounted on railings between adjacent spindles. For installation, opposed vertical aims of the rear railing support bracket may be drawn together to elastically deform the display clip to allow the rear bracket to fit between the adjacent spindles. Once between the spindles, the opposed spring clamps can be released to spring back to engage the spindles in order to secure the bracket on the railing. The rear spring clamps may have resilient bumpers mounted thereon to cushion and help hold the display clip on the railing spindles.

(4) An aspect of the present invention is to provide a display clip for mounting on railings comprising an upper hoop, a lower support base, and first and second opposing spring clamps extending between the upper hoop and the lower support base. The first opposing spring clamp is structured and arranged to engage a first railing spindle when the display clip is mounted on a railing, and the second opposing spring clamp is structured and arranged to engage a second railing spindle when the display clip is mounted on the railing. The first and second opposing spring clamps and at least one of the upper hoop and the lower support base are made from a single piece of rod.

(5) This and other aspects of the present invention will be more apparent from the following description.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a top front isometric view of a display clip that may be used to support and display plants on railings in accordance with an embodiment of the present invention.

(2) FIG. 2 is a top rear isometric view of the display clip of FIG. 1.

(3) FIG. 3 is a front view of the display clip of FIG. 1.

(4) FIG. 4 is a rear view of the display clip of FIG. 1.

(5) FIG. 5 is a right side view of the display clip of FIG. 1.

- (6) FIG. 6 is a left side view of the display clip of FIG. 1.
- (7) FIG. 7 is a top view of the display clip of FIG. 1.
- (8) FIG. 8 is a bottom view of the display clip of FIG. 1.
- (9) FIG. 9 is a partially schematic illustration of a display clip of the present invention mounted on railing spindles and supporting and displaying a potted plant.
- (10) FIG. 10 is a partially schematic rear view of the display clip of FIG. 9.
- (11) FIGS. 11-13 schematically illustrate steps for mounting a display clip on railing spindles in accordance with an embodiment of the present invention.
- (12) FIG. 14 is a top view of a display clip kit including a packaging pocket that may be used to contain railing bumpers in accordance with an embodiment of the present invention.
- (13) FIG. 15 is a top view of the display clip kit of FIG. 14 with the packaging pocket in an open position showing a length of bumper material that may be installed on the clip prior to mounting on a railing.
- (14) FIGS. 16-18 schematically illustrate steps of cutting and mounting bumpers on opposing spring clamps of a display clip in accordance with an embodiment of the present invention.
- (15) FIGS. 19 and 20 schematically illustrate steps of mounting the display clip and bumpers of FIGS. 16-18 on railing spindles.
- (16) FIG. 21 is a partially schematic isometric view of display clips in accordance with an embodiment of the present invention mounted on railing spindles.
- (17) FIG. 22 is a partially isometric view of a display clip of FIG. 21 mounted on railing spindles and supporting and displaying a potted plant.

DETAILED DESCRIPTION

- (18) FIGS. 1-8 illustrate a display clip 10 that may be used to support and display plants or other articles on railings or similar structures in accordance with an embodiment of the present invention. The display clip 10 includes an upper hoop 12, lower support base 20, and opposing spring clamps 30. The upper hoop 12 includes a generally circular front portion 14 terminating in rear transition portions 16. In the embodiment shown, the front portion 14 and rear transition portions 16 of the upper hoop 12 lie in an upper plane that is typically horizontal when the display clip 10 is installed on a railing. Although the front portion 14 of the upper hoop 12 is circular in the embodiment shown, any other suitable shape may be used such as ovular, square, rectangular, hexagonal, octagonal, or the like.
- (19) The lower support base 20 includes a first support rod 22 and a second support rod 24, which intersect each other at a transition nose 26 near the front of the display clip 10. The first and second support rods 22 and 24 terminate near the rear of the display clip 10 at rear base transition portions 28. In the embodiment shown, the lower support base 20 including the first and second support rods 22 and 24, and transition nose 26, lie in a lower plane that is typically horizontal when the display clip 10 is installed on a railing. Although the first and second support rods 22 and 24 shown in the figures are straight and intersect each other at the transition nose 26 to form a generally triangular shape, any other suitable support rod shapes and lower support base configurations may be used. For example, each of the first and second support rods may be curved to form circular arcs that meet at the front of the support base, e.g., the lower support base may include a generally circular lower hoop of the same shape and diameter as the generally circular upper hoop 12, or a generally circular hoop of smaller diameter than the upper hoop 12. In addition to the generally triangular shape of the support base 20 shown in the figures, or a generally circular lower support base as described above, any other suitable shapes or numbers of base support rods may be used. For example, additional support rod(s) may be connected to and extend radially inward from the front portion of the support base rods described above. Such additional base support rod(s) may be connected at any desired location(s) and may lie in substantially same lower plane as the other support rods of the lower support base 20.
- (20) As further shown in FIGS. 1-8, the display clip 10 may include a front connecting arm 29

extending between the upper hoop **12** and the lower support base **20**. In the embodiment shown, the front connecting arm extends vertically from the front portion **14** of the upper hoop **12** to the transition nose **26** of the lower support base **20**. However, any other suitable number of connecting arms and locations may be provided between the upper hoop **12** and lower support base **20**, e.g., zero, two, three, etc. connecting arms. While the front connecting arm **29** shown in the figures is vertical, any other suitable orientation may be used in which the connecting arm(s) extend in a direction having a vertical component, e.g., a straight connecting arm angled radially inward or outward as it extends from the upper hoop **12** to the lower support base **20**.

(21) As further shown in FIGS. **1-8**, the display clip **10** includes opposing spring clamps **30** that may be used to install the display clip **10** on railing spindles, as more fully described below. As most clearly shown in FIGS. **1, 2, 7** and **8**, the rear portion of the display clip **10** includes first and second upper clamp recesses **32** and first and second lower clamp recesses **34** that form first and second clamp channels **35** for receiving railing spindles when the display clip **10** is installed on a railing or similar structure. The spindle-receiving upper clamp channels **35** may be structured and arranged to engage the railing spindles to hold the display clip **10** in a desired position on a railing. In the embodiment shown, the first and second clamp channels **35** have recess openings that face away from each other, and the display clip **10** is installed on railing spindles by pinching the clamp channels **35** together. Alternatively, the first and second clamp channels may have recess openings that face each other, and the display clip is installed on railing spindles by pulling the clamp channels apart.

(22) As shown in FIGS. **1-6**, first and second rear connecting arms **36** may extend between the first and second upper clamp recesses **32** and the first and second lower clamp recesses **34**, respectively. In the embodiment shown, the rear connecting arms **36** extend vertically between the upper hoop **12** and lower support base **20**. However, any other suitable shape and orientation of connecting arms may be used. Upper transitions **37** are provided between the upper clamp recesses **32** and rear connecting arms **36**. Lower transitions **38** are provided between the lower clamp recesses **34** and the rear connecting arms **36**.

(23) As shown most clearly in FIGS. **1** and **2**, the upper hoop **12** transitions into the first and second upper clamp recesses **32** at the first and second rear transition portions **16**. Similarly, the first and second support rods **22** and **24** of the lower support base **20** transition into the first and second lower clamp recesses **34** at the first and second rear base transition portions **28**. As described above, the straight first and second support rods **22** and **24** may be replaced with a continuous circular hoop, in which case the first and second rear base transition portions **28** may transition into the lower base hoop in a similar manner as the upper hoop **12** transitions with the first and second rear transition portions **16**.

(24) As shown and labeled in FIGS. **1, 2, 7** and **8**, the upper and lower clamp recesses **32** and **34** that form the clamp channels **35** are separated from each other at a clamp separation distance C prior to installation of the display clip **10** on railing spindles or other structures. As further shown, the rear connecting arms **36** are separated from each other at rear arm separation distance A prior to installation. As more fully described below, during installation of the display clip **10**, the opposing spring clamps **30** may be forced or flexed toward each other to decrease the clamp separation distance C and rear arm separation distance A to fit the opposing spring clips **30** between adjacent railing spindles in order to mount the display clip **10** on the railing.

(25) As shown in FIGS. **7** and **8**, the shapes and dimensions of the clamp channels **35** formed by the upper and lower clamps recesses **32** and **34** may be controlled in order to receive various sizes and shapes of railing spindles. Each clamp channel **35** may have a radius R and a width W , as labeled in FIG. **8**. The clamp channel radius R may typically range from 0.1 to 1 inch, or from 0.2 to 0.8 inch, or from 0.3 to 0.5 inch. For smaller sized railing spindles, such as iron or aluminum spindles, R may be relatively small, while for larger sized railing spindles, such as wood or vinyl spindles, R may be relatively large. The clamp channel width W may typically range from 0.4 to 2

inches, or from 0.5 to 1.8 inches, or from 0.6 to 1.5 inches. For smaller sized railing spindles, W may be relatively small, while for larger sized railing spindles, W may be relatively large.

(26) The upper hoop **12** may be provided in any suitable size. For example, when the upper hoop is circular in shape, it may have a typical diameter of from 4 to 12 inches, for example, from 5 to 10 inches, or from 6 to 9 inches. The height of the upper hoop **12** measured from the plane of the lower support base **20** may typically be from 2 to 6 or more inches, for example, from 3 to 5 inches.

(27) The height or length of each of the rear connecting arms **30** may be the same as or similar to the height of the upper hoop **12**. The opposed vertical arms may be located at a distance from each other of from 3 to 10 inches, and may be selected to be slightly larger than the distance between adjacent spindles of railings upon which the plant display mounting system is to be mounted. While the plant display mounting system is mounted on adjacent spindles in the figures, it is possible to secure the rear support arms on two spindles with at least one spindle in between.

(28) FIGS. **9** and **10** illustrate a display clip **10** similar to that shown in FIGS. **1-8** installed on a railing **100** in accordance with an embodiment of the present invention. The railing **100** includes multiple vertical railing spindles **102**. As shown in the front view of FIG. **9**, the display clip **10** supports and displays a plant P with the display clip **10** and plant P extending forward from the railing. As shown in the rear view of FIG. **10**, the opposing spring clamps **30** of the display clip **10** contact and partially surround adjacent railing spindles **102** of the railing **100**. The upper clamp recesses **32**, as well as the lower clamp recesses **34**, contact and may press outwardly against the adjacent spindles **102** to retain the display clip **10** in a selected position along the height of the railing spindles **102**. Each rear connecting arm **36** extending between it corresponding upper and lower clamp recesses **32** and **34** extends in a direction substantially parallel with an adjacent railing spindle **102**.

(29) FIGS. **11-13** schematically illustrate installation steps for mounting a display clip **10** on railing spindles **102**. In FIG. **11**, the display clip and opposing spring clamps **30** are in an initial position with the clamp separation distance C and rear arm separation distance A as illustrated in FIGS. **1, 2, 7** and **8** above. The initial clamp separation distance C may typically range from 2 to 12 inches, or from 3 to 11 inches, or from 4 to 10 inches. The initial rear arm separation distances A may typically range from 1 to 10 inches, or from 2 to 9 inches, or from 3 to 8 inches. In certain installations where railing spindles are relatively far apart, it may be necessary to increase the initial distances C and A, e.g., by pulling the opposing spring clamps apart to slightly deform the upper hoop **12** and lower support base **20** to thereby widen the initial distances C and A before installation on the railing spindles.

(30) In FIG. **12**, the opposing spring clamps **30** including their corresponding upper clamp recesses **32**, lower clamp recesses **34**, and rear connecting arms **36** are forced or flexed together, i.e., by hand force, to an inwardly flexed position in which the flexed clamp separation distance C' is less than the initial clamp separation distance C, and the flexed rear arm separation distance A' is less than the initial rear arm separation distance A. The difference between the flexed clamp separation distance C' and the initial clamp separation distance C may be defined as a flexed clamp separation ratio C':C which may typically be less than 0.99:1, for example, less than 0.95:1, or less than 0.9:1. The clamp separation ratio C':C may typically range from 0.99:1 to 0.4:1, for example, from 0.5:1 to 0.95:1, or from 0.6:1 to 0.9:1. The flexed rear arm separation distance A' is less than the initial rear arm separation distance A such that the flexed rear arm separation distance to initial rear arm separation distance may be defined as a flexed rear arm separation ratio A':A of less than 0.99:1, for example, less than 0.95:1, or less than 0.9:1. The flexed rear arm separation ratio A':A may range from 0.99:1 to 0.4:1, for example, from 0.95:1 to 0.5:1, or from 0.6:1 to 0.9:1.

(31) In FIG. **13**, the opposing spring clamps **30** have been released from their inwardly flexed positions shown in FIG. **12** to an installed position on the railing spindles **102**. Thus, the opposing spring clamps **30**, including the upper and lower clamp recesses **32** and **34**, and rear connecting

arms **36**, are in an installed position on the adjacent railing spindles **102**. In the installed position, the opposing spring clamps **30** define an installed clamp separation distance C'' and an installed rear arm separation distance A'' . The installed clamp separation distance C'' may be greater than the flexed clamp separation distance C' . Similarly, the installed rear arm separation distance A'' may be greater than the flexed rear arm separation distance A' . The installed clamp separation distance C'' may be the same or less than the initial clamp separation distance C . Similarly, the installed rear arm separation distance A'' may be the same or less than the initial rear arm separation distance A .

(32) FIGS. **14** and **15** illustrate a display clip kit **50** in accordance with an embodiment of the present invention. The display clip kit **50** includes the display clip **10** and a packaging pocket **52**. In the embodiment shown, the packaging pocket **52** is mounted on the first and second support rods **22** and **24** of the lower support base **20**. However, the packaging pocket **52** may be mounted at various locations on lower support bases, as described above, or may be mounted at any other suitable location on the display clip **10**. The packaging pocket **52** is shown in a closed position in FIG. **14**, and in an open position in FIG. **15**. As shown in FIG. **15**, the packaging pocket **52** has an interior **54** that contains a length of bumper tube **40** that may be removed and cut to length as more fully described below.

(33) FIGS. **16-20** illustrate steps of cutting and mounting bumper sections **42** on the upper and lower clamp recesses **32** and **34** of the display clip **10**, followed by installing the display clip **10** and bumper sections **42** on railing spindles **102**. In FIG. **16**, an initial length of bumper tube **40**, such as shown in FIG. **15**, is cut into bumper sections **42**. FIG. **16** separately shows the bumper tube **40** prior to cutting into bumper sections. As shown, the bumper tube **40** may include a lengthwise slit **41** that facilitates installation of the bumper section **42** onto their respective upper clamp recesses **32** and lower clamp recesses **34**. As shown in FIG. **17**, a bumper section **42** may be bent to open its bumper slit **41**. In FIG. **18**, the bent bumper section **42** of FIG. **17** is pressed into an upper clamp recess **32** of the display clip **10**. In FIG. **19**, the display clip **10**, with four bumper sections **42** installed, is positioned for mounting on adjacent railing spindles **102** of the railing **100**. In the position shown in FIG. **19**, the opposing spring clamps **30** are in their initial positions with the clamp separation distance C and rear arm separation distance A of FIGS. **1**, **2**, **7** and **8**. In FIG. **20**, the opposing spring clamps **30**, which have been previously flexed to a position as shown in FIG. **12**, are subsequently expanded to the installed position shown to engage the opposing railing spindles **102**.

(34) FIGS. **21** and **22** illustrate display clips **110** in accordance with another embodiment of the present invention. Each display clip **110** has similar structural features as the embodiment shown in FIGS. **1-8**, except the front connecting arm **29** is not present. In FIG. **21**, two of the display clips **110** are mounted on different pairs of railing spindles **102**. In FIG. **22**, a single display clip **110** is mounted on adjacent railing spindles **102**.

(35) The display clips may be made from a single or multiple pieces of rod or wire. Any suitable cross-sectional shape and gauge or thickness of rod may be used, for example, diameters of from 0.1 to 0.3 or 0.4 inch, or from 0.12 to 0.25 inch, or from 0.15 to 0.2 inch. The rod may be made of any suitable material such as metal, e.g., steel, aluminum or the like. For example, the rod may comprise steel that may optionally be painted, powder coated or dip coated. Alternatively, the rod may be made of relatively rigid plastic, in which case the shape and thickness of the rod may be adjusted to provide sufficient support and flexibility for the display clips. The rod may be provided in any desired color.

(36) In one embodiment, plants or other articles may be displayed up and down the spindles at any desired height. In another embodiment, plants or other articles may be displayed on the base of railings by using the spindles and bottom rail or ground for support. This allows the user an unencumbered top rail and a top-down view of a container garden as opposed to the face of a window box (resting on top of a railing) or the bottom of a hanging basket. The rear opposing spring clamps **30** may be squeezed together to be slipped between two spindles and then expand

when released to partly wrap around the spindles. The contact with the spindles stabilizes the display clips **10** and **110** and prohibits more than a small movement side to side or front to back. Some spindles may require the additional support of a commercially available zip tie, washer, clip or the like around the spindles under the device. In one embodiment, the structure may slide down the spindles to meet the ground, floor or bottom rail. In this embodiment, the ground, floor or bottom rail may provide support for the weight of the plant and planter.

(37) Installed on the exterior, the display clips may provide curb appeal and create more room for living on the interior of outdoor living spaces. Installed on the interior, the display clips may secure plants or other articles to railing spindles so they are not dislodged, e.g., by wind conditions.

Installed indoors on railings or stairs, the display clips may provide a decorative element for house plants and seasonal decorations.

(38) As used herein, “including,” “containing” and like terms are understood in the context of this application to be synonymous with “comprising” and are therefore open-ended and do not exclude the presence of additional undescribed or unrecited elements, materials, phases or method steps. As used herein, “consisting of” is understood in the context of this application to exclude the presence of any unspecified element, material, phase or method step. As used herein, “consisting essentially of” is understood in the context of this application in accordance with its customary meaning to include the specified elements or method steps, where applicable, and to also include any unspecified elements or method steps that do not materially affect the basic or novel characteristics of the invention, while excluding unspecified elements or method steps that would materially affect the basic or novel characteristics of the invention.

(39) Notwithstanding that the numerical ranges and parameters setting forth the broad scope of the invention are approximations, the numerical values set forth in the specific examples are reported as precisely as possible. Any numerical value, however, inherently contains certain errors necessarily resulting from the standard variation found in their respective testing measurements.

(40) Also, it should be understood that any numerical range recited herein is intended to include all sub-ranges subsumed therein. For example, a range of “1 to 10” is intended to include all sub-ranges between (and including) the recited minimum value of 1 and the recited maximum value of 10, that is, having a minimum value equal to or greater than 1 and a maximum value of equal to or less than 10.

(41) In this application, the use of the singular includes the plural and plural encompasses singular, unless specifically stated otherwise. In addition, in this application, the use of “or” means “and/or” unless specifically stated otherwise, even though “and/or” may be explicitly used in certain instances. In this application and the appended claims, the articles “a,” “an,” and “the” include plural referents unless expressly and unequivocally limited to one referent.

(42) Whereas particular embodiments of this invention have been described above for purposes of illustration, it will be evident to those skilled in the art that numerous variations of the details of the present invention may be made without departing from the invention as defined in the appended claims.

Claims

1. A display clip for mounting on railings comprising: an upper hoop; a lower support base; and first and second opposing spring clamps extending between the upper hoop and the lower support base, wherein: the first opposing spring clamp is structured and arranged to engage a first railing spindle when the display clip is mounted on a railing; the second opposing spring clamp is structured and arranged to engage a second railing spindle when the display clip is mounted on the railing; and the first and second opposing spring clamps and at least one of the upper hoop and the lower support base are made from a single piece of rod.

2. The display clip of claim 1, wherein: The first opposing spring clamp comprises a first upper

clamp recess adjacent the upper hoop, a first lower clamp recess adjacent the lower support base, and a first rear connecting arm extending between the first upper clamp recess and the first lower clamp recess; and the second opposing spring clamp comprises a second upper clamp recess adjacent the upper hoop, a second lower clamp recess adjacent the lower support base, and a second rear connecting arm extending between the second upper clamp recess and the second lower clamp recess.

3. The display clip of claim 2, wherein the upper hoop, the first upper clamp recess and the second upper clamp recess lie in an upper plane.

4. The display clip of claim 3, wherein the lower support base, the first lower clamp recess and the second lower clamp recess lie in a lower plane below the upper plane.

5. The display clip of claim 2, wherein the lower support base, the first lower clamp recess and the second lower clamp recess lie in a lower plane.

6. The display clip of claim 2, wherein the upper hoop comprises a circular portion.

7. The display clip of claim 2, wherein the upper hoop is interrupted in a region between the first and second upper clamp recesses.

8. The display clip of claim 2, wherein the upper hoop comprises a front portion, a first rear transition portion extending to the first upper clamp recess, and a second rear transition portion extending to the second upper clamp recess.

9. The display clip of claim 2, wherein the lower support base comprises first and second support rods.

10. The display clip of claim 9, wherein at least one of the first and second support rods comprise a straight portion.

11. The display clip of claim 9, wherein the first and second support rods comprise straight portions connected together by a transition nose.

12. The display clip of claim 2, wherein the lower support base comprises a circular portion.

13. The display clip of claim 2, wherein the lower support base is interrupted in a region between the first and second lower clamp recesses.

14. The display clip of claim 2, wherein the lower support base comprises a first rear transition portion extending to the first lower clamp recess, and a second rear transition portion extending to the second lower clamp recess.

15. The display clip of claim 2, further comprising a front connecting arm extending between a front portion of the upper hoop and the lower support base.

16. The display clip of claim 15, wherein the upper hoop lies in an upper plane, the lower support base lies in a lower plane parallel with the upper plane, and the front connecting arm is normal to the upper and lower planes.

17. The display clip of claim 2, wherein the first upper clamp recess and the first lower clamp recess define a first clamp channel structured and arranged to receive at least a portion of the first railing spindle therein, and the second upper clamp recess and the second lower clamp recess define a second clamp channel structured and arranged to receive at least a portion of the second railing spindle therein.

18. The display clip of claim 2, wherein the first upper clamp recess, the first rear connecting arm, the second upper clamp recess, the second rear connecting arm, and the upper hoop are made from the single piece of rod.

19. The display clip of claim 2, wherein the first lower clamp recess, the first rear connecting arm, the second lower clamp recess, the second rear connecting arm, and the lower support base are made from the single piece of rod.

20. The display clip of claim 2, wherein the first upper clamp recess, the first lower clamp recess, the first rear connecting arm, the second upper clamp recess, the second low clamp recess, the second rear connecting arm, the upper hoop and the lower support base are made from the single piece of rod.

21. The display clip of claim 2, further comprising at least one bumper tube structured and arranged for mounting on at least one of the first upper clamp recess, the second upper clamp recess, the first lower clamp recess and the second lower clamp recess.
 22. The display clip of claim 21, wherein the at least one bumper tube comprises a length of tube that may be cut into separate bumper tube sections for mounting on the first upper clamp recess, the second upper clamp recess, the first lower clamp recess and the second lower clamp recess.
 23. The display clip of claim 21, wherein the bumper tube comprises a slit sidewall extending along a length of the bumper tube and is made of resilient foam or rubber.
 24. The display clip of claim 1, wherein the first and second opposing spring clamps and the upper hoop are made from the single piece of rod.
 25. The display clip of claim 1, wherein the first and second opposing spring clamps and the lower support base are made from the single piece of rod.
 26. The display clip of claim 1, wherein the first and second opposing spring clamps, the upper hoop, and the lower support base are made from the single piece of rod.
-