

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12396924
B2
August 26, 2025
Danopoulos; Panagiota

Adapter for use in a planetary mixer

Abstract

A dispensing container and adapter system for use with a planetary mixer is disclosed. The dispensing container has a longitudinal axis and a transverse axis. The dispensing container may include a nozzle and a removable cap to cover the nozzle. The removable cap may have a first width dimension measured along the transverse axis. The dispensing container may include a body having a second width dimension measured along the transverse axis. An adapter may receive the dispensing container. The adapter may include a cavity to receive the removable cap. The cavity may have a cavity width that exceeds the first width dimension. The adapter may also include a recess for receiving a portion of the dispensing container. The recess may extend from the cavity. At least a portion of the recess may have a width dimension smaller than both the first width dimension and the second width dimension.

Inventors: Danopoulos; Panagiota (St-Laurent, CA)
Applicant: MEDISCA PHARMACEUTIQUE INC. (Saint-Laurent, CA)
Family ID: 1000008781658
Assignee: MEDISCA PHARMACEUTIQUE INC. (Saint-Laurent, CA)
Appl. No.: 18/393974
Filed: December 22, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240148608 A1	May. 09, 2024

Related U.S. Application Data

continuation parent-doc US 17123442 20201216 US 11883359 child-doc US 18393974
continuation parent-doc US 16372006 20190401 US 10993876 20210504 child-doc US 17123442
continuation parent-doc US 16131986 20180914 US 10420705 20190924 child-doc US 16372006
continuation parent-doc US 15809636 20171110 US 10231903 20190319 child-doc US 16131986
us-provisional-application US 62420426 20161110

Publication Classification

Int. Cl.: A61J3/04 (20060101); A61J1/05 (20060101); A61K9/00 (20060101); A61K9/06 (20060101); A61K9/107 (20060101); A61K31/045 (20060101); A61K31/135 (20060101); A61K31/137 (20060101); A61K31/192 (20060101); A61K31/195 (20060101); A61K31/196 (20060101); A61K31/197 (20060101); A61K31/351 (20060101); A61K31/4418 (20060101); A61K31/4422 (20060101); A61K31/445 (20060101); A61K31/4458 (20060101); A61K31/565 (20060101); A61K31/57 (20060101); A61K31/7048 (20060101); A61K33/14 (20060101); A61K47/10 (20170101); A61K47/26 (20060101); A61K47/38 (20060101); A61K47/42 (20170101); A61K47/46 (20060101); B01F29/00 (20220101); B01F29/10 (20220101); B01F29/32 (20220101); B01F31/00 (20220101); B01F35/22 (20220101); B01F35/42 (20220101); B29B7/10 (20060101); B65B7/16 (20060101)

U.S. Cl.:

CPC A61J1/05 (20130101); A61J3/04 (20130101); A61K9/0034 (20130101); A61K9/06 (20130101); A61K9/107 (20130101); A61K31/045 (20130101); A61K31/135 (20130101); A61K31/137 (20130101); A61K31/192 (20130101); A61K31/195 (20130101); A61K31/196 (20130101); A61K31/197 (20130101); A61K31/351 (20130101); A61K31/4418 (20130101); A61K31/4422 (20130101); A61K31/445 (20130101); A61K31/4458 (20130101); A61K31/565 (20130101); A61K31/57 (20130101); A61K31/7048 (20130101); A61K33/14 (20130101); A61K47/10 (20130101); A61K47/26 (20130101); A61K47/38 (20130101); A61K47/42 (20130101); A61K47/46 (20130101); B01F29/10 (20220101); B01F29/32 (20220101); B01F29/40 (20220101); B01F29/401 (20220101); B01F29/4011 (20220101); B01F29/40221 (20220101); B01F31/00 (20220101); B01F35/2209 (20220101); B01F35/421 (20220101); B29B7/106 (20130101); B65B7/16 (20130101); A61K31/57 (20130101); A61K2300/00 (20130101); A61K31/195 (20130101); A61K2300/00 (20130101); A61K31/045 (20130101); A61K2300/00 (20130101); A61K31/351 (20130101); A61K2300/00 (20130101); A61K31/565 (20130101); A61K2300/00 (20130101); A61K31/192 (20130101); A61K2300/00 (20130101); A61K31/196 (20130101); A61K2300/00 (20130101); A61K31/4422 (20130101); A61K2300/00 (20130101); A61K31/197 (20130101); A61K2300/00 (20130101); A61K31/445 (20130101); A61K2300/00 (20130101); A61K31/135 (20130101); A61K2300/00 (20130101); B01F29/40365 (20220101)

Field of Classification Search

CPC: A61J (1/05); A61J (3/04); A61K (9/0034); A61K (9/06); A61K (9/107); A61K (47/26); A61K (47/38); A61K (47/42); A61K (47/46); A61K (9/0056); A61K (9/10); A61K (9/146); B01F (29/10); B01F (29/32); B01F (35/2209); B01F (29/40365)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
947922	12/1909	Lewis	N/A	N/A
1059947	12/1912	McHenry	N/A	N/A
1101351	12/1913	Suit	N/A	N/A
1998692	12/1934	Rossem et al.	N/A	N/A
2728494	12/1954	Hobson	N/A	N/A
3029187	12/1961	Steinhardt et al.	N/A	N/A
3164303	12/1964	Trautmann	N/A	N/A
3470927	12/1968	Craig	N/A	N/A
3778033	12/1972	Pullman	N/A	N/A
4114803	12/1977	Romanuaskas	N/A	N/A
4323492	12/1981	Zimmermann et al.	N/A	N/A
4483847	12/1983	Augart	N/A	N/A
4497581	12/1984	Miller	N/A	N/A
4900159	12/1989	Jamison	N/A	N/A
4966468	12/1989	Brüning	N/A	N/A
5238304	12/1992	Zimmermann	N/A	N/A
6099160	12/1999	Flackett	N/A	N/A
6634576	12/2002	Verhoff et al.	N/A	N/A
6755565	12/2003	Flackett	N/A	N/A
7213994	12/2006	Phipps et al.	N/A	N/A
7438460	12/2007	Schmidt et al.	N/A	N/A
7748892	12/2009	McCoy	N/A	N/A
8191729	12/2011	Deusser et al.	N/A	N/A
8360629	12/2012	Globerman et al.	N/A	N/A
8388984	12/2012	Huguet et al.	N/A	N/A
8408418	12/2012	Kuzelka	N/A	N/A
8845180	12/2013	Huckby	N/A	N/A
8932417	12/2014	Renz et al.	N/A	N/A
8945606	12/2014	Haley	N/A	N/A
8950929	12/2014	Globerman et al.	N/A	N/A
9043019	12/2014	Eliuk et al.	N/A	N/A
9259696	12/2015	Globerman et al.	N/A	N/A
9770697	12/2016	Denize et al.	N/A	N/A
10231903	12/2018	Danopoulos et al.	N/A	N/A
10420705	12/2018	Danopoulos et al.	N/A	N/A
10494164	12/2018	Nickerson et al.	N/A	N/A
10631906	12/2019	Globerman et al.	N/A	N/A
10765600	12/2019	Danopoulos et al.	N/A	N/A
10766047	12/2019	Wong et al.	N/A	N/A
10874489	12/2019	Pierson et al.	N/A	N/A
10993876	12/2020	Danopoulos et al.	N/A	N/A
11090224	12/2020	Danopoulos et al.	N/A	N/A
11096864	12/2020	Danopoulos et al.	N/A	N/A
2001/0019725	12/2000	Miller et al.	N/A	N/A
2002/0012701	12/2001	Kolter et al.	N/A	N/A
2002/0136089	12/2001	Folestad et al.	N/A	N/A
2003/0142583	12/2002	Santospago et al.	N/A	N/A
2003/0179646	12/2002	Miller	N/A	N/A
2003/0198126	12/2002	Flackett	N/A	N/A
2004/0211747	12/2003	Whitley	N/A	N/A
2004/0265344	12/2003	Zolotariov	N/A	N/A
2006/0105022	12/2005	Yokokawa et al.	N/A	N/A
2006/0108318	12/2005	Chisholm	N/A	N/A
2006/0175443	12/2005	Bysouth	N/A	N/A
2007/0002680	12/2006	Vanderbilt et al.	N/A	N/A
2007/0002681	12/2006	Vanderbilt	N/A	N/A
2007/0002682	12/2006	Vanderbilt et al.	N/A	N/A
2007/0025180	12/2006	Ishii	N/A	N/A
2007/0140049	12/2006	Johnson et al.	N/A	N/A
2007/0280038	12/2006	Schmidt et al.	N/A	N/A
2008/0212405	12/2007	Globerman et al.	N/A	N/A
2009/0040865	12/2008	Benjamin, II	N/A	N/A
2009/0163860	12/2008	Patrick et al.	N/A	N/A
2009/0196119	12/2008	Greco et al.	N/A	N/A

2010/0161113	12/2009	Tribble et al.	N/A	N/A
2010/0185322	12/2009	Bylsma et al.	N/A	N/A
2010/0265791	12/2009	Ishii	N/A	N/A
2012/0135047	12/2011	Dodd et al.	N/A	N/A
2012/0135846	12/2011	Yao et al.	N/A	N/A
2012/0269029	12/2011	Konietzko et al.	N/A	N/A
2012/0307586	12/2011	Globerman et al.	N/A	N/A
2013/0121105	12/2012	Denize et al.	N/A	N/A
2013/0261188	12/2012	Hibi et al.	N/A	N/A
2015/0336712	12/2014	Taheri	N/A	N/A
2016/0045876	12/2015	Kaucky et al.	N/A	N/A
2016/0067178	12/2015	Arps et al.	N/A	N/A
2016/0235459	12/2015	Globerman et al.	N/A	N/A
2016/0251121	12/2015	Hadar et al.	N/A	N/A
2016/0262421	12/2015	Biglari et al.	N/A	N/A
2018/0125753	12/2017	Danopoulos et al.	N/A	N/A
2018/0345305	12/2017	Wong et al.	N/A	N/A
2018/0353919	12/2017	LaRose	N/A	N/A
2019/0008723	12/2018	Danopoulos et al.	N/A	N/A
2019/0224073	12/2018	Danopoulos et al.	N/A	N/A
2020/0054522	12/2019	Danopoulos et al.	N/A	N/A
2020/0345581	12/2019	Danopoulos et al.	N/A	N/A
2020/0345582	12/2019	Danopoulos et al.	N/A	N/A
2021/0086150	12/2020	Danopoulos et al.	N/A	N/A
2024/0108543	12/2023	Danopoulos	N/A	A61K 9/146

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
112019009594	12/2018	BR	N/A
1246053	12/1987	CA	N/A
2352874	12/2005	CA	N/A
3062126	12/2017	CA	N/A
203107245	12/2012	CN	N/A
4216252	12/1992	DE	N/A
19855440	12/1999	DE	N/A
102006049347	12/2007	DE	N/A
102008039745	12/2008	DE	N/A
10066151	12/2009	DE	N/A
102010060650	12/2010	DE	N/A
102012105819	12/2013	DE	N/A
102015100006	12/2015	DE	N/A
202017007678	12/2023	DE	N/A
0599783	12/1997	EP	N/A
1559438	12/2004	EP	N/A
2033707	12/2008	EP	N/A
2581123	12/2012	EP	N/A
3538071	12/2021	EP	N/A
4151306	12/2022	EP	N/A
2317611	12/2008	ES	N/A
S63291635	12/1987	JP	N/A
H11226376	12/1998	JP	N/A
2001347152	12/2000	JP	N/A
2002320835	12/2001	JP	N/A
2006175349	12/2005	JP	N/A
2006289163	12/2005	JP	N/A
2006305512	12/2005	JP	N/A
3977918	12/2006	JP	N/A
2008531572	12/2007	JP	N/A
2009208026	12/2008	JP	N/A
2010194470	12/2009	JP	N/A
2013237038	12/2012	JP	N/A
2013237041	12/2012	JP	N/A
2014065010	12/2013	JP	N/A
2015500334	12/2014	JP	N/A
2015027676	12/2014	JP	N/A
2015092148	12/2014	JP	N/A
2016523950	12/2015	JP	N/A
2019535708	12/2018	JP	N/A
97/02089	12/1996	WO	N/A
2003089124	12/2002	WO	N/A
2006042091	12/2005	WO	N/A
2009020167	12/2008	WO	N/A
2012133492	12/2011	WO	N/A
2014083029	12/2013	WO	N/A
2014144814	12/2013	WO	N/A

OTHER PUBLICATIONS

Chemical Book, Lactose CAS# 63-42-3, obtained online at https://www.chemicalbook.com/ProductChemicalPropertiesCB8710411_EN.htm, downloaded on [unintelligible], cited by examiner

LiverTox: Clinical and Research Information on Drug-Induced Liver Injury [Internet]. Bethesda (MD): National Institute of Diabetes and Digestive and Kidney Diseases; 2012. National Institute of Diabetes and Digestive and Kidney Diseases. Nervous System (CNS) Stimulants. [Updated Aug. 12, 2021]. Available from: <https://www.ncbi.nlm.nih.gov/books/NBK548702/> (Year: 2021). cited by examiner

Chemical Book, 112111-43-0 (armodafinil), obtained online at https://www.chemicalbook.com/ChemicalProductProperty_US_CB3500844.aspx, downloaded on [unintelligible], cited by examiner

Allen, Loyd V., and M. A. Erickson. "Secundum Artem." Current and Practical Compounding Information for the Pharmacist Pharmaceutical Compounding Formulary 10.1. (Year: 2009). cited by examiner

Nichols, 6.1C: Melting Point Theory, obtained online at: <https://chem.libretexts.org/@go/page/93433>, downloaded on Jul. 28, 2024. (Year: 2022). cited by examiner

PPHhealthcare, Understanding the Temperature-Sensitive Nature of Drugs, obtained online at: <https://pphealthcaresolutions.co.uk/understanding-temperature-sensitive-nature-of-drugs/#:~:text=Thermolabile%20drugs%20are%20those%20that,drugs%20include%20insulin%20and%20vaccines>. Downloaded on Jan. 20, 2025. (Year: 2022). cited by examiner

World Health Organization. Temperature sensitivity of vaccines. No. WHO/IVB/06.10. World Health Organization, 2006. (Year: 2006). cited by examiner

Christchurch Medicines Information Service, Assessing medicines when stored outside manufacturer recommendations, obtained online at: <https://www.medicinesinformation.co.nz/bulletins/assessing-medicines-when-stored-outside-manufacturer-recommendations/>, downloaded on Jan. 20, 2025 (Year: 2022). cited by examiner

Crichton, Brian. "Keep in a cool place: exposure of medicines to high temperatures in general practice during a British heatwave." Journal of the royal society of medicine 97.3 (2004). cited by examiner

Notice of Allowance issued on Jan. 21, 2021, in connection with U.S. Appl. No. 16/372,006, 18 pages. cited by applicant

Notice of Allowance issued on Jun. 7, 2021, in connection with U.S. Appl. No. 16/932,313, 7 pages. cited by applicant

Notice of Allowance issued on May 13, 2021, in connection with U.S. Appl. No. 16/932,171, 5 pages. cited by applicant

Office Action issued on Feb. 24, 2021, in connection with European Patent Application No. 17868979.0, 6 pages. cited by applicant

Office Action issued on Jun. 2, 2021, in connection with U.S. Appl. No. 17/123,400, 16 pages. cited by applicant

Office Action issued on Mar. 29, 2021, in connection with U.S. Appl. No. 16/932,171, 7 pages. cited by applicant

Office Action issued on Mar. 4, 2021, in connection with U.S. Appl. No. 16/932,313, 21 pages. cited by applicant

Office Action issued on Mar. 9, 2021, in connection with U.S. Appl. No. 16/932,171, 12 pages. cited by applicant

Restriction Requirement issued on May 12, 2021, issued in connection with U.S. Appl. No. 17/123,400, 5 pages. cited by applicant

Examiner's report issued on Jul. 22, 2021, in connection with Canadian Patent Application No. 3,106,928, 3 pages. cited by applicant

Examiner's Report issued on Nov. 4, 2021, in connection with CA patent application No. 3,131,133—5 pages. cited by applicant

Examiner's Report issued on Nov. 9, 2021, in connection with CA patent application No. 3,106,934—6 pages. cited by applicant

Examiner's Report issued Dec. 2, 2021, in connection with CA patent application No. 3,131,129—6 pages. cited by applicant

Office Action issued Oct. 12, 2021, in connection with Japanese patent application No. 2019-524437—6 pages (+ English translation, 8 pages). cited by applicant

Final Office Action issued on Dec. 10, 2021, in connection with U.S. Appl. No. 17/123,400 (7 pages). cited by applicant

Communication under Rule 71(3) EPC issued Apr. 5, 2022, in connection with EP patent application No. 17 868 979.0 (7 pages). cited by applicant

Notice of Allowance issued Apr. 7, 2022, in connection with CA patent application No. 3,106,928 (1 page). cited by applicant

Examiner's Report issued May 3, 2022, in connection with CA patent application 3131129 (4 pages). cited by applicant

Notice of Allowance issued Apr. 27, 2022, in connection with CA patent application 3043494 (1 page). cited by applicant

Examiner's Report issued May 4, 2022, in connection with CA patent application 3131133 (4 pages). cited by applicant

A Novel Blending Method for Dispensing Powdered Medicine—Chem Pharm Bull 62(1) 54-57 (2014)—(4 pages). cited by applicant

Kitagawa, S. et al.; Effects of Mixing Procedure Itself on the Structure, Viscosity, and Spreadability of White Petrolatum and Salicylic Acid Ointment and the Effect of Salicylic Acid on the Viscosity of White Petrolatum. J. Pharm. Sci. 94(1) 1-10 (2005). cited by applicant

20 Ways Improving Patient Care & Pharmacy Profitability; Cardinal Health Community Specialty LTC; Copyright 2017 (92 pages). cited by applicant

The MAZ Mixing Machine-New Capabilities; YouTube video, <https://www.youtube.com/watch?v=Iddugkg88EI>, lists "Jan. 5, 2017". cited by applicant

Download the Maz Brochure [https://web.archive.org/web/20170731081433/https://www.medisca.com/Pages/Product Details/Mazerustar/pdf/ Mazerustar Brochure.pdf](https://web.archive.org/web/20170731081433/https://www.medisca.com/Pages/Product%20Details/Mazerustar/pdf/Mazerustar%20Brochure.pdf), 2017. cited by applicant

Medisca, Mazerustar—A Revolutionary Mixer Ideal for Topicals, Liquids, Creams, and Powders, from web archive.org that lists "20170731081433" in the URL <https://web.archive.org/web/20170731081433/https://www.medisca.com/mazerustar>, 2017. cited by applicant

Medisca, Your Trusted Partner in Compounding; The Maz Mix. Deaerate. Melt. Mill.; Learn More, taken from web.archive.org that lists "20170613112836" in the URL <https://web.archive.org/web/20170613112836/https://www.medisca.com/mazerustar>, 2017. cited by applicant

Medisca, Your Trusted Partner in Compounding; The Maz Mix. Deaerate. Melt. Mill.; Compounding Products, taken from web.archive.org that lists "20170613112836" in the URL <https://web.archive.org/web/20170613112836/https://www.medisca.com/?ReturnUrl=%2fpromotions>, 2017. cited by applicant

Medisca, Your Trusted Partner in Compounding; Promotions, Your Monthly Specials Are Here; View Specials, taken from web.archive.org that lists "20170613112836" in the URL <https://web.archive.org/web/20170603222511/https://www.medisca.com/promotions>, 2017. cited by applicant

Compounding Pharmacy Products and Services at Medisca; Medisca, Your Trusted Partner in Compounding; Promotions, Your Monthly Specials Are Here; View Specials, taken from web.archive.org that lists "20170603222511" in the URL (37 pages), 2017. cited by applicant

Tian et al.; "Vesicular phospholipid gel-based depot formulations for pharmaceutical proteins: Development and in vitro evaluation"; Journal of Controlled Release 161.3 (2014) 325. cited by applicant

Mazerustar, One Single Technology Multiple Capabilities, Apr. 12, 2017, Medisca (8 pages). cited by applicant

Medisca, Your Trusted Partner in Compounding: New Base (Gelatin Gum Base), Jun. 25, 2014, (1 page). cited by applicant

Hunnius Pharmazeutisches Wörterbuch, Walter de Gruyter GmbH, Berlin/Boston, copyright 2014 (6 pages). cited by applicant

Expert Opinion of Prof. Dr. Gerhard Winter regarding German part of the European patent EP 3 538 071 B1, Jan. 17, 2024 (28 pages). cited by applicant

Rudolf Voigt, Pharmazeutische Technologie Für Studium und Beruf, Deutscher Apotheker Verlag Stuttgart, copyright 2010 (8 pages). cited by applicant

Claim chart submitted in action for revocation of EP 3538071, dated Jan. 19, 2024 (3 pages). cited by applicant

Medisca Response to EPO Communication of Mar. 27, 2023, dated Sep. 22, 2023 (12 pages). cited by applicant

Medisca Response to EPO Communication of Dec. 22, 2023, dated Apr. 22, 2024 (24 pages). cited by applicant

EPO Summons to attend Oral Proceedings in EP 22192358.4, dated Jun. 10, 2024 (5 pages). cited by applicant

Oh! Planetary centrifugal mixers contribute to society, Mar. 2016 (20 pages). cited by applicant

Gako International Brochure, copyright 2016 (1 page). cited by applicant

Application for cancellation of utility model No. DE 202017007678, Jul. 10, 2024 (3 pages). cited by applicant

Submission regarding German utility model DE202017007678.0, dated Apr. 4, 2024 (132 pages). cited by applicant

Order of the District Court of Munich regarding EP 3 538 071, dated Apr. 9, 2024 (6 pages). cited by applicant

Martin A Erickson III, RPh, "Your Compounding Questions Answered," Pharmacy Times, vol. 78, Issue 7 (dated Jul. 9, 2012). cited by applicant

Lj. Djakovic et al., "Rheological Behavior of Thixotropic Starch and Gelatin Gels," vol. 42, No. 10, pp. 380-385 (copyright 1990). cited by applicant

Shilpa Sanwani et al., "Hydration of Gelatin Molecules in Glycerol—Water Solvent and Phase Diagram of Gelatin Organogels," J. Phys. Chem., vol. 115, pp. 2011). cited by applicant

Fernando A. Osorio et al., "Effects of Concentration, Bloom Degree, and pH on Gelatin Melting and Gelling Temperatures Using Small Amplitude Oscillatory Properties, vol. 10, pp. 841-851, (copyright 2007). cited by applicant

Susumu Goto et al., "Turbulent mixing in a precessing sphere," Phys. Fluids, vol. 26, 24 pages, (copyright 2014). cited by applicant

Pediatric Compounding—PCCA—Professional Compounding Centers of America website at <http://web.archive.org/web/20150926003212/http://www.pccarx.com/compounding/specialty-compounding/pediatric-compounding>, Sep. 26, 2015 (7 pages). cited by applicant

Flavor Compounding—PCCA—Professional Compounding Centers of America website at <http://web.archive.org/web/20151231124835/http://www.pccarx.com/compounding/specialty-compounding/flavor-compounding>, Dec. 31, 2015 (3 pages). cited by applicant

Francesca Milano et al., "Current Trends in Gelatin-Based Drug Delivery Systems," Pharmaceutics, vol. 15, (copyright 2023) (34 pages). cited by applicant

SpeedMixer Technology—Bladeless Mixing | Speedmixer website at <http://web.archive.org/web/20160128164145/http://speedmixer.com:80/speedmixer-tech> (pages). cited by applicant

SpeedMixer Containers website at <http://web.archive.org/web/20130119075143/http://www.speedmixer.com/containers.php>, Jan. 19, 2013 (1 page). cited by applicant

Mixer Mill MM400 website at <http://web.archive.org/web/20160115200322/http://www.retsch.com:80/products//milling/ball-mills/mixer-mill-mm-400/function> (6 pages). cited by applicant

International Search Report issued on Feb. 6, 2018 in connection with International Patent Application No. PCT/CA2017/051350, 3 pages. cited by applicant

Written Opinion issued on Feb. 6, 2018 in connection with International Patent Application No. PCT/CA2017/051350, 4 pages. cited by applicant

Non-Final Office Action issued on Apr. 10, 2018 in connection with U.S. Appl. No. 15/809,636, 19 pages. cited by applicant

Non-Final Office Action issued on Dec. 10, 2018 in connection with U.S. Appl. No. 16/131,986, 18 pages. cited by applicant

Restriction Requirement issued on May 24, 2019 in connection with U.S. Appl. No. 16/372,006, 6 pages. cited by applicant

Examiner's Report issued on Jul. 25, 2019 in connection with Canadian Patent Application No. 3,043,494, 3 pages. cited by applicant

Non-Final Rejection issued on USPTO on Aug. 15, 2019 in connection with U.S. Appl. No. 16/372,006, 17 pages. cited by applicant

Non-Final Office Action issued on Dec. 9, 2019 in connection with U.S. Appl. No. 16/662,423, 15 pages. cited by applicant

Examiner's Report issued on Dec. 13, 2019 in connection with Canadian Patent Application No. 3,043,494, 4 pages. cited by applicant

Final Office Action issued on Dec. 16, 2019 in connection with U.S. Appl. No. 16/372,006, 19 pages. cited by applicant

Examiner's Report issued on Feb. 6, 2020 in connection with Canadian Patent Application No. 3,062,126 3 pages. cited by applicant

Examiner's Report issued on Feb. 12, 2020 in connection with Canadian Patent Application No. 3,043,494, 5 pages. cited by applicant

Advisory Action and Applicant-initiated Interview Summary issued on Mar. 26, 2020 in connection with U.S. Appl. No. 16/372,006, 9 pages. cited by applicant

Notice of Allowance issued on Apr. 10, 2020 in connection with U.S. Appl. No. 16/662,423, 14 pages. cited by applicant

Supplementary European Search Report issued on Apr. 23, 2020 in connection with European Patent Application No. 17 86 8979, 2 pages. cited by applicant

Extended European Search Report issued May 6, 2020 in connection with European Patent Application No. 17 86 8979, 4 pages. cited by applicant

Restriction Requirement issued on Aug. 7, 2020 in connection with U.S. Appl. No. 16/932,313, 7 pages. cited by applicant

Restriction Requirement issued on Aug. 7, 2020 in connection with U.S. Appl. No. 16/932,171, 7 pages. cited by applicant

Office Action issued on Aug. 12, 2020 in connection with U.S. Appl. No. 16/372,006, 25 pages. cited by applicant

Examiner's Report issued on Oct. 23, 2020 in connection with Canadian Patent Application No. 3062126, 3 pages. cited by applicant

Applicant-initiated Interview summary issued on Oct. 26, 2020 in connection with U.S. Appl. No. 16/372,006, 12 pages. cited by applicant

Esezobo S et al., "Moisture and gelatin effects on the interparticle attractive forces and the compression behaviour of oxytetracycline formulations" 7 pages (Y applicant

English translation of Suzuki et al. JP 2002-320835 (Year: 2002)). cited by applicant

English translation of Thinky Corp et al. (JP 2009-208026) (Year: 2009). cited by applicant

Karim A.A. et al., Food Hydrocolloids, 23, pp. 563-576 (Year: 2009). cited by applicant

Intertronics, THINKY An Introduction to Planetary Centrifugal Mixers, obtained online at: http://www.intertronics.co.uk/wp-content/uploads/2017/04/getting_to_know_thinky_mixers.pdf, pp. 1-26. (Year: 2009). cited by applicant

Intertronics, THINKY An introduction to Planetary Centrifugal Mixers, obtained online at <https://www.intertronics.co.uk/wp-content/uploads/2017/04/getting-to-know-thinky-mixers.pdf>, 26 (Year:2011). cited by applicant

Ice.edu, Taste Test: Fluid Gels, obtained online at: <https://www.ice.edu/blog/taste-test-fluid-gels>, pp. 1-5 (Year:2012). cited by applicant

USP on Compounding, A Guide for the Compounding Practitioner—2014, Nov. 2013, (375 pages). cited by applicant

Miyazaki et al., "A novel blending method for dispensing powered medicine", Chem. Pharm. Bull., 2014, vol. 62, Issue 1, pp. 54-57. cited by applicant

Keiichi, Hori "User interview—Prossessor Keiichi hori JAXA", Thinky Library, obtained at: <https://www.thinkymixer.com/en-gl/library/interview/user-interview-jaxa/> Jul. 14, 2016. cited by applicant

Screen Captures from YouTube video clip entitled "Planetary Centrifugal Mixer ARE 310" obtained at: <https://www.youtube.com/watch?v=fIMHXrfWYfM>, 2016. cited by applicant

Notice of Allowance issued on Apr. 10, 2020 in connection with United States U.S. Appl. No. 16/662,423, 16 pages. cited by applicant

"Pursuing a Bright Future With Mixing Technology"; THINKY; final page of document lists Apr. 2016; (8 pages). cited by applicant

"Pioneering Planetary Centrifugal Mixers"; Thinky Mixer Series; final page of document lists "Oct. 2010" (32 pages). cited by applicant

THINKY Mixer ARE-310 Instruction Manual; "Planetary Centrifugal Mixer"; THINKY Corporation; p. 65 of document lists "Issued Nov. 7, 2008" and "Rev. 1.0" (pages). cited by applicant

Chen et al., "Nanonization Strategies For Poorly Water-Soluble Drugs," Drug Discovery Today, vol. 16, Nos. 7/8; Apr. 2011; 7 pages. cited by applicant

Food and Drug Administration; Draft "Guidance For Industry Powder Blends and Finished Dosage Units—Stratified In-Process Dosage Unit Sampling and Analysis" (pages). cited by applicant

Hiseman et al., "Granular Flow in a Planetary Mixer," Institution of Chemical Engineers, Trans IChemE; vol. 80, Part A, Jul. 2002, 9 pages. cited by applicant

Mehrotra et al., "Comparing Mixing Performance of Uniaxial and Biaxial Bin Blenders," Powder Technology 196 (2009), 7 pages. cited by applicant

Niwa et al., "Novel Technology to Prepare Oral Formulations for Preclinical Safety Studies," International Journal of Pharmaceutics 350 (2008), 9 pages. cited by applicant

Niwa et al., "Universal Wet-Milling Technique to Prepare Oral Nanosuspension Focused on Discovery and Preclinical Animal Studies—Development of Particulate Nanosuspensions," International Journal of Pharmaceutics 405 (2011), 10 pages. cited by applicant

Sawant et al., "Drug Nanocrystals: Novel Technique for Delivery of Poorly Soluble Drugs," International Journal of Science Innovations and Discoveries, vol. 15, 15 pages. cited by applicant

Takatsuka et al., "Nanosizing of Poorly Water Soluble Compounds Using Rotation/Revolution Mixer," Chem. Pharm. Bull. 57(10); Oct. 2009; 7 pages. cited by applicant

Yin, Trudy; "A Guide to Blend Uniformity," Journal of GXP Compliance, vol. 12, No. 1, Oct. 2007, 6 pages. cited by applicant

Applicant-initiated Interview Summary issued on Apr. 2, 2021, in connection with U.S. Appl. No. 16/932,171, 2 pages. cited by applicant

Examiner Report issued on May 21, 2021, in connection with Canadian Patent Application No. 3,043,494, 3 pages. cited by applicant

Examiner's Report issued on Mar. 5, 2021, in connection with Canadian patent application No. 3,106,928, 4 pages. cited by applicant

Examiner's Report issued on Feb. 5, 2021, in connection with Canadian patent application No. 3,043,494, 4 pages. cited by applicant

Examiner's Report issued on May 10, 2021, in connection with Canadian patent application No. 3,106,934, 4 pages. cited by applicant

Knowing your mix is completely homogeneous and air free, Intertronics presentation, Nov. 3, 2011 (35 pages). cited by applicant

S. Barbosa et al., "Physical-chemical properties of furosemide nanocrystals developed using rotation revolution mixer," Pharm. Dev. Technol., vol. 21, No. 7, cited by applicant

Kate Douglass et al., "Requirements and Best Practices for Sanitizing Engineering Controls," Pharmacy Purchasing & Products, Sep. 2013, pp. 16-22 (5 pages)

Planetary Centrifugal Mixer ARE 310 & Planetary Centrifugal Vacuum Mixer ARV 310; Youtube video; <https://www.youtube.com/watch?v=MudA4yDGtll&pp=ygVQUUGxhbmV0YXJ5IENlbnRyaWZ1Z2FsIE1peGVyIEFSRSaZMTAgJiBQbGFuZXRhcncgQ2VudHJpZnVnYWwgVmFjdXVtIEI> (1 page) 2015. cited by applicant

Department of Health, Board of Pharmacy, Compounding Rules Committee, Feb. 10, 2014 (5 pages). cited by applicant

Planetary Centrifugal Vacuum Mixer [ARV-310] | Thinky Corporation; Youtube video; <https://www.youtube.com/watch?v=QVHJzTRQLok>; (1 page), 2014. cited by applicant

Thinky mixer—Thinky Corporation; Youtube video; <https://www.youtube.com/watch?v=jtiVIP9Bm2I>; (1 page) 2014. cited by applicant

Primary Examiner: Vanhorn; Abigail

Attorney, Agent or Firm: Finnegan, Henderson, Farabow, Garrett & Dunner LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application is a continuation application of and claims the benefit of priority to U.S. application Ser. No. 17/123,442 filed on Dec. 16, 2020, which is a continuation application of and claims the benefit of priority to U.S. patent application Ser. No. 16/372,006 filed on Apr. 1, 2019 (now U.S. Pat. No. 10,993,876), which is a continuation application of and claims the benefit of priority to U.S. patent application Ser. No. 16/131,986 filed on Sep. 14, 2018 (now U.S. Pat. No. 10,420,705), which is a continuation application of and claims the benefit of priority to U.S. patent application Ser. No. 15/809,636 filed on Nov. 10, 2017 (now U.S. Pat. No. 10,231,903), which claims the benefit of priority to U.S. Provisional Patent Application No. 62/420,426 filed on Nov. 10, 2016, the contents of all of which are incorporated herein by reference in their entirety

TECHNICAL FIELD

(1) The present disclosure generally relates to the field of compounding pharmaceutical compositions and, more specifically, to compounded pharmaceutical compositions having improved quality properties as well as to systems and methods for making same.

BACKGROUND

(2) Medical facilities, licensed pharmacist or physicians may produce individual pharmaceutical compositions by blending together various ingredients, such as one or more active pharmaceutical ingredient (API) and pharmaceutically acceptable excipients, diluent or solvents, to create a medicine product tailored to the needs of an individual patient. Such activities are commonly referred as pharmaceutical compounding. Practically speaking, in the context of pharmacy compounding, the pharmacist will typically prepare such product tailored to the needs of an individual patient based on a medical prescription.

(3) Pharmaceutical compounding involves blending of the composition ingredients, which is typically performed using manual mixing, for example, using a pestle and mortar. However, manually mixing ingredients can be time-consuming and is often prone to cross-contamination from poorly decontaminated or sterilized equipment used for the mixing. Along with the contamination risk, there is also the problem that performing manual mixing often results in products that face repeatability and/or quality challenges. In other words, it is often difficult to obtain compositions having consistent concentrations of API from one composition to another and/or consistent homogeneous API concentration within one preparation per se. This may result in substantial qualitative differences during manufacture of the same recipe, which at minimum can have an effect on the effectiveness of the recipe.

(4) In this regard, various practical devices have been previously suggested to overcome the above deficiencies of compounding pharmaceutical compositions using manual mixing.

(5) U.S. 2012/0269029 (Konietzko) describes a program-controlled mixer, which includes a control unit, a motor-driven mixing unit with a blade mixing tool, which engages into a mixing vessel, and a lift unit. The lift unit produces an axial relative motion between the blade mixing tool and the mixing vessel, to move the blade mixing tool in the mixing vessel between an upper end position and a lower one, preferably at a constant lifting speed.

(6) A deficiency associated with many mixing devices is that they often involve mixing using blades that contact the mixture causing high shearing forces, which can generate so much heat during mixing so as to degrade thermally labile API.

(7) Additionally or alternatively, many mixing devices often entrain air into the composition being mixed. The entrained air forms air bubbles in the composition modifying thereafter the specific gravity of the pharmaceutical composition. Since the specific gravity is the ratio of the density of the composition to the density of a reference substance; equivalently, it is the ratio of the mass of the composition to the mass of a reference substance for the same given volume. Variations in specific gravity of a composition can be detrimental in that such variations alters the aforementioned ratio and, accordingly, alters the API weight content which is filled in a pharmaceutical container for a given volume of composition filled in. This is particularly critical for pharmaceutical dispensing devices dispensing measured doses which need to dispense consistent amounts of API for a given volume from one device to another one, and from one dispensed volume to the next in the same dispensing device.

(8) In other cases, the entrained air must be removed in order to eliminate the air bubbles from the pharmaceutical composition and thereby improve the appearance of the pharmaceutical composition. For instance, in the production of either translucent or transparent pharmaceutical compositions, it is mandatory to remove the air bubbles since these would otherwise negatively affect the translucency or transparency of the pharmaceutical compositions by imparting opacity zones thereto. However, such de-aeration is time consuming, lowers throughput and generally requires additional vacuum configurations, which can be cumbersome and increase overall manufacturing costs.

(9) Additionally or alternatively, many mixing devices often require mixing in device-specific mixing containers, which thus requires an additional step of decanting the pharmaceutical mixture into a dispensing device container, thereby increasing the risk of material loss during the decanting procedure. Device-specific containers also limit the volume and/or mass of materials that can be mixed to the specifications of such containers, which is not always ideal from a practical perspective. Device-specific containers also require implementing strict cleaning/sterilization procedures to avoid cross-contamination risk when one wishes to reuse the same mixing containers, which can be cumbersome and time-consuming. Otherwise, operation costs and waste are increased when container are used and are discarded after each mixing procedure, i.e., when used as single-use mixing containers.

SUMMARY

(10) This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key aspects or essential aspects of the claimed subject matter.

(11) There is a need to provide improved compounded pharmaceutical composition having improved quality properties as well as devices and methods for making same, which alleviate at least in part the deficiencies of the existing devices and methods for making compounded pharmaceutical compositions.

(12) In one embodiment, the present disclosure aims to at least address how to reduce qualitative differences during manufacturing of compounded

pharmaceutical composition mixtures, and/or increase productivity, and/or improve effectiveness of compounded pharmaceutical composition mixtures.

(13) In one broad aspect, the present disclosure relates to a composition comprising an active pharmaceutical ingredient (API) dispersed in a pharmaceutically acceptable excipient, carrier or diluent, the composition exhibiting a concentration gradient of the API with $\leq 6\%$, or $\leq 5\%$, or $\leq 4\%$, or $\leq 3\%$, or $\leq 2\%$, or $\leq 1\%$, or about 0% relative standard deviation (RSD) when measured by high-performance liquid chromatography (HPLC), wherein the concentration is that of at least top, middle and bottom layers of the composition within the container, and wherein the composition is personalized for a patient.

(14) In another broad aspect, the present disclosure relates to a composition comprising an active pharmaceutical ingredient (API) dispersed in a pharmaceutically acceptable excipient, carrier or diluent, the composition exhibiting a concentration gradient of the API with $\leq 6\%$, or $\leq 5\%$, or $\leq 4\%$, or $\leq 3\%$, or $\leq 2\%$, or $\leq 1\%$, or about 0% relative standard deviation (RSD) when measured by high-performance liquid chromatography (HPLC), wherein the concentration is that of at least top, middle and bottom layers of the composition within the container, and wherein the composition is personalized for a patient, the composition having a specific gravity which is within 20% of corresponding specific gravity of the pharmaceutically acceptable excipient, diluent or carrier in absence of the API.

(15) In yet another aspect, the present disclosure relates to a troche comprising an active pharmaceutical ingredient (API) dispersed in a pharmaceutically acceptable excipient, carrier or diluent, wherein the API is thermolabile at a temperature above 60°C ., and the troche includes less than 1% degradation products of the API, wherein the troche is personalized for a patient

(16) In yet another aspect, the present disclosure relates to a compounding method, comprising: providing a container including therein a pharmaceutically acceptable excipient, carrier or diluent, and an active pharmaceutical ingredient (API); subjecting the container to superimposed revolution and rotation movements to disperse the pharmaceutically acceptable excipient, carrier or diluent, and the API and produce a composition exhibiting a concentration gradient of the API with $\leq 6\%$, or $\leq 5\%$, or $\leq 4\%$, or $\leq 3\%$, or $\leq 2\%$, or $\leq 1\%$, or about 0% relative standard deviation (RSD) when measured by high-performance liquid chromatography (HPLC), wherein the concentration is that of at least top, middle and bottom layers of the composition within the container, and wherein the composition is personalized for a patient.

(17) In yet another aspect, the present disclosure relates to a compounding method, comprising: providing a container including therein a pharmaceutically acceptable excipient, carrier or diluent having a first specific gravity, and an active pharmaceutical ingredient (API); and subjecting the container to superimposed revolution and rotation movements to disperse the pharmaceutically acceptable excipient, carrier or diluent, and the API and produce a composition having a second specific gravity and exhibiting a concentration gradient of the API with $\leq 6\%$, or $\leq 5\%$, or $\leq 4\%$, or $\leq 3\%$, or $\leq 2\%$, or $\leq 1\%$, or about 0% relative standard deviation (RSD) when measured by high-performance liquid chromatography (HPLC), wherein the concentration is that of at least top, middle and bottom layers of the composition within the container, and wherein the composition is personalized for a patient, wherein the second specific gravity is within 50%, or 40%, or 30%, or 20%, or 10%, of the first specific gravity without introducing air into the composition.

(18) In yet another aspect, the present disclosure relates to a compounding method, comprising: providing a container including therein gelatin gum base particles; subjecting the container to first superimposed revolution and rotation movements to disperse the particles and produce a melt composition; adding an active pharmaceutical ingredient (API) into the melt to obtain an API-containing melt; subjecting the container comprising the API-containing melt to second superimposed revolution and rotation movements to disperse the API-containing melt and obtain a dispersed melt composition; and cooling the dispersed melt composition to obtain a dispersed solid composition, wherein the dispersed solid composition is personalized for a patient.

(19) In yet another aspect, the present disclosure relates to a compounding method, comprising: providing a container including therein particles of a pharmaceutically acceptable excipient, pharmaceutically acceptable carrier, or an active pharmaceutical ingredient (API), wherein the particles have a starting D.sub.50; subjecting the container to first superimposed revolution and rotation movements in presence of grinding beads to produce a milled composition including particles having a milled D.sub.50, wherein the starting D.sub.50 to milled D.sub.50 represent a ratio of at least 2.5, incorporating into the milled composition at least one of a pharmaceutically acceptable excipient, pharmaceutically acceptable carrier, or API and removing the grinding media from the container before or after said incorporating, and subjecting the container to second superimposed revolution and rotation movements to obtain a composition.

(20) In one embodiment, any one of the herein described method is performed in a pharmacy setting.

(21) In another embodiment, any one of the herein described method is performed under the supervision of a licensed pharmacist.

(22) In another embodiment, any one of the herein described method is performed by a licensed pharmacist or a licensed physician.

(23) In one embodiment, the composition can be a cream, ointment, lotion, emulsion, gel, suspension, powder, liquid solution, colloidal dispersion, troche or syrup.

(24) In one embodiment, the composition of the present disclosure is a composition which is personalized for a patient.

(25) For the purpose of the present disclosure, the expressions "compounded pharmaceutical composition" and "composition personalized for a patient" are used interchangeably and refer in particular to those single compositions which are assembled in a medical facility, or by a licensed pharmacy (as opposed to those compositions made in batch in a pharmaceutical industrial plant) where a pharmacist combines, mixes, or alters ingredients in response to a doctor's prescription to create a medicine tailored to the medical needs of an individual patient. In other words, the type and/or concentration of at least one of the API, the excipient, diluent or carrier is customized to create a composition tailored to the medical needs of the patient.

(26) Compounding may, thus, be used in a variety of situations where a patient cannot be treated with a standard, commercially available, FDA-(or other regulatory body) approved medicine.

(27) For example, a patient might be allergic to the kind of dye used in a commercially available medication. In this case, the compounding personnel would formulate the medication without the dye or with another dye. Or, sometimes elderly patients or children who cannot swallow tablets need their medicine in a liquid or suppository form that is not commercially available. Suspensions possess certain advantages over other dosage forms. Some drugs are insoluble in all acceptable media and must, therefore, be administered as a tablet, capsule, or as a suspension. Because of their liquid character, suspensions represent an ideal dosage form for patients who have difficulty swallowing tablets or capsules. This factor is of particular importance in administration of drugs to children. Suspensions of insoluble drugs may also be used externally, often as protective agents.

(28) In addition, disagreeable tastes can be masked by a suspension of the drug or a derivative of the drug, an example of the latter being the drug chloramphenicol palmitate. Finally, drugs in suspension are chemically more stable than in solution. This is particularly important with certain antibiotics and the pharmacist is often called on to prepare such a suspension just prior to the dispensing of the preparation.

(29) Sometimes, a patient may require a special API dosage and thus, the compounding personnel will customize the API concentration in the compounded composition.

(30) In other cases, a patient may be allergic to the API in the commercially available medication and the compounding personnel will thus customize the composition by replacing the API with another one, hypoallergenic for the patient.

(31) The person of skill will recognize that such are examples of a composition which is personalized for a patient.

(32) All features of embodiments which are described in this disclosure and are not mutually exclusive can be combined with one another. Elements of one embodiment can be utilized in the other embodiments without further mention. Other aspects and features of the present invention will become apparent to those ordinarily skilled in the art upon review of the following description of specific embodiments in conjunction with the accompanying Figures.

Description

BRIEF DESCRIPTION OF FIGURES

- (1) A detailed description of specific embodiments is provided herein below with reference to the accompanying drawings in which:
- (2) FIG. 1 shows a cross section view of a jar including a composition which is personalized for a patient, where the container is virtually separated in top, middle and bottom sections, each including respective top, middle and bottom layers of the composition, in accordance with an implementation of the present invention;
- (3) FIG. 2 is a flow diagram of a process to obtain the patient personalized composition of FIG. 1, in accordance with an implementation of the present invention;
- (4) FIG. 3 is a flow diagram of a variant of the process of FIG. 2 including operating superimposed revolution and rotation movements to obtain a melt containing an API, and molding the melt into a solid form of a patient personalized composition, in accordance with an implementation of the present invention;
- (5) FIG. 4 is a flow diagram of a variant of the process of FIG. 2 including operating superimposed revolution and rotation movements in presence of grinding media to reduce particle size distribution (PSD) of at least one ingredient of a patient personalized composition to a desired target PSD, in accordance with an implementation of the present invention;
- (6) FIG. 5 is a flow diagram of a variant of the process of FIG. 2 including operating superimposed revolution and rotation movements to disperse (mix) and de-aerate a patient personalized composition, in accordance with an implementation of the present invention;
- (7) FIG. 6 shows a system for compounding a pharmaceutical composition using superimposed revolution and rotation movements, in accordance with an implementation of the present invention;
- (8) FIG. 7 shows a top view of the jar of FIG. 1 for use with the system of FIG. 6, in accordance with an implementation of the present invention;
- (9) FIG. 8 shows a side isometric view of a variant dispensing jar for use with the system of FIG. 6, in accordance with an implementation of the present invention;
- (10) FIG. 9 shows a side isometric view of dispensing jars, each having a respective body having a different size from one another, for use with the system of FIG. 6, in accordance with an implementation of the present invention;
- (11) FIG. 10A shows a cross-sectional view of jar which contains a specific amount of composition, in accordance with an implementation of the present invention;
- (12) FIG. 10B shows a cross-sectional view of container placed inside jar, where the container contains the same specific amount of composition as in FIG. 10A, in accordance with an implementation of the present invention;
- (13) FIG. 11 shows a top isometric view of an adapter for use with a container for use with the system of FIG. 6, in accordance with a first implementation of the present invention;
- (14) FIG. 12 shows a side view of the container of FIG. 8, including details of the external threads on the nozzle of the container, in accordance with an implementation of the present invention;
- (15) FIG. 13 shows a top isometric view of a variant of the adapter of FIG. 11, in accordance with a second implementation of the present invention;
- (16) FIG. 14 shows a cross-sectional view of container secured to an inside surface of a jar via an adaptor, in accordance with an implementation of the present invention;
- (17) FIG. 15 shows a top isometric view of a variant of the adapter of FIG. 11, in accordance with a third implementation of the present invention;
- (18) FIG. 16 shows a top isometric view of containing system which includes the adaptor of FIG. 15 mounted onto the container of FIG. 8, in accordance with an implementation of the present invention;
- (19) FIG. 17 shows a cross-sectional view of a containing system placed inside a jar, in accordance with an implementation of the present invention;
- (20) FIG. 18A shows a top view of an adaptor having three prongs for use with a container, in accordance with an implementation of the present invention;
- (21) FIG. 18B shows a side view of the adaptor of FIG. 18A, in accordance with an implementation of the present invention;
- (22) FIG. 19 shows a top isometric view of adaptor of FIG. 18A in which is located the container, in accordance with an implementation of the present invention;
- (23) FIG. 20 show a cross-sectional view of the containing system placed inside a jar, in accordance with an implementation of the present invention;
- (24) FIG. 21 shows a top isometric view of an adaptor having four prongs for use with a container, in accordance with an implementation of the present invention;
- (25) FIG. 22 shows a top isometric view of adaptor with a rubberized exterior peripheral band 2012, in accordance with an implementation of the present invention;
- (26) FIG. 23A shows a top isometric view of adaptor with a retention element on the base of the adaptor, in accordance with an implementation of the present invention;
- (27) FIG. 23B shows a cross-sectional view of a jar having a retention element on the inside surface thereof corresponding to the retention element on the adaptor of FIG. 23A, in accordance with an implementation of the present invention;
- (28) FIG. 24 shows a cross-sectional view of adaptor of FIG. 18A receiving the container and located inside jar, which has a heat conductive material located in between the prong and the inside surface of the jar, in accordance with an implementation of the present invention;
- (29) FIG. 25 shows a cross-sectional view of adaptor of FIG. 18A receiving the container and located inside a jar, which has a thermally insulating material located in between the prong and the inside surface of the jar, in accordance with an implementation of the present invention;
- (30) FIG. 26 shows a side elevation of insert that may be removably positioned within the jar, in accordance with an implementation of the present invention;
- (31) FIG. 27 shows a top view of a jar containing grinding media, in accordance with an implementation of the present invention;
- (32) FIG. 28 represents non-limiting graphs showing the interaction profiles of combined effects on SD percent of progesterone in a composition prepared using superimposed revolution and rotation movements based on parameters varying revolution, rotation and time, in accordance with an implementation of the present invention;
- (33) FIG. 29 represents non-limiting graphs showing leverage plots of parameters with significant effects with respect to SD of percent progesterone in a composition prepared using superimposed revolution and rotation movements based on parameters varying revolution, rotation and time, in accordance with an implementation of the present invention;
- (34) FIG. 30 represents non-limiting graphs showing implementation of a desirability algorithm for optimization of dispersing (mixing) of the progesterone composition of FIG. 28 and FIG. 29, where the desirability is set such that SD of percentage progesterone is zero and time setting is minimized to the lowest value (i.e., 10 seconds), in accordance with an implementation of the present invention;
- (35) FIG. 31 represents non-limiting graphs showing initial particle size distribution (PSD) of sodium chloride (A) and the PSD after being processed according to prior art mortar and pestle dispersing (mixing) process (B), when processed using superimposed revolution and rotation movements in presence of grinding media spheres of 8 mm (C) or cylinders (D), in accordance with an implementation of the present invention;
- (36) FIG. 32 represents non-limiting graphs showing initial particle size distribution (PSD) of Gabapentin (A) and the PSD after being processed according to prior art mortar and pestle dispersing (mixing) process (B), when processed using superimposed revolution and rotation movements in

presence of grinding media spheres of 8 mm (C) or cylinders (D), in accordance with an implementation of the present invention;

(37) FIG. 33 shows a typical gum base gelatin particle unaltered from the manufacturers' container (left) and a plurality of these particles contained in the dispersion container (right). The block has a maximal extent size of about 1 inch, in accordance with an implementation of the present invention;

(38) FIG. 34 shows gum base gelatin particles which have been cut down from the initial size present in the manufacturers' container (left) and a plurality of these particles contained in the dispersion container (right). The cut down particles have a size of less than about 0.5 inch, in accordance with an implementation of the present invention;

(39) FIG. 35A-35E shows examples of gum base in the dispersion container that completely melted (35A), partially melted (35B, 35C and 35D), and did not melt (35E), in accordance with an implementation of the present invention;

(40) FIG. 36 represents a non-limiting graph showing melting of gum base gelatin when processed using superimposed revolution and rotation movements based on parameters of constant time and increasing G Force, in accordance with an implementation of the present invention;

(41) FIG. 37 represents a non-limiting graph showing melting of gum base gelatin when processed using superimposed revolution and rotation movements based on parameters of constant G force and increasing time, in accordance with an implementation of the present invention;

(42) FIG. 38 represents a non-limiting graph showing melting of gum base gelatin when processed using superimposed revolution and rotation movements based on parameters of constant G force and time, while increasing the mass, in accordance with an implementation of the present invention;

(43) FIG. 39 represents a non-limiting graph showing percentage de-aeration of a personalized composition when processed using superimposed revolution and rotation movements based on parameters of constant time and variable G force, in accordance with an implementation of the present invention;

(44) FIG. 40 represents a non-limiting graph showing percentage de-aeration of a personalized composition when processed using superimposed revolution and rotation movements based on parameters of constant G force and variable time, in accordance with an implementation of the present invention;

(45) FIG. 41 represents a non-limiting graph showing particle size (μm) with respect to D10, D50 and D90 of 23 gram of NaCl when processed using superimposed revolution and rotation movements based on parameters of constant G Force in presence of grinding media or when processed with control mortar and pestle, in accordance with an implementation of the present invention;

(46) FIG. 42 represents a non-limiting graph showing particle size (μm) with respect to D10, D50 and D90 of 50 gram of NaCl when processed using superimposed revolution and rotation movements based on parameters of constant G Force in presence of grinding media or when processed with control mortar and pestle, in accordance with an implementation of the present invention;

(47) FIG. 43 represents a non-limiting graph showing particle size (μm) with respect to D10, D50 and D90 of 22.9 gram of NaCl when processed using superimposed revolution and rotation movements based on parameters of 60 seconds in presence of grinding media or when processed with control mortar and pestle, in accordance with an implementation of the present invention;

(48) FIG. 44 represents a non-limiting graph showing temperature increase (gain in degrees Celsius) when processing NaCl when processed using superimposed revolution and rotation movements based on parameters of constant G force and increasing time period in presence of grinding media, in accordance with an implementation of the present invention;

(49) FIG. 45 represents a non-limiting graph showing temperature increase (gain in degrees Celsius) when processing NaCl when processed using superimposed revolution and rotation movements based on parameters of constant time period and increasing G force in presence of grinding media, in accordance with an implementation of the present invention;

(50) In the drawings, embodiments are illustrated by way of example. It is to be expressly understood that the description and drawings are only for the purpose of illustrating certain embodiments and are an aid for understanding. They are not intended to be a definition of the limits of the invention.

DETAILED DESCRIPTION

(51) Illustrative embodiments of the disclosure will now be more particularly described. The same features are denoted in all figures by the same reference signs. While the making and using of various embodiments of the present invention are discussed in detail below, it should be appreciated that the present invention provides many applicable inventive concepts that can be embodied in a wide variety of specific contexts. Specific embodiments discussed herein are merely illustrative of specific ways to make and use the disclosure and do not delimit the scope of the disclosure.

(52) A composition of the present disclosure includes one or more ingredient which is tailored to medical needs of an individual patient. The composition further includes one or more characteristics which, when compared to compositions obtained with prevalent compounding methods that make use, e.g., of manual mixing, may constitute an improvement from a safety and/or quality and/or effectiveness perspective.

(53) In one embodiment, the composition of the present disclosure can be a cream, ointment, lotion, emulsion, gel, suspension, powder, liquid solution, colloidal dispersion, troche or syrup. For the purpose of the present disclosure, the compounding composition of the present description may be packaged in a metered dose device and/or a unit dose package. A metered dose device allows administering a dose of compounding composition, the dose of compounding composition being metered by weight or by volume. In one non-limiting example, the metered dose device is an inhaler comprising a canister, a metering valve and an actuator. The canister encloses the compounding composition, while the metering valve allows a metered dose of the compounding composition to be dispensed at each actuation of the actuator, the actuator being a mouthpiece in this example. In another non-limiting example, the metered dose device comprises a container enclosing the compounding composition, an actuator manually operated, and a metering valve allowing a metered dose of the compounding composition to be dispensed at each actuation of the actuator. A unit dose package (also referred as "individual package") allows the compounded composition to be dispensed more safely and efficiently by enclosing each unit dose in a different recipient. A unit dose is typically a dose of medication comprising a dose of at least one compounded composition that is intended to be administered at once. The recipients may comprise paper, cardboard, plastic, metal and/or glass materials. In one non-limiting example, the recipients are paper envelopes. In another non-limiting example, the recipients are reusable boxes. In one non-limiting example, the recipients are single-use plastic boxes with a detachable paper lid. The recipients may be tagged, marked with information, such as a name of a patient, a name of a medication, a barcode and/or a moment (i.e. a day, a date and/or a moment of the day) at which the unit dose is intended to be administered. In one non-limiting example, each recipient is tagged with a day of the week and a meal: Monday-breakfast, Monday-diner, Tuesday-breakfast, etc. The unit dose package may be provided by manually packaging the unit doses or by an automated packaging system.

(54) In a first practical implementation, the composition of the present disclosure includes at least one active pharmaceutical ingredient (API) dispersed (mixed) in a pharmaceutically acceptable excipient, diluent or carrier in such a way that the composition has substantially the same API concentration in a top layer, a middle layer and a bottom layer of the composition, as measured with high-performance liquid chromatography (HPLC). Such composition will be referred to in this text as being a "substantially homogeneous composition".

(55) The concept of having substantially the same API concentration in a top, middle and bottom layer of the composition is illustrated in FIG. 1A, which shows a cross-sectional view of a container 102 including a patient personalized composition, where the container 102 is virtually separated in top, middle and bottom sections, each including respective top 2, middle 4 and bottom 6 layers of the composition. The concentration of the API dispersed (mixed) in the composition is then measured in each of layers 2, 4 and 6 using a suitable technique, such as HPLC. The standard deviation (SD) between the API concentrations of the three layers 2, 4 and 6 for a given composition is then determined. The relative standard deviation (% RSD), which expresses the precision and repeatability of an assay, is then calculated based on the ratio of the standard deviation to the mean.

(56) In a non-limiting embodiment, the composition exhibits a concentration gradient of the API having $\leq 3\%$ relative standard deviation (% RSD), or $\leq 2\%$ RSD, or $\leq 1\%$ RSD, when measured at least at the top 2, middle 4 and bottom 6 layers of the composition using HPLC. In a non-limiting embodiment, the concentration gradient of the API is nil (about 0% RSD), when measured at least at the top 2, middle 4 and bottom 6 layers of the composition using HPLC.

(57) In one embodiment, the API can be present in an amount of ≤ 80 wt. % relative to total weight of the composition. For example, the API can be present in an amount selected in the range of 0.05 wt. % to 80 wt. %, or 0.05 to 70 wt. %, or 0.05 to 60 wt. %, or 0.05 to 50%, or 0.05 to 50 wt. %, or any other desired amount.

(58) In a non-limiting embodiment, the composition includes at least a second API dispersed (mixed) in the pharmaceutically acceptable excipient, carrier or diluent, the second API, and the composition exhibiting a concentration gradient of the at least second API having $\leq 6\%$ RSD, or $\leq 3\%$ RSD, or $\leq 2\%$ RSD, or $\leq 1\%$ RSD, when measured at least at the top 2, middle 4 and bottom 6 layers of the composition using HPLC. In a non-limiting embodiment, the concentration gradient of the at least a second API is nil (about 0% RSD), when measured at least at the top 2, middle 4 and bottom 6 layers of the composition using HPLC.

(59) In a non-limiting embodiment, the concentration gradient of the at least second API can be approximately the same as the concentration gradient of the first API.

(60) In another non-limiting embodiment, the concentration gradient of the at least second API is significantly different than the concentration gradient of the first API.

(61) Different types of pharmaceutical compositions have been prepared by the present inventors with the above low % RSD values.

(62) In a second practical implementation, the composition of the present disclosure includes an API dispersed (mixed) in a pharmaceutically acceptable excipient, diluent or carrier in such a way that the composition has reduced air entrapment levels.

(63) One practical way of assessing air entrapment levels in the composition is to measure the specific gravity of the composition before and after the dispersion (mixing) procedure and/or of a composition prepared with the herein described process to a composition prepared with a dispersion procedure of the prior art, such as mixing with an electronic mortar and pestle.

(64) For example, it has been observed by the present inventors that compounding pharmaceutical ingredients using prior art processes such as the electronic mortar and pestle can incorporate significant amounts of air into the composition under certain circumstances (i.e., $>30\%$ variation in the composition's specific gravity). In such cases, the air entrapped in the composition creates air bubbles which are undesirable from a product quality perspective. It is, thus, common in the art to further process compositions which have been mixed with the electronic mortar and pestle with another device to remove the air bubbles entrapped therein. In such cases, the compounding process can thus include the use of at least two devices, the electronic mortar and pestle and another device such as the Unguator™ (Gako International GmbH), to remove entrapped air. The use of two devices can be cumbersome, increase operation costs, delays, likelihood of cross-contamination, material loss (e.g., through decanting from one container suitable for mixing with the electronic mortar and pestle to another container suitable for the Unguator), and/or other undesirable effects which will become apparent to the person of skill in view of the present disclosure.

(65) In contrast, and as will be further discussed later in this text, the herein described superimposed revolution and rotation movements, typically, will not introduce air during the dispersing (mixing) process, and if the starting composition ingredients (i.e., before dispersion) initially include air entrapped therein, the herein described superimposed revolution and rotation movements will deaerate the composition while dispersing (mixing) the ingredients. This can be advantageous, in particular when the herein described superimposed revolution and rotation movements is implemented in a single device, as will be further discussed later in this text.

(66) In this particular implementation, the patient personalized composition of the present disclosure includes an API dispersed (mixed) in a pharmaceutically acceptable excipient, diluent or carrier. The composition has a specific gravity which is within 20%, or within 10%, or within 5%, or within 2%, of the specific gravity of the pharmaceutically acceptable carrier, diluent or excipient in absence of the API. Preferably, such composition exhibits a concentration gradient of the API with $\leq 6\%$ RSD, or $\leq 3\%$ RSD, or $\leq 2\%$ RSD, or $\leq 1\%$ RSD, or RSD being nil (about 0%), when measured at least at the top 2, middle 4 and bottom 6 layers of the composition using HPLC. relative standard deviation (RSD) when measured at least at a top, middle and bottom layers of the composition by high-performance liquid chromatography (HPLC).

(67) In one embodiment, the composition of the present disclosure includes an API dispersed (mixed) in a pharmaceutically acceptable excipient, diluent or carrier, and has a specific gravity which is substantially identical to the specific gravity of the pharmaceutically acceptable carrier, diluent or excipient without the API.

(68) In a third practical implementation, the composition of the present disclosure includes an API which is thermally labile at a temperature above 50°C ., or above 60°C ., or above 80°C . The API is dispersed (mixed) in a pharmaceutically acceptable excipient, diluent or carrier. This composition includes less than 1.0% degradation products of the thermally labile API. The person of ordinary skill will readily appreciate that the percentage here represents a wt./wt. percentage relative to the total weight of the thermally labile API added into the composition before dispersion (mixing).

(69) In one non-limiting embodiment, the amount of degradation products of the thermally labile API represents less than 0.75%, 0.5%, 0.1%, 0.05%, or 0.01% wt./wt. percentage relative to the total weight of the thermally labile API added into the composition before dispersion.

(70) For the purpose of the present specification, a thermally labile API is an active pharmaceutical compound that is altered or degrades when exposed to high temperatures, e.g. above 50°C ., or above 60°C ., or above 80°C ., or more. Typically, compounding methods that make use of blades for mixing will generate high temperatures, which can alter or degrade thermally labile API to a certain extent such that it increases costs and/or reduces yield of composition having effective API concentrations and/or produces unwanted degradation and/or alteration of the API, possibly generating by-products. In certain prior art compounding methods that make use of blades, it can be quite common to obtain dispersed composition having more than 1.5% degradation products of thermally labile API.

(71) The reader will readily understand that quantification of API degradation product levels in the dispersed composition can be performed using one of a variety of chromatographic or spectroscopic techniques known in the art, including HPLC, thin-layer chromatography (TLC), High performance thin layer chromatography (HPTLC), Atomic absorption spectroscopy (AAS), and the like.

(72) In a fourth practical implementation, the composition of the present disclosure is in the form of a molded troche and includes an API dispersed in a pharmaceutically acceptable excipient, diluent or carrier. The API is thermolabile at a temperature above 60°C . and the composition includes less than 1.0% degradation products of the thermally labile API wt./wt. percentage relative to the total weight of the thermally labile API added into the composition before dispersion.

(73) In one non-limiting embodiment, the amount of degradation products of the thermally labile API in the troche represents less than 0.75%, 0.5%, 0.1%, 0.05%, or 0.01% wt./wt. percentage relative to the total weight of the thermally labile API added into the composition before dispersion.

(74) In a specific embodiment, the troche is a chewable troche.

(75) In a specific embodiment, the troche includes a gum base gelatin.

(76) The troche can have similar features as those set forth previously with respect to the composition, namely a concentration gradient of the API with $\leq 6\%$ RSD, or $\leq 3\%$ RSD, or $\leq 2\%$ RSD, or $\leq 1\%$ RSD, or RSD being nil (about 0%), when measured at least at a top, middle and bottom layers of the troche by high-performance liquid chromatography (HPLC)

(77) A troche (also interchangeably referred to in the text as a "lozenge") is intended to be held in the mouth or pharynx and contains one or more API(s) either dissolved or dispersed in a base. Troches are typically used for patients who have difficulty swallowing solid oral dosage forms (for example, paediatric or geriatric patients) as well as for API(s) which should be released slowly to yield a constant amount of drug in the oral cavity or

to coat the throat tissues with the API(s). Commercial lozenges are made by moulding or by compression.

(78) Compression techniques are typically used when manufacturing solid troches that are intended to slowly dissolve or disintegrate in the mouth. Compression is also advisable when incorporating thermolabile APIs, as there is no excessive heat involved when compressing the troche ingredients.

(79) Moulding techniques are typically used when manufacturing solid, soft or chewable troches and in particular, when one wishes to impart a specific shape to the troche. Moulding techniques usually involve high temperature processing of the ingredients to obtain a melt, dispersing the API in the melt to obtain an API-containing melt, and casting the dispersed API-containing melt into a mold having a desired shape, and cooling the API-containing melt into the desired shape. Because of the high temperatures (e.g., 90-100° C.) usually involved with moulding, troches made with this technique typically do not include thermolabile APIs, as thermolabile APIs will usually degrade or convert to by-products in presence of such high temperatures. This in turn effectively limits the nature or concentration of the API that can be incorporated into molded troches to a certain non-thermolabile subset, which may not be practical for certain applications.

(80) As explained later in the present disclosure, the herein described superimposed revolution and rotation movements can be used to obtain a melt and disperse therein a thermolabile API at a temperature which is sufficiently low so as to limit the degradation of the thermolabile API and obtain an API-containing melt which can be molded into a troche having less than 1.0%, 0.75%, 0.5%, 0.1%, 0.05%, or 0.01% degradation products of the thermally labile API.

(81) Superimposed Revolution and Rotation Movements

(82) A number of devices can be used to obtain the compounded pharmaceutical composition of the present disclosure so long as the device is capable of implementing the superimposed revolution and rotation movements as described herein.

(83) In one non-limiting practical implementation, the herein described superimposed revolution and rotation movements can be performed using a planetary mixer.

(84) A planetary mixer is capable of performing the herein described superimposed revolution and rotation movements by continually and concurrently revolving and rotating a container which includes the composition ingredients. This dual action eliminates the need for mixing rods, blades or media, or an evacuation device and can dramatically reduce processing times relative to other mixing devices that use blades to mix ingredients. In one embodiment, the mixing time may be no more than 900 seconds. For example, the herein described superimposed revolution and rotation movements may be performed for less than 10, 15, 20, 25, 30, 35, 40, 45, 50, 55, 60, 75, 100, 120, 150, 180, 240, 300, 400, 500, 600, 700, 800, or 900 seconds, as well as any values included therein.

(85) Such processing time is significantly reduced when compared to the processing time required for compounding processes known in the art for compounding pharmaceutical compositions, such as the typical mortar and pestle system or devices with mixing blades, which may require an additional vacuum step to remove air entrapment in the composition. While the processing time in the superimposed revolution and rotation movements of the present disclosure is thus relatively reduced, the intensity of the processing procedure is sufficiently intense to disperse the ingredients to the point where the resulting mixture is substantially homogenous and is sufficiently gentle to prevent the internal temperature of the mixture from reaching or getting close to a degradation temperature threshold of the API.

(86) In one embodiment, the superimposed revolution and rotation movement parameters may induce a maximal G force value of at least 50 g (corresponding to approximately 1490 m/s.sup.2). In some cases, the superimposed revolution and rotation movement parameters may induce a maximal G force value of less than 500 g, or in the range of 50 g to 400 g, or 75 g to 350 g, or any suitable value within these ranges. Inducing such a maximal G force in a process by performing the herein described superimposed revolution and rotation movements can be useful for compounding compositions which are otherwise difficult or cumbersome to compound using prior art electronic mortar and pestle system or devices with mixing blades.

(87) In one embodiment, the superimposed revolution and rotation movements are operated with operational parameters that may include revolution speeds of from at least 400 revolutions per minute ("rpm" or "RPM"). For example, a suitable revolution speed can be selected in the range of from 400 to about 4000 rpm, or from 400 to about 2000 rpm, or any suitable value within these ranges.

(88) In one embodiment, the superimposed revolution and rotation movements are operated with operational parameters that may include revolution:rotation rpm ratios of about 10:4.

(89) In certain embodiments, the revolution rpm, the rotation rpm and the mixing time are configurable parameters and their values may be individually selectable or they may be selectable from pre-determined combinations of parameter values. In other embodiments, the ratio between rotation rpm and revolution rpm may be a configurable parameter and thus would constrain the revolution rpm for a certain rotation rpm or vice versa. Moreover, the geometric configuration of the planetary mixer (e.g., the eccentricity (distance between the center of rotation and the center of revolution), the dimensions of the container, etc.), combined with the revolution rpm and rotation rpm, results in a certain acceleration (G force, measured in g or m/s.sup.2) being felt by the material in the container. In some embodiments, the desired G force may be input to the planetary mixer, which could result in selection, by the planetary mixer, of the revolution rpm and/or the rotation rpm.

(90) In other embodiments, the minimum or maximum G force may be specified, resulting in thresholding of the rotation rpm and/or the revolution rpm, depending on the values entered. In still further embodiments, certain parameters (such as the rotation rpm or the revolution rpm) may be dynamic (i.e., vary over time) and may be input as a function of time function so as to follow a pre-determined curve. There may exist still further controllable parameters of superimposed revolution and rotation movements implemented by a planetary mixer, such as the total weight of the container being mixed.

(91) The reader will readily recognize that the herein described process offers a number of benefits to the compounding industry, in particular when this process can be integrated within a single device, namely a planetary mixer.

(92) Various implementations of the herein described superimposed revolution and rotation movements will now be described with reference to dispersing, milling, melting and de-aerating applications for compounding pharmaceutical compositions (i.e., patient personalized compositions), which can be advantageously performed in a pharmacy setting in a single device, namely a planetary mixer.

(93) While each of these applications is described in the following sections as separate variant processes, the reader will readily understand that these applications are not mutually exclusives. In other words, more than one of these applications can be performed during the same superimposed revolution and rotation movements implemented in single planetary mixer, i.e., ingredients of a patient personalized composition can be processed so as to mix and de-aerate; or so as to mix, melt and de-aerate; or so as to mix and grind; or any other combinations thereof.

(94) Mixing Process

(95) FIG. 2 is a flow chart of a general process **100** of preparing a compounded pharmaceutical composition in accordance with an embodiment of the present disclosure.

(96) In the process **100**, the superimposed revolution and rotation movements are implemented in a planetary mixer for preparing a patient personalized composition by dispersing an API into a pharmaceutically acceptable excipient, diluent or carrier so as to obtain a substantially homogeneous patient personalized composition.

(97) At step **110**, the process includes providing the composition ingredients in a container (also referred to in this text as a "jar") configured for containing the composition ingredients. Typically, the composition ingredients include at least one API and at least one pharmaceutically acceptable excipient, diluent or carrier.

(98) At step **120**, the process includes obtaining pre-determined or determining dispersing parameters which are required to perform a superimposed revolution and rotation movements on the composition ingredients to obtain a substantially homogeneous dispersed composition.

(99) At step **130**, the process includes dispersing the composition using the superimposed revolution and rotation movements at least based on the pre-determined or determined dispersing parameters so as to produce the substantially homogeneous dispersed composition.

(100) Melting Process

(101) FIG. **3** is a flow chart of a process variant **100'** of preparing a compounded pharmaceutical composition in accordance with an embodiment of the present disclosure. In this variant, the process **100'** is implemented in a planetary mixer for preparing a patient personalized composition by reversibly melting pharmaceutically acceptable excipient, diluent or carrier initially in the form of solid or semi-solid particles, incorporate into the resulting melt an API, dispersing the API into the melt, and casting the melt into a desired shape, such as a troche.

(102) The variant **100'** includes at step **210**, providing pharmaceutically acceptable excipient, diluent or carrier in the form of solid or semi-solid particles in a container configured for containing the particles. Optionally, at this step, at least one API is also provided in the container.

(103) In one embodiment, the excipient, diluent or carrier in the form of solid or semi-solid particles is a polymeric material which can be reversibly melted. In a particular implementation, excipient, diluent or carrier in the form of solid or semi-solid particles is a gelatin-based material.

(104) At step **220**, the process includes obtaining pre-determined or determining dispersing parameters which are required to perform the superimposed revolution and rotation movements on the solid or semi-solid particles to obtain a more or less viscous melt.

(105) At step **230**, the process includes dispersing the solid or semi-solid particles at least based on the pre-determined or determined parameters to obtain the melt. Without being bound by any theory, it is believed that the superimposed revolution and rotation movements can melt the solid or semi-solid particles through impact of the particles against each other and/or against the container walls, thus generating kinetic energy, without requiring the addition of external heat. This process advantageously can melt the material at a temperature which is below the Tg or Tm of the solid or semi-solid particles.

(106) In one embodiment, the at least one API is not incorporated into the container at step **210**. In such embodiment, the solid or semi-solid particles are thus melted in step **230** in the absence of an API. In such embodiment, it is thus necessary to incorporate at least one API at one point to obtain the compounded pharmaceutical composition. This is achieved with optional step **240**, in which an API is added to the melt obtained in step **230** so as to obtain an API-containing melt. In FIG. **3**, step **240** is therefore labelled as being optional as it may be discarded in case at least one API was incorporated into the container at step **210** and no further API is added to the composition.

(107) At step **250**, the process includes obtaining pre-determined or determining second dispersing parameters which are required to perform second superimposed revolution and rotation movements on the API-containing melt to obtain a substantially homogeneous dispersed composition.

(108) At step **260**, the process then includes dispersing the API-containing melt at least based on the pre-determined or determined second dispersing parameters to so as to produce a substantially homogeneous dispersed composition.

(109) At step **270**, the process then includes incorporating the dispersed composition into a mold having a desired shape and causing the incorporated dispersed composition to solidify into the mold shape.

(110) This process **100'** thus affords the reversible melt of pharmaceutically acceptable excipients, carriers or diluents which can be useful, for example, when making compositions which require pouring into some sort of mold to impart a shape thereto, for instance when making compounded pharmaceutical compositions in the form of troches, suppositories or throat lozenges. Advantageously, the melt can be obtained with the herein described dispersing process at temperatures below the typical molten transition temperature of the ingredients being dispersed such that it may enable the production of solid dispersion systems from thermally incompatible materials. In other words, such composition can advantageously incorporate thermally labile API which are typically not found or are found in limited concentration in troches.

(111) In the prior art, such shaped compounded pharmaceutical compositions are typically made by first thermally treating a suitable pharmaceutically acceptable excipients, carriers or diluents in solid form for a sufficient extent of time so as to obtain a melt, adding the desired API (or mixture thereof), dispersing the API into the melt to obtain a mixture, and pouring the mixture into the mold so as to obtain the desired shaped compounded pharmaceutical composition. It will be noted that, typically, API which are incorporated into such melted pharmaceutically acceptable excipients, carriers or diluents are more thermally resistant so as to be able to bear the higher temperatures involved with melting the carrier, excipient or diluent. This, in turn, can limit the nature of the API that can be incorporated into such melts or requires higher amounts of API to take into account the expected API thermal degradation.

(112) Milling Process

(113) FIG. **4** is a flow chart of a process variant **100''** of preparing a compounded pharmaceutical composition in accordance with an embodiment of the present disclosure. In this variant, the process **100''** is implemented in a planetary mixer for preparing a patient personalized composition which includes a step of reducing the particle size distribution (PSD) of at least one of the ingredients in the patient personalized composition. Reducing the PSD of one of the ingredients can be useful in reducing the gritty feeling of the resulted compounded composition, such as for example but not being limited to the case of a topical cream, ointment or gel.

(114) The process **100''** includes at step **310**, providing a container including at least one patient personalized composition ingredient such as one of an API, a pharmaceutically acceptable excipient, diluent or carrier in the form of particles where the container is configured for containing the particles.

(115) At step **320**, the process includes obtaining pre-determined or determining dispersing parameters which are required to perform superimposed revolution and rotation movements on the particles to reduce the PSD to a desired target PSD. Advantageously, the pre-determined or determined dispersing parameters are selected so as to ensure that any heat generation which could be caused during the dispersing step through the impact of particles and/or grinding media against each other and/or against the container inner walls does not reach a degradation temperature of the API.

(116) At step **330**, the process includes adding grinding media to the container. It will be apparent to the reader that steps **320** and **330** can occur in any sequence and are not limited to a serial sequence. In other words, the step **330** can occur before, during or after step **320**.

(117) At step **340**, the process includes dispersing the grinding media and the particles at least based on the pre-determined or determined parameters to reduce the PSD to the desired target PSD.

(118) At step **350**, the grinding media is separated from the dispersed composition. This can be achieved either by removing from the container, the grinding media or the dispersed composition.

(119) When step **310** does not include the addition of an API and/or when the compounding prescription recipe requires addition of an API after the dispersing step **340**, the process includes a step **360**. It will be apparent that this step is optional as the API can be incorporated at step **310**. At step **360**, an API is incorporated into the dispersed composition obtained after step **350**.

(120) At optional step **370**, the process includes obtaining pre-determined or determining second dispersing parameters which are required to perform superimposed revolution and rotation movements on the dispersed composition obtained after step **360** so as to obtain a substantially homogeneous dispersed composition.

(121) At optional step **380**, the process includes dispersing the composition using the superimposed revolution and rotation movements at least based on the pre-determined or determined second dispersing parameters so as to produce the substantially homogeneous dispersed composition.

(122) It will be apparent that in a variant, the superimposed revolution and rotation movements in presence of grinding media are performed on the API in presence of the pharmaceutically acceptable excipient, diluent or carrier.

(123) In another variant, the superimposed revolution and rotation movements in presence of grinding media are performed on the API in absence of the pharmaceutically acceptable excipient, diluent or carrier.

(124) When performing the process in presence of grinding media, the size of the particles to grind, the size of the grinding media used to grind, and the size of the resulting particles can be selected such that, for example:

0.004<MS(SP)/MS(B)<0.12

0.0025<MS(FP)/MS(SP)<0.25 where MS (SP) represents the mean size diameter of the particles before grinding (starting particles), MS (FP) represents the mean size diameter of the particles after grinding (final particles), and MS (B) is the mean size diameter of the grinding beads.

(125) The grinding media may include balls (spheres) or pellets (cylinders) made of, for example, but not limited to, hardened steel, stainless steel, tungsten carbide, agate, sintered aluminium oxide, silicon nitride or zirconium oxide.

(126) De-Aerating Process

(127) FIG. 5 is a flow chart of a process variant **100'** of preparing a compounded pharmaceutical composition in accordance with an embodiment of the present disclosure.

(128) In this variant, the process **100'** is implemented in a planetary mixer for preparing a patient personalized composition by dispersing an API into a pharmaceutically acceptable excipient, diluent or carrier in such manner as to minimize air entrapment into the dispersed composition or to remove any air which was present in the composition before dispersion. This can be useful in controlling the composition's specific gravity and/or reducing incorporation of air bubbles in the resulting patient personalized composition, such as for example but not limited to topical creams, ointments or gels.

(129) The process **100'** includes at step **410**, providing patient personalized composition ingredients such as an API, a pharmaceutically acceptable excipient, diluent or carrier in a container configured for receiving these ingredients.

(130) At step **420**, the process includes obtaining pre-determined or determining dispersing parameters which are required to perform superimposed revolution and rotation movements on the personalized composition ingredients to disperse same while reducing or maintaining a target content of incorporated air in the composition.

(131) At step **430**, the process includes dispersing the ingredients using the superimposed revolution and rotation movements at least based on the pre-determined or determined parameters to disperse same while reducing or maintaining a target content of incorporated air in the composition. Equipment and Processes for Industrial Applicability of the Invention

(132) The herein described bladeless dispersion pattern process may be performed in a single device, notably in a planetary mixer.

(133) Commercially available planetary mixers, such as the MAZERUSTAR mixer KK-300SS, KK-400W or KK-1000W from Kurabo Industries, Ltd. of Osaka, Japan or the THINKY MIXER AR-100, ARE-310, ARE-400TWIN, ARE-500, ARV-50LED, ARV-310/310LED, ARV-930-TWIN, ARV-5000, ARV-3000TWIN, and ARV-10kTWIN from Thinky Corporation of Tokyo, Japan, and the like, can be used for this purpose.

(134) A planetary mixer typically includes a jar arranged eccentrically on a so-called sun wheel, at a certain distance from the center. The jar is configured for receiving a container which contains the ingredients being processed. The planetary mixer is configured to impart a revolution movement to the sun wheel and a rotational movement to the jar, where the revolution movement is in an opposite direction to that one of the rotation such that the ingredients contained in the container are subjected to a pattern of motion throughout space, which includes superimposed revolution and rotation movements. Advantageously, this pattern of motion throughout space does not involve any blades, i.e., it is a bladeless dispersion pattern of motion throughout space. When grinding media is added to the container, the grinding media is also subjected to these superimposed movements, where the difference in speeds between the grinding media and the container produces an interaction between frictional and impact forces, which releases high dynamic energies causing size reduction of the materials in the container.

(135) In certain embodiments, the container receiving the ingredient is adapted to receive on a top end thereof, a dispensing system element such as a pump, a spray nozzle, applicator cap, and the like. It will be appreciated that the dispensing system element can further be adapted for dispensing metered doses as described, e.g., in U.S. 2014/0221945 filed Feb. 4, 2014 and PCT/CA2016/050179, filed Feb. 23, 2016. This implementation effectively avoids or eliminates decanting steps, thus, minimizing the risk of material loss. This implementation also reduces time required for cleaning the container after a compounding procedure, which is typically required to avoid cross-contamination risks that exist when using the same container for dispersion of various compounded pharmaceutical compositions. The reader will appreciate that when performing the milling step, the grinding media is preferably removed from the container before the latter receives the dispensing system element at the top end thereof.

(136) Such features are also advantageous to the compounding industry and are believed to address an unmet need in this industry.

(137) FIG. 6 generally shows a planetary mixing system **10** which includes a planetary mixing apparatus **100** configured to effect the herein described superimposed revolution and rotation movements through rotation and revolution of a jar **102** placed in a jar holder **104**.

(138) The system **10** includes a lid **106** that attaches onto a mouth **108** of the jar **102**. The lid **106** may be a screw-on lid as shown, or it may be a snap-on lid, for example. The jar **102** and the lid **106** may be made of high density polyethylene (HDPE) or polypropylene, for example.

(139) The jar **102** may have different interior and exterior dimensions. With reference to the elevated cross-sectional view in FIG. 1, the jar **102** may have an inside diameter **202**, **204**, **206** that changes from the top of the jar **102** to the bottom of the jar **102**. For example, the inside diameter **202** at the top of the jar **102** may be smaller than the inside diameter **206** at the bottom of the jar **102**. This gradient can be achieved in two or more sections or as a gradual taper. In the illustrated embodiment, the jar **102** has three sections **212**, **214**, **216**, with the top section **212** having the smallest inside diameter **202**, the bottom section **216** having the largest inside diameter **206** and the middle section **214** whose inside diameter **204** is somewhere in between. Example dimensions for the top, middle and bottom inside diameters, not to be considered limiting, are 65 to 70 mm, 65 to 70 mm and 65 to 70 mm, respectively. Alternatively, one can consider that the top inside diameter **202** is between 90 and 99.9 percent of the middle inside diameter **204**, and the middle inside diameter **204** is between 90 and 99.9 percent of the inside diameter **206**. Also, there are multiple height dimensions possible for the jar **102**. For example, the height dimension of the jar **102** (measure externally) could be in the range from 85 mm to 120 mm.

(140) The outside of the jar **102** may be configured to be received in the jar holder **104**. In particular, the jar holder **104** may include a plurality of circumferentially spaced projections **104A**. Correspondingly, and as shown with additional reference to FIG. 7, the jar **102** may, accordingly, include a plurality of circumferentially spaced notches **302** that receive the projections **104A**, so as to prevent free-spinning of the jar **102** within the jar holder **104**. As a result, rotation of the jar **102** will only occur when the jar **104** holder itself rotates. Other rotational stoppage mechanisms may be provided in different embodiments. In other embodiments, the jar **102** may be of any other suitable shape and may include an internal surface that may be smooth, rough, and/or comprise any suitable texture.

(141) Containers of various sizes for containing pharmaceutical composition exist in the market, such as (i) containers in which compounds are traditionally dispersed by an electric mortar/pestle and (ii) containers from which compounds are dispensed (such as bottles and syringes). As will be discussed later in this text, the system **10** may be configured to implement the superimposed revolution and rotation movements described here in containers/jars of various sizes.

(142) FIG. 8 shows an example container **402** in which pharmaceutical composition ingredients would traditionally be dispersed by an electric mortar/pestle. One example of the container **402** is referred to in the industry as an Unguator™ jar (available from GAKO Konietzko GmbH, Bamberg, Germany), although recently similar containers have been made available by Samix GmbH, Zella-Mehlis, Germany.

(143) The container **402** includes a body **404** and a cover **406**. The body **404** and the cover **406** may be complementarily threaded. The cover **406** includes a nozzle **408**, which may include an external thread **408A** to receive an internally threaded cap **410**. The cap **410** has an external diameter denoted **410A**. The nozzle **408** has an aperture **412** that allows fluid to escape the container **402** when the cap **410** is removed and a piston (not shown) is pushed from underneath the body **404**. For electric mortar/pestle mixing, the cap **410** is removed from the cover, the cover **406** is removed from the body **404**, a blade shaft (not shown) is inserted from underneath the cover **406** and through the aperture **412** and connected to a motor (not shown); meanwhile, the body is filled with the composition ingredients to be dispersed, then the blade is positioned inside the body **404** and the cover **406** is secured back onto the body **404**.

(144) FIG. 9 shows alternative containers **502A**, **502B** and **502C**. The containers **502A**, **502B** and **502C** include a respective cylindrical body **504**,

504' and 504'', and an actuator 506. The actuator 506 can be actuated by a user to dispense a composition contained in the body 504. Depending on the embodiment, the actuator 506 may in fact allow metered dispensing of the composition.

(145) As is apparent from the above, the containers used for dispersing pharmaceutical composition ingredients (e.g., containers 402, 502A) do not necessarily correspond to the jar 102. As such, in accordance with various embodiments, and with reference to FIG. 10B, there is provided an adapter 602 between the jar 102 and the container 600 (generally referred to by 600 but which could be one of the aforementioned containers 402, 502A). The container 600 has a smaller volume than the jar 102 and is secured to an interior of the jar 102 by the adapter 602. The adapter is designed not to hold the composition but rather to secure the container 600 to the jar 102. The ability to secure a container 600 with a smaller volume entirely within the jar 102 can allow smaller quantities of pharmaceutical composition ingredients to undergo efficient dispersing despite the small amount of the composition.

(146) In one embodiment, the jar 102 may have a volume of approximately 250 ml, while the container 600 may have a volume of approximately 100 ml, or approximately 80 ml, or approximately 50 ml, or approximately 35 ml, or approximately 30 ml, or approximately 20 ml or approximately 15 ml. It should be appreciated that a height-to-base ratio (HBR) associated with a certain quantity of a composition to be dispersed in a particular vessel may be defined as the quotient between a height dimension occupied by the quantity of the composition and a base dimension occupied by the quantity of the composition, when that quantity is placed into the particular vessel. The HBR may be a parameter indicative of how efficiently the composition will be dispersed, where more efficient dispersing could be defined as reaching the same degree of homogeneity earlier in the dispersion process, or reaching a higher degree of homogeneity at the same duration of dispersion.

(147) With continued reference to FIG. 10A, there is shown an example quantity of composition 610 placed in the jar 102 and with reference to FIG. 10B, the same quantity of composition 612 placed in the container 600 that is secured to the jar 102 by the adapter 602. The height dimension occupied by the composition 610 in the jar 102 is given by HJ and the base dimension is given by the bottom inside diameter 206 of the jar 102, which can be referred to as B206. Thus, the HBR associated with the quantity of composition 610 is HJ/B206 for the jar 102. Turning now to the case of the container 600, it is seen that the height dimension occupied by the composition 612 in the container 600 is given by HC and the base dimension is given by the bottom inside diameter of the container 600, which can be referred to as BC. Thus, the HBR associated with the quantity of composition 612 is HC/BC for the container 600.

(148) It should be apparent, therefore, that for the same quantity of pharmaceutical composition, the HBR for the container 600 is greater than for the jar 102. In fact, the smaller the quantity of the composition, the greater the difference in HBR between the jar 102 and the container 600. This increase in HBR from the jar 102 to the container 600 (for the same quantity of composition) is a function of the ratio between the base area of the jar and the base area of the container. For certain quantities of ingredients and certain container sizes, the HBR will fall outside a desired range (e.g., 0.75 to 1.5, or 0.75 to 1.33, or even 1 to 1.25) if the composition is placed directly in the jar 102 and will be closer to, or within, the desired range, if the composition is placed in the container 600.

(149) Another parameter that could be indicative of how efficiently the composition will be dispersed may be “percent volume occupancy” (PVO). For a quantity of composition in a vessel with a generally cylindrical internal volume, the PVO may be defined as the ratio of the height dimension occupied by the composition to the overall interior height dimension of the vessel. In the example of FIG. 10A, the PVO for the jar 102 is clearly under 20%, whereas for the container 600 in FIG. 10B it is over 50%. It should be apparent, therefore, that for the same quantity of composition, the PVO for the container 600 is greater than for the jar 102. In fact, the smaller the quantity of the composition, the greater the difference in PVO between the jar 102 and the container 600.

(150) Expressed another way, the use of the container 600 with the jar 102 can allow a composition that occupies $\frac{1}{2}$ of the jar capacity to have an HBR between 0.75 and 1.5 (or between 0.75 and 1.33, or even between 1 and 1.25) when the composition is placed into the container 600.

(151) As such, it may be more desirable to utilize a container 600 having a certain size, rather than the jar 102, in order to process smaller quantities of composition, so as to obtain a more suitable HBR or PVO. This is especially the case when the quantity of the composition to be processed is less than half the capacity of the jar 102 or less than a quarter of the capacity of the jar or less than a tenth of the capacity of the jar.

(152) To allow the use of a smaller container with improved HBR or PVO, the adapter 602 may help reduce or prevent rattling and other instabilities within the jar 102 during processing by the apparatus 100. The adapter 602 is disposed between the interior of the jar 102 and the exterior of the container 600. When the adapter 602 is attached to the container 600, it can be inserted into and removed from the jar 102, and for this reason the container 600 together with the adapter 602 may be referred to as a removable “containing system” 606.

(153) Different embodiments of the adapter 602 may be provided for different versions of the container 600. Thus, depending on whether the container 600 is a compounding bottle with a nozzle (such as container 402) or a cylindrical bottle (such as container 502A), the adapter 602 may take on a different shape or structure. This is now described in some detail.

(154) FIG. 11 shows a non-limiting embodiment of an adapter 700 for use with a nozzleed container, such as the container 402. The adapter 700 may be in the form of a disk with an aperture 702 in the center thereof. The adapter 700 occupies an area in 3-dimensional space that is outlined by an envelope 704. The adapter 700 may be populated with voids 706 that reduce the weight of the adapter and therefore the density of the adapter 700 vis-à-vis the envelope 704 that it occupies. In some embodiments, the voids 706 are evenly spaced circumferentially and give the adapter 700 the appearance of a wheel.

(155) In some embodiments, the adapter 700 is configured to attach to a container with a nozzle, such as the container 402 previously described. To this end, the aperture 702 has a dimensionality that is selected according to the configuration of the nozzle 408 of the container 402. In particular, FIG. 12 shows details of the external threads 408A on the nozzle 408 and the adapter 700 shown in FIG. 11 may accordingly include internal threads 708 in the area of the central aperture 702 so as to enable the adapter 700 to be screwed onto the nozzle 408. It should be appreciated that when nozzleed containers of different sizes all share the same design of the nozzle 408, the same adapter 700 may be used for these various containers.

(156) FIG. 13 shows an alternative non-limiting embodiment of an adapter 900, also including an aperture 902, but where the aperture 902 is made slightly wider than the aperture 702 and in fact slightly wider than the maximum diameter of the external threads 408A of the nozzle 408. However, the width of the aperture 902 is smaller than the external diameter 410A of the cap 410 (shown in FIG. 8). Thus, when the adapter 900 is placed over the nozzle 408 and then the cap 410 is threaded onto the nozzle 408, the adapter 900 ends up being enclosed between the cover 406 and the cap 410.

(157) The adapters 700, 900 may have a thickness of between 0.5 mm and 5 mm, or even between 1 and 3 mm, although it may be thinner in some embodiments and thicker in others. Other design considerations include (i) that there be sufficient threading 408A in the nozzle 408 to allow the cap 410 to be securely mounted thereto and (ii) once the cap 410 is mounted to the nozzle 408 (on top of the adapters 700, 900) and a containing system 606 is positioned in the jar 102, that there be sufficient clearance (the minimum being zero, i.e., flush) between the top of the cap 410 and the underside of the lid 106 of the jar 102 once the lid 106 has been mounted to the mouth 108 of the jar 102.

(158) To mitigate lateral rattling, the containing system 606 should fit frictionally within the jar 102. To this end, with reference to FIG. 14, the adapter 602 is seen as having a cross-sectional width 1002 that is substantially equal to the cross-sectional width 108W of the mouth 108 of the jar 102. When the containing system 606 is placed into the jar 102, the maximum space between the outer edge of the adapter 602 and the inner surface 218 of the jar 102 may be less than 2 mm, in some cases less than 1 mm and in some cases less than 100 microns.

(159) It should be appreciated that although it is important that there be sufficient clearance between the top of the cap 410 (mounted to the adapters 700, 900) and the underside of the lid 106 of the jar 102 once the lid 106 has been mounted to the mouth 108 of the jar 102, excessive clearance could allow motion along the main axis 608 of the containing system 606 during mixing by the mixing apparatus 100. (Of course, the main axis 608 is shown as being vertical in the drawings, but in use, it is recognized that the jar 102 sits at an angle, and therefore the main axis 608 will be oblique). Excessive clearance is caused by the smaller container sizes that do not have sufficient height dimensions, such that when the adapters 700,

900 are used, the ensuing containing system 606 would still be free to travel in a piston like fashion.

(160) With reference to FIG. 15, there is shown an alternative embodiment of an adapter 1100, which may be useful with smaller container sizes. The adapter 1100 includes a disk 1102 and a band 1104 that surrounds and extends upwardly from the disk 1102. The disk 1102 has a central aperture 1106 that could be similar to the aperture 702 in FIG. 11 (which is internally threaded to engage the external thread 408A of the nozzle 408) or to the aperture 902 in FIG. 13 (which is wider than the nozzle 408). The band 1104 includes a ring 1108 and, optionally, a lip 1110. The ring 1108 has an outside diameter 1112 that is substantially equal to the top inside diameter 202 of the jar 102. The lip 1110 extends radially outwardly beyond the ring 1108, but only slightly, as it is configured to rest on the mouth 108 of the jar 102 without protruding radially from the jar 102. The lip 1110 therefore also has a circular shape and its maximum diameter corresponds to the outer diameter 220 of the jar body 102. The ring 1110 therefore fits frictionally into the jar 102, descending towards the middle section 214 of the jar 102, while the lip 1110 acts as a stopper to prevent the ring 1108 from being pushed too deep into the jar 102. The lid 106 may still be placed onto the mouth 108 of the jar 102, although in reality it is being placed onto an upper surface of the lip 1110. Thus, the height of the jar is increased by no more than 1 or 2 mm, on top of which the lid 106 is positioned.

(161) As shown in FIG. 16, the adapter 1100 may be attached to the container 402 between the top surface of the cover 406 and the bottom surface of the cap 410. When the containing system 606 is placed in the jar 102, a range of smaller sizes of containers 402 can be secured in place by the adapter 1100. In particular, assuming that they all share the same nozzle 408 and cap 410 configuration, the largest size container 402 will be the one whose bottom 1114 touches the bottom of the inside of the bottom surface of the jar 102 when attached to the adapter 1100 of FIGS. 15 and 16.

(162) Thus, smaller sizes of the container 402 can be accommodated by the adapter 1100. In particular, containers having less height can be accommodated by attaching the adapter 1100 in exactly the same way. The difference is that the container will now be suspended within the jar. This is shown in the cross-sectional drawing of FIG. 17. In particular, it is seen that no direct contact exists between the container 1302 and the inner wall 218 of the jar 102. Rather, the adapter 1100 provides the only contact with inner wall 218 of the jar 102. However, this is not a requirement. For example, in other embodiments (not shown), the cap 410 that is threaded onto the nozzle 408 of the container 1302 may contact the underside of the lid 106 of the jar 102. An advantage of the adapter 1100 of FIGS. 15 to 17 may be that the same adapter 1100 can accommodate different size nozzled containers, for example, 50 ml, 30 ml or 20 ml, to name a few non-limiting possibilities.

(163) It should be appreciated that for certain container sizes, although the container 1302 is suspended within the jar 102 at rest by the adapter 1100, during operation, there may be contact between the outer wall of the container 1302 and the inner wall 218 of the jar 102. This may be caused by the high centrifugal force exerted by the apparatus 100 on the containing system 1306 (i.e., the adapter 1100 and the container 1302, including its contents), which could temporarily deform the container 1302 and/or the adapter 1100 to a point where at least a portion surface of the container 1302 makes direct contact with the inner wall 218 of the jar 102.

(164) In another embodiment, the container that contains the composition to be dispersed does not have a cover with a threaded nozzle. Rather, the container may be a cylindrical container with a substantially smooth and even cylindrical profile. In this case, the adapter may be configured to clamp the container from the sides.

(165) Specifically, FIGS. 18A and 18B each show an embodiment of an adapter 1400 at rest, including a base 1402 and a plurality of prongs 1404 distributed circumferentially. The adapter 1400 defines a central opening 1414 into which a container such as the container 502A may be inserted and surrounded by the prongs 1404. The adapter 1400 has a height dimension 1406 that may correspond substantially to the inside height of the jar 102. The prongs 1404 may be resilient and slightly outwardly biased. As such, when the adapter 1400 is at rest (outside the jar 102, as shown in FIGS. 18A and 18B), the prongs 1404 define a substantially band-like cross-section 1408 with an inside width 1410 and an outside width 1412. The inside width 1410, near the top of the adapter 1400, is slightly greater than an outside diameter 508 of the container 502A for which it is configured. Thus there is a gap 1502 as shown in FIG. 19. Also, at rest, the outside width 1412, near the top of the adapter 1400, is slightly greater than the top inside diameter 202 of the jar 102 (see FIG. 1). As will now be explained, there is enough resiliency in the prongs 1404 so that they may be compressed radially inwardly.

(166) In particular, FIG. 20 shows a cross-sectional view of the adapter 1400 when the containing system 1600 (including the adapter 1400 and the container 502A) is placed inside the jar 102. Here, the prongs 1504 are compressed inwardly (towards the center) and the inside width 1410 of the band-like cross-section 1408 formed by the prongs 1404 is now substantially the same as the outside diameter 508 of the container 502A and the outside width 1412 of the band-like cross-section formed by the prongs 1404 is now substantially the same as the top inside diameter 202 of the jar 102. As a result, the container 502A is more snugly maintained by the prongs 1404 within the central opening 1414.

(167) The number of prongs 1404 is not particularly limited. The embodiment of FIGS. 18A and 18B show the adapter 1400 having three prongs 1404. However, in other embodiments, such as in FIG. 21, the adapter 1700 has four prongs 1704.

(168) To limit the amount of material used to make the adapter 1400, 1700, the adapter may include cut-outs 1418, 1718 between the prongs 1404, 1704. The cut-outs have a depth defined as a relative distance occupied by the cut-outs in a height dimension of the adapter compared to the overall height of the respective adapter 1400, 1700. For example, for the adapter 1700 for which a side elevational view is shown in FIG. 21, the depth of the cut-outs 1718 is over 50%. In other embodiments, such as for the adapter 1400 for which a side elevational view is shown in FIG. 18, the depth of the cut-outs 1418 may be over 60%, over 70% or even over 80%. In further embodiments, it may be between 40% and 50%.

(169) The cut-outs 1418, 1718 may take on different shapes and configurations. In FIGS. 18B and 21, the cut-outs 1418, 1718 have a deep parabolic shape. In other embodiments, the cut-outs may have a more square-like (or rectangular) appearance.

(170) In certain embodiments, as shown in FIG. 19, the container 502A may include a vertical viewing window 1504 that allows a user to see a level to which the container 502A is filled. Accordingly, the cut-outs 1418 may be shaped so as to allow at least part of the viewing window 1504 to be unobstructed.

(171) Turning back to FIG. 18, with additional reference to FIG. 14, the base 1402 of the adapter 1400 may be circular and may have a diameter D1402 that is substantially identical to the top inside diameter 202 of the jar 102, or even slightly greater than it (e.g., corresponding to the middle inside diameter 204 or by up to 1 mm or even 2 mm larger). Thus, aligning the base 1402 of the adapter 1400 with the mouth 108 of the jar 102 may make it difficult or even impossible to fit the adapter 1400 into the jar 102. Thus, a different technique for inserting the adapter 1400 into the jar 102 may be required. To this end, the base 1402 can be tilted and then placed onto the mouth 108 of the jar 102, such that only two diametrically opposite extremities 1419, 1420 of the base 1402 are in contact with the inner surface 218 of the jar at respective contact points 222, 224 of the adapter 1400. The adapter 1400 is then urged into the jar, which causes a very slight expansion of the width of the mouth 108, while resulting in a contraction of the mouth elsewhere between the two aforementioned contact points 222, 224. However, since the adapter 1400 is not in contact with these contracting regions, the jar 102 is allowed to flex, and thus allows the adapter 1400 to slip into the jar 102. Once the two contact points 222, 224 of the adapter 1400 pass the top section 212 of the jar 102 (which has the smallest width, namely the top inside diameter 202) and move to the middle section 214 of the jar 102 (which has the second-smallest width, namely the middle inside diameter 204), the mouth 108 of the jar 102 returns back to its original shape, which may be circular.

(172) It should be appreciated that in the case of the container 502A, with a cylindrical exterior shape, the actuator 506 may be provided so that the mixed composition can be dispensed to an end user without the need for transfer into a separate dispenser. Of course, the actuator 506 takes up part of the headroom available between the container 502A and the underside of the lid 106, thus limiting the volume of the composition that can be placed in the body 504 for mixing. Thus, it is possible to provide a container consisting primarily of the body 504 but without the actuator 506. In this case, a temporary cap (not shown) could be fitted on the container body 504, with the temporary cap being relatively short (a height less than that of the actuator 506) and having a maximum width that is no wider than the body 504 of the container 502A. After mixing, the temporary cap may be removed, and replaced with the actuator 506. Because the temporary cap can be designed with a smaller height dimension than the actuator 506,

higher (i.e., more voluminous) containers may be accommodated.

(173) Those ordinarily skilled in the art will appreciate that further improvements may be made to the design of the adapter. In particular, in the case where an adapter is designed that has a maximum width that is less than the width of the jar, rotational motion of the jar may induce slippage in the containing system (which includes the adapter and the container). The amount of slippage may further be a function of the dimensions of the container and the weight and/or volume of the composition contained therein. To reduce slippage, various possible anti-slippage mechanisms may be provided, depending on operational requirements.

(174) Firstly, FIG. 22 shows an adapter **2100** fitted with a rubberized exterior peripheral band **2012**. In another example, as shown in FIG. 23, the inner surface **218** of the jar **102** may be provided with an engaging element **2202** and an adapter **2200** may be provided with a complementary engaging element **2204** that engages with the engaging element **2202**. For example, one of the engaging elements **2202**, **2204** may be a slot, while the other one of the engaging elements **2202**, **2204** may be a protrusion or pin. Of course, many other forms of complementary engaging elements may be devised that inhibit rotational motion of the adapter **2200** and/or the containing system within the jar **102**.

(175) Those skilled in the art will recognize that further improvements may be made to enhance performance during the herein described bladeless dispensing pattern process. For example, in the event that the user wishes to mix a composition that gives off heat, such heat may damage the API of the composition above a certain temperature, known as the degradation temperature threshold. With additional reference to FIG. 24, it is within the scope of the present invention to delay reaching this temperature by providing a heat conductive material **2304** between the adapter **1400** (or **1700**) and the inner surface **218** of the jar **102**. The heat conductive material **2304** may serve to dissipate heat better than simply the air that would ordinarily occupy this space. In some cases, a thermally conductive foil, foam or gel may be provided, as are made available by Fischer Elektronik GmbH, Lüdenscheid, Germany.

(176) In another embodiment, rather than a thermally conductive material, it may be desirable to place a thermally insulating material **2404** between the adapter **1400** and the inner surface **218** of the jar **102**, as shown in FIG. 25. The insulating material **2404** may serve as a barrier to heat leaving the container **502A**, which will result in an increase in the temperature within the container **502A**. As a result, it may be possible to melt the compound that is undergoing the herein described bladeless dispensing pattern process within the container **502A**, thereby leading to a state change of the composition through novel use of the apparatus **100**. Moreover, the use of the heat insulating material **2404** may accelerate the melting process, i.e., shortening the time it takes to melt the composition, thus leading to a more efficient usage of the apparatus **100**.

(177) With reference to FIG. 26, there is shown an insert **2502** that may be removably positioned within the jar **102**. The insert **2502** has the form of a metallic cup with a bottom, but in other embodiments it may be a bottomless sleeve. The insert **2502** may be made of hardened steel, stainless steel, tungsten carbide, agate, sintered aluminium oxide, silicon nitride or zirconium oxide, for example. Also provided are grinding media **2504** such as balls or pellets made of similar materials, as shown in FIG. 27. In an embodiment, the insert **2502** is friction fitted to the inner surface **218** of the jar **102** and may have a thickness of between 10 and 100 mils, although other thicknesses are possible. In another embodiment, the insert **2502** may have a smaller volume and may be held in place within the jar by an adapter, which may be similar to the previously described adapters. As a result, it may be possible to grind ingredients of the compounding composition through novel use of the apparatus **100**.

Definitions

(178) Compounding activities, in the context of the present specification, also applies to combining, mixing or altering ingredients for a cosmetic composition which may include active over the counter (OTC) ingredients or prescription pharmaceutical ingredients. Within the context of the present specification, OTC and prescription ingredients are encompassed by the expression “active pharmaceuticals ingredients” (i.e., “API”).

(179) Examples of active pharmaceuticals ingredients (APIs) include, but are not limited to, antibiotics, analgesics, vaccines, anticonvulsants; antidiabetic agents, antifungal agents, antineoplastic agents, antiparkinsonian agents, anti-rheumatic agents, appetite suppressants, biological response modifiers, cardiovascular agents, central nervous system stimulants, contraceptive agents, dietary supplements, vitamins, minerals, lipids, saccharides, metals, amino acids (and precursors), nucleic acids and precursors, contrast agents, diagnostic agents, dopamine receptor agonists, erectile dysfunction agents, fertility agents, gastrointestinal agents, hormones, immunomodulators, antihypercalcemia agents, mast cell stabilizers, muscle relaxants, nutritional agents, ophthalmic agents, osteoporosis agents, psychotherapeutic agents, parasympathomimetic agents, parasympatholytic agents, respiratory agents, sedative hypnotic agents, skin and mucous membrane agents, smoking cessation agents, steroids, sympatholytic agents, urinary tract agents, uterine relaxants, vaginal agents, vasodilator, anti-hypertensive, hyperthyroid, anti-hyperthyroid, anti-asthmatics and vertigo agents.

(180) In certain embodiments, the API is a poorly water-soluble drug or a drug with a high melting point.

(181) The API may be found in the form of one or more pharmaceutically acceptable salts, esters, derivatives, analogs, prodrugs, and solvates thereof. As used herein, a “pharmaceutically acceptable salt” is understood to mean a compound formed by the interaction of an acid and a base, the hydrogen atoms of the acid being replaced by the positive ion of the base. Non-limiting examples of pharmaceutically acceptable salts include sulfate, citrate, acetate, oxalate, chloride, bromide, iodide, nitrate, bisulfate, phosphate, acid phosphate, isonicotinate, lactate, salicylate, acid citrate, tartrate, oleate, tannate, pantothenate, bitartrate, ascorbate, succinate, maleate, gentisinate, fumarate, gluconate, glucuronate, saccharate, formate, benzoate, glutamate, methanesulfonate, ethanesulfonate, benzenesulfonate, p-toluenesulfonate, and pamoate. Another method for defining the ionic salts may be as an acidic functional group, such as a carboxylic acid functional group, and a pharmaceutically acceptable inorganic or organic base. Non-limiting examples of bases include, but are not limited to, hydroxides of alkali metals such as sodium, potassium and lithium; hydroxides of calcium and magnesium; hydroxides of other metals, such as aluminum and zinc; ammonia; and organic amines, such as unsubstituted or hydroxy substituted mono-, di-, or trialkylamines; dicyclohexylamine; tributylamine; pyridine; N-methyl-N-ethylamine; diethylamine; triethylamine; mono-, bis- or tris-(2-hydroxy-lower alkyl amines), such as mono-bis- or tris-(2-hydroxyethyl)amine, 2-hydroxy-tert-butylamine, or tris-(hydroxymethyl)methylamine, N,N-di-lower alkyl-N-(hydroxy lower alkyl)-amines, such as N,N-dimethyl-N-(2-hydroxyethyl)amine, or tri-(2-hydroxyethyl)amine; N-methyl-D-glucamine; and amino acids such as arginine, lysine, and the like.

(182) The APIs may be used in a variety of application modalities, including oral delivery as tablets, capsules or suspensions; pulmonary and nasal delivery; topical delivery as emulsions, ointments or creams; transdermal delivery; and parenteral delivery as suspensions, microemulsions or depot.

(183) For the purpose of the present disclosure, the pharmaceutically acceptable excipient, diluent or carrier may be a solid, semi-solid (more or less viscous fluid) or fluid (for example a cream or an emulsion). The person of skill will appreciate that pharmaceutically acceptable excipients, diluents or carriers are known in the art and may include, but without being limited thereto, anti-adherents such as magnesium stearate; binders, such as saccharides and their derivatives (sucrose, lactose, starches, cellulose or modified cellulose, sugar alcohols such as xylitol, sorbitol or maltitol), proteins such as gelatins, synthetic polymers such as polyvinylpyrrolidone (PVP) or polyethylene glycol (PEG); coloring dyes or fragrance; glidants such as fumed silica, talc, and magnesium carbonate; hydrophilic or hydrophobic lubricants such as talc or silica, and fats, e.g. vegetable stearin, magnesium stearate or stearic acid; preservatives such as antioxidant vitamins or synthetic preservatives like parabens; sorbents or other desiccant; vehicles that serve as a medium for conveying the active ingredient such as petrolatum, gum base gelatin, dimethyl sulfoxide and mineral oil or commercial products such as VersaPro™ Gel, HRT™ Cream, OleaBase™ Plasticized, PLO Gel Mediflo™, Oral Mix™ or VersaPro™ cream, all from Medisca Pharmaceutique (Canada).

(184) For the purpose of the present disclosure, the compounding compositions of the present description may be adapted for oral, rectal, vaginal, topical, urethral, ocular, or transdermal administration.

EXAMPLES

(185) Details of specific practical implementation of the present disclosure will be further described in the following examples.

Example 1

(186) In the following experiment, a compounding composition of 150 ml including 10% progesterone dispersed in an excipient was prepared according to the herein described superimposed revolution and rotation movements. The characteristics of the resulting composition were assessed. (187) In a dispersing container, 15 g of USP micronized progesterone (NDC: 0043-08, Lot: 56345/B) was levigated with 12.5 mL of ethoxy diglycol by hand. The container was then filled with 122.75 mL of pharmaceutically acceptable excipient VersaPro™ Cream (NDC: 2529-01, Lot: 56035D), and placed in a planetary mixer (Mazerustar KK-250S). The parameters for operating the superimposed revolution and rotation movements were set, including revolution, rotation and time variables. The resulting dispersed 10% progesterone composition was separated in the container into three layers, namely top (T), middle (M) and bottom (B) layers.

(188) The progesterone concentration of each layer was determined using high performance liquid chromatography (HPLC). The person of skill will be able to determine the HPLC assay parameters without undue effort as HPLC is a known technique. The standard deviation (SD) between the progesterone concentrations of the three layers for each prepared formulation was determined. The design of experiment (DOE) was setup as a 23 full factorial design. Explanatory operating parameters included: revolution (x1), rotation (x2) and time (x3). The response variable (y1) was defined as the standard deviation (SD) between the concentrations of progesterone from three separated layers of the prepared composition in the dispersing container. Coding of these variables with respect to mixer settings are shown in Table 1.

(189) TABLE-US-00001 TABLE 1 Coding of Explanatory Variables KK-250S Mixer Setting Explanatory Low Value Centre Point Value High Value Coding Variables (-1) (0) (+1) Equation Revolution, x_1 1 5 $9 \frac{x_1-5}{4}$ Rotation, x_2 1 5 $9 \frac{x_2-5}{4}$ Time, x_3 1 (10 s) 7 (70 s) 15 (150 s) $\frac{x_3-8}{7}$

(190) Eight experimental runs were executed at boundary conditions and three were done at centre point values as set forth in Table 2

(191) TABLE-US-00002 TABLE 2 Trial parameters Randomized Formulation Trial Runs Mixer Ethoxy Trial Setting Progesterone Diglycol VersaPro Mass of Samples [g] x_1 x_2 x_3 Run # x_1 x_2 x_3 [g] [g] [g] Top Middle Bottom 1 1 1 1 9 9 15 15.035 12.912 122.574 48.918 48.311 41.019 0 0 0 2 5 5 7 15.069 12.956 122.492 44.109 45.606 49.642 -1 -1 -1 3 1 1 1 15.037 12.895 122.009 49.097 45.395 52.768 -1 1 1 4 1 9 15 15.053 13.052 122.652 44.340 46.901 55.213 -1 -1 1 5 1 1 15 15.048 12.849 122.816 50.134 46.522 51.165 1 1 -1 6 9 9 1 15.083 12.826 122.695 50.382 50.591 45.714 0 0 0 7 5 5 7 15.030 12.744 122.454 49.940 45.959 5.454 1 -1 -1 8 9 1 1 15.012 12.778 122.784 48.311 44.961 54.641 1 -1 1 9 9 1 15 15.024 12.811 122.705 48.878 49.262 48.490 -1 1 -1 10 1 9 1 15.054 12.725 122.615 49.342 49.447 49.141

(192) Trials were randomized and the results are found in Table 3:

(193) TABLE-US-00003 TABLE 3 Percent Progesterone and Standard Deviation Values for Each Formulation Relative Top, Standard Percent Middle, Average Standard Deviation Progesterone Bottom Concentration Deviation (RSD) Sample # (w/w) layers (w/w) (SD) (%) 1 9.0 T 9.3 0.351 3.77 2 9.3 M 3 9.7 B 4 9.7 T 9.7 0.300 3.09 5 9.4 M 6 10.0 B 7 1.2 T 5.9 4.392 74 8 6.6 M 9 9.9 B 10 8.2 T 9.5 2.166 22 11 8.3 M 12 12.0 B 13 3.3 T 9.4 10.078 107 14 3.8 M 15 21.0 B 16 9.7 T 9.5 0.346 3.64 17 9.1 M 18 9.7 B 19 9.8 T 9.6 0.208 2.17 20 9.7 M 21 9.4 B 22 1.1 T 7.8 8.997 115 23 4.2 M 24 18.0 B 25 7.1 T 8.8 3.659 41 26 6.3 M 27 13.0 B 28 4.2 T 9.1 8.545 93 29 4.2 M 30 19.0 B

(194) The mixing process can be modeled by the following predictive cubic regression:

(195)

$$SD_{\text{PercentProgesterone}} = 3.886 - 1.478(\frac{x_1-5}{4}) - 1.965(\frac{x_2-5}{4}) - 0.62(\frac{x_3-8}{7}) - 1.025(\frac{x_1-5}{4})(\frac{x_2-5}{4}) - 0.58(\frac{x_1-5}{4})(\frac{x_2-8}{7}) - 0.84(\frac{x_1-5}{4})(\frac{x_2-8}{7}) + 2.176(\frac{x_1-5}{4})(\frac{x_2-5}{4})(\frac{x_3-8}{7})$$

(196) In the equation (1), x.sub.1 is the revolution setting, x.sub.2 is the rotation setting and x.sub.3 is the time setting.

(197) The combined effect of revolution, rotation and time was found to have the greatest effect, followed by rotation and revolution. The time setting x.sub.3 by itself, was not statistically significant. The interaction effects were found to be relatively influential, particularly the combination effect of all three parameters. The interaction effects can be seen in FIG. 28.

(198) The model was reduced through an iterative method in order to better observe the parameter and interaction effects on a more statistically significant level. The codependency of the revolution, rotation and time was observed to have the strongest effect on the SD of progesterone concentration, followed by rotation and revolution. As expected, faster rotation and revolution speeds, decreased the SD of percent progesterone. These relationships are illustrated in FIG. 29.

(199) The reduced model can be represented by the following reduced equation:

$$(200) \quad SD_{\text{PercentProgesterone}} = 3.904 - 1.478(\frac{x_1-5}{4}) - 1.965(\frac{x_2-5}{4}) + 2.176(\frac{x_1-5}{4})(\frac{x_2-5}{4})(\frac{x_3-8}{7}) \quad \text{equa. (2)}$$

(201) In equation 2, x.sub.1 is the revolution setting, x.sub.2 is the rotation setting and x.sub.3 is the time setting.

(202) Based on the cubic regression model (equation 1), a desirability algorithm was derived for optimization of the dispersing process. For optimal conditions, desirability was set such that SD of percent progesterone was zero and the time setting was minimized to the lowest value (i.e., 10 seconds). It was found that ideal conditions could be met given the following mixer settings: revolution=9, rotation=9 and time=1. This optimization is shown in FIG. 30.

Example 2

(203) In this example, the superimposed revolution and rotation movements were performed in a planetary mixer (Mazerustar kk-300ss) in presence of grinding media. The following assays surprisingly demonstrated that the herein described superimposed revolution and rotation movements can be used to grind particles in presence of grinding media to obtain a desirable particle size distribution, while maintaining the temperature of the materials being grinded at a safe level below typical degradation temperature of thermally labile API.

(204) Briefly, the container was filled with grinding media and sodium chloride for a total volume of 32 ml, and the superimposed revolution and rotation movements were performed at 1000 rpm (revolution) and 400 rpm (rotation) for 60 seconds with either sphere grinding media of 8 mm (58 beads) or cylinder grinding media of 10 mm (37 beads). A control grinding experiment was performed using mortar and pestle of sodium chloride.

(205) A first assay was performed with 20 g of sodium chloride (NDC 0629-08; lot number 602576/B, melting temperature of 801° C.). FIG. 31A shows that the sodium chloride prior to processing had the following particle size distribution (PSD) in μm : D.sub.10 of 225.563, D.sub.50 of 354.819 and D.sub.90 of 539.090. FIG. 31B shows that the control experiment of mortar and pestle for 60 seconds demonstrated virtually no change in the PSD, with the following values in μm : D.sub.10 of 171.989, D.sub.50 of 328.938 and D.sub.90 of 548.544. FIG. 31C shows that in contrast, grinding with spheres of 8 mm significantly shifted the PSD to the following lower values in μm : D.sub.10 of 8.476, D.sub.50 of 43.919 and D.sub.90 of 126.183, while maintaining the temperature of the mixture at a safe level below typical degradation temperature of thermally labile API. Similarly, FIG. 31D shows that grinding with cylinders also significantly shifted the PSD to the following lower values in μm : D.sub.10 of 11.835, D.sub.50 of 64.803 and D.sub.90 of 181.616, while maintaining the temperature of the mixture at a safe level below typical degradation temperature of thermally labile API. The results are also reported in the following Table 4:

(206) TABLE-US-00004 TABLE 4 Grinding of sodium chloride Mortar Grinding Grinding and Media Media Control Pestle (spheres) (cylinders) Surface Weighted 297.087 194.680 18.511 25.690 Mean (μm) Volume Weighted 367.953 343.262 57.384 99.796 Mean (μm) D.sub.10 (μm) 225.563 171.989 8.476 11.835 D.sub.50 (μm) 354.819 328.938 43.919 64.803 D.sub.90 (μm) 539.090 548.544 126.183 181.616 Temp. before/ 24.7/NA 24.5/24.1 24.7/39.8 25.9/36.9 after (° C.) Weight before/ 5.016/NA 20.012/19.989 20.027/19.887 20.025/19.908 after (g)

(207) Similar results were obtained when milling 30 g of sodium chloride using a mix of bead sizes, namely 80 beads were 8 mm and 25 beads were 6 mm, for a total weight of 310 g. Qualitative assessment of grinding efficacy was also performed in the planetary mixer using as starting material, granular sodium chloride at 10 g, 20 g or 30 g with 45 beads (spherical) of 8 mm filling the bottom layer of the container, for 60 sec at 1000 rpm. The results are that the various weights of materials were effectively grinded with these parameters.

(208) A second assay was performed with Gabapentin (NDC 2461-05; lot number 607832/B; melting temperature of 162° C.). FIG. 32A shows that the API prior to milling had the following particle size distribution (PSD) in μm : D.sub.10 of 9.688, D.sub.50 of 59.399 and D.sub.90 of 164.334. FIG. 32B shows that the control experiment of mortar and pestle for 60 seconds demonstrated virtually no change in the PSD, with the following

values in μm : D.sub.10 of 1.524, D.sub.50 of 9.170 and D.sub.90 of 58.913, while maintaining the temperature of the mixture at a safe level below the degradation temperature of the API. Similarly, FIG. 32D shows that grinding with cylinders for 60 seconds at 1000 rpm also significantly shifted the PSD to the following lower values in μm : D.sub.10 of 3.878, D.sub.50 of 33.616 and D.sub.90 of 150.820, while maintaining the temperature of the mixture at a safe level below the degradation temperature of the API.

(209) The results are also reported in the following Table 4A:

(210) TABLE-US-00005 TABLE 4A Grinding of Gabapentin Grinding Grinding Mortar Media Media Control and Pestle (spheres) (cylinders) Surface Weighted 21.005 18.094 3.826 10.126 Mean (μm) Volume Weighted 76.316 81.389 25.998 91.378 Mean (μm) D.sub.10 (μm) 9.688 8.033 1.524 3.878 D.sub.50 (μm) 59.399 53.500 9.170 33.616 D.sub.90 (μm) 164.334 163.239 58.913 150.820 Temperature Before/ 24.2/NA 23.8/25.1 24.1/37.4 24.6/29.8 After ($^{\circ}\text{C}$.) Weight Before/ 2.508/NA 10.003/9.797 10.011/9.292 10.019/9.599 After (g)

(211) Similar results were obtained when milling 15 g of Gabapentin using a mix of bead sizes, namely 80 beads were 8 mm and 42 beads were 6 mm, for a total weight of 310 g.

(212) Other experiments were also made with the following starting material and grinding media using higher settings, namely a revolution speed of 2000 rpm and a rotation speed of 800 rpm:

(213) TABLE-US-00006 TABLE 4B Grinding of various API starting material Temperature and melting Before/ temp. ($^{\circ}\text{C}$.) grinding media After ($^{\circ}\text{C}$.) Observation Menthol, 20 balls, 5 mm, 24.3/31.5 (30 sec) begins to clump (30 sec) 5 g (31) spherical 24.3/32.5 (60 sec) melting (60 sec) Sodium 20 balls, 5 mm, 24.5/32.9 (30 sec) No visible reduction in Chloride, spherical 24.5/48.3 (60 sec) particle size. 5 g (801) Sodium 20 balls, 5 mm, 24.5/45.1 (30 sec) No visible reduction in Chloride, cylindrical 24.5/58.5 (60 sec) particle size. 5 g (801) Gabapentin, 20 balls, 5 mm, 24.2/36.7 (30 sec) begins to clump (30 sec) 3 g (162) cylindrical 24.2/46.8 (60 sec) very large clumps (60 sec) Gabapentin, 25 balls, 10 mm, 24.2/39.1 (30 sec) 1500 rpm/600 rpm; 2 g (162) cylindrical Container is hot to the touch. Powder has not clumped together.

(214) Other experiments were also made with 2 g of sodium chloride as starting material and grinding media using various settings to more easily visually detect particle size reduction:

(215) TABLE-US-00007 TABLE 4C Grinding of sodium chloride at various milling parameters Temperature Before/ grinding media After ($^{\circ}\text{C}$.) Observation 45 balls, 8 mm, 23.4/28.7 (30 sec) 1000 rpm/400 rpm spherical 24.7/35.8 (60 sec) (rev./rot); Visual reduction in particle size without clumping. 45 balls, 8 mm, 23.8/42.5 (30 sec) 1500 rpm/600 rpm spherical (rev./rot); Visual reduction in particle size without clumping. 25 balls, 10 mm, 24.1/30.6 (30 sec) 1000 rpm/400 rpm cylindrical 24.2/39.5 (60 sec) (rev./rot); Visual reduction in particle size without clumping.

(216) Other experiments were also made with Gabapentin 2 g as starting material and grinding media using lower settings, namely a revolution speed of 1000 rpm and a rotation speed of 400 rpm:

(217) TABLE-US-00008 TABLE 4D Grinding of Gabapentin Temperature Before/ grinding media After ($^{\circ}\text{C}$.) Observation 45 balls, 8 mm, 24.2/30.8 (30 sec) Visual reduction in particle size spherical 25.7/35.7 (60 sec) without clumping. 25 balls, 10 mm, 24.4/25.6 (30 sec) Visually the powder does not cylindrical 23.6/25.5 (60 sec) look as micronized compared to tests with spheres.

(218) These last results suggest that processing time parameters of 30 and 60 seconds keep temperature below 40°C ., which is below the typical degradation temperature for a thermally labile API.

Example 3

(219) In this example, the following compounded pharmaceutical compositions were prepared using the herein described superimposed revolution and rotation movements using a planetary mixer (Mazerustar kk-300ss) with the following dispersion parameters: processing time of 30 sec or 60 sec (either continuously or in two intervals of 30 seconds each), and dispersion speeds of 2000 rpm revolution and 800 rpm rotation. In some cases, a dye was added to the ingredients showing that the herein described superimposed revolution and rotation movements can be used to also disperse colorant within a compounded pharmaceutical composition.

(220) TABLE-US-00009 TABLE 5 Ointment pharmaceutical composition 2% Mucirocin Ointment Ingredient (NDC, Lot) Mupirocin (2545-03, 602996/B), Mineral Oil (0949-08, 38546/1), Medisca OleaBase Plasticized (2575-05, 601610/B) API Melting Temperature ($^{\circ}\text{C}$.) Mupirocin (77-78) Specific Gravity of Base OleaBase Plasticized (0.85)

(221) TABLE-US-00010 TABLE 6 Hormone replacement therapy (HRT) pharmaceutical composition (emulsion) 0.5% Estriol Vaginal Cream (Emulsion, 30 ml) Ingredient (NDC, Lot) Estriol (0732-03, 51222/C), Propylene Glycol (0510-08, 45008/B), VersaPro Cream (2529-08, 124989/B) API Melting Temperature ($^{\circ}\text{C}$.) Estriol (288) Specific Gravity of Base VersaPro Cream (0.97) Temperature before/after ($^{\circ}\text{C}$.) 23.6/25.4 (30 sec.) 25.2/26.2 (30 sec., rest, 30 sec.) 25.8/28.0 (60 sec)

(222) TABLE-US-00011 TABLE 7 Hormone replacement therapy pharmaceutical composition (cream base) Estradiol 0.5 mg/ml, Estriol 2 mg/ml, Progesterone 150 mg/ml Cream Base Ingredient (NDC, Lot) Estradiol Estriol (0732-03, 51222/C), Progesterone (0043-08, 56345/B), Propylene Glycol (0510-08, 45008/B), HRT Cream (0701-08, 46213/K/B) API Melting Temperature ($^{\circ}\text{C}$.) Estriol (288) Estradiol (178) Progesterone (129) Specific Gravity of Base VersaPro Cream (0.97) Temperature before/after ($^{\circ}\text{C}$.) 23.5/29.4 (30 sec.) 29.1/29.7 (30 sec., rest, 30 sec.) 29.1/31.0 (60 sec.)

(223) TABLE-US-00012 TABLE 8 Hormone replacement therapy pharmaceutical composition (cream base) Estradiol 0.5 mg/ml, Estriol 2 mg/ml, Progesterone 150 mg/ml, HRT Cream Base Ingredient (NDC, Lot) Estradiol Estriol (0732-03, 51222/C), Progesterone (0043-08, 56345/B), Propylene Glycol (0510-08, 45008/B), HRT Cream (0701-08, 46213/K/B) API Melting Temperature ($^{\circ}\text{C}$.) Estriol (288) Estradiol (178) Progesterone (129) Specific Gravity of Base HRT Cream (0.98) Viscosity of Base HRT Cream (370 000 cP) Temperature before/after ($^{\circ}\text{C}$.) 23.5/29.4 (30 sec.) 29.1/29.7 (30 sec., rest, 30 sec.) 29.1/31.0 (60 sec.)

(224) TABLE-US-00013 TABLE 9 Gel composition Ibuprofen 5%, Menthol 3% Topical Gel (Suspension, 50 g) Ingredient (NDC, Lot) Ibuprofen (0299-05, 57128/A), Menthol (0521-05, 41612/B), Propylene Glycol (0510-08, 45008/B), VersaPro Gel (2636-05, 45712/P) API Melting Temperature ($^{\circ}\text{C}$.) Ibuprofen (76), Menthol (41-44) Specific Gravity of Base VersaPro Gel (1.00) Viscosity of Base VersaPro Gel (1,000,000 cP) Temperature before/after ($^{\circ}\text{C}$.) 23.0/27.3 (30 sec.) 22.9/26.0 (30 sec., rest, 30 sec.) 23.1/29.3 (60 sec.)

(225) TABLE-US-00014 TABLE 10 Gel composition Ibuprofen 5%, Menthol 3%, Medisca VersaPro Gel Base Ingredient (NDC, Lot) Ibuprofen (0299-05, 57128/A), Menthol (0521-05, 41612/B), Propylene Glycol (0510-08, 45008/B), VersaPro Gel (2636-05, 45712/P) API Melting Temperature ($^{\circ}\text{C}$.) Ibuprofen (76), Menthol (41-44) Specific Gravity of Base VersaPro Gel (0.984) Viscosity of Base VersaPro Gel (1,000,000 cP) Temperature before/after ($^{\circ}\text{C}$.) 23.2/24.8 (30 sec.) 24.8/25.7 (30 sec., rest, 30 sec.) 25.6/28.4 (60 sec.)

(226) TABLE-US-00015 TABLE 11 Pain pharmaceutical composition Gabapentin 6%, Ketoprofen 5%, Diclofenac 3%, Pentylene Glycol 3%, Ethoxy Diglycol 3%, Medisca VersaPro Cream Base. Ingredient (NDC, Lot) Gabapentin (2461-05, 57807/1), Ketoprofen (0078-05, 56561 /B), Diclofenac (2552-08, 44843/B), Pentylene Glycol (2752-08, 50713/A), Ethoxy Diglycol (1903-05, 54500/B), VersaPro Cream (2529-08, 124989/B) Red dye API Melting Temperature ($^{\circ}\text{C}$.) Gabapentin (162-166) Ketoprofen (94) Diclofenac (283-285) Specific Gravity of Base VersaPro Cream (0.99) Temperature before/after ($^{\circ}\text{C}$.) 23.3/24.9 (30 sec.) 24.7/25.5 (30 sec., rest, 30 sec.) 25.4/26.6 (60 sec.)

(227) In the particular pain pharmaceutical composition described in Table 11, the red dye was added on top of the ingredients. Following the dispersion of the ingredients, the resulting mixture had a substantially homogeneous pink color as early as 30 sec.

(228) TABLE-US-00016 TABLE 12 Amlodipine Suspension Amlodipine 1 mg/mL, Medisca Oral Mix Ingredient (NDC, Lot) Amlodipine (2734-blk, 49214, 04/2018), Medisca Oral Mix (2512-08,1102/A, 09/2015) Red dye API Melting Temperature ($^{\circ}\text{C}$.) Amlodipine (178-179) Specific Gravity of Base Oral Mix (1.1202) Viscosity of Base Oral Mix (300 cP) Temperature before/after ($^{\circ}\text{C}$.) 15.8/16.0 (30 sec.) 16.0/16.2 (30 sec., rest, 30 sec.)

16.2/17.0 (60 sec).

(229) In this particular example of a pharmaceutical suspension being dispersed in presence of a red dye, the dye was placed on top of the ingredients. Following the dispersion of the ingredients, the resulting mixture had a substantially homogeneous pink color as early as 30 sec.

Example 4

(230) In this example, the following compounded pharmaceutical compositions were prepared using the herein described superimposed revolution and rotation movements in a planetary mixer (Mazerustar kk-300ss). The dispersing time and the dispersing speed parameters were modified, and a dispersing assessment was made, as indicated in the following tables. Note that the rotation speed (rpm) was kept at a value of 40% of the revolution speed (rpm).

(231) TABLE-US-00017 TABLE 13 Cellulose, NF (Microcrystalline) Ingredient (NDC, Lot) Cellulose, NF (0567-08, 27688/B) Weight (g) 50 25 Temperature before/ 29.3 (1000 rpm/120 sec) 33.0 (1500 rpm/60 sec) after (° C.) when room 35.3 (1500 rpm/120 sec) 30.4 (1500 rpm/30 sec) temperature at 24° C. 31.4 (1500 rpm/60 sec) Mixing assessment 1000 rpm/120 sec + 1500 rpm/60 sec ++ 1500 rpm/120 sec + 1500 rpm/30 sec ++

(232) TABLE-US-00018 TABLE 14 Lactose, NF (Monohydrate) at variable dispersing time Ingredient (NDC, Lot) Lactose, NF (Monohydrate) (0315-08, 600938/Cand 603118/B) Weight (g) 50 Temperature after (° C.) when room Revolution Dispersing temperatureat (rpm) time (sec) 24° C. Mixing assessment 1000 150 29.7 ++ 1000 120 29.4 ++ 1000 90 28.0 ++ 1000 60 28.0 ++ 500 30 25.2 + 1000 30 26.7 ++ 1500 30 30.9 ++ 2000 30 40.5 ++

(233) TABLE-US-00019 TABLE 15 Lactose, NF (Monohydrate) at 180 sec dispersing time Ingredient (NDC, Lot) Lactose, NF (Monohydrate) (0315-08, 600938/C and 603118/B) Red dye Dispersing time (sec) 180 Temperature after Revolution (° C.) when room Mixing Weight (g) (rpm) temperature at 24° C. assessment 25 500 24.6 ++ 1000 29.6 ++ 1500 38.1 ++ 2000 51.5 50 500 26.7 ++ 1000 32.1 ++ 1500 43.8 ++ 2000 63.2 60 500 * ++ 1000 31.1 1500 44.0 2000 ** 75 500 * ++ 1000 27.9 ++ 1500 37.2 ++ 2000 55.5

(234) In the above results, * means that the G forces were observed as being insufficient to achieve a mix whereas ** means that the temperature exceeded the pre-determined threshold temperature of 45° C. for thermally labile API. In this example, a red dye was used to qualitatively assess the dispersion.

(235) TABLE-US-00020 TABLE 16 Capsulend at 60 sec dispersing time Ingredient (NDC, Lot) Capsulend-P (2594-08, 58203/C) Capsulend-S (2593-05, 51997/B and 38893/B) Red dye Dispersing time (sec) 60 Temperature after (° C.) when room Weight Revolution Rotation temperature Mixing (g) (rpm) (rpm) at 24° C. assessment 25 400 160 25.0 — 1000 400 27.5 — 1500 600 31.1 — 2000 800 37.5 ++ 50 400 160 25.1 — 1000 400 27.9 — 1500 600 32.4 — 2000 800 41.9 ++

Example 5

(236) In this example, the following compounded pharmaceutical compositions including 3 different APIs were prepared using the herein described superimposed revolution and rotation movements, or using an Unguator™ as control comparative blade mixing device (Gako International), with the following ingredients:

(237) TABLE-US-00021 TABLE 17 Ingredients % g/ml NDC Lot Diclofenac Sodium 3.0 7.5, 7.95, 7.8 2705-05 44843/B Gabapentin 6.0 15, 15.9, 15.6 603948/A Ketoprofen 5.0 12.5, 13.25, 13 602182/F Pentylene Glycol 3.0 7.5, 6.5, 6.25 2752-08 507131/A Ethoxy Diglycol 3.0 7.5, 6.5, 6.25 54500/B VersaPro Cream QS to 250 g 188.5, 265, 260 605062/A Base

(238) The superimposed revolution and rotation movements parameters were: 2000 rpm for 30 sec (samples 1-3). The parameters for the Unguator™ control comparative blade mixing device (samples 4-5) were: speed 5 for 120 sec (sandwich protocol). Each of the resulting composition was then separated in top, middle and bottom layers and the concentration of each API in each layer was measured with HPLC. The average concentration ([]), the standard deviation (SD) and the relative standard deviation (% RSD) were calculated for each API. The results are shown in the following Table:

(239) TABLE-US-00022 TABLE 17A Results for a composition including 3 API Diclofenac 3% Gabapentin 6% Ketoprofen 5% Assay [] SD % RSD [] SD % RSD [] SD % RSD 1 2.8 0.000 0.0% 5.9 0.047 0.8% 4.9 0.125 2.5% 2 2.8 0.047 1.7% 5.8 0.000 0.0% 4.9 0.082 1.7% 3 2.7 0.000 0.0% 5.7 0.000 0.0% 4.8 0.047 1.0% 4 2.8 0.125 4.4% 5.6 0.262 4.7% 4.9 0.283 5.8% 5 2.7 0.094 3.5% 5.4 0.262 4.8% 4.7 0.216 4.6% 6 2.8 0.082 2.9% 5.5 0.170 3.1% 4.8 0.094 2.0%

(240) These results show that the average % RSD is significantly lower when using the superimposed revolution and rotation movements relative to the Unguator™ control comparative blade mixing device. The inventors were also able to consistently (in over 80% of the cases) obtain for a given API less than 3% RSD, suggesting a significant homogeneity in the compositions made as well as more reproducible results (i.e., less variations from one composition to another). In contrast, the Unguator™ control comparative blade mixing device consistently (in over 80% of the cases) showed higher and variable % RSD for a given API, suggesting less homogeneous compositions and less reproducible results.

Example 6

(241) In this example, the following compounded pharmaceutical compositions including 4 different APIs were prepared using the herein described superimposed revolution and rotation movements, with the following ingredients:

(242) TABLE-US-00023 TABLE 18 Ingredients Ingredients % g/ml NDC Lot Baclofen, USP 2.0 4.0 0388-04 112624/E Bupivacaine HCl, USP 2.5 5.0 0524-04 122720/I Cyclobenzaprine HCl, USP 6.0 12.0 0395-05 115114/E Diclofenac Sodium, USP 10.0 20.0 2705-05 118032/I Ethoxy Diglycol 3.5 7.0 1903-05 119825/D Pentylene Glycol 3.5 7.0 2752-08 122018/B VersaPro Cream Base 72.5 145.0 2529-08 121176/D

(243) The superimposed revolution and rotation movements parameters were: 2000 rpm for 30 sec (samples 4-6). The parameters for the Unguator™ control comparative blade mixing device (samples 1-3) were: speed 5 for 120 sec (sandwich protocol). Each of the resulting composition was then separated in top, middle and bottom layers and the concentration of each API in each layer was measured with HPLC. The average concentration ([]), the standard deviation (SD) and the relative standard deviation (% RSD) were calculated for each API. The results are shown in the following Table:

(244) TABLE-US-00024 TABLE 19 Results for a composition including 4 API Baclofen, Bupivacaine, Cyclobenzaprine, Diclofenac, 2% 2.5% 6% 10% Assay [] SD % RSD [] SD % RSD [] SD % RSD [] SD % RSD 1 2.0 0.265 13% 2.1 0.265 13% 5.4 0.586 11% 9.5 1.079 11% 2 2.0 0.058 3% 2.1 0.100 5% 5.3 0.208 4% 9.3 0.361 4% 3 1.9 0.306 16% 2.0 0.306 15% 5.1 0.794 16% 9.1 1.401 15% 4 2.1 0.058 3% 2.2 0.058 3% 5.6 0.208 4% 9.9 0.321 3% 5 2.1 0.100 5% 2.2 0.115 5% 5.5 0.306 6% 9.6 0.586 6% 6 1.9 0.000 0% 2.1 0.000 0% 5.2 0.153 3% 9.1 0.153 2%

(245) These results show that the average % RSD is significantly lower when using the superimposed revolution and rotation movements relative to the Unguator™ control comparative blade mixing device. The inventors were also able to consistently (in over 80% of the cases) obtain for a given API less than 3% RSD, suggesting a significant homogeneity in the compositions made as well as more reproducible results (i.e., less variations from one composition to another). In contrast, the Unguator™ control comparative blade mixing device consistently (in over 80% of the cases) showed higher and variable % RSD for a given API, suggesting less homogeneous compositions and less reproducible results.

Example 7

(246) In this example, a jar container having a certain internal ratio was used to disperse ingredients using the herein described superimposed revolution and rotation movements. The jar is equipped with an adaptor to fit the jar container into a receiving basket of a planetary mixer. The ingredients used a pharmaceutically acceptable carrier, excipient or diluent, Versapro Cream Base and a red dye, as a tracer. The amount of Versapro added into the container was sufficient to reach the top of the viewing window on the jar container (MD line of containers, from Medisca Pharmaceutique). Note that the rotation speed (rpm) was kept at a value of 40% of the revolution speed (rpm).

(247) TABLE-US-00025 TABLE 20 Results for Versapro Cream in MD jar container Volume of Versapro Cream Revolution Temperature Base (rpm)

(° C.), Time Observation 30 ml 400 23.3 (30 sec) 23.7 (60 sec) Dye moved 5 mm further (60 sec) 24.0 (90 sec) Dye moved 2 mm further (90 sec) 24.3 (120 sec) Dye 2 mm from bottom. (120 sec) 1000 24.7 (30 sec) Dye reached the bottom, homogeneous mix 25.2 (120 sec) (30 and 120 sec) 1500 25.9 (120 sec) Dye reached the bottom, homogeneous mix 2000 24.0 (30 sec) Dye reached the bottom, homogeneous mix 26.5 (120 sec) (30 and 120 sec) 50 ml 400 23.7 (120 sec) 1000 24.0 (30 sec) Dye reached the bottom, homogeneous mix 25.7 (120 sec) (30 and 120 sec) 1500 23.9 (30 sec) Dye reached the bottom, homogeneous mix 25.7 (120 sec) (30 and 120 sec) 2000 Slight leakage past the piston at all tested times, except for 120 sec where it is severe leakage 80 ml 400 23.6 (120 sec) Dye reached the bottom, homogeneous mix 1000 23.8 (30 sec) Dye reached the bottom, homogeneous mix 24.6 (120 sec) 1500 23.9 (30 sec) Dye reached the bottom, homogeneous mix 25.8 (120 sec) 2000 27.2 (120 sec) Dye reached the bottom, homogeneous mix

(248) Safe dispersing parameters so as to avoid leakage, thus, appear to be 1500 rpm at 0.5 min, and are applicable to all sizes of the MD line of jar containers.

Example 8

(249) In this example, a 6.5 ml syringe container (Medisca Pharmaceutique) was used to disperse ingredients using the herein described superimposed revolution and rotation movements. The syringe container is equipped with an adaptor to fit the syringe container into a receiving basket of the planetary mixer. The ingredients used were a pharmaceutically acceptable carrier, excipient or diluent, Versapro Cream Base and a red dye, as a tracer. The amount of Versapro added into the syringe container was of 6.5 g. The dispersed cream was then visually assessed for entrapped air bubbles levels and red dye homogeneity dispersion. Note that the rotation speed (rpm) was kept at a value of 40% of the revolution speed (rpm). (250) TABLE-US-00026 TABLE 21 Results for Versapro Cream in syringe container Revolution Time (rpm) (sec) Observation 500 120 Dye failed to travel down. No noticeable change in air bubble size or shape. 1000 120 Dye failed to travel down. Air bubbles size has decreased but still large number of bubbles visible (mostly non-uniform in size and shape). 1500 30 Dye moved down 2 cm. Air bubbles size has decreased and shape of air bubbles is more uniform. 60 Dye moved down a further 0.5 cm. Layers of colour near the center suggesting heterogeneous mixing. 90 Dye moved down a further 0.5 cm. Layers of colour near the center suggesting heterogeneous mixing. 120 Dye stopped at center cartridge. Heterogeneous mix 2000 30 Dye moved down effectively (2.7 cm). Fewer air bubbles, size has also decreased. Less bubble towards the top. 60 Dye moved down an additional 1-1.5 cm. Mixing flow visible. Layers of distinct shades of pink indicate non-uniform mixing near the center. Slightly more uniform bubble size and shape. No significant change in number of bubbles. Temperature: 28.5° C. 90 Dye moved down (1 cm above the bottom of the cartridge). Mixing flow visible. Top layer (darker pink) has increased, more uniform in the middle compared to before, however, layers still visible. No significant Change in size, shape or number of bubbles. Temperature: 29.7 C. ° 120 Dye has reached bottom of cartridge completely. Mixing flow visible. Layers are less prevalent, color is more uniform throughout. Noticeable change in number of bubbles. Size has slightly decreased. Temp: 31.2 C. °

(251) Similar results were obtained when dispersing in a syringe container of 5.0 ml (Medisca Pharmaceutique, Montreal, Canada).

Example 9

(252) In this example, various pharmaceutically acceptable excipients, carriers or diluents in solid or semi-solid form (i.e., more or less viscous, so long as it cannot be poured like a liquid) were submitted to the herein described superimposed revolution and rotation movements in an attempt to obtain a reversible melt. The dispersing parameters used were 2000 rpm revolution and 800 rpm rotation.

(253) TABLE-US-00027 TABLE 22 Melting of excipient, carrier or diluent Excipient, carrier or diluent Observation VersaPro™ Cream 300 sec dispersing resulted in a temperature of 31.6° C., appears as a cream OleaBase™ Plastisized 240 sec dispersing resulted in a temperature of 38.2° C. Ointment Base 300 sec dispersing resulted in a temperature of 34.2° C., the base became very soft and liquid. There is a major change in consistency and texture. PLO Gel Mediflo™ 30 210 sec dispersing resulted in a temperature of 39.1° C., the gel appears like a cream, not a pourable liquid PolyPeg Suppository Base 300 sec dispersing resulted in a temperature of 51.1° C., the base appears like a cream, not a pourable liquid SPG Supposi-Base™ 300 sec dispersing resulted in a temperature of 34.1° C., the base appears like a cream, not a pourable liquid Gum Base Gelatin 180 sec dispersing resulted in a temperature of 55.1° C., the initial cube shaped gelatin forms melt into a pourable liquid.

(254) The experiment was repeated in different planetary mixer devices, as per the following paragraphs.

(255) TABLE-US-00028 TABLE 22.1 Mazerustar KK-300SS comparison of gelatin gum base chunk size Test 10 Test 16 Lot Number 617221/A 617221/A Mass (gram) 50.02 50.07 RPM 2000 2000 G Force 284 284 Time (seconds) 180 180 Temperature Before (° C.) 23.8 25.5 Temperature After (° C.) 59.6 57.7 ΔT (° C.) 35.8 32.2 Observation fully melted not fully melted as little blocks cut stuck to the top

(256) FIG. 33 shows a typical gum base gelatin particle unaltered from the manufacturers' container (left) and a plurality of these particles contained in the dispersion jar (right). The block has a maximal extent size of about 1 inch.

(257) FIG. 34 shows gum base gelatin particles which have been cut down from the initial size present in the manufacturers' container (left) and a plurality of these particles contained in the dispersion jar (right). The cut down particles have a size of less than about 0.5 inch.

(258) A two (2) decimal place balance was used to weigh the gelatin gum base. During the weighing operations, a plastic jar was placed on the balance and tared. During the first experiment run, 50 grams was processed unaltered. During the second experiment run, the 50 grams of gelatin gum base was minced into smaller pieces. The initial temperature was recorded using a digital thermometer with stainless steel probe by inserting the tip inside of the gum base gelatin before being inserted inside the planetary mixer. The final temperature was measured once the dispersion process was completed, by inserting and swirling the stainless steel probe in the gelatin in order to avoid coagulation as much as possible.

(259) The herein described superimposed revolution and rotation movements was used to melt the gelatin gum base and the process parameters/results obtained were compared to those performed/obtained when using a hot plate. The melted gelatin gum base was assessed by measuring the temperature before and after the melting process by using a digital thermometer with a stainless-steel probe. FIG. 35A-35E shows examples of gum base that completely melted (35A), partially melted (35B, 35C and 35D), and did not melt (35E).

(260) TABLE-US-00029 TABLE 22.2 Mazerustar KK-300SS-25 gram, 180 seconds, variable G Force Test 3 Test 2 Test 4 Lot Number 617221/A 617221/A 617221/A Mass (gram) 25.00 25.20 25.03 RPM 1600 1800 2000 G Force 182 230 284 Time (seconds) 180 180 180 Temperature Before (° C.) 24.3 24.3 24.3 Temperature After (° C.) 50.5 49.1 51.6 ΔT (° C.) 26.2 24.8 27.3 Observation partially melted completely completely melted

(261) TABLE-US-00030 TABLE 22.3 Mazerustar KK-300SS-50 gram, 180 seconds, variable G Force Test 7 Test 9 Test 10 Lot Number 617221/A 617221/A 617221/A Mass (gram) 50.04 50.01 50.02 RPM 1600 1800 2000 G Force 182 230 284 Time (seconds) 180 180 180 Temperature Before (° C.) 24.3 24.0 23.8 Temperature After (° C.) 50.7 56.1 59.6 ΔT (° C.) 26.4 32.1 35.8 Observation partially melted completely completely melted

(262) TABLE-US-00031 TABLE 22.4 Mazerustar KK-300SS-75 gram, 180 seconds, variable G Force Test 8 Test 11 Test 12 Lot Number 617221/A 617221/A 617221/A Mass (gram) 75.03 75.03 75.03 RPM 1600 1800 2000 G Force 182 230 284 Time (seconds) 180 180 180 Temperature Before (° C.) 23.6 23.4 23.3 Temperature After (° C.) 30.6 30.3 56.4 ΔT (° C.) 7.0 6.9 33.1 Observation not melted not melted completely melted

(263) TABLE-US-00032 TABLE 22.5 Mazerustar KK-300SS-75 gram, constant G Force, variable time Test 12 Test 18 Test 17 Lot Number 617221/A 617221/A 617221/A Mass (gram) 75.03 75.01 75.00 RPM 2000 2000 2000 G Force 284 284 284 Time (seconds) 180 300 450 Temperature Before (° C.) 23.3 25 23.7 Temperature After (° C.) 56.4 60.9 61.9 ΔT (° C.) 33.1 35.9 38.2 Observation completely completely completely melted melted melted

(264) TABLE-US-00033 TABLE 22.6 Mazerustar KK-300SS-Constant G Force, 180 seconds, variable mass Test 4 Test 10 Test 12 Lot Number 617221/A 617221/A 617221/A Mass (gram) 25.03 50.02 75.03 RPM 2000 2000 2000 G Force 284 284 284 Time (seconds) 180 180 180 Temperature Before (° C.) 24.3 23.8 23.3 Temperature After (° C.) 51.6 59.6 56.4 ΔT (° C.) 27.3 35.8 33.1 Observation completely completely

completely melted completely melted melted

(265) TABLE-US-00034 TABLE 22.7 Mazerustar KK-300SS-Constant G Force, 300 seconds, variable mass Test 20 Test 19 Test 18 Test 13 Lot Number 617221/A 617221/A 617221/A 617221/A Mass (gram) 25.04 50.03 75.01 100.03 RPM 2000 2000 2000 2000 G Force 284 284 284 284 Time (seconds) 300 300 300 300 Temp. Before (° C.) 24.3 24.1 25 23.4 Temp. After (° C.) 54.2 60.4 60.9 60.1 ΔT (° C.) 29.9 36.3 35.9 36.7 Observation completely completely completely completely melted melted melted melted

(266) TABLE-US-00035 TABLE 22.8 Mazerustar KK-400-75 gram, Constant time, variable G Force Test 14 Test 13 Test 12 Lot Number 617221/A 617221/A 617221/A Mass (gram) 75.02 75.02 75.03 Revolution Setting # 7 8 9 Rotation Setting # 7 8 9 RPM 1058 1218 1340 G Force 170 226 273 Time (seconds) 450 450 450 Temperature Before (° C.) 24.5 24.5 24.3 Temperature After (° C.) 34.5 63.8 66.3 ΔT (° C.) 10.0 39.3 42.0 Observation not melted completely completely melted melted

(267) TABLE-US-00036 TABLE 22.9 Mazerustar KK-400-25 gram, Constant G Force, variable time Test 18 Test 3 Test 5 Test 1 Lot Number 617221/A 617221/A 617221/A 617221/A Mass (gram) 25.00 25.00 25.05 25.00 Revolution Setting # 9 9 9 9 Rotation Setting # 9 9 9 9 RPM 1340 1340 1340 1340 G Force 273 273 273 273 Time (seconds) 180 300 450 600 Temp. Before (° C.) 23.5 24.4 24.7 24.3 Temp. After (° C.) 32.2 32.6 56.3 61.8 ΔT (° C.) 8.7 8.2 31.6 37.5 Observation not melted not melted completely completely melted melted

(268) TABLE-US-00037 TABLE 22.10 Mazerustar KK-400-50 gram, Constant G Force, variable time Test 19 Test 2 Test 8 Test 11 Lot Number 617221/A 617221/A 617221/A 617221/A Mass (gram) 50.06 50.00 50.04 50.01 Revolution Setting # 9 9 9 9 Rotation Setting # 9 9 9 9 RPM 1340 1340 1340 1340 G Force 273 273 273 273 Time (seconds) 180 300 450 600 Temp. Before (° C.) 24.0 24.3 23.9 24.5 Temp. After (° C.) 39.9 44.8 64.2 67.5 ΔT (° C.) 15.9 20.5 40.3 43.0 Observation partially partially completely completely melted melted melted melted

(269) TABLE-US-00038 TABLE 22.11 Mazerustar KK-400-75 gram, Constant G Force, variable time Test 10 Test 6 Test 12 Test 15 Lot Number 617221/A 617221/A 617221/A 617221/A Mass (gram) 75.06 75.01 75.03 75.02 Revol. Setting # 9 9 9 9 Rotation Setting # 9 9 9 9 RPM 1340 1340 1340 1340 G Force 273 273 273 273 Time (seconds) 180 300 450 600 Temp. Before (° C.) 23.6 25.2 24.3 24.4 Temp. After (° C.) 33.5 65.6 66.3 69.5 ΔT (° C.) 9.9 40.4 42.0 45.1 Observation not melted completely completely completely melted melted melted

(270) TABLE-US-00039 TABLE 22.12 Mazerustar KK-400-100 gram, Constant G Force, variable time Test 22 Test 16 Test 20 Lot Number 617221/A 617221/A 617221/A Mass (gram) 100.09 100.02 100.00 Revolution Setting # 9 9 9 Rotation Setting # 9 9 9 RPM 1340 1340 1340 G Force 273 273 273 Time (seconds) 300 450 600 Temperature Before (° C.) 23.4 25.0 23.6 Temperature After (° C.) 65.0 69.6 68.7 ΔT (° C.) 41.6 44.6 45.1 Observation completely completely completely melted melted melted

(271) TABLE-US-00040 TABLE 22.13 Mazerustar KK-400-Constant G Force, 180 seconds, variable mass Test 18 Test 19 Test 10 Lot Number 617221/A 617221/A 617221/A Mass (gram) 25.00 50.06 75.06 Revolution Setting # 9 9 9 Rotation Setting # 9 9 9 RPM 1340 1340 1340 G Force 273 273 273 Time (seconds) 180 180 180 Temperature Before (° C.) 23.5 24.0 23.6 Temperature After (° C.) 32.2 39.9 33.5 ΔT (° C.) 8.7 15.9 9.9 Observation not melted partially melted not melted

(272) TABLE-US-00041 TABLE 22.14 Mazerustar KK-400-Constant G Force, 300 seconds, variable mass Test 3 Test 2 Test 6 Test 22 Lot Number 617221/A 617221/A 617221/A 617221/A Mass (gram) 25.00 50.00 75.01 100.09 Revolution Setting # 9 9 9 9 Rotation Setting # 9 9 9 9 RPM 1340 1340 1340 1340 G Force 273 273 273 273 Time (seconds) 300 300 300 300 Temp. Before (° C.) 24.4 24.3 25.2 23.4 Temp. After (° C.) 32.6 44.8 65.6 65 ΔT (° C.) 8.2 20.5 40.4 41.6 Observation not melted partially completely completely melted melted melted

(273) TABLE-US-00042 TABLE 22.15 Mazerustar KK-400-Constant G Force, 450 seconds, variable mass Test 5 Test 8 Test 12 Test 16 Lot Number 617221/A 617221/A 617221/A 617221/A Mass (gram) 25.05 50.04 75.03 100.02 Revolution Setting # 9 9 9 9 Rotation Setting # 9 9 9 9 RPM 1340 1340 1340 1340 G Force 273 273 273 273 Time (seconds) 450 450 450 450 Temp. Before (° C.) 24.7 23.9 24.3 25.0 Temp. After (° C.) 56.3 64.2 66.3 69.6 ΔT (° C.) 31.6 40.3 42 44.6 Observation completely completely completely completely melted melted melted melted

(274) TABLE-US-00043 TABLE 22.16 Mazerustar KK-400-Constant G Force, 600 seconds, variable mass Test 1 Test 11 Test 15 Test 20 Test 17 Lot Number 617221/A 617221/A 617221/A 617221/A 617221/A Mass (gram) 25.00 50.01 75.02 100.00 151.03 Revolution Setting # 9 9 9 9 9 Rotation Setting # 9 9 9 9 9 RPM 1340 1340 1340 1340 1340 G Force 273 273 273 273 273 Time (seconds) 600 600 600 600 600 Temperature Before (° C.) 24.3 24.5 24.4 23.6 23.4 Temperature After (° C.) 61.8 67.5 69.5 68.7 67.5 ΔT (° C.) 37.5 43 45.1 45.1 44.1 Observation completely completely completely completely completely melted melted melted melted melted

(275) TABLE-US-00044 TABLE 22.17 Mazerustar KK-1000-200 grams, 450 seconds, variable G Force Test 7 Test 6 Test 2 Lot Number 608721/A & 608721/A 617221/A 605082/A Mass (gram) 200.01 200.02 200.07 Revolution Setting # 7 8 9 Rotation Setting # 7 8 9 RPM 770 860 950 G Force 149 186 227 Time (seconds) 450 450 450 Temperature Before (° C.) 23.2 22.8 24.9 Temperature After (° C.) 57.5 60.6 68 ΔT (° C.) 34.3 37.8 43.1 Observation completely completely completely melted melted melted

(276) TABLE-US-00045 TABLE 22.18 Mazerustar KK-1000-200 grams, Constant G Force, variable time Test 9 Test 4 Test 2 Test 5 Lot Number 605082/A 617221/A 617221/A 617221/A Mass (gram) 200.15 200.20 200.07 200.05 Revolution Setting # 9 9 9 9 Rotation Setting # 9 9 9 9 RPM 950 950 950 950 G Force 227 227 227 227 Time (seconds) 180 300 450 600 Temperature Before 23.0 24.5 24.9 24.9 (° C.) Temperature After 63.6 63.8 68.0 72.8 (° C.) ΔT (° C.) 40.6 39.3 43.1 47.9 Observation completely completely completely completely completely melted melted melted melted

(277) TABLE-US-00046 TABLE 22.19 Mazerustar KK-1000-Constant G Force, 450 seconds, variable mass Test 1 Test 2 Test 3 Test 8 Lot Number 617221/A 617221/A 617221/A 608721/A Mass (gram) 100.05 200.07 300.09 525.53 Revolution Setting # 9 9 9 9 Rotation Setting # 9 9 9 9 RPM 950 950 950 950 G Force 227 227 227 227 Time (seconds) 450 450 450 450 Temperature Before 24.9 24.9 24.7 23.4 (° C.) Temperature After 33.0 68.0 71.2 67.7 (° C.) ΔT (° C.) 8.1 43.1 46.5 44.3 Observation not melted completely completely completely melted melted melted

Hot Plate

(278) TABLE-US-00047 TABLE 22.20 Hot Plate Test 1 Test 2 Test 3 Lot Number 10810/B 10810/B 608721/A Mass (gram) 50.325 70.273 100.090 Time (seconds) 559 790 1059 Temperature Before (° C.) 24.5 24.5 24.5 Temperature After (° C.) 59.1 59.6 58.4 ΔT (° C.) 34.6 35.1 33.9 Observation completely completely completely melted melted melted

Material and Methods

(279) Hot Plate

(280) A water bath was set with a water temperature of 65° C. A hot plate Thermos Scientific Cimarec™ model SP131325 was used. A beaker of size Pyrex™ number 1003 with capacity 1000 ml, 4 in diameter and 6 in in height, was used to contain the water. A beaker of size Veegee™ Glassco number 20229 with capacity 600 ml, 3.5 in diameter and 5 in in height, was used to contain the gelatin. The gelatin gum base was placed in the melting beaker and the timer was started. The water temperature of 65° C. was maintained while briefly mixing every 3 minutes. Time was recorded once all gelatin cubes had melted. Final temperature of melted gelatin gum base was recorded. This experimental assessment was reproduced for 50, 75 and 100 grams.

(281) Mazerustar KK-300SS, KK-400 and KK-1000

(282) A two (2) decimal place balance was used to weight the gelatin gum base. During the weighing operations, a plastic jar was placed on the balance and tared. Various amounts of gelatin gum base were tested due to the varying capacities of the different planetary mixers, the weights of 25, 50, 75, 100, 120, 150, 200, 300 and 500 grams were selected. The temperature was recorded using a digital thermometer with stainless steel probe by inserting the tip inside of the gelatin gum base. The final temperature was measured by repeating the process and swirling the stainless steel probe as to avoid coagulation as much as possible.

(283) Mazerustar KK-300SS

(284) Parameters of 180 seconds time period in combination with 25, 50 and 75 grams were used for increasing G Force and RPM. For the Mazerustar KK-300SS: 182 G Force corresponds to 1600 RPM; 230 G Force corresponds to 1800 RPM; and 284 G Force corresponds to 2000 RPM.

(285) Parameters of G Force of 284 (2000 RPM) in combination with 75 grams were used for increasing the time of melting in the Mazerustar. For the Mazerustar KK-300SS times of 180, 300 and 450 seconds were used.

(286) Parameters of G force of 284 (2000 RPM) in combination with 180 seconds were used for increasing the mass of melting in the Mazerustar. For the Mazerustar KK-300SS mass of 25, 50 and 75 grams were used.

(287) Parameters of G force of 284 (2000 RPM) in combination with 300 seconds were used for increasing the mass of melting in the Mazerustar. For the Mazerustar KK-300SS mass of 25, 50, 75 and 100 grams were used.

(288) Mazerustar KK-400

(289) Parameters of 450 seconds time period in combination with 75 grams were used for increasing G Force and RPM. For the Mazerustar KK-400:170 G Force corresponds to 1058 RPM; 226 G Force corresponds to 1218 RPM; and 273 G Force corresponds to 1340 RPM.

(290) Parameters of G Force of 273 (1340 RPM) in combination with 25, 50 and 75 grams were used for increasing the time of melting in the Mazerustar. For the Mazerustar KK-400 times of 180, 300, 450 and 600 seconds were used.

(291) Parameters of G Force of 273 (1340 RPM) in combination with 100 grams were used for increasing the time of melting in the Mazerustar. For the Mazerustar KK-400 times of 300, 450 and 600 seconds were used.

(292) Parameters of G force of 273 (1340 RPM) in combination with 180 seconds were used for increasing the mass of melting in the Mazerustar. For the Mazerustar KK-400 mass of 25, 50 and 75 grams were used.

(293) Parameters of G force of 284 (2000 RPM) in combination with 300 and 450 seconds were used for increasing the mass of melting in the Mazerustar. For the Mazerustar KK-400 mass of 25, 50, 75 and 100 grams were used.

(294) Parameters of G force of 284 (2000 RPM) in combination with 600 seconds were used for increasing the mass of melting in the Mazerustar. For the Mazerustar KK-400 mass of 25, 50, 75, 100 and 150 grams were used.

(295) Mazerustar KK-1000

(296) Parameters of 450 seconds time period in combination with 200 grams were used for increasing G Force and RPM. For the Mazerustar KK-1000:149 G Force corresponds to 770 RPM; 186 G Force corresponds to 860 RPM; and 227 G Force corresponds to 950 RPM.

(297) Parameters of G Force of 227 (950 RPM) in combination with 200 grams were used for increasing the time of melting in the Mazerustar. For the Mazerustar KK-1000 times of 180, 300, 450 and 600 seconds were used.

(298) Parameters of G force of 227 (950 RPM) in combination with 450 seconds were used for increasing the mass of melting in the Mazerustar. For the Mazerustar KK-1000 mass of 100, 200, 300 and 500 grams were used.

Results and Discussion

(299) The following can be deduced from the results reported in tables 20 and 20.1 to 20.20 as well as in FIGS. 36-38.

(300) The gelatin particles melted as the planetary motion induced friction between the particles and the inside surfaces of the jar. By nature, gelatin gum base has an adhesive surface. The gelatin gum base chunk volume and mass increased proportionally. However, the surface area adhering to the plastic of the same chunk of gelatin gum base also increased but at a lower rate than the mass. The smaller the mass of the gelatin chunk, the more difficulty the planetary mixer had of dislodging the mass of gelatin stuck on the wall and, thus, not being able to melt.

(301) The results show that that there was a direct correlation between melting and the planetary mixer's G Force/RPM speed, time and mass of gum base gelatin. The final temperature of the melted substance increased as the G Force/RPM speed increased and the time increased. The final temperature of the melted substance followed a quadratic function, where a minimal and a maximal mass can be used to melt the gelatin gum base.

Example 10

(302) In this example, an Unguator cartridge was used to disperse ingredients the herein described superimposed revolution and rotation movements. The cartridge is fitted with an adaptor to fit the Unguator cartridge into a receiving basket of the planetary mixer. The ingredients used were a pharmaceutically acceptable carrier, excipient or diluent, Versapro Cream Base and a red dye, as a tracer. The amount of Versapro added into the Unguator cartridge was the nominal value recommended by the Unguator manufacturer. The dispersed cream was then visually assessed for red dye homogeneity dispersion. Note that the rotation speed (rpm) was kept at a value of 40% of the revolution speed (rpm).

(303) TABLE-US-00048 TABLE 23 Versapro in Unguator cartridge Volume of Unguator revolution Temperature cartridge (rpm) (° C.), Time Observation 15 ml 400 25.1 (120 sec) Not completely homogeneous mix, very light color in the middle. 1000 23.7 (30 sec) Dye reached the bottom, homogeneous mix (30 and 25.7 (120 sec) 120 sec) 1500 24.1 (30 sec) Dye reached the bottom, homogeneous mix (30 and 26.2 (120 sec) 120 sec) 2000 No leakage beyond the piston. However, jar came loose from the lid and cream spilled out. 20 ml 400 24.1 (120 sec) Not completely homogeneous, lighter color in the middle (30 sec). Dye reached the bottom, homogeneous mix and uniform color. (120 sec) 1000 25.8 (30 sec) Dye reached the bottom, homogeneous mix and 25.8 (120 sec) uniform color (30 sec and 120 sec) 1500 25.8 (30 sec) Dye reached the bottom, homogeneous mix and 26.3 (120 sec) uniform color (30 sec and 120 sec) 2000 No leakage beyond the piston. However, jar came loose and detached from the lid and cream spilled out. 30 ml 400 Dye did not reach the bottom, not a homogeneous mix. (30 sec and 120 sec) 1000 23.2 (30 sec) Dye reached the bottom, homogeneous mix (30 sec 24.6 (120 sec) and 120 sec) 1500 23.1 (30 sec) Dye reached the bottom, homogeneous mix (30 sec) No leakage beyond the piston. However, jar came loose and detached from the lid and cream spilled out. (60 sec) 2000 — — 50 ml 400 23.9 (120 sec) Dye did not reach the bottom, not a homogeneous mix (30 sec) Dye reached the bottom, homogeneous mix and uniform color. (120 sec) 1000 23.1 (30 sec) Dye reached the bottom, homogeneous mix (30 sec 25.1 (120 sec) and 120 sec) 1500 No leakage beyond the piston. However, jar came loose and detached from the lid and cream spilled out. (30 sec) 100 ml 400 23.1 (120 sec) Dye did not reach the bottom, not a homogeneous mix (30 sec) Dye reached the bottom, homogeneous mix and uniform color. (120 sec) 1000 24.2 (30 sec) Dye reached the bottom, homogeneous mix (30 sec) 24.2 (120 sec) 1500 23.2 (30 sec) Dye reached the bottom, homogeneous mix and uniform color. However, jar had become slightly loose from the lid. (30 sec) No leakage beyond the piston. However, jar came loose and detached from the lid and cream spilled out. (60 sec)

(304) Safe dispersing parameters so as to avoid leakage, thus, appear to be 1000 rpm at 0.5 min, and are applicable to all sizes of the Unguator cartridge line of containers with the herein described adaptors.

Example 11

(305) In this example, grinding of variable amounts of ingredient particles was performed the herein described superimposed revolution and rotation movements in a planetary mixer (Mazerustar kk-300ss, kk-400 or kk-1000) in presence of grinding media. The container was filled with grinding media and the ingredient particles. The dispersing time and the dispersing speed parameters were modified, and a dispersing assessment was made, as indicated in the following tables.

(306) It is to be noted that this tables make reference to particle size distribution values such as D.sub.10, D.sub.50 and D.sub.90. These are known manners to represent particle size distribution. For example, D.sub.90 signifies the point in the size distribution, up to and including which, 90% of the total volume of material in the sample is 'contained'. For example, if the Doo is 844 nm, this means that 90% of the sample has a size of 844 nm or smaller.

(307) TABLE-US-00049 TABLE 24 Standard NaCl particle size (LOT number 613788, NDC 0629) Surface Weighted Mean (µm) 248.715 Volume Weighted Mean (µm) 371.042 D.sub.10 (µm) 203.931 D.sub.50 (µm) 354.291 D.sub.90 (µm) 575.27

(308) TABLE-US-00050 TABLE 25 Mazerustar KK-300SS-Constant time, variable G Force Test 1 Test 2 Test 3 Test 4 NaCl (grams) 22.90 22.90 22.90 22.90 RPM 1100 1300 1600 1800 G Force 86 120 182 230 Time (seconds) 60 60 60 60 Surface Weighted Mean (µm) 17.011 10.850 N/A N/A Volume Weighted Mean (µm) 171.164 178.076 N/A N/A D.sub.10 (µm) 7.593 5.077 N/A N/A D.sub.50 (µm) 44.899 31.239 N/A N/A D.sub.90 (µm) 725.785 826.723 N/A N/A Temperature Before (° C.) 23.7 24.2 N/A N/A Temperature After (° C.) 43.3 52.0 N/A N/A

(309) TABLE-US-00051 TABLE 26 Mazerustar KK-300SS-Variable time, constant G Force Test 1 Test 6 Test 7 Test 8 Test 9 NaCl (grams) 22.90

22.90 22.90 22.90 22.90 RPM 1100 1100 1100 1100 1100 G Force 86 86 86 86 86 Time (seconds) 60 90 120 180 300 Surface Weighted 17.011 7.933 6.284 4.956 4.56 Mean (μm) Volume Weighted 171.164 41.888 32.521 32.939 42.691 Mean (μm) D.sub.10 (μm) 7.593 3.992 3.190 2.292 2.012 D.sub.50 (μm) 44.899 21.823 17.793 14.002 12.835 D.sub.90 (μm) 725.785 81.408 66.279 59.787 109.449 Temperature Before 23.7 22.1 24.3 23.5 26.0 (° C.) Temperature After 43.3 54.1 58.8 46.7 64.7 (° C.)

(310) TABLE-US-00052 TABLE 27 Mazerustar KK-400-Constant time, variable G Force Test 1 Test 2 Test 3 Test 4 NaCl (grams) 22.90 22.90 22.90 22.90 Revolution Setting # 5 6 7 8 Rotation Setting # 5 6 7 8 RPM 804 935 1058 1218 G Force 98 133 170 226 Time (seconds) 60 60 60 60 Surface Weighted Mean (μm) 23.095 11.283 6.553 5.915 Volume Weighted Mean (μm) 81.929 57.473 32.390 36.968 D.sub.10 (μm) 10.468 5.624 3.592 3.083 D.sub.50 (μm) 64.028 31.677 17.864 15.731 D.sub.90 (μm) 181.26 107.833 68.490 83.828 Temperature Before (° C.) 23.1 25.3 24.7 25.5 Temperature After (° C.) 34.1 47.3 63.7 78.4

(311) TABLE-US-00053 TABLE 28 Mazerustar 400-Variable time, constant G Force Test 1 Test 6 Test 7 Test 8 Test 9 NaCl (grams) 22.90 22.90 22.90 22.90 22.90 Revolution Setting # 5 5 5 5 5 Rotation Setting # 5 5 5 5 5 RPM 804 804 804 804 804 G Force 98 98 98 98 98 Time (seconds) 60 90 120 180 300 Surface Weighted 23.095 11.527 8.580 5.84 4.82 Mean (μm) Volume Weighted 81.929 44.4229 33.358 35.459 33.206 Mean (μm) D.sub.10 (μm) 10.468 5.889 4.613 2.864 2.278 D.sub.50 (μm) 64.028 31.852 22.848 16.457 13.084 D.sub.90 (μm) 181.26 101.156 76.524 35.459 66.116 Temperature Before 23.1 26.6 24.9 26.9 26.3 (° C.) Temperature After 34.1 42.6 46.0 49.8 47.8 (° C.)

(337) The temperature gain increased as the processing time increases. The temperature gain stabilised quickly for any value after the 90-second marks.

(338) TABLE-US-00054 TABLE 29 Mazerustar KK-1000-Constant time, variable G Force Test 1 Test 2 Test 3 Test 4 NaCl (grams) 53.00 53.00 53.00 53.00 Revolution Setting # 5 6 8 9 Rotation Setting # 5 6 8 9 RPM 590 680 860 960 G Force 88 116 186 227 Time (seconds) 60 60 60 60 Surface Weighted Mean (µm) 190.024 20.891 5.586 5.964 Volume Weighted Mean (µm) 375.514 80.659 28.893 40.497 D.sub.10 (µm) 184.331 9.437 2.845 2.900 D.sub.50 (µm) 361.686 60.390 15.174 15.937 D.sub.90 (µm) 602.621 182.817 63.131 97.955 Temperature Before (° C.) 22.7 25.6 23.7 24.8 Temperature After (° C.) 27.9 41.9 85.5 107.4

(339) TABLE-US-00055 TABLE 30 Mazerustar 1000-Variable time, constant G Force Test 1 Test 6 Test 7 Test 8 Test 9 NaCl (grams) 53.00 53.00 53.00 53.00 53.00 Rev # 5 5 5 5 5 Rot # 5 5 5 5 5 RPM 590 590 590 590 590 G Force 88 88 88 88 88 Time (seconds) 60 90 120 180 300 Surface Weighted 190.024 17.128 10.585 6.498 10.365 Mean (µm) Vol. Weighted 375.514 69.509 40.890 33.689 96.187 Mean (µm) D.sub.10 (µm) 184.331 7.750 5.386 3.295 5.12 D.sub.50 (µm) 361.686 45.419 28.919 19.327 32.163 D.sub.90 (µm) 602.621 141.883 93.219 68.821 127.26 Temperature Before 22.7 24.8 26.4 24.9 24.9 (° C.) Temperature After 27.9 42.9 48.2 53.9 54.8 (° C.)

(340) TABLE-US-00056 TABLE 31 Mortar & Pestle-Variable time & weight Test 1 Test 2 Test 3 Test 4 Test 5 Test 6 User User 1 User 1 User 1 User 2 User 2 User 2 NaCl (grams) 22.90 22.90 22.90 22.90 22.90 22.90 Time (seconds) 60 180 300 60 180 300 D.sub.10 (µm) 79.86 19.108 10.27 128.563 26.732 8.070 D.sub.50 (µm) 322.183 218.789 127.252 329.516 253.368 103.698 D.sub.90 (µm) 564.429 459.647 326.609 567.004 493.422 287.631 Temp. 25.6 26.3 26.8 N/A N/A N/A Before (° C.) Temp. 26.3 26.8 27.0 N/A N/A N/A After (° C.)

(341) TABLE-US-00057 TABLE 32 Mortar & Pestle-Variable time & weight Test 7 Test 8 Test 9 Test 10 Test 11 Test 12 User User 1 User 1 User 1 User 2 User 2 User 2 NaCl (grams) 50.00 50.00 50.00 50.00 50.00 50.00 Time (seconds) 60 180 300 60 180 300 D.sub.10 (µm) 187.352 157.311 99.553 184.351 114.791 89.662 D.sub.50 (µm) 358.969 346.437 327.158 348.63 331.814 322.701 D.sub.90 (µm) 593.531 586.343 567.563 584.389 575.718 561.756 Temperature 25.1 24.7 25.4 N/A N/A N/A Before (° C.) Temperature 24.7 25.4 25.4 N/A N/A N/A After (° C.)

Example 12

(342) In the following experiment, a compounding composition including 3 API was dispersed in an excipient was prepared according to the herein described superimposed revolution and rotation movements, or using an Electric Mortar and Pestle (EMP) Mixer as control comparative mixing device. The characteristics of the resulting composition were assessed. Notably, this experiment demonstrated that the superimposed revolution and rotation movements can be implemented independently of the processing capacity or planetary mixer model used.

(343) Homogeneity was assessed by measuring the API potency with high performance liquid chromatography (HPLC) at three layers of a given mixing vessel (top, middle and bottom layers). The API potency was reported in the form of a weight/weight concentration on triplicate batches. In other words, the formulation for a given container and volume size was repeated three (3) times in order to obtain statistically significant data.

(344) The assays were performed with different planetary mixer models, namely the Mazerustar KK-300SS, KK-400W, and KK-1000W and an EMP Mixer.

(345) Samples were prepared using six (6) different mixer/volume configurations with a formula of Baclofen 2%, Cyclobenzaprine 6% and Diclofenac 10% in VersaPro™ Cream. Briefly, the baclofen and cyclobenzaprine hydrochloride were weighted into separate glass mortar and pestles. The baclofen and cyclobenzaprine hydrochloride were triturated until a fine powder with no grittiness was formed. In a glass mortar and pestle the desired quantity of baclofen, cyclobenzaprine hydrochloride and diclofenac sodium were combined. Desired amounts of ethoxy diglycol and pentyleneglycol were incorporated into the powder blend until the powder blend was levigated and a smooth paste was achieved.

(346) The dispersing container (Mazerustar or EMP jar) was filled with the desired amount of Versapro Cream and placed into the respective device (planetary Mazerustar or EMP). The parameters for operating the devices were set, including revolution, rotation and time variables for the planetary mixers.

(347) The resulting 3 API formulation composition were separated in the container into three layers, namely top (T), middle (M) and bottom (B) layers.

(348) TABLE-US-00058 TABLE 33 List of Ingredients for 3-API Formulation grams or mL 1 2 3 KK- KK- KK- 4 5 6 300SS 400W 1000W EMP EMP EMP Ingredient (200 g) (300 g) (750 g) (200 g) (300 g) (750 g) NDC Lot Baclofen USP 4 6 15 Baclofen USP 4 6 15 Baclofen USP Cyclobenzaprine 12 18 45 Cyclobenzaprine 12 18 45 Cyclobenzaprine Hydrochloride Hydrochloride Hydrochloride USP USP USP Diclofenac 20 30 75 Diclofenac 20 30 75 Diclofenac Sodium USP Sodium USP Sodium USP (Micronized) (Micronized) (Micronized) Ethoxy 9 13.5 36 Ethoxy 9 13.5 36 Ethoxy Diglycol Diglycol Diglycol Pentyleneglycol 8 12 30 Pentyleneglycol 8 12 30 Pentyleneglycol Glycol Glycol Glycol VersaPro 147 220.5 549 VersaPro 147 220.5 549 VersaPro Cream Base Cream Base Cream Base

(349) The superimposed revolution and rotation movement parameters in the planetary mixer were (samples 1-3): 1. Mazerustar KK-300SS: 2000 RPM (revolution)/800 RPM (rotation) for 30 sec (standard jar) [which provides a G force of 284 g] 2. Mazerustar KK-400W: 1340 RPM (revolution)/1340 RPM (rotation) for 70 sec [which provides a G force of 273 g] 3. Mazerustar KK-1000W: 960 RPM (revolution)/950 RPM (rotation) for 130 sec [which provides a G force of 227 g]

(350) The EMP parameters were (samples 4-6): 4. EMP 200 mL Jar: Lift Engine Step 01, Mix Engine Step 06 for 120 sec 5. EMP 300 mL Jar: Lift Engine Step 01, Mix Engine Step 06 for 120 sec 6. EMP 1 L Jar: Lift Engine Step 01, Mix Engine Step 06 for 180 sec

(351) Each of the resulting composition was then separated in top, middle and bottom layers and the concentration of each of the 3 API in each layer was measured with HPLC. The average concentration ([]), the standard deviation (SD) and the relative standard deviation (% RSD) were calculated for each API. The results are shown in the following Tables:

(352) TABLE-US-00059 TABLE 34 Results for a composition including 3 API dispersed in Mazerustar KK-300SS Layer (top, Formulation Sample middle, Baclofen Cyclobenzaprine Diclofenac # # bottom) (w/w) (w/w) (w/w) 1 1 Top 2.045 6.144 10.045 2 Middle 2.019 6.070 9.925 3 Bottom 2.070 6.175 10.114 2 4 Top 1.992 6.129 9.970 5 Middle 2.085 6.251 10.156 6 Bottom 2.032 6.270 10.191 3 7 Top 2.071 6.334 10.319 8 Middle 2.070 6.311 10.265 9 Bottom 2.116 6.421 10.456

(353) TABLE-US-00060 TABLE 35 Results for a composition including 3 API dispersed in Mazerustar KK-400W Layer (top, Formulation Sample middle, Baclofen Cyclobenzaprine Diclofenac # # bottom) (w/w) (w/w) (w/w) 4 10 Top 2.089 6.332 10.334 11 Middle 2.113 6.345 10.375 12 Bottom 2.127 6.316 10.352 5 13 Top 2.069 6.340 10.292 14 Middle 2.090 6.426 10.486 15 Bottom 2.051 6.397 10.438 6 16 Top 2.067 6.321 10.306 17 Middle 2.094 6.312 10.3 18 Bottom 2.081 6.394 10.41

(354) TABLE-US-00061 TABLE 36 Results for a composition including 3 API dispersed in Mazerustar KK-1000W Layer (top, Formulation Sample middle, Baclofen Cyclobenzaprine Diclofenac # # bottom) (w/w) (w/w) (w/w) 7 19 Top 2.085 6.432 10.556 20 Middle 2.068 6.435 10.535 21 Bottom 2.039 6.295 10.32 8 22 Top 2.105 6.426 10.374 23 Middle 2.106 6.427 10.389 24 Bottom 2.086 6.46 10.418 9 25 Top 2.130 6.369 10.382 26 Middle 2.108 6.224 10.179 27 Bottom 2.107 6.294 10.28

(355) TABLE-US-00062 TABLE 37 Results for a composition including 3 API dispersed in EMP 200 mL Jar Layer (top, Formulation Sample middle, Baclofen Cyclobenzaprine Diclofenac # # bottom) (w/w) (w/w) (w/w) 10 28 Top 2.165 6.475 10.612 29 Middle 2.021 6.089 9.985 30 Bottom 2.024 6.11 10.021 11 31 Top 2.133 6.44 10.536 32 Middle 2.12 6.288 10.285 33 Bottom 2.05 6.212 10.169 12 34 Top 2.209 6.457 10.565 35 Middle 2.074 6.182 10.136 36 Bottom 2.113 6.279 10.288

(356) TABLE-US-00063 TABLE 38 Results for a composition including 3 API dispersed in EMP 300 mL Jar Layer (top, Formulation Sample middle, Baclofen Cyclobenzaprine Diclofenac # # bottom) (w/w) (w/w) (w/w) 13 37 Top 2.235 6.674 10.935 38 Middle 2.082 6.272 10.295 39 Bottom 2.208 6.48 10.604 14 40 Top 2.185 6.557 10.752 41 Middle 2.087 6.205 10.15 42 Bottom 1.998 6.047 9.908 15 43 Top 2.23 6.743 11.035 44 Middle 2.089 6.228 10.205 45 Bottom 2.044 6.216 10.193

(357) TABLE-US-00064 TABLE 39 Results for a composition including 3 API dispersed in EMP 1 L Jar Layer (top, middle, Baclofen Cyclobenzaprine Diclofenac # # bottom) (w/w) (w/w) (w/w) 16 46 Top 2.113 6.376 10.454 47 Middle 2.073 6.097 10.003 48 Bottom 2.101 6.147 10.093 17 49 Top 2.031 6.294 10.301 50 Middle 2.094 6.488 10.558 51 Bottom 1.987 6.182 10.021 18 52 Top 2.098 6.396 10.284 53 Middle 2.154 6.506 10.486 54 Bottom 2.088 6.182 9.932

(358) TABLE-US-00065 TABLE 40 % RSD Results for the compositions of Table 34 to 39 Baclofen, Cyclobenzaprine, Diclofenac, 2% 6% 10% Formulation # % RSD 1 1.2% 0.9% 1.0% 2 2.3% 1.2% 1.2% 3 1.3% 0.9% 1.0% 4 0.9% 0.2% 0.2% 5 0.9% 0.7% 1.0% 6 0.6% 0.7% 0.6% 7 1.1% 1.3% 1.2% 8 0.5% 0.3% 0.2% 9 0.6% 1.2% 1.0% 10 4.0% 3.5% 3.4% 11 2.1% 1.8% 1.8% 12 3.3% 2.2% 2.1% 13 3.8% 3.1% 3.0% 14 4.5% 4.2% 4.2% 15 4.6% 4.7% 4.6% 16 1.0% 2.4% 2.3% 17 2.6% 2.4% 2.6% 18 1.7% 2.6% 2.7%

Example 13

(359) In the following experiment, a compounding composition including 2 API was dispersed in an excipient was prepared according to the herein described superimposed revolution and rotation movements, or using an Electric Mortar and Pestle (EMP) Mixer as control comparative mixing device. The characteristics of the resulting composition were assessed. Notably, this experiment demonstrated that the superimposed revolution and rotation movements can be implemented independently of the processing capacity or planetary mixer model used.

(360) Homogeneity was assessed as in Example 12. The dispersing processes were performed with the same devices as in Example 12.

(361) Samples were prepared using six (6) different mixer/volume configurations with a formula of Estradiol 0.05% and Estriol 0.2% in VersaPro Cream. Briefly, the estradiol and estriol were weighted into separate plastic weigh boats. A 3 decimal place balance was used to prepare the formulation. Desired amounts of propylene glycol were incorporated into the powder blend until the powder blend was levigated and a smooth homogeneous liquid. The dispersing container (Mazerustar or EMP jar) was filled with the desired amount of Versapro Cream and placed into the respective device (planetary Mazerustar or EMP). The parameters for operating the devices were set, including revolution, rotation and time variables for the planetary mixers.

(362) The resulting 2 API formulation composition were separated in the container into three layers, namely top (T), middle (M) and bottom (B) layers.

(363) TABLE-US-00066 TABLE 41 List of Ingredients for 2-API Formulation grams or mL 1 2 3 KK- KK- KK- 4 5 6 300SS 400 1000 EMP EMP EMP Ingredient (200 g) (300 g) (750 g) (200 g) (300 g) (750 g) NDC Lot Estradiol, USP 0.1 0.15 0.375 0.1 0.15 0.375 0869 614901/B (Micronized) Estriol USP 0.4 0.6 1.5 0.4 0.6 1.5 0732 615107/B (Micronized) Propylene 1 1.5 3.75 1 1.5 3.75 0510 605764/C Glycol VersaPro 198.5 297.75 744.375 198.5 297.75 744.375 2529 611448 Cream Base

(364) The superimposed revolution and rotation movement parameters in the planetary mixer (samples 1-3) and the EMP parameters (samples 4-6) were the same as in Example 12.

(365) Each of the resulting composition was then separated and analyzed as in Example 12. The results are shown in the following Tables:

(366) TABLE-US-00067 TABLE 42 Results for a composition including 2 API dispersed in KK-300SS Layer (top, middle, Estriol Estradiol Formulation # Sample # bottom) (w/w) (w/w) 19 55 Top 0.181 0.055 56 Middle 0.179 0.055 57 Bottom 0.183 0.054 20 58 Top 0.211 0.046 59 Middle 0.204 0.044 60 Bottom 0.208 0.045 21 61 Top 0.199 0.048 62 Middle 0.198 0.047 63 Bottom 0.196 0.047

(367) TABLE-US-00068 TABLE 43 Results for a composition including 2 API dispersed in Mazerustar KK-400W Layer (top, middle, Estriol Estradiol Formulation # Sample # bottom) (w/w) (w/w) 22 64 Top 0.195 0.049 65 Middle 0.194 0.048 66 Bottom 0.194 0.049 23 67 Top 0.201 0.048 68 Middle 0.201 0.048 69 Bottom 0.201 0.048 24 70 Top 0.18 0.05 71 Middle 0.181 0.051 72 Bottom 0.181 0.05

(368) TABLE-US-00069 TABLE 44 Results for a composition including 2 API dispersed in Mazerustar KK-1000W Layer (top, middle, Estriol Estradiol Formulation # Sample # bottom) (w/w) (w/w) 25 73 Top 0.201 0.05 74 Middle 0.203 0.051 75 Bottom 0.202 0.05 26 76 Top 0.198 0.037 77 Middle 0.198 0.037 78 Bottom 0.197 0.037 27 79 Top 0.203 0.051 80 Middle 0.201 0.051 81 Bottom 0.201 0.051

(369) TABLE-US-00070 TABLE 45 Results for a composition including 2 API dispersed in EMP 200 mL Jar Layer (top, middle, Estriol Estradiol Formulation # Sample # bottom) (w/w) (w/w) 28 82 Top 0.236 0.058 83 Middle 0.19 0.047 84 Bottom 0.169 0.041 29 85 Top 0.247 0.064 86 Middle 0.164 0.043 87 Bottom 0.132 0.034 30 88 Top 0.303 0.07 89 Middle 0.179 0.041 90 Bottom 0.141 0.033

(370) TABLE-US-00071 TABLE 46 Results for a composition including 2 API dispersed in EMP 300 mL Jar Layer (top, middle, Estriol Estradiol Formulation # Sample # bottom) (w/w) (w/w) 31 91 Top 0.213 0.055 92 Middle 0.207 0.053 93 Bottom 0.177 0.045 32 94 Top 0.207 0.053 95 Middle 0.168 0.043 96 Bottom 0.17 0.044 33 97 Top 0.204 0.056 98 Middle 0.203 0.055 99 Bottom 0.193 0.053

(371) TABLE-US-00072 TABLE 47 Results for a composition including 2 API dispersed in EMP 1 L Jar Layer (top, middle, Estriol Estradiol Formulation # Sample # bottom) (w/w) (w/w) 34 100 Top 0.183 0.044 101 Middle 0.184 0.044 102 Bottom 0.178 0.043 35 103 Top 0.15 0.038 104 Middle 0.16 0.041 105 Bottom 0.16 0.041 36 106 Top 0.183 0.043 107 Middle 0.166 0.039 108 Bottom 0.174 0.041

(372) TABLE-US-00073 TABLE 48 % RSD Results for the compositions of Tables 42 to 47 Estriol Estradiol Formulation % RSD 19 1.1% 1.1% 20 1.7% 2.2% 21 0.8% 0.0% 22 0.3% 1.2% 23 0.0% 0.0% 24 0.3% 1.1% 25 0.5% 1.1% 26 0.3% 0.0% 27 0.6% 0.0% 28 17.3% 17.7% 29 32.8% 32.8% 30 40.8% 40.6% 31 9.7% 10.4% 32 12.1% 11.8% 33 3.0% 2.8% 34 1.8% 1.3% 35 3.7% 4.3% 36 4.9% 4.9%

(373) Other examples of implementations will become apparent to the reader in view of the teachings of the present description and as such, will not be further described here.

(374) Note that titles or subtitles may be used throughout the present disclosure for convenience of a reader, but in no way these should limit the scope of the invention. Moreover, certain theories may be proposed and disclosed herein; however, in no way they, whether they are right or wrong, should limit the scope of the invention so long as the invention is practiced according to the present disclosure without regard for any particular theory or scheme of action.

(375) All references cited throughout the specification are hereby incorporated by reference in their entirety for all purposes.

(376) It will be understood by those of skill in the art that throughout the present specification, the term “a” used before a term encompasses embodiments containing one or more to what the term refers. It will also be understood by those of skill in the art that throughout the present specification, the term “comprising”, which is synonymous with “including,” “containing,” or “characterized by,” is inclusive or open-ended and does not exclude additional, un-recited elements or method steps.

(377) Unless otherwise defined, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure pertains. In the case of conflict, the present document, including definitions will control.

(378) As used in the present disclosure, the terms “around”, “about” or “approximately” shall generally mean within the error margin generally accepted in the art. Hence, numerical quantities given herein generally include such error margin such that the terms “around”, “about” or “approximately” can be inferred if not expressly stated.

(379) In the present disclosure, each of the variously stated ranges is intended to be continuous so as to include each numerical parameter between the stated minimum and maximum value of each range. For Example, a range of about 1 to about 4 includes: about 1, 1, about 2, 2, about 3, 3, about 4, and 4.

(380) Although various embodiments of the disclosure have been described and illustrated, it will be apparent to those skilled in the art in light of the present description that numerous modifications and variations can be made. The scope of the invention is defined more particularly in the appended claims.

Claims

1. A method, comprising: subjecting a container, that includes an edible material in a solid state therein, to superimposed revolution and rotation movements in a bladeless planetary mixer, wherein the superimposed revolution and rotation movements are sufficient to raise the temperature of the edible material to between 55° C. and 72° C. to melt the edible material without adding external heat to obtain a pourable edible material, wherein the edible material includes gelatin and can be reversibly melted; and cooling the pourable edible material to obtain a solid edible composition.
 2. The method of claim 1, wherein the superimposed revolution and rotation movements are configured to cause an elevation in temperature of the edible material by at least 25 degrees Celsius and not more than 35 degrees Celsius.
 3. The method of claim 1, wherein the superimposed revolution and rotation movements are configured to cause the elevation in temperature of the edible material by at least 35 degrees Celsius and not more than 40 degrees Celsius.
 4. The method of claim 1, wherein the superimposed revolution and rotation movement are configured to cause the elevation in temperature of the edible material by at least 40 degrees Celsius and not more than 48 degrees Celsius.
 5. The method of claim 1, further comprising adding an active pharmaceutical ingredient (API) to the container containing the edible material in the solid state prior to subjecting the container to the superimposed revolution and rotation movements in the bladeless planetary mixer.
 6. The method of claim 1, wherein the superimposed revolution and rotation movements are first superimposed revolution and rotation movements, the method further comprising adding an active pharmaceutical ingredient (API) to the container containing the melted edible material and subjecting the container to second superimposed revolution and rotation movements to mix the API with the pourable edible material before cooling the edible material to obtain the solid edible composition.
 7. The method of claim 1, wherein cooling the edible pourable material includes cooling in a mold having a desired shape.
 8. The method of claim 1, wherein the superimposed revolution and rotation movements are maintained for a period of time of at least 180 seconds.
 9. The method of claim 1, wherein the superimposed revolution and rotation movements are maintained for a period of time of at least 300 seconds.
 10. The method of claim 1, wherein the superimposed revolution and rotation movements generate a G force on the edible material of at least 180 G.
 11. The method of claim 1, wherein the superimposed revolution and rotation movements generate a G force on the edible material of at least 200 G.
 12. The method of claim 1, wherein the superimposed revolution and rotation movements generate a G force on the edible material of at least 250 G.
 13. The method of claim 5, wherein the API includes a dietary supplement.
 14. The method of claim 5, wherein the API includes a nutritional agent.
 15. A method, comprising: subjecting a container, that includes an edible material in a solid state therein, to first superimposed revolution and rotation movements in a bladeless planetary mixer, wherein the superimposed revolution and rotation movements are sufficient to melt the edible material without the addition of external heat to obtain a pourable edible material, wherein the edible material includes gelatin and can be reversibly melted, and wherein the superimposed revolution and rotation movements are configured to cause an elevation in temperature of the edible material by at least 31 degrees Celsius and not more than 48 degrees Celsius; and cooling the edible pourable material to obtain a solid edible composition.
 16. The method of claim 15, wherein the superimposed revolution and rotation movements are first superimposed revolution and rotation movements, the method further comprising adding an active pharmaceutical ingredient (API) to the container containing the melted edible material and subjecting the container to second superimposed revolution and rotation movements to mix the API with the pourable edible material, before cooling the edible material to obtain the solid edible composition.
 17. The method of claim 15, wherein the superimposed revolution and rotation movements are maintained for a period of time of at least 180 seconds.
 18. A method, comprising: subjecting a container, that includes an edible material in a solid state therein, to superimposed revolution and rotation movements in a bladeless planetary mixer, wherein the edible material includes gelatin and can be reversibly melted, wherein the superimposed revolution and rotation movements are sufficient to raise the temperature of the edible material to between 55° C. and 72° C. to melt the edible material without the addition of external heat to obtain a pourable edible material, and wherein the superimposed revolution and rotation movements are maintained for a period of time of at least 180 seconds; and cooling the edible pourable material to obtain a solid, semi-solid or chewable edible composition.
 19. The method of claim 18, wherein the superimposed revolution and rotation movements are first superimposed revolution and rotation movements, the method further comprising adding an active pharmaceutical ingredient (API) to the container containing the melted edible material and subjecting the container to second superimposed revolution and rotation movements to mix the API with the pourable edible material.
-