

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398882
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Chen; Wei-Long

Torch head of blowtorch

Abstract

A torch head includes a head body portion and a nozzle system inserted into the head body portion. The nozzle system includes a suction seat, an inner tube, and an outer tube. The suction seat includes a first outer channel extending longitudinally and at least one side channel extending radially. The first outer channel and the at least one side channel are not connected with each other. The inner and the outer tubes are connected to the second end of the suction seat. The outer tube circumferentially surrounds the inner tube. The first outer channel is opened to and communicated with the outer tube. The at least one side channel is opened to and communicated with the inner tube. The inner tube has an end opened to and communicated with the outer tube.

Inventors:	Chen; Wei-Long (Taichung, TW)
Applicant:	Pro-Iroda Industries, Inc. (Taichung, TW)
Family ID:	1000008781679
Assignee:	PRO-IRODA INDUSTRIES, INC. (Taichung, TW)
Appl. No.:	17/993099
Filed:	November 23, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230280029 A1	Sep. 07, 2023

Foreign Application Priority Data

TW	111107607	Mar. 02, 2022
----	-----------	---------------

Publication Classification

Int. Cl.: F23D14/38 (20060101); F23D14/02 (20060101)

U.S. Cl.:

CPC F23D14/38 (20130101); F23D14/02 (20130101);

Field of Classification Search

CPC: F23D (14/02); F23D (14/38)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2269831	12/1941	Senner	431/238	A01G 13/06
2552492	12/1950	Nathan	432/223	F23R 3/12
2720257	12/1954	Roberts	431/353	F23D 14/38
3774622	12/1972	Steigerwald	131/193	A24C 1/00
4990060	12/1990	Cheng-Chung	417/87	F04D 25/16
10161629	12/2017	Yang	N/A	N/A
2005/0112518	12/2004	Watanabe	431/153	F23D 14/28
2015/0354813	12/2014	Yang	431/364	F23D 14/28

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
108361694	12/2017	CN	N/A
2010249449	12/2009	JP	N/A
I537528	12/2015	TW	N/A

Primary Examiner: Hoang; Michael G

Assistant Examiner: Jones; Logan P

Attorney, Agent or Firm: MUNCY, GEISSLER, OLDS & LOWE, P.C.

Background/Summary

BACKGROUND OF THE INVENTION

1. Field of the Invention

(1) The present invention relates to a blowtorch and, particularly, to a torch head of the blowtorch.

2. Description of the Related Art

(2) TW Patent No. 1537528 discloses a head of a blowtorch including a replaceable barrel. The head includes a body and a barrel. One end of the body is recessed along an axial direction to form a receiving space. The barrel is releasably connected to the body along the axial direction. The barrel includes a pipe and a limit ring. The pipe extends along the axial direction and has two opposite ends, a receiving seat at one end and a discharge head at another end. When the barrel is connected to the body, the receiving seat is located in the receiving space, the limit ring is sleeved on the outer periphery of the pipe, the limit ring has two opposite ends and includes a connecting portion at one end and an abutting portion at another end, the connecting portion is connected to the

main body, and the abutting portion abuts against a side of the receiving seat opposite the body. The body includes a switch valve selectively opened and closed. When the gas switch valve is opened, gas can enter the barrel from the body. When the gas switch valve is closed, the body no longer outputs gas, but gas remained in the barrel may flow backward or the flame will flash back, resulting in a gas explosion in the barrel or the body.

(3) The present invention is, therefore, intended to obviate or at least alleviate the problems encountered in the prior art.

SUMMARY OF THE INVENTION

(4) According to the present invention, a torch head of a blowtorch includes a head body portion and a nozzle system. The nozzle system has a rear end and a front end opposite the rear end. The rear end is inserted into the head body portion and the front end protrudes out of the head body portion respectively. The nozzle system includes a suction seat, an inner tube, and an outer tube. The suction seat includes a first outer channel extending along a longitudinal direction of the nozzle system from a first end adjacent to the rear end to a second end adjacent to the front end. The suction seat includes at least one side channel extending from an outer periphery thereof along a radial direction of the nozzle system. The at least one side channel is not opened to and communicated with the first outer channel. The inner and the outer tubes are connected to the second end of the suction seat which is adjacent to the front end. The outer tube is disposed circumferentially around the inner tube. The inner tube is hollow and defines an inner channel. The outer tube is hollow and defines a second outer channel. The first outer channel is opened to and communicated with the second outer channel. The inner channel has a first end adjacent to the suction seat opened to and communicated with the at least one side channel. The inner channel has a second end opposite the first end opened to and communicated with the second outer channel. The first and the second outer channels are passages for mixtures of air and fuel. When the torch head produces a flame, the mixtures of air and fuel in the second outer channel are ignited, and so a negative pressure condition is created in the nozzle system, which cause air outside the torch head to be able to be sucked into the at least one side channel. The air sucked is able to be delivered to the second outer channel through the inner channel, thereby improving combustion efficiency and heating temperatures, preventing the mixtures of the air and fuel in the second outer channel from flowing in reverse direction toward the rear end, and inhibiting the flame from burning backward to the rear end, and preventing a gas explosion in the torch head.

(5) There has thus been outlined, rather broadly, the more important features of the invention in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the invention that will be described hereinafter and which will form the subject matter of the claims appended hereto.

(6) In this respect, before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and to the arrangements of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments and of being practiced and carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein are for the purpose of description and should not be regarded as limiting.

(7) As such, those skilled in the art will appreciate that the conception, upon which this disclosure is based, may readily be utilized as a basis for the designing other structures, methods and systems for carrying out the several purposes of the present invention. It is important, therefore, that the claims be regarded as including such equivalent constructions insofar as they do not depart from the spirit and scope of the present invention.

(8) Further, the purpose of the abstract is to enable the public generally, and especially scientists, engineers and practitioners in the art who are not familiar with patent or legal terms or phraseology, to determine quickly from a cursory inspection the nature and essence of the technical disclosure.

The abstract is neither intended to define the invention, which is measured by the claims, nor is it intended to be limiting as to the scope of the invention in any way.

(9) Other objectives, advantages, and new features of the present invention will become apparent from the following detailed description of the invention when considered in conjunction with the accompanied drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a perspective view of a torch head of a blowtorch in accordance with the present invention.

(2) FIG. 2 is an exploded perspective view of the torch head of FIG. 1.

(3) FIG. 3 is a cross-sectional view of the torch head of FIG. 1.

(4) FIG. 4 is a partial enlarged view of FIG. 3 illustrating the use of the torch head of FIG. 1.

(5) FIG. 5 is another cross-sectional view of the torch head of FIG. 1.

(6) FIG. 6 is a partial enlarged view of FIG. 5 illustrating the use of the torch head of FIG. 1.

DETAILED DESCRIPTION OF THE INVENTION

(7) Refer to FIGS. 1 through 6, a torch head **10** of a blowtorch in accordance with the present invention includes a head body portion **20** and a nozzle system **30** disposed in the head body portion **20**.

(8) The head body portion **20** includes a mixing seat **21** therein which includes a fuel channel **211** and a mixing air channel **212** extending radially to the fuel channel **211**. The fuel channel **211** is a passage for fuel. The mixing air channel **212** is a passage for air. The mixing air channel **212** is opened to and communicated with the fuel channel **211**, so that fuel and air are mixed, thereby improving the combustion effect of the fuel.

(9) The nozzle system **30** is provided with a rear end **31** and a front end **32** opposite the rear end **31**. The rear end **31** is inserted into the head body portion **20** and the front end **32** protrudes out of the head body portion **20** respectively. The nozzle system **30** includes a suction seat **33**, an inner tube **34**, and an outer tube **35**. The suction seat **33** includes a first outer channel **331** extending along a longitudinal direction of the nozzle system **30** from a first end adjacent to the rear end **31** to a second end adjacent to the front end **32**. The first outer channel **331** is a passage for mixtures of air and fuel. The suction seat **33** also includes at least one side channel, i.e. a first side channel **332** and a second side channel **333**, extending from an outer periphery thereof along a radial direction of the nozzle system **30**. The first and the second side channels **332** and **333** are not opened to and communicated with the first outer channel **331**. The first and the second side channels **332** and **333** are radially arranged. The inner and the outer tubes **34** and **35** are connected to the second end of the suction seat **33** which is adjacent to the front end **32**. The outer tube **35** circumferentially surrounds the inner tube **34**. The inner tube **34** is hollow and defines an inner channel **341**. The inner channel **341** has a first end adjacent to the suction seat **33** opened to and communicated with the first and the second side channels **332** and **333**. The inner channel has a second end opposite the first end opened to and communicated with the second outer channel **351**. The outer tube **35** is hollow and defines a second outer channel **351**. The second outer channel **351** is a passage for mixtures of air and fuel. The first outer channel **331** is opened to and communicated with the second outer channel **351**. The second outer channel has a first end connected to the second end of the suction seat **33** and a second end being open to outside of the torch head **10**.

(10) The nozzle system **30** further includes an extension tube **36** connected to the first end of the suction seat **33** and including a third outer channel **361** opened to and communicated with the first outer channel **331**. The third outer channel **361** is a passage for mixtures of air and fuel.

Specifically, the third outer channel **361** has widths smaller than widths of the first outer channel

331. The widths of the first and the third outer channels **331** and **361** are measured along the radial direction of the nozzle system **30**. Additionally, the widths of the third outer channel and **361** are greater than widths of the fuel channel **211**. The widths of the fuel channel **211** are measured along a radial direction of the mixing seat **21**.

(11) The nozzle system **30** further includes a connecting seat **37** interconnecting the mixing seat **21** and the extension tube **36**. The connecting seat **37** includes a fourth outer channel **371** including a first end opened to and communicated with the fuel channel **211** and a second end opened to and communicated with the third outer channel **361**. The fourth outer channel **371** is a passage for mixtures of air and fuel. Specifically, the fourth outer channel **371** has widths greater than widths of the fuel channel **211**. The widths of the fourth outer channel **371** are measured along the radial direction of the nozzle system **30**. The widths of the fuel channel **211** are measured along the radial direction of the mixing seat **21**.

(12) The nozzle **30** further includes a cover tube **38** including a first end connected to the connecting seat **37** and a second end connected to a first end of the outer tube **35** which is opposite a second end of the outer tube **35** which is connected to the second end of the suction seat **33**. The cover tube **38** circumferentially surrounds the suction seat **33**, the outer tube **35** and the extension tube **36**. The cover tube **38** does not contact the suction seat **33** or the extension tube **36**.

(13) Further, an ignition system **39** is disposed in the head body portion **20** and protrudes into the second outer channel **351**.

(14) In view of the foregoing, when the torch head **10** produces a flame, the mixtures of air and fuel in the second outer channel **351** are ignited, and so a negative pressure condition is created in the nozzle system **30**, which cause air outside the torch head **10** to be able to be sucked into the at last one side channel **332**. The air sucked is able to be delivered to the second outer channel **351** through the inner channel **341**, thereby improving combustion efficiency and heating temperatures, preventing the mixtures of the air and fuel in the second outer channel **351** from flowing in reverse direction toward the rear end **31**, and inhibiting the flame from burning backward to the rear end **31**, and preventing a gas explosion in the torch head **10**.

(15) The foregoing is merely illustrative of the principles of this invention and various modifications can be made by those skilled in the art without departing from the scope and spirit of the invention.

Claims

1. A torch head of a blowtorch comprising: a head body portion; a nozzle system, wherein the nozzle system has a rear end and a front end opposite the rear end, wherein the rear end is inserted into the head body portion and the front end protrudes out of the head body portion respectively, wherein the nozzle system includes a suction seat, an inner tube, and an outer tube, wherein the suction seat includes a first outer channel extending along a longitudinal direction of the nozzle system from a first end adjacent to the rear end to a second end adjacent to the front end, wherein the suction seat includes at least one side channel extending from an outer periphery thereof along a radial direction of the nozzle system, wherein the at least one side channel is not opened to and communicated with the first outer channel, wherein the inner and the outer tubes are connected to the second end of the suction seat which is adjacent to the front end, wherein the outer tube circumferentially surrounds the inner tube, wherein the inner tube is hollow and defines an inner channel, wherein the outer tube is hollow and defines a second outer channel, wherein the first outer channel is opened to and communicated with the second outer channel, wherein the inner channel has a first end adjacent to the suction seat opened to and communicated with the at least one side channel, and wherein the inner channel has a second end opposite the first end opened to and communicated with the second outer channel, wherein the first and the second outer channels are passages for mixtures of air and fuel, wherein when the torch head produces a flame, the

mixtures of air and fuel in the second outer channel are ignited, and so a negative pressure condition is created in the nozzle system, which cause air outside the torch head to be able to be sucked into the at last one side channel, and wherein the air sucked is able to be delivered to the second outer channel through the inner channel, thereby improving combustion efficiency and heating temperatures, preventing the mixtures of the air and fuel in the second outer channel from flowing in reverse direction toward the rear end, and inhibiting the flame from burning backward to the rear end, and preventing a gas explosion in the torch head; and an ignition system disposed in the head body portion protrudes into the second outer channel.

2. The torch head as claimed in claim 1, wherein the head body portion includes a mixing seat therein which includes a fuel channel and a mixing air channel extending radially to the fuel channel, and wherein the mixing air channel is opened to and communicated with the fuel channel.

3. The torch head as claimed in claim 2, wherein the nozzle system includes an extension tube connected to the first end of the suction seat and including a third outer channel opened to and communicated with the first outer channel.

4. The torch head as claimed in claim 3, wherein the nozzle system includes a connecting seat interconnecting the mixing seat and the extension tube, and wherein the connecting seat includes a fourth outer channel including a first end opened to and communicated with the fuel channel and a second end opened to and communicated with the third outer channel.

5. The torch head as claimed in claim 4, wherein the nozzle system includes a cover tube including a first end connected to the connecting seat and a second end connected to a first end of the outer tube which is opposite a second end of the outer tube which is connected to the second end of the suction seat, wherein the cover tube circumferentially surrounds the suction seat, the outer tube and the extension tube, and wherein the cover tube does not contact the suction seat or the extension tube.

6. The torch head as claimed in claim 1, wherein the at least one side channel includes a first side channel and a second side channel extending from the outer periphery thereof along the radial direction of the nozzle system, and wherein the first and the second side channels are radially arranged.

7. The torch head as claimed in claim 4, wherein the third and the fourth outer channels have widths greater than widths of the fuel channel, wherein the widths of the third and the fourth outer channels are measured along the radial direction of the nozzle system, and wherein widths of the fuel channel are measured along a radial direction of the mixing seat.

8. The torch head as claimed in claim 7, wherein the widths of the third outer channel are smaller than widths of the first outer channel, and wherein the widths of the first and the third outer channels are measured along the radial direction of the nozzle system.

9. The torch head as claimed in claim 1, wherein the second outer channel has a first end connected to the second end of the suction seat and a second end being open to outside of the torch head.

10. The torch head as claimed in claim 5, wherein the at least one side channel includes a first side channel and a second side channel extending from the outer periphery thereof along the radial direction of the nozzle system, and wherein the first and the second side channels are radially arranged.

11. The torch head as claimed in claim 5, wherein the second outer channel has a first end connected to the second end of the suction seat and a second end being open to outside of the torch head.

12. The torch head as claimed in claim 11, wherein the at least one side channel includes a first side channel and a second side channel extending from the outer periphery thereof along the radial direction of the nozzle system, and wherein the first and the second side channels are radially arranged.
