

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398945
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Schneider; Mark et al.

Refrigerator

Abstract

A refrigerator has an appliance body on which at least two doors arranged one above the other are pivotably mounted. The doors are mounted via a double hinge which is fixed to the appliance body with a mounting plate which is connected via a plurality of movable joint levers to an upper hinge part connected to the upper door and to a lower hinge part connected to the lower door via a plurality of further movable joint levers. The upper door is further pivotably mounted on the appliance body via a support hinge which is fixed to the appliance body by a mounting element that is connected to a plurality of joint levers connected to a further hinge part connected to the upper door. The joint levers of the support hinge have a greater vertical extent in the vertical direction than the joint levers of the double hinge.

Inventors:	Schneider; Mark (Porta Westfalica, DE), Tofall; Ralf (Bueckeburg, DE)
Applicant:	Hettich-ONI GmbH & Co. KG (Vlotho, DE)
Family ID:	1000008781722
Assignee:	Hettich-ONI GmbH & Co. KG (Vlotho, DE)
Appl. No.:	18/029152
Filed (or PCT Filed):	September 06, 2021
PCT No.:	PCT/EP2021/074492
PCT Pub. No.:	WO2022/069159
PCT Pub. Date:	April 07, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230366610 A1	Nov. 16, 2023

Foreign Application Priority Data

DE

10 2020 125 600.0

Sep. 30, 2020

Publication Classification

Int. Cl.: F25D23/02 (20060101); F25D23/06 (20060101)

U.S. Cl.:

CPC F25D23/028 (20130101); F25D23/063 (20130101);

Field of Classification Search

CPC: F25D (23/028); F25D (23/063); F25D (2323/024); E05Y (2900/31)

USPC: 312/405

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4084291	12/1977	Crowe	49/382	E05D 3/04
5158503	12/1991	Mitchell	16/302	E05D 3/12
2010/0244646	12/2009	Laible	312/405	F25D 23/10
2012/0080991	12/2011	Wilson	312/405	F25D 23/028
2022/0018591	12/2021	Kikuchi	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
10 2010 027 922	12/2010	DE	N/A
2 754 982	12/2013	EP	N/A
2017/089340	12/2016	WO	N/A
WO 2018075094	12/2017	WO	E05D 3/18
2019/117236	12/2018	WO	N/A
2020/116833	12/2019	WO	N/A

OTHER PUBLICATIONS

International Search Report in PCT/EP2021/074492, mailed Jan. 5, 2022. cited by applicant
German Search Report dated Feb. 23, 2021 in German Application No. 10 2020 125 600.0 with English translation of relevant parts. cited by applicant

Primary Examiner: Hansen; James O

Attorney, Agent or Firm: Collard & Roe, P.C.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is the National Stage of PCT/EP2021/074492 filed on Sep. 6, 2021, which claims priority under 35 U.S.C. § 119 of German Application No. 10 2020 125 600.0 filed on Sep. 30, 2020, the disclosure of which is incorporated by reference. The international application under PCT article 21(2) was not published in English.

BACKGROUND OF THE INVENTION

1. Field of the Invention

(2) The present invention relates to a refrigerator having an appliance body on which at least two doors arranged one above the other are pivotably mounted, which doors open or close an interior space of the appliance body, the doors being connected to the appliance body in the closed position via at least one seal, the two doors being pivotably mounted via a double hinge which is fixed to the appliance body with a mounting plate, which is connected via a plurality of movable joint levers to an upper hinge part connected to the upper door and via a plurality of further movable joint levers to a lower hinge part connected to the lower door, and the upper door is pivotably mounted on the appliance body via a support hinge which is fixed to the appliance body by a mounting element which is connected via a plurality of joint levers to an upper hinge part connected to the upper door.

2. The Prior Art

(3) EP 2 754 982 A1 discloses a refrigerator in which two doors arranged one above the other are pivotably mounted on a body. The middle hinge between the doors is designed as a double hinge, which has only one mounting element that is fixed to the body, but two movable hinge parts, so that the upper hinge part holds the upper door and the lower hinge part holds the lower door. The disadvantage of this refrigerator is that the use of the double hinge means that the gap between the upper door and the lower door is comparatively large. The relatively large volume of the double hinge leads to disadvantages with regard to the insulation of the refrigerator and also to poor utilisation of the installation space.

(4) WO 2019/117236 A1 shows a refrigerator in which two doors are held pivotably by a double hinge. Here, too, the large vertical extension of the double hinge leads to a loss of storage space and increases the cost of insulation.

SUMMARY OF THE INVENTION

(5) It is therefore an object of the present invention to provide a refrigerator in which two doors are pivotably mounted on an appliance body in an improved manner.

(6) This object is achieved with a refrigerator having the features of claim 1.

(7) The refrigerator according to the invention comprises at least two doors arranged one above the other which open or close an interior space of the appliance body. The two doors are pivotably mounted by means of a double hinge which is fixed to the appliance body with a mounting plate which is connected to an upper hinge part connected to the upper door with a plurality of movable joint levers and to a lower hinge part connected to the lower door with a plurality of further movable joint levers. Thus, a pivotable mounting of both doors can be achieved via the fixing of the mounting plate. The term “mounting plate” does not require a plate-shaped design, and it is sufficient if the mounting plate has a plate-shaped section.

(8) The upper door is further pivotably mounted on the appliance body via a support hinge which is fixed to the appliance body with a mounting element which is connected to an upper hinge part connected to the upper door with several joint levers. According to the invention, the joint levers of the support hinge are formed in a vertical direction with a greater extension in height than the joint levers of the double hinge. As a result, higher weight loads can be absorbed via the support hinge

than via the hinge part of the double hinge coupled to the support hinge, which serves to guide the upper door in the lower area, but can be very compact due to the rather thin design of the joint levers in the vertical direction. As a result, the double hinge with the narrow joint levers requires less installation space and enables improved insulation of the appliance body, as only a smaller area of the installation space is occupied by the double hinge.

(9) A joint lever of the double hinge or the support hinge is an elongated component that is articulated via at least two axes. Each joint lever can be a single piece or composed of several parts. The distance between two end rotary axes determines the lever length of the joint lever.

(10) Preferably, the support hinge absorbs more weight forces of the upper door than the hinge part of the double hinge coupled to the support hinge. The support hinge can be more stable and thus has less deflection under a weight load, so that also doors with a high weight are held securely. Due to the support of the support hinge, the hinge part of the double hinge coupled to the support hinge is loaded with weight forces to a lesser extent, preferably the weight forces acting in the vertical direction on the hinge part of the double hinge are less than half of the weight forces acting on the support hinge. This allows the upper door to support significant weights, for example between 20 kg to 80 kg door weight.

(11) In a preferred embodiment, the joint levers of the double hinge and the joint levers of the support hinge have the same axes of rotation and the same lever lengths. The axes of rotation are imaginary vertical lines that extend through the centre of rotation of each joint lever. By providing the same pivot axes and the same lever lengths on the support hinge and the double hinge, the top door remains vertically aligned when pivoted and is moved substantially only horizontally. Alternatively, the pivot axes and/or the lever lengths may be different to modify the swing path of the door.

(12) The joint levers of the double hinge are preferably at least partially plate-shaped, whereby at least the outer joint levers of the support hinge, preferably all joint levers, are designed as levers with a U-shaped cross-section. In this case, the levers of the support hinge can be manufactured in one piece by sheets bent into a U-shape. The joint levers of the support hinge thus have a high degree of rigidity.

(13) The support hinge can, for example, comprise four joint levers and be formed as a seven-joint hinge. Each joint lever can be bent in a U-shape so that in a closed position the joint levers at least partially overlap each other. The support hinge can be box-shaped in the closed position, while in the maximum open position the joint levers are arranged in an extended position relative to each other and thus the upper door is held with a gap in front of the appliance body.

(14) Preferably, the support hinge has a greater extension in the vertical direction than the entire double hinge. Optionally, further functions can be integrated into the support hinge, for example, a spring element can be provided to pretension the upper door in the closing direction. Optionally, a damping device can also be provided to slow down a closing movement of the support hinge before it reaches the closed position. The damping device can be provided in or on the support hinge. However, it is also possible that the damping device is arranged at another position. In addition, a damping device may also be provided in the area of the double hinge. The damping device or devices comprise a linear damper with a piston or a rotational damper.

(15) The joint levers of the double hinge are at least partially formed from two plates that lie on top of each other in certain areas. This allows the individual joint levers to have a particularly flat structure, whereby the joint levers preferably do not lie against each other over the entire surface but have a step, which increases the rigidity of the joint lever. The thickness of the joint levers of the double hinge in the vertical direction is preferably less than 10 mm, in particular less than 8 mm, for example between 2 mm and 7 mm. Of course, the individual joint levers can have different thicknesses. A hollow space can be formed between the two plates of a joint lever, into which another joint lever projects at least in a folded position.

(16) The support hinge preferably comprises a support lever hinged to the mounting element,

which is one of the joint levers and has the greatest extension in the vertical direction. This support lever is preferably at least twice as thick as a lever of the double hinge which is hinged to the mounting plate and has the greatest extension in the vertical direction of the joint levers of the double hinge. When a seven-bar hinge is formed, two joint levers are usually pivotably connected to the mounting element or the mounting plate, so that the thicker joint lever of the support hinge is compared with the thicker joint lever of the double hinge in each case.

(17) The support hinge is preferably formed as a seven-joint hinge comprising four joint levers which provide positive guidance of the hinge part relative to the mounting plate when the upper door is pivoted. Similarly, the joint levers on the double hinge are designed as a seven-joint hinge, each joint mechanism being composed of four joint levers connecting the hinge part to the mounting element. Alternatively, other types of hinges can be used for the support hinge or the double hinge, for example four-joint hinges.

(18) To prevent engagement with the support hinge or the double hinge, covers can be provided on the top and bottom of the support hinge and the double hinge respectively to cover gaps between the joint levers. The covers can be made of a thin material, for example foil, or a thin plate, which swivel together with the joint levers.

(19) In a preferred embodiment, the lower door of the refrigerator is connected to the appliance body in the upper area via the double hinge and in the lower area via a further support hinge. This further support hinge can be of identical construction to the support hinge with which the upper door is pivotably mounted on the appliance body. The refrigerator can comprise two doors or several doors that close off an interior space.

(20) Preferably, at least one joint lever of the double hinge has a recess in which a spring is inserted by means of which a hinge part of the double hinge can be pretensioned in the closing direction. This makes it possible to support a closing movement and hold a door in the closed position with a compact design. The spring can act on a pivotable lever or a pusher which can be moved along a curve guide so that the spring does not act on the door in the closing direction over the entire pivoting range, but only in a predetermined opening range of the door by means of a tightening force.

(21) To increase stability, an axis holder for the common axes is preferably arranged on the mounting element between the joint levers for the upper door and the joint levers for the lower door. The axis holder can be plate-shaped and extend parallel to the two outer walls of the mounting element. Preferably, the joint levers for the upper door and the joint levers for the lower door are held pivotably on the mounting element and the axis holder via a common axis pin. The axis holder also allows the lower joint mechanism with the lower hinge part to be omitted from the double hinge. This allows refrigerator designs to be provided with hinges where there are only upper doors and instead of the lower doors there are, for example, drawers, i.e. no lower door.

(22) To avoid loud impact noises, the upper door and the lower door are each braked by a damping device during a closing process, whereby the damping device can comprise a linear damper with a displaceable piston or a rotary damper, for example a damper housing filled with fluid.

(23) Preferably, the appliance body of the refrigerator is integrated in a piece of furniture with side walls, whereby the side walls of the piece of furniture protrude over the appliance body and cover at least a part of the lateral end faces of the doors from the side. This allows the unit of furniture and appliance body to be arranged in a visually appealing way. At least one door on the side facing the interior space, in addition to insulation, may also comprise compartments and/or holding means for storing objects. The support hinge can allow an opening angle of at least 115° so that the interior space is almost completely accessible from a front side.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The invention is explained in more detail below by means of several embodiments with reference to the accompanying drawings. It is shown in:
- (2) FIGS. **1A** and **1B** Two views of a refrigerator according to the invention;
- (3) FIGS. **2A** and **2B** Two views of a modified refrigerator according to the invention;
- (4) FIGS. **3A** to **3C** Several views of the refrigerator of FIGS. **1** and **2** in the area of the front side of the doors;
- (5) FIGS. **4A** to **4C** Several views of a support hinge of the refrigerator;
- (6) FIG. **5** An exploded view of the support hinge of FIGS. **4A** to **4C**.
- (7) FIGS. **6A** to **6C** Multiple views of a double hinge of the refrigerator in the closed position;
- (8) FIGS. **7A** and **7B** Two views of the double hinge in different opening positions;
- (9) FIGS. **8A** and **8B** Two views of the double hinge with only one joint mechanism in one opening position;
- (10) FIG. **9** An exploded view of part of the double hinge of FIGS. **6A** to **6C**.
- (11) FIG. **10A** perspective view of a modified double hinge;
- (12) FIG. **11** An exploded view of part of the double hinge of FIG. **10**;
- (13) FIGS. **12A** to **12C** Several views of the double hinge of FIG. **10** in different positions, and
- (14) FIGS. **13A** to **13C** Several views of a further double hinge in different positions, and
- (15) FIGS. **14A** and **14B** Two views of a refrigerator integrated into a piece of furniture.

DETAILED DESCRIPTION OF THE EMBODIMENTS

- (16) A refrigerator **1** comprises an appliance body **2** in which an upper interior space **3** and a lower interior space **4** are provided, which are separated from each other by a floor **5**. The upper interior space **3** can be closed via an upper door **6**, while the lower interior space **4** can be closed via a lower door **7**. The doors **6** and **7** can comprise compartments and holding means for storing objects in addition to insulation on the side facing the interior spaces **3** and **4**. A seal **8** is also provided on each door **6** and **7** which, in the closed position, provides a seal against the interior spaces **3** or **4**.
- (17) The upper door **6** is pivotably held on the appliance body **2** via an upper support hinge **10** and an upper joint mechanism on a double hinge **20**. The lower door **7** is pivotably held on the upper side by a lower joint mechanism on the double hinge **20** and on the lower side by a further support hinge **10**.
- (18) FIGS. **2A** and **2B** show a modified refrigerator **1'** which comprises an appliance body **2'** on which two upper doors **6** and two lower doors **7** are pivotably mounted. The two upper doors **6** close an upper interior space **3'** in the appliance body **2'**, and the two lower doors **7** close a lower interior space **4'**. The interior spaces **3'** and **4'** are divided from each other by a floor **5'**. The doors **6** are each pivotably mounted at the top via a support hinge **10** and at the bottom via a double hinge **20**. The lower doors **7** are pivotably mounted at the top via the double hinge **20** and at the bottom via a further support hinge **10**.
- (19) The refrigerators **1** or **1'** can be set up as free-standing appliances, but can also be installed within a cabinet unit. In order to avoid a collision with side walls of a cabinet unit, the support hinges **10** and the double hinge **20** are designed in such a way that a hinge part on the doors **6** and **7** is removed from the appliance body **2** or **2'** during a pivoting movement.
- (20) FIGS. **3A** to **3C** show the area of the support hinges **10** and the double hinge in detail. Each support hinge **10** is fixed to the appliance body **2** or **2'** by a mounting element **11**. Via a joint mechanism, the mounting element **11** is connected to a hinge part **12** on which the door **6** is held.
- (21) The double hinge **20** comprises a mounting plate **21** which is fixed to the appliance body **2** or **2'**. The mounting plate **21** does not have to be formed plate-shaped, but can also have a different geometry. The mounting plate **21** is connected to an upper hinge part **30** via a joint mechanism and to a lower hinge part **40** via a further joint mechanism. The upper hinge part **30** is fixed to the door **6**, while the lower hinge part **40** is fixed to the door **7**.

(22) The double hinge **20** has a height h in the vertical direction that is smaller than the height H of a support hinge **10**. The double hinge **20** thus has a very compact design and ensures small gaps between the doors **6** and **7** as well as effective insulation.

(23) FIGS. **4A** to **4C** show one of the support hinges **10** in various positions. In the folded closed position shown in FIG. **4A**, the support hinge **10** is essentially box-shaped, with the hinge part **12** and the mounting element **11** arranged next to each other. When the support hinge **10** is moved in an opening direction, the hinge part **12** pivots in the opening direction via a joint mechanism, as shown in FIG. **4B**. The mounting element **11** is connected via two joint levers **13** and to two further joint levers **14** and **16**, which in turn are articulated to the hinge part **12**. In order to prevent engagement in the gaps between the joint levers **13**, **14**, **15** and **16**, a cover **17** is provided on the upper side and the lower side respectively, which covers gaps between the joint levers **13** to **16**. The support hinge **10** is designed as a seven-joint hinge and has four joint levers **13** to **16**, although other hinges, for example four-joint hinges, can also be used.

(24) FIG. **5** shows an exploded view of the support hinge. The joint levers **13**, **14**, **15** and **16** are manufactured as bent sheet steel parts and have a U-shaped cross-section. This achieves a high rigidity of the joint mechanism, as the two legs are connected to each other via an integrally formed base at each joint lever **13**, **14**, **15** and **16**.

(25) The first joint lever **13** is mounted on the mounting element **11** via an axis **A1** and has two further axes **A2** and **A5**. The third joint lever **15** is hingedly mounted on the mounting element **11** on the axis **A3**, on the protruding end of which an axis **A4** is formed which corresponds to the axis **A4** on the second joint lever **14**. The second joint lever **14** is connected to the first joint lever **13** by axis **A2**, and on the opposite side to the hinge part **12** via axis **A6**. The fourth joint lever **16** is connected to the first joint lever **13** by axis **A5** and to the hinge part **12** via axis **A7**. The hinge part **12** comprises a bracket and a bearing element which are connected to each other via axes **A6** and **A7**. This facilitates the assembly. Optionally, the hinge part **12** can be formed in one piece, for example as a U-shaped bent component.

(26) The axes **A1** to **A7** can be formed by pins which are inserted into the respective openings on the joint levers **13** to **16**.

(27) The two covers **17** are rotatably held on the first joint lever **13** by an axis **A17**. Each cover **17** comprises a slot **19** which surrounds an axis **A19** provided on the hinge part **12**. This allows the axis **A19** to be moved along the slot **19**.

(28) The support hinge **10** further comprises a height adjustment means, wherein the mounting element **11** is not directly fixed to the appliance body **2** or **2'**, but via a height adjustment element **18**. This allows the mounting element **11**, and thus the support hinge **10**, to be adjusted in height relative to the height adjustment element **18** in order to align with the appliance body **2** or **2'**.

(29) FIGS. **6A** to **6C** show the double hinge **20** in a closed position. The double hinge **20** is also box-shaped in the closed position. The two hinge parts **30** and **40** are arranged one above the other and next to the mounting plate **21**. The mounting plate **21** is formed as a U-shaped bent sheet metal part. The hinge part **30** is connected to the mounting plate **21** via an upper joint mechanism and the hinge part **40** via a lower joint mechanism.

(30) In FIGS. **7A** and **7B**, the double hinge **20** is shown in different opening positions, in which both hinge parts **30** and **40** are shown lying on top of each other and in FIG. **7A** in a maximum opening position. The hinge parts **30** and **40** are arranged at a distance from the mounting plate **21**, for example at a distance between 10 mm to 80 mm, in particular 20 mm to 50 mm.

(31) In FIG. **8A**, the lower hinge part **40** is in a closed position while the upper hinge part **30** is in the maximum open position. In FIG. **8B**, on the other hand, the upper hinge part **30** is arranged in a closed position, while the lower hinge part **40** is arranged pivoted in a maximum open position. The two hinge parts **30** and **40** can thus each be moved independently of each other via a joint mechanism and are held on the stationary mounting plate **21**.

(32) FIG. **9** shows the upper joint mechanism of the upper hinge part **30** of the double hinge **20**,

wherein the upper joint mechanism and the lower joint mechanism of the hinge part **40** are substantially identical in construction, for example mirror-inverted to a central horizontal plane.

(33) The mounting plate **21** is U-shaped and comprises a plate-shaped bottom which can be fixed to the appliance body **2** or **2'**. The bottom of the mounting plate **21** can also be fixed to the floor **5** or **5'** for dividing the interior spaces **3** and **4**.

(34) The joint mechanism comprises four joint levers **22**, **23**, **24** and **25**, by means of which the upper hinge part **30** is pivotably mounted. The first joint lever **22** is hingedly connected to the mounting plate **21** via an axis **A1** and comprises two further axes **A2** and **A5**. The third joint lever **24** is hingedly connected to the mounting plate **21** via an axis **A3** and is hingedly connected to the second joint lever **23** at the opposite end via an axis **A4**. The second joint lever **23** is hingedly connected to the first joint lever **22** via axis **A2** and is hingedly connected to the hinge part **30** via an axis **A6**. The axis **A4** is located between the axes **A2** and **A6**. The fourth joint lever **25** is hingedly connected to the first joint lever **22** via axis **A5** and at the opposite end is hingedly connected to the hinge part **30** via an axis **A7**. In the assembled position of the double hinge **20**, the axes **A1** to **A7** are mounted in the same way as the axes **A1** to **A7** on the support hinge **10**, only vertically offset.

(35) The double hinge **20** comprises covers **26** on the joint mechanism with the joint levers **22**, **23**, **24** and **25** on the upper side and the lower side, each cover **26** being hingedly fixed to an axis **A26** on the first joint lever **22**. The cover **26** comprises a slot **28** into which an axis **A28** on the hinge part is inserted, thus guiding the cover **26** during a pivoting movement of the double hinge **20**.

(36) The double hinge **20** further comprises a height adjustment means, wherein the mounting plate **21** is not directly fixed to the appliance body **2** or **2'**, but via a height adjustment element **27**. This allows the mounting plate **21** to be adjusted in height relative to the height adjustment element **27** to align with the appliance body **2** or **2'**.

(37) The joint levers **22**, **23**, **24** and **25** are relatively flat compared to the U-shaped joint levers **13**, **14**, **15** and **16** of the support hinge **10**. Preferably, the joint levers **22**, **23**, **24** and **25** are formed from two plates, in particular a steel plate, which rest on each other at least in some areas. For example, the joint lever **22** comprises two plates which lie on top of each other in areas and are spaced apart in other areas. The spaced areas can be arranged parallel to each other. This increases the bending stiffness despite the small thickness of the joint lever **22**. The joint lever **23** is also formed of two plates which rest on each other in some areas and on which a step is formed so that the plates are spaced apart in some areas. The joint levers **24** and **25** comprise two spaced plates, between which a spacer can optionally be provided. A height of the joint levers **22**, **23**, **24** and **25** in the vertical direction is preferably in a range smaller than 10 mm, in particular smaller than 8 mm. The height of the joint levers **22**, **23**, **24** and **25** can, for example, be between 2 mm and 7 mm.

(38) An axis holder **29** is arranged on the mounting element **21** between the upper joint levers for the upper door and the joint hinge levers for the lower door. The axis holder **29** is plate-shaped and extends parallel to the two outer walls of the mounting element **21**. Openings are provided in the axis holder **29** for the axes **A1** and **A3** to pass through, at which the first and third joint levers **22** and **24** can be pivoted.

(39) FIG. **10** shows a modified double hinge **20** which comprises a spring **50** on each joint mechanism to bias one of the doors **6** or **7** in the closing direction in a closing area. Each spring **50** can be effective, for example, in an opening area of the door **6** or **7** between the closed position and a pivoting of the hinge part **30** or **40** up to, for example, 30°, in order to bias the door **6** or **7** into the closed position only in this closing area.

(40) FIG. **11** shows the double hinge of FIG. **10** with an joint mechanism for the hinge part **30**. A guide lever **53** is fixed to the first joint lever **22** and forms a curve guide **54** at one end. A lever **52**, which is rotatably mounted about an axis **A52** on a modified fourth joint lever **25'**, rests against the curve guide **54**. A tension lever **51** is provided on the fourth joint lever **25'**, on which a spring **50** is received in a recess. In the assembled position, the spring **50** also lies in a recess of the fourth joint

lever 25'. The tensioning lever 51 is rotatably mounted about the axis A7 of the fourth joint lever 25', whereby the spring 50 can be compressed via the lever 52.

(41) FIG. 12A shows the double hinge with the spring 50 in the maximum opening position of the hinge part 30. The spring 50 is in the tensioned compressed position and the lever 52 pushes the spring 50 into the tension lever 51. A pin or other guide element may be provided in the tension lever 51 to prevent the spring 50 from moving. When the double hinge 30 is moved in the closing direction, as shown in FIG. 12B, the spring 50 remains in the cocked position and the lever 52 does not initially pivot relative to the cocking lever 51. In this pivoting range, the spring 50 is inoperative except for frictional forces, and the curve guide 54 pushes the lever 52 towards the spring 50, not assisting or braking the pivoting movement due to the constant length of the spring 50.

(42) When the double hinge with the hinge part 30 moves from the position shown in FIG. 12B to the closed position shown in FIG. 12C, an area of the curve guide 54 comes into contact with the lever 52, which allows the lever 52 to pivot so that the spring 50 can relax and pivot the lever 52. In the closed position, the spring 50, which is in the form of a compression spring, has a greater length than in the central open position shown in FIG. 12B, so that the closing action of the double hinge is assisted in the closing area.

(43) In FIGS. 10 to 12, the spring 50 is coupled to the pivoted lever 52. FIGS. 13A to 13C show a modified embodiment of a double hinge 20 in which a spring 50 is inserted into a recess of a joint lever 60 and acts on a movable slider 61. The spring 50 is again a compression spring and presses the pusher 61 against a cam 62 formed on the hinge part 30 or a component fixed to the hinge part 30.

(44) In the closed position of FIG. 13A, the pusher 61 is spaced from the joint lever 60, and when opening, the pusher 61 is moved towards the joint lever 60 by the cam 62 so that the spring 50 is compressed against the spring force. In this compressed and tensioned position, the spring 50 can be moved from the middle opening position according to FIG. 13B to a maximum opening position according to FIG. 13C without changing the length of the spring 50. The pusher 61 is moved along the curve guide 62.

(45) In an alternative embodiment, the curve guides 54 and 62 can also be formed differently so that the hinge part 30, 40 is pretensioned over the entire travel in the closing direction. It is also possible that the curve guides automatically move the hinge part 30, 40 into an open position from a predetermined opening angle.

(46) Only during a closing movement can the spring 50 in the opening area between FIGS. 13B and 13A relax again and thus bias the door 6 or 7 into the closed position.

(47) In addition to the spring element, a damper can also be provided on the support hinge 10 and/or the double hinge 20 to slow down a closing movement in order to avoid loud impact noises.

(48) FIGS. 14A and 14B show a refrigerator 1, 1' in a closed and open door position, in which the appliance body 2, 2' is integrated in a piece of furniture 70.

(49) The furniture has two side walls 71 which project beyond the appliance body 2, 2' at the front, so that the front of the doors 6 and 7 are flush with the narrow side of the side walls 71 in the closed position. In the closed position, the side face 9 of the doors 6 and 7 is thus concealed from a side view by the side walls 71. In the fully open door position, the narrow side of the side panel 71 and the lateral end face 9 of the doors 6, 7 are at an angle to each other. In FIGS. 14A and 14B, the refrigerator 1, 1' has two opposing doors 6 and 7. However, the refrigerator 1, 1' can also have only one door 6 and one door 7.

(50) Due to the arrangement with a support hinge 10 and a double hinge 20, high door weights can be realised so that the doors 6 and 7 can also have different or combined additional functions such as an ice cube area, a beverage flap, interior organisation or a touch screen.

(51) In addition to a damping device for the closing process of the door 6,7, an electronic opening aid can also be provided on the refrigerator 1, 1' to assist the operator in opening the door 6,7 or to

open the door 6,7 at least partially.

LIST OF REFERENCE SIGNS

(52) **1, 1'** Refrigerator **2, 2'** Appliance body **3, 3'** Interior space **4, 4'** Interior space **5, 5'** Floor **6** Door **7** Door **8** Seal **9** Front side **10** Support hinge **11** Mounting element **12** Hinge part **13** Joint lever **14** Joint lever **15** Joint lever **16** Joint lever **17** Cover **18** Height adjustment element **19** Slot **20** Double hinge **21** Mounting plate **22** Joint lever **23** Joint lever **24** Joint lever **25, 25'** Joint lever **26** Covering **27** Height adjustment element **28** Slot **29** Axis holder **30** Hinge part **40** Hinge part **50** Spring **51** Tensioning lever **52** Lever **53** Guide lever **54** Curve guide **60** Joint lever **61** Pusher **62** Curve guide **70** Furniture **71** Sidewall H Height H Height **A1** Axis **A2** Axis **A3** Axis **A4** Axis **A5** Axis **A6** Axis **A7** Axis **A17** Axis **A19** Axis **A26** Axis **A28** Axis **A52** Axis

Claims

1. A refrigerator (**1, 1'**) with an appliance body (**2, 2'**), on which at least two doors (**6, 7**) arranged one above the other are pivotably mounted, which open or close an interior space (**3, 4**) of the appliance body (**2, 2'**), a) wherein the doors (**6, 7**) are connected to the appliance body (**2, 2'**) in a closed position via at least one seal (**8**), b) wherein the two doors (**6, 7**) form an upper door (**6**) and a lower door (**7**) and are pivotably mounted via a double hinge (**20**) which is fixed to the appliance body (**2, 2'**) with a mounting plate (**21**) which is connected via a plurality of movable joint levers (**22, 23, 24, 25**) to an upper hinge part (**30**) connected to the upper door (**6**) and via a plurality of further movable joint levers to a lower hinge part (**40**) connected to the lower door (**7**), c) wherein the upper door (**6**) is further pivotably mounted on the appliance body (**2, 2'**) via a support hinge (**10**) which is fixed to the appliance body (**2, 2'**) with a mounting element (**11**) which is connected to a further upper hinge part (**12**) connected to the upper door (**6**) with a plurality of further joint levers (**13, 14, 15, 16**), d) wherein the lower door (**7**) is pivotably mounted on the appliance body (**2, 2'**) in an upper area via the double hinge (**20**) and in a lower area via a further support hinge (**10**) and the further support hinge (**10**) is of identical construction to the support hinge (**10**) with which the upper door (**6**) is pivotably mounted on the appliance body (**2, 2'**), wherein the joint levers (**13, 14, 15, 16**) of the support hinge (**10**) have a greater vertical extension than the joint levers (**22, 23, 24, 25**) of the double hinge (**20**), wherein the support hinge (**10**) comprises a support lever hinged to the mounting element (**11**), the support lever being formed by one of the further joint levers (**13, 14, 15, 16**) that has a greatest extension in a vertical direction of the further joint levers, and wherein the support lever is at least twice as thick as one of the joint levers (**22, 23, 24, 25**) of the double hinge (**20**) which is hinged to the mounting plate (**21**) and has the greatest extension in the vertical direction of the joint levers (**22, 23, 24, 25**) of the double hinge (**20**).
2. The refrigerator according to claim 1, wherein the support hinge (**10**) absorbs more weight forces of the upper door (**6**) than a part of the double hinge (**20**) connected to the upper door (**6**).
3. The refrigerator according to claim 1, wherein the joint levers (**22, 23, 24, 25**) of the double hinge (**20**) and the joint levers (**13, 14, 15, 16**) of the support hinge (**10**) have the same axes of rotation and the same lever lengths.
4. The refrigerator according to claim 1, wherein the joint levers (**22, 23, 24, 25**) of the double hinge (**20**) and the joint levers (**13, 14, 15, 16**) of the support hinge (**10**) have unequal axes of rotation and unequal lever lengths.
5. The refrigerator according to claim 1, wherein the joint levers (**22, 23, 24, 25**) of the double hinge (**20**) are at least partially plate-shaped and at least outer joint levers (**13, 16**) of the support hinge (**10**) are formed as levers which are U-shaped in cross-section.
6. The refrigerator according to claim 1, wherein the support hinge (**10**) has a greater height in a vertical direction than a height of the double hinge (**20**).
7. The refrigerator according to claim 1, wherein the joint levers (**22, 23, 24, 25**) of the double hinge (**20**) are formed at least partially from at least two plates which lie one on top of another in

certain areas.

8. The refrigerator according to claim 7, wherein the at least two plates form a cavity into which a further joint lever (22, 23, 24, 25) projects.
 9. The refrigerator according to claim 1, wherein a plate-shaped cover (17, 26) for covering gaps between the joint levers (13, 14, 15, 16, 22, 23, 24, 25) is provided on an upper side and a lower side of the support hinge (10) and/or the double hinge (20).
 10. The refrigerator according to claim 1, wherein the joint levers (22, 23, 24, 25) on the double hinge (20) form an articulated lever mechanism with seven joints.
 11. The refrigerator according to claim 1, wherein at least one of the joint levers of the double hinge (20) has a recess into which a spring (50) is inserted, by means of which a hinge part (30, 40) can be pretensioned in a closing direction.
 12. The refrigerator according to claim 11, wherein the spring (50) acts on a pivotable lever (52) or a pusher (61) which is movable along a curve guide (54, 62).
 13. The refrigerator according to claim 1, wherein an axis holder (29) for common axes (A3, A1) is arranged on the mounting plate (21) between the joint levers (22, 24) for the upper door (6) and the joint levers (22, 24) for the lower door (7).
 14. The refrigerator according to claim 13, wherein the joint levers (22, 24) for the upper door (6) and the joint levers (22, 24) for the lower door (7) are held on the mounting plate (21) and the axis holder (29) via a common axis bolt.
 15. The refrigerator according to claim 1, wherein the upper door (6) and the lower door (7) are braked by a damping device during a closing process, the damping device comprising a linear damper with a piston or a rotary damper, the damper being filled with a fluid.
 16. The refrigerator according to claim 1, wherein the appliance body (2, 2') is integrated in a piece of furniture (70) with side walls (71), the side walls (71) of the piece of furniture (70) projecting beyond the appliance body (2, 2') and covering at least part of lateral end faces (9) of the doors (6, 7) from the side.
 17. The refrigerator according to claim 1, wherein at least one door (6, 7) on a side facing the interior space (3, 4) has, in addition to insulation, compartments and/or holding means for storing objects and the support hinge (10) allows an opening angle of at least 115° so that the interior space (3, 4) is at least almost completely freely accessible.
-