

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401243
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Rapant; Russell M. et al.

Rotor assembly for an electric motor

Abstract

A method of forming a molded rotor assembly for an electric motor includes providing a lamination stack, molding an insulative material to the lamination stack to form an integral fan and magnet retention coupled to the lamination stack, the lamination stack and the integral fan and magnet retention together forming a rotor body, and pressing a shaft into a central aperture formed in the rotor body to achieve an interference fit between the shaft and the lamination stack.

Inventors: Rapant; Russell M. (Menomonee Falls, WI), Beyerl; Andrew T. (Pewaukee, WI)

Applicant: MILWAUKEE ELECTRIC TOOL CORPORATION (Brookfield, WI)

Family ID: 1000008781626

Assignee: MILWAUKEE ELECTRIC TOOL CORPORATION (Brookfield, WI)

Appl. No.: 18/364903

Filed: August 03, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230378834 A1	Nov. 23, 2023

Related U.S. Application Data

division parent-doc US 16698283 20191127 US 11742710 child-doc US 18364903
us-provisional-application US 62772924 20181129

Publication Classification

Int. Cl.: H02K1/28 (20060101); H02K1/17 (20060101); H02K15/12 (20060101)

U.S. Cl.:

CPC **H02K1/28** (20130101); **H02K1/17** (20130101); **H02K15/12** (20130101); Y10T29/49012 (20150115); Y10T29/53143 (20150115)

Field of Classification Search

CPC: H02K (9/06); H02K (5/18); H02K (9/04); H02K (1/27); H02K (1/28); H02K (2201/06); Y10T (29/49012); Y10T (29/49009); Y10T (29/49071); Y10T (29/49073); Y10T (29/53143)

USPC: 29/598; 29/557; 29/558; 29/592; 29/596; 29/597; 29/605; 29/606; 29/729; 29/732; 29/738

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4883408	12/1988	Borcherding	N/A	N/A
5329199	12/1993	Yockey et al.	N/A	N/A
5536985	12/1995	Ward et al.	N/A	N/A
6735846	12/2003	Du	N/A	N/A
6819022	12/2003	Yamamoto et al.	N/A	N/A
6946758	12/2004	Du et al.	N/A	N/A
7013552	12/2005	Du	N/A	N/A
7096566	12/2005	Du et al.	N/A	N/A
7215048	12/2006	Du et al.	N/A	N/A
7464455	12/2007	Du et al.	N/A	N/A
7591063	12/2008	West	N/A	N/A
7685697	12/2009	Du et al.	N/A	N/A
7814641	12/2009	Du et al.	N/A	N/A
7847457	12/2009	Achor	N/A	N/A
8203239	12/2011	Du et al.	N/A	N/A
8291574	12/2011	Achor	N/A	N/A
8324764	12/2011	Du et al.	N/A	N/A
8850690	12/2013	Du et al.	N/A	N/A
8866353	12/2013	Miyama	310/58	H02K 11/33
8896176	12/2013	Ryu et al.	N/A	N/A
8901787	12/2013	Du et al.	N/A	N/A
8937412	12/2014	Du et al.	N/A	N/A
8987964	12/2014	Achor	N/A	N/A
8997332	12/2014	Du et al.	N/A	N/A
9472989	12/2015	Du et al.	N/A	N/A
9755490	12/2016	Inuzuka	N/A	N/A
10205365	12/2018	Beyerl et al.	N/A	N/A
10276067	12/2018	Nadig	N/A	G09B 23/188
2006/0055264	12/2005	Johnson et al.	N/A	N/A
2006/0261694	12/2005	Chien-Hsiung et al.	N/A	N/A
2006/0273679	12/2005	Iwase et al.	N/A	N/A

2007/0236091	12/2006	Fukushima	N/A	N/A
2011/0293448	12/2010	Ishiguro	N/A	N/A
2012/0183417	12/2011	Linnenbrock et al.	N/A	N/A
2014/0042834	12/2013	Asahi et al.	N/A	N/A
2014/0125158	12/2013	Hessenberger et al.	N/A	N/A
2016/0181891	12/2015	Fogle et al.	N/A	N/A
2016/0197535	12/2015	De Filippis et al.	N/A	N/A
2017/0207669	12/2016	Zhang et al.	N/A	N/A
2017/0288499	12/2016	Beyerl et al.	N/A	N/A
2017/0346364	12/2016	Hessenberger et al.	N/A	N/A
2017/0373569	12/2016	Fung et al.	N/A	N/A
2020/0177041	12/2019	Rapant et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201307810	12/2008	CN	N/A
204243940	12/2014	CN	N/A
205489850	12/2015	CN	N/A
107147256	12/2016	CN	N/A
207304189	12/2017	CN	N/A
108494127	12/2017	CN	N/A
102007060011	12/2008	DE	N/A
2824810	12/2014	EP	N/A
2963775	12/2015	EP	N/A
S631341	12/1987	JP	N/A
H04190656	12/1991	JP	N/A
H0914174	12/1996	JP	N/A
2007209178	12/2006	JP	N/A
2012139070	12/2011	JP	N/A
2019990036381	12/1998	KR	N/A
1020030023279	12/2002	KR	N/A
1020180020041	12/2017	KR	N/A
101842760	12/2017	KR	N/A
2018103969	12/2017	WO	N/A

OTHER PUBLICATIONS

European Patent Office Action for Application No. 19888772.1 dated May 31, 2024 (6 pages).
cited by applicant

Partial Supplementary European Search Report for Application No. 21841695.6 dated Jul. 11, 2024
(18 pages). cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2019/063682 dated
Mar. 23, 2020 (7 pages). cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2021/041363 dated
Oct. 29, 2021 (14 pages). cited by applicant

Extended European Search Report for Application No. 19888772.1 dated Jul. 29, 2022 (10 pages).
cited by applicant

Chinese Patent Office Action for Application No. 201980090493.3 dated Sep. 8, 2024 (17 pages
including machine English translation). cited by applicant

Extended European Search Report for Application No. 21841695.6 dated Oct. 2, 2024 (17 pages).
cited by applicant

Zhou Weiping, "Mechanical Manufacturing Technology," Huazhong University of Science and Technology Press, Aug. 2002, p. 300 (5 total pages including English translation). cited by applicant

Chinese Patent Office Action for Application No. 201980090493.3 dated Mar. 6, 2025 (18 pages including machine English translation). cited by applicant

Primary Examiner: Phan; Thiem D

Attorney, Agent or Firm: Michael Best & Friedrich LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a divisional of U.S. patent application Ser. No. 16/698,283, filed on Nov. 27, 2019, now U.S. Pat. No. 11,742,710, which claims priority to U.S. Provisional Patent Application No. 62/772,924, filed on Nov. 29, 2018, the entire contents of both of which are incorporated herein by reference.

FIELD OF THE INVENTION

(1) The present invention relates to power tools, and more particularly to power tools including electric motors having a molded rotor assembly.

BACKGROUND OF THE INVENTION

(2) Tools, such as power tools, can include an electric motor having a rotor assembly to rotate a shaft and generate a torque output. The rotor assembly may include a fan molded to a lamination stack to form a rotor body, and the shaft may be pressed into the rotor body to form the rotor assembly.

SUMMARY OF THE INVENTION

(3) The present invention provides, in one aspect, a method for forming a molded rotor assembly for an electric motor. The method includes providing a lamination stack, molding an insulative material to the lamination stack to form an integral fan and magnet retention coupled to the lamination stack, the lamination stack and the integral fan and magnet retention together forming a rotor body. The method further includes pressing a shaft into a central aperture formed in the rotor body to achieve a press-fit engagement between the shaft and the lamination stack.

(4) The present invention provides, in another aspect, a method of manufacturing an electric motor. The method includes forming a molded rotor assembly and providing a stator assembly operable to produce a rotating magnetic field with which the rotor assembly interacts. The molded rotor assembly is formed by providing a lamination stack, molding an insulative material to the lamination stack to form an integral fan and magnet retention coupled to the lamination stack, the lamination stack and the integral fan and magnet retention together form a rotor body, and pressing a shaft into a central aperture formed in the rotor body to achieve an interference fit between the shaft and the lamination stack.

(5) Other aspects of the application will become apparent by consideration of the detailed description and accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is an exploded view of a prior art rotor assembly for an electric motor.

(2) FIG. 2 is a perspective view of a rotor assembly according to an embodiment of the present

invention.

(3) FIG. 3 is a perspective view of a rotor body of the rotor assembly of FIG. 2.

(4) FIG. 4 is another perspective view of the rotor body of FIG. 3.

(5) FIG. 5 is an end view of a lamination stack of the rotor assembly of FIG. 2.

(6) FIG. 6 is a perspective view of an integral fan and magnet retention of the rotor assembly of FIG. 2.

(7) FIG. 7 is an end view of the rotor body of FIG. 3.

(8) FIG. 8 is a partially exploded view of the rotor assembly of FIG. 2.

(9) FIG. 9 is another perspective view of the rotor body of FIG. 3.

(10) FIG. 10 is a detail view of a portion of a rotor body according to another embodiment of the present invention.

(11) FIG. 11 is a flowchart depicting a method of manufacturing a molded rotor assembly for an electric motor.

(12) FIG. 12 is a perspective view of a rotor assembly according to another embodiment of the invention.

(13) Before any embodiments of the application are explained in detail, it is to be understood that the application is not limited in its application to the details of construction and the arrangement of components set forth in the following description or illustrated in the following drawings. The application is capable of other embodiments and of being practiced or of being carried out in various ways.

DETAILED DESCRIPTION

(14) FIG. 1 illustrates an exploded view of a prior art rotor assembly 10 for an electric motor (not shown). The rotor assembly 10 is supported for rotation with respect to a stator (not shown) and includes a solid shaft 14 that extends along a longitudinal or rotational axis 18. The rotor assembly 10 also includes a lamination stack 22, a fan 26, a rubber ring 30, and a balance bushing 34. The lamination stack 22 is formed from a plurality of laminations that are stacked along the rotational axis 18. The shaft 14 is received into a central aperture (not shown) formed in the lamination stack 22. The fan 26 is coupled to the shaft 14 adjacent the lamination stack 22 so that the fan 26 rotates with the shaft 14 and provides cooling air to the electric motor. The rubber ring 30 is disposed between the fan 26 and the lamination stack 22. The balance bushing 34 is coupled to the shaft 14 adjacent the lamination stack 22 and opposite the fan 26 to rotationally balance the rotor assembly 10.

(15) An outer surface of the shaft 14 includes knurls or splines 38 that engage the central aperture of the lamination stack 22 to rotatably fix the lamination stack 22 to the shaft 14. Moreover, the central aperture of the lamination stack 22 includes notches (not shown) that are used for orientation of parts for magnetization of magnets during the assembly process. In the prior art rotor assembly 10, imperfect knurls formed on the shaft 14 combined with the notches in the lamination stack 22 can be a source of imbalance in the rotor assembly 10. Thus, the balance bushing 34 is required to balance the rotor assembly 10.

(16) FIGS. 2-9 illustrate a molded rotor assembly 100 (and portions thereof) for an electric motor (not shown) according to the present invention. The electric motor may be used in various different tools, such as power tools (e.g., rotary hammers, pipe threaders, cutting tools, etc.), outdoor tools (e.g., trimmers, pole saws, blowers, etc.), and other electrical devices (e.g., motorized devices, etc.).

(17) The electric motor is configured as a brushless DC motor. In some embodiments, the motor may receive power from an on-board power source (e.g., a battery, not shown). The battery may include any of a number of different nominal voltages (e.g., 12V, 18V, etc.), and may be configured having any of a number of different chemistries (e.g., lithium-ion, nickel-cadmium, etc.).

Alternatively, the motor may be powered by a remote power source (e.g., a household electrical outlet) through a power cord. The motor includes a substantially cylindrical stator (not shown)

operable to produce a magnetic field. The rotor assembly **100** is rotatably supported by a solid shaft **104** and configured to co-rotate with the shaft **104** about a longitudinal or rotational axis **108**.

(18) The rotor assembly **100** includes an integral fan and magnet retention **110** or main body (FIG. **6**) formed of an insulative material (e.g., plastic) that is molded to a lamination stack **112** to form a rotor body **114**. The integral fan and magnet retention **110** includes a fan portion **116** and a magnet retention portion **120** formed opposite the fan portion **116**. When the integral fan and magnet retention **110** is molded to the lamination stack **112**, the fan portion **116** abuts one end of the lamination stack **112** to define a fan end **124** of the rotor body **114**, and the magnet retention portion **120** abuts an opposite end of the lamination stack **112** to define a magnet retention end **128**.

(19) The lamination stack **112** defines a longitudinally extending central aperture **132** that receives the shaft **104** by press-fit engagement. Magnet slots **136** (FIG. **5**) are formed in the lamination stack **112** and configured to receive permanent magnets (not shown). The lamination stack **112** also includes injection channels **140** formed about the central aperture **132** and extending longitudinally between the fan end **124** and magnet retention end **128**. When the integral fan and magnet retention **110** is molded to the lamination stack **112**, the insulative material of the integral fan and magnet retention **110** flows through the channels **140** and joins the fan portion **116** to the magnet retention portion **120**. The insulative material also extends around the magnets within the magnet slots **136** to form magnet holding portions **144** (FIG. **6**). The magnet holding portions **144** extend through the magnet slots **136** between the fan portion **116** and the magnet retention portion **120**, and surround the permanent magnets to retain the magnets within the slots **136**.

(20) The rotor body **114** is secured to the shaft **104** by interference fit (e.g., by press-fit) to form the molded rotor assembly **100**. With reference to FIGS. **7** and **8**, unlike the prior art shaft **14** having splines **38** described above, the shaft **104** of the present invention includes a smooth annular outer surface **148**. In the illustrated embodiment, the smooth annular outer surface **148** is cylindrical and devoid of splines or other retention features. The central aperture **132** of the lamination stack **112** is partially defined by press-fit portions **152** (FIG. **7**) that contact and engage the smooth annular outer surface **148** of the shaft **104** to transfer torque between the rotor body **114** and the shaft **104**. The central aperture **132** is further defined by relief notches **156** formed in the lamination stack **112** between adjacent press-fit portions **152** to relieve stresses during the pressing process. By providing the shaft **104** with the smooth annular outer surface **148** and pressing the shaft **104** into the central aperture **132**, the rotor assembly **100** of the present invention eliminates the imbalance issue associated with the prior art splines **38**. Thus, the rubber ring **30** and the balance bushing **34** of the prior art rotor assembly **10** are eliminated in the molded rotor assembly **100**.

(21) In known prior art electric motors in which the fan is molded to the lamination stack and the shaft engages the lamination stack by press-fit, the shaft is pressed into the lamination stack prior to the molding process. In the molded rotor assembly **100** of the present invention, the shaft **104** is pressed into the rotor body **114** after the integral fan and magnet retention **110** is molded to the lamination stack **112**. This avoids the costs of having many sets of molding inserts for different shaft sizes and reduces the cost of the shaft **104** itself.

(22) The shaft **104** is pressed into the rotor body **114** from the fan end **124** as indicated by the arrow shown in FIG. **8**, and the rotor body **114** is supported at the magnet retention end **128** during pressing. The fan portion **116** and the magnet retention portion **120** each include shaft openings **160** (FIG. **6**) that correspond to the central aperture **132** to permit the shaft **104** to pass therethrough. With reference to FIG. **9**, the magnet retention portion **120** defines a bearing surface **164**, and the rotor body **114** is supported at the bearing surface **164** as the shaft **104** is pressed into the rotor body **114** from the fan end **124**. In other embodiments (not shown), the bearing surface may alternatively be provided on the fan portion **116**. In such embodiments, the shaft **104** may be pressed into the rotor body **114** from the magnet retention end **128** (i.e., in a direction opposite to the arrow shown in FIG. **8**). A fixture (not shown) may be employed to support the rotor body **114** during pressing.

(23) FIG. 10 illustrates another embodiment of a molded rotor assembly **200** similar to the molded rotor assembly **100** described above, with like features shown with reference numerals plus “100.” The rotor assembly **200** also includes a lamination stack **212** and an integral fan and magnet retention **210**, and a shaft **204** that is pressed into a central aperture **232** formed in the lamination stack **212**. To avoid a risk of cracks developing in the magnet retention portion **220** during pressing, the magnet retention portion **220** may include an oversized shaft opening **268** (FIG. 10) that exposes an alternative bearing surface **272** located on the lamination stack **212**. The central aperture **232** may be of a first diameter $D1$, measured between the press-fit portions **252**, while the oversized shaft opening **268** may be of a second diameter $D2$ larger than $D1$. The rotor body **214** is supported at the alternative bearing surface **272** of the lamination stack **212** during pressing while the shaft **204** is pressed from the fan end **224**. In other embodiments (not shown), the oversized shaft opening may alternatively be provided in the fan portion, so that the alternative bearing surface is located at the fan end **224**. In such embodiments, the shaft **204** may be pressed from the magnet retention end while the rotor body **214** is supported at the alternative bearing surface at the fan end **224**.

(24) FIG. 11 illustrates a method **300** of manufacturing a rotor assembly for an electric motor according to the present invention. In general, the illustrated method **300** includes a step **302** to form a lamination stack, a step **304** to insert permanent magnets into magnet slots formed in the lamination stack, a step **306** to mold an integral fan and magnet retention to the lamination stack to form a rotor body, and a step **308** to press a shaft into a central aperture formed in the rotor body. The method of FIG. 11 differs from prior art methods in that the pressing occurs at step **308** after the integral fan and magnet retention is molded to the lamination stack at step **306**. In some embodiments, the process may omit one or more of the steps **302** and **304** yet still fall within the scope of the present invention.

(25) FIG. 12 illustrates another embodiment of a molded rotor assembly **400** similar to the molded rotor assemblies **100** described above, with like features shown with reference numerals plus “300.” The rotor assembly **400** includes a shaft **404** rotatable about a longitudinal or rotational axis **408**, and a rotor body **414** secured to the shaft **404** (e.g., by interference fit via the pressing method described above). The rotor body **414** includes a lamination stack **412** and an integral magnet retention **410** or main body (FIG. 12). The integral magnet retention **410** is formed of an insulative material (e.g., plastic) that is molded to the lamination stack **412** to form the rotor body **414**.

(26) Unlike the integral fan and magnet retentions **110**, **210** described above, the integral magnet retention **410** does not include a fan portion. Instead, the integral magnet retention **410** includes a pair of magnet retention portions **420** abutting each axial end of the lamination stack **412**. In the illustrated embodiment, the two magnet retention portions **420** are identical. When the integral magnet retention **410** is molded to the lamination stack **412**, the insulative material of the magnet retention **410** flows through channels (not shown) formed in the lamination stack **412** and joins the two respective magnet retention portions **420**. The insulative material also extends around the magnets within the magnet slots (not shown) to form magnet holding portions (not shown), similar to that described above with respect to FIG. 6. The magnet holding portions extend through the magnet slots between the two magnet retention portions **420**, and surround the permanent magnets to retain the magnets within the slots. Each magnet retention portion **420** also defines a bearing surface **464**, and the rotor body **414** can be supported at the bearing surface **464** of either of the two magnet retention portions **420** as the shaft **404** is pressed into the rotor body **414**.

(27) Although the application has been described in detail with reference to certain preferred embodiments, variations and modifications exist within the scope and spirit of one or more independent aspects of the application as described.

Claims

1. A method of forming a molded rotor assembly for an electric motor, the method comprising: providing a lamination stack; molding an insulative material to the lamination stack to form an integral fan and magnet retention coupled to the lamination stack, the lamination stack and the integral fan and magnet retention together forming a rotor body; and pressing a shaft into a central aperture formed in the rotor body to achieve an interference fit between the shaft and the lamination stack.
2. The method of claim 1, wherein the shaft is pressed into the rotor body after the insulative material is molded to the lamination stack.
3. The method of claim 1, wherein the lamination stack defines a plurality of magnet slots configured to receive permanent magnets, and wherein the method further comprises inserting the permanent magnets into the magnet slots prior to molding the insulative material to the lamination stack.
4. The method of claim 1, wherein the integral fan and magnet retention includes a fan portion and a magnet retention portion abutting opposite ends of the lamination stack, the magnet retention portion defining a bearing surface, and wherein the method further includes supporting the rotor body at the bearing surface prior to pressing the shaft into the central aperture.
5. The method of claim 1, wherein the lamination stack defines the central aperture and the shaft includes an outer surface, and wherein pressing the shaft into the central aperture includes engaging the outer surface of the shaft and the central aperture of the lamination stack.
6. The method of claim 5, wherein the outer surface of the shaft is cylindrical.
7. The method of claim 5, wherein the central aperture has a size smaller than the outer surface of the shaft.
8. The method of claim 7, wherein the integral fan and magnet retention includes an oversized shaft opening larger than the central aperture and the outer surface of the shaft.
9. The method of claim 5, wherein the central aperture has an inner diameter smaller than an outer diameter of the shaft.
10. The method of claim 1, wherein the insulative material is plastic.
11. The method of claim 1, wherein the central aperture of the lamination stack includes a plurality of press-fit portions and a plurality of relief notches formed between adjacent press-fit portions, the relief notches being configured to relieve stress while the shaft is pressed into the central aperture.
12. A method of manufacturing an electric motor, the method comprising: forming a molded rotor assembly by providing a lamination stack, molding an insulative material to the lamination stack to form an integral fan and magnet retention coupled to the lamination stack, the lamination stack and the integral fan and magnet retention together forming a rotor body, and pressing a shaft into a central aperture formed in the rotor body to achieve an interference fit between the shaft and the lamination stack; and providing a stator assembly operable to produce a rotating magnetic field with which the rotor assembly interacts.
13. The method of claim 12, wherein the shaft is pressed into the rotor body after the insulative material is molded to the lamination stack.
14. The method of claim 12, further comprising locating the rotor assembly relative to the stator assembly such that the rotating magnetic field produced by the stator assembly imparts torque to the rotor assembly.
15. The method of claim 12, further comprising inserting the rotor assembly within the stator assembly to create an inner rotor electric motor.
16. The method of claim 12, wherein the lamination stack defines a plurality of magnet slots configured to receive permanent magnets, and wherein the method further comprises inserting the permanent magnets into the magnet slots prior to molding the insulative material to the lamination stack.
17. The method of claim 12, wherein during molding of the insulative material to the lamination

stack, the insulative material flows through an injection channel of the lamination stack.

18. The method of claim 17, wherein the injection channel extends longitudinally between a fan end adjacent a fan portion of the integral fan and magnet retention and a magnet retention end adjacent a magnet retention portion of the integral fan and magnet retention.

19. The method of claim 12, wherein the insulative material is plastic.

20. The method of claim 12, wherein the central aperture of the lamination stack includes a plurality of press-fit portions and a plurality of relief notches formed between adjacent press-fit portions, the relief notches being configured to relieve stress while the shaft is pressed into the central aperture.
