

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401907
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Park; Jaehyoung et al.

Electronic device including folded camera module for flare compensation and control method thereof

Abstract

An aspect of the disclosure provides an electronic device. The electronic device may include a lens assembly, an image sensor including multiple unit pixels configured to convert the light passed through the lens assembly into an electrical signal, and a processor electrically connected to the image sensor to output an image based on the electrical signal. At least one unit pixel included in the multiple unit pixels includes a micro-lens and at least two subpixels formed to correspond to the micro-lens, and the processor is configured to acquire multiple electrical signals from the at least two subpixels, identify a ratio of the multiple electrical signals, and determine, based on the identified ratio, whether flare is generated due to refraction or reflection of the light.

Inventors:	Park; Jaehyoung (Suwon-si, KR), Won; Jonghun (Suwon-si, KR)
Applicant:	Samsung Electronics Co., Ltd. (Suwon-si, KR)
Family ID:	1000008781577
Assignee:	Samsung Electronics Co., Ltd. (Suwon-si, KR)
Appl. No.:	18/324325
Filed:	May 26, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230388648 A1	Nov. 30, 2023

Foreign Application Priority Data

KR	10-2022-0065178	May. 27, 2022
KR	10-2022-0136864	Oct. 21, 2022

Related U.S. Application Data

continuation parent-doc WO PCT/KR2023/007306 20230526 PENDING child-doc US 18324325

Publication Classification

Int. Cl.: H04N23/71 (20230101); G06T5/80 (20240101); H04N23/55 (20230101)

U.S. Cl.:

CPC H04N23/71 (20230101); G06T5/80 (20240101); H04N23/55 (20230101);

Field of Classification Search

CPC: H04N (23/71); H04N (23/55); H04N (23/54); H04N (23/57); H04N (23/67); H04N (23/672); H04N (23/687); H04N (23/81); H04N (23/84); H04N (25/61); H04N (25/704); G06T (5/80); H01L (27/146)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9936121	12/2017	Kawakami	N/A	G06T 5/50
2004/0130647	12/2003	Kuba	N/A	N/A
2011/0025866	12/2010	Seo et al.	N/A	N/A
2011/0310290	12/2010	Douchida	N/A	N/A
2016/0269602	12/2015	Osborne	N/A	G03B 13/36
2017/0330348	12/2016	Park et al.	N/A	N/A
2018/0081149	12/2017	Bae	N/A	G02B 7/021
2020/0029035	12/2019	Agranov et al.	N/A	N/A
2020/0186723	12/2019	Kang	N/A	H04N 23/67
2021/0066375	12/2020	Kim	N/A	G02B 3/0056
2022/0070376	12/2021	Lee et al.	N/A	N/A
2022/0075161	12/2021	Im et al.	N/A	N/A
2022/0091373	12/2021	Saiga et al.	N/A	N/A
2022/0159188	12/2021	Lee	N/A	H04N 23/63
2023/0042544	12/2022	Lee	N/A	G06V 10/141
2023/0177709	12/2022	Lee et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2000-121944	12/1999	JP	N/A
2004-205796	12/2003	JP	N/A
2013055566	12/2012	JP	N/A

10-2011-0099983	12/2010	KR	N/A
20170127638	12/2016	KR	N/A
20200092165	12/2019	KR	N/A
10-2021-0018249	12/2020	KR	N/A
10-2021-0128803	12/2020	KR	N/A
10-2022-0014495	12/2021	KR	N/A
10-2022-0029310	12/2021	KR	N/A
10-2022-0033399	12/2021	KR	N/A
20230026092	12/2022	KR	N/A
WO-2021210875	12/2020	WO	G06T 5/001

OTHER PUBLICATIONS

Search Report dated Sep. 1, 2023 in International Patent Application No. PCT/KR2023/007306.
cited by applicant

Written Opinion dated Sep. 1, 2023 in International Patent Application No. PCT/KR2023/007306.
cited by applicant

Extended Search Report dated May 8, 2025 in European Patent Application 23812209.7. cited by
applicant

Primary Examiner: Haliyur; Padma

Attorney, Agent or Firm: Nixon & Vanderhye, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of International Application No. PCT/KR2023/007306 designating the United States, filed May 26, 2023, in the Korean Intellectual Property Receiving Office and claiming priority to Korean Patent Application No. 10-2022-0065178, filed May 27, 2022, in the Korean Intellectual Property Office and to Korean Patent Application No. 10-2022-0136864, filed Oct. 21, 2022, in the Korean Intellectual Property Office. The entire disclosures of each of these applications are incorporated herein by reference for all purposes.

BACKGROUND

Field

(1) The disclosure relates to an electronic device including a camera module and a control method thereof.

Description of Related Art

(2) As consumer's interest shift from compact cameras to camera modules embedded in a smartphone, an important issue in camera manufacturing is achieving miniaturization while maintaining image quality. A large optical system and a large imaging surface (image sensor) are advantageous in terms of image quality, and thus high image quality and miniaturization are in a trade-off relationship. In order to solve this problem, multiple single-focus lens type camera modules have been included in one electronic device.

(3) Single-focus lens type modules are generally configured to have different focal lengths, and may be properly mixed and operated with digital zoom, thereby making a zoom effect. As for a camera, based on a 35 mm camera optical system and a 24-35 mm focal length (wide), a shorter focal length type and a longer focal length type are commonly applied. Among these, a telephoto

(typically 3×) optical system with a relatively long focal length requires a longer mounting space in the longitudinal plane, and thus, in general, an optical system having a smaller size than a wide-angle optical system is adopted and mounted. However, since the market requires higher zoom performance, the difficulty of mounting a camera in a limited space is increasing. In order to solve this problem, a camera module with a refractive (or curved) optical system using reflection of a prism, which is more mountable, is being developed. A camera module to which a refractive optical system is applied may be made by reflecting and/or refracting incident light two or more times via a prism (or a mirror) and changing the incident path of light while maintaining an effective focal length of the light.

(4) A camera module including such a refractive optical system may have a flare phenomenon in which light reflected along an unwanted optical path in the prism is imaged on an image sensor as it is.

(5) The foregoing information may be provided as background technologies for helping understanding of the disclosure. No claim or determination is made as to whether any of the above description may be applied as prior art in relation to the disclosure.

SUMMARY

(6) An embodiment of the disclosure may provide an electronic device. The electronic device may include a lens assembly, an image sensor including multiple unit pixels configured to image light having passed through the lens assembly and convert the imaged light into an electrical signal, and a processor electrically connected to the image sensor to output an image using the electrical signal, wherein at least one unit pixel included in the multiple unit pixels includes a micro lens and at least two subpixels formed to correspond to the micro lens. The processor may be configured to acquire multiple electrical signals from the at least two subpixels, identify a ratio of the multiple electrical signals, and determine, based on the identified ratio, whether flare is generated due to refraction or reflection of the light, and/or compensate the flare.

(7) An embodiment of the disclosure may provide a method for controlling an electronic device. The electronic device may include a camera module including a lens assembly and an image sensor including multiple unit pixels, and a processor. The method of controlling the electronic device may be implemented by the processor and the processor may acquire multiple electrical signals from at least two subpixels included in each of the multiple unit pixels, based on a ratio of light incident through a first optical path in which light is reflected or refracted at least twice in the lens assembly and a second optical path different from the first optical path, identifying a ratio of the multiple electrical signals, and determining, based on the identified ratio, whether flare is caused by refraction or reflection of the light, and/or compensating the flare.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and/or other aspects of the disclosure will be more apparent by describing certain embodiments of the disclosure with reference to the accompanying drawings, in which:

(2) FIG. 1 is a block diagram of an electronic device in a network environment according to various embodiments.

(3) FIG. 2 is a front perspective view illustrating constituent elements of an electronic device according to various embodiments;

(4) FIG. 3 is a rear perspective view of an electronic device according to various embodiments;

(5) FIG. 4 is an exploded perspective view of an electronic device according to an embodiment.

(6) FIG. 5 illustrates an electronic device including a camera module according to an embodiment.

(7) FIG. 6 illustrates a camera module including a curved optical system according to an embodiment.

- (8) FIG. 7 illustrates a camera module including a curved optical system according to an embodiment.
- (9) FIG. 8 conceptually illustrates a camera module including a curved optical system according to an embodiment.
- (10) FIG. 9 illustrates a 2PD subpixel according to an embodiment.
- (11) FIGS. 10A, 10B, 10C, 10D, 10E, 10F, and 10G illustrate image sensors including multiple subpixels according to various embodiments of the disclosure.
- (12) FIG. 11 is a block diagram illustrating constituent elements of an electronic device according to an embodiment.
- (13) FIG. 12 illustrates a calibration operation according to an embodiment.
- (14) FIG. 13 illustrates a flare compensation method according to an embodiment.
- (15) FIG. 14A is an actual view showing a flare phenomenon according to an embodiment.
- (16) FIG. 14B illustrates the image in FIG. 14A displayed on a magenta background; and
- (17) FIG. 15 illustrates an actual view to which flare compensation is applied according to an embodiment.

DETAILED DESCRIPTION

- (18) A refractive optical system according to an embodiment may be formed to have a structure in which three prism pieces constitute a parallelogram prism structure with an acute angle of approximately 30 degrees and an optical lens is disposed on one surface having an acute angle in a lens lead type structure (a structure in which a lens on an optical path is disposed in front of a refractive optical system). Light is input through the optical lens and the optical path is reflected four times in the parallelogram prism structure. The optical path is terminated at an image sensor for imaging located on a rear surface having another acute angle. It is possible to effectively configure a long focusing distance by reflecting incident light four times in a relatively narrow instrument structure.
- (19) A refractive optical system according to an embodiment may be formed in a lens lead type, and may have a structure in which an approximately 45-degree triangular prism is disposed under an aperture lens, an operable and movable optical system such as auto focus (AF) is disposed on a refracted optical path, and another approximately 45-degree triangular prism is additionally disposed on the opposite side of a prism under an aperture, and an image sensor is mounted next to the aperture. In this embodiment, by reflecting incident light twice, a lens with a long focal length can be effectively mounted in a narrow space, and a space for movement of an AF structure can also be secured.
- (20) In such a multi-refraction lens, a flare phenomenon may occur due to differently formed optical paths. The flare phenomenon due to the optical paths being differently formed may refer, for example, to a phenomenon in which, in an optical system designed such that light is reflected light four times and then terminated at an image sensor, when light reflected twice is directed to an image sensor surface, an acquired image is blurred or output in the form of a double image by this light. Unlike a flare phenomenon due to the high brightness of a subject itself of a typical direct-type optical system without refraction, the flare phenomenon due to the optical paths being differently formed is a flare phenomenon that occurs along a predicted inner surface optical path, and may imply an artifact due to the adoption of a refractive optical system.
- (21) An embodiment of the disclosure provides an electronic device for preventing or reducing a flare phenomenon due to these optical paths being differently formed, and a method for controlling the same.
- (22) The technical features and advantages to be achieved herein are not limited to the features and advantages described above, and other features and advantages not described above will be clearly understood from the description below.
- (23) The following description of the accompanying drawings may provide understanding of various types of example implementations of the disclosure, including the claims and equivalents

thereto. Although embodiments disclosed in the following description include various specific details to help understanding, these embodiments are considered to be one of the various exemplary embodiments. Accordingly, those skilled in the art will understand that various changes and modifications of various types of implementation described herein may be made without departing from the scope and technical spirit of the disclosure. Also, descriptions of well-known functions and configurations may be omitted for clarity and conciseness.

(24) The terms and words used in the following description and claims are not limited to referenced meanings, and may be used to clearly and consistently describe an embodiment of the disclosure. Accordingly, it will be apparent to those skilled in the art that the following description of various types of example implementations of the disclosure is provided to describe, and not to limit, the scope of the disclosure and equivalents thereof.

(25) It should be understood that the singular forms of “a”, “an”, and “the” include plural meanings, unless the context clearly dictates otherwise. Thus, for example, the wording “a constituent element surface” may be understood to include one or more of the surfaces of a constituent element.

(26) FIG. 1 is a block diagram illustrating an electronic device **101** in a network environment **100** according to an embodiment of the disclosure. Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In an embodiment, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In an embodiment, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**).

(27) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation. According to an embodiment, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of, the main processor **121**.

(28) The auxiliary processor **123** may control, for example, at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the

main processor **121**, while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active (e.g., executing an application) state. According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence model is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted Boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof, but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(29) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(30) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(31) The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(32) The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of, the speaker.

(33) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(34) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or an external electronic device (e.g., an electronic device **102** (e.g., a speaker or a headphone)) directly or wirelessly coupled with the electronic device **101**.

(35) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature

sensor, a humidity sensor, or an illuminance sensor.

(36) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(37) A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, an HDMI connector, a USB connector, an SD card connector, or an audio connector (e.g., a headphone connector).

(38) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his/her tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(39) The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

(40) The power management module **188** may manage power supplied to the electronic device **101**. According to an embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(41) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(42) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify or authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

(43) The wireless communication module **192** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The

wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(44) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module may include an antenna including a radiating element composed of or including a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(45) According to an embodiment, the antenna module **197** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, an RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(46) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(47) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the external electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more external devices of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency

services using, e.g., distributed computing or mobile edge computing. In an embodiment, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(48) The electronic device according to embodiments of the disclosure may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(49) It should be appreciated that embodiments of the disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B”, “at least one of A and B”, “at least one of A or B”, “A, B, or C”, “at least one of A, B, and C”, and “at least one of A, B, or C”, may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd”, or “first” and “second” may be used to simply distinguish a corresponding component from another, and do not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with”, “coupled to”, “connected with”, or “connected to” another element (e.g., a second element), the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(50) As used in connection with embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic”, “logic block”, “part”, or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(51) Embodiments of the disclosure may be implemented as software (e.g., the program) including one or more instructions that are stored in a storage medium (e.g., internal memory or external memory) that is readable by a machine (e.g., the electronic device). For example, a processor (e.g., the processor) of the machine (e.g., the electronic device) may invoke at least one of the one or more instructions stored in the storage medium, and execute it. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(52) According to an embodiment, a method according to embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-

ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(53) According to an embodiment, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to an embodiment, one or more of the above-described components or operations may be omitted, or one or more other components or operations may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to an embodiment, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

(54) In the following detailed description, the longitudinal direction, width direction, and/or thickness direction of an electronic device may be described. The longitudinal direction may, for example, be defined as “Y-axis direction”, the width direction may, for example, be defined as “X-axis direction”, and/or the thickness direction may, for example, be defined as “Z-axis direction”. In an embodiment, with respect to the direction in which a constituent element is directed, “negative/positive (−/+)” may be described together with the orthogonal coordinate system illustrated in the drawings. For example, the front surface of an electronic device or a housing may, for example, be defined as “the surface facing the +Z direction”, and the rear surface may, for example, be defined as “the surface facing the −Z direction”. In an embodiment, the side surface of the electronic device or the housing may include an area facing the +X direction, an area facing the +Y direction, an area facing the −X direction, and/or an area facing the −Y direction. In an embodiment, “the X-axis direction” may, for example, include both “the −X direction” and “the +X direction”. This is based on the orthogonal coordinate system illustrated in the drawings for conciseness of description, and it is noted that descriptions of these directions or constituent elements do not limit the embodiment(s) of the disclosure.

(55) FIG. 2 is a perspective view illustrating the front surface an example electronic device **200** according to various embodiments. FIG. 3 is a perspective view illustrating the rear surface of the example electronic device **200** illustrated in FIG. 2 according to various embodiments.

(56) Referring to FIGS. 2 and 3, the electronic device **200** according to an embodiment may include a housing **210** including a first surface (or a front surface) **210A**, a second surface (or a rear surface) **210B**, and a side surface **210C** surrounding a space between the first surface **210A** and the second surface **210B**. In an embodiment (not shown), the housing may refer to a structure forming some of the first surface **210A**, the second surface **210B**, and the side surface **210C** in FIG. 2.

According to an embodiment, the first surface **210A** may be formed by a front plate **202** (e.g., a polymer plate or a glass plate including various coated layers) having at least a part which is substantially transparent. The second surface **210B** may be formed by a rear plate **211** which is substantially opaque. The rear plate **211** may be formed of, for example, coated or colored glass, ceramic, polymer, metal (e.g., aluminum, stainless steel (STS), or magnesium), or a combination of at least two of the above materials. The side surface **210C** may be coupled to the front plate **202** and the rear plate **211** and may be formed by a lateral structure (or a “lateral bezel structure”) **218** including metal and/or polymer. In an embodiment, the rear plate **211** and the lateral structure **218** may be integrally formed and may include the same material (e.g., a metal material such as aluminum).

(57) In the illustrated embodiment, the front plate **202** may include two first areas **210D**, which are curved and seamlessly extended from the first surface **210A** toward the rear plate **211**, at both ends of a long edge of the front plate **202**. In the illustrated embodiment (see FIG. 3), the rear plate **211** may include two second areas **210E**, which are curved and seamlessly extended from the second surface **210B** toward the front plate **202**, at both ends of a long edge. In an embodiment, the front plate **202** (or the rear plate **211**) may include only one of the first areas **210D** (or the second areas **210E**). In an embodiment, some of the first areas **210D** or the second areas **210E** may not be included. In the above embodiments, when viewed from the side surface of the electronic device **200**, the lateral structure **218** may have a first thickness (or width) at a side surface that does not include the first areas **210D** or the second areas **210E** as described above, and may have a second thickness smaller than the first thickness at a side surface including the first areas **210D** or the second areas **210E**.

(58) According to an embodiment, the electronic device **200** may include at least one among a display **201**, audio modules **203**, **207**, and **214**, sensor modules **204**, **216**, and **219**, camera modules **205**, **212**, and **213**, key input devices **217**, a light-emitting element **206**, and connector holes **208** and **209**. In an embodiment, in the electronic device **200**, at least one (e.g., the key input devices **217** or the light-emitting element **206**) of the constituent elements may be omitted, or other constituent elements may be additionally included.

(59) The display **201** may be visually exposed through, for example, a significant portion of the front plate **202**. In an embodiment, at least a portion of the display **201** may be visually exposed through the front plate **202** forming the first surface **210A** and the first areas **210D** of the side surface **210C**. In an embodiment, corners of the display **201** may be shaped to be substantially identical to the shape of outer edge of the front plate **202** adjacent thereto. In an embodiment (not shown), in order to enlarge an area in which the display **201** is visually exposed, the distance between the outer edge of the display **201** and the outer edge of the front plate **202** may be formed to be substantially uniform.

(60) In an embodiment (not shown), recesses or openings may be formed in a part of a screen display area of the display **201**, and at least one among the audio module **214**, the sensor module **204**, the camera module **205**, and the light-emitting element **206** aligned with the recesses or the openings may be included. In an embodiment (not shown), the rear surface of the screen display area of the display **201** may include at least one among the audio module **214**, the sensor module **204**, the camera module **205**, a fingerprint sensor **216**, and the light-emitting element **206**. In an embodiment (not shown), the display **201** may be combined with or disposed adjacent to a touch sensing circuit, a pressure sensor capable of measuring the strength (pressure) of a touch, and/or a digitizer for detecting a magnetic stylus pen. In an embodiment, at least some of the sensor modules **204** and **219** and/or at least some of the key input devices **217** may be disposed in the first areas **210D** and/or the second areas **210E**.

(61) The audio modules **203**, **207**, and **214** may include a microphone hole **203** and speaker holes **207** and **214**. In the microphone hole **203**, a microphone for acquiring external sound may be disposed, and in an embodiment, multiple microphones may be disposed to detect the direction of sound. The speaker holes **207** and **214** may include an external speaker hole **207** and a receiver hole **214** for communication. In an embodiment, the speaker holes **207** and **214** and the microphone hole **203** may be implemented as a single hole, or a speaker may be included without the speaker holes **207** and **214** (e.g., a piezo speaker).

(62) The sensor modules **204**, **216**, and **219** may generate electrical signals or data values corresponding to an internal operation state of the electronic device **200** or an external environmental state. The sensor modules **204**, **216**, and **219** may include, for example, a first sensor module **204** (e.g., a proximity sensor) and/or a second sensor module (not shown) (e.g., a fingerprint sensor) disposed on the first surface **210A** of the housing **210**, and/or a third sensor module **219** (e.g., a Heart Rate Monitor (HRM) sensor) and/or a fourth sensor module **216** (e.g., a

fingerprint sensor) disposed on the second surface **210B** of the housing **210**. The fingerprint sensor may be disposed on the second surface **210B** as well as the first surface **210A** (e.g., the display **201**) of the housing **210**. The electronic device **200** may further include the sensor module **176** in FIG. **1**, for example, at least one of a gesture sensor, a gyro sensor, a barometric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illumination sensor.

(63) The camera modules **205**, **212**, and **213** may include a first camera device **205** disposed in the first surface **210A** of the electronic device **200**, and a second camera device **212** and/or a flash **213** disposed on the second surface **210B**. The camera devices **205** and **212** each may include one or multiple lenses, an image sensor, and/or an image signal processor. The flash **213** may include, for example, a light-emitting diode or a xenon lamp. In an embodiment, two or more lenses (infrared camera, wide-angle, and telephoto lenses) and image sensors may be disposed on one surface of the electronic device **200**.

(64) The key input devices **217** may be disposed on the side surface **210C** of the housing **210**. In an embodiment, the electronic device **200** may not include some or all of the above-mentioned key input devices **217**, and the key input devices **217** that are not included may be implemented in other forms such as soft keys on the display **201**. In an embodiment, the key input devices may include the sensor module **216** disposed on the second surface **210B** of the housing **210**.

(65) The light-emitting element **206** may be disposed on the first surface **210A** of the housing **210**, for example. The light-emitting element **206** may provide, for example, state information of the electronic device **200** in the form of light. In an embodiment, the light-emitting element **206** may provide, for example, a light source interoperating with the operation of the camera module **205**. The light-emitting element **206** may include, for example, an LED, an IR LED, and a xenon lamp.

(66) The connector holes **208** and **209** may include a first connector hole **208** capable of accommodating a connector (e.g., a USB connector) for transmitting and receiving power and/or data to and from an external electronic device, and/or a second connector hole (e.g., an earphone jack) **209** capable of accommodating a connector for transmitting and receiving audio signals to and from an external electronic device.

(67) FIG. **4** is an exploded perspective view of the electronic device **200** illustrated in FIG. **2** according to an embodiment.

(68) Referring to FIG. **4**, an electronic device **300** (e.g., the electronic device **200** in FIG. **2** or **3**) may include a lateral structure **310** (e.g., the lateral structure **218** in FIG. **2**), a first support member **311** (e.g., a bracket), a front plate **320** (e.g., the front plate **202** in FIG. **2**), a display **330** (e.g., the display **201** in FIG. **2**), a printed circuit board **340** (e.g., a printed circuit board (PCB), a printed board assembly (PBA), a flexible PCB (FPCB), or a rigid-flexible PCB (RFPCB)), a battery **350**, a second support member **360** (e.g., a rear case), an antenna **370**, and a rear plate **380** (e.g., the rear plate **211** in FIG. **3**). In an embodiment, in the electronic device **300**, at least one (e.g., the first support member **311** or the second support member **360**) of the constituent elements may be omitted, or other constituent elements may be additionally included. At least one of the constituent elements of the electronic device **300** may be identical or similar to at least one of the constituent elements of the electronic device **200** in FIG. **2** or **3**, and redundant descriptions thereof will not be repeated.

(69) The first support member **311** may be disposed in the electronic device **300** and connected to the lateral structure **310**, or may be formed integrally with the lateral structure **310**. The first support member **311** may be formed of, for example, a metal material and/or a non-metal (e.g., polymer) material. The first support member **311** may have one surface coupled to the display **330** and the other surface coupled to the printed circuit board **340**. A processor, a memory, and/or an interface may be mounted on the printed circuit board **340**. The processor may include, for example, at least one of a central processing unit, an application processor, a graphics processing unit, an image signal processor, a sensor hub processor, or a communication processor.

(70) The memory may include, for example, volatile memory or non-volatile memory.

(71) The interface may include, for example, a high-definition multimedia interface (HDMI), a universal serial bus (USB) interface, an SD card interface, and/or an audio interface. The interface may electrically or physically connect the electronic device **300** to an external electronic device, and may include a USB connector, an SD card/MMC connector, or an audio connector.

(72) The battery **350** is a device for supplying power to at least one constituent element of the electronic device **300**, and may include, for example, a non-rechargeable primary battery, a rechargeable secondary battery, or a fuel cell. At least a portion of the battery **350** may be disposed substantially on the same plane as the printed circuit board **340**, for example. The battery **350** may be integrally disposed in the electronic device **300**, or may be disposed detachably from the electronic device **300**.

(73) The antenna **370** may be disposed between the rear plate **380** and the battery **350**. The antenna **370** may include, for example, a near-field communication (NFC) antenna, a wireless charging antenna, and/or a magnetic secure transmission (MST) antenna. The antenna **370** may, for example, perform short-range communication with an external device or wirelessly transmit/receive power required for charging to/from the external device. In an embodiment, an antenna structure may be formed by a part of the lateral structure **310** and/or the first support member **311** or a combination thereof. In the detailed description below, reference may be made to the electronic devices **101**, **102**, **104**, **200**, and **300** of the preceding embodiments, and it is noted that in the drawings, the same reference numeral is assigned to an element that can be easily understood through the preceding embodiments, or omitted, and that the detailed description may also be omitted.

(74) FIG. 5 is a plan view illustrating the rear surface of an electronic device **400** (e.g., the electronic devices **101**, **102**, **104**, **200**, and **300** in FIGS. 1, 2, 3, and 4) according to an embodiment of the disclosure. FIG. 6 is a cross-sectional view of a portion of the electronic device **400** according to an embodiment of the disclosure, taken along line AA' in FIG. 5. FIG. 7 is a configuration diagram illustrating an optical path of a lens assembly **500** in the electronic device **400** according to an embodiment of the disclosure.

(75) Referring to FIGS. 5 and 6, the electronic device **400** according to an embodiment of the disclosure may include a camera window **385** disposed on one surface (e.g., the second surface **210B** in FIG. 3). In an embodiment, the camera window **385** may be a portion of the rear plate **380**. In an embodiment, the camera window **385** may be coupled to the rear plate **380** through a decorative member **389**, and, when viewed from the outside, the decorative member **389** may be exposed in the form of surrounding the camera window **385**. According to an embodiment, the camera window **385** may include multiple transparent areas **387**, and the electronic device **400** may receive external light or transmit light to the outside through at least one of the transparent areas **387**. For example, the electronic device **400** may include at least one lens assembly **500** (e.g., the camera modules **180**, **205**, **212**, and **213** in FIGS. 1, 2, and 3) disposed to correspond to at least some of the transparent areas **387**, a lighting module, and at least one light source (e.g., an infrared light source) disposed to correspond to others of the transparent areas **387**. In an embodiment, through any one of the transparent areas **387**, the lens assembly **500** or the light source may receive external light or may emit light to the outside of the electronic device **400**. In an embodiment, the electronic device **400** or the lens assembly **500** may further include a camera support member **381**. The camera support member **381** may position or fix at least one of the lens assembly **500** or another lens assembly (e.g., a wide-angle camera, an ultra-wide-angle camera, or a macro camera) adjacent thereto to the inside of the rear plate **380** or the camera window **385**. In an embodiment, the camera support member **381** may be substantially a portion of the first support member **311** or the second support member **360** in FIG. 4.

(76) According to an embodiment, the electronic device **400** may include the lens assembly **500** or at least one of a wide-angle camera, an ultra-wide-angle camera, a macro camera, a telephoto camera, or an infrared photodiode as a light-receiving device, and may include a flash (e.g., the

flash **213** in FIG. 3) or an infrared laser diode as a light source or a light-emitting element. In an embodiment, the electronic device **400** may emit an infrared laser toward a subject using an infrared laser diode and an infrared photodiode, and may receive the infrared laser reflected by the subject to detect the distance or depth to the subject. In an embodiment, the electronic device **400** may photograph a subject using any one or a combination of at least two cameras, and may provide illumination toward the subject using a flash as necessary.

(77) According to an embodiment, a wide-angle camera, an ultra-wide-angle camera, or a macro camera among cameras has a shorter total track length along the optical axis direction of the lens(es) when compared with a telephoto camera (e.g., the lens assembly **500**). For example, in a telephoto camera (e.g., the lens assembly **500**) having a relatively long focal length, the total track length of the lens(es) **421a**, **421b**, **423a**, **423b**, and **423c** or **521a**, **521b**, **523a**, and **523b** is greater than that of other cameras. The “total track length” of the lens(es) may refer to, for example, the distance from a subject-side surface of a lens closest to a subject to the imaging surface of an image sensor **411**. As in the embodiment to be described later (e.g., the lens assembly **600** in FIG. 8), when other optical member(s) (e.g., mirror or prism) is disposed between the lens(es) and the image sensor, the “total track length” of the lens(es) may refer to, for example, the distance from the subject-side surface of a lens closest to a subject to the sensor-side surface of a lens closest to the image sensor. In an embodiment, in the case of a wide-angle camera, an ultra-wide-angle camera, or a macro camera, even when lens(es) are arranged along the direction of thickness (e.g., the thickness measured in the Z-axis direction in FIG. 4 or 6) of the electronic device **400**, a substantial effect of the arrangement on the thickness of the electronic device **400** may be small. For example, a wide-angle camera, an ultra-wide-angle camera, or a macro camera may be disposed in the electronic device **400** in a state in which a direction in which light is incident on the electronic device **400** from the outside is substantially identical to the optical axis direction of lens(es). This wide-angle camera, ultra-wide-angle camera, or macro camera may be referred to as a direct-type optical system. In an embodiment, when compared with a wide-angle camera, an ultra-wide camera, or a macro camera, the lens assembly **500** (e.g., a telephoto camera) has a small angle of view, but may be useful for photographing a subject at a greater distance and may include more lenses **421a**, **421b**, **423a**, **423b**, and **423c** or **521a**, **521b**, **523a**, and **523b**. For example, when the lens(es) **423a**, **423b**, and **423c** or **521a**, **521b**, **523a**, and **523b** of the lens assembly **500** are arranged in the thickness direction (e.g., the Z-axis direction) of the electronic device **400**, the thickness of the electronic device **400** may increase, or the lens assembly **500** may protrude to a significant extent outside the electronic device **400**. In an embodiment of the disclosure, the lens assembly **500** may include at least one reflective and/or refractive member (including, e.g., reflector and/or refractor) **413** or **415**, or **513** or **515** that reflects or refracts incident light IL in a different direction. In implementing a telephoto function, the lenses **423a**, **423b**, and **423c** or **521a**, **521b**, **523a**, and **523b** may be arranged to be movable forward and backward in the incident direction of light or in the traveling direction of reflected or refracted light, and thus the thickness of the electronic device **400** may be prevented from increasing or may be reduced.

(78) Referring to FIGS. 6 and 7, the lens assembly **500** may include a first reflective and/or refractive member **413** or **513**, a second reflective and/or refractive member **415** or **515**, an image sensor **411** or **511**, and/or at least one lens system (e.g., a second lens group **423** or **523** including second lenses **423a**, **423b**, and **423c** or **523a** and **523b** or a dummy member **423d**).

(79) The lens assembly **500** in FIGS. 6 and 7 is a lens assembly in which the traveling direction of light can be bent at least twice, and a camera including the lens assembly **500** may be referred to, for example, as a “folded camera”, and an optical system formed by such a camera may be referred to, for example, as a “refractive optical system”. In the folded camera, the lens assembly **500** may include at least one lens system (e.g., the second lens group **423** or **523** including the second lenses **423a**, **423b**, and **423c** or **523a** and **523b** or the dummy member **423d**) so as to bend the traveling direction of light at least twice. In addition, in an embodiment of the at least one lens system, at

least one optical member may guide or focus light RL1 reflected or refracted by the first reflective and/or refractive member **413** or **513** onto the second reflective and/or refractive member **415** or **515**, and may prevent the light RL1 reflected or refracted by the first reflective and/or refractive member **413** or **513** from being directly incident onto the image sensor **411** or **511**.

(80) According to an embodiment, the first reflective and/or refractive member **413** or **513** may include, for example, at least one prism, and/or at least one mirror. For example, the first reflective and/or refractive member **413** or **513** may be formed as a prism and/or a combination of a plurality of prisms. For example, the first reflective and/or refractive member **413** or **513** may be formed as a mirror and/or a combination of a plurality of mirrors. For example, the first reflective and/or refractive member **413** or **513** may be formed as a prism including at least one mirror. For example, at least one surface of the first reflective and/or refractive member **413** or **513** may be formed as a prism including a mirror. The first reflective and/or refractive member **413** or **513** may reflect or refract light IL, incident in a first direction D1, in a second direction D2 crossing the first direction D1. The first direction D1 may be, for example, a direction in which the light IL is incident from the outside to the electronic device **400** or the lens assembly **500** through one of the transparent areas **387** in FIG. 5 when photographing a subject. In an embodiment, the first direction D1 may refer to, for example, a photographing direction, a subject direction, an oriented direction of the lens assembly **500**, or a direction parallel thereto. In an embodiment, the first direction D1 may be parallel to the Z-axis direction or the thickness direction of the electronic device **400**.

(81) According to an embodiment, the second reflective and/or refractive member **415** or **515** may include, for example, at least one prism, and/or at least one mirror. For example, the second reflective and/or refractive member **413** or **513** may be formed as a prism and/or a combination of a plurality of prisms. For example, the second reflective and/or refractive member **413** or **513** may be formed as a mirror and/or a combination of a plurality of mirrors. For example, the second reflective and/or refractive member **415** or **515** may be formed as a prism including at least one mirror. For example, at least one surface of the second reflective and/or refractive member **415** or **515** may be formed as a prism including a mirror. The second reflective and/or refractive member **415** or **515** may reflect or refract light RL1, reflected or refracted by the first reflective and/or refractive member **413** and **513** and incident along the second direction D2, in a third direction D3 crossing the second direction D2. In an embodiment, the third direction D3 may be substantially perpendicular to the second direction D2. For example, the third direction D3 may refer to, for example, a direction parallel to the Z-axis direction. However, an embodiment of the disclosure is not limited thereto, and the third direction D3 may refer to, for example, a direction inclined with respect to the second direction D2 or the X-Y plane according to the arrangement and specifications of the lens assembly **500** or the second reflective and/or refractive member **415** in the electronic device **400**. In an embodiment, the third direction D3 may be substantially parallel to the first direction D1. Also, referring to FIG. 6, the third direction D3 may be toward the outside of the electronic device so as to correspond to the image sensor **411** disposed adjacent to the camera window **385**. However, the third direction D3 of the disclosure is not limited thereto, and, as illustrated in FIG. 7, may be toward the inside of an electronic device so as to correspond to the image sensor **511** disposed in the inside (e.g., the camera support member **381** in FIG. 6) of the electronic device.

(82) According to an example embodiment, the image sensor **411** or **511** may be configured to detect light RL2 that is reflected or refracted by the second reflective and/or refractive member **415** or **515** and is incident in the third direction D3. For example, light IL incident from the outside may be detected by the image sensor **411** or **511** via the first reflective and/or refractive member **413** or **513** and the second reflective and/or refractive member **415** or **515**, and the electronic device **400** or the lens assembly **500** may acquire a subject image based on a signal or information detected through the image sensor **411** or **511**. In an embodiment, the image sensor **411** or **511** may be disposed substantially parallel to the X-Y plane. For example, when the lens assembly **500** has an

image stabilization function of shifting the image sensor **411** or **511**, the image sensor **411** or **511** may move horizontally on a plane perpendicular to the first direction **D1** or the third direction **D3**. (83) According to an embodiment, in performing the image stabilization operation, the image sensor **411** or **511** may be shifted in the longitudinal direction (e.g., the Y-axis direction) or the width direction (e.g., the X-axis direction) of the electronic device **400**. For example, the image sensor **411** or **511** may be disposed on a plane perpendicular to the first direction **D1** or the third direction **D3**, so that, in an electronic device having a small thickness (e.g., approximately 10 mm or less), it may be easy to expand the size of the image sensor **411** or **511** and/or to secure a space for an image stabilization operation. In an embodiment, when the lens assembly **500** is used as a telephoto camera, the quality of a captured image may be further improved by installation of an image stabilization function. In an embodiment, when the size of the image sensor **411** or **511** increases, performance of the lens assembly **500** may further increase.

(84) According to an embodiment, the lens assembly **500** may further include a lens system (e.g., a first lens group **421** or **521** including at least one first lens **421a**, **421b**, **521a**, or **521b**) that guides or focuses the light **IL** incident in the first direction **D1** onto the first reflective and/or refractive member **413** or **513**. In an embodiment, the first lens group **421** or **521**, or the first lens (e.g., the first lens **421a** or **521a**) disposed on the subject side in the lens assembly **500** may have positive refractive power. For example, the first lens **421a** or **521a** may be configured to focus or align the light **IL** incident from the outside on or with the first reflective and/or refractive member **413** or **513**, so that an optical system ranging from the first lens **421a** or **521a** to the image sensor **411** or **511** may be miniaturized. When the lens assembly **500** includes the first lens group **421** or **521**, a camera including the lens assembly may be referred to, for example, as a “lens lead-type camera”. According to embodiments, the first lens group **421** or **521** may further include additional first lens(es) **421b** or **521b** in order to focus or align light incident from the outside.

(85) According to an embodiment, the second lens group **423** or **523** may include a dummy member **423d** and a light blocking member **425**. For example, the dummy member **423d** may be disposed inside the lens assembly **500** or the electronic device **400**, may have a cylindrical shape extending in the second direction **D2**, and may allow the light **RL1** traveling along the second direction **D2** to pass therethrough. In an embodiment, the dummy member **423d** may be, for example, one of lenses having positive or negative refractive power. In an embodiment, the dummy member **423d** may be a component formed integrally with any one of the second lenses **423a**, **423b**, and **423c** or **523a** and **523b** or the second reflective and/or refractive member **415** or **515**.

(86) According to an embodiment, the light blocking member **425** may be formed or disposed on at least a portion of the outer circumferential surface of the dummy member **423d**, and may absorb, scatter, or reflect light. The light blocking member **425** may be formed by, for example, etching, black lacquering, and/or printing or depositing a reflective layer on at least a portion of the outer circumferential surface of the dummy member **423d**. In an embodiment, a part of light reflected or refracted by the first reflective and/or refractive member **413** or **513** may be absorbed, scattered, or reflected by the light blocking member **425**. In an embodiment, the light blocking member **425** may substantially prevent light reflected or refracted by the first reflective and/or refractive member **413** or **513** from being directly incident on the image sensor **411** or **511** without passing through the second lens group **423** or **523** and/or the second reflective and/or refractive member **415** or **515**. For example, in the lens assembly **500**, light sequentially traveling in the first direction **D1**, the second direction **D2**, and/or the third direction **D3** (e.g., light following paths indicated by “**IL**”, “**RL1**”, and “**RL2**” in FIG. 7) may be incident on the image sensor **511**, and light having traveled along another path may be substantially prevented from being incident on the image sensor **511**.

(87) According to an embodiment, at least one of the second lenses **423a**, **423b**, and **423c** or **523a** and **523b** may move forward and backward between the first reflective and/or refractive member **413** or **513** and the second reflective and/or refractive member **415** or **515** along an axis having a direction substantially identical to the second direction **D2**. For example, the electronic device **400**

(e.g., the processor **120** in FIG. 1) or the lens assembly **500** may perform focal length adjustment or focus adjustment by moving at least one second lens **423a**, **423b**, or **423c** or **523a** or **523b** forward and backward along an axis having a direction substantially identical to the second direction (D2). A miniaturized electronic device such as a smartphone may have a thickness of about 10 mm, and in this case, the range in which the lens can move forward and backward in the thickness direction may be limited.

(88) According to an embodiment, the second direction D2 may, for example, be substantially parallel to the longitudinal direction (e.g., the Y-axis direction in FIG. 4), the width direction (e.g., the X-axis direction in FIG. 4), and/or the X-Y plane, and, when compared to a typical wide-angle camera that moves forward and backward in the Z-axis direction for focus adjustment, a range in which the at least one second lens **423a**, **423b**, or **423c** or **523a** or **523b** can move forward and backward may be large. For example, as the at least one second lens **423a**, **423b**, or **423c** or **523a** or **523b** moves forward and backward along an axis having a substantially direction identical to the second direction D2, telephoto performance is improved in the lens assembly **500**, and the degree of design freedom may be improved in securing a forward and backward movement space for focal length adjustment or focus adjustment.

(89) According to an embodiment, the electronic device **400** and/or the lens assembly **500** may further include an infrared blocking filter **519**. In an embodiment, the infrared blocking filter **519** may block light of an infrared or near-infrared wavelength band from being incident onto the image sensor **411** or **511**, and may be disposed at an arbitrary position in an optical path between the first lens **421a** or **521a** and the image sensor **411** or **511**. In an embodiment, the infrared cut filter **519** may be disposed at a position close to the image sensor **411** or **511** (e.g., between the image sensor **411** or **511** and the second reflective and/or refractive member **415** or **515**), thereby restraining or preventing the infrared blocking filter **519** from being visually exposed to the outside. In an embodiment, the first reflective and/or refractive member **413** or **513**, the second reflective and/or refractive member **415** or **515**, and/or at least one optical member (e.g., the second lens group **423** or **523**) may include an infrared blocking coating layer, and in this case, the infrared blocking filter **519** may be omitted. In an embodiment, the infrared blocking coating layer may be provided to at least one of an image sensor-side surface and a subject-side surface of the dummy member **423d** or to the second reflective and/or refractive member **415** or **515**. Accordingly, the image sensor **411** or **511** may detect light that has substantially passed through the infrared blocking filter **519** (or the infrared blocking coating layer).

(90) FIG. 8 is a configuration diagram illustrating an optical path of a lens assembly **600** in the electronic device **400** according to an embodiment of the disclosure.

(91) The lens assembly **600** may form a first optical path by refracting or reflecting light at least twice. Referring to FIG. 8, the first optical path may be indicated by a dotted line, and light traveling along the first optical path may follow paths indicated by “IL”, “RL1”, “RL2”, “RL3”, and “RL4” in FIG. 8. According to an embodiment, the first optical path may be an optical path that passes through the center of the lens assembly **600** and is substantially perpendicularly incident on an image sensor **611**. The first optical path may be formed by at least one reflective and/or refractive member included in the lens assembly **600** and at least one lens that may be additionally provided to the at least one reflective and/or refractive member according to embodiments. For example, the lens assembly **600** may include one reflective and/or refractive member **613**. In this case, the reflective and/or refractive member **613** may be formed in, for example, a trapezoidal prism or mirror structure. When the reflective and/or refractive member **613** is formed in a parallel trapezoidal prism or mirror structure, the reflective and/or refractive member **613** may include, for example, a first reflective surface **613a**, a second reflective surface **613b**, a third reflective surface **613c**, and a fourth reflective surface **613d**. In the embodiment in FIG. 8, the first reflective surface **613a** and the fourth reflective surface **613d** may be parallel to each other, and the second reflective surface **613b** and the third reflective surface **613c** may be parallel to each other, so that an optical

path similar to that of the embodiment in FIG. 7 may be formed. In other words, in the embodiment in FIG. 8, the reflective and/or refractive member **613** may form a parallelogram prism or mirror structure. However, examples of the lens assembly **600** of the disclosure are not necessarily limited thereto. For example, unlike the embodiment shown in FIG. 8, the first reflective surface **613a** and the fourth reflective surface **613d** may be formed in an equiangular trapezoid that has the second reflective surface **613b** or the third reflective surface **613c** as the base and has two interior angles (base angles) having the same size. When the lens assembly **600** is formed in an equiangular trapezoidal shape, an optical path similar to that of the embodiment in FIG. 6 may be formed. According to an embodiment, the reflective and/or refractive member **613** included in the lens assembly **600** may be formed to have a trapezoidal prism or mirror structure of one body, but multiple prisms or mirror pieces may be combined and/or coupled to form the reflective and/or refractive member **613** of a trapezoidal prism or mirror structure.

(92) According to an embodiment, the lens assembly **600** may include multiple reflective and/or refractive member. For example, as illustrated in FIGS. 6 and 7, the lens assembly **600** may include at least two reflective and/or refractive member (e.g., the first reflective and/or refractive member **413** or **513** and the second reflective and/or refractive member **415** or **515**) to refract or reflect light at least twice, thereby forming a first optical path. When the lens assembly **600** includes multiple reflective and/or refractive member (e.g., the first reflective and/or refractive member **413** or **513** and the second reflective and/or refractive member **415** or **515**), at least one lens system (e.g., the second lens group **423** or **523** including the second lenses **423a**, **423b**, and **423c** or **523a** and **523b** or the dummy member **423d** in FIGS. 6 and 7) may be further included between the multiple reflective and/or refractive member.

(93) In addition, although not illustrated in the drawing, the lens assembly **600** may further include the infrared blocking filter **519** described in FIG. 7. According to an embodiment, the lens assembly **600** may further include a lens system (e.g., a first lens group **621** including at least one first lens **621a** or **621b**) for guiding or focusing light IL incident from the outside onto the at least one reflective and/or refractive member **613**. In an embodiment, the first lens group **621**, or the first lens (e.g., the first lens **621a**) disposed on a subject side in the lens assembly **600** may have positive refractive power. For example, as the first lens **621a** is configured to focus or align light IL, which is incident from the outside, onto the at least one reflective and/or refractive member **613**, an optical system ranging from the first lens **621** to the image sensor **611** may be miniaturized. In addition, when the lens assembly **600** includes the first lens group **621**, a camera including this lens assembly may be referred to, for example, as a “lens lead-type camera”. According to embodiments, the first lens group **621** may further include additional first lens(es) **621b** in order to focus or align light incident from the outside.

(94) Referring to FIG. 8, a trapezoidal prism or mirror structure (or a parallelogram prism or mirror structure) and a refractive optical system including the same may be designed such that light refracted or reflected by the first reflective surface **613a**, the second reflective surface **613b**, the third reflective surface **613c**, and the fourth reflective surface **613d**, that is, only light refracted or reflected 4 times, is incident on the image sensor. However, according to an embodiment, as illustrated in FIG. 8, at least part of the light refracted or reflected by the reflective and/or refractive member **613** may be incident on the image sensor **611** along a second optical path different from the first optical path. Here, the second optical path may be indicated by a dash-dotted line, and light traveling along the second optical path may follow paths indicated by “IL”, “RL1”, and “RL2” in FIG. 8. For example, in the trapezoidal prism or mirror structure (or parallelogram prism or mirror structure) and the refractive optical system including the same, light refracted or reflected by the first reflection surface **613a** and the second reflection surface **613b**, that is, light refracted or reflected twice, may be incident on the image sensor **611**, an image acquired by such light may be output blurry, and the occurrence of such a phenomenon may be referred to, for example, as occurrence of flare.

(95) The disclosure may provide various embodiments in which it is possible to determine whether the above-described flare has occurred and/or to compensate the flare. In order to determine whether the flare has occurred and/or to compensate the flare, the image sensor **611** may include multiple unit pixels for imaging light having passed through the lens assembly and converting the imaged light into an electrical signal, and a processor (e.g., an image signal processor **732** in FIG. **10** described below) electrically connected to the image sensor to output an image using the electrical signal.

(96) The image sensor **611** of the disclosure will be described in more detail through embodiments in FIG. **8** described above and FIGS. **9** and **10** described below.

(97) FIG. **9** illustrates a 2PD subpixel according to an embodiment. FIG. **10** illustrates an image sensor including multiple subpixels according to various embodiments of the disclosure.

(98) The image sensor **611** of the disclosure may include multiple pixels. The image sensor **611** may include hundreds, thousands, or tens of thousands to hundreds of millions of pixels. In FIG. **8**, the image sensor **611** is disposed on a plane substantially parallel to the xy plane in the electronic device. However, the plane on which the image sensor **611** is disposed may be variously configured depending on various optical paths according to how many times and positions at which light traveling in the lens assembly **600** is refracted and/or reflected. For example, the position at which the image sensor **611** is disposed in the electronic device may be varied, such as a plane substantially parallel to the xy plane as well as a plane substantially perpendicular to the xy plane.

(99) Referring to FIGS. **8** and **9**, the image sensor **611** of the disclosure may include one micro lens **611a** for each unit pixel included in the image sensor **611**. The micro-lens **611a** may play a role of refracting and/or focusing light. According to an embodiment, multiple micro-lenses **611a** may be regularly arranged to form a micro-lens array. Although not illustrated in the drawings, the image sensor **611** may include a color filter which includes multiple colors of one or more kinds, is spatially divided, and is capable of selectively allowing light to pass. The color filter may be disposed behind the micro-lens with reference to a light movement path to allow light having a designated reference color, that is, light having a designated wavelength range, to pass therethrough. Multiple designated reference colors (e.g., red (R), green (G), and blue (B)) may be allocated to each of the multiple pixels included in the image sensor **611** through the color filter. Each of the multiple pixels may be designed to receive light having a wavelength range designated thereto. A light-receiving element (e.g., a photodiode, a pinned-photodiode, a phototransistor, or a photogate) may be disposed in each of the multiple pixels of the image sensor **611**. When light reaches the light-receiving element, an electrical signal corresponding to the incident light may be output by a photoelectric effect. In addition, the electrical signal may generate charge (or current) according to the intensity (or amount) of the received light.

(100) According to an embodiment, one micro-lens and one color filter may be disposed in a unit pixel, and one light-receiving element may be disposed behind the color filter. That is, one light-receiving element may be disposed in one unit pixel. According to an embodiment of the disclosure, one micro-lens and one color filter may be disposed in a unit pixel, and multiple light-receiving elements **611c** may be disposed behind the color filter.

(101) According to an embodiment, two, three, or four or more light-receiving elements may be disposed in a unit pixel. When two light-receiving elements are disposed in a unit pixel, the unit pixel structure may be referred to, for example, as a dual pixel structure (hereinafter, referred to as a “2PD pixel structure”). When three light-receiving elements are disposed in a unit pixel, the unit pixel structure may be referred to, for example, as a triple pixel structure (hereinafter, referred to as a “3PD pixel structure”). When four light-receiving elements are disposed in a unit pixel, the unit pixel structure may be referred to, for example, as a quad pixel structure (hereinafter, referred to as a “4PD pixel structure”). As such, in the disclosure, a case in which multiple (N) light-receiving elements are included in a unit pixel (or a case in which multiple (N) of light-receiving elements are included in each micro-lens) may be referred to, for example, as an “NPD pixel structure”. In

the embodiments in FIGS. **8** and **9**, a 2PD pixel structure in which two light-receiving elements are disposed in a unit pixel is disclosed. Hereinafter, when a unit pixel includes two light-receiving elements, each light-receiving element may be referred to, for example, as a “sub pixel”.

(102) Multiple light-receiving elements included in each unit pixel may independently capture incident light as an image. In the process in which the multiple light-receiving elements independently capture the incident light as an image, the incident light may be output as a photoelectric conversion signal.

(103) Referring back to FIGS. **8** and **9**, the lens assembly **600** according to the disclosure is disposed such that a direction (e.g., the X direction) in which at least two subpixels of the image sensor are distinguished corresponds to the second optical path. Here, the fact that the distinct directions of the at least two subpixels correspond to the second optical path may refer, for example, to the arrangement direction (e.g., the X direction) of different subpixels being parallel to an imaginary line projected from the second optical path onto a plane where the image sensor is disposed (e.g., a plane parallel to the xy plane). At this time, the second optical path may be inclined by a predetermined angle (Ang) with respect to the first optical path. For example, the first optical path of light incident on the image sensor may be incident on the image sensor **611** along a path indicated as RL4, the second optical path may be incident on the image sensor **611** along a path indicated as RL2', and the image sensor **611** of the disclosure may include at least two subpixels **611c-L** and **611c-R** as multiple light-receiving elements **611c**, and these two subpixels **611c-L** and **611c-R** may be arranged separately from each other in a direction corresponding to the second optical path direction. That is, when the second optical path is projected onto the image sensor, the two subpixels **611c-L** and **611c-R** may be separately disposed as two different parts along the X-axis direction parallel to the second optical path in one unit pixel. A real or imaginary partition wall **611c-W** may be provided to distinguish subpixels, for example, at least two subpixels, from each other. At this time, when the second optical path passes, the partition wall **611c-W** and the second optical path pass may form a predetermined angle (Ang).

(104) FIGS. **10a**, **10B**, **10C**, **10D**, **10E**, **10F**, and **10G** illustrate example image sensors including multiple subpixels according to various embodiments of the disclosure.

(105) When multiple light-receiving elements are disposed in a unit pixel, elements having the same specifications may be disposed to be symmetrical (line-symmetrical or point-symmetrical) to each other with respect to the center of the unit pixel. For example, when two light-receiving elements are disposed in a unit pixel, the light-receiving elements may be disposed to be line-symmetrical to each other in left/right or top/bottom directions with respect to the center of the unit pixel. Referring to FIG. **10A**, it is illustrated that in the unit pixel disposed in the image sensor **611**, the subpixels **611c-L** and **611c-R** are separately disposed up/down (or left/right) directions, but the unit pixel does not necessarily have such a form. For example, as illustrated in FIG. **10B**, a 2PD form having a slanted boundary is also possible. Also, the unit pixel of the image sensor **611** may have a form as illustrated in FIGS. **10C** and **10D**. As illustrated in FIGS. **10C** and **10D**, a unit pixel of the image sensor **611** may be formed in a structure in which the unit pixel includes 4 subpixels or 9 subpixels, that is, a 4PD pixel structure or a 9PD pixel structure. In addition, any PD form in which unit pixels of the image sensor **611** are separate from each other in the direction in which abnormal incident light (e.g., the second optical path (RL2' in FIG. **9**)) causing flare to be incident may be applied. A unit pixel of the image sensor **611** may have an NPD pixel structure (wherein N is a square of a natural number greater than or equal to 4). For example, the unit pixel may include a 2PD pixel structure including a metal shield as illustrated in FIGS. **10E** and **10F**, and a 2×1 OCL (on-chip-lens lens) PD structure as illustrated in FIG. **10G**.

(106) FIG. **11** is a block diagram illustrating constituent elements of an electronic device **700** (e.g., the electronic device **101** in FIG. **1**) according to various embodiments. The electronic device **700** according to an embodiment may collect light reflected from a subject to take a photograph (or video). The electronic device **700** may include an image capture part **710**, an interface **720** (e.g., an

image sensor interface), an image processing part **730**, a first memory **740**, a processor **760**, a display **770**, and a second memory **780**. According to various embodiments, the image capture part **710** may constitute a camera module (e.g., the camera module **180** in FIG. 1), and the image signal processor **732** and the processor **760** may constitute at least one processor (e.g., the processor **120** in FIG. 1).

(107) In an embodiment, the image capture part **710** may include a lens part **711**, an aperture **712**, an imaging element **713** (hereinafter, referred to as “image sensor **713**”), a shutter **714**, and driving parts **715** and **716**.

(108) In an embodiment, the lens part **711** may collect light reflected from a subject and reaching the electronic device **700**. The lens part **711** includes at least one lens, and may be implemented as, for example, a lens assembly having multiple lenses aligned in an optical axis direction. In this case, the image capture part **710** may be, for example, a dual camera, a 360-degree camera, or a spherical camera. The lenses included in the lens assembly may have the same lens attributes (e.g., angle of view, focal length, auto focus, f number, or optical zoom), or at least one lens may have at least one different lens attribute from the other lenses. The lens assembly may include, for example, a wide-angle lens or a telephoto lens. The amount (light amount) of light collected through the lens part **711** may be adjusted through the aperture **712**, and the light having passed through the aperture **712** may reach the image sensor **713**. In the embodiment illustrated in FIG. 11, the aperture **712** is shown as an element separate from the lens part **711**, but, unlike this, the aperture **712** may be integrated into the lens part **711**.

(109) In an embodiment, the image sensor **713** may include a pixel array in which multiple image pixels are two-dimensionally arranged in a lattice shape. One of multiple reference colors may be allocated to each of the multiple image pixels. According to various embodiments, the multiple reference colors may include, for example, red, green, and blue (RGB); red, green, blue, and white (RGBW); cyan, magenta, and yellow (CMY); cyan, magenta, yellow, and black (CMYK); red, yellow, and blue (RYB); or RGB infrared ray (RGBIR). Multiple micro-lenses may be disposed on a side close to the subject in the optical axis direction with reference to the multiple image pixels. The image sensor **713** may generate a digital signal (or electrical signal) based on light reflected from a subject, and may generate digital image data (hereinafter, referred to as “image data” for short) based on the electrical signal. The image sensor **713** may include, for example, an image sensor selected from among image sensors having different attributes, such as an RGB sensor, a black and white (BW) sensor, an IR sensor, or a UV sensor, multiple image sensors having the same attributes, or multiple image sensors having different attributes. For example, a charge coupled device (CCD) or a complementary metal oxide semiconductor (CMOS) may be used as the image sensor **713**.

(110) According to various embodiments, the image sensor **713** may include a photo diode PD, a transfer transistor TX (or a transfer gate), a reset transistor RX (or a reset gate), and a floating diffusion node FD. The photodiode PD may generate and accumulate a photo-charge corresponding to an optical image of a subject. The transfer transistor TX may transmit a photo-charge focused on the photodiode PD to the floating diffusion node FD in response to a transfer signal. The reset transistor RX may discharge a charge stored in the floating diffusion node FD in response to a reset signal. Before the reset signal is applied, the charge stored in the floating diffusion node (PD) is output. At this time, correlated double sampling (CDS) processing may be performed, and an analog signal on which the CDS processing has been performed may be converted into a digital signal through an analog-to-digital circuit (ADC) and/or an analog front end (AFE). An example of the image sensor **713** of the disclosure may be one in which four photodiodes are provided in a pixel corresponding to one micro-lens (e.g., a 4PD pixel).

(111) In an embodiment, the shutter **714** may adjust a time during which the image sensor **713** is exposed to light. For example, when the shutter **714** operates slowly, a large amount of light may be incident on the image sensor **713**, and when the shutter **714** operates quickly, a small amount of

light may be incident on the image sensor **713**.

(112) In an embodiment, the driving parts **715** and **716** (each including, e.g., a driver) may be elements for adjusting the position of the lens part **711**, the aperture **712**, or the image sensor **713**. The driving parts **715** and **716** may include a first driving part **715** and a second driving part **716**. For example, the first driving part **715** may move the lens part **711** so as to be substantially parallel to the optical axis direction. The auto focusing (AF) operation of the image capture part **710** may be implemented through the first driving part **715**, thereby adjusting the focus of the light imaged on the image sensor **713**. In addition, for example, the second driving part **716** may adjust the position of the lens part **711** or the image sensor **714** to prevent shaking occurring during a user's manipulation of the image capture part **710**. In response to the movement of the image capture part **710** or the electronic device **700** including the same, the second driving part **716** may move or perform control (e.g., read-out timing control, etc.) on the image sensor **713** or at least one lens included in the lens assembly in a specific direction in order to at least partially compensate for the negative effect (e.g., image shaking) of the movement on an image being captured. According to an embodiment, the second driving part **716** may be implemented as, for example, an image stabilizer or an optical image stabilizer, and may detect the movement by using a gyro sensor (not shown) or an acceleration sensor (not shown) disposed inside or outside the image capture part **710**.

(113) In an embodiment, the interface **720** (e.g., the image sensor interface including image sensor interface circuitry) may be disposed between the image sensor **713** and the image processing part **730** to perform interfacing. Data output from the image sensor **713** through the interface **720** may be transmitted to the image processing part **730** (including, e.g., image processing circuitry). According to the configuration of the electronic device **700**, the interface **720** may be included in the image processing part **730**. Also, according to the configuration of the electronic device **700**, the interface **720** may be omitted or another interface not illustrated in the drawing may be additionally provided.

(114) In an embodiment, the memories **740** and **780**, for example, may at least temporarily store at least a part of an image acquired through the image sensor **713** for a next image processing task, or may store commands or data related to at least one other constituent element (e.g., the image processing part **730**) of the electronic device **700**. For example, when image acquisition based on the shutter **714** is delayed or when multiple images are acquired at high speed, an acquired original image (e.g., a high-resolution image) may be stored in the memories **740** and **780**, and a corresponding copy image (e.g., a low-resolution image) may be previewed through a display module (e.g., the display module **160** in FIG. 1). Thereafter, when a designated condition is satisfied (e.g., a user input or a system command), at least a part of the original image stored in the memory **740** or **780** may be acquired and processed by, for example, the image signal processor **732**. According to an embodiment, the memories **740** and **780** may be formed as at least a part of a memory (e.g., the memory **130** in FIG. 1) of the electronic device **700** or a separate memory operated independently thereof.

(115) According to an embodiment, the memories **740** and **780** may include the first memory **740** and the second memory **780** distinguished from each other as illustrated in FIG. 11. According to an embodiment, the first memory **740** may store at least one piece of compensation data (e.g., white balance compensation data, gamma compensation data, knee compensation data, etc.). For example, the at least one piece of compensation data may be stored in a lookup table (LUT) format. According to an embodiment, the second memory **780** may be a non-volatile memory (e.g., flash memory), and may store image data generated by the image processing part **730**. In FIG. 11, for convenience of description, the memories **740** and **780** are illustrated as separate elements according to functions performed, but it should be noted that the memories are not necessarily limited to the illustration, and may be implemented as, for example, one element.

(116) In an embodiment, the image processing part **730** may be an element for variously processing image data that has been output from the image sensor **713**. With respect to an image acquired

through the image sensor **713** or an image stored in a memory (e.g., the first memory **740**), the image processing part **730** may perform image processing (e.g., depth map generation, three-dimensional modeling, panorama generation, feature point extraction, image synthesis, or image compensation (e.g., noise reduction, resolution adjustment, brightness adjustment, blurring, sharpening, or softening)). Additionally or alternatively, the image processing part **730** may perform control (e.g., exposure time control, read-out timing control, etc.) on at least one (e.g., the image sensor **713**) of the constituent elements included in the image capture part **710**. The image processed by the image processing part **730** may be stored again in the memory **740** or **780** for additional processing, or may be transmitted to a constituent element (e.g., the memory **130**, the display module **160**, the electronic device **102**, the electronic device **104**, or the server **108** in FIG. **1**) outside the image capture part **710**. According to an embodiment, the image processing part **730** may include a pre-processing part (e.g., Pre ISP) **731** (including, e.g., pre-processing circuitry) and the image signal processor (ISP) **732** (including, e.g., image signal processing circuitry). The pre-processing part **731** may perform a function such as image matching or gamma processing. For example, when there is shaking between multiple images that have been continuously photographed, the pre-processing part **731** may remove or reduce a shaking component through an image matching process. The image signal processor **732** may generate an entire image signal by compensating and synthesizing signals received from the pre-processing part **731**. According to an embodiment, the pre-processing part **731** may be integrated with the image signal processor **732** to form the image processing part **730**.

(117) According to various embodiments, the image processing part **730** may be configured as at least a part of the processor **760** (e.g., the processor **120** in FIG. **1**) or as a separate processor operated independently of the processor **760**. For example, according to an embodiment, the pre-processing part **731** and the image signal processor **732** of the image processing part **730** may be integrated into the processor **760**. In contrast, when the image processing part **730** is configured as a separate processor different from the processor **760**, images processed by the image processing part **730** may be displayed through the display module **160** as they are or after additional image processing by the processor **760**.

(118) According to various embodiments, the image processing part **730** may generate a signal for controlling the lens part **711** or the image sensor **713**, in addition to analyzing and calculating image data that has been output from the image sensor **713**. For example, the image processing part **730** may generate a signal for controlling the first driving part **715** in order to move the lens part **711** in the optical axis direction, or may generate a signal for controlling the second driving part **716** in order to move the lens part **711** or the image sensor **713** to perform image stabilization.

(119) In an embodiment, the processor **760** (e.g., the processor **120** in FIG. **1** and including e.g., processing circuitry) may include at least one of a central processing unit (CPU), an application processor (AP), or a communication processor (CP)). The processor **760** may execute, for example, calculations or data processing related to communication and/or control of at least one other element included in the electronic device **700**. As described above, the processor **760** may include the image processing part **730** as at least a part of the processor **760** or may operate as a separate processor operated independently of the image processing part **730**.

(120) In an embodiment, the display **770** may include, for example, an LCD display, an LED display, an OLED display, a MEMS display, or an electronic paper display. The display **770** may display, for example, an image captured by the image capture part **710**, an image having white balance compensated by the image processing part **730**, and the like. According to various embodiments, the display **770** may include a touch screen, and may receive, for example, touch, gesture, proximity, or hovering input using an electronic pen or a part of a user's body. In describing the following embodiments, the pre-processing part **731** may be included in at least a part of the image signal processor **732**, and accordingly, a description may be made on the assumption that the image signal processor **732** is substantially the same as the image processing

part **730**. In various embodiments of the disclosure, reference to “at least one processor” may refer to, for example, both a case in which the image processing part **730** is provided as at least a part of the processor **760** and a case in which the image processing part **730** is provided separately from the processor **760**. In describing the following embodiments, the description may be made of an example in which the image signal processor **732** is a separate processor that operates independently of the processor **760**. However, it should be noted that this is for convenience of description and does not limit a combination of the image processing part **730**, the image signal processor **732**, and the processor **760** according to various embodiments of the disclosure to any one form. According to an embodiment of the disclosure, the processor (e.g., the image processing part **730**, the image signal processor **732**, the processor **760**, or a combination of at least two thereof) may acquire multiple electrical signals from at least two subpixels, may identify a ratio of the multiple electrical signals, and may determine whether flare occurs and/or may compensate the flare based on the identified ratio.

(121) According to an embodiment, the memories (e.g., the first memory **740** and the second memory **780**) may store in advance a lookup table (LUT) related to a ratio according to a direction predetermined based on the second optical path. When executed, the processor (e.g., the image processing part **730**, the image signal processor **732**, the processor **760**, or a combination of at least two thereof) may determine whether flare occurs and/or may compensate the flare using the ratio and the LUT stored in the memory.

(122) In addition, the processor (e.g., the image processing part **730**, the image signal processor **732**, the processor **760**, or a combination of at least two thereof) may distinguish a saturated subpixel, based on multiple electrical signals acquired from at least two subpixels, and may differently perform calculation depending on the number of saturated subpixels. For example, when at least two subpixels in one unit pixel are all saturated, flare may be compensated using non-saturated unit pixels around the saturated unit pixels. In this case, when part of at least two subpixels in one unit pixel are saturated, flare may be compensated using a non-saturated subpixel, autofocusing (AF) information, and non-saturated unit pixels around the saturated subpixels.

(123) Summarizing the above-described content, according to an embodiment of the disclosure, the processor (e.g., the image processing part **730**, the image signal processor **732**, the processor **760**, or a combination of at least two thereof) may determine whether flare occurs due to refraction or reflection of light, only for a specific area of the image sensor in which light incident through the second optical path is received. As the light incident through the second optical path is received, at least one subpixel among the at least two subpixels may output a high gain compared with other subpixels, and the processor may identify a ratio of multiple electrical signals with reference to the subpixel outputting the high gain.

(124) An example operation (control method) of determining whether a flare has occurred or compensating the flare may be as follows. The control operation may be basically divided into a calibration operation for determining whether flare occurs and a compensation operation for compensating, after the calibration operation, a video (or image) in which flare has occurred.

(125) FIG. **12** illustrates a calibration operation according to an embodiment. FIG. **13** illustrates a flare compensation method according to an embodiment.

(126) A calibration operation and a compensation operation for a flare-generated video (or image) will be described in detail with reference to FIGS. **12** and **13**.

(127) Referring to FIG. **12**, the calibration operation may include an operation **S1201** of storing information about a flat light source such as a series of integrating spheres, and may include an operation **S1203** of storing a ratio between subpixels (e.g., **611c-L** and **611c-R**).

(128) For example, in relation to operation **S1201**, light source information according to various color temperatures (e.g., **5500K**) may be stored as light source information of the integrating sphere. In another example, light source information regarding a standard light source (e.g., a **D65** light source) may be stored as light source information of the integrating sphere. The integrating

sphere may be photographed in order to store the light source information of the integrating sphere. For example, the integrating sphere may be photographed for each auto focusing (AF) position, and the integrating sphere may be photographed for each zoom position.

(129) For example, in relation to operation **S1203**, a light source may output an amount of light sufficient to saturate a pixel, and another light source may output an amount of light to the extent that a pixel is not saturated. When an abnormal optical path that causes flare occurs even if a light source does not saturate the pixel, a gain difference may occur between subpixels (e.g., **611c-L** and **611c-R**). For example, in the embodiments in FIGS. **8** and **9**, it may be expected that, in the case of a left subpixel **611c-L** and a right subpixel **611c-R**, the right subpixel **611c-R** will receive a larger amount of light that may cause flare. That is, in one unit pixel, a gain difference between subpixels may occur, and a ratio thereof may be measured and/or stored. This ratio may vary depending on various reasons such as the color of a color filter of an image sensor, the direction of a subpixel, the position of the image sensor, the auto focusing (AF) position of a lens, or the position of the lens during zoom operation. In operation **S1203**, calculation of the ratio for each subpixel may be performed. According to an embodiment, information about these calculated values may be stored in a lookup table (LUT), and may be used to determine whether flare has occurred or to compensate the flare. The processor may use at least a part of the information stored in the LUT to determine whether flare has occurred and to determine whether to compensate the flare. According to an embodiment, since the processor can perform interpolation calculation, it is possible to properly select (e.g., resize) and store ratios of only some subpixels without storing ratios of subpixels included in all pixels of the image sensor. For example, in the 4PD pixel structure, 9PD pixel structure, etc. described with reference to FIG. **10**, it is possible to obtain ratios in various phase difference directions including left/right and up/down directions, as well as a ratio in either direction of the left/right direction or the up/down direction. When the LUT is separately stored for each direction, a more accurate calculation of whether flare has occurred may be possible.

(130) In relation to the calibration operation, a function for determining the amount of flare using the stored LUT as an input may be made in the memory (e.g., the first memory **740** and the second memory **780**) (**S1204**).

(131) For example, in relation to operation **S1204**, this function may be determined experimentally. For example, if this function is defined as a polynomial, coefficients of the polynomial may be experimentally stored in advance using the LUT ratio as an input. It may be difficult to predict whether flare will occur, but basically, when a unit pixel included in the image sensor is not saturated, it may be assumed that whether flare will occur has some correlation with the LUT ratio.

(132) In relation to the calibration operation, instruction(s) related to information about a calculation value for a ratio of each subpixel and/or information about a function for determining the amount of flare may be stored in a memory (**S1205**). The calculation value for the ratio of each subpixel may be stored in the form of a lookup table (LUT).

(133) Referring to FIG. **13**, the flare compensation operation may first include an operation **S1301** of determining the degree of saturation of an acquired image (or video). In addition, the amount of flare that occurs may be calculated based on the determination of the degree of saturation of a pixel (**S1303**).

(134) In relation to operation **S1301**, since a saturated pixel outputs a signal different from an electrical signal that is output from a non-saturated pixel, a separate signal processing process may be required. In the pixel saturation determination, when a pixel is determined to be a saturated pixel, masking may be performed. According to an embodiment, even when only one subpixel among multiple subpixels included in a unit pixel of the image sensor is saturated, the unit pixel may be treated as a saturated pixel.

(135) In relation to operation **S1303**, the function and LUT information (**S1302**) previously stored in the memory in the calibration operation may be used. The amount of flare that occurs for an input value may be calculated using the function and LUT stored in the calibration operation in

FIG. 12. For example, referring to FIGS. 8 and 9, among the left subpixel **611c-L** and the right subpixel **611c-R**, the right subpixel **611c-R** may have a greater amount of flare that occurs, wherein a normal signal of electrical signals output from the left subpixel **611c-L** and the right subpixel **611c-R** may be found by extracting the amount of flare experimentally obtained in the calibration operation step.

(136) Next, the flare that has occurred may be removed through a flare removal operation **S1305**. The flare removal operation **S1305** may include an operation **S1307** of processing a saturated pixel.

(137) In relation to operation **S1307**, when there is a saturated pixel, whether some of subpixels are saturated or all subpixels are saturated may be determined, and when all subpixels are determined to have been saturated, an original value may be inferred using another pixel, among non-saturated pixels, which is closest to the saturated pixel. According to an embodiment, the calculation may be performed by sequentially calculating the other non-saturated pixels from a pixel close to the saturated pixel to a pixel far from the saturated pixel. The pixel determined to be saturated by the processor may be processed as a saturated pixel, and the processor may use this information to perform learning for calculation on images to be acquired later. When information about the saturated pixel previously determined by the processor is no longer valid, the processor may perform learning (e.g., deep learning (DL)) or reduce the exposure of auto exposure (AE) to make the calculation more accurate in the next frame.

(138) According to an embodiment, the processor may compensate flare in consideration of autofocus (AF) information. For example, in a high-frequency domain where AF is out of focus, a gain difference between subpixels may occur due to AF defocus, thereby cause artifacts. Therefore, when AF is out of focus, flare may be compensated by taking AF information into account.

(139) After the flare is compensated, the processor (e.g., the image processing part **730**, the image signal processor **732**, the processor **760**, or a combination of at least two thereof) may remove an artifact of the saturated subpixel or an artifact therearound through gamma or clipping calculation. For example, in the case of flare compensation, processing such as clipping and gamma compensation may be performed as the last step. Due to the gamma or clipping calculation, a dynamic range (DR) may be reduced, but a saturation-related artifact may be partially prevented (reduced).

(140) FIG. **14A** is an actual view showing a flare phenomenon according to an embodiment. FIG. **14B** illustrates the image in FIG. **14A** displayed on a magenta background. FIG. **15** illustrates an actual view to which flare compensation is applied according to an embodiment.

(141) FIG. **14B** may show a portion, in which flare has occurred in an image illustrated in FIG. **14A**, on a horizontal axis and vertical axis coordinate system regarding distance. Here, the flare that has occurred may include not only a flare due to refraction and/or reflection of light while the light passes through a reflective and/or refractive member, but also flare due to other causes.

(142) Referring to FIG. **14A**, flare may be detected in an actual captured image. The flare may occur around a light source and may occur due to various causes. Referring to FIG. **14B**, flare may occur in a partial area of an image rather than the entire area of the image. From this, it is confirmed that the flare may be detected only in a specific area of an image sensor, but not in the entire area of the image sensor. The electronic device of the disclosure may include a processor, and the processor may perform at least one (e.g., the flare compensation operation) of the aforementioned operations to predict and calculate a flare caused by refraction and/or reflection of light while the light passes through the reflective and/or refractive member, thereby removing and/or reducing the flare occurring in a specific area of the image sensor. Accordingly, an image in which flare has been removed and/or reduced may be acquired as illustrated in FIG. **15** below.

(143) According to an embodiment of the disclosure, an electronic device (e.g., electronic device **101**, **200**, **300**, or **400**) may include a lens assembly (e.g., lens assembly **500** or **600**), an image sensor (e.g., image sensor **411**, **511**, or **611**) including multiple unit pixels configured to convert the

light passed through the lens assembly into an electrical signal, and a processor (e.g., the image processing part **730**, the image signal processor **732**, the processor **760**, or a combination of at least two thereof) electrically connected to the image sensor to output an image by using the electrical signal. One unit pixel included in the multiple unit pixels may include a micro-lens (e.g., micro-lens **611a**) and at least two subpixels (e.g., sub-pixels **611c-L** and **611c-R**) formed to correspond to the micro-lens. The processor may acquire multiple electrical signals from the at least two subpixels, may identify a ratio of the multiple electrical signals, and may determine, based on the identified ratio, whether flare is generated due to refraction or reflection of the light.

(144) According to an embodiment, the flare may be compensated based on whether the flare is caused by the refraction or reflection.

(145) According to an embodiment, the at least two subpixels may output different electrical signals depending on an incident angle of light incident through the micro-lens.

(146) According to an embodiment, the lens assembly may include at least one reflective and/or refractive member (e.g., reflective and/or refractive member **413**, **415**, **513**, **515**, or **613**) configured to refract or reflect the light.

(147) According to an embodiment, at least a part of the light refracted or reflected by the reflective and/or refractive member may be incident on the image sensor along a second optical path different from a first optical path which is incident on the image sensor vertically.

(148) According to an embodiment, a determination of whether flare is generated due to the refraction or reflection of the light may be performed only for a specific area of the image sensor in which the light incident along the second optical path is received.

(149) According to an example embodiment, as the light incident along the second optical path is received, at least one of the at least two subpixels may output a higher gain than other subpixels, and the processor may identify a ratio of multiple electrical signals with reference to the subpixel outputting the higher gain.

(150) According to an example embodiment, the electronic device may further include a memory configured to pre-store a lookup table (LUT) related to a ratio according to a direction predesignated based on the second optical path.

(151) According to an example embodiment, at least two subpixels of the image sensor are distinguished in a direction corresponding to a second optical path.

(152) According to an example embodiment, the processor may determine whether flare is generated and compensate the flare using the LUT stored in the memory and the identified ratio, when executed.

(153) According to an embodiment, the processor may distinguish saturated subpixels based on the multiple electrical signals acquired from the at least two subpixels, and may compensate the flare depending on the number of saturated subpixels.

(154) According to an embodiment, when all of at least two subpixels in one unit pixel are saturated, the processor may compensate the flare using a non-saturated unit pixel around the saturated unit pixel.

(155) According to an embodiment, when part of at least two subpixels in one unit pixel are saturated, the processor may compensate the flare using a non-saturated subpixel, AF (autofocusing) information, and/or a non-saturated unit pixel around the saturated subpixel.

(156) According to an embodiment, after the flare is compensated, the processor may remove an artifact of the saturated subpixel or an artifact therearound through gamma or clipping calculation.

(157) According to an embodiment, the image sensor may have a micro-lens configuration including 2PD, 4PD, 9PD, NPD, metal shield, slanted 2PD, or 2×1 OCL PD.

(158) An embodiment of the disclosure may provide a method for controlling an electronic device which includes a camera module including a lens assembly and an image sensor including multiple unit pixels, and a processor, wherein the method may include acquiring multiple electrical signals from at least two subpixels included in each of the multiple unit pixels, based on a ratio of light

incident along a first optical path formed to be refracted at least twice in the lens assembly and a second optical path different from the first optical path, identifying a ratio of the multiple electrical signals, and determining, based on the identified ratio, whether flare is generated by refraction or reflection of the light, and compensate the flare.

(159) In the disclosure, an embodiment has been illustrated and described. However, it should be understood that various embodiments are for illustrative purposes rather than for limiting the disclosure. It will be apparent to those skilled in the art that various changes may be made in the form and detailed configuration without departing from the overall scope of the disclosure, including the appended claims and equivalents thereof. For example, the shape, the type, and the number of reflective and/or refractive member included in the lens assembly of the disclosure and/or an electronic device including the lens assembly may vary depending on embodiments, and an optical path that is refracted or reflected while passing through the reflective and/or refractive member may vary depending on embodiments. The scope of the disclosure may encompass these various embodiments. It will also be understood that any of the embodiment(s) described herein may be used in conjunction with any other embodiment(s) described herein.

Claims

1. An electronic device comprising: a lens assembly, including at least one lens, and at least one reflector or refractor, which has a trapezoid shape, configured to refract or reflect light; an image sensor including multiple unit pixels configured to convert the light passed through the lens assembly into an electrical signal; and at least one processor, comprising processing circuitry, electrically connected to the image sensor to output an image based on the electrical signal, wherein at least a part of the light refracted or reflected by the reflector or refractor is incident on the image sensor along a second optical path different from a first optical path which is incident on the image sensor, wherein at least one unit pixel included in the multiple unit pixels comprises: a micro-lens; and at least two subpixels formed to correspond to the micro-lens and arranged in a direction corresponding to the second optical path, and wherein the at least one processor is configured to: acquire multiple electrical signals from the at least two subpixels; identify a ratio of the multiple electrical signals; and determine, based on the identified ratio, whether flare is generated due to refraction or reflection of the light.
2. The electronic device of claim 1, wherein the at least one processor is configured to: compensate the flare, based on the identified ratio.
3. The electronic device of claim 2, wherein the at least two subpixels are arranged in a direction corresponding to an incident angle of light incident through the micro-lens.
4. The electronic device of claim 1, wherein the at least one processor is configured to determine whether the flare is generated due to the refraction or reflection of the light only for a specific area of the image sensor in which the light incident along the second optical path is received.
5. The electronic device of claim 4, wherein, as the light incident along the second optical path is received, at least one of the at least two subpixels is configured to output a higher gain than other subpixels, and the at least one processor is configured to identify a ratio of multiple electrical signals with reference to the subpixel outputting the higher gain.
6. The electronic device of claim 4, further comprising a memory configured to pre-store a lookup table (LUT) related to a ratio according to a direction predesignated based on the second optical path.
7. The electronic device of claim 6, wherein the at least one processor is configured to, when executed, determine whether the flare is generated and compensate the flare using the LUT stored in the memory and the identified ratio.
8. The electronic device of claim 1, wherein the at least one processor is configured to: distinguish saturated subpixels based on the multiple electrical signals acquired from the at least two subpixels;

and compensate the flare depending on a number of saturated subpixels.

9. The electronic device of claim 8, wherein the at least one processor is configured to compensate, in a case that each of the at least two subpixels in one unit pixel are saturated, the flare using a non-saturated unit pixel around the saturated unit pixel.

10. The electronic device of claim 8, wherein the at least one processor is configured to compensate, in a case that one or more of the at least two subpixels in one unit pixel are saturated, the flare using a non-saturated subpixel, AF (autofocusing) information, or a non-saturated unit pixel around the saturated subpixel.

11. The electronic device of claim 10, wherein the at least one processor is configured to remove an artifact of the saturated subpixel or an artifact therearound through gamma or clipping calculation after the flare is compensated.

12. The electronic device of claim 1, wherein the image sensor is configured to have a micro-lens configuration comprising 2PD, 4PD, 9PD, NPD, metal shield, slanted 2PD, or 2×1 OCL PD.

13. A method for controlling an electronic device comprising a camera comprising a lens assembly, at least one reflector or refractor, which has a trapezoid shape, configured to refract or reflect light, and an image sensor comprising multiple unit pixels; and at least one processor comprising processing circuitry, the method comprising: acquiring multiple electrical signals from at least two subpixels included in each of the multiple unit pixels and arranged in a direction corresponding to a second optical path, based on a ratio of light incident along a first optical path in which the light is refracted or reflected at least twice in the lens assembly and the second optical path different from the first optical path; identifying a ratio of the multiple electrical signals; determining, based on the identified ratio, whether a flare is generated by refraction or reflection of the light; and compensate the flare.

14. The method of claim 13, further comprising: determining whether the flare is generated or compensate the flare using a LUT stored in a memory and the identified ratio.

15. The method of claim 13, further comprising: distinguishing saturated subpixels based on the multiple electrical signals acquired from the at least two subpixels; and compensating the flare depending on a number of saturated subpixels.

16. The method of claim 13, further comprising: compensating, in a case that all of at least two subpixels in one unit pixel are saturated, the flare using a non-saturated unit pixel around the saturated unit pixel.
