

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250277307

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

SHARMA; Shashank et al.

3D PRINTED INTEGRATED GAS MIXER

Abstract

Embodiments of the present disclosure generally relate to mixing gases for deposition processes. Specifically, the disclosure relates to a 3D printed single piece gas mixer that mixes a plurality of gases prior to the gases entering a processing chamber. In one embodiment a mixer is provided. The mixer includes a body, an inlet, an outlet, and a hollow passage. The hollow passage is disposed through the body and fluidly connects the inlet to the outlet. The hollow passage includes a sidewall. The mixer further includes a plurality of fins formed on the sidewall. The plurality of fins extend into the hollow passage, and the plurality of fins and the sidewall form a monolithic structure.

Inventors: SHARMA; Shashank (Raipur, IN), KUMPALA; Sandeep (Bangalore, IN), HEMADRI; Sandesh (Bangalore, IN), DHANAKSHIRUR; Akshay (Hubli, IN)

Applicant: Applied Materials, Inc. (Santa Clara, CA)

Family ID: 96880940

Appl. No.: 19/063607

Filed: February 26, 2025

Foreign Application Priority Data

IN 202441015287

Mar. 01, 2024

Publication Classification

Int. Cl.: C23C16/455 (20060101)

U.S. Cl.:

CPC C23C16/45512 (20130101); C23C16/45544 (20130101); C23C16/45591 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims priority to Indian Provisional Application No. 202441015287, filed Mar. 1, 2024, which is incorporated by reference herein in its entirety.

BACKGROUND

Field

[0002] Embodiments of the present disclosure generally relate to mixing gases for deposition processes. Specifically, the disclosure relates to a 3D printed single piece gas mixer that mixes a plurality of gases prior to the gases entering a processing chamber.

Description of the Related Art

[0003] Atomic layer deposition (ALD) is a process performed in semiconductor manufacturing. ALD implements multiple deposition steps using different gases to deposit material on a substrate. After ALD processes, cleaning processes that use different gases are performed. Each step of the process requires multiple gases and these gases are mixed prior to entering a processing volume. Mixing the gases is critical to proper deposition of material on the substrate.

[0004] Longer mixing lengths provide better mixing of gases. However, due to design constraints on length in processing chambers, gas mixers are used to mix the gases. Therefore, what is needed in the art is new gas mixers for mixing gases.

SUMMARY

[0005] In one embodiment a mixer is provided. The mixer includes a body, an inlet, an outlet, and a hollow passage. The hollow passage is disposed through the body and fluidly connects the inlet to the outlet. The hollow passage includes a sidewall. The mixer further includes a plurality of fins formed on the sidewall. The plurality of fins extend into the hollow passage, and the plurality of fins and the sidewall form a monolithic structure.

[0006] In another embodiment, a processing chamber is provided. The processing chamber includes a chamber body defining a processing volume. The chamber body includes a gas box having a port, and a bottom. The processing chamber further includes a mixer disposed on the lid and fluidly connected to the port. The mixer includes a body, an inlet, an outlet fluidly connected to the processing volume of the chamber body, and a hollow passage. The hollow passage is disposed through the body, and fluidly connects the inlet to the outlet. The hollow passage includes a sidewall. The mixer further includes a plurality of fins formed on the sidewall. The plurality of fins extend into the hollow passage, and the plurality of fins and the sidewall form a monolithic structure. The processing chamber further includes a plurality of gas lines fluidly connected to the inlet of the mixer.

[0007] In another embodiment, a method of mixing gases is provided. The method includes fluidly connecting an inlet of a mixer to a plurality of gas lines, and fluidly connecting an outlet of the mixer to a port of a processing chamber. The mixer includes a body, the inlet, the outlet, and a hollow passage. The hollow passage is disposed through the body and fluidly connects the inlet to the outlet. The hollow passage includes a sidewall. The mixer further includes a plurality of fins formed on the sidewall. The plurality of fins extend into the hollow passage, and the plurality of fins and the sidewall form a monolithic structure. The method further includes flowing a first gas and a second gas through the gas lines and into the mixer to produce a mixed gas, and flowing the mixed gas through the outlet of the mixer and into a processing volume of the processing chamber.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] So that the manner in which the above recited features of the present disclosure can be understood in detail, a more particular description of the disclosure, briefly summarized above, may be had by reference to embodiments, some of which are illustrated in the appended drawings. It is to be noted, however, that the appended drawings illustrate only exemplary embodiments and are therefore not to be considered limiting of its scope, and may admit to other equally effective embodiments.

[0009] FIG. 1 is a schematic, side view of a processing chamber with a substrate support, according to embodiments.

[0010] FIG. 2A is a schematic, cross sectional view of a gas mixer, according to embodiments.

[0011] FIG. 2B is a schematic, isometric view of a gas mixer, according to embodiments.

[0012] FIG. 3 is a flow diagram of a method for mixing gases, according to embodiments.

[0013] To facilitate understanding, identical reference numerals have been used, where possible, to designate identical elements that are common to the figures. It is contemplated that elements and features of one embodiment may be beneficially incorporated in other embodiments without further recitation.

DETAILED DESCRIPTION

[0014] Embodiments of the present disclosure generally relate to mixing gases for atomic layer deposition processes. Specifically, the disclosure relates to a 3D printed single piece gas mixer that mixes a plurality of gases prior to the gases entering processing chambers.

[0015] Current mixer designs have two parts, a mixer part and a spacer part, for the mixer to operate. The mixer part mixes the gases between the spacer part. However, two-part mixers have several drawbacks. For example, in two-part mixers, the mixer part moves relative to the spacer part. The movement of the mixer part can lead to particle generation. Another issue with the two-part mixer is the mixer part can also tilt in the spacer part, affecting deposition on a substrate during processing. The two-part mixer can also be damaged when installed in a processing chamber. Additionally, the two-part mixer has a high cost and lead time due to the precise machining needed to form the mixing part of the two-part mixer.

[0016] In various embodiments, the single piece mixer address these and other design issues of two-part mixers. For example, in various embodiments, the mixer is an integrated mixer and spacer formed by additive manufacturing. In some embodiments, the mixer has a plurality of fins that change the direction of gas flowing through the mixer. Changing the direction of the gas mixes the gas. Further, the mixer does not have a risk of particle generation or mixer tilting due to the mixer being formed as a single part. The single part design of the mixer also reduces the risk of damage during installation in process chambers. In addition, the mixer can be formed via additive manufacturing, reducing cost and lead time.

[0017] FIG. 1 is a schematic, side view of a processing chamber **100** with a substrate support **116**. The process chamber **100** includes a chamber body **102** and a gas box **104** defining a process volume **114** therein. A bottom **105** of the chamber body **102** is opposite the gas box **104**. A port **106** is formed through the gas box **104**. A gas mixer **200** is in fluid communication with the port **106**. A showerhead **110** is coupled to the gas box **104**. A plurality of openings **112** are formed through the showerhead **110**. The gas mixer **200** is in fluid communication with the process volume **114** via the port **106** and the openings **112**.

[0018] A substrate support **116** is moveably disposed in the process volume **114** opposite the gas box **104**. The substrate support **116** includes a support body **118** disposed on a stem **120**. The support body **118** includes a support surface **122** disposed opposite the stem **120** and facing the showerhead **110**. The support surface **122** includes a plurality of mesas **124**. An opening **148** is formed through the chamber body **102** between the gas box **104** and the bottom **105**. During operation, a substrate **101** is loaded onto the support surface **122** through the opening **148**. An

actuator **126** is coupled to the substrate support **116** to move the substrate support **116** toward and away from the showerhead **110** for loading and processing the substrate **101** thereon. Although the processing chamber **100** described herein is provided as an example of a chamber with which the single piece mixer can be implemented, in various embodiments, the single piece mixer can be implemented with other types of processing chambers.

[0019] The gas mixer **200** is fluidly connected to a first gas source **128** and a second gas source **130**. In some embodiments, the gas mixer **200** is fluidly connected to other gas sources. The first gas source **128** is fluidly connected to the gas mixer **200** with a first gas line **132**. The second gas source **130** is fluidly connected to the gas mixer **200** with a second gas line **134**. Gas enters the gas mixer **200** and mixes in a hollow passage **201**. The hollow passage **201** extends through the gas mixer **200** fluidly connecting the gas sources **128**, **130** to the port **106**. The gas exits the port into a showerhead volume **136** defined by the gas box **104** and the showerhead **110**. The gas box **104** is an RF hot point on the process chamber **100**. The gas box **104** contains one of a plurality of electrodes (not shown) for plasma generation.

[0020] The process chamber **100** is used for atomic layer deposition (ALD) processes. ALD processes include at least two deposition steps and at least two purging steps. A deposition step will be followed by a purging step to remove unused deposition gases in the process chamber **100**. During a first deposition step, the first gas may be a precursor gas. Different precursor gases may be used for different deposition steps. During the first deposition step, the second gas may be a purge gas. The purge gas is a RPS purge gas. The purge gas includes at least one of argon gas, or a similar gas. Mixing the precursor gas and the purge gas is critical to the thickness uniformity on the substrate **101** during processing. During a first purge step, the purge gas is flowed through the first gas line **132** to remove unused precursor gases. The purge gas may be oxygen gas (O.sub.2) or a gas suitable to rid the gas line **132** of the unused precursor gas from the first deposition step. During the first purge step, the purge gas from the first deposition step is flowed through the second gas line **134**. A second deposition step is performed after the first purge step. The second deposition step can include a different precursor gas. After the second deposition step, a second purge step is performed. In some embodiments, additional deposition steps and purge steps may be performed. In some embodiments, for example, the first deposition step includes a precursor gas that contains silicon and the second deposition gas includes a precursor gas of oxygen (O.sub.2). That deposition would form silicon dioxide (SiO.sub.2) on the substrate **101**. During ALD processes, the second gas line **134** is flowing the second gas at all steps.

[0021] After the ALD process is complete, a cleaning process is performed. The cleaning process removes unwanted material deposited on the process chamber **100**. During the cleaning process, the first gas is a purge gas. The purge gas may include the purge gases described above. During the cleaning process, the second gas is a clean gas. The clean gas includes at least one of nitrogen trifluoride (NF.sub.3), fluorine radicals, oxygen (O.sub.2), or different gases compatible with cleaning the selected precursor gas. Mixing the cleaning gas and the purge gas is critical to the cleaning process and the gases mixed in the gas mixer **200**.

[0022] FIG. 2A is a schematic, cross sectional view of a gas mixer **200**. The gas mixer **200** includes an inlet **203**, an outlet **205**, and an interior section **207**. The inlet **203** is positioned on a first surface **209** of the gas mixer **200**. The inlet **203** is fluidly connected to the first gas line **132** and the second gas line **134**. The inlet **203** is also fluidly connected to the interior section **207**. The first gas line **132** enters the inlet **203** at an angle. The second gas line **134** enters the inlet **203** vertically. The inlet **203** may be shaped as a semicircular flange. In some embodiments, a gas assembly **211** is positioned on the first surface **209** of the gas mixer **200**. The gas assembly **211** includes the first gas line **132** and the second gas line **134**. The gas assembly **211** is a RF ground point. The gas assembly **211** is at a low voltage compared to the gas box **104**. The outlet **205** is positioned on a second surface **213** of the gas mixer **200**. The outlet **205** is fluidly connected to the port **106**. The outlet **205** is also fluidly connected to the interior section **207**. The second surface **213** is disposed on the

gas box **104** of the processing chamber **100**. A body of the gas mixer is defined by the interior section **207**, the first surface **209**, and the second surface **213**.

[0023] The hollow passage **201** extends through the interior section **207** from the inlet **203** to the outlet **205**. In one or more embodiments, the hollow passage **201** includes a sidewall **216**. A plurality of fins **215** are formed on the sidewall **216**. Further, the sidewall **216** extends around the hollow passage **201**. The plurality of fins **215** and the sidewall **216** form a monolithic structure in the gas mixer **200** (e.g., the sidewall **216** and the plurality of fins **215** include the same material and the sidewall **216** and the plurality of fins **215** are inseparable). In one or more embodiments, the plurality of fins **215** are formed on the interior section **207** to form the monolithic structure in the gas mixer **200** (e.g., the interior section **207** and the plurality of fins **215** include the same material and the interior section **207** and the plurality of fins **215** are inseparable). In one or more embodiments, the hollow passage **201** includes a sleeve (not pictured). The sleeve includes an interior wall and an exterior wall where the exterior wall contacts the interior section **207** and interior wall contacts the hollow passage **201**. The plurality of fins **215** are formed on the interior wall of the sleeve such that the plurality of fins **215** and the sleeve form a monolithic structure in the gas mixer **200** (e.g., the sleeve and the plurality of fins **215** include the same material and the sleeve and the plurality of fins **215** are inseparable).

[0024] The fins **215** have a first surface **220**, a second surface **221** and an edge surface **222**. The first surface **220** extends from the sidewall **216** at a first angle **224**. The first angle **224** may be about 70 degrees to about 110 degrees, such as about 80 degrees to about 100 degrees, such as about 85 degrees to about 95 degrees, such as about 90 degrees. The second surface **221** extends from the sidewall **216** at a second angle **226**. The second angle **226** may be about 20 degrees to about 80 degrees, such as about 30 degrees to about 70 degrees, such as about 40 degrees to about 65 degrees, such as about 45 degrees to about 60 degrees. The second angle **226** is calculated from the sidewall **216** counter-clockwise to the second surface **221** as shown in FIG. 2A. The second angle **226** is selected to give the fin **215** structural strength in the hollow passage **201**. The first surface **220** is opposite the second surface **221**. The edge surface **222** connects the first surface **220** to the second surface **221**. Further, the edge surface is opposite the sidewall **216**. The edge surface **222** is an extended surface of each fin **215** positioned within the hollow passage **201**. Additionally, one fin **215** is not connected to another fin **215**, the fins **215** are connected only to the sidewall **216**. The fins **215** disrupt the linear path of the hollow passage **201** from the inlet **203** to the outlet **205**. The plurality of fins **215** includes at least three fins **215**.

[0025] The fins **215** change the direction of gases through the hollow passage **201** and a cross-sectional area through the hollow passage **201**. By changing the direction of the gases, the fins **215** cause the gases to enter turbulent flow. The turbulent flow mixes the gases. The plurality of fins **215** cause the gases traveling through the hollow passage **201** to cross a center axis **214** of the hollow passage **201**, the center axis **214** extending from the inlet **203** to the outlet **205**. The fins **215** narrow the path through the hollow passage **201** from a first cross-sectional area **218** to a second cross-sectional area **217** and a third cross-sectional area **219**. Further, the first cross-sectional area **218** is defined as the area between the sidewall **216** without the fins **215** obstructing the path. The first cross-sectional area **218** is about 0.5 in.^{sup.2} to about 1.5 in.^{sup.2}, such as about 0.6 in.^{sup.2} to about 1 in.^{sup.2}, such as about 0.8 in.^{sup.2}. The diameter creating the first cross-sectional area **218** is about 0.6 in to about 1.4 in, such as about 1 in. The second cross-sectional area is the area in the path in a Y-direction between the sidewall **216** with a fin **215** obstructing part of the path. The second cross-sectional area **217** is about 0.1 in.^{sup.2} to about 0.9 in.^{sup.2}, such as about 0.3 in.^{sup.2} to about 0.5 in.^{sup.2}, such as about 0.4 in.^{sup.2}. The diameter creating the second cross-sectional area **217** is about 0.3 in to about 1 in, such as about 0.5 in to about 0.8 in. In addition, the third cross-sectional area **219** is defined as the cross-sectional area between fins **215** in an X-direction. The third cross-sectional area **219** is about 0.005 in.^{sup.2} to about 0.1 in.^{sup.2}, such as about 0.01 in.^{sup.2} to about 0.02 in.^{sup.2}. The diameter creating the third cross-sectional area **219**

is about 0.05 in to about 0.4 in, such as about 0.1 in to about 0.2 in. In various embodiments, the third cross-sectional area **219** is less than the second cross-sectional area **217**. The second cross-sectional area **217** is less than the first cross-sectional area **218**. For example, in some embodiments, the second cross-sectional area **217** is constant throughout the hollow passage **201** due to the fins being the same length. In other embodiments, the second cross-sectional area **217** varies throughout the hollow passage **201** due to the fins **215** having different lengths. In various embodiments, the third cross-sectional area **219** is constant throughout the hollow passage **201** due to the fins **215** being spaced equidistant. In other embodiments, the third cross-sectional area **219** varies throughout the hollow passage **201** due to the varied spacing of the fins **215**. The fins **215** alternate the cross-sectional area of the hollow passage **201** between the second cross-sectional area **217** and the third cross-sectional area **219**. Varying the cross-sectional area of the hollow passage **201** assists in mixing the gases. By attaching the fins **215** to the sidewall **216**, the gas mixer **200** does not have any extra volume added to the hollow passage **201**. For ALD processes, reduction of volume in the gas mixer **200** is beneficial as reduction of the volume leads to a quicker evacuation of gases from the gas mixer **200**, decreasing the cycle time of the ALD process. Timing of the flowing of the gases is critical in the ALD process. By having the fins **215** integrated into the gas mixer **200**, the volume of components that would mount the fins **215** in the gas mixer **200** is eliminated, reducing the volume of the gas mixer **200**. Therefore, the gas mixer **200** has the benefit of not slowing down the process by exposing the gases to extra volume compared to two-part mixers.

[0026] The fins **215** change the direction of a path that the gas flows through the hollow passage **201**, for example, by creating turbulent flow. The path starts in the inlet **203** in a Y-direction. The path changes direction at a fin **215** causing the path to move in a first X-direction. The path continues in the first X-direction until the path contacts the sidewall **216** causing the path to move in the Y-direction. The path contacts another fin **215** causing the path to move in a second X-direction. The path continues to change directions as described above until the path contacts the sidewall **216** for the last time. Finally, the path then moves in the Y-direction towards the outlet **205**. The amount of fins **215** is optimized to increase the efficiency of the ALD process. Increasing the number of fins **215** increases the mixing of the gases but also increases the amount of time required for the gases to reach the processing volume **114**. Decreasing the amount of fins **215** reduces the time required for the gases to reach the processing volume **114**, but too few fins **215** cannot ensure proper mixing. The type of gases used in the ALD process can affect the optimal amount of fins **215**. The hollow passage **201** may include three fins **215** to four fins **215**, such as four fins **215**. The changing of direction of the path causes the gases to be mixed when flowing through the path of the hollow passage **201**. This mixing reduces the length required for the gas mixer **200**.

[0027] FIG. 2B is a schematic, isometric view of a gas mixer **200**. FIG. 2B illustrates the inlet **203** and a plurality of fastener ports **223** extend from the first surface **209** of the gas mixer **200** to the second surface **213**. The fastener ports **223** are configured to attach the first surface **209** to the gas lines and/or the gas assembly **211**. The fastener ports **223** are also configured to attach the second surface **213** to the gas box **104** of the processing chamber **100**. The interior section **207** is between the first surface **209** and second surface **213**. The hollow passage **201** is disposed through the interior section **207**. FIG. 2B illustrates the gas mixer **200** having a body with a cylindrical shape. The cylindrical shape has a diameter **225** that is determined based on design constraints and space availability above the process chamber **100**. The cylindrical shape has a mixer thickness **227** that is determined based on design constraints and space availability above the process chamber **100**. In some embodiments, the gas mixer **200** has a different shape (e.g., rectangular, oval, polygonal, etc.).

[0028] The gas mixer **200** is formed from a ceramic material. In various embodiments, the ceramic material includes at least one of aluminum oxide (Al.sub.2O.sub.3), aluminum nitride (AlN), or a

similar material. The ceramic material allows the gas mixer **200** to act as a barrier between the RF hot gas box **104** of the processing chamber **100** and the RF ground gas assembly **211**. The ceramic material allows a voltage difference to exist between the gas box **104** (e.g., held at a higher voltage) and the gas assembly **211** (e.g., held at a lower voltage). When performing the cleaning process with fluorine radicals, surface recombination is an issue. Surface recombination causes two fluorine radicals to combine into fluorine gas when coming into contact with a surface. Fluorine gas does not react with the unwanted deposited material removed during the cleaning process. Therefore, fluorine gas reduces the cleaning efficiency of the cleaning process. The ceramic material reduces the surface recombination increasing the cleaning efficiency. Ceramic materials cause surface recombination at a rate that is significantly slower than aluminum materials (e.g., less than 10% the rate of surface recombination in aluminum materials). In some embodiments, the gas mixer **200** is formed from an aluminum alloy.

[0029] The gas mixer **200** is formed in an additive manufacturing process (e.g., 3D printing). The additive manufacturing process allows for internal features (e.g., the fins **215**) to be formed in the gas mixer **200**. Conventional manufacturing cannot form such internal features in the gas mixer **200**. Accordingly, processes such as 3D printing reduce the cost and lead time of manufacturing the gas mixer **200**. The 3D printing process may form a gas mixer **200** that has a purity of material greater than or equal to 99.5%, such as 99.8%. Such a high purity allows for lower defects on the substrate **101**, better material properties, and reduction of a risk of outgassing.

[0030] FIG. **3** is a flow diagram of a method **300** for mixing gases. At operation **301**, the inlet **203** of the gas mixer **200** is fluidly connected to the plurality of gas lines and the outlet **205** of the gas mixer **200** is fluidly connected to the port **106** of the processing chamber **100**. The gas mixer **200** is described in FIGS. **2A** and **2B**.

[0031] At operation **303**, the first gas and the second gas are flowed into the gas mixer **200**. The first gas and the second gas flow to the inlet **203** of the gas mixer **200**. During the deposition process, the first gas is the precursor gas, and the second gas is the purge gas. During the cleaning process, the first gas is the purge gas, and the second gas is the cleaning gas. The first gas flows from the first gas source **128** to the inlet **203** via the first gas line **132**. The second gas flows from the second gas source **130** to the inlet **203** via the second gas line **134**. The path that the gases enter the inlet **203** is in the Y-direction. The first gas and the second gas are mixed in the gas mixer **200**. The gases are mixed by flowing through the path of the hollow passage **201**. The gases are mixed while changing directions in the hollow passage **201**. The plurality of fins **215** change the direction of the hollow passage **201**. The path of the gases through the hollow passage **201** is described in FIG. **2A**. The gases undergo turbulent flow. The gas mixer **200** produces a mixed gas. The mixed gas then moves in the Y-direction towards the outlet **205**.

[0032] At operation **305**, the mixed gas flows out the gas mixer **200** into the processing volume **114**. After moving towards the outlet **205**, the mixed gas exits the gas mixer **200** through the outlet **205**. Further, the mixed gas passes through the outlet **205** into the port **106**. After passing through the port **106**, the mixed gas enters the showerhead volume **136**. The mixed gas travels through the showerhead volume **136** to the showerhead **110**. At the showerhead **110**, the mixed gas travels through the openings **112** into the processing volume **114**. During the depositing process, the mixed gas then is used in processing to deposit material on the substrate **101**. During the cleaning process, the mixed gas cleans the surfaces the mixed gas contacts.

[0033] In summation, embodiments of the present disclosure generally relate to mixing gases for deposition processes, such as atomic layer deposition. Specifically, the disclosure relates to a single piece gas mixer that mixes a plurality of gases prior to the gases entering the processing chamber. The gas mixer integrates the mixer and spacer by using fins in a hollow passage. The gas mixer is formed in an additive manufacturing process. Benefits of the gas mixer include reducing the risk of particle generation and reducing the risk of damage. The gas mixer has increased repairability and cannot become tilted due to the gas mixer being one continuous part. The additive manufacturing

process used to form the gas mixer reduces the cost and lead time of forming the gas mixers.
[0034] While the foregoing is directed to embodiments of the present disclosure, other and further embodiments of the disclosure may be devised without departing from the basic scope thereof, and the scope thereof is determined by the claims that follow.

Claims

1. A mixer, comprising: a body; an inlet; an outlet; a hollow passage disposed through the body and fluidly connecting the inlet to the outlet, the hollow passage comprising a sidewall; and a plurality of fins formed on the sidewall and extending into the hollow passage, wherein the plurality of fins and the sidewall form a monolithic structure.
2. The mixer of claim 1, wherein the plurality of fins cause a gas traveling through the hollow passage to cross a center axis of the hollow passage, the center axis extending from the inlet to the outlet.
3. The mixer of claim 1, wherein each fin in the plurality of fins comprises: a first surface extending from the sidewall at a first angle; a second surface extending from the sidewall at a second angle, the second surface opposite the first surface; and an edge surface connecting the first surface to the second surface, the edge surface opposite the sidewall and positioned within the hollow passage.
4. The mixer of claim 3, wherein: the first angle is between 80 degrees and 100 degrees; and the second angle is between 30 degrees and 70 degrees.
5. The mixer of claim 3, wherein: the first angle is between 85 degrees and 95 degrees; and the second angle is between 40 degrees and 65 degrees.
6. The mixer of claim 1, wherein the plurality of fins includes at least three fins.
7. The mixer of claim 1, wherein the body comprises a ceramic material, the ceramic material reducing surface recombination of radicals in a gas configured to pass through the hollow passage.
8. The mixer of claim 1, wherein the monolithic structure is formed using an additive manufacturing process.
9. A processing chamber, comprising: a chamber body defining a processing volume, the chamber body comprising: a gas box having a port; and a bottom; a mixer disposed on the gas box and fluidly connected to the port, the mixer comprising: a body; an inlet; an outlet fluidly connected to the processing volume of the chamber body; a hollow passage disposed through the body and fluidly connecting the inlet to the outlet, the hollow passage comprising a sidewall; and a plurality of fins formed on the sidewall and extending into the hollow passage, wherein the plurality of fins and the sidewall form a monolithic structure; and a plurality of gas lines fluidly connected to the inlet of the mixer.
10. The processing chamber of claim 9, wherein the plurality of fins cause a gas traveling through the hollow passage to cross a center axis of the hollow passage, the center axis extending from the inlet to the outlet.
11. The processing chamber of claim 9, wherein each fin in the plurality of fins comprises: a first surface extending from the sidewall at a first angle; a second surface extending from the sidewall at a second angle, the second surface opposite the first surface; and an edge surface connecting the first surface to the second surface, the edge surface opposite the sidewall and positioned within the hollow passage.
12. The processing chamber of claim 11, wherein: the first angle is between 80 degrees and 100 degrees; and the second angle is between 110 degrees and 150 degrees.
13. The processing chamber of claim 9, wherein the plurality of gas lines are disposed in a gas assembly, the plurality of gas lines configured to flow a plurality of gases towards the inlet of the mixer.
14. The processing chamber of claim 13, wherein the plurality of gases includes a precursor gas

and a purge gas.

15. The processing chamber of claim 14, wherein a gas line for the precursor gas enters the inlet at an angle relative to a first direction, and a gas line for the purge gas enters the inlet in the first direction.

16. The processing chamber of claim 9, wherein the mixer comprises a ceramic material.

17. A method of mixing gases, comprising: fluidly connecting an inlet of a mixer to a plurality of gas lines; fluidly connecting an outlet of the mixer to a port of a processing chamber, the mixer comprising: a body; the inlet; the outlet; a hollow passage disposed through the body and fluidly connecting the inlet to the outlet, the hollow passage comprising a sidewall; and a plurality of fins formed on the sidewall and extending into the hollow passage, wherein the plurality of fins and the sidewall form a monolithic structure; flowing a first gas and a second gas through the gas lines and into the mixer to produce a mixed gas; and flowing the mixed gas through the outlet of the mixer and into a processing volume of the processing chamber.

18. The method of claim 17, further comprising performing at least one deposition process with the mixed gas, the first gas comprising a precursor gas, and the second gas comprising a purge gas.

19. The method of claim 17, further comprising performing at least one cleaning process with the mixed gas, the first gas comprising a purge gas, and the second gas comprising a cleaning gas.

20. The method of claim 17, further comprising, prior to flowing the mixed gas through into the processing volume, passing the mixed gas through the outlet to the port of the processing chamber and through a showerhead disposed in the processing chamber.
