

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250277420

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

El Mallawany; Ibrahim et al.

SPLICE FREE FEEDTHROUGH MECHANICAL PACKER

Abstract

Disclosed herein are embodiments of an apparatus and method related to a splice-free feedthrough mechanical packer. In one embodiment, an apparatus to be positioned in a wellbore comprises a packer mandrel; and a packing element assembly including at least a packing element and an interior channel; wherein a continuous control line is configured to be installed external to the packer mandrel and positioned in the interior channel of the packing element assembly without being spliced.

Inventors: El Mallawany; Ibrahim (Al-Khobar, SA), Perez; Eddie (Dhahran, SA)

Applicant: Halliburton Energy Services, Inc. (Houston, TX)

Family ID: 96880970

Appl. No.: 18/594360

Filed: March 04, 2024

Publication Classification

Int. Cl.: E21B23/06 (20060101); E21B33/129 (20060101)

U.S. Cl.:

CPC E21B23/06 (20130101); E21B33/129 (20130101);

Background/Summary

FIELD OF THE DISCLOSURE

[0001] Some implementations relate generally to the field of downhole tools positioned in a wellbore completion and more particularly to the field of mechanical packers in wellbore

completions.

BACKGROUND

[0002] When a well is completed, prior to production, a completion string is run into the well. On run in the string must be open to allow fluid to flow up the tubing of the string. The tubing must be sealed so that sufficient downhole pressure can be created to set the production packer mounted on the string and together provide a downhole barrier. The barrier thus allows pressure testing to be undertaken prior to the tubing string being opened so that produced oil can flow up the completion string to the surface. Control lines may be run through various downhole tools. Control lines may need to run along and downhole of a packer, but certain packers may not allow the control line to be positioned external to the packing element or may require splicing if fed internal of the packer element. What is needed is a control line that can be fed through and positioned internal to a packing element without needing to splice the control line.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0003] Implementation of the disclosure may be better understood by referencing the accompanying drawings.

[0004] FIG. 1 is a diagrammatic illustration of an example well system, according to some implementations.

[0005] FIG. 2A is a perspective view of one embodiment of a mechanical packer and a lower assembly thereof, according to some implementations.

[0006] FIG. 2B-2C are side view of the mechanical packer shown in FIG. 2A.

[0007] FIG. 3 is a diagrammatic illustration of a rig for installation of wellbore components, according to some implementations.

[0008] FIG. 4 is a side view of a packing element assembly of a packer, according to some implementations.

[0009] FIG. 5A-5C are perspective and side views of the packer, showing installation of the packing element assembly onto the lower assembly, according to some implementations.

[0010] FIG. 6 is a perspective view of the assembled packer, according to some implementations.

[0011] FIGS. 7A and 7B are perspective views of a sealing element, according to some implementations.

[0012] FIG. 8 is a perspective view of a packer with the sealing element, according to some implementations.

[0013] FIG. 9 is a side view of a sealing and locking element, according to some implementations.

[0014] FIG. 10A-10F are side views of a sealing and locking element for a packer, at different stages of installation, according to some implementations.

[0015] FIG. 11 is a diagrammatic illustration of a rig for installation of wellbore components, according to some implementations.

[0016] FIG. 12A-12C are perspective views of another embodiment of a packing element assembly for a packer, according to some implementations.

[0017] FIG. 13 is a flowchart illustrating a method, according to some implementations.

DESCRIPTION

[0018] The description that follows includes example systems, methods, techniques, and program flows that embody aspects of the disclosure. However, it is understood that this disclosure may be practiced without these specific details. For instance, this disclosure refers to one or more components configured to induce vibrations for an impulse turbine in a wellbore. Aspects of this disclosure can also be applied to other components and/or a combination of components configured to induce vibrations for an impulse turbine positioned in wellbore. For clarity, some well-known

instruction instances, protocols, structures, and techniques have been omitted.

[0019] In the drawings and descriptions that follow, like parts are typically marked throughout the specification and drawings with the same reference numerals, respectively. The drawn figures are not necessarily to scale. Certain features of the disclosure may be shown exaggerated in scale or in somewhat schematic form and some details of certain elements may not be shown in the interest of clarity and conciseness. The present disclosure may be implemented in embodiments of different forms.

[0020] Unless otherwise specified, use of the terms “connect,” “engage,” “couple,” “attach,” or any other like term describing an interaction between elements is not meant to limit the interaction to a direct interaction between the elements and may also include an indirect interaction between the elements described. Unless otherwise specified, use of the terms “up,” “upper,” “upward,” “uphole,” “upstream,” or other like terms shall be construed as generally away from the bottom, terminal end of a well; likewise, use of the terms “down,” “lower,” “downward,” “downhole,” or other like terms shall be construed as generally toward the bottom, terminal end of the well, regardless of the wellbore orientation. Use of any one or more of the foregoing terms shall not be construed as denoting positions along a perfectly vertical axis. In some instances, a part near the end of the well can be horizontal or even slightly directed upwards. Unless otherwise specified, use of the term “subterranean formation” shall be construed as encompassing both areas below exposed earth and areas below earth covered by water such as ocean or fresh water.

[0021] Feedthrough mechanical packers can be set quickly but require splicing or cutting of control lines. Splicing or cutting the control lines to be fed through or placed internal to the packing element may result in a leak path and/or be detrimental to the signal quality for fiber optic and electric lines. The splicing process also requires additional operational time on the rig floor during installation. Certain swell packers may provide control line feedthrough without splicing, but swelling time is not fully controlled which may delay rig operations. There is currently no solution for a splice free feed-through of control lines for mechanical packer applications.

[0022] Provided herein are embodiments of mechanical packers having feedthrough control lines fed through and internal to the packing element without the need for cutting or splicing. The feedthrough packers disclosed herein provide for the mechanical setting of the packers to be quicker and on demand, as opposed to swell packers. Non-spliced or cut control lines improve the signal for fiber optic and electric lines, and minimize leak paths for hydraulic lines, thereby increasing overall reliability. Eliminating control line splicing may also reduce deployment/installation times. Embodiments of the feedthrough packers disclosed herein may be used with permanent mechanical packers and retrievable packers.

[0023] In one embodiment, a packer may include a packer mandrel and a packing element assembly, the packing element assembly including at least a packing element and an interior channel. A continuous control line is configured to be installed external to the packer mandrel and positioned in the interior channel of the packing element assembly without being spliced.

[0024] In another embodiment, a wellbore system includes a downhole tool and a packer positioned uphole of the downhole tool, the downhole tool coupled with a control line from the surface. The packer includes at least a packer mandrel and a packing element assembly, the packing element assembly including at least a packing element and an interior channel. A continuous control line is configured to be installed external to the packer mandrel and positioned in the interior channel of the packing element assembly without being spliced.

[0025] In another embodiment, there is a method. The method includes mounting a control line on a rig for installation into a wellbore, and inserting the control line, uncut or un-spliced, through a packing element assembly of a packer while the control line is mounted on the rig. The packing element assembly may include at least a packing element and an interior channel for positioning the control line therein. The packer may be positioned to be run into the wellbore, the packer including a packer mandrel. The control line may be laid externally over the packer mandrel and

then the packer element assembly is coupled with the packer mandrel.

Example Systems

[0026] FIG. 1 is a diagrammatic illustration of an example well system, according to some implementations. In particular, a well system **100** of FIG. 1 includes a wellbore **102** in a subsurface formation **101**. The wellbore **102** includes casing **104** and number of perforations **116**, **118** being made in the casing **104**. Each set of perforations **116**, **118** is located in a respective reservoir **130**, **132** to allow reservoir fluids (i.e., oil, water, and gas) from the respective reservoirs **130**, **132** to flow into the wellbore **102** and into the tubular string **106** (the production tubing or drill string). The tubular string **106** may include one or more packers, such as packer **112** and **114** that may prevent the comingling of fluids produced from the reservoirs **130**, **132** in the wellbore **102**. A production assembly **108** may allow the inflow of fluid produced from the reservoir **130** into the tubular string **106**. Likewise, a production assembly **110** may allow the inflow of fluid produced from the reservoir **132** into the tubular string **106**.

[0027] Each of the production assemblies **108**, **110** may include one or more downhole tools (not pictured). Some examples of downhole tools may include inflow control valves (ICVs), permanent downhole gauges, chemical injection mandrels, fiber optic sensors, and more. In some implementations, the downhole tools may be configured to control the flow of fluid produced from the reservoirs **130**, **132** and into the tubular string **106**. In some implementations, each of the production assemblies **108**, **110** may also include electronics to control (e.g., for controlling timing, directionality, and/or voltage threshold for powering and/or activating the downhole tool) the respective downhole tools. Control lines may be run downhole to the production assemblies. In many implementations, the control lines may include fiber optic and electric lines to power and communicate with permanent downhole gauges. In some embodiments, the control lines may include a plurality of individual control lines, or may be bundled into a pack or conduit, such as a flatpack.

[0028] Provided herein are embodiments of mechanical packers having feedthrough control lines fed through and internal to the packing element without the need for cutting or splicing. The packer may have a central packer mandrel and a packing element assembly configured to receive the control lines internal to the packing element assembly. Some examples may also include a lower assembly, which may include an external channel for receiving the control line therein and may also include traditional components of a packer including a setting piston, an upper cone, an anchoring element, such as slips, and a lower cone. The packing element assembly includes at least a packing element and an internal channel for the control line, and may in some examples include an element mandrel beneath the packing element and a sleeve, wherein the sleeve engages the setting piston when the packing element assembly is coupled with the lower assembly. The packer may also include an anti-preset and locking mechanism such as included with traditional mechanical packers.

Example Assembly

[0029] FIG. 2A-2C illustrates one embodiment of a mechanical packer **200**. The packer **200** includes a tubing or packer mandrel **202** having a lower assembly **204** coupled thereabout. The packer **200** includes a packing element assembly, which will be shown in FIG. 4 and FIG. 5A-5C and described herein, wherein the packing element assembly will include at least a packing element and an interior channel. The packer **200** may include at least a setting element, which in this embodiment is a setting piston **206** of the lower assembly **204**. The piston **206**, in this embodiment, includes a central member **208** with upper cylinders or rods **210**, and lower cylinders or rods **212** on each side of the central member **208**. Positioned below, or downhole of the piston **206** is an anchoring element **216** for anchoring the packer **200** with the wellbore casing. The anchoring element **216** may be slips as shown in FIG. 2A. The anchoring element **216** may be positioned between an upper cone **214** and a lower cone **218**.

[0030] One or more control lines **220** will be laid over the lower assembly **204** of the packer **200**

externally such that the control lines **220** connected with one or more downhole tools positioned downhole of the packer **200** can be fed through without splicing. The control line **220** may include one or more individual control lines or may be a flat pack with a plurality of control lines (hydraulic, electric, and/or fiber optic lines) contained within. Each of the components of the lower assembly **204** may be constructed with at least one external channel for receiving the control line **220** on an external surface. The piston **206** may include one or more longitudinal channels **209** in an external surface of the central member **208** thereof. The upper cone **214** may include one or more openings or channels **215** in at least a portion of its external surface. The anchoring element **216**, slips in this example, may be segmented such that there is one or more openings **217** between the slips such that the control line **220** may lay between two of the slips. The lower cone **218** may include a similar longitudinal channel **219** for the control line **220**. Although the packer **200** illustrated is a retrievable packer with certain activation components thereof, the disclosure may be implemented on any variation of a mechanical packer, such as packers that do not have an anchoring element, and packers having different setting element configurations and features.

[0031] FIG. 2B and 2C are side view of the lower assembly **204** and illustrate additional features such as a pressure port **226** in the mandrel **202** and a shear pin or shear ring **228** which illustrate certain features related to pressure setting the packer **200**. Fluid internal of mandrel **202** may enter the pressure port **226** and pressure to apply a hydraulic force on pistons **210** and **212**. The upper rods **210** will push upward to engage the packing element and the lower rods **212** will push downward and engage the upper cone **214**, which will engage the anchor element **216**. Shear pin **228** may hold the lower cone **218** in place to prop up anchor element **216** as upper cone **214** is pushed down. Once engaged by both the upper cone **214** and the lower cone **218**, the anchor element **216** will move radially outward and engage a casing of the wellbore to anchor the packer **200** inside the casing.

[0032] FIG. 3 is a perspective view of a rig **300** for installing tools into a wellbore. During preparation for an intelligent completion string to be run in hole, the control line **220** or flatpack will be mounted on the rig **300** and spooling **304**, and fed through a sheave **302**. The control line **220** may also be fed through one or more packing element assemblies **240**. There will be a packing element assembly **240** for each packer to be installed downhole. The packing element assemblies **240** may be secured to the rig **300** in a way to ensure the packing elements do not get damaged.

[0033] FIG. 4 is a side view of a packing element assembly **240** to be positioned onto a packer, such as packer **200**, which may be being prepared to be run in hole. The packing element assembly **240** may also be called an element cartridge. The packing element assembly **240** may include an element mandrel **242** with a packing element **244** installed about the element mandrel **242**. The packing element assembly **240** may also include a sleeve **246** for engaging and coupling with the packer mandrel **202**, and in some examples engage the lower assembly **204**. The packing element assembly **240** is configured to position the control line **220** internal to the packing element assembly, positioned at least between the packing element **244** and the packer mandrel, such as packer mandrel **202**. In this embodiment, the control line **220** is also positioned internal to the element mandrel **242**. In some examples, the packing element assembly **240** may include one or more components for setting the packing element, but in the illustrated example, the packing element is set by the setting piston of the lower assembly **204**.

[0034] FIG. 5A-FIG. 5C illustrate different stages of installation of the control line **220** and packing element assembly onto the lower assembly **204** of packer **200**. In FIG. 5A, there is shown a perspective view of the packing element assembly **240**. The element mandrel **242** includes an internal groove or channel **250** on an inner surface thereof to fit the control line **220** or flat pack therein. When it is time to run the packer **200** in hole, the control line **220** will be laid over the packer mandrel **202** and externally over the lower assembly **204** as shown in FIG. 5A. Next, the packing element assembly **240** will be lowered onto the lower assembly **204** of the packer **200**. The packing element assembly **240** will then be mounted onto the packer mandrel **202** and pushed onto

the lower assembly **204** until the sleeve **246** shoulders onto and engages the piston assembly **206** as shown in FIG. 5B.

[0035] FIG. 5C is a side view showing the control line **220** positioned internally to the packing element assembly and external to the lower assembly. As shown, the control line **220** is positioned internal to the packing element assembly **240**, positioned between the packing element **244** and the packer mandrel **202**, and external to the lower assembly **204**. In some embodiments, the control line **220** may run between two of the upper rods **210** and similarly between two of the lower rods (although not shown in FIG. 5C). When the packer **200** is set, the upper rods **210** of the setting piston will engage the sleeve **246**, which may, in some examples, push uphole to engage the packing element **244** axially outward into engagement with the wellbore casing. The packer illustrated herein is a tubing conveyed packer and may be set by tubing pressure, but the packing element assembly and external channel of the lower assembly may be adapted for various types of mechanical packers.

[0036] Referring now to FIG. 6, after the packing element assembly **240** is positioned and engaged with the lower assembly, a locking element may be positioned about the packer mandrel **202** to axially lock the packing element assembly **240** into place. In this example, the locking element is a snap ring **252** positioned at an uphole end of the packing element assembly **240** to lock the packing element assembly **240** (element cartridge) in place to prevent movement thereof. In this example, the snap ring **252** is engaged with the element mandrel **242**.

[0037] Referring now to FIG. 7A-FIG. 7B, there is shown a sealing member **760**. The sealing member **760** may be placed between the packer mandrel and the packing element in order to seal the control lines or flatpack. In this example, the sealing member **760** may include a ring **764** with a housing **766** on an external surface thereof for receiving the control lines or flatpack. The housing **766** may include at least split **768** for placing the control line into the housing **766**. The ring **764** and housing **766** may comprise one or more of any combination of elastomers, metals, and polymers, such as polyether ether ketone (PEEK) materials for anti-extrusion or other suitable materials. The metals may comprise a first portion and the peek materials may comprise an adjacent portion. The sealing member **760** in this example may also include an elastomer portion **770** for sealing the control line. The elastomer portion **770** may also include at least one split **772**. Although the elastomer portion **770** is shown in FIG. 7B to include a ring, the elastomer portion may in some examples, comprise only a portion of the housing. Ideally the elastomer **770** may be a swellable rubber so it can have a slight clearance for ease of installation and then would swell when submerged in downhole fluids and create a seal when downhole. The seal prevents any pressure communication through the path created by the opening/channels for the control line.

[0038] FIG. 8 is a perspective view of the packer **200** showing the sealing member **760** being installed about the packer mandrel **202** uphole of the packing element assembly **240** and about the control line **220**.

[0039] As shown in FIG. 9, the ring **764** is positioned about the packer mandrel **202**. The ring **764** may engage and be positioned within an uphole end of the element mandrel **242**. The elastomer portion **770** will surround the control line **220** and provide a seal between the packer **200** and the control line.

[0040] FIG. 10A-FIG. 10F illustrate another embodiment of a sealing and locking element **1060** and installation of the control line **220** with a packer. In this embodiment, the sealing and locking element **1060** are combined as a seal ring **1004** which uses a back up ring **1001** retained with a threaded cap **1002**. The packing element assembly with the sealing and locking element **1060** as shown in FIG. 10A will be on the rig without the seal and is lowered over the packer mandrel **202** as shown and described above in at least FIG. 5A-FIG. 5C above. If installed the threaded cap **1002** is removed as shown in FIG. 10B and the back up ring **1001** is removed as shown in FIG. 10C. The seal **1004** may then be installed about the control line **220**, over packer mandrel **202** and under element mandrel **242** as shown in FIG. 10D. The back up ring **1001** is then lowered to capture the

seal ring **1004** as shown in FIG. **10E**. Note that back up ring **1001** has a slot (not shown) for the control line **220** and does not spin during assembly. As shown in FIG. **10F**, the threaded cap **1002** is then re-attached and assembly of the sealing and locking element **1060** with the packer is complete. [0041] FIG. **11** illustrates another embodiment of an installation rig **1100** for installing one or more packing element assemblies **242** (element cartridges) onto mechanical packers placed within a wellbore. In this embodiment, instead of loading the packing element assemblies **240** after the sheave **1102**, the packing element assemblies **240** may be installed on a spool **1104** prior to deployment of the rig **1100**. In this example, the control line **220** must be taken out of the sheave **1102** during packer installation then remounted on the sheave **1102**. Sheave **1102** may be designed in a way to facilitate removal and installation of the control line **220**.

[0042] FIG. **12A**-FIG. **12C** illustrate another alternate embodiment of a packing element assembly **1240** to be coupled with a packer. In this embodiment, instead of having a packer element on a small mandrel as described in examples shown in FIG. **4**-FIG. **5C** above, an element **1244** may have an inner diameter (ID) cutout in the components of the element **1244** to house the control line **220** (flatpack or individual control lines). FIG. **12A** is a cutaway view of the internal side of the element **1244**. FIG. **12B** and **12C** are perspective views. In this embodiment, a locking element is still needed to prevent lateral movement of the packer element after installation.

[0043] FIG. **13** illustrates a method **1300** for preparing a feedthrough mechanical packer for installation into a wellbore. In a block **1302**, a control line is mounted on a rig for installation into a wellbore. In a block **1304**, the control line is fed through at least one packing element assembly of a packer, the packing element assembly including at least a packer element, and wherein the control line is positioned within an interior channel of the packing element assembly.

[0044] In a block **1306**, a lower assembly of the packer is positioned into the wellbore. The lower assembly may include at least a packer mandrel and an anchoring element, and have at least one external channel configured to receive the control line therein. In a block **1308**, the control line is laid externally over the lower assembly into the external channel.

[0045] In a block **1310**, the packing element assembly is placed over the packer mandrel and coupled with the lower assembly. In a block **1312**, a sealing element may also be placed about the control line. In a block **1314**, the packing element assembly is locked into place to prevent lateral movement. In some examples, the lock and sealing element may comprise different components, and in other examples, may be one integral component with a locking element and a sealing element.

[0046] Blocks **1304** through **1314** may be repeated for other packers to be installed in the wellbore.

[0047] While the aspects of the disclosure are described with reference to various implementations and exploitations, it will be understood that these aspects are illustrative and that the scope of the claims is not limited to them. Many variations, modifications, additions, and improvements are possible.

[0048] Plural instances may be provided for components, operations or structures described herein as a single instance. Finally, boundaries between various components, operations and data stores are somewhat arbitrary, and particular operations are illustrated in the context of specific illustrative configurations. Other allocations of functionality are envisioned and may fall within the scope of the disclosure. In general, structures and functionality presented as separate components in the example configurations may be implemented as a combined structure or component. Similarly, structures and functionality presented as a single component may be implemented as separate components. These and other variations, modifications, additions, and improvements may fall within the scope of the disclosure.

[0049] Various modifications to the implementations described in this disclosure may be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other implementations without departing from the spirit or scope of this disclosure. Thus, the claims are not intended to be limited to the implementations shown herein but are to be accorded

the widest scope consistent with this disclosure, the principles and the novel features disclosed herein.

[0050] Certain features that are described in this specification in the context of separate implementations also may be implemented in combination in a single implementation. Conversely, various features that are described in the context of a single implementation also may be implemented in multiple implementations separately or in any suitable subcombination. Moreover, although features may be described as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination may in some cases be excised from the combination, and the claimed combination may be directed to a subcombination or variation of a subcombination.

[0051] Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. Further, the drawings may schematically depict one more example process in the form of a flow diagram. However, some operations may be omitted and/or other operations that are not depicted may be incorporated in the example processes that are schematically illustrated. For example, one or more additional operations may be performed before, after, simultaneously, or between any of the illustrated operations. In certain circumstances, multitasking and parallel processing may be advantageous. Moreover, the separation of various system components in the implementations described should not be understood as requiring such separation in all implementations, and the described program components and systems may generally be integrated together in a single software product or packaged into multiple software products. Additionally, other implementations are within the scope of the following claims. In some cases, the actions recited in the claims may be performed in a different order and still achieve desirable results.

Example Implementations

[0052] Aspects disclosed herein include:

[0053] Aspect A: An apparatus to be positioned in a wellbore, the apparatus comprising a packer mandrel; and a packing element assembly including at least a packing element and an interior channel. A continuous control line is configured to be installed external to the packer mandrel and positioned in the interior channel of the packing element assembly without being spliced.

[0054] Aspect B: A system for use in a wellbore, comprising a downhole tool; a control line extending from an uphole end of the wellbore and coupled to the downhole tool; and a packer positioned above the downhole tool, the packer comprising: a packer mandrel; and a packing element assembly including at least a packing element and an interior channel. A continuous control line is configured to be installed external to the packer mandrel and positioned in the interior channel of the packing element assembly without being spliced.

[0055] Aspect C: A method comprising mounting a control line on a rig for installation into a wellbore; inserting the control line through a packing element assembly of a packer while the control line is mounted on the rig, the packing element assembly including at least a packing element and an interior channel for positioning the control line therein; positioning the packer to be run into the wellbore, the packer including a packer mandrel; laying the control line over the packer mandrel; and coupling the packing element assembly with the packer mandrel

[0056] Aspects A, B, and C may have one or more of the following additional elements in combination:

[0057] Element 1: further comprising a locking element positioned about the packer mandrel to axially lock the packing element assembly.

[0058] Element 2: wherein the locking element is a snap ring.

[0059] Element 3: wherein the locking element includes a back up ring and a threaded cap.

[0060] Element 4: further comprising a sealing member positioned between the packing element assembly and the packer mandrel.

[0061] Element 5: wherein the sealing member includes a ring and a housing positioned on an external surface of the ring, wherein the housing has at least one split which opens for receiving the control line therein.

[0062] Element 6: wherein the housing comprises at least one of an elastomer portion, a metal portion, and a polymer portion.

[0063] Element 7: further comprising a lower assembly, the lower assembly positioned about the packer mandrel and including at least one external channel, wherein the continuous control line is configured to be installed in the at least one external channel.

[0064] Element 8: wherein the lower assembly further includes an anchor element, a setting piston and an upper cone positioned above the anchor element, and a lower cone positioned below the anchor element.

[0065] Element 9: wherein the packing element assembly is mounted on the rig.

[0066] Use of the phrase “at least one of” preceding a list with the conjunction “and” should not be treated as an exclusive list and should not be construed as a list of categories with one item from each category, unless specifically stated otherwise. A clause that recites “at least one of A, B, and C” can be infringed with only one of the listed items, multiple of the listed items, and one or more of the items in the list and another item not listed.

[0067] As used herein, the term “or” is inclusive unless otherwise explicitly noted. Thus, the phrase “at least one of A, B, or C” is satisfied by any element from the set {A, B, C} or any combination thereof, including multiples of any element.

Claims

1. An apparatus to be positioned in a wellbore, the apparatus comprising: a packer mandrel; and a packing element assembly including at least a packing element and a channel positioned along an interior surface of the packing element assembly; wherein a continuous control line is configured to be installed external to the packer mandrel and positioned in the channel of the packing element assembly without being spliced.

2. The apparatus according to claim 1, further comprising a locking element positioned about the packer mandrel to axially lock the packing element assembly.

3. The apparatus according to claim 2, wherein the locking element is a snap ring.

4. The apparatus according to claim 2, wherein the locking element includes a back up ring and a threaded cap.

5. The apparatus according to claim 1, further comprising a sealing member positioned between the packing element assembly and the packer mandrel.

6. The apparatus according to claim 5, wherein the sealing member includes a ring and a housing positioned on an external surface of the ring, wherein the housing has at least one split which opens for receiving the control line therein, and wherein the housing comprises at least one of an elastomer portion, a metal portion, and a polymer portion.

7. The apparatus according to claim 1, wherein the packing element assembly further includes an element mandrel and the channel is positioned along an interior surface of the element mandrel.

8. The apparatus according to claim 1, further comprising a lower assembly, the lower assembly positioned about the packer mandrel and including at least one external channel, wherein the continuous control line is configured to be installed in the at least one external channel.

9. The apparatus according to claim 8, wherein the lower assembly further includes an anchor element, a setting piston and an upper cone positioned above the anchor element, and a lower cone positioned below the anchor element.

10. A system for use in a wellbore, comprising: a downhole tool; a continuous control line extending from an uphole end of the wellbore and coupled to the downhole tool; and a packer positioned above the downhole tool, the packer comprising: a packer mandrel; and a packing

element assembly including at least a packing element, and a channel positioned along an interior surface of the packing element assembly; wherein the continuous control line is configured to be installed external to the packer mandrel and positioned in the channel of the packing element assembly without being spliced.

11. The system according to claim 10, further comprising a locking element positioned about the packer mandrel to axially lock the packing element assembly in place.

12. The system according to claim 11, wherein the locking element is one of a snap ring and a back up ring and threaded cap.

13. The system according to claim 10, further comprising a sealing member positioned between the packing element assembly and the packer mandrel.

14. The system according to claim 10, wherein the packer further includes a lower assembly positioned about the packer mandrel, the lower assembly including at least one external channel, wherein the continuous control line is configured to be installed in the at least one external channel.

15. A method, the method comprising: mounting a control line on a rig for installation into a wellbore; inserting the control line through a packing element assembly of a packer while the control line is mounted on the rig, the packing element assembly including at least a packing element and a channel along an interior surface of the packing element assembly for positioning the control line therein; positioning the packer to be run into the wellbore, the packer including a packer mandrel; laying the control line over the packer mandrel; and coupling the packing element assembly with the packer mandrel.

16. The method according to claim 15, wherein the packing element assembly is mounted on the rig.

17. The method according to claim 15, further comprising sealing the control line, wherein sealing the control line includes placing a sealing member between the packer mandrel and the packing element assembly.

18. The method according to claim 17, wherein the sealing member includes a ring and a housing positioned on an external surface of the ring, wherein the housing has at least one split which opens for receiving the control line therein, and wherein the housing comprises at least one of an elastomer portion, a metal portion, and a polymer portion.

19. The method according to claim 15, further comprising securing the packing element assembly into a fixed position by placing a locking element about the packer mandrel.

20. The method according to claim 15, wherein the packer further includes a lower assembly positioned about the packer mandrel, the lower assembly including at least one external channel, wherein the control line is configured to be installed in the at least one external channel.
