

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250283366

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

DUER; Stefan

ARRANGEMENT FOR MOVING AT LEAST ONE COVERING ELEMENT

Abstract

An arrangement has a guide device within a cavity of a furniture part, a support to be moved along the guide device, and a pivoting device. The covering element can be mounted so as to be pivotable on the support by the pivoting device. The arrangement has a stabilizing device by which the covering element, during a movement along the guide device, can be held at a predetermined distance from the guide device and/or from a wall of the fixed furniture part. The wall delimits the cavity, wherein the stabilizing device comprises a coupling element which to be coupled to the covering element in each position of the covering element.

Inventors: DUER; Stefan (Schwarzach, AT)

Applicant: Julius Blum GmbH (Hoechst, AT)

Family ID: 88863337

Appl. No.: 19/215767

Filed: May 22, 2025

Foreign Application Priority Data

AT

A 50910/2022

Nov. 30, 2022

Related U.S. Application Data

parent WO continuation PCT/AT2023/060379 20231109 PENDING child US 19215767

Publication Classification

Int. Cl.: E05D15/58 (20060101); E05F3/20 (20060101); E05F7/00 (20060101)

Background/Summary

[0001] The present application is a continuation of International Application PCT/AT2023/060379 filed on Nov. 9, 2023. Thus, all of the subject matter of International Application PCT/AT2023/060379 is incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0002] The present invention relates to an arrangement for moving at least one covering element.

[0003] Furthermore, the invention relates to a piece of furniture and a furniture part with such an arrangement.

[0004] Such arrangements have the task of guiding and stabilizing a covering element, such as a sliding door or folding sliding door, and are already known from the prior art.

[0005] For example, AT 524607 A1 shows an arrangement for guiding a movable piece of furniture or covering element, wherein, in addition to a guide device, a separate additional guide mechanism is provided which ensures the direct guidance of the covering element on the fixed furniture part.

[0006] The disadvantage of this solution is that this additional guide mechanism requires the covering element to be coupled to the guide mechanism and thus to the furniture part, whereby errors or problems such as jamming and/or jerking can occur during coupling.

SUMMARY OF THE INVENTION

[0007] The task of the present invention is therefore to provide an arrangement that is an improvement on the prior art, which prevents malfunctions and ensures stable guidance of the covering element.

[0008] This task is solved by an arrangement, a piece of furniture with an arrangement, and a furniture part with an arrangement, as described below.

[0009] The improved arrangement according to the invention is an arrangement for moving at least one covering element, preferably a door or folding door, relative to a fixed furniture part, which has at least one, preferably shaft-shaped, cavity for receiving the covering element and at least one interior space which can be covered by the covering element at least in some areas. The arrangement comprises at least one guide device for translational movement of the covering element within the cavity, at least one carrier movable along the guide device, and at least one swivel device. The covering element can be mounted on the carrier by means of the swivel device so as to be pivotable about a pivot axis parallel to the carrier. The arrangement comprises at least one stabilizing device with which the covering element can be held at a predetermined distance from the guide device and/or a wall of the fixed furniture part which delimits the cavity when moving along the guide device. The stabilizing device comprises at least one coupling element which can be coupled to the covering element in every position of the covering element.

[0010] A first major advantage of the invention is that there is a permanent connection between the covering element and the furniture part, so that there is no need for any coupling or uncoupling operations and therefore no malfunctions can occur during coupling.

[0011] This means that there is a connection between the covering element and the furniture part at all times and in every position of the covering element in relation to the furniture component.

[0012] Another advantage of the invention is that, due to the continuous coupling provided by the stabilizing device, the distance between the covering element and the furniture part, in particular the distance between the covering element and a wall adjacent to the cavity of the furniture part,

can be kept constant when the covering element, in particular with the carrier on which the covering element is arranged, moves along the at least one guide device.

[0013] This means that the invention enables stabilization of the covering element, whereby the stabilization counteracts tilting of the covering element in particular, and whereby the covering element is stabilized in the fully lowered position of the covering element in the cavity by means of the stabilizing device, preferably at the front or outwardly facing area of the covering element.

[0014] In other words, during its movement between a fully retracted position in the cavity and a closed position in which the covering element at least partially conceals the interior of the furniture component, the covering element is stabilized and guided.

[0015] The stabilizing device can also be regarded as a type of guide due to its partial second guide device, whereby it guides the covering element during both translational and rotational movements.

[0016] The covering element is held, in particular during its translational movement along the guide device, at a predetermined distance from the guide device and/or from the furniture part and/or from a wall of the cavity of the furniture part, wherein the distance may result from the geometry and/or design of the stabilizing device.

[0017] The immediate beneficial effects of the invention are consistently precise and stable coupling and guidance of the covering element, which in turn enables component-friendly use with low component wear and smooth and pleasant operation of the arrangement by a user.

[0018] An arrangement according to the invention can be used in already known embodiments of the prior art, such as those described in the introductory part of the description, and can be installed subsequently.

[0019] It is particularly preferred that the stabilizing device has a cavity guide which is arranged or can be arranged on a wall of the cavity and is designed to support the coupling element in a displaceable manner, in particular translatorily parallel to the direction of movement of the covering element.

[0020] Preferably, the cavity guide is designed as a rail along which the coupling element can slide in a form-fitting manner.

[0021] Preferably, the cavity guide is designed so that the coupling element can be inserted into and/or removed from the cavity guide, preferably by means of an opening, for example at one end.

[0022] It is conceivable that an opening for inserting the coupling element is only temporary, in particular for installing the stabilizing device in a piece of furniture, and/or can be covered, e.g. by means of a cover.

[0023] It is particularly preferred that the stabilizing device has at least one cavity guide stop, and the cavity guide stop in particular limits relative movement of the coupling element with respect to the cavity guide.

[0024] It is particularly preferred that the stabilizing device has at least one coupling element stop, and the coupling element stop limits in particular a relative movement of the coupling element relative to the cavity guide.

[0025] The cavity guide stop and/or the coupling element stop can also act as a kind of abutment for at least one force storage member, whereby the force storage member can be charged and/or discharged.

[0026] For example, a force storage member in the form of a spring, such as a compression spring, can be tensioned and/or relaxed by means of the cavity guide stop and/or the coupling element stop.

[0027] In a preferred embodiment of the coupling element, the coupling element has two coupling element stops.

[0028] It is particularly preferred that the stabilizing device has a covering element guide which is arranged or can be arranged on the covering element and is designed to mount the coupling element so that it can be displaced, in particular in a translational manner.

[0029] Preferably, the covering element guide is designed as a rail along which the coupling

element can slide.

[0030] It is preferable for the covering element guide to be designed in such a way that the coupling element can be inserted and/or hooked into the covering element guide, preferably by means of an opening, for example at one end.

[0031] It is preferable for the covering element guide to be designed such that the coupling element, preferably in the middle of an opening, for example at one end, can be inserted and/or hooked into the covering element guide.

[0032] It is conceivable that an opening for inserting the coupling element is only temporary, in particular for installing the stabilizing device in a piece of furniture, and/or can be covered, e.g. by a cover.

[0033] It is preferable for the covering element guide to be designed so that it can be attached to the covering element, for example by a screw, snap-in, or adhesive mechanism.

[0034] It is particularly preferred that the stabilizing device has at least one covering element guide stop which limits relative movement of the coupling element relative to the covering element guide, in particular so that the coupling element cannot become unhooked and/or a force storage member can be charged and/or discharged.

[0035] In a preferred embodiment of the covering element guide, the at least one covering element guide stop is arranged at one end of the covering element guide. However, it can also be arranged at another location.

[0036] It is particularly preferred that at least one sliding element, preferably a rolling element, is provided, preferably which coupling element is designed to slide and/or roll in the cavity guide and/or the covering element guide.

[0037] It is particularly preferred that the coupling element consists of at least two coupling element parts, wherein at least two of the at least two coupling element parts are connected to each other by means of at least one hinge.

[0038] The hinge is particularly advantageous in that it allows relative rotational movement between the two coupling elements, with the axis of rotation being essentially parallel to the pivot axis of the covering element.

[0039] However, it is also conceivable that the hinge has more than one degree of freedom and/or is a ball hinge and/or a solid hinge.

[0040] It is particularly preferred that at least one of the at least two coupling element parts is a spacer element which is designed to maintain the specified distance between the covering element and the at least one guide device constant when the covering element moves along the guide device.

[0041] Preferably, the stabilizing device has at least one support element which is designed to support the coupling element, preferably the at least one spacer element of the coupling element, in such a way that the predetermined distance between the covering element and the guide device and/or the wall of the cavity is maintained when the covering element moves along the guide device.

[0042] Preferably, the support element is designed and/or arranged in such a way that the spacer element can be supported so that the specified distance is maintained.

[0043] It is particularly preferred that the stabilizing device has at least one force storage member which is designed at least to support a relative, in particular translational, movement of the coupling element for guiding the cavity and/or the covering element guide.

[0044] In a particularly preferred embodiment, the force storage member comprises a spring, in particular a compression spring, which is arranged around the coupling element and/or within the cavity guide.

[0045] Preferably, the at least one force storage member is arranged on the coupling element and/or on the cavity guide and/or on the covering element guide.

[0046] It is particularly preferred that the force member storage is arranged between the cavity

guide stop of the cavity guide and at least one coupling element stop of the coupling element, in particular wherein the cavity guide stop and/or the coupling element stop serves as an abutment for the force storage member.

[0047] It is possible that the stabilizing function for at least one force storage member includes stabilizing the covering element in an intermediate position of the covering element.

[0048] It is particularly preferred that the at least one force storage member has a locking function for locking the covering element in a closed position of the covering element.

[0049] It is possible that the at least one force storage member has a damping function for damping the movement of the coupling element.

[0050] It is particularly preferred that the at least one force storage member has a return effect on the covering element in the direction of a fully retracted position of the covering element.

[0051] Furthermore, protection is sought for a piece of furniture with at least one covering element, preferably a door or folding door, at least one fixed furniture part, which has at least one, preferably shaft-shaped, cavity for receiving the covering element and at least one interior space, which can be covered at least in part by the covering element. The piece of furniture has at least one arrangement as noted above for moving at least one covering element relative to the at least one furniture part.

[0052] In addition, protection is sought for a furniture part with at least one, preferably shaft-shaped, cavity for receiving a covering element, preferably a door or folding door, at least one interior space which can be covered by the covering element at least in some areas, and an arrangement as noted above for moving the covering element relative to the furniture part.

[0053] It is particularly preferred that the stabilizing device is arranged essentially in the middle and/or the upper half of the furniture part and/or the covering element so that the stabilizing device optimally counteracts the tilting of the covering element.

[0054] Preferably, the furniture part has a further compensation device for compensating a tilting moment of the carrier or of the covering element arranged thereon. Preferably, the compensation device has at least one cable pull device and/or a pivot lever mechanism.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0055] Further advantages and details of the invention will be apparent from the drawings, in which:

[0056] FIG. 1-2 are views of a first embodiment of an arrangement in an intermediate position of the covering element,

[0057] FIG. 3-4 are views of the first embodiment of an arrangement in a closed position of the covering element,

[0058] FIG. 5-6 are views of a first embodiment of a stabilizing device,

[0059] FIG. 7-13 show a sequence of movements of the first embodiment of an arrangement or of the first embodiment of a stabilizing device,

[0060] FIG. 14-17 show a sequence of movements of a second embodiment of an arrangement or a second embodiment of a stabilizing device,

[0061] FIG. 18-20 are views of a second embodiment of an arrangement in a closed position of the covering element,

[0062] FIG. 21-26 are views of the third embodiment of a stabilizing device, and

[0063] FIG. 27-33 show a sequence of movements of the second embodiment of an arrangement or a third embodiment of a stabilizing device.

DETAILED DESCRIPTION OF THE INVENTION

[0064] FIGS. 1 and 2 show views of a first embodiment of an arrangement 1 in an intermediate position 25 of the covering element 2, wherein FIG. 1 additionally shows a detailed view of the

connection point of a swivel device **8** on the carrier **7**. The stabilizing device **10** is not visible in these views because it is concealed by the covering element **2**.

[0065] FIG. **1** shows primarily those components that belong to the general state of the art. In particular, a furniture part **3** is shown with at least one, preferably shaft-shaped, cavity **4** for receiving a covering element **2**, preferably a door or folding door, at least one interior space **5**, which can be covered at least in part by the covering element **2**, a guide device **6** for translational movement of the covering element **2** within the cavity **4**, a carrier **7** movable along the guide device **6**, two swivel devices **8** by means of which the covering element **2** is mounted on the carrier **7** so as to be pivotable about a pivot axis **9**.

[0066] FIGS. **3** and **4** show views of the first embodiment of an arrangement **1** in a closed position **26** of the covering element **2**, wherein the stabilizing device **10** is now also shown, which stabilizing device **10** comprises a coupling element **12** which is coupled to the covering element **2** in every position of the covering element **2**.

[0067] FIG. **4** shows, in particular, a cavity guide **13**, which is attached to a wall **14** of the shaft-shaped cavity **4**, a covering element guide **17**, which is attached to the covering element **2**, and the coupling element **12**.

[0068] FIGS. **5** and **6** show views of a first embodiment of a stabilizing device **10**, which comprises a cavity guide **13**, a covering element guide **17**, and a coupling element **12**.

[0069] In this first embodiment of the stabilizing device **10**, the covering element guide **17** has a covering element guide stop **18** which can limit relative movement of the coupling element **12** relative to the covering element guide **17**.

[0070] FIG. **6** shows the cavity guide **13**, the covering element guide **17**, and the coupling element **12** spaced apart from each other in an exploded view so that further sub-elements of the stabilizing device **10** are also visible.

[0071] In this embodiment, the coupling element **12** has two coupling element stops **16**, wherein a force storage member **24** in the form of a spring, in particular a compression spring, is arranged on one coupling element stop **16**, which spring surrounds the coupling element **12**.

[0072] In this embodiment, the coupling element **12** consists of two coupling element parts **20**, which are connected to each other by a hinge **21**.

[0073] One of the two coupling elements **20** in this embodiment is a spacer element **22**, which is designed at least to maintain the specified distance **11** between the covering element **2** and the guide device **6** constant when the covering element **2** moves along the guide device **6**.

[0074] In this embodiment, two sliding elements **19** in the form of rolling elements, preferably running wheels, are arranged on a coupling element part **20**, in particular on the spacer element **22**, which are designed to be moved along the covering element guide **17**.

[0075] FIGS. **7-13** show horizontal sections of a sequence of movements of the first embodiment of an arrangement **1** and of the first embodiment of a stabilizing device **10**, respectively. FIG. **7** shows the entire arrangement **1**; FIGS. **8-13** show detailed views of the sequence of movements of the stabilizing device **10**.

[0076] FIGS. **8-13** also show that the cavity guide **13** has a cavity guide stop **15** which can limit relative movement of the coupling element **12** relative to the cavity guide **13** and/or can act as an abutment for a force storage member **24**, in particular by means of which abutment the force storage member **24** can be charged.

[0077] The force storage member **24** or the spring can generally support a relative, in particular translational, movement of the coupling element **12** relative to the cavity guide **13** and/or the covering element guide **17**.

[0078] In FIG. **8**, the covering element **2** is in the closed position **26**, whereby it is completely outside the cavity **4** and at least partially covers the interior space **5** of the furniture part **3**.

[0079] In closed position **26**, the force storage member **24** or the spring is in a relaxed or only relatively tensioned state.

[0080] In this embodiment, the force storage member **24** is slightly preloaded in the closed position **26** so that the force storage member **24** has a locking function for locking the covering element **2** in the closed position **26**.

[0081] In FIG. **9**, the covering element **2** is in an intermediate position **25**, whereby the covering element **2** swivels about the pivot axis **9** and/or rotates about the hinge **21**.

[0082] In this embodiment, the force storage member **24** is relatively strongly biased in this intermediate position **25**, whereby the force storage member **24** exerts a restoring force on the covering element **2** in the direction of a fully retracted position **27** of the covering element **2**.

[0083] In FIG. **10**, the covering element **2** is in an intermediate position **25**, wherein the covering element **2** is pivoted by 90° about the pivot axis **9** and/or rotated about the hinge **21** starting from the closed position **26**, so that the covering element **2** is essentially parallel to the wall **14** of the furniture part **3** or aligned with the cavity **4**.

[0084] In this intermediate position **25**, the coupling device **14**, in particular the spacer element **22** of the coupling device **12** and/or the at least one sliding element **19**, contacts the covering element guide stop **18** so that the covering element **2** is also held by the stabilizing device **10** and/or remains coupled and/or a translational movement out of the cavity **4**.

[0085] In this embodiment of the stabilizing device **10**, the spacer element **22** of the coupling element **12** strikes the coupling element stop **16** so that the rotation of the spacer element **22** about the hinge **21** is limited.

[0086] It is also conceivable that at least one additional support element **19** is provided, in particular instead of at least one coupling element stop **16**. See FIGS. **14-17**, where such a support element **19** is shown.

[0087] In this intermediate position **25**, the cavity guide stop **15** of the cavity guide **13** and the coupling element stop **16** of the coupling element **12** closer to the covering element **2** touch each other so that no translational movement of the coupling element **12** along the cavity guide **13** takes place and/or the force storage member **24** is relaxed or only relatively slightly tensioned.

[0088] FIGS. **10-13** show the specified distance **11** between the covering element **2** and the guide device **6** and/or the wall **14** of the furniture part **3**, which wall **14** adjoins the cavity **4**.

[0089] FIG. **11** shows an intermediate position **25** in which the coupling element **12** is essentially in a rest position and the covering element **2** is guided by the stabilizing device **10** further into the cavity **4** toward a fully retracted position **27**.

[0090] When the covering element **2** moves toward the fully retracted position **27**, the covering element **2** slides along the coupling element **12**, in particular along the spacer element **22** and/or the at least one sliding element **19**, by means of the covering element guide **17**.

[0091] FIG. **12** shows an intermediate position **25** in which the covering element **2** is further in the cavity **4** closer to a fully retracted position **27**.

[0092] FIG. **13** essentially shows a fully retracted position **27** of the covering element **2**, wherein the covering element **2** is advantageously stabilized by means of the stabilizing device **10** at the front or outwardly facing region of the covering element **2**.

[0093] During the entire movement sequence of the covering element **2**, the force storage member **24** can also have a damping function to dampen the movement of the covering element **2** and/or the coupling element **12**.

[0094] It is also conceivable that the force storage member **24** has a stabilizing function for stabilizing the covering element **2** in an intermediate position **25**.

[0095] FIG. **14-17** show horizontal sections of a sequence of movements of a second embodiment of an arrangement **1** and a second embodiment of a stabilizing device **10**, respectively.

[0096] This sequence of movements essentially corresponds to the movement steps shown in FIGS. **7-13** of the first embodiment of a stabilizing device **10**.

[0097] In this embodiment, however, the stabilizing device **10** has an additional support element **23**, which is arranged in particular on the cavity guide **13** and limits the rotational movement of the

spacer element **22** about the hinge **21**.

[0098] The stabilizing device **10** and/or the support element **23** is preferably designed such that the specified distance **11** between the covering element **2** and the guide device **6** remains constant when the covering element **2** moves along the guide device **6**.

[0099] As previously in the position shown in FIG. **13**, in the position shown in FIG. **14**, the covering element **2** is stabilized by means of the stabilizing device **10**, preferably at the front or outwardly facing area of the covering element **2**.

[0100] FIGS. **18-20** show views of a second embodiment of an arrangement **1** in a closed position **26** of the covering element **2**.

[0101] In this second embodiment, the stabilizing device **10** is essentially located in the middle and/or upper half of the furniture part **3**, in particular on a wall **14** of the cavity **4** and/or the covering element **2**.

[0102] Particularly in the case of large covering elements **2**, it may be helpful to arrange the stabilizing device **10** in the upper region in order to counteract the tilting moment of the covering element **2** and/or the carrier **7**.

[0103] It is also conceivable to arrange several stabilizing devices **10** on the furniture part **3**.

[0104] The second embodiment of an arrangement **1** has several additional elements compared to the first embodiment.

[0105] In particular, FIG. **20** shows, in addition to the stabilizing device **10**, four guide devices **6**, which are attached to the side edges of the cavity **4**, and a further compensation device **28** for compensating a tilting moment of the carrier **7** or of the covering element **2** arranged thereon.

[0106] It is possible that the compensation device **28** has at least one cable pull device and/or a pivot lever mechanism.

[0107] FIGS. **21-26** show views of the third embodiment of a stabilizing device **10** comprising a cavity guide **13**, a covering element guide **17**, and a coupling element **12**.

[0108] FIG. **22** shows, in particular and in contrast to the first two embodiments of the stabilizing device **10**, a substantially single-piece coupling element **2**, which has a curved end **29** closer to the covering element **2**.

[0109] The curved end **29** of the coupling element **12** is preferably designed in accordance with the specified distance **11**.

[0110] The coupling element **2** of this embodiment of a stabilizing device **10** has a coupling element stop **16**, which serves in particular as an abutment for the force storage member **24**.

[0111] In this embodiment, the force storage member **24** is arranged next to the coupling element **12** and between an end of the cavity guide **13** serving as an abutment and the coupling element stop **16**.

[0112] The arrangement of the force storage member **24** in this third embodiment is thus different from the first two embodiments of the stabilizing device **10**, in which the force storage member **24** at least partially surrounds the coupling element **12**.

[0113] Furthermore, FIG. **22** contains detailed views of the two ends of the covering element guide **17**, one end having a covering element guide stop **18**.

[0114] In this embodiment, one end of the covering element guide **17** has an opening **30** through which the coupling element **12** can be inserted.

[0115] Furthermore, FIG. **23** shows a cavity guide stop **15** of the cavity guide **13**, which can act as a limit for the movement of the coupling element **12** and/or as an abutment for a force storage member **24**.

[0116] FIGS. **27-33** show a sequence of movements of the second embodiment of an arrangement **1** or a third embodiment of a stabilizing device **10**, which has a curved end **29**.

[0117] FIG. **27** shows a closed position **26** of the covering element **2**, wherein the covering element **2** is completely outside the cavity **4**.

[0118] FIG. **28** shows an intermediate position **25**, wherein the covering element **2** is pivoted about

the pivot axis **9** and/or rotated about the curved end **29** and/or about at least one sliding element **19**.
[0119] In the position shown in FIG. **28**, the curved end **29** of the coupling element **12** and/or the at least one sliding element **19** touches the covering element guide stop **18** of the covering element guide **17**.

[0120] FIG. **29** shows another intermediate position **25** in which the covering element **2** is aligned parallel to the wall **14** of the furniture part **3**.

[0121] FIGS. **30-32** show two further intermediate positions **25**, in which the covering element **2** moves translationally toward a fully retracted position **27** of the covering element **2** in the cavity **4**.

[0122] In the position shown in FIG. **30**, the coupling element **12** moves translatorily in the direction of the fully retracted position **27** into the cavity **4**.

[0123] In FIGS. **31** and **32**, the coupling element **12** is located in the lowest possible position against the stop in the cavity guide **13**, so that only the covering element **2** moves further into the cavity **4**, whereby the covering element guide **17** is guided by at least one sliding element **19** and/or the bent end **29**.

[0124] In the position shown in FIG. **33**, the covering element **2** is essentially in a fully retracted position **27** within the cavity **4**, whereby the covering element **2** is preferably stabilized by means of the stabilizing device **10** at the front or outwardly facing area of the covering element **2**.

Claims

1. An arrangement for moving at least one covering element, preferably a door or folding door, relative to a fixed furniture part, which has at least one, preferably shaft-shaped, cavity for receiving the covering element and at least one interior space, which can be covered at least in part by the covering element, wherein the arrangement has at least one guide device for translational movement of the covering element within the cavity, at least one carrier movable along the guide device and at least one swivel device, wherein the covering element can be mounted on the carrier by means of the swivel device so as to be pivotable about a pivot axis parallel to the carrier, wherein the arrangement comprises at least one stabilizing device by means of which the covering element can be held at a predetermined distance from the guide device and/or a wall of the fixed furniture part which delimits the cavity when moving along the guide device, wherein the stabilizing device comprises at least one coupling element which can be coupled to the covering element in every position of the covering element.
2. The arrangement according to claim 1, wherein the stabilizing device has a cavity guide which is arranged or can be arranged on the wall of the cavity and is designed to support the coupling element in a displaceable manner.
3. The arrangement according to claim 1, wherein the stabilizing device has at least one cavity guide stop which limits relative movement of the coupling element to the cavity guide.
4. The arrangement according to claim 1, wherein the stabilizing device has at least one coupling element stop which limits relative movement of the coupling element relative to the cavity guide.
5. The arrangement according to claim 1, wherein the stabilizing device has a covering element guide which is arranged or can be arranged on the covering element and is designed to mount the coupling element so that it can be displaced.
6. The arrangement according to claim 1, wherein the stabilizing device has at least one covering element guide stop which limits relative movement of the coupling element to the covering element guide.
7. The arrangement according to claim 1, wherein the coupling element has at least one sliding element, preferably at least one rolling element.
8. The arrangement according to claim 1, wherein the coupling element consists of at least two coupling element parts, wherein at least two of the at least two coupling element parts are connected to each other by means of at least one hinge.

- 9.** The arrangement according to claim 8, wherein at least one of the at least two coupling element parts is a spacer element which is designed to maintain the predetermined distance between the covering element and the guide device constant during movement of the covering element along the guide device.
- 10.** The arrangement according to claim 1, wherein the stabilizing device has at least one support element which is designed to support the coupling element, preferably the at least one spacer element of the coupling element, in such a way that the predetermined distance between the covering element and the guide device is maintained when the covering element moves along the guide device.
- 11.** The arrangement according to claim 1, wherein the stabilizing device has at least one force storage member which is designed at least to support a relative, in particular translational, movement of the coupling element to the cavity guide and/or the covering element guide.
- 12.** The arrangement according to claim 11, wherein the at least one force storage member comprises at least one spring.
- 13.** The arrangement according to claim 11, wherein the at least one force storage member is arranged: on the coupling element, and/or on the cavity guide, and/or on the covering element guide.
- 14.** The arrangement according to claim 11, wherein the at least one force storage member: has a locking function for locking the covering element in a closed position, and/or has a damping function for damping the movement of the coupling element, and/or has a return effect on the covering element in the direction of a retracted position of the covering element.
- 15.** A furniture with at least one covering element, preferably a door or folding door, at least one fixed furniture part, which has at least one, preferably shaft-shaped, cavity for receiving the covering element and at least one interior space, which can be covered at least in some areas by the covering element, wherein the furniture has at least one arrangement according to claim 1 for moving at least one covering element relative to the at least one furniture part.
- 16.** A furniture part with at least one preferably shaft-shaped cavity for receiving a covering element, preferably a door or folding door, at least one interior space which can be covered at least in part by the covering element, and an arrangement according to claim 1 for moving the covering element relative to the furniture component.
- 17.** The furniture part according to claim 16, wherein the stabilizing device is arranged essentially in the middle and/or the upper half of the furniture part and/or the covering element.
- 18.** The furniture part according to claim 16, wherein the furniture part has a compensation device for compensating a tilting moment of the carrier or of the covering element arranged thereon, preferably wherein the compensation device comprises at least one cable pull device and/or a pivot lever mechanism.
-