

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402718
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Xu; Zhenwu et al.

Toothbrush

Abstract

A toothbrush includes a brush head linkage (**100**), a connecting mechanism (**200**) and a toothbrush handle (**300**); the connecting mechanism (**200**) includes a first connector (**210**), a second connector (**220**) and an elastic structural element (**230**) connected to the second connector (**220**); the first connector (**100**) is rotatably connected to the second connector (**220**), and the axis of rotation extends in a front-rear direction; and the elastic structural element (**230**) includes at least one return torsion spring (**231**), the return torsion spring (**231**) includes a helix spring (**2311**) in the form of a cylinder with an opening of the cylinder oriented in a direction parallel to an extension direction of an oscillating reference line, the helix spring is in stop fit with the second connector (**220**) in a direction perpendicular to the oscillating reference line, and the return torsion spring further includes a first torsion bar (**2311**) and a second torsion bar (**2312**) respectively connected to a front end and a rear end of the helix spring (**2311**). The toothbrush according to the present disclosure can protect teeth.

Inventors:	Xu; Zhenwu (Shanghai, CN), Dai; Xiaoguo (Shanghai, CN)
Applicant:	SHANGHAI SHIFT ELECTRICS CO., LTD. (Shanghai, CN)
Family ID:	76985330
Assignee:	SHANGHAI SHIFT ELECTRONICS CO., LTD. (Shanghai, CN)
Appl. No.:	18/044790
Filed (or PCT Filed):	April 26, 2022
PCT No.:	PCT/CN2022/089200
PCT Pub. No.:	WO2022/247559
PCT Pub. Date:	December 01, 2022

Prior Publication Data

Document Identifier	Publication Date
---------------------	------------------

Foreign Application Priority Data

CN

202110578515.X

May. 26, 2021

Publication Classification**Int. Cl.:** A46B5/00 (20060101); A46B9/04 (20060101)**U.S. Cl.:****CPC** A46B5/007 (20130101); A46B9/04 (20130101); A46B2200/1066 (20130101)**Field of Classification Search****CPC:** A46B (2200/1066); A46B (5/002); A46B (5/0033); A46B (5/0041); A46B (5/007); A46B (5/0062); A46B (5/0058); A46B (5/0054); A46B (5/0025); A46B (5/0091); A46B (7/06); A46B (7/02); A61C (17/222); A61C (17/225); Y10T (403/608)**USPC:** 15/167.1; 15/143.1-14

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
706144	12/1901	Young	403/220	A46B 5/00
1092014	12/1913	Briggs	403/93	A46B 5/0075
2236627	12/1940	McWhirter	15/176.3	A46B 5/0095
4731896	12/1987	de La Tour	N/A	N/A
5901397	12/1998	Hafele et al.	N/A	N/A
6611984	12/2002	Halm	15/167.1	A46B 5/007
2023/0404727	12/2022	Xu	N/A	A61C 17/222

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103494434	12/2013	CN	N/A
203828321	12/2013	CN	N/A
112369793	12/2020	CN	A46B 7/08
113180365	12/2020	CN	N/A
215603806	12/2021	CN	N/A
2413268	12/2004	GB	N/A
2010017212	12/2009	JP	N/A
2013226202	12/2012	JP	N/A

OTHER PUBLICATIONSInternational Search Report of PCT/CN2022/089200. cited by applicant

Background/Summary

FIELD

(1) The present disclosure belongs to the field of oral care, and in particular relates to a toothbrush.

BACKGROUND ART

(2) When a toothbrush is in use, the force of the toothbrush to clean teeth comes from pressing and pushing forces of a human hand. When brushing the teeth, a user may unconsciously increase the stress applied to the teeth through a tooth handle due to expectation for a better cleaning effect, and the teeth are subjected to more stress than is required for cleaning, and the stress may cause damage to the teeth.

SUMMARY OF THE DISCLOSURE

(3) Embodiments of the present disclosure are to overcome the above-mentioned shortcomings in the prior art and provide a toothbrush, which aims to avoid damage to teeth caused by brushing the teeth too hard.

(4) The present disclosure includes

(5) a toothbrush, including a brush head linkage, a connecting mechanism and a toothbrush handle which are sequentially arranged from top to bottom, and a brushing structure for brushing teeth is connected to the brush head linkage; the connecting mechanism includes a first connector, a second connector and an elastic structural element connected to the second connector; one of the first connector and the second connector is connected to the toothbrush handle, and the other one is connected to the brush head linkage; the first connector is rotatably connected to the second connector, and the axis of rotation is an oscillating reference line perpendicular to a vertical direction; the elastic structural element includes at least one return torsion spring, the return torsion spring includes a helix spring in the form of a cylinder with an opening of the cylinder oriented in a direction parallel to an extension direction of the oscillating reference line, the helix spring is in stop fit with the second connector in a direction perpendicular to the oscillating reference line, and the return torsion spring further includes a first torsion bar and a second torsion bar respectively connected to a front end and a rear end of the helix spring; and a free end of the first torsion bar is in stop fit with the first connector, and a free end of the second torsion bar is in stop fit with the second connector.

(6) In one embodiment, the second connector is provided with a mounting portion;

(7) there are two return torsion springs, and free ends of the two second torsion bars are connected to each other; and

(8) the two helix springs respectively elastically abut against two opposite sides of the mounting portion.

(9) In one embodiment, the two opposite sides of the mounting portion are each formed with a spring limiting groove extending in the direction of the oscillating reference line, and the two spring limiting grooves respectively partially accommodate one of the helix springs and limit movement of the corresponding helix springs in the vertical direction.

(10) In one embodiment, the mounting portion is formed with a torsion bar limiting groove which accommodates the two second torsion bars, and the torsion bar limiting groove limits movement of the two second torsion bars in the vertical direction.

(11) In one embodiment, an opening of the torsion bar limiting groove is of a flaring structure.

(12) In one embodiment, two opposite sides of the second connector are each provided with a limiting flange in a protruding manner, and the two limiting flanges each abut against one end of one of the helix springs.

- (13) In one embodiment, each of the limiting flanges is provided with a limiting post, and each of the limiting posts is inserted into a cylinder cavity of the corresponding helix spring; and
- (14) the first connector has an anti-detaching portion, and the anti-detaching portion is configured to prevent the two helix springs from detaching from the corresponding limiting post.
- (15) In one embodiment, the two return torsion springs are arranged symmetrically in the vertical direction.
- (16) In one embodiment, the first connector has a first limiting portion and a second limiting portion, the first limiting portion abuts against the second connector when the second connector rotates counterclockwise relative to the first connector to a first preset limit angle, and the second limiting portion abuts against the second connector when the second connector rotates clockwise relative to the first connector to a second preset limit angle.
- (17) In one embodiment, the brushing structure includes bristles connected to one side of the brush head linkage and extending in a direction parallel to the oscillating reference line.
- (18) When the teeth are brushed, the brushing structure needs to be pressed against the teeth, and based on the structure of the present disclosure and in conjunction with mechanical principles, the force applied by the user to the toothbrush handle needs to be transmitted to the brush head linkage through the connecting mechanism. The return torsion spring limits the transmission of the force that is not perpendicular to a direction parallel to the front-rear direction. In one embodiment, when the force that needs to be transmitted to the brush head linkage through the connecting mechanism and that is not perpendicular to the direction parallel to the front-rear direction is just greater than an external force required for the elastic deformation of the return torsion spring, each of the return torsion springs is elastically deformed, the first connector and the second connector rotate relative to each other, and at this time, the stress applied by the brushing structure to the teeth is not too large, and the teeth are not damaged.
- (19) When the first connector and the second connector rotate relative to each other, the brush head linkage and the toothbrush handle also rotate relative to each other, the attitude of the toothbrush handle changes, and the user can quickly feel the change of attitude of the toothbrush handle. At this time, the user can consciously control the strength, and the stress applied by the brushing structure to the teeth reduces or stops increasing, to avoid damage to the teeth.
- (20) As can be seen from the above, the toothbrush according to the present disclosure can protect the teeth.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) In order to explain the embodiments of the present disclosure more clearly, the accompanying drawings used in the embodiments will be briefly introduced below. The accompanying drawings in the following description are only some of the embodiments of the present disclosure.
- (2) FIG. 1 is a perspective view of a toothbrush according to an embodiment of the present disclosure;
- (3) FIG. 2 is an exploded view of the toothbrush according to an embodiment of the present disclosure in one perspective;
- (4) FIG. 3 is an enlarged structural schematic diagram of part A in FIG. 2;
- (5) FIG. 4 is an enlarged structural schematic diagram of part B in FIG. 3;
- (6) FIG. 5 is an exploded view of the toothbrush according to an embodiment of the present disclosure in another perspective;
- (7) FIG. 6 is an enlarged structural schematic diagram of part C in FIG. 5;
- (8) FIG. 7 is an enlarged structural schematic diagram of part D in FIG. 6; and
- (9) FIG. 8 is a perspective view of an elastic structural element according to an embodiment of the

present disclosure.

DESCRIPTION OF REFERENCE SIGNS

(10) **100** Brush head linkage **110** Brushing structure **200** Connecting mechanism **210** First connector **211** Anti-detaching portion **212** First limiting portion **213** Second limiting portion **220** Second connector **221** Mounting portion **2211** Limiting flange **2212** Limiting post **22101** Spring limiting groove **22102** Torsion bar limiting groove **230** Elastic structural element **231** Return torsion spring **2311** Helix spring **2312** First torsion bar **2313** Second torsion bar **230** Enclosure **300** Toothbrush handle

DETAILED DESCRIPTION OF EMBODIMENTS

(11) For making the purpose, the embodiments of the present disclosure more apparent, the present disclosure will be further described in detail below in conjunction with the accompanying drawings and embodiments. It is to be understood that specific embodiments described herein are only intended to explain the present disclosure, and are not taken to limit the present disclosure.

(12) It should be noted that, in embodiments of the present disclosure, it is defined according to an XYZ Cartesian coordinate system established in FIG. 1, FIG. 2 and FIG. 5 that: the side located in the positive direction of the X-axis is defined as the front side, and the side located in the negative direction of the X-axis is defined as the rear side; the side located in the positive direction of the Y-axis is defined as the left side, and the side located in the negative direction of the Y-axis is defined as the right side; and the side located in the positive direction of the Z-axis is defined as the upper side, and the side located in the negative direction of the Z-axis is defined as the lower side.

(13) An embodiment of the present disclosure provides a toothbrush.

(14) Referring to FIG. 1 to FIG. 8, the toothbrush includes a brush head linkage **100**, a connecting mechanism **200** and a toothbrush handle **300** which are sequentially arranged from top to bottom.

(15) The brush head linkage **100** is connected to a brushing structure **110** for brushing teeth. During use, the brushing structure **110** needs to be inserted into an oral cavity, and the brush head linkage **100** is usually elongated, and a length direction is a vertical direction.

(16) The toothbrush handle **300** is configured to be grasped by a human hand. For ease of grasping by the human hand, the toothbrush handle **300** is also elongated and extends in the vertical direction, and an outer surface of the toothbrush handle **300** may be provided with an anti-slip soft rubber, as well as a groove structure that fits with the structure of the human hand, etc.

(17) The connecting mechanism **200** is configured to connect the brush head linkage **100** to the toothbrush handle **300**. The connecting mechanism **200** includes a first connector **210**, a second connector **220** and an elastic structural element **230** connected to the second connector **220**, one of the first connector **210** and the second connector **220** being connected to the toothbrush handle **300**, and the other one being connected to the brush head linkage **100**. In an embodiment of the present disclosure, the first connector **210** is connected to the toothbrush handle **300**, and the second connector **220** is connected to the brush head linkage **100**. In other embodiments, the first connector **210** may be connected to the brush head linkage **100**, and the second connector **220** is connected to the toothbrush handle **300**.

(18) The first connector **210** is rotatably connected to the second connector **220**, and the axis of rotation is an oscillating reference line perpendicular to the vertical direction. In this embodiment, an extension direction of the oscillating reference line is parallel to a front-rear direction, and the brush head linkage **100** oscillates in a left-right direction relative to the toothbrush handle **300**. While in other embodiments, the extension direction of the oscillating reference line may be parallel to the left-right direction, and the brush head linkage **100** oscillates in the front-rear direction relative to the toothbrush handle **300**. The elastic structural element **230** includes at least one return torsion spring **231**. The return torsion spring **231** includes a helix spring **2311** in the form of a cylinder with an opening of the cylinder oriented in a direction parallel to the extension direction of the oscillating reference line, and the helix spring is in stop fit with the second connector **220** in a direction perpendicular to the oscillating reference line; and the return torsion

spring further includes a first torsion bar **2312** and a second torsion bar **2313** which are respectively connected to a front end and a rear end of the helix spring **2311**, a free end of the first torsion bar **2312** is in stop fit with the first connector **210**, and a free end of the second torsion bar **2313** is in stop fit with the second connector **220**.

(19) When the teeth are brushed, the brushing structure **110** needs to be pressed against the teeth, and based on the structure of the present disclosure and in conjunction with mechanical principles, the force applied by the user to the toothbrush handle **300** needs to be transmitted to the brush head linkage **100** through the connecting mechanism **200**. The return torsion spring **231** limits the transmission of the force that is not perpendicular to a direction parallel to the front-rear direction. Specifically, when the force that needs to be transmitted to the brush head linkage **100** through the connecting mechanism **200** and that is not perpendicular to the direction parallel to the front-rear direction is just greater than an external force required for the elastic deformation of the return torsion spring **231**, each of the return torsion springs **231** is elastically deformed, the first connector **210** and the second connector **220** rotate relative to each other, and at this time, the stress applied by the brushing structure **110** to the teeth is not too large, and the teeth are not damaged.

(20) When the first connector **210** and the second connector **220** rotate relative to each other, the brush head linkage **100** and the toothbrush handle **300** also rotate relative to each other, the attitude of the toothbrush handle **300** changes, and the user can quickly feel the change of attitude of the toothbrush handle **300**. At this time, the user can consciously control the strength, and the stress applied by the brushing structure **110** to the teeth reduces or stops increasing, to avoid damage to the teeth.

(21) From the above analysis, the toothbrush according to an embodiment of the present disclosure can protect the teeth.

(22) Referring to FIG. 2 to FIG. 7, in an embodiment of the present disclosure, the second connector **220** is provided with a mounting portion **221**. There are two return torsion springs **231**, and free ends of two second torsion bars **2313** are connected to each other. Two helix springs **2311** respectively elastically abut against two opposite sides of the mounting portion **221**. In this embodiment, the two helix springs **2311** respectively elastically abut against a left side and a right side of the mounting portion **221**. Based on this, during assembly, the two helix springs **2311** are clamped to the mounting portion **221**, and as such, the elastic structural element **230** is installed on the second connector **220**, which greatly increases the efficiency of installation of the elastic structural element **230** and the second connector **220**.

(23) Referring to FIG. 2 to FIG. 7, in an embodiment of the present disclosure, two opposite sides of the mounting portion **221** are each formed with a spring limiting groove **22101** extending in the direction of the oscillating reference line. In this embodiment, the left side and the right side of the mounting portion **221** are each formed with the spring limiting groove **22101** extending in the front-rear direction. Each of two spring limiting grooves **22101** respectively partially accommodate one of the helix springs **2311** and limits movement of the corresponding helix spring **2311** in the vertical direction. In this way, when the two helix springs **2311** are respectively partially accommodated in the two spring limiting grooves **22101**, the two spring limiting grooves **22101** respectively limit the movement of the corresponding helix springs **2311** in the vertical direction, preventing the two helix springs **2311** from moving relative to the second connector **220** in the vertical direction, which can improve the stability of connection between the elastic structural element **230** and the second connector **220**.

(24) Specifically, in an embodiment of the present disclosure, the shape of the spring limiting groove **22101** fits with a portion of the corresponding helix spring **2311**.

(25) Referring to FIG. 2 to FIG. 7, in an embodiment of the present disclosure, the mounting portion **221** is formed with a torsion bar limiting groove **22102** which accommodates the two second torsion bars **2313**, and the torsion bar limiting groove **22102** limits movement of the two second torsion bars **2313** in the vertical direction. In this way, when the two second torsion bars

2313 are accommodated in the torsion bar limiting groove **22102**, the torsion bar limiting groove **22102** limits the movement of the two second torsion bars **2313** in the vertical direction, and in turn limits the movement of the elastic structural element **230** in the vertical direction, which can further improve the stability of connection between the elastic structural element **230** and the second connector **220**.

(26) Further, in an embodiment of the present disclosure, an opening of the torsion bar limiting groove **22102** is of a flaring structure. Based on this, when the two second torsion bars **2313** are accommodated in the torsion bar limiting groove **22102**, the flaring structure of the opening of the torsion bar limiting groove **22102** enables quick accommodation of the two second torsion bars **2313** in the torsion bar limiting groove **22102**, to improve the efficiency of accommodating the two second torsion bars **2313** in the torsion bar limiting groove **22102**.

(27) In other embodiments, the torsion bar limiting groove **22102** may be disposed on a rear side of the mounting portion **221**.

(28) Referring to FIG. 2 to FIG. 7, in an embodiment of the present disclosure, two opposite sides of the second connector **220** are each provided with a limiting flange **2211** in a protruding manner. In this embodiment, the two opposite sides of the second connector **220** are each provided with the limiting flange **2211** in a protruding manner. The two limiting flanges **2211** abut against one end of one of the helix springs **2311**. In combination with the aforementioned structure, when the two helix springs **2311** are clamped to the mounting portion **221**, it usually takes a little time to adjust the relative position between the elastic structural element **230** and the mounting portion **221** in the front-rear direction. Based on this structure, when the two helix springs **2311** are clamped to the mounting portion **221**, one end of each of the two helix springs **2311** is pushed against the corresponding limiting flange **2211**, and as such, the adjustment of the relative position between the elastic structural element **230** and the mounting portion **221** in the front-rear direction is completed. The whole process is simple and fast, which greatly improves the adjustment efficiency of adjusting the relative position between the elastic structural element **230** and the mounting portion **221** in the front-rear direction.

(29) It should be noted here that, in an embodiment of the present disclosure, the helix spring **2311** abuts with its rear end against the limiting flange **2211**, while in other embodiments where the torsion bar limiting groove **22102** is disposed on the rear side of the mounting portion **221**, the helix spring **2311** abuts with its front end against the limiting flange **2211**.

(30) Referring to FIG. 2 to FIG. 7, in an embodiment of the present disclosure, each of the limiting flanges **2211** is provided with a limiting post **2212**, and the limiting post **2212** is inserted into a cylinder cavity of the corresponding helix spring **2311**. The first connector **210** has an anti-detaching portion **211**, and the anti-detaching portion **211** is configured to prevent the two helix springs **2311** from detaching from the corresponding limiting post **2212**. Based on this, by limitation of the limiting post **2212** and the anti-detaching portion **211** on the position of the elastic structural element **230**, the elastic structural element **230** is prevented from detaching from a predetermined position during deformation, and it is difficult for the elastic structural element **230** to fail, to improve the structural reliability of the connecting mechanism **200**.

(31) When the two helix springs **2311** are respectively partially accommodated in the two spring limiting grooves **22101**, the two spring limiting grooves **22101** respectively limit the movement of the corresponding helix springs **2311** in the vertical direction, preventing the two helix springs **2311** from moving relative to the second connector **220** in the vertical direction, which can improve the stability of connection between the elastic structural element **230** and the second connector **220**.

(32) Referring to FIG. 2 to FIG. 8, in an embodiment of the present disclosure, the two return torsion springs **231** are arranged symmetrically on two sides of the oscillating reference line.

(33) Referring to FIG. 2 to FIG. 7, in an embodiment of the present disclosure, the first connector **210** has a first limiting portion **212** and a second limiting portion **213**. The first limiting portion **212** abuts against the second connector **220** when the second connector **220** rotates counterclockwise

relative to the first connector **210** to a first preset limit angle, and the second limiting portion **213** abuts against the second connector **220** when the second connector **220** rotates clockwise relative to the first connector **210** to a second preset limit angle. Based on this, first of all, when the second connector **220** rotates counterclockwise relative to the first connector **210** to the first preset limit angle, the first limiting portion **212** abuts against a left side face of the second connector **220**, and the first limiting portion **212** limits the second connector **220** from continuing to rotate counterclockwise. In this embodiment, the first limiting portion **212** limits the extent to which the brush head linkage **100** is turned to the left relative to the toothbrush handle **300**. In this way, excessive counterclockwise rotation of the brush head linkage **100** relative to the toothbrush handle **300**, which affects the normal use of the toothbrush, is avoided. Secondly, when the second connector **220** rotates clockwise relative to the first connector **210** to the second preset limit angle, the second limiting portion **213** abuts against the second connector **220**. In this embodiment, the second limiting portion **213** limits the second connector **220** from continuing to rotate rightward. In this way, excessive clockwise rotation of the brush head linkage **100** relative to the toothbrush handle **300**, which affects the normal use of the toothbrush, is avoided.

(34) Specifically, in this embodiment, the first preset limit angle and the second preset limit angle are both 10 degrees.

(35) Referring to FIG. 1, FIG. 2 and FIG. 5, in an embodiment of the present disclosure, the brushing structure **110** includes a plurality of tooth bristles connected to one side of the brush head linkage **100** and extending in a direction parallel to the oscillating reference line. Based on this, during specific use, that is, when the teeth are brushed, tips of the tooth bristles face downward or upward (this orientation is the actual orientation) against the teeth, and at this time, the toothbrush handle **300** can be rotated to the left or to the right through the connecting mechanism **200** (this orientation is the reference orientation shown in the figures), and the toothbrush handle **300** is closer to a human mouth, to improve the comfort of the user in holding the toothbrush handle **300**. Therefore, the present disclosure can not only protect the teeth, but also improve the comfort in holding the toothbrush handle **300**.

(36) In other embodiments, the tooth bristles are connected to a rear side face of the brush head linkage **100**.

(37) Referring to FIG. 2 to FIG. 7, in an embodiment of the present disclosure, the connecting mechanism **200** further includes an enclosure **240**, the enclosure **240** and the first connector **210** together enclose an enclosed space for accommodating the elastic structural element **230**, and a part of the second connector **220** is accommodated in the enclosed space, to protect the elastic structural element **230**.

(38) The above descriptions are merely some embodiments of the present disclosure and are not used to limit the present disclosure, and any modifications, equivalent replacements or improvements, etc. that are made within the spirit and principle of the present disclosure should be included within the scope of protection of the present disclosure.

Claims

1. A toothbrush, comprising: a brush head linkage, a connecting mechanism and a toothbrush handle which are sequentially arranged from top to bottom, and a brushing structure for brushing teeth is connected to the brush head linkage; the connecting mechanism comprises a first connector, a second connector and an elastic structural element connected to the second connector; one of the first connector and the second connector is connected to the toothbrush handle, and the other one is connected to the brush head linkage; the first connector is rotatably connected to the second connector, and the axis of rotation is an oscillating reference line perpendicular to a vertical direction; the elastic structural element comprises at least one return torsion spring, the at least one return torsion spring comprises a helix spring in a cylindrical form with an opening of the cylinder

oriented in a direction parallel to an extension direction of the oscillating reference line, the helix spring is in stop fit with the second connector in a direction perpendicular to the oscillating reference line, and the at least one return torsion spring further comprises a first torsion bar and a second torsion bar respectively connected to a front end and a rear end of the helix spring; and a free end of the first torsion bar is in stop fit with the first connector, and a free end of the second torsion bar is in stop fit with the second connector.

2. The toothbrush of claim 1, wherein the second connector is provided with a mounting portion; there are two return torsion springs, and free ends of two second torsion bars are connected to each other; and two helix springs respectively elastically abut against two opposite sides of the mounting portion.

3. The toothbrush of claim 2, wherein the two opposite sides of the mounting portion are each formed with a spring limiting groove extending in the direction of the oscillating reference line, and the two spring limiting grooves respectively partially accommodate one of the helix springs and limit movement of the corresponding helix springs in the vertical direction.

4. The toothbrush of claim 3, wherein the mounting portion is formed with a torsion bar limiting groove which accommodates the two second torsion bars, and the torsion bar limiting groove limits movement of the two second torsion bars in the vertical direction.

5. The toothbrush of claim 4, wherein an opening of the torsion bar limiting groove is of a flaring structure.

6. The toothbrush of claim 3, wherein two opposite sides of the second connector are each provided with a limiting flange in a protruding manner, and the two limiting flanges each abut against one end of one of the helix springs.

7. The toothbrush of claim 6, wherein each of the two limiting flanges is provided with a limiting post, and each of the limiting posts is inserted into a cylinder cavity of the corresponding helix spring; and the first connector has an anti-detaching portion, and the anti-detaching portion is configured to prevent the two helix springs from detaching from the corresponding limiting post.

8. The toothbrush of claim 2, wherein the two return torsion springs are arranged symmetrically on two sides of the oscillating reference line.

9. The toothbrush of claim 1, wherein the first connector has a first limiting portion and a second limiting portion, the first limiting portion abuts against the second connector when the second connector rotates counterclockwise relative to the first connector to a first preset limit angle, and the second limiting portion abuts against the second connector when the second connector rotates clockwise relative to the first connector to a second preset limit angle.

10. The toothbrush of claim 1, wherein the brushing structure comprises a plurality of tooth bristles connected to one side of the brush head linkage and extending in a direction parallel to the oscillating reference line.
