

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403272
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Alshaiba Saleh Ghannam Almazrouei; Mohammed et al.

Ultrasonic mist inhaler

Abstract

An ultrasonic mist inhaler, including a liquid reservoir structure including a liquid chamber adapted to receive liquid to be atomized, the liquid chamber including a top surface representing a maximum level of the liquid chamber and a bottom surface representing a minimum level of the liquid chamber, a sonication chamber in fluid communication with the liquid chamber, the sonication chamber includes a piezoelectric transducer and a capillary material extending between the sonication chamber and the liquid chamber, wherein the piezoelectric transducer and the liquid chamber are arranged according to one of the following configurations: the piezoelectric transducer is disposed close to or at the bottom surface of the liquid chamber, the piezoelectric transducer is disposed close to or at the top surface of the liquid chamber as depicted in FIG. 3.

Inventors: Alshaiba Saleh Ghannam Almazrouei; Mohammed (Abu Dhabi, AE), Lahoud; Imad (Abu Dhabi, AE)

Applicant: SHAHEEN INNOVATIONS HOLDING LIMITED (Abu Dhabi, AE)

Family ID: 76478218

Assignee: Shaheen Innovations Holding Limited (Abu Dhabi, AE)

Appl. No.: 18/537694

Filed: December 12, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240100269 A1	Mar. 28, 2024

Related U.S. Application Data

continuation parent-doc US 16959958 US 11911559 WO PCT/IB2019/060808 20191215 child-doc US 18537694

Publication Classification

Int. Cl.: **A61M15/00** (20060101); **A24F40/05** (20200101); **A24F40/42** (20200101); **A61M11/00** (20060101); **A61M15/06** (20060101); A24F40/10 (20200101); A24F40/40 (20200101)

U.S. Cl.:

CPC **A61M15/0085** (20130101); **A24F40/05** (20200101); **A24F40/42** (20200101); **A61M11/005** (20130101); **A61M15/06** (20130101); A24F40/10 (20200101); A24F40/40 (20200101); A61M15/0021 (20140204); A61M2205/3331 (20130101); A61M2205/50 (20130101); A61M2205/8206 (20130101)

Field of Classification Search

CPC: A61M (15/0085); A61M (15/06); A61M (15/0021); A61M (2205/3331); A61M (2205/50); A61M (2205/8206); A61M (2016/0018); A61M (11/005); A24F (40/05); A24F (40/10); A24F (40/40); A24F (40/42); A24B (15/167); B06B (1/20)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4119096	12/1977	Drews	261/DIG.65	A61M 15/0085
4334531	12/1981	Reichl	239/338	B05B 17/0684
5355873	12/1993	Del Bon	N/A	N/A
5518179	12/1995	Humberstone et al.	N/A	N/A
5551416	12/1995	Stimpson	N/A	N/A
5894841	12/1998	Voges	N/A	N/A
5950619	12/1998	van der Linden	N/A	N/A
6011345	12/1999	Murray	N/A	N/A
6040560	12/1999	Fleischhauer	N/A	N/A
6402046	12/2001	Loeser	N/A	N/A
6601581	12/2002	Babaev	N/A	N/A
6679436	12/2003	Onishi	N/A	N/A
7129619	12/2005	Yang	N/A	N/A
8991722	12/2014	Friend	N/A	N/A
9242263	12/2015	Copeman	N/A	B06B 1/0246
9278365	12/2015	Banco	N/A	N/A
9415412	12/2015	Kawashima	N/A	N/A
9687029	12/2016	Liu	N/A	N/A
9687627	12/2016	Gallem	N/A	N/A
9718078	12/2016	Chau	N/A	N/A
9867398	12/2017	Guo	N/A	N/A
9980140	12/2017	Spencer	N/A	N/A
10034495	12/2017	Alarcon	N/A	N/A

10071391	12/2017	Yu	N/A	N/A
10195368	12/2018	Wang	N/A	N/A
10300225	12/2018	Terry	N/A	N/A
10327479	12/2018	Popplewell	N/A	N/A
10328218	12/2018	Reed	N/A	N/A
10412996	12/2018	Bright	N/A	N/A
10506827	12/2018	Liu	N/A	N/A
10561803	12/2019	Liu	N/A	N/A
10617150	12/2019	Cameron	N/A	N/A
10757971	12/2019	Liu	N/A	N/A
11039641	12/2020	Liu	N/A	N/A
11207711	12/2020	Hejazi	N/A	N/A
11219245	12/2021	Liu	N/A	N/A
11278055	12/2021	Liu	N/A	N/A
11304451	12/2021	Hejazi	N/A	N/A
11324253	12/2021	Liu	N/A	N/A
11431242	12/2021	Liu	N/A	N/A
11517685	12/2021	Danek	N/A	N/A
11589609	12/2022	Liu	N/A	N/A
11641876	12/2022	Liu	N/A	N/A
11690963	12/2022	Danek	N/A	N/A
11700881	12/2022	Liu	N/A	N/A
11744282	12/2022	Liu	N/A	N/A
11744284	12/2022	Liu	N/A	N/A
11771133	12/2022	Lin	N/A	N/A
11771137	12/2022	Liu	N/A	N/A
11796732	12/2022	Novak, III	N/A	N/A
11877600	12/2023	Liu	N/A	N/A
11911559	12/2023	Lahoud	N/A	A61M 15/06
11964301	12/2023	Hejazi	N/A	N/A
2002/0129813	12/2001	Litherland	N/A	N/A
2003/0164545	12/2002	Nadd	N/A	N/A
2003/0192532	12/2002	Hopkins	N/A	N/A
2003/0209005	12/2002	Fenn	N/A	N/A
2006/0243277	12/2005	Denyer	N/A	N/A
2006/0243820	12/2005	Ng	N/A	N/A
2007/0125370	12/2006	Denyer	N/A	N/A
2008/0054091	12/2007	Babaev	N/A	N/A
2008/0088202	12/2007	Duru	N/A	N/A
2008/0156320	12/2007	Low	N/A	N/A
2008/0164339	12/2007	Duru	N/A	N/A
2009/0022669	12/2008	Waters	N/A	N/A
2009/0065600	12/2008	Tranchant	N/A	N/A
2010/0084488	12/2009	Mahoney, III	N/A	N/A
2010/0139652	12/2009	Lipp	N/A	N/A
2011/0012677	12/2010	Lutsen	N/A	N/A
2012/0126041	12/2011	Mahito et al.	N/A	N/A
2013/0220315	12/2012	Conley	N/A	N/A
2014/0007864	12/2013	Gordon	N/A	N/A

2014/0151457	12/2013	Wilkerson	N/A	N/A
2014/0261414	12/2013	Weitzel	N/A	N/A
2014/0270727	12/2013	Ampolini	N/A	N/A
2015/0069146	12/2014	Lowy	N/A	N/A
2015/0202387	12/2014	Yu	N/A	N/A
2015/0230522	12/2014	Horn	N/A	N/A
2015/0231347	12/2014	Gumaste	N/A	N/A
2015/0272214	12/2014	Giller	N/A	N/A
2016/0001316	12/2015	Friend	N/A	N/A
2016/0066619	12/2015	Di Carlo	N/A	N/A
2016/0089508	12/2015	Smith	N/A	N/A
2016/0198770	12/2015	Alarcon	N/A	N/A
2016/0199594	12/2015	Finger	N/A	N/A
2016/0206001	12/2015	Eng	N/A	N/A
2016/0213866	12/2015	Tan	N/A	A61M 15/0021
2016/0264290	12/2015	Hafer	N/A	N/A
2016/0324212	12/2015	Cameron	N/A	N/A
2016/0331022	12/2015	Cameron	N/A	N/A
2016/0338407	12/2015	Kerdemelidis	N/A	N/A
2017/0042242	12/2016	Hon	N/A	N/A
2017/0119052	12/2016	Williams	N/A	N/A
2017/0119059	12/2016	Zuber	N/A	N/A
2017/0135411	12/2016	Cameron	N/A	N/A
2017/0136194	12/2016	Cameron	N/A	N/A
2017/0136484	12/2016	Wilkerson	N/A	N/A
2017/0251718	12/2016	Armoush	N/A	N/A
2017/0265521	12/2016	Do	N/A	N/A
2017/0281883	12/2016	Li	N/A	N/A
2017/0303594	12/2016	Cameron	N/A	N/A
2017/0368273	12/2016	Rubin	N/A	N/A
2018/0042306	12/2017	Atkins	N/A	N/A
2018/0153217	12/2017	Liu	N/A	N/A
2018/0160737	12/2017	Verleur	N/A	A61M 15/06
2018/0166981	12/2017	Leppard	N/A	N/A
2018/0192702	12/2017	Li	N/A	N/A
2018/0269867	12/2017	Terashima	N/A	N/A
2018/0286207	12/2017	Baker	N/A	N/A
2018/0296777	12/2017	Terry	N/A	N/A
2018/0296778	12/2017	Hacker	N/A	N/A
2018/0310625	12/2017	Alarcon	N/A	N/A
2018/0338532	12/2017	Verleur	N/A	N/A
2018/0343926	12/2017	Wensley	N/A	N/A
2019/0056131	12/2018	Warren	N/A	N/A
2019/0098935	12/2018	Phan	N/A	N/A
2019/0116863	12/2018	Dull	N/A	N/A
2019/0133186	12/2018	Fraser	N/A	N/A
2019/0158938	12/2018	Bowen	N/A	N/A
2019/0166913	12/2018	Trzecieski	N/A	N/A

2019/0167923	12/2018	Kessler	N/A	N/A
2019/0216135	12/2018	Guo	N/A	A24F 40/44
2019/0255554	12/2018	Selby	N/A	N/A
2019/0289914	12/2018	Liu	N/A	N/A
2019/0289915	12/2018	Heidl	N/A	N/A
2019/0289918	12/2018	Hon	N/A	N/A
2019/0321570	12/2018	Rubin	N/A	N/A
2019/0329281	12/2018	Lin	N/A	B05B 17/0623
2019/0335580	12/2018	Lin	N/A	H01R 12/714
2019/0336710	12/2018	Yamada	N/A	A61M 15/06
2019/0373679	12/2018	Fu	N/A	N/A
2019/0374730	12/2018	Chen	N/A	N/A
2019/0387795	12/2018	Fisher	N/A	N/A
2020/0000143	12/2019	Anderson	N/A	N/A
2020/0000146	12/2019	Anderson	N/A	N/A
2020/0009600	12/2019	Tan	N/A	N/A
2020/0016344	12/2019	Scheck	N/A	N/A
2020/0022416	12/2019	Alarcon	N/A	N/A
2020/0046030	12/2019	Krietzman	N/A	N/A
2020/0068949	12/2019	Rasmussen	N/A	N/A
2020/0085100	12/2019	Hoffman	N/A	N/A
2020/0120989	12/2019	Danek	N/A	A24B 15/167
2020/0120991	12/2019	Hatton	N/A	N/A
2020/0146361	12/2019	Silver	N/A	N/A
2020/0178598	12/2019	Mitchell	N/A	N/A
2020/0178606	12/2019	Liu	N/A	N/A
2020/0214349	12/2019	Liu	N/A	N/A
2020/0221771	12/2019	Atkins	N/A	N/A
2020/0221776	12/2019	Liu	N/A	H01R 33/205
2020/0245692	12/2019	Cameron	N/A	B05B 17/0684
2020/0345058	12/2019	Bowen	N/A	A61K 31/465
2020/0404975	12/2019	Chen	N/A	N/A
2021/0015957	12/2020	Bush	N/A	N/A
2021/0076733	12/2020	Liu	N/A	B05B 17/0684
2021/0112858	12/2020	Liu	N/A	A24F 40/485
2021/0120880	12/2020	Liu	N/A	N/A
2021/0153548	12/2020	Twite	N/A	N/A
2021/0153549	12/2020	Twite	N/A	N/A
2021/0153564	12/2020	Hourmand	N/A	N/A
2021/0153565	12/2020	Twite	N/A	N/A
2021/0153566	12/2020	Hourmand	N/A	N/A

2021/0153567	12/2020	Twite	N/A	N/A
2021/0153568	12/2020	Twite	N/A	N/A
2021/0153569	12/2020	Twite	N/A	N/A
2021/0177056	12/2020	Yilmaz	N/A	N/A
2021/0212362	12/2020	Liu	N/A	A24F 40/42
2021/0378303	12/2020	Liu	N/A	B05B 17/0646
2021/0401061	12/2020	Davis	N/A	N/A
2022/0030942	12/2021	Lord	N/A	N/A
2022/0151301	12/2021	Liu	N/A	N/A
2022/0240589	12/2021	Liu	N/A	N/A
2022/0273037	12/2021	Liu	N/A	N/A
2022/0279857	12/2021	Liu	N/A	N/A
2022/0295876	12/2021	Liu	N/A	N/A
2022/0395023	12/2021	Liu	N/A	N/A
2022/0400747	12/2021	Liu	N/A	N/A
2023/0001107	12/2022	Connolly	N/A	N/A
2023/0013741	12/2022	Liu	N/A	N/A
2023/0020762	12/2022	Liu	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2648836	12/2003	CN	N/A
101648041	12/2009	CN	N/A
104055225	12/2013	CN	N/A
104082853	12/2013	CN	N/A
204070580	12/2014	CN	N/A
104640708	12/2014	CN	N/A
204499481	12/2014	CN	N/A
105747277	12/2015	CN	N/A
105768238	12/2015	CN	N/A
105795526	12/2015	CN	N/A
105876873	12/2015	CN	N/A
205432145	12/2015	CN	N/A
106108118	12/2015	CN	N/A
205831074	12/2015	CN	N/A
106422005	12/2016	CN	N/A
205947130	12/2016	CN	N/A
206025223	12/2016	CN	N/A
206043451	12/2016	CN	N/A
206079025	12/2016	CN	N/A
206119183	12/2016	CN	N/A
206119184	12/2016	CN	N/A
106617319	12/2016	CN	N/A
206303211	12/2016	CN	N/A
206333372	12/2016	CN	N/A
107048479	12/2016	CN	N/A
206586397	12/2016	CN	N/A
206949536	12/2017	CN	N/A

107822195	12/2017	CN	N/A
207185926	12/2017	CN	N/A
105476071	12/2017	CN	N/A
207383536	12/2017	CN	N/A
207400330	12/2017	CN	N/A
108283331	12/2017	CN	N/A
108355210	12/2017	CN	N/A
105876873	12/2017	CN	N/A
109619655	12/2018	CN	N/A
208354603	12/2018	CN	N/A
208434721	12/2018	CN	N/A
106108118	12/2018	CN	N/A
208837110	12/2018	CN	N/A
209060228	12/2018	CN	N/A
110150760	12/2018	CN	N/A
209255084	12/2018	CN	N/A
105876870	12/2018	CN	N/A
209900345	12/2019	CN	N/A
210076566	12/2019	CN	N/A
210225387	12/2019	CN	N/A
110946315	12/2019	CN	N/A
211675730	12/2019	CN	N/A
217643921	12/2021	CN	N/A
2656370	12/1977	DE	N/A
2656370	12/1977	DE	N/A
2656370	12/1978	DE	N/A
100 51 792	12/2001	DE	N/A
10122065	12/2001	DE	N/A
0 258 637	12/1987	EP	N/A
0 295 122	12/1987	EP	N/A
0 258 637	12/1989	EP	N/A
0 442 510	12/1990	EP	N/A
0 442 510	12/1994	EP	N/A
0 516 565	12/1995	EP	N/A
0 824 927	12/1997	EP	N/A
0 833 695	12/1997	EP	N/A
0 845 220	12/1997	EP	N/A
0 893 071	12/1998	EP	N/A
0 970 627	12/1999	EP	N/A
1 083 952	12/2004	EP	N/A
1 618 803	12/2007	EP	N/A
3 088 007	12/2015	EP	N/A
3 192 381	12/2016	EP	N/A
3 278 678	12/2017	EP	N/A
3 298 912	12/2017	EP	N/A
3 088 007	12/2017	EP	N/A
3 434 118	12/2018	EP	N/A
3 469 927	12/2018	EP	N/A
3 505 098	12/2018	EP	N/A
3 520 634	12/2018	EP	N/A

3 278 678	12/2018	EP	N/A
3 545 778	12/2018	EP	N/A
3 574 902	12/2018	EP	N/A
3 516 971	12/2020	EP	N/A
3 528 651	12/2020	EP	N/A
3 837 999	12/2020	EP	N/A
3 574 778	12/2020	EP	N/A
3 593 656	12/2020	EP	N/A
4033927	12/2022	EP	N/A
3043576	12/2016	FR	N/A
3064502	12/2017	FR	N/A
1 528 391	12/1977	GB	N/A
2566766	12/2018	GB	N/A
2570439	12/2018	GB	N/A
05093575	12/1992	JP	N/A
2579614	12/1997	JP	N/A
2001069963	12/2000	JP	N/A
2005288400	12/2004	JP	N/A
2008-104966	12/2007	JP	N/A
2011-500160	12/2010	JP	N/A
2012-507208	12/2011	JP	N/A
2014-004042	12/2013	JP	N/A
2019515684	12/2018	JP	N/A
2019521671	12/2018	JP	N/A
2019-524113	12/2018	JP	N/A
2019-526240	12/2018	JP	N/A
2019-526241	12/2018	JP	N/A
2020535846	12/2019	JP	N/A
20120107219	12/2011	KR	N/A
210-2013-0052119	12/2012	KR	N/A
10-2013-0095024	12/2012	KR	N/A
WO 92/21332	12/1991	WO	N/A
WO 93/09881	12/1992	WO	N/A
WO 2000/050111	12/1999	WO	N/A
WO 2002/055131	12/2001	WO	N/A
WO 02094342	12/2001	WO	N/A
WO 2003/055486	12/2002	WO	N/A
WO 2003/0101454	12/2002	WO	N/A
WO 2004/080216	12/2003	WO	N/A
WO 2007/083088	12/2006	WO	N/A
WO 2008/076717	12/2007	WO	N/A
WO 2009/096346	12/2008	WO	N/A
WO 2012/062600	12/2011	WO	N/A
WO 2012/138835	12/2011	WO	N/A
WO 2013/028934	12/2012	WO	N/A
WO 2014/182736	12/2013	WO	N/A
WO 2015/128499	12/2014	WO	N/A
WO2015/084544	12/2014	WO	N/A
WO 2015/115006	12/2014	WO	N/A
WO 2016/010864	12/2015	WO	N/A

WO 2016/0116386	12/2015	WO	N/A
WO 2016/118941	12/2015	WO	N/A
WO 2016/175720	12/2015	WO	N/A
WO 2016/196915	12/2015	WO	N/A
WO 2017/076590	12/2016	WO	N/A
WO 2017/108268	12/2016	WO	N/A
WO 2017/143515	12/2016	WO	N/A
WO 2017/177159	12/2016	WO	N/A
WO 2017/197704	12/2016	WO	N/A
WO 2017/205692	12/2016	WO	N/A
WO 2017/206022	12/2016	WO	N/A
WO 2017/206212	12/2016	WO	N/A
WO 2017/215221	12/2016	WO	N/A
WO 2018/000761	12/2017	WO	N/A
WO 2018/000829	12/2017	WO	N/A
WO 2018/023920	12/2017	WO	N/A
WO2018/027189	12/2017	WO	N/A
WO 2018/032672	12/2017	WO	N/A
WO 2018/040380	12/2017	WO	N/A
WO 2018/041106	12/2017	WO	N/A
WO 2018/058884	12/2017	WO	N/A
WO 2018/111843	12/2017	WO	N/A
WO 2018/113669	12/2017	WO	N/A
WO 2018/115781	12/2017	WO	N/A
WO 2018/163366	12/2017	WO	N/A
WO 2018/167066	12/2017	WO	N/A
WO 2018/188616	12/2017	WO	N/A
WO 2018/188638	12/2017	WO	N/A
WO 2018/211252	12/2017	WO	N/A
WO 2018/220586	12/2017	WO	N/A
WO2018/220599	12/2017	WO	N/A
WO 2019/016681	12/2018	WO	N/A
WO 2019/048749	12/2018	WO	N/A
WO 2019/052506	12/2018	WO	N/A
WO 2019/052574	12/2018	WO	N/A
WO 2019/069160	12/2018	WO	N/A
WO 2019/138076	12/2018	WO	N/A
WO 2019/173923	12/2018	WO	N/A
WO 2019/198688	12/2018	WO	N/A
WO 2019/211324	12/2018	WO	N/A
WO 2019/238064	12/2018	WO	N/A
WO 2019/242746	12/2018	WO	N/A
WO 2020/019030	12/2019	WO	N/A
WO 2020/048437	12/2019	WO	N/A
WO 2020/057636	12/2019	WO	N/A
WO2020187138	12/2019	WO	N/A
WO 2020/225534	12/2019	WO	N/A
WO 2020/227717	12/2019	WO	N/A
WO 2020/254862	12/2019	WO	N/A
WO 2021/036827	12/2020	WO	N/A

OTHER PUBLICATIONS

UKIPO Search Report dated Nov. 24, 2021 for Application No. GB2111261.0. cited by applicant
UKIPO Search Report dated Nov. 24, 2021 for Application No. GB2113623.9. cited by applicant
EPO Search Report dated Nov. 12, 2021 for corresponding European Application No. 19870060.1. cited by applicant
EPO Search Report dated Oct. 27, 2021 for corresponding European Application No. 19870058.5. cited by applicant
EPO Search Report and Search Opinion for International Appl. No. EP 19870057.7 (PCT/IB2019/060812) dated Jun. 22, 2021. cited by applicant
Extended EPO Report and Search Opinion for corresponding EP Application No. 20214228.7 dated May 26, 2021. cited by applicant
Written Opinion mailed Nov. 10, 2020 for corresponding International Application No. PCT/IB2019/060812. cited by applicant
International Search Report mailed Nov. 10, 2020 for corresponding International Application No. PCT/IB2019/060812. cited by applicant
EPO Search Report mailed Nov. 9, 2020 for corresponding EPO Application No. 19870059.3 (PCT/IB2019/060808). cited by applicant
Written Opinion mailed Nov. 4, 2020 for corresponding International Application No. PCT/IB2019/060806. cited by applicant
International Search Report mailed Nov. 4, 2020 for corresponding International Application No. PCT/IB2019/060806. cited by applicant
Written Opinion mailed Nov. 4, 2020 for corresponding International Application No. PCT/IB2019/060807. cited by applicant
International Search Report mailed Nov. 4, 2020 for corresponding International Application No. PCT/IB2019/060807. cited by applicant
Written Opinion mailed Oct. 20, 2020 for corresponding International Application No. PCT/IB2019/060811. cited by applicant
International Search Report mailed Oct. 20, 2020 for corresponding International Application No. PCT/IB2019/060811. cited by applicant
Written Opinion mailed Oct. 19, 2020 for corresponding International Application No. PCT/IB2019/060810. cited by applicant
International Search Report mailed Oct. 19, 2020 for corresponding International Application No. PCT/IB2019/060810. cited by applicant
Extended EPO Search Report mailed Sep. 15, 2020 for corresponding EPO Application No. 20168938.7. cited by applicant
Written Opinion mailed Jun. 25, 2020 for corresponding International Application No. PCT/IB2019/060808. cited by applicant
International Search Report mailed Jun. 25, 2020 for corresponding International Application No. PCT/IB2019/060808. cited by applicant
Written Opinion mailed Apr. 29, 2020 for corresponding International Application No. PCT/IB2019/055192. cited by applicant
International Search Report mailed Apr. 29, 2020 for corresponding International Application No. PCT/IB2019/055192. cited by applicant
European Search Report mailed Nov. 15, 2022 for co-pending European application No. 22181106.0. cited by applicant
European Search Report mailed Dec. 1, 2022 for co-pending European application No. 19933337.8. cited by applicant
Japanese Exam Report mailed Nov. 1, 2022 for co-pending Japanese application No. 2022-545772. cited by applicant

Office Action, co-pending KR Application No. 10-2022-7024269 dated Dec. 20, 2023; 10 pages. (with English translation). cited by applicant
Akira Kubo, Part 1: What is Personal Authentication?—The Last Resort for Internet Security-Series: Re-Introduction to PKI, Japan, @IT, Apr. 5, 2003;
https://atmarkit.itmedia.co.jp/fsecurity/rensai/re_pki01/re_pki01.html (newly cited reference showing well-known technique) (No English version). cited by applicant

Primary Examiner: Vo; Tu A

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of application Ser. No. 16/959,958, filed Jul. 2, 2020; which is a National Phase Application under 35 U.S.C. § 371 of International Application No. PCT/IB2019/060808, filed Dec. 15, 2019, the entire contents of which are incorporated herein by reference.

FIELD OF THE DISCLOSED TECHNOLOGY

(1) The invention relates to an ultrasonic mist inhaler for atomizing a liquid by ultrasonic vibrations.

BACKGROUND

(2) Electronic vaporizing inhalers are becoming popular among smokers who also want to avoid the tar and other harsh chemicals associated with traditional cigarettes and who wish to satisfy the craving for nicotine. Electronic vaporizing inhalers may contain liquid nicotine, which is typically a mixture of nicotine oil, a solvent, water, and sometimes flavoring. When the user draws, or inhales, on the electronic vaporizing inhaler, the liquid nicotine is drawn into a vaporizer where it is heated into a vapor. As the user draws on the electronic vaporizing inhaler, the vapor containing the nicotine is inhaled. Such electronic vaporizing inhalers may have medical purpose.

(3) Electronic vaporizing inhalers and other vapor inhalers typically have similar designs. Most electronic vaporizing inhalers feature a liquid nicotine reservoir with an interior membrane, such as a capillary element, typically cotton, that holds the liquid nicotine so as to prevent leaking from the reservoir. Nevertheless, these cigarettes are still prone to leaking because there is no obstacle to prevent the liquid from flowing out of the membrane and into the mouthpiece. A leaking electronic vaporizing inhaler is problematic for several reasons. As a first disadvantage, the liquid can leak into the electronic components, which can cause serious damage to the device. As a second disadvantage, the liquid can leak into the electronic vaporizing inhaler mouthpiece, and the user may inhale the unvaporized liquid.

(4) Electronic vaporizing inhalers are also known for providing inconsistent doses between draws. The aforementioned leaking is one cause of inconsistent doses because the membrane may be oversaturated or undersaturated near the vaporizer. If the membrane is oversaturated, then the user may experience a stronger than desired dose of vapor, and if the membrane is undersaturated, then the user may experience a weaker than desired dose of vapor. Additionally, small changes in the strength of the user's draw may provide stronger or weaker doses. Inconsistent dosing, along with leaking, can lead to faster consumption of the vaping liquid.

(5) Additionally, conventional electronic vaporizing inhalers tend to rely on inducing high temperatures of a metal heating component configured to heat a liquid in the e-cigarette, thus vaporizing the liquid that can be breathed in. Problems with conventional electronic vaporizing inhalers may include the possibility of burning metal and subsequent breathing in of the metal along with the burnt liquid. In addition, some may not prefer the burnt smell caused by the heated

liquid.

(6) Electronic vaporizing inhalers are generally designed so that the liquid nicotine reservoir is arranged away from the metal heating component to prevent heating the unused liquid in the reservoir. This arrangement makes the inhaler device cumbersome and more complex to produce.

(7) In the electronic vaporizing inhalers, the vapor chamber is generally distant from the liquid reservoir and the mouthpiece to prevent heating the liquid or the vapor before the user drawn.

(8) Thus, a need exists in the art for an electronic vaporizing inhaler that is better able to withstand these disadvantages.

BRIEF SUMMARY

(9) According to one aspect of the invention, an ultrasonic mist inhaler, comprises: a liquid reservoir structure comprising a liquid chamber adapted to receive liquid to be atomized, the liquid chamber comprising a top surface representing the maximum level of the liquid chamber and the bottom surface representing the minimum level of the liquid chamber, a sonication chamber in fluid communication with the liquid chamber, the sonication chamber comprising means of ultrasonic vibrations and a capillary element extending between the sonication chamber and the liquid chamber, wherein the means of ultrasonic vibrations and the liquid chamber are arranged according to one of the following configurations: the means of ultrasonic vibrations are disposed close to or at the bottom surface of the liquid chamber, the means of ultrasonic vibrations are disposed close to or at the top surface of the liquid chamber.

(10) The arrangement of the means of ultrasonic vibrations disposed close to or at the bottom surface of the liquid chamber renders the fluid passage to the means of ultrasonic vibrations by gravity faster.

(11) The arrangement of the means of ultrasonic vibrations disposed close to or at the top surface of the liquid chamber renders the mist passage to a mouthpiece shorter.

(12) The expression “means of ultrasonic vibrations” is similar to the expression “ultrasonic oscillation component” used in the patent application PCT/IB2019/055192.

(13) In the ultrasonic mist inhaler, in the arrangement close to or at the top surface, the means of ultrasonic vibrations may have at least an atomization surface parallel to the top surface.

(14) In the ultrasonic mist inhaler, in the arrangement close to or at the top surface, the means of ultrasonic vibrations may have at least an atomization surface perpendicular to the top surface.

(15) The atomization surface perpendicular to the top surface permits smaller thickness of the inhaler.

(16) In the configuration of the atomization surface perpendicular to the top surface, the inhaler may comprise one of the following features taken alone or in combination: the liquid reservoir structure may comprise an inner container and an outer container wherein the inner container is surrounded by the outer container, the inner container forms the liquid reservoir, the capillary element is wrapped around the means of ultrasonic vibrations, the means of ultrasonic vibrations is supported by an elastic member, the elastic member is formed from an annular plate-shaped rubber, the elastic member has an inner hole wherein a groove is designed for maintaining the means of ultrasonic vibrations, the inner container has an opening into which the elastic member is introduced at least partly, the elastic member having a radial groove wherein the capillary element passes and penetrates the liquid chamber, the elastic member is inserted into the opening of the inner container by tight adjustment.

(17) It is noted that the expression “mist” used in the invention means the liquid is not heated as usually in traditional inhalers known from the prior art. In fact, traditional inhalers use heating elements to heat the liquid above its boiling temperature to produce a vapor, which is different from a mist.

(18) In fact, when sonicating liquids at high intensities, the sound waves that propagate into the liquid media result in alternating high-pressure (compression) and low-pressure (rarefaction) cycles, at different rates depending on the frequency. During the low-pressure cycle, high-intensity

ultrasonic waves create small vacuum bubbles or voids in the liquid. When the bubbles attain a volume at which they can no longer absorb energy, they collapse violently during a high-pressure cycle. This phenomenon is termed cavitation. During the implosion very high pressures are reached locally. At cavitation, broken capillary waves are generated, and tiny droplets break the surface tension of the liquid and are quickly released into the air, taking mist form.

(19) The ultrasonic mist inhaler according to the invention, wherein said liquid to be received in the liquid chamber comprises 57-70% (w/w) vegetable glycerin and 30-43% (w/w) propylene glycol, said propylene glycol including nicotine and flavorings.

(20) An ultrasonic mist inhaler or a personal ultrasonic atomizer device, comprising: a liquid reservoir structure comprising a liquid chamber or cartridge adapted to receive liquid to be atomized, a sonication chamber in fluid communication with the liquid chamber or cartridge, wherein said liquid to be received in the liquid chamber comprises 57-70% (w/w) vegetable glycerin and 30-43% (w/w) propylene glycol, said propylene glycol including nicotine and flavorings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Some embodiments are illustrated by way of example and not limitation in the figures of the accompanying drawings.

(2) FIG. 1 is an exploded view of components of the ultrasonic mist inhaler according to a first arrangement of means of ultrasonic vibrations disposed close to or at a bottom surface of a liquid chamber.

(3) FIG. 2 is an exploded view of components of the inhaler liquid reservoir structure according to the first arrangement.

(4) FIG. 3 is a cross section view of components of the inhaler liquid reservoir structure according to FIG. 1 or 2 wherein means of ultrasonic vibrations are arranged according to a first embodiment.

(5) FIG. 4A is an isometric view of an airflow member of the inhaler liquid reservoir structure according to FIGS. 2 and 3.

(6) FIG. 4B is a cross section view of the airflow member shown in FIG. 4A.

(7) FIG. 5 is a cross section view of a second arrangement of means of ultrasonic vibrations disposed close to or at a top surface of the liquid chamber.

(8) FIG. 6 is a cross section view of a second arrangement of means of ultrasonic vibrations disposed close to or at the top surface of the liquid chamber.

DETAILED DESCRIPTION

(9) The foregoing summary, as well as the following detailed description of certain embodiments of the present invention, will be better understood when read in conjunction with the appended drawings.

(10) As used herein, an element recited in the singular and preceded with the word “a” or “an” should be understood as not excluding plural of said elements, unless such exclusion is explicitly stated. Furthermore, the references to “one embodiment” of the present invention are not intended to be interpreted as excluding the existence of additional embodiments that also incorporate the recited features. Moreover, unless explicitly stated to the contrary, embodiments “comprising” or “having” an element or a plurality of elements having a particular property may include additional such elements not having that property.

(11) The present invention is directed to an ultrasonic mist inhaler. The description of the invention and accompanying figures will be directed to the electronic vaporizing inhaler embodiment; however, other embodiments are envisioned, such as an inhaler for hookah, flavored liquids, medicine, and herbal supplements. Additionally, the device can be packaged to look like an object

other than a cigarette. For instance, the device could resemble another smoking instrument, such as a pipe, water pipe, or slide, or the device could resemble another non-smoking related object.

(12) Ultrasonic mist inhalers are either disposable or reusable. The term “reusable” as used herein implies that the energy storage device is rechargeable or replaceable or that the liquid is able to be replenished either through refilling or through replacement of the liquid reservoir structure. Alternatively, in some embodiments reusable electronic device is both rechargeable and the liquid can be replenished. A disposable embodiment will be described first, followed by a description of a reusable embodiment.

(13) Conventional electronic vaporizing inhaler tend to rely on inducing high temperatures of a metal component configured to heat a liquid in the inhaler, thus vaporizing the liquid that can be breathed in. The liquid typically contains nicotine and flavorings blended into a solution of propylene glycol (PG) and vegetable glycerin (VG), which is vaporized via a heating component at high temperatures. Problems with conventional inhaler may include the possibility of burning metal and subsequent breathing in of the metal along with the burnt liquid. In addition, some may not prefer the burnt smell or taste caused by the heated liquid.

(14) In contrast, aspects of the present disclosure include an ultrasonic mist inhaler that atomizes the liquid through ultrasonic vibrations, which produces micro water bubbles in the liquid. When the bubbles come into contact with ambient air, water droplets of about 0.25 to 0.5 microns spray into the air, thereby generating micro-droplets that can be absorbed through breathing, similar to breathing in a mist.

(15) No heating elements are involved, thereby leading to no burnt elements and reducing second-hand smoke effects.

(16) FIG. 1 to FIG. 4 illustrate a first arrangement of means of ultrasonic vibrations disposed close to or at a bottom surface of a liquid chamber.

(17) FIG. 1 depicts a disposable ultrasonic mist inhaler embodiment **100** of the invention. As can be seen in FIG. 1, the ultrasonic mist inhaler **100** has a cylindrical body with a relatively long length as compared to the diameter. In terms of shape and appearance, the ultrasonic mist inhaler **100** is designed to mimic the look of a typical cigarette. For instance, the inhaler can feature a first portion **101** that primarily simulates the tobacco rod portion of a cigarette and a second portion **102** that primarily simulates a filter. In the disposable embodiment of the invented device, the first portion and second portion are regions of a single, but-separable device. The designation of a first portion **101** and a second portion **102** is used to conveniently differentiate the components that are primarily contained in each portion.

(18) As can be seen in FIG. 1, the ultrasonic mist inhaler comprises a mouthpiece **1**, a liquid reservoir structure **2** and a casing **3**. The first portion **101** comprises the casing **3** and the second portion **102** comprises the mouthpiece **1** and the reservoir structure **2**.

(19) The first portion **101** contains the power supply energy.

(20) An electrical storage device **30** powers the ultrasonic mist inhaler **100**. The electrical storage device **30** can be a battery, including but not limited to a lithium-ion, alkaline, zinc-carbon, nickel-metal hydride, or nickel-cadmium battery; a super capacitor; or a combination thereof. In the disposable embodiment, the electrical storage device **30** is not rechargeable, but, in the reusable embodiment, the electrical storage device **30** would be selected for its ability to recharge. In the disposable embodiment, the electrical storage device **30** is primarily selected to deliver a constant voltage over the life of the inhaler **100**. Otherwise, the performance of the inhaler would degrade over time. Preferred electrical storage devices that are able to provide a consistent voltage output over the life of the device include lithium-ion and lithium polymer batteries.

(21) The electrical storage device **30** has a first end **30a** that generally corresponds to a positive terminal and a second end **30b** that generally corresponds to a negative terminal. The negative terminal is extending to the first end **30a**.

(22) Because the electrical storage device **30** is located in the first portion **101** and the liquid

reservoir structure **2** is located in the second portion **102**, the joint needs to provide electrical communication between those components. In the present invention, electrical communication is established using at least an electrode or probe that is compressed together when the first portion **101** is tightened into the second portion **102**.

(23) In order for this embodiment to be reusable, the electrical storage device **30** is rechargeable. The casing **3** contains a charging port **32**.

(24) The integrated circuit **4** has a proximal end **4a** and a distal end **4b**. The positive terminal at the first end **30a** of the electrical storage device **30** is in electrical communication with a positive lead of the flexible integrated circuit **4**. The negative terminal at the second end **30b** of the electrical storage device **30** is in electrical communication with a negative lead of the integrated circuit **4**. The distal end **4b** of the integrated circuit **4** comprise a microprocessor. The microprocessor is configured to process data from a sensor, to control a light, to direct current flow to means of ultrasonic vibrations **5** in the second portion **102**, and to terminate current flow after a preprogrammed amount of time.

(25) The sensor detects when the ultrasonic mist inhaler **100** is in use (when the user draws on the inhaler) and activates the microprocessor. The sensor can be selected to detect changes in pressure, air flow, or vibration. In a preferred embodiment, the sensor is a pressure sensor. In the digital embodiment, the sensor takes continuous readings which in turn requires the digital sensor to continuously draw current, but the amount is small and overall battery life would be negligibly affected.

(26) Additionally, the integrated circuit **4** may comprise a H bridge, preferably formed by 4 MOSFETs to convert a direct current into an alternate current at high frequency.

(27) Referring to FIG. 2 and FIG. 3, illustrations of a liquid reservoir structure **2** according to an embodiment are shown. The liquid reservoir structure **2** comprises a liquid chamber **21** adapted to receive liquid to be atomized and a sonication chamber **22** in fluid communication with the liquid chamber **21**.

(28) In the embodiment shown, the liquid reservoir structure **2** comprises an inhalation channel **20** providing an air passage from the sonication chamber **22** toward the surroundings.

(29) As an example of sensor position, the sensor may be located in the sonication chamber **22**.

(30) The inhalation channel **20** has a frustoconical element **20a** and an inner container **20b**.

(31) As depicted in FIGS. 4A and 4B, further the inhalation channel **20** has an airflow member **27** for providing air flow from the surroundings to the sonication chamber **22**.

(32) The airflow member **27** has an airflow bridge **27a** and an airflow duct **27b** made in one piece, the airflow bridge **27a** having two airway openings **27a'** forming a portion of the inhalation channel **20** and the airflow duct **27b** extending in the sonication chamber **22** from the airflow bridge **27a** for providing the air flow from the surroundings to the sonication chamber.

(33) The airflow bridge **27a** cooperates with the frustoconical element **20a** at the second diameter **20a2**.

(34) The airflow bridge **27a** has two opposite peripheral openings **27a''** providing air flow to the airflow duct **27b**.

(35) The cooperation with the airflow bridge **27a** and the frustoconical element **20a** is arranged so that the two opposite peripheral openings **27a''** cooperate with complementary openings **20a''** in the frustoconical element **20a**.

(36) The mouthpiece **1** and the frustoconical element **20a** are radially spaced and an airflow chamber **28** is arranged between them.

(37) As depicted in FIGS. 1 and 2, the mouthpiece **1** has two opposite peripheral openings **1''**.

(38) The peripheral openings **27a''**, **20a''**, **1''** of the airflow bridge **27a**, the frustoconical element **20a** and the mouthpiece **1** directly supply maximum air flow to the sonication chamber **22**.

(39) The frustoconical element **20a** includes an internal passage, aligned in the similar direction as the inhalation channel **20**, having a first diameter **20a1** less than that of a second diameter **20a2**,

such that the internal passage reduces in diameter over the frustoconical element **20a**.

(40) The frustoconical element **20a** is positioned in alignment with the means of ultrasonic vibrations **5** and a capillary element **7**, wherein the first diameter **20a1** is linked to an inner duct **11** of the mouthpiece **1** and the second diameter **20a2** is linked to the inner container **20b**.

(41) The inner container **20b** has an inner wall delimiting the sonication chamber **22** and the liquid chamber **21**.

(42) The liquid reservoir structure **2** has an outer container **20c** delimiting the outer wall of the liquid chamber **21**.

(43) The inner container **20b** and the outer container **20c** are respectively the inner wall and the outer wall of the liquid chamber **21**.

(44) The liquid reservoir structure **2** is arranged between the mouthpiece **1** and the casing **3** and is detachable from the mouthpiece **1** and the casing **3**.

(45) The liquid reservoir structure **2** and the mouthpiece **1** or the casing **3** may include complimentary arrangements for engaging with one another; further such complimentary arrangements may include one of the following: a bayonet type arrangement; a threaded engaged type arrangement; a magnetic arrangement; or a friction fit arrangement; wherein the liquid reservoir structure **2** includes a portion of the arrangement and the mouthpiece **1** or the casing **3** includes the complimentary portion of the arrangement.

(46) In the reusable embodiment, the components are substantially the same. The differences in the reusable embodiment vis-a-vis the disposable embodiment are the accommodations made to replace the liquid reservoir structure **2**.

(47) As shown in FIG. 3, the liquid chamber **21** has a top wall **23** and a bottom wall **25** closing the inner container **20b** and the outer container **20c** of the liquid chamber **21**.

(48) The capillary element **7** is arranged between a first section **20b1** and a second section **20b2** of the inner container **20b**.

(49) The capillary element **7** has a flat shape extending from the sonication chamber to the liquid chamber.

(50) As depicted in FIG. 2 or 3, the capillary element **7** comprises a central portion **7a** in U-shape and a peripheral portion **7b** in L-shape.

(51) The L-shape portion **7b** extends into the liquid chamber **21** on the inner container **20b** and along the bottom wall **25**.

(52) The U-shape portion **7a** is contained into the sonication chamber **21**. The U-shape portion **7a** on the inner container **20b** and along the bottom wall **25**.

(53) In the ultrasonic mist inhaler, the U-shape portion **7a** has an inner portion **7a1** and an outer portion **7a2**, the inner portion **7a1** being in surface contact with an atomization surface **50** of the means of ultrasonic vibrations **5** and the outer portion **7a2** being not in surface contact with the means of ultrasonic vibrations **5**.

(54) The bottom wall **25** of the liquid chamber **21** is a bottom plate **25** closing the liquid chamber **21** and the sonication chamber **22**. The bottom plate **25** is sealed, thus preventing leakage of liquid from the sonication chamber **22** to the casing **3**.

(55) The bottom plate **25** has an upper surface **25a** having a recess **25b** on which is inserted an elastic member **8**. The means of ultrasonic vibrations **5** are supported by the elastic member **8**. The elastic member **8** is formed from an annular plate-shaped rubber having an inner hole **8'** wherein a groove is designed for maintaining the means of ultrasonic vibrations **5**.

(56) The top wall **23** of the liquid chamber **21** is a cap **23** closing the liquid chamber **21**.

(57) The top wall **23** has a top surface **23** representing the maximum level of the liquid that the liquid chamber **21** may contain and the bottom surface **25** representing the minimum level of the liquid in the liquid chamber **21**.

(58) The top wall **23** is sealed, thus preventing leakage of liquid from the liquid chamber **21** to the mouthpiece **1**.

(59) The top wall **23** and the bottom wall **25** are fixed to the liquid reservoir structure **2** by means of fixation such as screws, glue, or friction.

(60) As depicted in FIG. 3, the elastic member **8** is in line contact with the means of ultrasonic vibrations **5** and prevents contact between the means of ultrasonic vibrations **5** and the inhaler walls, suppression of vibrations of the liquid reservoir structure are more effectively prevented. Thus, fine particles of the liquid atomized by the atomizing member can be sprayed farther.

(61) As depicted in FIG. 3, the inner container **20b** has openings **20b'** between the first section **20b1** and the second section **20b2** from which the capillary element **7** is extending from the sonication chamber **21**. The capillary element **7** absorbs liquid from the liquid chamber **21** through the apertures **20b'**. The capillary element **7** is a wick. The capillary element **7** transports liquid to the sonication chamber **22** via capillary action. Preferably the capillary element **7** is made of bamboo fibers; however, cotton, paper, or other fiber strands could be used for a wick material.

(62) In one embodiment of the ultrasonic mist inhaler **100**, as can be seen in FIG. 3, the means of ultrasonic vibrations **5** are disposed directly below the capillary element **7**.

(63) The means of ultrasonic vibrations **5** may be a transducer. For example, the means of ultrasonic vibrations **5** may be a piezoelectric transducer, preferably designed in a circular plate-shape. The material of the piezoelectric transducer is preferably in ceramic.

(64) A variety of transducer materials can also be used for the means of ultrasonic vibrations **5**.

(65) The end of the airflow duct **27b1** faces the means of ultrasonic vibrations **5**. The means of ultrasonic vibrations **5** are in electrical communication with electrical contactors **101a**, **101b**. It is noted that, the distal end **4b** of the integrated circuit **4** has an inner electrode and an outer electrode. The inner electrode contacts the first electrical contact **101a** which is a spring contact probe, and the outer electrode contacts the second electrical contact **101b** which is a side pin. Via the integrated circuit **4**, the first electrical contact **101a** is in electrical communication with the positive terminal of the electrical storage device **30** by way of the microprocessor, while the second electrical contact **101b** is in electrical communication with the negative terminal of the electrical storage device **30**.

(66) The electrical contacts **101a**, **101b** crossed the bottom plate **25**. The bottom plate **25** is designed to be received inside the perimeter wall **26** of the liquid reservoir structure **2**. The bottom plate **25** rests on complementary ridges, thereby creating the liquid chamber **21** and sonication chamber **22**.

(67) The inner container **20b** comprises a circular inner slot **20d** on which a mechanical spring is applied.

(68) By pushing the central portion **7a1** onto the means of ultrasonic vibrations **5**, the mechanical spring **9** ensures a contact surface between them.

(69) The liquid reservoir structure **2** and the bottom plate **25** can be made using a variety of thermoplastic materials.

(70) When the user draws on the ultrasonic mist inhaler **100**, an air flow is drawn from the peripheral openings **1''** and penetrates the airflow chamber **28**, passes the peripheral openings **27a''** of the airflow bridge **27a** and the frustoconical element **20a** and flows down into the sonication chamber **22** via the airflow duct **27b** directly onto the capillary element **7**. At the same time, the liquid is drawn from the reservoir chamber **21** by capillarity, through the plurality of apertures **20b'**, and into the capillary element **7**. The capillary element **7** brings the liquid into contact with the means of ultrasonic vibrations **5** of the inhaler **100**. The user's draw also causes the pressure sensor to activate the integrated circuit **4**, which directs current to the means of ultrasonic vibrations **5**. Thus, when the user draws on the mouthpiece **1** of the inhaler **100**, two actions happen at the same time. Firstly, the sensor activates the integrated circuit **4**, which triggers the means of ultrasonic vibrations **5** to begin vibrating. Secondly, the draw reduces the pressure outside the reservoir chamber **21** such that flow of the liquid through the apertures **20b'** begins, which saturates the capillary element **7**. The capillary element **7** transports the liquid to the means of ultrasonic

vibrations **5**, which causes bubbles to form in a capillary channel by the means of ultrasonic vibrations **5** and mist the liquid. Then, the mist liquid is drawn by the user.

(71) The ultrasonic mist inhaler **100** of the present disclosures is a more powerful version of current portable medical nebulizers, in the shape and size of current e-cigarettes and with a particular structure for effective vaporization. It is a healthier alternative to cigarettes and current e-cigarettes products.

(72) The ultrasonic mist inhaler **100** of the present disclosures has particular applicability for those who use electronic inhalers as a means to quit smoking and reduce their nicotine dependency. The ultrasonic mist inhaler **100** provides a way to gradually taper the dose of nicotine.

(73) FIG. **5** illustrate a second arrangement of means of ultrasonic vibrations disposed close to or at a top surface of the liquid chamber.

(74) The mouthpiece **1** is extending down to the bottom end of the inner container **20b**. While the liquid chamber **21** is delimited by the outer container **20c** and an inner peripheral container **20e** joined by a bottom wall **25**. The liquid chamber is closed by a top wall **23**.

(75) The top wall **23** has the top surface **23** representing the maximum level of the liquid that the liquid chamber **21** may contain and the bottom surface **25** representing the minimum level of the liquid in the liquid chamber **21**. The top wall **23** is sealed, thus preventing leakage of liquid from the liquid chamber **21** to the mouthpiece **1**.

(76) As depicted in FIG. **5**, the means of ultrasonic vibrations **5** has a flat shape having an atomization surface **50** parallel to the top surface **23** and disposed close to or at the top surface **23**.

(77) The top wall **23** is fixed to the liquid reservoir structure **2** by means of fixation such as screws or glue.

(78) Contrary to the first arrangement, the capillary element **7** is not shown to make the illustrated features more clear.

(79) Of course, the capillary element **7** may have the same configuration that the first arrangement. In this second arrangement, the L-shape is extending down to the bottom surface **25**.

(80) FIG. **6** illustrate a second arrangement of means of ultrasonic vibrations disposed close to or at a top surface of the liquid chamber.

(81) In the second arrangement, the liquid reservoir structure **2** may comprise an inner container **200c** and an outer container **200b** wherein the inner container **200c** is surrounded by the outer container **200b**, the inner container **200c** forms the liquid chamber **21**.

(82) The capillary element **7** is wrapped around the circular shape of the means of ultrasonic vibrations **5**.

(83) Further, the means of ultrasonic vibrations **5** is supported by an elastic member **8** formed from an annular plate-shaped rubber.

(84) The elastic member **8** has an inner hole wherein a groove **80** is designed for maintaining the capillary element **7** and the means of ultrasonic vibrations **5**.

(85) The inner container **200c** has a flat opening into which the elastic member **8** is introduced at least partly, the elastic member **8** having a radial groove **80** wherein the capillary element **7** passes and penetrates the liquid chamber.

(86) The inner container **200c** is sealed with the elastic member **8**, for example, by glue or mastic disposed around the peripheral of the flat opening.

(87) In this third arrangement, the means of electrical contacts rise through electrical contact holes **200b1** and **200b2** on either side of inner container **200c** and connect with the rear of the means of ultrasonic vibrations **5**.

(88) Other embodiments of the invented ultrasonic mist inhaler **100** are easily envisioned, including medicinal delivery devices.

(89) It is to be understood that the above description is intended to be illustrative, and not restrictive. For example, the above-described embodiments may be used in combination with each

other. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the invention without departing from its scope.

Claims

1. An ultrasonic mist inhaler, comprising: a liquid reservoir structure comprising a first container forming a liquid chamber adapted to receive liquid to be atomized, the first container comprises a top wall, a bottom wall, and a side wall positioned between the top wall and the bottom wall, the top wall comprises an interior surface, an exterior surface and an upward facing curved surface is formed between the exterior surface and the interior surface of the top wall, the upward facing curved surface forms an aperture to provide access to the liquid chamber, the liquid chamber is formed by the interior surface of the top wall, wherein the interior surface of the top wall is a top surface of the liquid chamber representing a maximum level of the liquid chamber, wherein the bottom wall comprises an interior surface that is a bottom surface of the liquid chamber representing a minimum level of the liquid chamber, and wherein the top surface being in a plane, a sonication chamber in fluid communication with the liquid chamber, the sonication chamber comprising a piezoelectric transducer, wherein the piezoelectric transducer is disposed adjacent to the top surface of the liquid chamber, the piezoelectric transducer having an atomization surface in a plane perpendicular to the plane of the top surface of the liquid chamber, a capillary material extending between the sonication chamber and the liquid chamber, and an annular elastic support for supporting the piezoelectric transducer, the annular elastic support having a plate-shaped configuration and an annular wall surrounding at least a portion of the piezoelectric transducer, the annular elastic support having a passage extending radially through a portion of the annular wall, wherein the aperture in the top wall of the first container is sized and configured to receive at least a lower wall portion of the annular wall therein, such that a first part of the lower wall portion of the annular wall is configured to engage the upward facing curved surface of the top wall of the liquid reservoir and a second part of the lower wall portion of the annular wall is positioned within the liquid chamber, wherein a portion of the capillary material passes through the passage of the annular elastic support and penetrates the liquid chamber.
 2. The ultrasonic mist inhaler according to claim 1, wherein the first container is an inner container, and the liquid reservoir structure further comprises an outer container, and the inner container is surrounded by the outer container.
 3. The ultrasonic mist inhaler according to claim 1, wherein the capillary material is wrapped around the piezoelectric transducer.
 4. The ultrasonic mist inhaler according to claim 1, wherein the passage is formed by a groove that penetrates the lower wall portion of the annular wall of the annular elastic support.
 5. The ultrasonic mist inhaler according to claim 4, wherein the annular elastic support is inserted into the aperture by tight adjustment.
 6. The ultrasonic mist inhaler according to claim 1, wherein the annular elastic support having a radial groove, wherein the radial groove is configured to maintain the capillary material therein, the capillary material passing through the groove and penetrating the liquid chamber.
 7. The ultrasonic mist inhaler according to claim 1, wherein the liquid to be received in the liquid chamber comprises 57-70% (w/w) vegetable glycerin, 30-43% (w/w) propylene glycol, nicotine, and flavorings.
-